

Candy 1000kg/hr

BOOKLET FOR COMPLETE PRODUCT LINES

New



**Starmers**  
Engineering Works

## COMPLETE PRODUCT LINE FOR CANDY 1000 KG/HOUR

1. GLUCOSE TANK SEW-201 ✓
2. STEAM GENERATOR SEW-202 ✓
3. STEAM HEADLER SEW-103 ✓
4. CANDY CONTINUOUS ~~VACUUM BATCH~~ COOKER SEW-204 ✓
- ~~5. VACUUM COOKER~~ 5. Vacuum Pump SEW-205 ✓
6. DISSOLVING TANK SEW-206 ✓
7. STORAGE TANK SEW-208 ✓
8. COOLING TABLE SEW-~~207~~ <sup>208</sup> ✓
9. KNEADING MACHINE SEW-209 ✓
10. ~~Bubble Gum Mixer~~ <sup>SEW-210</sup> ✓
11. ~~CENTER FILLING PUMP LIQUID SEW-110~~ <sup>211</sup> Bubble Gum Extruder ✓
12. ~~CENTER FILLING PUMP POWDER SEW-112~~ <sup>213</sup> ✓
13. ~~BATCH ROLLER SEW-214~~ ✓
14. ROPE SIZER 5 STAGES SEW-215 ✓
15. UNIPLAST FORMING MACHINE SEW-216C ✓
16. ROTARY DIE WITH CUTTING RING SEW-217 ✓
17. DIE STAND SEW-218 ✓
18. COOLING ~~TUNNEL~~ <sup>TUNNEL</sup> 3 STAGES SEW-219 ✓
19. COOLING AC UNIT SEW-220 ✓
20. VIBRATOR SEW-~~221~~ <sup>221</sup> ✓
21. WRAPPING MACHINE SEW-~~222~~ <sup>222</sup> ✓

## 1.GLUPOSE TANK SEW-101

### Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, Stable and crystal free storage of liquid glucose and Syrups for industrial applications. ✓

### Specifications:

|                            |                                              |
|----------------------------|----------------------------------------------|
| Size:                      | 14 ft height x 7.0 ft diameter (approximate) |
| Grade:                     | S.S 304                                      |
| Sheet thickness:           | 5 mm upper and lower sheet                   |
| Outer dia sheet thickness: | 3 mm                                         |
| Design Type:               | Vertical                                     |
| Heating System:            | Coil on the base of tank                     |
| Ladder:                    | Outside the tank                             |
| Capacity:                  | 20 ton Glucose                               |

Dimension: 14 ft Height x 7.0 ft diameter

Weight:

Power load: ☺

## Trast:

- The Steam generator heats water to produce high pressure steam for heating, cleaning or industrial processes.

### 2. STEAM GENERATOR SEW-202

#### Detail of Mechanical Parts:

- |                                                              |    |   |
|--------------------------------------------------------------|----|---|
| 1. Gauge Glass <del>like a new</del> =                       | 01 | ✓ |
| 2. Stop Valve diameter <del>2"</del> =                       | 01 | ✓ |
| 3. Safety Valve diameter 1 1/2" =                            | 01 | ✓ |
| 4. NRV diameter 1" <del>like a new</del> =                   | 01 | ✓ |
| 5. Blow down diameter 1.5" =                                 | 01 | ✓ |
| 6. Air Vent diameter 1" globe Valve =                        | 01 | ✓ |
| 7. Feed Water Pump 01 Multistage (Grundfos) =                | 01 | ✓ |
| 8. Electric panel Box with complete auto controlled system = | 01 | ✓ |
| 9. Stack diameter 15" height 20 ft. thick 2.5 mm =           | 01 | ✓ |

#### Detail of Electric Parts:

- |                                                                |      |   |
|----------------------------------------------------------------|------|---|
| 1. Burner with gas assembly and diesel pump                    | ✓    |   |
| 2. Panel Box 16" x 30" x 8" thick 18 gauge                     |      |   |
| 3. Overload company <del>Schlender</del> <b>Schneider</b>      | = 02 | ✓ |
| 4. Pressure switch 10 kg imported                              | = 02 | ✓ |
| <del>5. Loading and unloading Responsibility of Client</del>   |      |   |
| 6. Electric Contactor                                          | = 02 | ✓ |
| 7. Power relay company (Finder)                                | = 04 | ✓ |
| 8. Push <del>button</del> <b>button</b> company (Telemechanic) | = 03 | ✓ |

4/12/25  
Approved by Anslon Shaid  
[Signature]



Specifications:

|                            |              |   |
|----------------------------|--------------|---|
| Type of passes:            | 3 pass       | ✓ |
| Test pressure:             | 225 psi      | ✓ |
| Working pressure:          | 150 psi      | ✓ |
| Tube Dia:                  | 2" or 2 1/2" | ✓ |
| Pressure Shell thickness:  | 1/2"         | ✓ |
| Tube sheet thick:          | 1/2"         | ✓ |
| Rock wool thickness        | 2"           | ✓ |
| Isolation sheet thickness: | 24 GUAGE     | ✓ |
| Burner motor               | 3hp          | ✓ |
| Feedwater motor            | 3hp          | ✓ |

Capacity: 2000kg ✓

Dimension:-

~~Weight:-~~

Power Load:-

7hp

Approved by  Anshu Shukla  
4/12/25

### 3. STEAM HEADLER SEW-103

#### Trait:

Steam headers are design to collect steam from a boiler or steam generator and distribute high-quality, dry steam to various user points while performing several critical functions. ✓

#### Specifications:

- Material of header = M.S ✓
- Diameter = 1 ft ✓
- Branch pipes = 1", 2", 3", 4 "depend on system needs ✓
- Design = Cushioned Cylinder ✓

Dimension: Dia 1ft Length 5ft

Weight:

Power load: 0



4/12/25  
Approved by Anshu Ghelard

#### 4. CANDY CONTINUOUS VACUUM BATCH COOKER SEW-204

##### Trait:

The automatic continuous cooker produces hard-boiled candy/lollipop mass of finest quality with extreme smoothness and exceptional clarity while maintaining mass moisture levels under 1 % (Varies on special integrity masses). Equipped with a high efficiency, energy saving, Tube in Shell Heat Exchanger. ~~The innovative new design of Starmer's special cooking tubes are much more efficient and easy to clean in order to adhere to the GMP standards.~~ Starmer's SEW-204 consists of a Tube in Shell heat exchanger for cooking of the mass. In the Starmer SEW-204 cooker the pre-blend syrup is pumped through single pass, high efficiency, stainless steel Shell and Tube heat exchanger, which cooks the syrup to the required temperature and then transfers it to the flash chamber for vapor removal. After the vapor removal the syrup is automatically transferred to the two receiving kettles for vacuumizing the mass for moisture reduction. After the vacuum process, the cooked mass is unloaded from the stainless-steel kettles for further processing. Starmer's SEW-204 offers high output, with high transparency of syrup while fulfilling fast cooking speed. With its vertical design, and innovative operation, SEW-204 achieves excellent and highly efficient heat transfer characteristics.

##### SPECIFICATIONS:

- Output: Up to 1000 kg/hour ✓
- Drive: 2 hp ✓
- Dozing pump: 3hp (imported used) ✓
- ~~Sugar pump: 2hp 1450rpm~~ ✓
- Pans: S.S 304 (2Nos) ✓
- Body: S.S 304 (double jacketed) ✓
- Electric Panel: with all new features ✓
- For Syrup Pump: 2.0 hp 1450 rpm ✓
- ~~Vacuum Pump: 20 hp 1450 rpm~~ ✓
- Steam working pressure: 150-pound PSI ✓
- Steam inlet Valve: 1" ¼ ✓
- Steam Safety Valve: 1" ✓
- Steam outlet: 3" / 4 ✓
- Hydraulic Test Pressure: 200-pound PSI ✓

Dimension: (2250L x 2110W x 2360H) mm ~~Weight:~~

Power load: 25hp

#### 5. Vacuum Pump SEW-205

The vacuum pump is used to rapidly remove moisture vapors from the cooked candy mass under reduced pressure. It allows lower temperature boiling and prevents caramelization burning of sugars.

Dimension: ?

Power load: 20hp

Specification:  
20 hp  
1400 rpm  
Frame = M.S

## D. DISSOLVING TANK SEW-206

### Trait:

The dissolving tank is an essential unit in the candy manufacturing process designed for the controlled dissolution of sugar, glucose syrup, and other ingredients in water to form a homogeneous sugar solution or slurry. ✓

### Specifications:

- 750kg capacity ✓
- Double jacketed (main body S.S 304 double jacket with M.S.) ✓
- Body in S.S 304 ✓
- Legs in ~~S.S 304~~ M.S. ✓
- Stirrer in S.S 304 ✓
- Gear motor main drive 3hp SEW Brand Germany ✓
- Steam Working Pressure 125-pound P.S.I ✓
- Hydraulic Test Pressure 200-pound P.S.I ✓
- Steam Valve Inlet 1" ✓
- Steam Safety Valve 3"/4 ✓
- Steam Outlet 3"/4 ✓

✓  
Dimension: 2150mmx750mm

~~Weight:~~

✓  
Power load: 3hp

9/12/25  
Approved by Arshad Shabir



## B. STORAGE TANK SEW-200

### Trait:

The storage tank is designed to hold and maintain cooked sugar mass or syrup at a controlled temperature before feeding it into the forming or depositing section of the candy line. ✓

### Specifications:

- 750kg capacity ✓
- single jacketed ✓
- Body in S.S 304 ✓
- Stirrer in S.S 304 ✓
- ~~Gear motor main drive 2hp~~ ✓
- Outlet Valve 2" ✓
- Gear motor main drive 2hp ✓

Dimension: (1250L\*815W) mm

~~Weight:~~

Power Load: 2hp

Approved by:  Anshu Shukla  
9/12/25

## COOLING TABLE SEW-108

### Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch.

### Specifications

- **Base plate thickness:** 10mm in S.S 304
- **Material of plate:** Boundry wall S.S 304
- **Cooling medium water:** Cooling system A frame work for moving water Inlet and outlet Valve 6- Legs4 Nos in S.S 201 grade

Dimension: 3ft x 6ft x 2'6"

Weight:

Power Load:

## 98. KNEADING MACHINE SEW-109

### Trait:

The rotary kneading machine (SEW-109) is a specialized piece of confectionery equipment perfectly suited for the uniform mixing and kneading of the cooked sugar mass used in producing hard-boiled candy. ✓

Its primary function is to guarantee the uniform distribution of essential ingredients, including solids, acids, and any other additives, ensuring a consistent and high-quality final product. ✓

To maintain food safety standards, the machine operates in a hygienic way, utilizing stainless steel for all contact parts, which are also efficiently water-cooled to manage the high temperatures of the candy mass during the kneading process. ✓

This machine eliminates the need for tiresome and exhausting manual mixing and saves on the labor costs. ✓

### Specifications: ✓

- Roller S.S 304 ✓
- Main drive 5hp ✓
- Steel plate 4ft ✓
- Switch on / off ✓
- Side sheets in S.S 201 ✓
- Main plate in S.S 304 ✓

Dimension: 6' x 5.6" x 5.6" Weight:

Power Load: 5hp



## 10: Bubble Gum Mixer SEW-210

Trait:

The bubble gum mixer is used to blend all materials into homogenous gum base mass suitable for further processing (extrusion & shaping).

Spec:-

- 100 Kg in 20 minutes
- Pan in S.S 304
- Double Jacketed with SS 304
- Double Jacketed
- 2 Arms S.S 304
- Pan cover in SS 304
- Gear Motor Main Drive 20hp
- Heavy Duty M.S structure
- Electric Heaters 6000 watt
- Electric pannel with all new features
- Side sheds in S.S 201
- Tilting System

Dimension:-  $\frac{H}{6ft} \times \frac{W}{8ft} \times \frac{L}{8ft}$

Power load: 28hp

## 11: Bubble Gum Extruder SEW-211

Trait:- Bubble gum extruder shapes the mixed gum mass into a continuous rope or sheet with uniform thickness, texture & density making it suitable for further forming (cutting, rolling or shaping). It essentially transforms the soft irregular gum from the mixer into a consistent product form for downstream processing.

Specifications:-

- 1 rope
- 2 worms
- 7.5 hp gear motor drive
- 10 hp inverter
- M.S structure
- Keif in S.S 304
- Electric heaters 6000 watt
- Electric pannel with all new features
- Helping roller system in keef.

Dimensions?

Power load: 18hp

12- CENTER FILLING PUMP

Trait:

The center filling pump is a precision pump for syrup, chocolate, cream, ensures consistent.

<sup>12</sup>  
9. CENTER FILLING PUMP LIQUID SEW-11 ✓

Trait:

The center filling pump is a precision dosing system designed to inject liquid filling (such as fruit syrup, chocolate, cream, or jam) into the core of the candy rope during the forming process. It ensures consistent filling quantity and uniform distribution across all candies. ✓

Specifications:

- Filling chocolate and liquid ✓
- keef in S.S 304 ✓
- keef double-jacketed ✓
- Rod in S.S with Teflon covering food-grade heat proof material ✓
- Pipe flexible food grade ✓
- Electric panel with new feature ✓
- Gear motor 2 hp main drive ✓
- Stand in M.S ✓
- Electric heater to moderate temperature 1000 watt 1 NOS ✓
- Electric inverter 2HP to increase or decrease filling in product ✓
- Overflow system to recycle liquid/Chocolate ✓

Dimension:

Weight:

Power Load: 33 hp



### <sup>3</sup> 10. CENTER FILLING PUMP POWDER SEW-110<sup>3</sup>

Trate: ✓

The center filling powder pump is a precision feeding and dosing unit designed to inject or ✓  
deliver dry or semi-dry powdered filling materials (such as milk powder, cocoa powder, fruit ✓  
powder, or malt-based mixtures) into the center of a candy rope during forming. It ensures ✓  
consistent and uniform distribution of powder filling across all pieces. ✓

Specifications:

- Centre Filing Powder ✓
- -Keef in S.S 304 grade ✓
- ~~Covering~~ ✓
- Electric panel ✓
- Gear motor 2hp ✓
- Variable Inverter 2hp for speed control ✓
- Stand in M.S ✓
- Rod With Teflon covering with S.S worm inside ✓

Dimension:

Weight:

Power Load: 2hp



## 1. BATCH ROLLER SEW-210

### Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffee, fudge production line designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavour, and color before feeding into the rope sizer or forming machine

### Specifications:

- Frame work horizontal ✓
- Rollers Quantity 4 ✓
- Rollers material in S.S 304 food grade ✓
- Upper body in S.S 304 food grade ✓
- Gear motor main drive 2hp ✓
- Up and down drive 2hp ✓
- ~~Electric panel for control~~ ✓
- Electric heaters to maintain temperature 1000 watt (2 NOS) ✓
- Capacity 125 kg ✓
- Gear motor SEW brand Germany ✓
- Roller caplene in casting material ✓
- Additional tray for removal of wastage ✓

Dimension: <sup>H x W x L</sup> 5'6" x 3' x 8'6" ✓

Weight:

Power Load: 5.3 hp

## 12. ROPE SIZER 5 STAGES SEW-210

### Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

### Specifications:

- Horizontal model ✓
- 5 stages (4 stages horizontal & 1 vertical) ✓
- 1st pair in S.S 304 37mm ✓
- 2nd pair in S.S 304 32mm
- 3rd pair in S.S 304 27mm
- 4th pair in S.S 304 22mm
- 5th pair in S.S 304 17mm
- Electric panel in S.S 201 ✓
- Sizer plates in S.S 304 ✓
- Side plates ~~201~~ 201 ✓
- Rope guide in brass ✓
- Electric inverter new brand INVENT company = 3HP ✓
- Gear motors are of SEW brand Germany : 3Hp ✓
- Heat controllers 2 NOS ✓
- Emergency break to stop equipment ✓
- Emergency switch to off equipment ✓
- Electric breakers ✓
- Electric components brand new
- Electric heaters 2kW ✓  $500 \times 4 = 2kW$

Dimension:  $H \times W \times L$   
4'6" x 3' x 5'6" ✓

Weight:

Power Load: 5.68hp

<sup>6</sup>  
13. UNIPLAST FORMING MACHINE SEW-213 C <sup>6</sup>

**Traits:**

SEW 160-C is a universal seamless sweet forming machine suitable for forming Eclairs, Hard Boiled

candy, Caramel, and gum products. The SEW 160-C promises reliable and problem-free 24/7 operation.

This machine requires minimal maintenance. The machine can manufacture sweets in various types like,

- Solid
- Centre-filled
- Liquid Filled
- Powder-Filled A number of features are incorporated to facilitate the operator to run the machine smoothly.
- 24/7 production with up to 1000kgs/hour
- Strong spring loaded punches with diamond polishing ensures long life of die and great finishing for products.
- Quick and easy changeover of die in approx. 3 minutes.
- Low scrap generation
- Universal size Sweet Forming Die

9/12/15  
Approved by Ansab Ghelid  




| Technical specifications                     |                                                                                                                                                             |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacity                                     | Up to 1000kg/hr ✓                                                                                                                                           |
| Speed                                        | 4000 to 6000 pieces/minute depending upon the size of the product also vary from product to product from high to low (candy, toffee, bubble) respectively ✓ |
| Net weight                                   | <del>1900 lbs (1050kg)</del> 1500kg                                                                                                                         |
| Gross weight                                 | <del>2250 lbs (1250kg)</del>                                                                                                                                |
| Inverter main drive die                      | 3 Hp ✓                                                                                                                                                      |
| Inverter main drive spreader                 | 1Hp ✓                                                                                                                                                       |
| Inverter main drive spreader box             | 1Hp ✓                                                                                                                                                       |
| Belt                                         | Teflon coted food grade ✓                                                                                                                                   |
| Grease pump                                  | Lubrication ✓                                                                                                                                               |
| Side Sheets                                  | In S.S 201 ✓                                                                                                                                                |
| Pressure Cams                                | In D2 Grade ✓                                                                                                                                               |
| Reserve cams                                 | In S.G.R iron grade ✓                                                                                                                                       |
| Sizer sets                                   | In High carbon steel ✓                                                                                                                                      |
| <del>Turning belt</del>                      | <del>To increase efficiency</del>                                                                                                                           |
| Gears                                        | In high carbon steel ✓                                                                                                                                      |
| Electrical panel                             | With all new features ✓                                                                                                                                     |
| Blower                                       | 2 Hp for cooling of die ✓                                                                                                                                   |
| Power load main drive                        | 3 Hp ✓                                                                                                                                                      |
| Power load sizer box drive                   | 1 Hp ✓                                                                                                                                                      |
| Power load spreader drive                    | 0.5 Hp ✓                                                                                                                                                    |
| Power load spreader movement                 | 0.5 Hp ✓                                                                                                                                                    |
| Power load of arms movement for die changing | 0.5 Hp ✓                                                                                                                                                    |

Dimension:

HxWxL  
6ft x 45ft x 8.5ft

Weight:

Power Load:

7.5hp

~~10.5hp~~

Approved by Aarsalam Shahid  
4/12/25

*[Signature]*

# High speed Grade

## 1. ROTARY DIE WITH CUTTING RING SEW-21A

### Trait:

The heart of any candy production line are the rotary dies in the forming machine. It literally shapes the product and adds to the face value. The forming dies are used for the production of hard boiled candies, Toffees, Eclairs, Powder-filled candies, Liquid filled candies and more.

Starmer Forming dies are recognized in the confectionery industry for their precision-based performance, along with being safe and having the functional efficiency.

Starmer machines are built for generational use, we offer supply of spare parts and die-heads for models that may have been discontinued for decades. As the leading confectionery machinery manufacturer, Starmer aims to be your reliable long-term business partner and offers the following benefits.

### Accuracy:

- Perfectly formed, seamless candies
- Nearly any shape of candy can be made
- To ensure accuracy, we provide drawings, products samples on request to help you visualize the sense of the product.

### Quality:

- Finest quality of raw-material used

### Durability:

- Our 55+ years of experience has garnered the forming dies into a piece of perfection, even with continuous production, the die-set does not damage easily.

### Specification:

Cutting ring in Grade EN 19 High Wear Resistance. This grade provides cutter Pitch (Teeth) of up to 2 mm

- Punch: Punch in Grade EN 19, Hardness up to 55 HRC High Wear Resistant Block: High Quality M.S Temperad & Good Wear Resistant.

• Guide pins: Guide pin in High speed Carbon steel. This will improve the guidance of punch resulting in better efficiency of die. ✓

• Die parts: Casting in Grade Cast Iron. ✓

Outer Ring: Outer ring in Brass Casting. For the improvement of rope cutting. ✓

Dimension:

Weight:

Power Load: ○

Dia: 1.5ft x L 2ft



## 15.DIE STAND SEW-215

### Trait:

For hanging the die and also used for die changing for operations ✓

### Specifications:

- Main Frame in M.S ✓
- Wheels for Movement ✓
- Die cap lane in casting material ✓
- Screw for die up/down ✓

### Dimension:

H x Dia  
5.5ft x 5ft

### Weight:

Power Load: 0

## 16. COOLING TUNNEL 3 STAGES SEW-216

Compact, high capacity cooling conveyor and tunnel, well suited for all types of hard candies and feed products, requiring sufficient cooling prior to packaging. Starmer cooling conveyors are designed for precision cooling of all types of hard and soft candy having solid or soft centres, wrapped or unwrapped. Our cooling conveyors come with an option of capability of up to 1000 kg/hr Starmer cooling conveyors are available in various sizes and parameters and can also be customized as per the customer's requirement. With fine product side guards and stainless steel transfer chutes, Individual tier cooling ducts for cooling the product from all sides. Benefits:

- ① Hygienic design ✓
- ② Low maintenance due to individually controlled motors for each tier. ✓
- ③ With variable speed A.C. drives to control speed of the belts. ✓
- ④ Perforated food grade Polypropylene belting allows for ventilation all around the product. ✓
- ⑤ Insulated walls for rapid cooling. ✓
- ⑥ Controlled Air conditioned ventilation. ✓

Specifications:

- ~~Model: 216~~ ✓
- Style: Three tier Horizontal Cooling Conveyor. ✓
- ① Size: 16ft long, 5ft width Size 20ft length, 4ft width
- ② Stage: 3 stages ✓
- ③ 1st step: Mesh 1st step mesh in ~~plastic teflon coated~~ ✓ PP in food grade material
- ④ 2nd step: mesh in ~~plastic teflon coated~~ ✓
- ⑤ 3rd step: \*\* mesh in ~~plastic & teflon coated~~ ✓
- ⑥ A.C: 20-Ton capacity ✓
- ⑦ Outer & inner side sheets in S.S 201 ✓
- ⑧ Electric panel: with all new features ✓
- ⑨ Inverter: new brand variable speed inverter, ~~Electric Inverter for controlling speed (2 hp each 3 nos)~~ 6hp ✓
- ⑩ All covers in S.S 201 ✓
- Double jacketed insulates with thermopore.
- Gear: Motor 3 KW (1 KW each 3 nos) SEW brand, ~~Water cool~~
- ~~air cool depend upon requirement of customer, Total power load of this machine = 24 hp~~

Dimension: L W H  
20ft x 4ft x 6ft

Weight:

Power Load: 6hp ~~34hp~~

4/12/25  
Approved by Anshul  
Anshul

<sup>20</sup>  
20. COOLING AC UNIT SEW-20

Specification of Ac unit: ✓

Indoor Unit capacity 20 Ton (25 HP) roof type for cooling conveyor Accessories indoor ✓

evaporator brand new copper tube size 3/8 gage 22 ✓

distance size 78 section header 3/8. ✓

2: aluminum fins thickness. 0.150mm company Breez ✓

3: High velocity Air blower With 3 HP motor 3 phase 440/v Hz ✓

50 ✓

4; expansion valve company Emerson model TCLE 25 HP. ✓

5: Base frame angle iron sizes are on customer demand ✓

6: indoor frame cover sheet Gi colored 22 gage ✓

7, indoor frame cover sheet insulation with insulated material ✓

8: Indoor copper pipe fitting 18 gage length tube ✓

25 HP OUTDOOR Company Bitzer with all his ACCESSORIES ✓

1. condensing unit Company Bitzer with high density condensing coil ✓

2: High static air flow fan 3phase 440/v Ha50 ✓

3: compressor semi sealed company Bitzer 3 phase 440N ✓

H250

4: Liquid receiver capacity 10 liter. ✓

5: Oil spreader in/out pipe size 1 1/8 ✓

6: Flexible pipe company Hong son 1 1/8 and 1 3/8 ✓

7: Hand valve 771 ✓

B: Filter 78 ✓

9: Copper length 8, T ya and T 3/8 ✓

10: section accumulator T 3/8. ✓

11: Copper long bead and 1 1/8 and T 3/8 elbow ✓

  
Approved by A. Alshukri  
4/12/25



12: dual high low pressure safety switch company Dantoss with high pressure leads. ✓

13: Outdoor base frame channel and angle ✓

15: refrigerant R-22 company ( Honey well USA ) ✓

ELECTRIC PANEL equipment's: ✓

1: 22 KVA inverter company (INVT 1. ✓

2: magnetic contactor 100A amperes for compressor ✓

3: Holding contactor. ✓

4: blower contactor. ✓

5: egra thermostat ✓

6: fan contactor. ✓

7. connection strip ✓

8: push button. ✓

9: Electric panel box size 24' x 36. ✓

Ducting ✓

indoor conveyor complete ducting with Gi sheet with insolation glass wool material ✓

Dimension:

Weight:

Power Load:

28hp

4/12/25  
Approved by Amran Shehid  


21  
18.VIBRATOR SEW-120

Trait:

The vibrator helps smoothly transport candies from the cooling and forming sections to packaging, preventing clumping or sticking. ✓

Specifications:

- Frame in M.S ✓
- Main sheet in S.S 304 ✓
- Fan 2 nos ✓
- Gear motor ~~1/2~~ 1/4 hp ✓
- Trays in S.S 304 for removal of wastage 2 nos ✓

Dimension:

4ft width  
8ft length

Weight:

Power Load: 1hp

## 22 Pillow Pack

### 10. WRAPPING MACHINE SEW-123

#### Trait:

Is high performance pillow pack wrapping machine for filled or un-filled candies, bubblegums and other similar items incorporating latest and precision components the machine is capable of achieving speed upto 800 pieces per minute. Fin seal and end seal are of high quality ensuring long shelf life of the product. Large size feed disc and brushes enable positive transfer of candies to the carrier chain

#### SPECIFICATIONS:

- OUTPUT:
- Upto 800 Pcs/min on candy ✓
- Upto 500 Pcs/min on bubble ✓
- ELECTRIC MOTORS:
- (1) 2 H.P./3-Phase ✓
- (2) ½ H.P. ✓
- ELECTRIC HEATERS: 3.2 Kw ✓
- STANDARD EQUIPMENT: Photo Electric Eye & Inverter ✓
- DIMENSIONS (L x W x H): 2,335 x 900 x 1,715 mm ✓
- WEIGHT: 750 Kg ✓
- REEL (Maximum Outer Dia / Core Dia): 280 / 70 mm ✓

#### Dimension:

Same as dynamic:  
H x W x L  
1,715 x 900 x 2,335 mm

#### Weight:

Same as dynamic  
~~750 kg~~

#### Power Load:

Same as dynamic