

Complete Candy line 200 kg/hr

BOOKLET FOR COMPLETE PRODUCT LINES

New



Starmmer
Engineering Works

COMPLETE CANDY LINE 200 KG/HR ✓

1. GLUCOSE TANK SEW-101 ✓

2. STEAM GENERATOR SEW-102 ✓

3. STEAM HEADER SEW-103 ✓

4. DISSOLVING TANK SEW-106 ✓

5. BATCH TYPE COOKER SEW-005 ✓

6. VACCUM PUMP SEW-006 ✓

7. COOLING TABLES SEW-108 ✓

8. KNEADING MACHINE SEW-109 ✓

9. BATCH ROLLER SEW-114 ✓

10. ROPE SIZER SEW-115 ✓

11. SMALL CANDY PLANT SEW-012 ✓

12. SMALL CANDY DIE ✓

13. VIBRATOR SEW-120

14. PILLOW PACK WRAPPING MACHINE SEW-123

9 → Powder filling pump SEW-009

✓ SEW-013

1. GLUCOSE TANK SEW-101

Traits:

Glucose storage tanks are engineered with specific traits to ensure hygienic, Stable and crystal free storage of liquid glucose and Syrups for industrial applications.

Specifications:

Size:	14 ft height x 7.5 ft diameter (approximate)
Grade:	S.S 304 ✓
Sheet thickness:	5 mm upper and lower sheet ✓
Outer dia sheet thickness:	3 mm ✓
Design Type:	Vertical ✓
Heating System:	Coil on the base of tank ✓
Ladder:	Outside the tank ✓
Capacity:	20 ton glucose

Dimension: ~~14 ft~~ ~~7.5 ft dia~~ 16 ft x 7 ft (H x diameter)

Weight: ?

Power Load: 0

2. STEAM GENERATOR SEW-102

TRAIT:

Steam generator heats water to produce high pressure steam for heading, cleaning or industrial process ✓

Detail of Mechanical Parts: ✓

- | | | |
|--|----|---|
| 1. Gauge Glass 1/2" = | 01 | ✓ |
| 2. Stop Valve diameter 1/2" = 1" | 01 | ✓ |
| 3. Safety Valve diameter 1/2" = 1" | 01 | ✓ |
| 4. NRV diameter 1" 1/2" = | 01 | ✓ |
| 5. Blow down diameter 1/2" = 1" | 01 | ✓ |
| 6. Air Vent diameter 1/2" globe Valve = 1/2" | 01 | ✓ |
| 7. Feed Water Pump 01 Multistage (Grundfos)= | 01 | ✓ |
| 8. Electric panel Box with complete auto controlled system = | 01 | ✓ |
| 9. Stack diameter 1/2" height 20 ft. thick 2.5 mm = | 01 | ✓ |

Detail of Electric Parts:

- | | | |
|--|------|---|
| 1. Burner with gas assembly & diesel pump | | |
| 2. Panel Box 16" x 30" x 8" thick 18 guage | | |
| 3. Overload company Schneider | = 02 | ✓ |
| 4. Pressure switch 10 kg imported | = 02 | ✓ |
| 5. loading and unloading Responsibility of Client | | |
| 6. Electric Contactor | = 02 | ✓ |
| 7. Power relay company (Finder) | = 04 | ✓ |
| 8. Push button company (Telemechanic) | = 03 | ✓ |

Capacity:

~~2000 lb~~ 600kg

Specifications:

Type of passes:	3 pass ✓
Test pressure:	225 psi ✓
Working pressure:	150 psi ✓
Tube Size:	2" or 2 1/2" ✓
Pressure Shell thickness:	1/2" 1/2" ✓

Tube sheet thick:	$\frac{1}{2}$ " ✓
Tube sheet thickness (repeated):	$\frac{1}{2}$ " ✓
Insulation Insulation sheet thickness:	24 guage ✓
Rock Wool thickness:	2"

Burner Motor	2 hp
--------------	------

Dimension: $8' \times 3'5" \times 3'5"$ Weight
H x L x W

Power Load: 5 hp

~~Capacity = 1500 kg/hr~~

~~Electric Load: 6 kW~~

~~Capac~~

3. STEAM HEADER SEW-103

Trait:

Steam headers are design to collect steam from a boiler or steam generator and distribute high-quality, dry steam to various user points while performing several critical functions.

Specifications:

- Material of header = M.S
- Diameter = 1 ft
- Branch pipes = 1, 2, 3, 4 depend on system needs

Design = Cushioned Cylinder

Dimension:

~~Weight:~~

Power Load: 0

4. DISSOLVING TANK SEW-106

Trait:

The dissolving tank is an essential unit in the candy manufacturing process designed for the controlled dissolution of sugar, glucose syrup, and other ingredients in water to form a homogeneous sugar solution or slurry. ✓

Specifications:

- . 400 kg capacity ✓
- . Double jacketed with M.S ✓
- . Body in S.S 304 ✓
- . Legs in M.S ✓
- . Stirrer in S.S 304 ✓
- . Gear motor main drive 2 hp ✓
- ~~Size 5'6" x 3'5" x 3'5" (H x W x L)~~
- Steam guage
- Safety valve
- Seat valve

(H x W x L)

Dimension: 5'6" x 3'5" x 3'5"

Weight:

Power Load: 2 hp

5. BATCH TYPE COOKER SEW-005

Traits:

A Batch Type Cooker (also called a batch cooker or batch vacuum cooker) is used to cook and concentrate the sugar syrup to the desired final moisture content and temperature, a critical step in producing high-quality candy. ✓

Specifications:

- 200 kg per hour ✓
- 2 hp gear motor main drive ✓
- Pan in S.S 304 ✓
- Main Body in S.S 304 ✓
- Electric Control Pannel ✓
- Guages ✓
- Cooker Frame in M.S ✓
- Double jacketed with M.S ✓

Dimension (H x W x L) = 8' x 2' 5" x 3' 5" ✓

Weight: ✓

Power Load: 2hp

6.VACUUM PUMP SEW-006

Trait:

The vacuum pump is used to rapidly remove moisture (Water vapour) from the cooked candy mass under reduced pressure, which allows lower temperature boiling and prevents caramelization or burning of sugars. ✓

Specification:

For vacuum pump 7.5 hp=1450 rpm ✓

Frame = M.S ✓

Dimension=~~HxWxL=15x14x5~~"

$$1-1 \times W \times L = 2 \text{ ft} \times 4 \text{ ft} \times 1 \text{ ft}$$

Weight:

Power Load: 7.5 hp

7.COOLING TABLES SEW-108

Trait:

- * The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch. ✓

Specifications:

- * ~~Dimension: 3 ft x 6 ft x 2'.6" (W x L x H)~~
- * Base plate thickness: 10 mm in S.S 304 ✓
- * Material of plate: ~~Bound~~ ^{Boundary} wall S.S 304 ✓
- * Cooling medium: Water Cooling system A frame work for moving water inlet and outlet * ~~valve~~. ✓

~~Value 6 Legs 4 Nos in S.S 201 grade~~

• legs 4 Nos in SS 201 grade

^{H x L x W}
Dimension: 3 ft x 6 ft x 2'.6" (~~W x L x H~~)

Weight:

Power load : 0

8.KNEADING MACHINE SEW-109

Trait:

- The rotary kneading machine (SEW-109) is a specialized piece of confectionery equipment perfectly suited for the uniform mixing and kneading of the cooked sugar mass used in producing hard-boiled candy. ✓
- Its primary function is to guarantee the uniform distribution of essential ingredients, including solids, acids, and any other additives, ensuring a consistent and high-quality final product. ✓
- To maintain food safety standards, the machine operates in a hygienic way, utilizing stainless steel for all contact parts, which are also efficiently water-cooled to manage the high temperatures of the candy mass during the kneading process. ✓
- This machine eliminates the need for tiresome and exhausting manual mixing and saves on the labor costs. ✓

Specifications:

- Roller in S.S 304 ✓
- Main drive: 5 hp. ✓
- Steel plate: 4 ft. ✓
- Switch on / off ✓
- Side sheets in SS 201 ✓
- Main plates: SS 304 ✓

Dimensions (H x W x L): 5' x 5' . 6" x 5'.6". ✓

Weight:

Power Load: 5hp

9. Center filling Powder Pump

Trait:- The center filling powder pump is a precision feeding and dosing unit designed to inject or deliver dry or semi dry powdered filling materials (such as milk powder, cocoa powder, fruit powder or malt-based mixtures) into the center of a candy rope during forming. It ensures consistent and uniform distribution of powder filling across all pieces.

Specification:-

- Centre filling Powder
- Keef in S.S 304 grade
- Electric Pannel
- Gear Motor 2hp
- Variable inverter 2hp for speed control
- Stand in M.S
- Rod with Teflon covering with S-S worm inside.

Dimension :-

H x W x L

Power load
2hp

¹⁰ BATCH ROLLER SEW-114

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffe, fudge production line designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavour, and color before feeding into the rope sizer or forming machine.

Specifications:

- Frame work horizontal ✓
 - Rollers quantity 4 ✓
 - Rollers material in S.S 304 food grade ✓
 - Upper body in S.S 304 food grade ✓
 - Gear motor main drive 1hp ✓
 - Up and down ~~system~~ drive 1 hp ✓
 - ~~Electric panel~~ for control (2 Nos) ✓
 - Electric heaters to maintain temperature 1000 watt ~~2nos - 2KW~~ ✓
 - Capacity 75 kg ✓
 - Length 6.5 ft ✓
 - ~~Dimension: 5'6" x 3' x 8'6"~~
 - Gear motor SEW brand Germany ✓
 - Roller caplene in casting material ✓
 - Additional tray for removal of wastage ✓
 - Bearing in gears.
- Dimension: ~~5'6" x 3' x 8'6"~~ 4'6" x 2'22" x 7' ✓

Weight:

Power Load: 4.68 hp

10. ROPE SIZER SEW-115

Traits:

- The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

General Specifications:

- Horizontal model
- ~~5 stages~~ (4 stages horizontal & ~~1 vertical~~)
- 1st pair in S.S 304 32 mm
- 2nd pair in S.S 304 27 mm
- 3rd pair in S.S 304 22 mm
- 4th pair in S.S 304 17 mm
- Electric panel in S.S 201
- Sizer plates in S.S 304
- Side ~~plates~~ ^{sheets} in S.S 201
- Rope guide in brass
- Electric inverter new brand invent company=2hp
- Gear motors are of SEW brand Germany=~~2hp~~
- Heat controllers digital 2 nos
- Emergency break to stop equipment
- Emergency switch to off equipment
- Electric breakers
- Bearings are used instead of bushes to reduce maintenance *of equipment*
- Main Drive gear motor=2hp
- Headers 500 Watt (4Nos) = 2kw

H x W x L
4.5ft x 2.5ft x 6ft

Dimensions = ~~4.5ft x 2.5ft x 6ft~~ H x W x L

~~4.5ft x 2~~ ✓

~~Weight:~~

Power Load: 4.68hp

1.2 SMALL CANDY PLANT SEW-011

Trait:

A Small Candy Former is a forming unit designed to shape, size and cut candy mass into uniform pieces under controlled mechanical and thermal conditions. ✓

Its primary function within the candy production line is to convert the candy rope produced after cooking and rolling into individual shaped units. ✓

Specification:

- Oil Bath System in Gears ✓
- Motor 1 hp ✓
- Side Sheets M.S (Mild Steel) ✓
- Without die ✓
- On/off Switch ✓
- Speed upto 1000 pieces/min ✓
- Capacity upto 200 kg/hr ✓
- filling of powder upto %

Dimension:

Weight:

Power Load: 1hp

15
~~13~~ SMALL CANDY DIE:

By Haseeb

14
13. VIBRATOR SEW-120

Trait:

The vibrator helps smoothly transport candies from the cooling and forming sections to packaging, preventing clumping or sticking. ✓

Specifications:

- Frame in M.S. ✓
- Main sheet in S.S 304 ✓
- Fan 2 nos ✓
- Gear motor ~~0.5 hp~~ 1hp ✓
- Trays in S.S 304 for removal of wastage 2 nos ✓

H x W x L
3.5ft x 4.5ft x 8ft

Dimension = ~~H x W x L = 36" x 46" x 96"~~

~~4ft width 8ft length~~

Weight:

Power Load: 1hp

15. PILLOW PACK WRAPPING MACHINE

Trait:

Is high performance pillow pack wrapping machine for filled or un-filled candies, bubblegums and other similar items incorporating latest and precision components the machine is capable of achieving speed upto 800 pieces per minute. Fin seal and end seal are of high quality ensuring long shelf life of the product. Large size feed disc and brushes enable positive transfer of candies to the carrier chain.

SPECIFICATIONS:

• OUTPUT:

• Upto 800 Pcs/min on candy • Upto 500 Pcs/min on bubble

• ELECTRIC MOTORS:

• (1) 2 H.P./3-Phase

• (2) ½ H.P.

• ELECTRIC HEATERS: 3.2 Kw

• STANDARD EQUIPMENT: Photo Electric Eye & Inverter

• DIMENSIONS (L x W x H): 2,335 x 900 x 1,715 mm

• WEIGHT: 750 Kg

• REEL (Maximum Outer Dia / Core Dia): 280 / 70 mm

Dimension :

Same as dynamic
(H x W x L) : (1,715 x 900 mm x 2,335)

Weight:

Same as dynamic
750 Kg

Power Load:

Same as dynamic