

Lollipop Complete line ~~250~~ kg/hr
200

BOOKLET FOR COMPLETE PRODUCT LINES

NEW



Starmers
Engineering Works

LOLLIPOP COMPLETE LINE 250KG/HOUR

1. Glucose Tank SEW-101 ✓
2. Steam Generator SEW-102 ✓
3. Steam Headler SEW-103 ✓
4. Batch Type Cooker SEW-005 ✓
5. Vacuum Pump SEW-006 ✓
6. Dissolving Tank SEW-106 ✓
7. Cooling Table SEW-108 ✓
8. Kneading Machine SEW-109 ✓
9. Bubble Gum Mixer SEW-112 ✓
10. Extruder SEW-113 ✓
11. Batch Roller 75KG SEW-114 ✓
12. Rope Sizer 5 Stages SEW-115 ✓
13. Lollipop Forming Machine SEW-411 ✓
14. Lollipop Standard Die (30-32 Plungers) ✓
15. AC 5 Ton Unit SEW-122 ✓
16. Cooling Conveyor 5 Stages with Elevator SEW-413 ✓
17. Wrapping Machine SEW-414 ✓

1. Glucose Tank SEW-101 ✓

Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, Stable and crystal free storage of liquid glucose and Syrups for industrial applications. ✓

Specifications:

Size:	14 ft height x 7.5 ft diameter (approximate)
Grade:	S.S 304
Sheet thickness:	5 mm upper and lower sheet
Outer dia sheet thickness:	3 mm
Design Type:	Vertical
Heating System:	Coil on the base of tank
Ladder:	Outside the tank
Capacity:-	20 ton glucose

Dimension: 16 ft height x 7 ft diameter.

Weight:

Power load: 0

2. Steam Generator SEW-102

Trait:

Steam generator heats water to produce high Pressure steam for heating, cleaning or industrial processes. ✓

Detail of Mechanical Parts:

- | | |
|--|------|
| 1. Gauge Glass like a new = | 01 ✓ |
| 2. Stop Valve diameter 2 1/2" = 1" | 01 ✓ |
| 3. Safety Valve diameter 1 1/2" = 1" | 01 ✓ |
| 4. NRV diameter 1" like a new = | 01 ✓ |
| 5. Blow down diameter 1 1/2" = 1" | 01 ✓ |
| 6. Air Vent diameter 1" globe Valve = 1/2" | 01 ✓ |
| 7. Feed Water Pump 01 Multistage (Grundfos)= | 01 ✓ |
| 8. Electric panel Box with complete auto controlled system = | 01 ✓ |
| 9. Stack diameter 18" height 20 ft. thick 2.5 mm = | 01 ✓ |
| 8" 15ft | |

Detail of Electric Parts:

- | | |
|--|--------|
| 1. Burner with gas assembly and diesel pump | |
| 2. Panel Box 16" x 30" x 8" thick 18g | |
| 3. Overload company Schlender Schneider | = 02 ✓ |
| 4. Pressure switch 10 kg imported | = 02 ✓ |
| 5. Loading and unloading Responsibility of Client | |
| 6. Electric Contactor | = 02 ✓ |
| 7. Power relay company (Finder) | = 04 ✓ |
| 8. Push button company (Telematic) | = 03 ✓ |
| button | |

Specifications:

✓ Type of passes:	3 pass ✓
✓ Test pressure:	225 psi ✓
✓ Working pressure:	150 psi ✓
✓ Tube Dia:	2" or 2 1/2" ✓
✓ Pressure Shell thickness:	1/2" ✓
✓ Tube sheet thick:	1/2" ✓
✓ Rock wool thickness	2" ✓
✓ Isolation sheet thickness:	24 GAUGE ✓
✓ Motor Burner	2hp ✓
✓ Feed water motor	3hp ✓

Capacity: ~~1200kg/hr~~ ✓

Electric Load: ~~5kW~~ 6kW ✓

Dimension: 8'x3'5"x3'5" ✓

Weight:

Power Load:

Approved by *4/12/25*
Amirah Ghani
11/2/25

3. Steam Header SEW-103

Trait:

Steam headers are design to collect steam from a boiler or steam generator and distribute high-quality, dry steam to various user points while performing several critical functions.

Specifications:

- Material of header = M.S
- Diameter = 1 ft
- Branch pipes = 1", 2", 3", 4 "depend on system needs
- Design = Cushioned Cylinder
- Connection = 5

Dimension: Dia 1ft X Length 3ft

~~Weight:~~

Power load: 0

4. Batch Type Cooker SEW-005

Traits:

A Batch Type Cooker (also called a batch cooker or batch vacuum cooker) is used to cook and concentrate the sugar syrup to the desired final moisture content and temperature, a critical step in producing high-quality candy. ✓✓

Specifications:

- * 200 kg per hour ✓
- * 2 hp gear motor main drive ✓
- * Pan in S.S 304 ✓
- * Main Body in S.S 304 ✓
- * Electric Control Pannel ✓
- * Guages ✓
- * Cooker Frame in M.S ✓
- * Double jacketed with M.S ✓

Dimension (H x W x L) = 8' x 2' 5" x 3' 5" ✓

Weight:

Power Load: 2hp

Approved by 
4/12/25

5. Vacuum Pump SEW-006

Trait:

The vacuum pump is used to rapidly remove moisture (Water vapour) from the cooked candy mass under reduced pressure, which allows lower temperature boiling and prevents caramelization or burning of sugars. ✓

Specification: ✓

For vacuum pump 7.5 hp=1450 rpm ✓

Frame = M.S ✓

Dimension=HxWxL:-1'5"x1'x3'5"

Weight:

Power Load:

4/12/25
Approved by Anshu Shehri


6. Dissolving Tank SEW-106

Trait:

The dissolving tank is an essential unit in the candy manufacturing process designed for the controlled dissolution of sugar, glucose syrup, and other ingredients in water to form a homogeneous sugar solution or slurry.

Specifications:

- 400kg capacity ✓
- Double jacketed with MS ✓
- Body in S.S 304 ✓
- Legs in M.S ✓
- Stirrer in S.S 304 ✓
- Gear motor main drive 2hp ✓
- Steam guage
- safety valve
- Seat valve

Dimension: 5'6"x 3'5"x 3'5"
H x W x L ✓

Weight:

Power Load: 2hp

7. Cooling Table SEW-108

Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch. ✓

Specifications

- **Base plate thickness:** 10mm in S.S 304 ✓
- **Material of plate:** Boundry wall S.S 304 ✓
- **Cooling medium water:** Cooling system A frame work for moving water Inlet and outlet ✓
Valve 6-~~legs 4 Nos in S.S 201 grade~~ ✓
- legs 4 Nos in S.S 201 grade

$H \times L \times W$
Dimension: 3ft x 6ft x 2'6" ✓

~~Weight:~~

Power Load: ⓪

8. Kneading Machine SEW-109

Trait:

The rotary kneading machine (SEW-109) is a specialized piece of confectionery equipment perfectly suited for the uniform mixing and kneading of the cooked sugar mass used in producing hard-boiled candy. ✓

Its primary function is to guarantee the uniform distribution of essential ingredients, including solids, acids, and any other additives, ensuring a consistent and high-quality final product. ✓

To maintain food safety standards, the machine operates in a hygienic way, utilizing stainless steel for all contact parts, which are also efficiently water-cooled to manage the high temperatures of the candy mass during the kneading process. ✓

This machine eliminates the need for tiresome and exhausting manual mixing and saves on the labor costs. ✓

Specifications:

- Roller S.S 304 ✓
- Main drive 5hp ✓
- Steel plate 4ft ✓
- Switch on / off ✓
- Side sheets in S.S 201 ✓
- Main plate in S.S 304 ✓

Dimension: $H \times W \times L$
5'x5'6"x5'6" ✓

~~Weight:~~

Power Load: 5hp

9. Bubble Gum Mixer SEW-112

Traits:

The bubble gum mixer is used to blend all the raw ingredients into a homogeneous gum base mass suitable for further processing (like extrusion and shaping).

Specification:

1. Capacity: 100 kg in 20 min ✓
2. Pan: In S.S 304 ✓
3. Double jacketed ✓
4. Double jacketed with 80 M.S. ✓
5. Z-arm: S.S 304 ✓
6. Pan cover: In S.S 304 ✓
7. Gear motor main drive: 20 hp ✓
8. Heavy duty: M.S structure ✓
9. Electric heaters ✓ 6000 Watt
10. Electric panel with all new features ✓
- ~~11. Weight: 2 ton approx~~
12. Side sheets: S.S ✓ 201
13. Tilting system

H x W x L

Dimension: (6' x 8' x 8')

~~Weight~~

Power Load: 28hp

10. Extruder SEW-113

Traits:

The bubble gum extruder shapes the mixed gum mass into a continuous rope or sheet with uniform thickness, texture, and density—making it suitable for further forming (cutting, rolling, or shaping). ✓

It essentially transforms the soft, irregular gum from the mixer into a consistent product form for downstream processing. ✓

Specifications: ✓

1. 1 rope ✓
2. 2 Worms ✓
3. 7.5 hp gear motor drive ✓
4. 10 hp inverter ✓
5. M.S structure ✓
6. keef in S.S 304 ✓
7. Electric heaters 6000 watt ✓
8. Electric panel with all new features ✓
9. Helping roller system in keef ✓

Dimension:



Power Load: 18 hp

11. Batch Roller 75KG SEW-114

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffe, fudge production line designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavour, and color before feeding into the rope sizer or forming machine.

Specifications:

- Frame work horizontal ✓
- Rollers Quantity 4 ✓
- Rollers material in S.S 304 food grade ✓
- Upper body in S.S 304 food grade ✓
- Bearing in gears ✓
- Gear motor main drive 1hp ✓
- Up and down drive 1hp ✓
- ~~drive 2 hp~~
- ~~Electric panel for control~~
- Electric heaters to maintain temperature 1000 watt (2 NOS) ✓
- Capacity 75 kg ✓
- Length 6.5 ft ✓
- Gear motor SEW brand Germany ✓
- Roller caplene in casting material ✓
- Additional tray for removal of wastage ✓

$H \times W \times L$
Dimension: 4'6"x2'2"x7' ✓

~~W 6.5 ft~~

Power Load: 4.6

12. Rope Sizer ⁴ Stages SEW-115

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

Specifications:

- Horizontal model
- 4 stages
- 1st pair in S.S 304 32mm
- 2nd pair in S.S 304 27mm
- 3rd pair in S.S 304 22mm
- 4th pair in S.S 304 17mm
- Electric panel in S.S 201
- Side sheets in S.S 201
- Sizer plates in S.S 304
- Rope guide in brass
- Electric inverter new brand INVENT company = 2HP
- Gear motors are of SEW brand Germany
- Heat controllers Digital 2 NOS
- Emergency break to stop equipment
- Emergency switch to off equipment
- Electric breakers
- Bearings are used instead of bushes to reduce maintenance of equipment
- Main Drive Gear Motor = 2HP
- Heaters 500 Watt (4 NOS) = ~~2kw~~ 2Kw

Dimension: H x W x L ~~W x H x L~~
4.5ft x 2.5ft x 6ft

Power Load: 4.68hp

13. Lollipop Forming Machine SEW-411

Trait:

The purpose of a 250 pieces round lollipop former machine is a critical function within a standard speed lollipop production line. It is the machine responsible for taking the cooked and prepared candy rope and transforming it into consistently sized, perfectly round lollipops with a stick inserted.

Specifications:

- Lollipop diameter: 17 mm – 34 mm
- Speed: 250 – 300 pcs/min.
- Main drive: gear motor 3 hp with variable inverter
- Electric panel with all new features
- Heavy Duty M.S structure.
- Side sheets: M.S

Dimension (HxWxL): (4'6" x 4'6" x 4'6").

Weight:

Power Load: 3hp

14. Lollipop Standard Die (30-32 Plungers)

size: 16-34 mm

Shape: Round

Trait:

A round lollipop standard-speed Die is a precision-machined forming component used in traditional or moderate-throughput lollipop production lines. It's primary function is to shape the candy rope into round lollipop heads with continuous stick insertion.

Material Specification:

- Cutting Ring: Cutting Ring in grade forged M.S. This grade provides cutter pitch (teeth) of 1.5 - 2.5 mm
- Punch: Punch in grade 1045, Hardness up to 45 HRC
- Block: High Quality M.S
- Guide Pins: Guide pins in grade Carbon Steel.
- Die Parts: Casting in grade Cast Iron

Durability:

- The Finest & quality raw material used
- Our 55+years of experience have garnered the Forming dies into a piece of Perfection. Even with continuous production, the die-set does not damage easily.

Dimension: 2'x2'x2'

~~Weight:~~

Power Load: ①

15. AC 5 Ton Unit SEW-122

Description:

Indoor Unit capacity 5 Ton (6.5 HP) floor standing type for cooling conveyor Accessories indoor:

- 1: evaporator brand new copper tube size 3/8 gage 22 distributor size 1/2 section header 7/8.**
- 2: aluminum fins thickness. 0.150mm company Breez.**
- 3: High-velocity air blower With 1 HP motor 3 phase 440/v Hz 50.**
- 4: expansion valve company Emerson model TCLE 6.5 HP.**
- 5: Base frame angle iron sizes are on customer demand.**
- 6: Indoor frame cover sheet GI colored 22 gage.**
- 7: indoor frame cover sheet insulation with insulated material.**
- 8: Indoor copper pipe fitting 18 gauge length tube.**

6.5 HP OUTDOOR Company Bitzer with all his ACCESSORIES:

- 1: condensing unit Company Bitzer with high-density condensing coil.**
- 2: High static air flow fan 3phase 440/v Hz50.**
- 3: compressor Copeland scroll capacity 6.5 HP 3 phase 440/v Hz50.**
- 4: Liquid receiver capacity 5 liter.**
- 5: Oil spreader in/out pipe size 7/8.**
- 6: Hand valve 1/2.**
- 7: Filter 1/2.**
- 8: Copper length 1/2 and 5/8.**
- 9: section accumulator 7/8**
- 10: Copper long bend 5/8 and 7/8 and 3/8 elbow.**
- 11: dual high low-pressure safety switch company Danfoss with high-pressure leads.**
- 12: Outdoor base frame channel and angle iron.**
- 13: refrigerant R-22 company (Honeywell USA).**

ELECTRIC PANEL equipment:

- 1: 7.5 KVA inverter company (INVT).
- 2: magnetic contactor 30A amperes for compressor
- 3: Holding contactor.
- 4: blower contactor.
- 5: digital thermostat
- 6: fan contactor.
- 7: connection strip
- 8: push button.
- 9: Electric panel box size 12" x 24".

Indoor and outdoor manufacturing with all his accessories testing installation complete material and labor charges capacity (6.5 HP) brand new total cost.

Dimension:

~~Weight:~~

Power Load:

16. Cooling Conveyor 5 Stages with Elevator SEW-413

Traits:

The 5-stages round lollipop conveyer with elevator is designed for gradual cooling, hardening, and smooth transfer of formed lollipops before packaging. The multi-stage conveyer ensures uniform air circulation and progressive temperature reduction, preventing deformation or sticking of candies. The integrated elevator system provides continuous elevation between forming machine and cooling conveyer.

Spherical Lollipop Cooling Conveyer 5 stages, with elevator.

Specifications:

- 1st stage S.S Plate with pores for Aircross
- 2nd stage S.S Plate with pores for Aircross
- 3rd stage S.S Plate with pores for Aircross
- 4th stage S.S Plate with pores for Aircross
- 5th stage S.S Plate with pores for Aircross
- Gear motor main drive: 5 hp
- Inverter to control speeds: 5 hp
- Elevator for shifting the products from machine to conveyer
- Gear motor for Elevator drive: 1 hp
- • Elevator Fans: 2 NOS for cooling of product
- Food grade T belt in Elevator

Dimension: $H \times W \times L$
8ft x 11.5ft x 6.5ft

Weight:

Power Load: 6hp

17. Wrapping Machine SEW-414

Trait:

The single-twist wrapping machine is designed to individually wrap round lollipops in a tight, hygienic single-twist film seal. Its purpose is to ensure product protection, maintain shelf life, and provide a uniform retail-grade presentation. The machine aligns, feeds, and wraps each lollipop at ~~low~~ speed, preventing contamination, reducing manual handling and ensuring consistent packaging quality before final packing.

Specification:

- Production speed: 110–130 Pcs/Min (based on standard lollipop shape)
- PLC control
- Motor: 2 hp
- Brush Motor: ³ ~~1~~ x 0.5 hp
- Electric heater: 0.15 KWx6
- Main drive inverter: 2 hp
- Servo Motor : by Yahya sb

~~6.5A x 1.5A x 1.5A~~
Dimensions (H x W x L): ~~2500 mm x 920 mm x 1520 mm~~

H x W x L : 2500mm x 920mm x 1520

~~Power Load:~~
Power Load: ~~4000W~~