

lollipop complete line 450kg/hr

BOOKLET FOR COMPLETE PRODUCT LINES

(New)



Starmers
Engineering Works

LOLLIPOP COMPLETE LINE 450KG/HOUR

- 1.GLUCOSE TANK SEW-101**
- 2.STEAM GENERATOR SEW-102**
- 3.STEAM HEADLER SEW-103**
- 4.CANDY CONTINUOUS COOKER SEW-104**
- 5.VACUUM PUMP SEW-105**
- 6.DISSOLVING TANK SEW-106**
- 7.STORAGE TANK SEW-107**
- 8.COOLING TABLE SEW-108**
- 9.KNEADING MACHINE SEW-109**
- 10.BUBBLE GUM MIXER SEW-112**
- 11.EXTRUDER SEW-113**
- 12.BATCH ROLLER SEW-114**
- 13.ROPE SIZER SEW-212**
- 14.LOLLIPOP FORMING MACHINE SEW-314**
- 15.LOLLIPOP HIGH SPEED DIE SEW-315**
- 16.DIE STAND SEW-118**
- 17.COOLING CONVEYER SEW-317**
- 18.AC UNIT SEW-318**
- 19.WRAPPING MACHINE SEW-320**

1. GLUCOSE TANK SEW-101 ✓

Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, Stable and ✓
crystal free storage of liquid glucose and Syrups for industrial applications. ✓

Specifications:

Size:	14 ft height x 7.5 ft diameter (approximate).
Grade:	S.S 304 ✓
Sheet thickness:	5 mm upper and lower sheet ✓
Outer dia sheet thickness:	3 mm ✓
Design Type:	Vertical ✓
Heating System:	Coil on the base of tank ✓
Ladder:	Outside the tank ✓
Capacity:	20 ton glucose

Dimension: 16 ft height x 7 ft diameter

~~Weight:~~

Power load: 0

2. STEAM GENERATOR SEW-102

Trait:

Steam generator heats water to produce high Pressure steam for heating, cleaning or industrial processes. ✓

Detail of Mechanical Parts:

- | | |
|--|------|
| 1. Gauge Glass Pressure = | 01 ✓ |
| 2. Stop Valve diameter 1-1/2" = | 01 ✓ |
| 3. Safety Valve diameter 1 1/2" = | 01 ✓ |
| 4. NRV diameter 1" Pressure = | 01 ✓ |
| 5. Blow down diameter 1" = | 01 ✓ |
| 6. Air Vent diameter 1/2" globe Valve = | 01 ✓ |
| 7. Feed Water Pump 01 Multistage (Grundfos)= | 01 ✓ |
| 8. Electric panel Box with complete auto controlled system = | 01 ✓ |
| 9. Stack diameter 15" height 20 ft. thick 2.5 mm = | 01 ✓ |

Detail of Electric Parts:

- | | |
|--|--------|
| 1. Burner with gas assembly ^{Or} diesel pump | |
| 2. Panel Box 18" x 30" x 8" thick 18 gauge | |
| 3. Overload company Schneider ^{Schneider} | = 02 ✓ |
| 4. Pressure switch 10 kg imported | = 02 ✓ |
| 6. Loading and unloading Responsibility of Client | |
| 6. Electric Contactor | = 02 ✓ |
| 7. Power relay company (Finder) | = 04 ✓ |
| 8. Push ^{button} button company (Telemechanic) | = 03 ✓ |

Specifications:

Type of passes:	3 pass ✓
Test pressure:	225 psi ✓
Working pressure:	150 psi ✓
Tube Dia:	2" or 2 1/2" ✓
Pressure Shell thickness:	1/2" ✓
Tube sheet thick:	1/2" ✓
Rock wool thickness	2" ✓
Insulation Insulation sheet thickness:	24 GAUGE ✓
Burner Motor:	2hp ✓

Feed water Motor

3hp

Capacity: ¹⁵⁰⁰~~1200~~ kg/hr ✓

Electric Load: ^{5hp}~~6hp~~ ✓

Dimension: 8'x3'5"x3'5" ✓

Weight:

Power Load:

3. STEAM HEADLER SEW-103 ✓

Trait: ✓

Steam headers are design to collect steam from a boiler or steam generator and distribute high-quality, dry steam to various user points while performing several critical functions. ✓

Specifications:

- Material of header = M.S ✓
- Diameter = 1 ft ✓
- Branch pipes = 1", 2", 3", 4 "depend on system needs ✓
- Design = Cushioned Cylinder ✓
- Connection = 5 ✓

Dimension: Dia 1ft x length 3ft

Weight:

Power load: ○

4. CANDY CONTINUOUS COOKER SEW-104 ✓

Trait:

The candy continuous vacuum cooker automatically produces hard-boiled candies and milk caramels with high clarity and smooth texture. It minimizes sugar loss and maintains consistent quality, even with moisture levels below 1%. ✓✓✓

Operating parameters such as output vacuum, temperature, cooking time, and batch weight are adjustable. Once set, the system runs automatically and continuously with low operating cost. ✓

Specifications:

- Electric Pannel ✓
- 450 kg per hour ✓
- Pans in S.S 304 ✓
- Body in S.S 304 ✓
- Electric panel with all new features ✓
- Body Double jacketed (S.S 304) ✓
- Output 450 kg/hr ✓
- Dozing pump 3 hp (imported used) ✓
- For sugar pump 2 hp 1450 rpm ✓
- Pan 2 nos in S.S 304 food grade ✓
- Batch Auto control
- Steam guage
- Safety valve
- Seat valve

Dimension:

H x W x L

8.5ft x 6ft x 7ft

Power Load: 4hp

5. Vacuum Pump SEW-105

Trait:

The vacuum pump is used to rapidly remove moisture (Water vapor) from the cooked candy mass under reduced pressure, which allows lower temperature boiling and prevents caramelization or burning of sugars.

Specification:

For vacuum pump ^{10hp} ~~7.5~~ hp=1450 rpm
Frame = M.S

Dimension:

Weight:

Power Load:

^{10hp} ~~7.5~~

~~14x14x14~~
~~24x14~~

~~Handwritten~~

HXLXW

2ft x 4ft x 1ft

Approved by ^{H.H.} ~~Handwritten~~
4/12/24

6. DISSOLVING TANK SEW-106

Trait:

The dissolving tank is an essential unit in the candy manufacturing process designed for the controlled dissolution of sugar, glucose syrup, and other ingredients in water to form a homogeneous sugar solution or slurry. ✓

Specifications:

- 400kg capacity ✓
- Double jacketed with MS ✓
- Body in S.S 304 ✓
- Legs in M.S ✓
- Stirrer in S.S 304 ✓
- Gear motor main drive 2hp ✓
- Steam gauge
- safety valve
- Seat valve

Dimension: 5'6" x 3'5" x 3'5"

H x W x L

Weight:

Power Load: 2hp

7.STORAGE TANK SEW-107 ✓

Trait:

The storage tank is designed to hold and maintain cooked sugar mass or syrup at a controlled temperature before feeding it into the forming or depositing section of the candy line. ✓

Specifications:

- 400kg capacity ✓
- single jacketed ✓
- Body in S.S 304 ✓
- Legs in M.S ✓
- Stirrer in S.S 304 ✓
- Gear motor main drive 1hp ✓

Dimension: ^{H W L} 6'x3'6"x3'6" ✓

~~Weight:~~

Power Load: 1hp ✓

8.COOLING TABLE SEW-108

Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch.

Specifications

- Base plate thickness: 10mm in S.S 304 ✓
- Material of plate: Boundry wall S.S 304 ✓
- Cooling medium water: Cooling system A frame work for moving water Inlet and outlet ✓
Valve ~~6~~ Legs 4 Nos in S.S 201 grade ✓
- legs 4 Nos in S.S 201 grade

W x L x H
Dimension: 3ft x 6ft x 2'6" ✓

~~✓~~

Power Load: ①

9.KNEADING MACHINE SEW-109

Trait:

The rotary kneading machine (SEW-109) is a specialized piece of confectionery equipment perfectly suited for the uniform mixing and kneading of the cooked sugar mass used in producing hard-boiled candy. ✓

Its primary function is to guarantee the uniform distribution of essential ingredients, including solids, acids, and any other additives, ensuring a consistent and high-quality final product. ✓

To maintain food safety standards, the machine operates in a hygienic way, utilizing stainless steel for all contact parts, which are also efficiently water-cooled to manage the high temperatures of the candy mass during the kneading process. ✓

This machine eliminates the need for tiresome and exhausting manual mixing and saves on the labor costs. ✓

Specifications:

- Roller ⁱⁿ S.S 304 ✓
- Main drive 5hp ✓
- Steel plate 4ft ✓
- Switch on / off ✓
- Side sheets in S.S 201 ✓
- Main plate in S.S 304 ✓

Dimension: ^{H x W x L} 5'x5'6"x5'6" ✓

~~Weight:~~

Power Load: 5hp

10. BUBBLE GUM MIXER SEW-112

Traits:

The bubble gum mixer is used to blend all the raw ingredients into a homogeneous gum base mass suitable for further processing (like extrusion and shaping).

Specification:

1. Capacity: 100 kg in 20 min ✓
2. Pan: In S.S 304 ✓
3. Double jacketed ✓
4. Double jacketed with ^{M.S} 304 ✓
5. Z-arm: S.S 304 ✓
6. Pan cover: In S.S 304 ✓
7. Gear motor main drive: 20 hp ✓
8. Heavy duty: M.S structure ✓
9. Electric heaters 6000 watt ✓
10. Electric panel with all new features ✓
- ~~11. Weight: 2 ton approx~~ ✓
12. Side sheets: S.S 204 ✓
13. Tilting system ✓

11 x W x L
Dimension: (6' x 8' x 8')

Weight:

Power Load: 28hp

11. EXTRUDER SEW-113

Traits:

The bubble gum extruder shapes the mixed gum mass into a continuous rope or sheet with uniform thickness, texture, and density—making it suitable for further forming (cutting, rolling, or shaping). ✓

It essentially transforms the soft, irregular gum from the mixer into a consistent product form for downstream processing. ✓

Specifications:

1. 1 rope ✓
2. 2 Worms ✓
3. 7.5 hp gear motor drive ✓
4. 10 hp inverter ✓
5. M.S structure ✓
6. keef in S.S 304 ✓
7. Electric heaters 6000 watt ✓
8. Electric panel with all new features ✓
9. Helping roller system in keef ✓

Dimension:

Weight:

Power Load: 18hp

12.BATCH ROLLER SEW-114

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffe, fudge production line designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavour, and color before feeding into the rope sizer or forming machine.

Specifications:

- Frame work horizontal ✓
- Rollers Quantity 4 ✓
- Rollers material in S.S 304 food grade ✓
- Upper body in S.S 304 food grade ✓
- Bearing in gears ✓
- Gear motor main drive 1hp ✓
- Up and down drive 1hp ✓
- ~~drive 2 hp~~
- ~~Electric panel for control~~
- Electric heaters to maintain temperature 1000 watt (2 NOS) ✓
- Capacity 75 kg ✓
- Length 6.5 ft ✓
- Gear motor SEW brand Germany ✓
- Roller caplene in casting material ✓
- Additional tray for removal of wastage ✓

Dimension: $H \times W \times L$
4'6" x 2'2" x 7' ✓

~~Weight~~:

Power Load: 4.684p

13. ROPE SIZER SEW-212

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

Specifications:

- Horizontal model ✓
- 5 stages (4 stages horizontal & 1 vertical) ✓
- 1st pair in S.S 304 37mm ✓
- 2nd pair in S.S 304 32mm
- 3rd pair in S.S 304 27mm
- 4th pair in S.S 304 22mm
- 5th pair in S.S 304 17mm
- Electric panel in S.S 201 ✓
- Sizer plates in S.S 304 ✓
- Side plates sheets S.S 201 ✓
- Rope guide in brass ✓
- Electric inverter new brand INVENT company = 3HP ✓
- Gear motors are of SEW brand Germany : 3Hp ✓
- Heat controllers 2 Nos ✓
- Emergency break to stop equipment ✓
- Emergency switch to off equipment ✓
- Electric breakers ✓
- Electric components brand new ✓
- Electric heaters 2kW $500 \times 4 = 2kW$

Dimension: $H \times W \times L$
4'6" x 3' x 5'6" ✓

Weight:

Power Load: 5.68hp

14.LOLLIPOP FORMING MACHINE SEW-314

Trait:

This Round lollipop Forming machine is a mechanical confectionery -shaping Unit designed to convert continuously rope sized sugar mass into uniform Round (spherical) lollipops. Operating at speeds up to 500-600 (Based on the size of lollipop) Pieces per minute with a stick inserted. It functions as the core forming stage within an integrated lollipop production line.

Specifications:

- Lollipop diameter:17mm-34mm
- Speed: 500-600 pcs/min
- Main power: 3KW
- Capacity: 500 kg/hour (Based on S ø 25 spherical lollipops).
- Gross weight: 1500 KG

~~Dimension: 1350 x 1050 x 1700 MM~~

~~Weight:~~

Power Load: 4.02hp

H x W x L
1600mm x 1050mm x 1350mm

15.LOLLIPOP HIGH SPEED DIE SEW-315

Traits:

High speed Round lollipop Die is a precision machined forming component mounted within the lollipop forming machine. Its primary purpose is to shape, compress and dimensionally stabilize the candy mass into uniform round lollipop heads and mechanically secure the stick within the candy body during continuous high speed production.

Size: 16 -34 mm

Shape: Round

Material Specifications:

- Cutting Ring: Cutting Ring in grade forged M.S. This grade provides cutter pitch (teeth) of 1.5 - 2.5 mm
- Punch: Punch in grade 1045, Hardness up to 45 HRC
- Block: High Quality M.S
- Guide Pins: Guide Pins in grade Carbon Steel
- Die Parts: Casting in grade Cast Iron

Durability:

- The finest quality raw material used
- Our 55years of experience have garnered the Forming dies into a piece of perfection, even with continuous production, the die-set does not damage easily.

Dimension:

~~Weight:~~

Power Load:



16.DIE STAND SEW-118

Trait:

It's main purpose is to make die changing and fitting easier and more efficient.

Specification:

- Main Frame in M.S
- Wheels for movement
- Die Caplone in casting Material
- Screw for die up/down

Dimension:

Weight:

Power Load:



5 stages with Elevator

17.COOLING CONVEYER, SEW-317

Traits:

The 5-stages round lollipop conveyer with elevator is designed for gradual cooling, hardening, and smooth transfer of formed lollipops before packaging. The multi-stage conveyer ensures uniform air circulation and progressive temperature reduction, preventing deformation or sticking of candies. The integrated elevator system provides continuous elevation between forming machine and cooling conveyer.

Spherical Lollipop Cooling Conveyer 5 stages, with elevator.

Specifications:

- 1st stage S.S Plate with pores for Aircross
- 2nd stage S.S Plate with pores for Aircross
- 3rd stage S.S Plate with pores for Aircross
- 4th stage S.S Plate with pores for Aircross
- 5th stage S.S Plate with pores for Aircross
- Gear motor main drive: 5 hp
- Inverter to control speeds: 5 hp
- Elevator for shifting the products from machine to conveyer
- Gear motor for Elevator drive: 1 hp
- • Elevator Fans: 2 NOS for cooling of product
- Food grade T belt in Elevator

Dimension: H x L x W
8ft x 11.5ft x 6.5ft

~~Weight~~

Power Load: 6 hp

18.AC UNIT SEW-318

Specification of AC Unit 5 Ton (6.5 HP):

Indoor Unit capacity 5 Ton (6.5 HP) floor standing type for cooling conveyor Accessories indoor:

- 1. Evaporator brand new copper tube size 3/8 gage 22 distributor size 1/2 section header 7/8.**
- 2. Aluminum fins thickness 0.150mm company Breez.**
- 3. High-velocity air blower With 1 HP motor 3 phase 440/v Hz 50.**
- 4. Expansion valve company Emerson model TCLE 6.5 HP.**
- 5. Base frame angle iron sizes are on customer demand.**
- 6. Indoor frame cover sheet GI colored 22 gage.**
- 7. Indoor frame cover sheet insulation with isolated material.**
- 8. Indoor copper pipe fitting 18 gauge length tube.**

6.5 HP OUTDOOR Company Bitzer with all his ACCESSORIES:

- 1. Condensing unit Company Bitzer with high-density condensing coil.**
- 2. High static air flow fan 3 phase 440/v Hz 50.**
- 3. Compressor Copeland scroll capacity 6.5 HP 3 phase 440/v Hz 50.**
- 4. Liquid receiver capacity 5 liter.**
- 5. Oil spreader in/out pipe size 7/8.**
- 6. Hand valve 1/2.**
- 7. Filter 1/2.**
- 8. Copper length 1/2 and 5/8.**
- 9. Section accumulator 7/8**
- 10. Copper long bend 5/8 and 7/8 and 3/8 elbow.**
- 11. Dual high low-pressure safety switch company Danfoss with high-pressure leads.**
- 12. Outdoor base frame channel and angle iron.**

13. Refrigerant R-22 company (Honeywell USA).

ELECTRIC PANEL equipment:

1. 1.7.5 KVA inverter company (INVT).

2. Magnetic contactor 30A amperes for compressor

3. Holding contactor.

4. Blower contactor.

5. Digital thermostat

Dimension:

Weight:

Power Load: