

BOOKLET FOR COMPLETE PRODUCT LINE



Starmmer
Engineering Works

COMPLETE PHARMA (Lozenges) 450 KG / HR

- 1. Glucose Tank SEW-101**
- 2. Steam Generator SEW- 102**
- 3. Steam Header SEW-103**
- 4. Candy Continuous Vacuum Cooker SEW-104**
- 5. Vacuum Pump SEW-105**
- 6. Dissolving Tank SEW-106**
- 7. Storage Tank SEW-107**
- 8. Cooling Table SEW-108**
- 9. Kneading Machine SEW-109**
- 10. Centre Filling Pump Liquid SEW-110**
- 11. Batch Roller SEW-114**
- 12. Rope Sizer 4 Stages SEW-115**
- 13. Uniplast SEW-116 A**
- 14. Rotary Forming Die with cutting Rings SW 112 V**
- 15. Die Stand SEW-118**
- 16. Cooling Conveyor Open Body SEW-119 V**
- 17. Vibrator SEW-120**
- 18. Close Body Cooling Tunnel SEW-121**
- 19. AC Unit 5 Ton SEW-122**
- 20. Wrapping Machine SEW-123**

1. Glucose Tank SEW-101

Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, stable and crystal free

storage of liquid glucose and Syrups for industrial applications.

Specifications:

- * Grade: S.S 304**
- * Sheet thickness: 5 mm upper and lower sheet**
- * Outer dia sheet thickness: 3 mm**
- * Design Type: Vertical**
- * Heating System: Coil on the base of tank for Steam Circulation**
- * Ladder: Outside the tank**
- * Capacity: 20 ton Glucose**
- * Dimension: 16ft height x 7ft diameter**
- * Power load: 0**

2. Steam Generator SEW- 102

Trait:

Steam generator heats water to produce high Pressure steam for heating, cleaning or industrial processes.

Detail of Mechanical Parts:

- 1. Gauge Glass:01**
- 2. Stop Valve diameter 1-1/2": 01**
- 3. Safety Valve diameter 1 1/2": 01**
- 4. NRV diameter 1": 01**
- 5. Blow down diameter 1": 01**
- 6. Air Vent diameter 1/2" globe Valve : 01**
- 7. Feed Water Pump 01 Multistage (Grundfos): 01**
- 8. Electric panel Box with complete auto controlled system: 01**
- 9. Stack diameter 15" height 20 ft thick 2.5 mm: 01**

Detail of Electric Parts:

- 1. Burner with gas assembly and diesel pump**
- 2. Panel Box 16" x 30" x 8" thick 18 guage**
- 3. Overload company Schneider: 02**
- 4. Pressure switch 10 kg imported: 02**
- 5. Electric Contactor: 02**
- 6. Power relay company (Finder): 04**
- 7. Push button company (Telemechanic): 03**
- 8. Loading and Unloading Responsibility of Client**

Specifications:

- * Type of passes: 3 pass**
- * Test pressure: 225 psi**

- * Working pressure: 150 psi
- * Tube Dia: 2" or 2 1/2"
- * Pressure Shell thickness:
- * Tube sheet thick: 1/2"
- * Rock wool thickness: 2"
- * Insolation sheet thickness: 24 GUAGE
- * Burner Motor: 2hp
- * Feed water motor: 3hp

General Details:

- * Capacity: 1500 kg/hr
- * Electric Load: 5 hp
- * Dimension: 8' x 3'5" x 3'5"

3. Steam Header SEW-103

Trait:

Steam headers are design to collect steam from a boiler or steam generator and distribute highquality,

dry steam to various user points while performing several critical functions.

Specifications:

- * Material of header: M.S**
- * Diameter: 1 ft**
- * Branch pipes: 1", 2", 3", 4" depend on system needs**
- * Design: Cushioned Cylinder**
- * Connection: 5**
- * Dimension: Dia 1ft x Length 3ft**
- * Power load: 0**

4. Candy Continuous Vacuum Cooker SEW-104

Trait:

The candy continuous vacuum cooker automatically produces hard-boiled candies and milk caramels with high clarity and smooth texture. It minimizes sugar loss and maintains consistent quality, even with moisture levels below 1%.

Operating parameters such as output vacuum, temperature, cooking time, and batch weight are adjustable. Once set, the system runs automatically and continuously with low operating cost.

Specifications:

- Electric Panel
- 450 kg per hour
- Pans in S.S 304
- Body in S.S 304
- Electric panel with all new features
- Body Double jacketed (S.S 304)
- Output 450 kg/hr
- Dozing pump 3 hp (imported used)
- For sugar pump 2 hp 1450 rpm
- Pan 2 nos in S.S 304 food grade
- Batch Auto Control
- Steam Gauge
- Safety Valve
- Sect Valve

Dimensions:

H \ W \ L

8.5ftx6ftx7ft

Power Load: 4 HP

5. Vacuum Pump SEW-105

Trait:

The vacuum pump is used to rapidly remove moisture (Water vapour) from the cooked candy mass under reduced pressure, which allows lower temperature boiling and prevents caramelization or burning of sugars.

Specification:

For vacuum pump 10 hp=1450 pm

Frame = M.S

Dimension= 2ftx4ftx1ft

Weight:

Power Load: 10 hp

6. Dissolving Tank SEW-106

Trait:

The dissolving tank is an essential unit in the candy manufacturing process designed for the controlled dissolution of sugar, glucose syrup, and other ingredients in water to form a homogeneous sugar solution or slurry.

Specifications:

- 400kg capacity
- Double jacketed with MS
- Body in ss 304
- Legs in M.S
- Stirrer in S.S 304
- Gear motor main drive 2hp
- Steam Gauge
- Safety valve
- * Scat valve

Dimension: 5'6"x 3'5"x 3'5"

Power Load: 2hp

7. Storage Tank SEW-107

Trait:

The storage tank is designed to hold and maintain cooked sugar mass or syrup at a controlled temperature before feeding it into the forming or depositing section of the candy line.

Specifications:

400kg capacity

single jacketed

Body in S.S 304

Legs in MS

Stirrer in S.S 304

Gear motor main drive 1hp

Dimension: 6'x3'6"×3'6"

Power Load: 1 hp

8. Cooling Table SEW-108

Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked

sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch.

Specifications

* Base plate thickness: 10mm in S.S 304

* Material of plate: Boundary wall S.S 304

* Cooling medium water: Cooling system A frame work for moving water Inlet and outlet Valve.

* Legs: 4 Nos in S.S 201 grade

Dimension: 3ft x 6ft x 2'6"

Power Load: 0

9. Kneading Machine SEW-109

Trait:

The rotary kneading machine (SEW-109) is a specialized piece of confectionery equipment perfectly suited for the uniform mixing and kneading of the cooked sugar mass used in producing hard-boiled candy.

Its primary function is to guarantee the uniform distribution of essential ingredients, including solids, acids, and any other additives, ensuring a consistent and high-quality final product.

To maintain food safety standards, the machine operates in a hygienic way, utilizing stainless steel for all contact parts, which are also efficiently water-cooled to manage the high temperatures of the candy mass during the kneading process.

This machine eliminates the need for tiresome and exhausting manual mixing and saves on the labor costs.

Specifications:

- Roller in s.s 304
- Main drive 5 hp
- Steel plate 4ft
- Switch on / off
- Side sheets in S.S 201
- Main plate in S.S 304

Dimension: 5'x5'6"x5'6"

Power Load: 5 hp

10. Center Filling Pump Liquid SEW-110

Trait:

The center filling pump is a precision dosing system designed to inject liquid filling (such as fruit syrup, chocolate, cream, or jam) into the core of the candy rope during the forming process. It ensures consistent filling quantity and uniform distribution across all candies.

Specifications:

- Filing chocolate and liquid
- keef in S.S 304
- keef double-jacketed
- Rod in S.S with Teflon covering food-grade heat proof material
- Pipe flexible food grade
- Electric panel with new feature
- Gear motor 2 hp main drive
- Stand in M.S
- Electric heater to moderate temperature 1000 watt 1 NOS
- Electric inverter 2HP to increase or decrease filling in product
- Overflow system to recycle liquid/Chocolate

Dimension:

HxWXL

Power Load: 3.34 hp

11. Batch Roller SEW-114

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffee, and fudge production line. It

is designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It

ensures consistent rope size and proper distribution of center filling, flavor, and color before feeding into

the rope sizer or forming machine.

Specifications:

- * Frame work horizontal**
- * Rollers Quantity 4**
- * Rollers material in S.S 304 food grade**
- * Upper body in S.S 304 food grade**
- * Bearing in gears**
- * Gear motor main drive 1hp**
- * Up and down drive 1hp**
- * Electric heaters to maintain temperature 1000 watt (2 NOS)**
- * Capacity 75 kg**
- * Length 6.5 ft**
- * Gear motor SEW brand Germany**
- * Roller caplene in casting material**
- * Additional tray for removal of wastage**

Dimensions (H x W x L): 4'6" x 2'2" x 7'

Power Load: 4.68hp

12. Rope Sizer 4 Stages SEW-115

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffe rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

Specifications:

- Horizontal model
- 4 stages
- 1st pair in S.S 304 32mm
- 2nd pair in S.S 304 27mm
- 3rd pair in S.S 304 22mm
- 4th pair in S.S 304 17mm
- Electric panel in S.S 201
- Side sheets in S.S 201
- Sizer plates in S.S 304
- Rope guide in brass
- Electric inverter new brand INVENT company =2hp
- Gear motors are of SEW brand Germany
- Heat controllers Digital 2 NOS
- Emergency break to stop equipment
- Emergency switch to off equipment
- Electric breakers
- Bearings are used instead of bushes to reduce maintenance of equipments
- Main Drive Gear Motor =2HP
- Heaters 500 Watt (4 NOS) = 2 Kw

Dimension:

HxWxL

4.3ftx 2.5ftx 6ft

Weight:

Power Load: 4•68 hp

13. Uniplast SEW-116 A

Trait:

- The SEW-4 has been designed for the continuous production of seamless sweets with or without center filling using a standard die arrangement.
- The machine can be used as a part of a complete production plant supplied by Starmer Engineering Works, or integrated into an existing line.
- Suitable for forming hard boiled candies, center liquid filled candies, center powder filled candies, toffees, chewy-toffee, chewy candies, chewing-gum & bubble gum products. It forms seamless sweets with high depth thickness.

Specifications:

- Main Drive: 5 hp motor
- Inverter: 5 hp inverter, new brand (INVENT Company)
- Production: Up to 450 Kg/hr
- Electric Panel: Equipped with all new features
- CAMS: Bearing steel grade
- Reverse Cams: S.G iron
- Gears: High carbon steel forged material
- Output Speed: 2500 to 3500 pieces/min depending upon size of product
- Filling: Up to 12% of the candy
- Dimension (H x W x L): 6.5 ft x 4.5 ft x 3.5 ft
- Power Load: 5 hp

14. Rotary Forming Die with cutting Rings SEW 112

Trait:

The heart of any candy production line is the rotary dies in the forming machine. They literally shape the product and add to its face value. The forming dies are used for the production of hard-boiled candies, Toffees, Eclairs, Powder-filled candies, liquid-filled candies, and more. Starmer Forming dies are recognized in the confectionery industry for their precision-based performance, safety, and functional efficiency.

Starmer machines are built for generational use, we offer a supply of spare parts and die-heads for models that may have been discontinued for decades. As the leading confectionery machinery manufacturer, Starmer aims to be your reliable long-term business partner, and offers the following benefits:

Accuracy:

- Perfectly formed, seamless candies
- Nearly any shape of candy can be made
- To ensure accuracy, we provide drawings, and product samples on request to help you visualize the sense of the product

Quality:

- The finest quality raw material used

Durability:

- Our 55+ years of experience have garnered the forming dies into a piece of perfection, even with continuous production, the die-set does not damage easily

Material specification:

- Cutting Ring: Cutting Ring in grade Forged M.S. This grade provides cutter pitch (teeth) of 2-3 mm.
- Punch: Punch in grade 1045, Hardness upto 45 Hrc
- Block: High Quality
- M.S. Guide Pins: Guide pins in grade Carbon Steel.
- Die Parts: Casting in grade Cast Iron.
- Outer Ring: Outer Ring in Brass Casting. For the improvement of rope cutting.

Dimension (H \ W \ L): 1ft x 1ft x 1'5"

Weight:

Power Load: 0

15. Die Stand SEW-118

Trait:

Its main purpose is to make die changing and fitting easier and more efficient.

Specification:

- **Main Frame (M.S)**
- **Movement: Equipped with wheels**
- **Die Caplene: Casting Material**
- **Adjustment: Screw for die up/down**
- **Dimension: 5.5ftx5ft**
- **Power Load: 0**

16. Cooling Conveyor Open Body SEW-119

Trait:

The open body cooling conveyor is an essential part at the post forming section in a candy production line. It's primary function is to cool and stabilize the hot candy mass after forming or rope sizing, before setting, wrapping or packaging.

SPECIFICATIONS:

- 18 feet long
- 3 steps
- With blower 3hp.
- 1st belt in Teflon 4-inch width.
- 2nd in mesh wire in SS 304 material-21 inch width.
- 3rd in mesh wire in SS 304 material=28 inch width.
- Gear motor 2 hp
- Variable inverter for speed control 2 hp
- Electric panel with all-new features
- Chain in M.S
- Sprockets in M.S
- Rods in S.S 304

Dimension:

H x W x L

X X 18ft

Power Load:

5hp

17. Vibrator SEW-120

Trait:

The vibrator helps smoothly transport candies from the cooling and forming sections to packaging, preventing clumping or sticking.

Specifications:

- **Frame: M.S**
- **Main sheet: S.S 304 (18 gauge)**
- **Fan: 2 nos**
- **Gear motor: 1 hp**
- **Trays: S.S 304 for removal of wastage (2 nos)**

Dimensions:

H x W x L

3.5 ft x 4.5 ft x 8 ft

Power Load:

1 hp

18. Close Body Cooling Tunnel SEW-121

Trait:

Its main purpose is to rapidly and uniformly reduce the temperature of freshly formed candy, ensuring dimensional stability, proper hardness, and surface quality before cutting, wrapping or packaging.

Specifications:

- 16ft long
- 3ft width
- With 5 ton AC
- 3 stages
- 1st step mesh wire in S.S 304 grade
- 2nd step mesh wire in S.S 304 grade
- 3rd step mesh wire in S.S 304 grade
- outer and inner Side sheets in S.S 201
- Electric panel with all new features
- Inverter new brand Invent (5hp)
- All covers in S.S 201
- Double jacketed insulates with thermopore
- Rods are in S.S 304 5mm thickness
- Chain in M.S 40 no
- Gear motor 3hp (1hp each 3 nos) SEW brand

Dimension: H \W \L

x3ftx16ft

Power Load: 3hp

19. AC Unit 5 Ton SEW-122

Description:

Indoor Unit capacity 5 Ton (6.5 HP) floor standing type for cooling conveyor Accessories indoor:

1: evaporator brand new copper tube size 3/8 gage 22 distributor size 1/2 section header 7/8.

2: aluminum fins thickness. 0.150mm company Breez.

3: High-velocity air blower With 1 HP motor 3 phase 440/v Hz 50.

4: expansion valve company Emerson model TCLE 6.5 HP.

5: Base frame angle iron sizes are on customer demand.

6: Indoor frame cover sheet GI colored 22 gage.

7: indoor frame cover sheet insulation with insulated material.

8: Indoor copper pipe fitting 18 gauge length tube.

6.5 HP OUTDOOR Company Bitzer with all his ACCESSORIES:

1: condensing unit Company Bitzer with high-density condensing coil.

2: High static air flow fan 3phase 440/v Hz50.

3: compressor Copeland scroll capacity 6.5 HP 3 phase 440/v Hz50.

4: Liquid receiver capacity 5 liter.

5: Oil spreader in/out pipe size 7/8.

6: Hand valve 1/2.

7: Filter 1/2.

8: Copper length 1/2 and 5/8.

9: section accumulator 7/8

10: Copper long bend 5/8 and 7/8 and 3/8 elbow.

11: dual high low-pressure safety switch company Danfoss with high-pressure leads.

12: Outdoor base frame channel and angle iron.

13: refrigerant R-22 company (Honeywell USA).

ELECTRIC PANEL equipment:

1: 7.5 KVA inverter company (INVT).

2: magnetic contactor 30A amperes for compressor

3: Holding contactor.

4: blower contactor.

5: digital thermostat

6: fan contactor.

7: connection strip

8: push button.

9: Electric panel box size 12" x 24".

Dimension:

Weight:

Power Load:

20. Wrapping Machine SEW-123

Trait:

This machine functions as a high-speed horizontal flow wrapping unit, responsible for accurately feeding, enclosing, heat-sealing, and cutting individual candies into uniform retail-ready packs, serving as the final primary packaging stage in a complete candy production line.

Specifications:

OUTPUT: Upto 800 Packs per Minute

- **ELECTRIC MOTORS:**
- **(1) 2 H.P./3-Phase**
- **(2) 1/2 H.P.**
- **ELECTRIC HEATERS: 3.2 Kw**
- **STANDARD EQUIPMENT: Photo Electric Eye & Inverter**
- **DIMENSIONS OF MACHINE (Length x Width x Height): 2,335 x 900 x 1,715 mm**
- **WEIGHT: 750 Kg.**
- **REEL (Maximum Outer Dia / Core Dia): 280 / 70 mm**

Dimension: H x W x L

1715 x 900 x 2335 mm

Power Load: