

Compiler	Tech.	Fabric	Workload	Cap (mW)	Freq. (MHz)	Power (mW)	ΔCap (%)	Success (orig 2× 4×)
RipTide	22FFL	6×6	FFT	0.30	50 25 12.5	0.24 0.12 0.06	20 60 80	Y Y Y
Snafu	22FFL	6×6	FFT	0.40	50 25 12.5	0.54 0.27 0.135	-35 32.5 66.25	N Y Y
UE-CGRA	28nm	8×8	FFT	5	750 325 162.5	14 7 3.5	-180 -40 30	N N Y
Plasticine	28nm	—	Inner Prod.	3000	280 140 70	18900 9450 4725	-530 -215 -57.5	N N N
Cascade	12nm	32×16	Inner Prod.	750	481 240.5 120.25	909.44 454.72 227.36	-21.26 39.37 69.69	N Y Y
Capstone I	16nm	32×16	Inner Prod.	750	294 147 73.5	510.24 255.12 127.56	31.97 65.98 82.99	Y Y Y
Capstone II	16nm	32×16	Inner Prod.	750	335 167.5 83.75	586.58 293.29 146.65	21.79 60.89 80.45	Y Y Y
Capstone III	16nm	32×16	Inner Prod.	750	366 183 91.5	645.57 322.78 161.39	13.92 56.96 78.48	Y Y Y
Cascade	12nm	32×16	SDDMM	1300	479 239.5 119.75	1488.56 744.28 372.14	-14.5 42.75 71.37	N Y Y
Capstone I	16nm	32×16	SDDMM	1300	310 155 77.5	893.98 446.99 223.5	31.23 65.62 82.81	Y Y Y
Capstone II	16nm	32×16	SDDMM	1300	346 173 86.5	1011.3 505.65 252.83	22.21 61.1 80.55	Y Y Y
Capstone III	16nm	32×16	SDDMM	1300	379 189.5 94.75	1121.44 560.72 280.36	13.74 56.87 78.43	Y Y Y