



EE-105

Arduino Installation

9/2/2025




What is Arduino?

- Microcontroller Development Board
- Open-source hardware + software.
- Simple programming with Arduino IDE.
- Used for rapid prototyping.

Why use Arduino?


- Low cost and widely available.
- Large community and libraries.
- Easy to connect sensors/actuators.
- Good entry point into embedded systems.



Different types of Arduino Boards



Arduino Nano 33 BLE



Installing the Arduino IDE




1. Connect the USB cable to Arduino
2. Download the latest release of the Arduino IDE here
<https://support.arduino.cc/hc/en-us/articles/360019833020-Download-and-install-Arduino-IDE>







1




2



3




1. Identify the COM port that Arduino is connected




2. Ensure that the Mbed OS Nano Boards package is installed



Tools -> Board: -> Boards Manager... -> Install "Arduino Mbed OS Nano Boards"





```
void setup() {  
    // initialize digital pin LED_BUILTIN as an  
    output.  
    pinMode(LED_BUILTIN, OUTPUT);  
}  
  
// the loop function runs over and over again  
forever  
void loop() {  
    digitalWrite(LED_BUILTIN, HIGH); // turn the  
    LED on (HIGH is the voltage level)  
    delay(1000); // wait for  
    a second  
    digitalWrite(LED_BUILTIN, LOW); // turn the  
    LED off by making the voltage LOW  
    delay(1000); // wait for  
    a second  
}
```




Another way of coding ➡

```
// Pin number for the built-in LED
const int ledPin = 13;

void setup() {
    // initialize digital pin 13 as an output.
    pinMode(ledPin, OUTPUT);
}

void loop() {
    digitalWrite(ledPin, HIGH); // turn the LED
on (HIGH is the voltage level)
    delay(1000);                // wait for a
second
    digitalWrite(ledPin, LOW);  // turn the LED
off by making the voltage LOW
    delay(1000);                // wait for a
second
}
```


Streaming Sensor Data to a Web App



1. Let's start using Arduino Cloud

https://cloud.arduino.cc/?gad_source=1&gbraid=0AAAAACbEa84ofzTu6ZqKTNrvcC00iYeOK&gclid=CjwKCAjwlbu2BhA3EiwA3yXyuyRs52Pa6IMOnlhxourjC6ZlovP8tXgo2qfPTzjIE3rKI_pymK4kmxoCDSMQAvD_BwE

2. You need to install Arduino Cloud Agent:


You need Arduino cloud agent to be able to detect or interact with your Arduino board, because web browsers don't have direct access to your computer's hardware.

<https://support.arduino.cc/hc/en-us/articles/360014869820-Install-the-Arduino-Create-Agent>

Bring your IoT projects to life quickly

Your next exciting journey to build, control and monitor your connected projects

GET STARTED FOR FREE SEE PLANS



Sketches → Create



ati213899
ati.abbasi722@gmail...

Home

Sketches

Devices

Things

Dashboards

Triggers

Templates

Resources

Courses

Integrations

Sketches

Search and filter Sketches

CREATE

☐	Name ↑	Device	Visibility	Last modified
☐	BLESense_dash_sketch_copy-1	Arduino Nano 33 BLE	Private	Aug 27, 2024, 9:49 PM
☐	BLESense_dash_sketch_copy-2	Arduino Nano 33 BLE	Private	Aug 28, 2024, 11:26 AM
☐	new_sketch_1724815259003	-	Private	Aug 27, 2024, 8:21 PM
☐	new_sketch_1724817574657	Arduino Nano 33 BLE	Private	Aug 27, 2024, 9:07 PM
☐	new_sketch_1724819128242	Arduino Nano 33 BLE	Private	Aug 27, 2024, 9:27 PM
☐	new_sketch_1724820689622	Arduino Nano 33 BLE	Private	Aug 27, 2024, 9:52 PM
☐	new_sketch_1724870192088	Arduino Nano 33 BLE	Private	Aug 28, 2024, 11:38 AM
☐	new_sketch_1724871339282	Arduino Nano 33 BLE	Private	Aug 28, 2024, 11:58 AM
☐	new_sketch_1724872033362	Arduino Nano 33 BLE	Private	Aug 28, 2024, 12:42 PM
☐	new_sketch_1724891254278	-	Private	Aug 28, 2024, 5:27 PM



✓ →

Arduino Nano 33 BLE

Serial Monitor

new_sketch_1724891555016

1

2

3

4

5

6

7

8

9

10

11

12

```
/*
 */
void setup() {
}

void loop() {
}
```

➤ Copy the Blink code into Arduino cloud and upload to verify that the cloud IDE is working.


How can we monitor the streamed data?




- Webapp link:
<https://arduino.github.io/ArduinoAI/BLESense-test-dashboard/>
- Upload this code to Arduino nano 33 ble to be able to stream the sensor data to a webapp
<https://app.arduino.cc/sketches/71cdba81-1380-4aee-9cb1-14cde2da7607?view-mode=preview>




1. After uploading the code, click on the green button



2. Now your Arduino BLE will pair with the web app



3. The sensor data is streaming to the web app




Using the Serial Monitor



- Testing pressure sensor

<https://app.arduino.cc/sketches/4573b54c-d240-41b0-94a4-4ac0dca97e66?view-mode=preview>

Your serial monitor output should look like this





The Arduino Nano 33 BLE is equipped with several built-in sensors, making it a powerful tool for various applications without needing additional hardware.

- **APDS9960**: Detects ambient light, color, proximity, and gestures.
- **LPS22HB**: Measures atmospheric pressure
- **LSM9DS1**: Tracks acceleration, rotation, and magnetic field orientation.
- **PDM Microphone**: Captures and analyzes sound signals.
- **RGB LED**: Provides visual feedback with controllable colors.



- **Color Detection:** The Colorimeter function in the web app is designed to detect and analyze the color of objects in the sensor's view. The APDS9960 sensor can measure the intensity of red, green, and blue light (RGB values) that is reflected from an object or present in the environment.
- **Proximity Sensor:** This sensor can detect objects within a certain distance, ranging from a few centimeters up to about 10 centimeters. It is commonly used in gesture control applications, where you can interact with devices without physical contact.
- **Gesture Detection:** The APDS9960 can recognize simple gestures like up, down, left, and right swipes. This feature enables touchless interaction with devices, such as controlling media playback or navigating menus with hand gestures.



- Accelerometer:** This sensor measures acceleration forces along the X, Y, and Z axes. It is used to detect movement, orientation, and vibration. Applications include motion tracking, tilt sensing, and detecting free fall in devices like smartphones and wearables.

- Gyroscope:** The gyroscope measures angular velocity (rotation) around the X, Y, and Z axes. It is used to detect and control the orientation of an object in 3D space. Common applications include stabilization in drones, gesture recognition, and gaming controllers.

- Microphone:** The PDM microphone captures audio signals by converting sound waves into electrical signals. The microphone's data is processed using an FFT (Fast Fourier Transform) to analyze the frequency components of the sound.

- Spectrogram is a visual representation of the spectrum of frequencies in a signal as it varies with time. In this case, the code is generating a spectrogram from audio data captured by a microphone, likely using the PDM (Pulse Density Modulation) microphone on the Arduino Nano 33 BLE Sense

Classwork 1



- Write a function in Arduino that can be used to change the frequency of LED blinking.
- Hint: This is how to define a function in the C programming language.

