

1  
2  
34     **The 2010 Census Confidentiality Protections Failed, Here's How and Why**

John M. Abowd<sup>†,\*</sup>, Tamara Adams<sup>‡</sup>, Robert Ashmead<sup>‡</sup>, David Darais<sup>◇</sup>,  
Sourya Dey<sup>◇</sup>, Simson L. Garfinkel<sup>△</sup>, Nathan Goldschlag<sup>‡</sup>, Daniel Kifer<sup>‡</sup>, Philip Leclerc<sup>‡</sup>,  
Ethan Lew<sup>◇</sup>, Scott Moore<sup>◇</sup>, Rolando A. Rodríguez<sup>‡</sup>, Ramy N. Tadros<sup>◇</sup>, Lars Vilhuber<sup>▽</sup>

5                             <sup>†</sup> Cornell University, U.S. Census Bureau (retired)  
                                      <sup>‡</sup> U.S. Census Bureau  
    <sup>◇</sup> Galois, Inc.  
    <sup>△</sup> BasisTech, formerly U.S. Census Bureau  
6                             <sup>▽</sup> Cornell University, formerly U.S. Census Bureau

ABSTRACT. Using only 34 published tables, we reconstruct five variables (census block, sex, age, race, and ethnicity) in the confidential 2010 Census person records. Using the 38-bin age variable tabulated at the census block level, at most 20.1% of reconstructed records can differ from their confidential source on even a single value for these five variables. Using only published data, an attacker can verify that all records in 70% of all census blocks (97 million people) are perfectly reconstructed. The tabular publications in Summary File 1 thus have prohibited disclosure risk similar to the unreleased confidential microdata. Reidentification studies confirm that an attacker can, within blocks with perfect reconstruction accuracy, correctly infer the actual census response on race and ethnicity for 3.4 million vulnerable population uniques (persons with nonmodal characteristics) with 95% accuracy, the same precision as the confidential data achieve and far greater than statistical baselines. The flaw in the 2010 Census framework was the assumption that aggregation prevented accurate microdata reconstruction, justifying weaker disclosure limitation methods than were applied to 2010 Census public microdata. The framework used for 2020 Census publications defends against attacks that are based on reconstruction, as we also demonstrate here. Finally, we show that alternatives to the 2020 Census Disclosure Avoidance System with similar accuracy (enhanced swapping) also fail to protect confidentiality, and those that partially defend against reconstruction attacks (incomplete suppression implementations) destroy the primary statutory use case: data for redistricting all legislatures in the country in compliance with the 1965 Voting Rights Act.

\*Corresponding author: john.abowd@cornell.edu

**Keywords:** statistical disclosure limitation, reconstruction attack, record linkage attack, differential privacy, swapping, suppression

#### MEDIA SUMMARY

The methods used to prevent disclosure of confidential information in the 2010 Census failed and could not be used for the 2020 Census necessitating rapid research and development of a new disclosure avoidance system for balancing privacy and utility. This paper also shows how the potential choices for the 2020 Census disclosure avoidance system—suppression, enhanced swapping, and differential privacy addressed the risks exposed by our reconstruction and reidentification studies. We included sufficient detail so that readers could review all data needed to judge this for themselves. It makes the paper longer, but it also shows that protecting vulnerable populations is not a matter of just “turning up the swap rate” or doing some suppression. You have to have a workable definition of “vulnerable populations,” which is what leave-one-out analysis provides. Then, you have to show that a comprehensive framework designed to protect all vulnerable populations works. The 2020 Census differential privacy framework succeeds. The other choices do not.

## 1. INTRODUCTION

Data products from the U.S. Decennial Census of Population and Housing are widely used for policy, research, and community planning including the allocation of approximately \$2.8 trillion in federal spending to state and local governments, nonprofits, businesses, and households (Villa Ross, 2023). In order to support these data uses, tens of billions of statistics are published, predominantly at the most granular level of geographic detail—the census block. With so many statistics published at such a fine geographic detail, an important question arises: “How accurately can a data user reconstruct the underlying confidential record-level data from the published tables?” Working against that accuracy are the confidentiality protections used in the 2010 Census publications. For the 1990, 2000 and 2010 Censuses, aggregation, age coarsening, noise infusion via targeted geographic identifier swapping, and, in 2010, partially synthetic data were used as the statistical disclosure limitation (SDL) framework to protect confidentiality (McKenna, 2018). We study the extent to which these SDL procedures limited the accuracy of reconstructed microdata and impeded reidentification. Hence, the related research question is: “To what extent data did aggregation and record swapping limit the accuracy of reconstruction?”

We reconstruct the underlying person-level records (called microdata) for the features (characteristics) labeled census block, sex, age, race, and ethnicity using only a small subset of publicly released tables. We match these reconstructed records to a low-quality commercial database acquired during the conduct of the 2010 Census containing personal identifiers and to a high-quality personal identifier database constructed from an extract of the 2010 Census data themselves. Our unique contributions to this literature are:

- the first demonstration supported by a national statistical agency that the reconstruction predicted by Dinur and Nissim (2003) is feasible at scale using its flagship publication;
- the complete empirical demonstration that using separate, incompatible, confidentiality protection frameworks for tabular and microdata publications fail if the tabular data are too detailed;
- the first mathematical proof requiring no access to confidential data that a large, identifiable subset of reconstructed records are the exact image of the underlying confidential records for the stated feature set;
- the first mathematical proof of an upper bound on the percentage of reconstructed records that can differ on no more than a single feature value from their confidential image on the stated feature set;
- the empirical demonstration that neither aggregation nor collapsing age into narrow bins prevents high-precision reidentification of census respondents from tabular data;
- the first empirical demonstration that reconstructed microdata succeed in reidentifying vulnerable individuals (those with characteristics that differ from the modal person in the relevant universe) with precision rates much higher than statistical baselines—racial and ethnic minorities in this work, but they could be other sensitive characteristics like occupancy-code violations, tribal identities, or same sex partners using other 2010 Census publications;
- the first research team to place the entire reconstruction workflow in the public domain, permitting others, including other statistical agencies, to assess the risk in the many similar products published by other data stewards;
- strong demonstration that the differential privacy framework used for the 2020 Census in its May 25, 2023 release defends against this attack at the parameter values used to produce the 2020 Census Demographic and Housing Characteristics File—successor to the

2010 Census Summary File 1, although there may attacks not yet discovered to which its algorithms remain vulnerable.

This paper also shows how the potential choices for the 2020 Census Disclosure Avoidance System—suppression, enhanced swapping, and differential privacy addressed the risks exposed by our reconstruction and reidentification studies. We included sufficient detail so that readers could review all data needed to judge this for themselves. It makes the paper longer, but it also shows that protecting vulnerable populations is not a matter of just “turning up the swap rate” or doing some suppression. You have to have a workable definition of “vulnerable populations,” which is what leave-one-out analysis provides. Then, you have to show that a comprehensive framework designed to protect all vulnerable populations works. The 2020 Census differential privacy framework succeeds. The other choices do not.

The 2020 Census Disclosure Avoidance System (DAS) took six years to develop, and the portion that produces the data comparable to the 2010 Census tables studied in this paper was finalized in November 2022. Experimentation with alternatives to the 2010 SDL framework began in 2016. The decision in 2018 to use a differentially private framework for the DAS was based exclusively on reconstruction results available at that time (Abowd, 2018); however, continuous research confirmed that reconstruction risk does imply privacy-violating reidentification risk. Our contributions are timely because traditional disclosure limitation experts continue to dispute the efficacy of reconstruction-based attacks (Muralidhar, 2022; Muralidhar & Domingo-Ferrer, 2023) using incomplete formulations of the problem, and domain experts continue to assert that the methods are no better than guessing (Francis, 2022; Ruggles & Van Riper, 2022) or ineffective (Kenny et al., 2021). Many of these critiques are addressed directly in Jarmin et al. (2023) and Garfinkel (2023). However, the analysis of how to properly assess the disclosure risk associated with publishing massive tabulations from a single confidential input continues to focus on methods with the same flaws that our experimental attack exploits (Hotz et al., 2022). Every major textbook or review article on SDL (Duncan et al., 2011; Elliot & Domingo-Ferrer, 2018; Hundepool et al., 2012; Willenborg & de Waal, 2000) recommends using distinct methods for tabular and microdata publications. However, the format of the data publication is immaterial because, as we show in this paper, tabulations can be converted into microdata. The use of weaker SDL standards for tabulations as compared to microdata is precisely the flaw that our attack exploits and the recommendation that our research challenges.

Section 2 elaborates the legal, ethical, and statistical confidentiality requirements that the Census Bureau's SDL is meant to implement. Section 3 lays out the complete schematic workflow of our research, describes all input data sources, and provides a reference table that shows the feature sets (characteristics or variables) of every input and output dataset used in this research. Section 4 details the complete reconstruction methodology and explains how to use the integer programs in the replication archive to perform reconstruction on the same public data. Section 5 describes the algorithms used to match data sets in order to assess reconstruction agreement and reidentification risk. Section 6 assesses the solution variability of our reconstructed microdata. Section 7 demonstrates the strong agreement of our reconstructed microdata with the confidential data. Section 8 assesses the reidentification risk of the reconstructed microdata focusing on the accuracy of inferences for vulnerable populations—those whose characteristics differ from the modal person in the relevant universe. Section 9 demonstrates that the SDL used for the 2010 Census did not meet the Census Bureau's stated standards for that census. Section 10 demonstrates that the differentially private framework used for the 2020 Census successfully addresses the failures of the methods used in 2010. Section 11 concludes.

## 2. LEGAL, ETHICAL AND STATISTICAL CONFIDENTIALITY REQUIREMENTS

It is fundamentally important to address the confidentiality breaches arising from the inconsistency in the SDL methods that were used for past U.S. decennial censuses and many other publications. For the 1990, 2000, and 2010 Censuses, the primary SDL framework was household-level record swapping (McKenna, 2018). Once the record swapping was implemented, there were separate, additional requirements for confidentiality protection of tabular summaries (McKenna, 2018) and microdata (McKenna, 2019a). For tabular summaries, publications used the universe of records (no sampling), created tables down to the census block level, and used detailed schemas for demographic variables. Tabular summaries in the 2010 Census imposed no minimum population or household counts on any tables in the main release—the 2010 Summary File 1 (SF1) (U.S. Census Bureau, 2012). In contrast, the public-use microdata sample required sampling, minimum population in a geographic area of at least 100,000 persons, and minimum national population in one-way marginals for demographic variables of at least 10,000 persons (McKenna, 2019a). These requirements are inconsistent if the published tabular data can be used to reconstruct an accurate image of the underlying confidential microdata record that includes a geographic identifier with no minimum population, has a record for every person in the census, and includes demographic information for groups with national populations as small as one.

If an accurate reconstruction of the record-level data is possible from tabular summaries, then the rules adopted for the 2010 Census disclosure avoidance, noted in the paragraph above, would require sampling to introduce deliberate sampling error, the suppression of most census block-level data even if the aforementioned 100,000 population threshold were significantly relaxed, and the suppression or aggregation of many race categories even if the population threshold of 10,000 were significantly relaxed. Thus, the application of technology used in the 2010 Census to the 2020 Census data would have resulted in substantial data loss compared to modern methods based on the differential privacy framework.

Furthermore, if an accurate reconstruction of the record-level data is possible from the tabular summaries, it makes the published 2010 Census data susceptible to a reconstruction-abetted reidentification attack in which an attacker reconstructs all or parts of the record-level confidential database from the publicly available information and combines these reconstructed records with an external source of person-level or household-level data containing personal identifiers, thus potentially reidentifying the respondent or another person in the household and learning response data associated with that person. This is a traditional attack vector that has been recognized by statistical agencies (Harris-Kojetin et al., 2005; McKenna, 2019b), the National Institute for Standards and Technology (Garfinkel et al., 2023), and general researchers (Dick et al., 2023; Rocher et al., 2019). When there is sufficient detail in the reconstructed records and there are enough common variables in the reconstructed and external microdata, the attacker may infer previously unknown person or household-level attributes from the reconstructed database with high accuracy, thus associating these characteristics with the individuals or households in their external dataset. Using census data to learn specific responses supplied by identifiable individuals is a prohibited, nonstatistical use as defined in the controlling statutes.<sup>1</sup> It is the obligation of statistical agencies to prevent or impede such uses.

---

<sup>1</sup>Within the U.S., federal policy on statistical and nonstatistical uses is governed by Statistical Policy Directive 1, now codified in the Confidential Information Protection and Statistical Efficiency Act of 2018 in 44 U.S. Code §§ 3561-4, in particular, the definitions in 3561(8) of “nonstatistical purpose” and (12) “statistical purpose.” For the Census Bureau such prohibited uses are also codified in The Census Act of 1954 (as amended) in 13 U.S. Code §§ 8(b) & 9, See Section 2.1.

155 In order to understand what we mean by a prohibited, nonstatistical inference, we must also  
 156 be clear about an allowable statistical or generalizable inference. The most straightforward way  
 157 to do this is by using concepts from robust statistics, specifically leave-one-out (LOO) estimation  
 158 and inference (Wasserman, 2010). Inferences about personal characteristics consist of associating  
 159 an attribute measured in a survey or census with a particular individual. When such inferences  
 160 are based on estimators that exclude only the individual under study, they are called LOO infer-  
 161 ences. LOO inferences cannot be privacy violations in our analysis because they cannot depend on  
 162 the particular individual’s confidential data—it was not used in the calculation. This connection  
 163 between robust inference and privacy analysis was first noticed by Dwork and Lei (2009), and it is  
 164 now well-accepted in social science, statistics and computer science. It is a form of causal inference  
 165 in the sense of Imbens and Rubin (2015) that has also been applied to confidentiality protection in  
 166 machine learning (Ye et al., 2023).

167 LOO inference is, by construction, generalizable scientific inference. Non-LOO inference is a  
 168 privacy violation if it is too precise. The difference in precision between LOO inferences and  
 169 inferences based on estimators that include the particular individual’s data measures the extent  
 170 to which the individual’s data caused the inference that associates the feature value with the  
 171 identifiable person. Therefore, when the difference in precision between the LOO inference and  
 172 the non-LOO inference is large, there is a strong presumption that the non-LOO inference is a  
 173 confidentiality violation because the gain in precision from the non-LOO inference is provably due  
 174 to the presence of data about the individual under study in the estimator used to make the inference.  
 175 Put directly, the analyst’s precision gain was caused (again, in the sense of Imbens and Rubin, 2015)  
 176 by the use of data supplied by that person. In this paper we evaluate the efficacy of our attack  
 177 by focusing on situations where the data strongly suggest that inferences based on the published  
 178 2010 Census data are much more precise than LOO inferences would be. That is, in the language  
 179 of causal inference, the observed outcome is a statistic officially published from 2010 Census data  
 180 and the counterfactual outcome is an approximation of the same statistic published after deleting  
 181 that individual’s record from the input data.

182 We present an example here that foreshadows the results of our study. Suppose a user of published  
 183 census data wishes to learn the racial and ethnic makeup of each individual in a small neighborhood,  
 184 for example, a census block. The census block contains 12 non-Hispanic Whites, 5 non-Hispanic  
 185 Blacks, 1 non-Hispanic Asian, 1 Hispanic White and 1 Hispanic Black. The analyst also has other  
 186 census block-level information on age and sex sufficient to perform the reconstruction studied in  
 187 this paper. For each individual, the analyst might guess “non-Hispanic White” (the modal value) or  
 188 guess in proportion to the observed frequencies. Other forecast models are feasible (e.g., guess each  
 189 of the 126 possible race and ethnicity values used in the schema for the 2010 Census with probability  
 190  $1/126$  or guess using a model that combines data at different levels of geography), but this example  
 191 is unchanged if such models are used. The modal or proportional block-level forecast may be a  
 192 statistical or generalizable inference, which is permitted by the legislation and ethical standards  
 193 governing statistical agencies.<sup>2</sup> Now suppose the user independently knows the name, sex and age  
 194 of each person in this block. The same user takes published tables from the census and creates 20  
 195 records with values of sex, age, race, and ethnicity that are consistent with the information in the  
 196 block-level tables (and possibly tract- and county-level tables containing this block). The user then

---

<sup>2</sup>Formally, whether such an inference is statistical or nonstatistical depends on how much other data are also released about the same individuals. As the rest of the example makes clear, the ensemble of published data can enable nonstatistical inferences even in cases where the use of block-level race and ethnicity data by themselves might not.

197 associates the race and ethnicity from these reconstructed census records with the 20 persons in  
198 the block by matching on sex and age. Now that user has name, sex, age, race, and ethnicity for  
199 every person on the block, coded consistently with the schemas used in the published tables.

200 One measure of the data user's gain from the reconstructed microdata relative to having only  
201 the race by ethnicity counts for the census block is the increased precision of the race and ethnicity  
202 forecast for each person compared to the precision possible if no data for that person were used  
203 in the published census results. Deleting the record of a non-Hispanic White, in this case, has  
204 an ambiguous effect on the precision of such race/ethnicity forecasts. If the user adopted the  
205 modal prediction method, the mode is unchanged by deleting one non-Hispanic White, and so the  
206 forecast precision is the same with or without that record. If the user adopted the proportional  
207 guess method, then deleting one non-Hispanic White record, slightly lowers the proportion of non-  
208 Hispanic Whites; hence, there is a slight reduction in precision when the record is removed from  
209 the census data. Now consider the sole Hispanic White on the block. If that person's record is  
210 removed, there is no possibility that the forecast models for race/ethnicity considered here can get  
211 the right combination. Both modal guessing and proportional guessing have no chance of being  
212 correct; that is, they have precision of exactly zero in the absence of the Hispanic White's census  
213 data. On the other hand, if the user's independent data on age and sex for the Hispanic White  
214 are close enough to the values in the reconstructed census data, then the user will correctly infer  
215 Hispanic White for this person when data from all 20 persons on the block are used in the census  
216 tables. There is an infinite gain in prediction accuracy when the record for the unique Hispanic  
217 White is included in the published data. The user's externally supplied name, sex, and age of the  
218 target were associated with a report of Hispanic White on the census record. When reliably correct,  
219 that is a prohibited, nonstatistical inference because it is only possible when the target person's  
220 record is used to produce the published tables.<sup>3</sup>

221 One might ask "What's the harm?" That's a perfectly legitimate question, even if outside the  
222 scope of the legal requirements governing the Census Bureau. One can see the harm by considering  
223 two routine uses of census data: redistricting and local demographics. Experts in both fields  
224 maintain databases that contain names, addresses, and some demographic data. They routinely  
225 update these databases. Redistricting experts use voter registration lists and purchase commercial  
226 data. Demographers use school district and commercial data. Both groups have mission-valid  
227 reasons to improve the accuracy of those databases. Both groups do this using their models and  
228 microdata-level conversions of published census tables (Jarmin et al., 2023). When those census  
229 tables permit nonstatistical (non-LOO) inferences, these users gain access to information about a  
230 specific person that is only possible because that person responded to the census and that response  
231 was used in the tabulations. Even though redistricters have legitimate interest in these data, a data  
232 steward who has made a confidentiality pledge to collect the data should not subsequently violate  
233 that pledge by permitting uses that depend specifically on the response provided. Individuals have  
234 a right to privacy that is reinforced by the same statute that ensures the confidentiality of the  
235 response should the individual answer the census. That right extends to protecting their responses  
236 from use by redistrictors or school districts via privacy-violating inferences. Such protection is the  
237 point of data confidentiality laws—they balance the utility of published data against the potential  
238 for privacy breaches. A user might want to know a characteristic more accurately than a statistical

---

<sup>3</sup>In traditional statistical disclosure limitation, e.g., (Duncan et al., 2011, p. 30), the inference associating the Hispanic White race/ethnicity with a specific, named person in the census block might be called either an identity or attribute disclosure—both of which are prohibited—depending on the setup of the attack. See Garfinkel et al. (2023) and Kifer et al. (2022).



(LOO) inference permits, but the data steward should not facilitate that learning by publishing data that permit strong non-LOO inferences. To prevent the extraction and nonstatistical use of personal information, statistical agencies must periodically analyze their SDL methods because nonstatistical actors, and especially malicious actors, do not publicly advertise their plans or methods. The goal of this paper is to assess the effectiveness of the SDL methods used in the 2010 Census in preventing nonstatistical inferences based on the published data.

We analyze the effectiveness of the confidentiality protections applied to the data products published from the 2010 Census by simulating what we call a *reconstruction-abetted reidentification attack*. We first attempt to reconstruct the underlying microdata for the features of census block, sex, age, race, and ethnicity from publicly released tables. We then attempt to match those reconstructed records to (a) records in low-quality commercial databases acquired during the conduct of the 2010 Census with person and address identifiers (representing attackers with the same quality contemporaneously available information in 2010) and (b) records containing a limited subset of variables from the 2010 Census itself (person identifier, census block, sex and age; representing attackers higher-quality contemporaneous external information). We used shared variables, called “key variables” in (Duncan et al., 2011, p. 20) or “quasi-identifiers” in (Garfinkel et al., 2023, p. 49), to determine how accurately we could link records and then infer the race and ethnicity of the persons in (a) the commercial records and (b) the quasi-identifier-only version of the 2010 Census records. We compare the results in several scenarios against baseline attackers who predicted using either (a) the most common race and ethnicity pair in the block (modal prediction from public tables) or (b) the race and ethnicity pair proportional to the distribution of block-level race by ethnicity combinations (proportional prediction from public tables). In all cases, we assess the prediction accuracy using the full set of 2010 Census variables (person identifier, census block, sex, age, race and ethnicity). For census block, sex, race, and ethnicity we always used the same schema. For age, we considered two different schemas: the block-level table schema (38 narrow age categories) and the tract-level schema (111 exact age categories). For the person identifier, we used the same vintage of the Census Bureau’s production record linkage system to replace the reported name and address with internal identifiers routinely used for person and household record linkage.

**2.1. Why Protections Are Required.** Title 13 of the U.S. Code mandates that information gathered from individuals and establishments remain confidential. Specifically, Section 8(b) allows the Census Bureau to “furnish copies of tabulations and other statistical materials which do not disclose the information reported by, or on behalf of, any particular respondent,” and Section 9 prohibits the release of “any publication whereby the data furnished by any particular establishment or individual under this title can be identified.” First and foremost, the Census Bureau is required to protect the confidentiality of respondents by law. Additionally, it is in the best interest of data quality that the public trust the Census Bureau to protect their data so that truthful responses are given, especially to sensitive questions (Childs et al., 2019; Childs et al., 2012, 2015, 2020).

There is a common misconception that there is nothing sensitive in the decennial census data. One of the reasons for this belief is that potentially harmful inferences are often about how an individual differs from a reference population. Hence, people who belong to demographic majorities in their area may have fewer or no concerns about confidentiality-violating inferences. However, there are many situations in which individuals may feel uncomfortable sharing their true data:

- Age, sex, race, and ethnicity data about children are often missing in commercial databases due to legal restrictions, because information about children is generally considered more sensitive.



- Household composition may be a sensitive subject in some areas and the decision to reveal this information in identifiable form should be up to the household and not the Census Bureau according to the principles guiding statistical agencies National Academies of Sciences, Engineering, and Medicine, 2021, p.3. This includes the detailed (census block-level) location of same-sex spouses, unmarried partners, mixed-race households, households with adopted children, older individuals living alone, etc. Thus, to encourage accurate reporting, the Census Bureau should protect the confidentiality of those responses.
- Individuals, especially those who are demographic minorities in their region, may believe that commercial databases should not collect detailed information about them without their consent. Race and ethnicity information are often missing or inaccurate in commercial data but are much more accurate in census data because they are mandatory self-report items on the questionnaire.
- Residents of rented properties in which the occupancy capacity is exceeded may wish this information to be protected.

Another argument that some give against strong confidentiality protections for census data is that there is so much personal information data “out there” that the census data does not pose an incremental risk. While there are large amounts of data available externally, the accuracy of this information is generally unknown. Our experiments demonstrate that circa 2010 external data were indeed inaccurate, or at least very noisy, compared the the decennial census data; however, circa 2020 external data are much more accurate (Brown et al., 2023). Additionally, if a data steward adopts the policy that data they collect should not be protected because it is already “out there,” then survey response rates would drop: “why should I fill out the survey if my data is already out there, just use that and don’t bother me?” But even when this position is accepted by a statistical agency, the relevant confidentiality statutes still require that the census responses, including any generated from external data, be protected. One might be able to learn respondent-specific information collected on the census from other sources, but the census publications cannot facilitate this learning (Statistics Canada, 2016).

**2.2. Household Data Swapping in the 2010 Census.** In the 2010 Census, the agency used noise infusion via targeted data swapping as the primary SDL framework. Households deemed at high risk for reidentification were swapped with a higher probability, but all records that were not entirely imputed had some chance of being swapped (McKenna, 2018). High-risk households were those in low-population census blocks or those who had a member with a unique race category in the census block. Pairs of swapped households matched on two key demographic variables: the total number of persons and the number of adults living in the household. Once swap pairs were determined, the geographic identifiers were swapped, effectively relocating the two records in different geographies from their 2010 Census values. The swapped file was used to produce all tabular and microdata products. Data swapping, by itself, is highly susceptible to attack (Kifer, 2015). For example, if the swap rate is 1%, then each record has a 99% chance of being unaltered and hence an attacker linking to a record can have high confidence that attributes learned from the record are correct. Furthermore, external data can help identify swapped records and even undo data swaps. If a household A, placed in a different census block in the swapped data than its census response, can be linked to external data based on matching attributes that are not affected by the swap, but does not match based on some of the attributes changed in the swap, then that household was likely targeted for swapping. Furthermore, if a household B in a nearby census block is a better match on the attributes affected by swapping, then it is likely that A and B were swapped with each other. For this reason, swapping is often paired with aggregation in an attempt to further thwart

330 attackers. Note that our reconstruction-abetted reidentification attack only attempts to undo the  
331 aggregation and does not take the further step of undoing the swapping protections.

332 **2.3. Related Work.** Reconstruction and reidentification attacks have been studied both theoret-  
333 ically and practically. Dinur and Nissim (2003) demonstrated conditions under which a database  
334 could be reconstructed even when only perturbed queries were reported. Dwork et al. (2017)  
335 provided an overview of reidentification and reconstruction attacks. Notable reconstruction and  
336 reidentification attacks include reidentification of individuals in a homicide database by making  
337 comparisons with public social security data (Ochoa et al., 2002), reidentification of patients in  
338 de-identified pharmaceutical marketing data using publicly available hospital discharge and am-  
339 bulatory claims data and voting list data (Sweeney, 2011), an attack against official foreign-trade  
340 statistics released in Brazil that reidentified companies performing import transactions (Favato et  
341 al., 2022), a genomics data reconstruction attack (Ayo et al., 2021), and reidentification of in-  
342 dividuals in census microdata publications with very high precision (Rocher et al., 2019). Dick  
343 et al. (2023) demonstrated a simulation-based reconstruction attack on census data with a very  
344 high success rate in identifying population uniques. There are many more examples in Garfinkel  
345 (2015) and Garfinkel et al. (2023).

346 In our results we include two separate statistical baseline models for comparisons that reflect a  
347 random-guessing attacker using statistical (LOO) inference to assign race and ethnicity. We find  
348 that the reconstruction aids the attacker substantially in correctly inferring the race and ethnicity  
349 of reidentified persons whose race and ethnicity differ from the majority race and ethnicity in the  
350 census block where they live. Specifically, we find that for a large set of reconstructed records,  
351 the attacker can prove that they have found the exact image of the source census record in the  
352 reconstruction using only public data, that this image is unique in the population, and that the  
353 race and ethnicity pair associated with the record is the same as the pair on the confidential census  
354 record even when that person is the only member of the race and ethnicity group in their census  
355 block. In other words, the only reason that the attacker found the correct race and ethnicity pair  
356 was because that person’s response was used to produce the underlying tables that supported the  
357 reconstruction. This is a prohibited nonstatistical use of census data made possible by the use in  
358 the 2010 Census of SDL methods that did not anticipate reconstruction-abetted reidentification  
359 attacks.

360 **2.4. Statistical Inference vs. Breaches of Confidentiality.** Privacy and confidentiality pro-  
361 tections are subtle concepts that give rise to many misunderstandings. It is a common but incorrect  
362 belief that breaches of confidentiality, colloquially known as *privacy breaches*, occur when a dataset  
363 is used to make any harmful or unwanted inference about an individual. Such an error has made its  
364 way into many peer-reviewed papers (Jarmin et al., 2023, SI section 5). In order to see where the  
365 problem lies, we first discuss the canonical “smoking causes cancer” thought experiment (Dwork,  
366 2011) and then discuss possible confidentiality concerns in the 2020 Census data. A more complete  
367 version of these arguments can be found in Kifer et al. (2022).

368 The first Cancer Prevention Study, also known as CPS-I, followed a cohort of volunteers from  
369 1959 to 1972 and conclusively established the link between smoking tobacco cigarettes as a cause  
370 of death from lung cancer and coronary heart disease (American Cancer Society, undated). As a  
371 result of this study, we know that persons who smoke have a much higher risk of developing lung  
372 cancer. Such inferences about smokers can definitely be unwanted, as they result in higher health  
373 and life insurance premiums. Persons born after 1972 may be subject to this inference caused by  
374 the study; however, since their data were not used for the study (they were not born until after it

was completed), the study cannot possibly be considered a privacy breach of their data. For those people, one would say that the inference is purely statistical in nature. Another way to phrase this is that the link between smoking and lung cancer is a population property, or statistical use (in the sense of the 2018 Confidential Information Protection and Statistical Efficiency Act, Title III of the 2018 Foundations of Evidence-based Policymaking Act; 44 U.S. Code § 3561(12)) that was uncovered with the help of the data set. This is exactly why data sets are collected and published.


In contrast, an unwanted inference is a privacy breach when it is specifically caused by the inclusion of the individual's information in the dataset from which the inference was made, what we call non-LOO inference. Now consider a hypothetical CPS-I study participant named Charlie who was a lifelong smoker. Suppose that as a result of the study, Charlie's insurance company decided to ask enrollees whether or not they smoked and charge a higher premium if they did. As a result, Charlie was harmed by the result of the study in which he was a participant. Is this now a privacy breach? To answer that question, we turn to causal reasoning, and specifically consider a counterfactual in which Charlie had not participated in the study; that is, we compare the non-LOO inference with a properly computed LOO one. Would the outcome of the study have been different enough without Charlie's participation to change the findings—thus changing whether the insurance company enacted their policy of charging smokers a higher premium policy which harmed Charlie? Given the strength of the findings in CPS-I (Hammond & Horn, 1954), we can be confident that the study would have drawn the same conclusions even if Charlie had not participated. Therefore, this example would also not be considered a confidentiality breach.

What would be considered a confidentiality breach for our hypothetical participant Charlie? Suppose the CPS-I data were released publicly, and Charlie's record could be reidentified in the data. If the data indicated that Charlie was one of the participants who developed lung cancer, then Charlie's insurance company would not have to ask him if he was a smoker—the insurance company would only need to check the public data to learn that he had lung cancer (whether he was a smoker or not), and could then increase his premium or deny coverage altogether. This is an example of a confidentiality breach because the unwanted inference (Charlie has lung cancer) was only possible because of Charlie's participation in the CPS-I study.

One also must be careful about the conflation of harmful inferences with privacy violations for another reason, which is also related to privacy and trust in statistical agencies, again as they are expressed in 44 U.S. Code § 3561-4 and (National Academies of Sciences, Engineering, and Medicine, 2021). Specifically, sometimes a statistical inference should not be allowed even if it is not privacy violating. A statistical agency might be asked to produce data on a particular sensitive population that could reasonably expect harm from those data even if they passed the LOO inference test. For example, in 2010, communities with a high percentage of same-sex married couples in states that did not permit such weddings might expect harm even if only a statistical summary were published. A statistical summary that could have affected the 2020 Census is the proportion of residents in the census block who were not U.S. citizens. Whether or not the government has a legitimate statistical interest in these populations is indeed a policy question, but the policy concerns ingesting the data with the intention to publish summaries in the first place. Barring the collection or publication of data on the grounds that even statistical inference may be harmful is a policy concern. In this paper, we presume that the agency's legitimate interest in supporting statistical inference has already been determined; that is, the collection of data in the decennial census and their publication for statistical purposes are authorized by Congress and undertaken consistent with the required trust and confidentiality policies.

In practice, the distinction between privacy-violating and statistical inferences is not always so clear-cut as in our smoking example. Information obtained from individuals is often aggregated, fields are suppressed (e.g., direct identifiers), and some SDL framework beyond aggregation may also be used. Still, it is important to disentangle what could be learned from statistical inference versus what can be specifically learned or caused by a person’s participation/inclusion in a study or dataset. This idea is the basis for research in the scientific field of “differential privacy” (Dwork & Roth, 2014).

### 3. 2010 CENSUS AND COMMERCIAL DATA INPUTS



**Figure 1.** Overview of the reconstruction, agreement, and reidentification workflow. Based on Summary File 1 (SF1) tables, a database with the features and rows of the confidential Hundred-percent Detail File (HDF) is reconstructed, validated for agreement with the HDF and the confidential Census Edited File (CEF), linked to commercial databases and a quasi-identifier-only copy of the CEF (labeled  $CEF_{atri}$ ) to determine putative reidentifications, then reidentifications are confirmed by linkage to the full-feature CEF. SF1 is itself tabulated from the HDF using a processing sequence that begins with the Census Unedited File (CUF). See Figure 2.

**3.1. Overview of the Complete Workflow.** Figure 1 provides a high-level overview of the databases that underlie the confidential and published versions of the 2010 Census and also summarizes our workflow using these databases. We begin by describing the internal Census Bureau databases from which the public SF1 was created. Next, we describe SF1 itself. We also describe the attributes and limitations of the commercial databases used in the analysis. We deliberately abstract from some of the complexity of these databases in order to focus on the features that are salient to our reconstruction and reidentification attacks.

**3.2. 2010 Census internal databases.** The U.S. Constitution mandates a census of population conducted every ten years. Since the 1970 Census, these enumerations have collected primarily self-reported information on households and the individuals in those households. For the 2010 Census, the confidential respondent microdata were stored in several databases. For our purposes, describing the relevant feature sets and provenance requires starting with the 2010 Census Unedited File (CUF), which contains the raw census responses for all living quarters, unduplicated and deemed in-scope for the enumeration. The 2010 Census Edited File (CEF) constitutes the final, fully edited, permanent electronic record of these responses to the 2010 Census. The application of confidentiality protections and tabulation recodes to the CEF produces the Hundred-percent

**Table 1.** Feature Sets for Data Used in the Experiments

Dataset	<i>name</i>	<i>address</i>	<i>pik</i>	<i>block</i>	<i>sex</i>	<i>age</i>	<i>agebin</i>	<i>race</i>	<i>ethnicity</i>
CUF	x	x			x	x	y	x	x
CEF			x	x	x	x	y	x	x
HDF				x	x	z	y	x	x
COMRCL			x	x	x	x	y		
CEF <sub>atkr</sub>			x	x	x	x	y		
rHDF <sub>b,t</sub>				x	x	z	y	x	x
rHDF <sub>b</sub>				x	x		x	x	x
Putative rHDF <sub>b,t</sub>			x	x	x	z	y	x	x
Putative rHDF <sub>b</sub>			x	x	x		x	x	x
Confirmed rHDF <sub>b,t</sub>			x	x	x	z	y	x	x
Confirmed rHDF <sub>b</sub>			x	x	x		x	x	x
MDG			x	x	x	z	y	g	g
PRG			x	x	x	z	y	h	h
MDF				x	x	z	y	x	x
rMDF <sub>b,t</sub>				x	x	z	y	x	x
rSWAPLo <sub>b,t</sub>				x	x	z	y	x	x
rSWAPHi <sub>b,t</sub>				x	x	z	y	x	x

Notes: The symbol x means the feature is present in the dataset. In all cases *age* is based on available birthdate information and calculated as of April 1, 2010. The symbol y, used for the feature *agebin*, means the available age information is sufficient to recode to the binned age schema. The symbol z means that the *age* feature in this dataset aggregates ages 100–104, 105–109, and 110 or older into three bins. The rows beginning Putative and Confirmed refer to the output of reidentification experiments. The schemas for MDG and PRG include the variables required to select only putative reidentifications based on either rHDF<sub>b,t</sub> or rHDF<sub>b</sub>. The symbol g means use the mode of the block-level *race* × *ethnicity* table from SF1. The symbol h means assign {*race*, *ethnicity*} with probability proportional to the counts in the block-level *race* × *ethnicity* table in SF1. The rows labeled MDF and rMDF<sub>b,t</sub> refer to the output of the 2020 Census Disclosure Avoidance System TopDown Algorithm applied to the 2010 CEF. The rows labeled rSWAPLo<sub>b,t</sub> and rSWAPHi<sub>b,t</sub> refer to the output of our reconstruction-abetted reidentification attack applied to specially swapped versions of the 2010 CEF. *Throughout the text, features shown in this table are denoted in italics to distinguish them from ordinary uses of the same word.*

444 Detail File (HDF), which is used to create all published data products. The tabulation edits in  
 445 HDF recode the residential location to the 2010 Census tabulation geography, create various age  
 446 groupings, and create a variety race and ethnicity groupings, all described below.

447 As part of the internal confidentiality safeguards, the respondent’s name and address are stored  
 448 on the CUF, not the CEF. Census data processing links the physical address to an identifier called  
 449 the Master Address File Identifier (MAFID) that the Census Bureau’s Geography Division has  
 450 determined to be a living quarter that existed on April 1, 2010, as either a housing unit or an  
 451 occupied group quarters facility, and thus is in-scope for data collection in the 2010 Census. To

452 facilitate research while safeguarding the name and address, the Census Bureau creates a crosswalk  
 453 that relates the internal person-record identifier on the CEF to a person identifier called a Protected  
 454 Identification Key (*pik*) using the production household data record-linkage system called the Person  
 455 Identification Validation System (PVS).<sup>4</sup> While the feature sets for the full hierarchical CUF, CEF  
 456 and HDF are much larger, the portions of the CUF that we use are shown in Table 1 in the row  
 457 labeled “CUF.”

458 The use of the Census Bureau’s production record-linkage system, and the selection of the 2010  
 459 Census vintage allowed us to do record linkage on name and address without having to design our  
 460 own linkage system. We ensured that the same vintage of PVS was used for the commercial data  
 461 we discuss later in this section. If the PVS recognized a person in the 2010 Census, it is extremely  
 462 likely that the same vintage of the software would recognize the same person in the commercial  
 463 data, thus assigning the same *pik*. All record linkage systems are subject to false positive and  
 464 negative linkages. By employing the same production PVS system on all data used for this paper,  
 465 we accept linkages based on *piks* with the error properties described in Layne et al. (2014).

466 Not all records in the CEF have a *pik* and in some cases the same *pik* appears on multiple  
 467 records because the PVS was not designed to unduplicate the input data set. For the purposes of  
 468 this paper, we refer to the subset of records in the CEF with a distinct *pik* within the record’s census  
 469 block as the *data-defined population*. To create the data-defined population, if there were multiple  
 470 records with the same *pik* within a census block, one record was randomly chosen. The data-  
 471 defined population is 276,000,000 records (89% of all records in the CEF). Records with duplicate  
 472 *piks* within a single block appeared in 15% of blocks. In total, 1% of records with a *pik* were  
 473 removed by this unduplication. The remainder of the difference between the total 2010 Census  
 474 population and the data-defined population are incomplete or imputed census responses to which  
 475 the PVS cannot assign a *pik* because the CUF contained insufficient respondent-supplied data.

476 The MAFID is further geocoded into the 2010 Census tabulation geography. In this paper, we  
 477 distinguish two components of the 15-digit tabulation geography—census tract (11-digit concatena-  
 478 tion of FIPS state, county equivalent, tract) and census block (15-digit concatenation of FIPS state,  
 479 county equivalent, tract, block).<sup>5</sup> The HDF is formed from the CEF by applying the SDL methods  
 480 described in Section 2.2, which are called “confidentiality edits” in the technical documentation  
 481 (U.S. Census Bureau, 2012). Finally, the parts of the person records in CEF and HDF used in this  
 482 paper have the feature sets shown in Table 1 in the appropriately labeled rows.

483 The confidential databases share the same schema and feature sets: one column for the cen-  
 484 sus block, one column each for the person identifier (*pik*), *sex*, *age*, and *ethnicity* (Hispanic or

---


<sup>4</sup>The PVS has evolved over time. The application of the production record linkage system was completed contemporaneously with the 2010 Census data processing using the 2010-vintage version of the PVS. For details on *pik* assignment, see Wagner and Layne (2014).

<sup>5</sup>FIPS stands for Federal Information Processing Standards, and refers to numeric and two-letter alphabetic codes defined in U.S. FIPS Publication 5-2. FIPS 5-2 was superseded by ANSI standard INCITS 38:2009. For details, see U.S. Census Bureau (2023b). Census blocks are a statistical definition of geography, not the commonly used “city block,” with complete coverage of the entire territory of the United States, and are the atoms in the Census Bureau’s geographic lattice that are used to build all other geographic tabulation summary levels, such as census tracts or county equivalents. Census blocks are defined in terms of territory, not population, and tessellate the entire United States. Some blocks may therefore be uninhabited (even underwater), others may have a very large population. See Rossiter (2011) for an overview. For more details on the person and geography attributes, see U.S. Census Bureau (2012).



485 Lation/Not Hispanic or Latino), and six columns for the required *race* categories.<sup>6</sup> Persons may  
 486 self-declare multiple race categories; hence the binary *race* features are not mutually exclusive.  
 487 In practice, most 2010 Census respondents only identified with a single race. The feature *age* is  
 488 recorded in integer values. If a census response is missing, the process that creates the CEF performs  
 489 edits and imputation, called “allocation” in the technical documents. There are no missing data in  
 490 the CEF and, in particular, at least one of the six race categories must be selected. Excluding *pik*,  
 491 which is standing in for name, we define all valid combinations of *block*, *sex*, *age*, *race*, and *ethnicity*  
 492 as the feature space (sample space in statistics) for CEF and HDF,  $\chi$ . There are approximately  
 493  $161 \times 10^9$  (161 billion) such combinations which gives the cardinality  $|\chi|$ .<sup>7</sup> Finally, note that we  
 494 used data for the 50 states and the District of Columbia.<sup>8</sup> We excluded Puerto Rico because the  
 495 2010 vintage of the Census Bureau’s production name and address record linkage system did not  
 496 work as well for this commonwealth.

497 **3.3. 2010 Summary File 1.** The most extensive and widely used 2010 Census data product is  
 498 Summary File 1 (U.S. Census Bureau, 2012). Figure 2 illustrates the process of creating SF1  
 499 from the internal census databases. SF1 contains counts of persons, households, families within  
 500 households, group quarters residents, and housing units tabulated at the census block, census tract,  
 501 and county-equivalent geographic levels. SF1 also includes the tables released separately as the  
 502 2010 P.L. 94-171 Redistricting Data Summary File, which form the basis for redistricting every  
 503 legislative body in the United States and are normally released by March 31st of the year following  
 504 the decennial census, several months before SF1.<sup>9</sup>



**Figure 2.** Summary of the creation of SF1. Collected census data is edited (CEF), confidentiality protections are applied (HDF), and then tabulated into tables, for instance SF1.

505 The SF1 and other published tables are created by tabulating the HDF according to various  
 506 combinations of geographic and demographic detail. All published data from the 2010 Census used  
 507 the same geographic hierarchy. See Appendix A of U.S. Census Bureau (2012) for more details.  
 508 The census block is the most detailed geographic category. There were 11,078,297 blocks defined  
 509 for 2010 Census publications of which 6,207,027 had nonzero populations.<sup>10</sup> These census blocks

<sup>6</sup>For details on the person attributes, see U.S. Census Bureau (2012). For background on the definitions of the required race and ethnicity categories, see Statistical Policy Directive 15 (Office of Management and Budget, 1997). The category “some other race” is mandated by law, not statistical policy.

<sup>7</sup>Cardinality  $|\chi| = 161, 109, 592, 812 = 6, 207, 027 \times 2 \times 103 \times 63 \times 2$ , where 6, 207, 027 is the number of inhabited blocks in the 2010 Census, 103 is the number of single-year age categories 0 to 99 plus grouped ages 100-104, 105-109, 110+ allowed in the published tables, and 63 is the number of allowable race combinations. Note that, for technical reasons, when we implement the reconstructions of HDF, we modify the feature set to eliminate the age binning for ages 100+.

<sup>8</sup>The use of the term “state” in this document refers to all 51 state-equivalent political divisions.

<sup>9</sup>The populations used for apportionment include a limited number of U.S. citizens and their families living abroad, known as the Federally Affiliated Overseas Population. These persons do not have records in the CEF, and their total for each state is added to the residential population for that state prior to apportionment, see Appendix G of U.S. Census Bureau (2012). The P.L. 94-171 Redistricting Data Summary File tables are renumbered in SF1 but are otherwise identical to the original release.

<sup>10</sup>Whether a block was inhabited or not was published without any confidentiality edits in 2010.



510 aggregate into 73,057 defined census tracts of which 72,531 had nonzero populations. These census  
 511 tracts, in turn, aggregate into 3,143 county equivalents, all of which had nonzero populations.

512 Within this hierarchy, tables of varying demographic and household detail are created. In this  
 513 paper, we focus on block- and tract-level tabular summaries of persons using only the 34 tables  
 514 shown in Table 2. The census block-level tables, labeled P in Panel A of Table 2, provide detailed  
 515 information on sex and race, but with coarsened age information for those age 22 and over. The  
 516 census tract-level summaries, labeled PCT $x$  in Panel B of Table 2, report most of the detail in  
 517 block-level tables in addition to reporting more detailed age.<sup>11</sup> We note for completeness that the  
 518 2010 Census PUMS, Summary File 2, and the American Indian/Alaska Native Summary File were  
 519 also created from the HDF. The 2010 HDF itself, but not the 2010 CEF, can be used by external  
 520 researchers with approved projects in the Federal Statistical Research Data Centers.

**Table 2.** Tables from 2010 Summary File 1 Used in Reconstruction Experiments

Panel A: Tabulated at the Census Block Level							
P1	P6	P7	P8	P9	P10	P11	P12
P14	P12A	P12B	P12C	P12D	P12E	P12F	P12G
P12H	P12I						
Panel B: Tabulated at the Census Tract Level							
PCT12	PCT12A	PCT12B	PCT12C	PCT12D	PCT12E	PCT12F	PCT12G
PCT12H	PCT12I	PCT12J	PCT12K	PCT12L	PCT12M	PCT12N	PCT12O

Source: 2010 Summary File 1 technical documentation (U.S. Census Bureau, 2012).

Notes: Overall, there are 8.6 billion linearly independent statistics in the census block-level tables and 241 million linearly independent statistics in the census tract-level tables. The tables for blocks with zero population are completely zero-filled. The total number of linearly independent statistics counting only blocks and tracts with positive population is 5.0 billion.

521 **3.4. The Treatment of Age in Summary File 1.** 2010 SF1 tabulated age differently depending  
 522 on the specific table and the level of geographic detail. At the tract level and above (e.g., Table  
 523 PCT12), age was tabulated in single years from 0 to 99 years, then binned into the ranges 100-104  
 524 years, 105-109 years, and 110 years and over. At the block level in most tables (e.g., Table P12),  
 525 age was binned into the following ranges: 0-4; 5-9; 10-14; 15-17; 18-19; 20; 21; 22-24; 25-29; 30-34;  
 526 35-39; 40-44; 45-49; 50-54; 55-59; 60-61; 62-64; 65-66; 67-69; 70-74; 75-79; 80-84; and 85+. Also at  
 527 the block level, Tables P10 and P11 selected only persons age 18 and older. Finally, the block-level  
 528 table P14 selected only individuals age 20 or younger and encoded age in single years. Combining  
 529 the different age binning and universe selection rules applied at the census block level defines the  
 530 most detailed age schema that these tables can support. That schema has 38 age groups: single  
 531 year of age from 0 to 21, then: 22-24; 25-29; 30-34; 35-39; 40-44; 45-49; 50-54; 55-59; 60-61; 62-64;  
 532 65-66; 67-69; 70-74; 75-79; 80-84; and 85+. We use this 38-bin age schema (feature *agebin*) in  
 533 our assessments of agreement of the reconstructed HDF with the HDF and CEF. We show in the  
 534 reidentification experiments that the 38-bin age schema provides sufficient uniqueness for persons  
 535 at the census block level to enable reconstruction-abetted reidentification. It is important to note  
 536 that tables P12 and P14, when combined, give the exact number of males and females in each of

<sup>11</sup>The tract-level schema for race is less detailed than the block-level schema; however this does not affect our reconstructions because we never use the tract-level data alone, and its race and ethnicity schema is nested in the block-level schema.

the 38 age bins in each census block, so any remaining uncertainty is in the race and ethnicity distribution within each sex and age bin. For *any* reconstructed microdata based on at least the tables in Panel A of Table 2, there is only one possible reconstruction on the feature set  $\{block, sex, agebin\}$ ; that is, the reconstruction is exact on that feature set. In our matching algorithms, we distinguish between matches based on exact age (feature *age*) and those based on binned age (feature *agebin*). In Section 4.5 we elaborate on the solution variability of our reconstructions.

**3.5. Circa 2010 Commercial Databases.** We created the commercial data (COMCRL) used for our reidentification experiments by combining data extracts originally purchased in support of the 2010 Census evaluations from four commercial providers between 2009 and 2011.<sup>12</sup> The COMCRL data serve as the background knowledge of an attacker with low-quality information contemporaneous with the release of the 2010 SF1. While the database schema and the purposes for which these commercial databases were originally collected vary, they all share certain attributes. All have basic personal identifying information (PII) including names, addresses, sex, and birthdates. The vintage 2010 versions of these databases that we used did not include self-reported race and ethnicity data.<sup>13</sup>

We harmonized the feature sets for the commercial data to match the schemas used in the CEF, as indicated in the COMCRL row of Table 1. These data were originally acquired because the features we use—name, address, sex, and birthdate in particular—were expected to closely resemble those collected on the 2010 Census. In our harmonization, name and address were mapped to *pik* and MAFID, respectively. The MAFIDs were originally geocoded in 2009–2011, when these commercial databases were acquired. Because the final 2010 tabulation geography schema was not available at that time, we remapped the MAFID to final 2010 tabulation blocks in early 2019. PII was standardized and mapped to *pik* using the same 2010-vintage PVS that was used for the 2010 CUF. Table 3 shows that there were 289,100,000 records with a valid  $\{pik, block, sex, age\}$  in the commercial database. We excluded the 2,449,000 COMCRL records that have census block IDs outside the 2010 CEF universe from all reidentification studies using COMCRL. Among the COMCRL records in the CEF universe, only 106,300,000 (37.1%) matched a CEF record on  $\{pik, block, sex, agebin\}$ , i.e., using binned age instead of exact age. Because our experiments on vulnerable populations—those whose characteristics differ from the modal person—use the census block universe for the  $\{race, ethnicity\}$  features to define vulnerable populations, only the 106,300,000 COMCRL records that match CEF records on the feature set  $\{block, pik, sex, agebin\}$  are available for those studies. Thus, the commercial data used here are not very accurate compared to the 2010 CEF, and we do not rule out the possibility that better quality data may have been available in 2010. Better external data were available for the 2020 Census (Brown et al., 2023).

#### 4. RECONSTRUCTION METHODOLOGY

We define *database reconstruction* as any attempt to re-create the record-level image of the database from which a set of published query results or tabulations were originally calculated; in this case, that is the confidential HDF.<sup>14</sup> Database reconstruction attempts to “reverse engineer” the confidential HDF records that were the input data used in a tabulation system with the goal

<sup>12</sup>The four commercial databases were provided by Experian Marketing Solutions Incorporated, Infogroup Incorporated, Targus Information Corporation, and VSGI LLC. The databases used are the same as in Rastogi and O’Hara (2012) except that we excluded data provided by the Melissa Data Corporation, which contain address information but not sex and age data.

<sup>13</sup>Race and ethnicity data are modeled in some of the commercial databases (Rastogi & O’Hara, 2012).

<sup>14</sup>See Garfinkel et al. (2018) for a longer discussion of how to understand database reconstruction.

**Table 3.** Overlap of Data-Defined Person Records in CEF and COMRCL Databases

	In CEF Universe		Not in CEF	Total
	Matched ( $\times 10^{-3}$ )	Unmatched ( $\times 10^{-3}$ )	Universe ( $\times 10^{-3}$ )	( $\times 10^{-3}$ )
Records in COMRCL	106,300	180,400	2,449	289,100
Records not in COMRCL	169,700			
Total	276,000			

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. The commercial data contain census block geocodes not found in the CEF universe. The columns “In CEF Universe, Matched” and “In CEF Universe, Unmatched” reflect only records with 2010 census block geocodes in the CEF universe. The balance of the data-defined COMRCL records are shown in the column “Not in CEF Universe.” The research in this paper can only use those records in the CEF universe. When COMRCL records are classified as modal or nonmodal we limit to “Matched” records for which CEF attributes are known. “Matched” means the records agree on the feature set  $\{block, pik, sex, agebin\}$ .

of making the reconstruction as close as possible to these confidential data. We note that the reconstruction described here is not the most powerful feasible reconstruction. We used only a subset of the SF1 tables, we made no attempt to reconstruct households or characteristics of the householder (adult respondent providing the census data on CUF), and we did not use statistical modeling to improve the reconstruction (e.g., in blocks where multiple different reconstructions were consistent with the published tables, we did not use statistical methods to identify the most likely reconstruction). Even without these enhancements, we show that the disclosure avoidance methods of the 2010 Census are highly susceptible to attack.

**4.1. Reconstruction Overview.** Table 2 shows the 34 tables we included in our reconstruction for any universe that was part of the total population.<sup>15</sup> These tables, computed from the HDF person records, are multidimensional marginal counts related to age, sex, race, and ethnicity by census block and tract. Our reconstructed microdata contain these same variables and only these variables. The reconstructed data, therefore, necessarily reflect the schemas used for SF1 and are only informative about variables, in particular age, in the schemas used for publication, as described in Section 3.4.

Our experiments used two different subsets of SF1 data as shown in Table 2. The first reconstruction, which we denote as  $rHDF_{b,t}$ , uses both tract and block-level SF1 tables, taking advantage of both the geographic and race detail in the block summaries and the age detail in the tract summaries. The second reconstruction,  $rHDF_b$ , uses only the block-level tables. Thus, the second reconstruction removes the more granular age information found in the tract-level tables while retaining the full race and ethnicity schema used in the block-level data. Comparing results from  $rHDF_{b,t}$  and  $rHDF_b$  to HDF and CEF shows the loss of reconstruction accuracy from removing tract-level tables.

**4.2. A Simplified Algebraic Representation of the Reconstruction Problem.** Because it is very useful for understanding the mathematical structure of the reconstruction experiments, we begin by explaining the linear algebra representation of the reconstruction problem. Then, in Section 4.3, we provide a description of the integer program (IP) setup we used to generate the

<sup>15</sup>We did not use tables where the universe was households, which means that we did not use the “relationship to the householder” information to reconstruct household characteristics or to improve the reconstructed data for persons in those households.

solutions discussed in our results. This IP formulation does not convey the high-level structure of the problem as simply but closely follows our software implementation.

The inputs to the reconstruction are the database schema for the tabulation feature set  $\{block, sex, age, race, ethnicity\}$ ; the vector of all published statistics in the appropriate order; and the matrix workload that maps the histogram representation of the HDF onto the published statistics. We represent the table of the record-level data as the vectorized fully saturated contingency table (called a *histogram* in computer science) where every cell corresponds to a possible record type in  $\chi$  and its value is the number of records of that type. Thus, instead of a multi-dimensional array, the contingency table is flattened into a vector (like the operation `as.vector()` in R or `np.flatten()` in numpy). Let  $\mathbf{x}$  represent the contingency table vector. Database reconstruction consists of finding at least one non-negative integer solution for  $\mathbf{x}$  in the equation system

$$(4.1) \quad \mathbf{A}\mathbf{x} = \mathbf{c} \text{ such that } x_i \in \mathbb{Z}^+ \text{ for all } i,$$

where  $\mathbf{c}$  is  $K \times 1$  column vector of the  $K$  statistics extracted from SF1 for a given reconstruction,  $\mathbf{A}$  is the matrix for computing those SF1 tabulations from a contingency table vector  $\mathbf{x}$ , and  $\mathbb{Z}^+$  is the set of non-negative integers. Each row of  $\mathbf{A}$  and corresponding component of  $\mathbf{c}$ , therefore, represent a single query (i.e., statistic) and its realized value in SF1, respectively.

There are fewer statistics published per block than points in the sample space ( $|\chi| > K$ ), meaning that a unique solution to equation (4.1) is not always guaranteed. However, many low-population blocks have published tables that contain a large number of entries whose values are zero. This eliminates many candidate solutions, and often there is only one unique non-negative, integer-valued solution to equation (4.1). There is always at least one solution because SF1 was tabulated from a single real database with the schema encoded in  $\chi$  (i.e., the HDF). The commercial software Gurobi<sup>TM</sup> has a robust toolkit for solving IPs and related mixed integer linear programs (MILP) to produce solutions to problems such as these. See Section 4.3 for details. When multiple solutions exist, Gurobi<sup>TM</sup> will pick one. In principle, statistical modeling could be used to select among candidate solutions to improve reconstruction quality, but we did not do this.

Given a solution  $\hat{x}$  to equation (4.1), another question of interest is how different  $\hat{x}$  could be from other possible solutions. If  $\hat{x}$  is the only solution to equation (4.1), then it represents an exact reconstruction of the microdata used to tabulate SF1, namely HDF, with certainty. Moreover, if the uniqueness of the solution can be determined from the published inputs to equation (4.1), then an attacker knows that those reconstructed records were present in HDF with certainty. To examine how often the solution  $\hat{x}$  was strongly constrained, we designed an algorithm for measuring solution variability by building a second IP model. Its goal is to find a second solution,  $\tilde{x}$ , that maximizes the  $L_1$  distance to  $\hat{x}$ . This allows an attacker, using only public information, to determine the maximum number of records in the reconstruction that could be incorrect. This problem is described in Section 4.5.

**4.3. The Integer Programming Version of the Reconstruction Model.** This section describes how the IP is implemented as a mathematical programming problem, which is the method used in all our statistical calculations. We begin by describing how we converted the basic schema for the feature set  $\{block, sex, age, race, ethnicity\}$  into the binary variables used in our reconstruction. The following notation describes the nine demographic features: W, BL, AIAN, ASIAN, NHOPI, SOR, HISP, SEX, and AGE and the values allowed for each feature.

(4.2) **Reconstruction Feature Sets Using Exact Age**

$$W = \{\text{White} = 1, \text{Not White} = 0\}$$

$$BL = \{\text{Black or African American} = 1, \text{Not Black or African American} = 0\}$$

$$AIAN = \{\text{American Indian or Alaskan Native} = 1, \text{Not American Indian or Alaskan Native} = 0\}$$

$$ASIAN = \{\text{Asian} = 1, \text{Not Asian} = 0\}$$

$$NHOPI = \{\text{Native Hawaiian or Other Pacific Islander} = 1,$$

$$\text{Not Native Hawaiian or Other Pacific Islander} = 0\}$$

$$SOR = \{\text{Some Other Race} = 1, \text{Not Some Other Race} = 0\}$$

$$HISP = \{\text{Hispanic or Latino} = 1, \text{Not Hispanic or Latino} = 0\}$$

$$SEX = \{\text{Male} = 0, \text{Female} = 1\}$$

$$AGE = \{0, 1, 2, \dots, 110\}.$$

A potential record corresponds to a setting of the block  $b$  along with settings for the demographic attributes ( $w, bl, aian, asian, nhopi, sor, hisp, a, s$ ). Here the lowercase italic letters index the permitted values of the uppercase feature set of the same name (e.g. *aian* represents a value of the feature AIAN). We create one variable for the IP for each potential record. Since we do not know, a priori, how many records exist with the same demographic type and block, we must create multiple variables  $\mathcal{B}_{(i,b,w,bl,aian,asian,nhopi,sor,hisp,a,s)}$  for  $i = 0, 1, 2, \dots$ . We use Table P12 from SF1 (age group by sex for each census block) to obtain an upper bound on the number  $i$  for each block and combination of demographics. For example, for the demographic type of a 22-year-old Asian Hispanic female in a block  $b$ , suppose Table P12 for that block indicates that there are 50 females in the age group 22-24 (See Table 4 for the age groupings in P12). This is an upper bound on the number of potential records for 22-year-old Asian Hispanic females in the block. Thus, we create the 50 variables  $\mathcal{B}_{(i,b,w=0,bl=0,aian=0,asian=1,nhopi=0,sor=0,hisp=1,a=22,s=1)}$  for  $i = 0, \dots, 49$ . These variables are binary, with a value of 1 indicating the presence of the potential record in a candidate microdata reconstruction. Once the binary variables are assigned values, the summation

$$\sum_{i=0}^{49} \mathcal{B}_{(i,b,w=0,bl=0,aian=0,asian=1,nhopi=0,sor=0,hisp=1,a=22,s=1)}$$

represents the number of 22-year-old female Asian Hispanic people in that block. Formally, we created the complete set of binary variables as follows.

- We define an age binning function AGEBIN\_P12 (shown in Table 4) based on the age groupings used in the SF1 Table P12. For any age  $a \in \text{AGES}$ , the value of AGEBIN\_P12( $a$ ) is the bin from Table 4 containing that age.
- For any age  $a$ , sex  $s$ , and block  $b$ , define the constant  $c_{b,\text{AGEBIN\_P12}(a),s}^{P12}$  to be the count in SF1 Table P12 of the number of people in block  $b$  with sex  $s$  and an age that is in the same age bin as age  $a$ .
- For every block  $b$ , age  $a$ , sex  $s$ , and value of the race/ethnicity variables  $w, bl, aian, asian, nhopi, sor, hisp$ , we define the binary variables:

$$(4.3) \quad \mathcal{B}_{(i,b,w,bl,aian,asian,nhopi,sor,hisp,a,s)} \in \{0, 1\}, \text{ for } i = 0, \dots, c_{b,\text{AGEBIN\_P12}(a),s}^{P12} - 1$$

We emphasize that using SF1 Table P12 in this manner does not coarsen the age schema. It only determines the maximum number of  $\mathcal{B}_{(\cdot)}$  variables that the integer program may use for each demographic type in the full schema.

**Table 4.** Index Mapping for the 23-bin Age Grouping in Table P12,  $z = \text{AGEBIN\_P12}(a)$ 

a	0-4	5-9	10-14	15-17	18-19	20	21	22-24	25-29	30-34	35-39
z	0	1	2	3	4	5	6	7	8	9	10
a	40-44	45-49	50-54	55-59	60-61	62-64	65-66	67-69	70-74	75-79	80-84
z	11	12	13	14	15	16	17	18	19	20	21
a	85-110										
z	22										

**Table 5.** Index Mapping for the 38-bin Age Grouping,  $z = \text{AGEBIN\_BLOCK}(a)$ 

a	0	1	2	3	4	5	6	7	8	9	10
z	0	1	2	3	4	5	6	7	8	9	10
a	11	12	13	14	15	16	17	18	19	20	21
z	11	12	13	14	15	16	17	18	19	20	21
a	22-24	25-29	30-34	35-39	40-44	45-49	50-54	55-59	60-61	62-64	65-66
z	22	23	24	25	26	27	28	29	30	31	32
a	67-69	70-74	75-79	80-84	85-110						
z	33	34	35	36	37						

Notes: This 38-bin age grouping summarizes the most detailed age data tabulated in any block-level SF1 table. It also defines the relation of the feature *agebin* to the feature *age*.

Let  $T$  represent the set of all census tract indices, and  $B_t$  represent the set of all census block indices in tract  $t$ . We next illustrate how each SF1 table adds additional constraints on the  $\mathcal{B}_{(\cdot)}$  variables. For example, consider the tract-level table PCT\_12I, which encodes the tabulation sex by age group in each tract for people who are “White Alone” and “Not Hispanic or Latino.” The age binning used by this table is  $\{0, 1, \dots, 99, 100 - 104, 105 - 109, 110+\}$ , so let  $\text{AGEBIN\_PCT12I}(a)$  be the function that returns the appropriate PCT12I age bin  $z$  for a given age  $a$ . For each tract  $t$ , PCT12I age bin  $z$ , and sex  $s$ , let  $c_{t,s,z}^{\text{PCT12I}}$  be the corresponding count in table PCT12I. Then for each  $t, s, z$  we add the following constraint:

$$\sum_{b \in B_t, a: \text{AGEBIN\_PCT12I}(a)=z} \sum_i \mathcal{B}_{(i,b,w=1,bl=0,aian=0,asian=0,nhopi=0,sor=0,hisp=0,a,s)} = c_{t,s,z}^{\text{PCT12I}}$$

where the summation over  $i$  uses the upper bound on the number of  $\mathcal{B}_{(\cdot)}$  variables in equation (4.3) (i.e.,  $i = 0, \dots, c_{b, \text{AGEBIN\_P12}(a), s}^{\text{P12}} - 1$ ).

We use the notational shorthand  $\mathcal{T}_t[\text{tablename}, \bigcup_{b' \in B_t} \text{rHDF}_{b,t}(b')] = c_t^{\text{tablename}}$  to represent all such constraints created by SF1 tract-level table *tablename* (e.g., PCT12I) for tract  $t$ . Specifically, the notation  $\text{rHDF}_{b,t}(b')$  refers to the optimization variables for records in a block  $b'$  when performing the  $\text{rHDF}_{b,t}$  reconstruction, the notation  $\bigcup_{b' \in B_t} \text{rHDF}_{b,t}(b')$  indicates that we form the constraints using the optimization variables for all blocks  $b'$  that belong inside tract  $t$  (i.e.,  $\forall b' \in B_t$ ). For example, in the case of SF1 Table PCT12I, this means an application of equation (4.3) for each age bin  $z$  and sex  $s$  for the record variables in the tract. The tract-level tables used are listed in Panel B of Table 2. Similarly, we use the shorthand  $\mathcal{T}_b[\text{tablename}, \text{rHDF}_{b,t}(b')] = c_{b'}^{\text{tablename}}$  for the block-level constraints in block  $b'$  created by SF1 block-level table *tablename* (Panel A of Table 2).

690 With this notation, the IP problem for the rHDF<sub>b,t</sub> reconstruction model for tract *t* can be  
 691 written as:

$$(4.4) \quad \max 0$$

$$s.t \mathcal{T}_t[tablename, \bigcup_{b' \in B_t} \text{rHDF}_{b,t}(b')] = c_t^{tablename} \quad \forall tablename \in \text{Panel B of Table 2}$$

$$\mathcal{T}_b[tablename, \text{rHDF}_{b,t}(b')] = c_b^{tablename} \quad \forall tablename \in \text{Panel A of Table 2} \quad \forall b' \in B_t$$

692 The objective function “max 0” indicates that any feasible solution that satisfies the constraints  
 693 can be returned (i.e., if there are multiple candidate solutions, no statistical modeling or maximum  
 694 entropy is used, and Gurobi<sup>TM</sup> picks a solution arbitrarily). The optimization variables are the  
 695  $\mathcal{B}_{(\cdot)}$  defined in equation (4.3). Once we have a feasible solution, for every  $\mathcal{B}_{(\cdot)}$  that is set to 1,  
 696 we add a corresponding record for that block and demographic type to the reconstructed dataset.  
 697 For rHDF<sub>b,t</sub>, we also recode the feature *age* into *agebin* because our matching algorithms require  
 698 access to both variables. See Section 5. Thus, upon completion, the IP from equation (4.4) yields  
 699 a reconstructed version of the HDF, called rHDF<sub>b,t</sub>, that contains one record for each person in the  
 700 2010 Census with the features indicated in row rHDF<sub>b,t</sub> of Table 1.<sup>16</sup>

701 Next, we present the IP for the reconstruction rHDF<sub>b</sub>, which uses only the SF1 block-level  
 702 tables shown in Panel A of Table 2. Block-level tables use several age binning schemes, but their  
 703 intersection is not exact age. Instead, their intersection is the age grouping shown in Table 5, which  
 704 has 38 age bins. Since this is the most fine-grained age resolution that can possibly be obtained  
 705 from block-level tables, rHDF<sub>b</sub> contains age reconstructed up to this 38-age binning (the feature  
 706 that represents this age grouping is called *agebin*). To simplify the implementation, the IP uses the  
 707  $\mathcal{B}_{(\cdot)}$  optimization variables from equation (4.3). This means that the solution provides single-year  
 708 ages, but after the reconstructed microdata are created, we recode *age* into *agebin* as defined in  
 709 Table 5. The IP for the block-level reconstruction is similar to the tract-level reconstruction. For  
 710 each block *b'*, solve

$$(4.5) \quad \max 0$$

$$s.t \mathcal{T}_b[tablename, \text{rHDF}_b(b')] = c_b^{tablename} \quad \forall tablename \in \text{Panel A of Table 2}.$$

711 Again, no statistical modeling is used to return the most plausible solution if multiple feasible  
 712 solutions exist. Once we obtain a feasible solution, for every  $\mathcal{B}_{(\cdot)}$  that is set to 1, a corresponding  
 713 record for that block and demographic type is created. Because our matching algorithm requires  
 714 access to both age-related features, we retain the feature *age* and create the feature *agebin* using  
 715 the appropriate bin in Table 5. The resulting record is added to the reconstructed dataset rHDF<sub>b</sub>  
 716 whose feature set is shown in the row rHDF<sub>b</sub> of Table 1.

717 **4.4. Implementation Notes.** The IP formulation of the reconstruction problem is mathematically  
 718 equivalent to the simplified model in Section 4.1. The only difference is that the optimization  
 719 variables  $\mathcal{B}_{(\cdot)}$  in the IP implemented in our code correspond to potential records, while the vector  
 720  $\mathbf{x}$  in equation (4.1) contains counts from the fully saturated contingency table defined on the  
 721 sample space  $\chi$ . The code in the replication archive implements the IP in equations (4.4) and  
 722 (4.5), and these equations are useful for reading the software implementation in the replication

<sup>16</sup>Since SF1 always groups all persons 100 years of age or older into the bins: “100-104 years”, “105-109 years”, and “110 years and over” or uses even coarser age groups, the IP can never resolve the feature *age* more precisely than these bins. The IP still has variables for individual ages 100, ..., 110 and so Gurobi will arbitrarily choose a specific age within those age bins. This means that there is inherent solution variability in the ages of the oldest sub-populations.



archive, whereas the histogram representation in equation (4.1) is useful for understanding the high-level structure of the problem. For reconstruction outcomes, only run-time, not the space of feasible solutions, is affected by the choice of which representation to implement. It is not obvious a priori which representation should solve more quickly. We have direct experience solving the IP representation, and we found it to consistently solve very quickly at default Gurobi<sup>TM</sup> settings for the set of tables we used in the reconstruction. Equation (4.1) is succinct, easy to represent in any matrix programming language that implements sparse matrix storage and MILP solvers, and yields a model with considerably fewer variables. On the other hand, the IP representation, while it produces less succinct models, uses only binary variables in the solution set, rather than non-negative integers, and binary variables are usually processed more efficiently in modern MILP solvers. Our discussion switches between the two representations to permit clarity of expression (equation (4.1)) versus fidelity to the details of our implemented reconstruction code (equations (4.4) and (4.5)).

**4.5. Solution Variability.** When an attacker performs a reconstruction, an important question is whether the attacker can determine if the reconstruction in a block is unique, or if the attacker can compute an upper bound on the number of reconstructed records that may be erroneous (i.e., a confidence score for reconstruction accuracy). In blocks with zero reconstruction error, an attacker would also be more confident about linking these reconstructed records to other data sources, since swapping and record-level synthetic data would be the only remaining disclosure avoidance techniques that could cause these reconstructed HDF records to differ from their CEF counterparts. This would be especially problematic if the swap rate were low. On the other hand, a high swap rate may prevent some records from being linked, but for the remainder of the records that are linked (and hence probably not swapped), the attacker would be more likely to learn additional attributes about those individuals from the reconstructed data. Recall that reconstruction error is limited to the race and ethnicity variables, along with the specific *age* within *agebin*. As explained in Section 3.4, SF1 tables P12 and P14 already give the exact count of males and females in each of the 38 age bins (from the block level schema) for each block. This means that an attacker can always create microdata records with the correct sex and binned age values by expanding those tables. In the block-level schema (for  $\text{rHDF}_b$ ), the only remaining uncertainty is in which race and ethnicity to attach to those records. In the tract-level schema (for  $\text{rHDF}_{b,t}$ ), there is also uncertainty about single year of age within age bin (except for the population 21 years and under, since each of these age bins contains exactly one age).

For any reconstruction  $\text{rHDF}$  and geographic region  $g$ , such as a specific tract or block, we let  $\text{rHDF}(g)$  represent the subset of records in  $\text{rHDF}$  that belong to geographic region  $g$ . If there are two feasible reconstructions,  $\text{rHDF}^*$  and  $\text{rHDF}'$ , we consider them equivalent for region  $g$  if and only if the difference is the ordering of the records; that is, if one is a permutation of the other. In other words, two reconstructions are equivalent on  $g$  if their corresponding fully saturated contingency tables for region  $g$  are the same. Letting  $\text{Hist}(\cdot)$  represent the operator that converts a reconstruction into a fully saturated contingency table, two possible reconstructions  $\text{rHDF}^*(g)$  and  $\text{rHDF}'(g)$  in region  $g$  are distinct whenever  $\text{Hist}(\text{rHDF}^*(g)) \neq \text{Hist}(\text{rHDF}'(g))$ .

Let  $i = 1, \dots, k$  index the  $k$  cells of the histogram representation of the contingency table. We measure the difference between two histograms using the  $L_1$  norm:

$$L_1\{\text{Hist}(\text{rHDF}^*(g)), \text{Hist}(\text{rHDF}'(g))\} = \sum_{i=1, \dots, k} |\text{Hist}(\text{rHDF}^*(g))_i - \text{Hist}(\text{rHDF}'(g))_i|.$$

765 Note that the cells depend on the reconstruction schema. For example, when reconstructing  $\text{rHDF}_b$ ,  
 766 the histograms use the 38-bin age grouping shown in Table 5. Also note that

$$L_1(\text{Hist}(\text{rHDF}^*(g)), \text{Hist}(\text{rHDF}'(g))) \leq 2N_g,$$

767 where  $N_g$  is the total population of geographic unit  $g$ . Equality is achieved if and only if the  
 768 two histograms completely disagree on the types of records present in  $g$ . This bound follows  
 769 because  $\text{rHDF}^*(g)$  and  $\text{rHDF}'(g)$  are both constrained to have exactly  $N_g$  records, so we can think  
 770 of  $\text{rHDF}'(g)$  as being constructed by modifying a sequence of records in  $\text{rHDF}^*(g)$ . Each such  
 771 modification can increase the  $L_1$  distance by no more than 2, and at most every one of the  $N_g$   
 772 records can be modified, for a total  $L_1$  distance of  $2N_g$  when the two histograms no longer have any  
 773 records in common. On the other hand, the  $L_1$  norm is 0 if and only if the two histograms agree  
 774 exactly on the types and multiplicities of records present.

775 Given a feasible solution  $\text{rHDF}^*$ , we define solution variability relative to  $\text{rHDF}^*$  as the following  
 776 function *solvar* for geographic unit  $g$ :

$$(4.6) \quad \text{solvar}(\text{rHDF}^*, g) = 100 \times \max_{\{\text{feasible rHDF}'\}} \frac{L_1\{\text{Hist}(\text{rHDF}^*(g)), \text{Hist}(\text{rHDF}'(g))\}}{2N_g},$$

777 where feasible solutions use equation (4.4) when  $g$  is a tract or equation (4.5) when  $g$  is a block.  
 778 Note that the multiplication by 100 allows us to interpret  $\text{solvar}(\text{rHDF}^*, g)$  as the percentage of  
 779 its maximum value.

780 If solution variability in equation (4.6) is 0, then there is a single, unique solution to the re-  
 781 construction problem in geounit  $g$ , and the  $\text{rHDF}^*$  records in  $g$  must exactly match the HDF for  
 782 the variables present in records of both data sets and under the schema used to create  $\text{rHDF}^*$ .  
 783 When solution variability in equation (4.6) is 100, there is at least one other reconstruction  $\text{rHDF}'$   
 784 that has no records in common with  $\text{rHDF}^*$ . In this case,  $\text{rHDF}^*$  may be a poor reconstruction  
 785 of HDF, and any agreement between the two may be due to happenstance. In general, *solvar* is  
 786 an upper bound on the percentage of records in  $\text{rHDF}^*$  that could differ from any other possible  
 787 reconstruction, including the actual HDF. For example, if the solution variability is 10, then at  
 788 most one-tenth of the records (i.e., 10%) in  $\text{rHDF}^*$  could differ from the actual HDF. Note that  
 789 “differ” means that at least one attribute of the record is incorrect; it does not necessarily mean all  
 790 attributes in the record were wrong.

791 It is worth noting that solution variability is a property specific to a given reconstruction  $\text{rHDF}^*$   
 792 because it measures the maximum percentage of records of  $\text{rHDF}^*$  that can be changed while still  
 793 maintaining a feasible reconstruction. Thus two different reconstructions  $\text{rHDF}^*$  and  $\text{rHDF}^\dagger$  can  
 794 have different solution variabilities. For instance, suppose  $\text{rHDF}^*$  is in the middle of the feasible  
 795 region and  $\text{rHDF}^\dagger$  is in a remote corner of the feasible region. Then, the solution variability of  
 796  $\text{rHDF}^*$  is less than that of  $\text{rHDF}^\dagger$ .

797 Given that an attacker may use a different solver or statistical modeling to find a feasible re-  
 798 construction, it is important for the data curator to understand the range of solution variability  
 799 any attacker may obtain. Fortunately, using our method, the data curator can estimate a 100%  
 800 confidence interval that is guaranteed to contain the attacker's *solvar* value. To do so, the data  
 801 curator obtains a reconstruction  $\text{rHDF}^*$ , computes its solution variability  $\text{solvar}(\text{rHDF}^*, g)$  for a  
 802 region  $g$ , and appeals to the triangle inequality as follows. For any other feasible  $\text{rHDF}'$ ,

$$(4.7) \quad \frac{\text{solvar}(\text{rHDF}^*, g)}{2} \leq \text{solvar}(\text{rHDF}', g) \leq \max(2\text{solvar}(\text{rHDF}^*, g), 100),$$

and hence any attacker's *solvar* will be within a factor of 2 of the data curator's *solvar*.<sup>17</sup>

Computing  $\text{solvar}(\text{rHDF}^*, b)$  for each block  $b$  is manageable using Gurobi<sup>TM</sup>, but computing *solvar* for larger regions  $g$  can be very computationally expensive. Let  $\text{Blocks}(g)$  denote the set of blocks composing region  $g$  and, as usual,  $N_b$  and  $N_g$  refer to the population counts in block  $b$  and region  $g$ , respectively. Given  $\text{solvar}(\text{rHDF}^*, b)$  for each  $b \in \text{Blocks}(g)$ , we define cumulative solution variability, *cumsolvar*, as:

$$(4.8) \quad \text{cumsolvar}(\text{rHDF}^*, \text{Blocks}(g)) = \frac{1}{\sum_{b \in \text{Blocks}(g)} N_b} \sum_{b \in \text{Blocks}(g)} N_b \times \text{solvar}(\text{rHDF}^*, b).$$

Recalling that  $B_t$  is the set of all the blocks in tract  $t$ ,  $\max(2\text{cumsolvar}(\text{rHDF}^*, B_t), 100)$  is an upper bound on the percentage of records in tract  $t$  for which any two solutions to  $\text{rHDF}_{b,t}$  can differ.<sup>18</sup> The function *cumsolvar* is of particular interest for regions  $g$  composed of all blocks with  $\text{solvar}(\text{rHDF}^*, b)$  no greater than the  $q^{\text{th}}$  percentile for different values of  $q$  (see Table 6). In particular, we focus our attention on persons who live in the set of blocks with *cumsolvar* = 0. For these blocks, we know that the attacker is certain that the reconstructed records are in HDF regardless of the method used to compute the reconstruction.

**4.6. Solvar Implementation Details.** The integer program that determines solution variability in geography  $g$  is computationally more expensive to solve than solving for an initial  $\text{rHDF}^*$ . For an attacker who wants to target a small number of blocks or tracts, that is not much of an issue. However, the data curator needs to compute the solution variability for all block and tracts. We found that computing a solution to equation (4.6), in which the feasible  $\text{rHDF}'$  is required to be consistent with the block and tract level tables, is too expensive to perform for the entire nation. Hence, we relaxed the optimization problem to make it easier to solve while still allowing us to bound the solution variability for an attacker who performs a reconstruction using block and tract-level tables. While concerted research on this problem class is likely to yield faster solutions, we found that the following changes made the problem easier to solve. First, we use the 38-bin age groupings (feature *agebin*) that appear in the block-level tables.

Next, we change the starting solution,  $\text{rHDF}^{S0}$ , around which *solvar* is computed by relaxing the tract-level constraints that define a feasible solution from equality constraints to inequality constraints. For a given block  $b'$  and its containing tract  $t$ , we solve the following optimization problem:

$$(4.9) \quad \begin{aligned} \text{rHDF}^{S0}(b') &= \arg \max 0 \\ \text{s.t. } \mathcal{T}_t[\text{tablename}, \text{rHDF}^{S0}(b')] &\leq c_t^{\text{tablename}} \quad \forall \text{tablename} \in \text{Panel B of Table 2} \\ \mathcal{T}_b[\text{tablename}, \text{rHDF}^{S0}(b')] &= c_b^{\text{tablename}} \quad \forall \text{tablename} \in \text{Panel A of Table 2.} \end{aligned}$$

The differences from the reconstruction in equation (4.4) are that equality constraints for tract-level tables become inequality constraints, and the other blocks in tract  $t$  are ignored when computing

<sup>17</sup>These bounds also address a technical caveat which is appropriate for our implementation: as an engineering quirk, the process we followed to produce the solution variability estimates involved re-solving the initial reconstruction optimization problems,  $\text{rHDF}_b$ , not directly re-loading the original reconstruction solutions used for the initial reconstruction-abetted re-identification attack. The Gurobi<sup>TM</sup> software that we used for reconstruction is largely, but not completely, deterministic at default settings. This nondeterminism could have caused the  $\text{rHDF}^*$  used in solution variability problems to differ from the original reconstructed solutions in some cases, although we suspect this would be unusual.

<sup>18</sup>The analogous claim is not true for  $\text{rHDF}_b$ , because our solution variability models, described in equations (4.9) and (4.10), make use of some tract-level tabulations. By removing tract-level tabulations,  $\text{rHDF}_b$  is less constrained and so has a larger feasible region.

a reconstruction for block  $b'$ . Specifically, only optimization variables for block  $b'$  are used when forming the tract-level constraints, hence the left-hand side of the tract-level constraint is an underestimate of the counts in the tract-level tables.

Once we have  $\text{rHDF}^{S_0}(b')$  for a block  $b'$ , we search for the  $\text{rHDF}'(b')$  that is furthest from  $\text{rHDF}^{S_0}(b')$  while satisfying the same constraints. Specifically, for a given  $\text{rHDF}^{S_0}(b')$  corresponding to block  $b'$  in tract  $t$ , we solved the following IP:

$$(4.10) \quad \begin{aligned} \text{solvar}(\text{rHDF}^{S_0}, b') = 100 \times & \max_{\{\text{feasible rHDF}'\}} \frac{L_1\{\text{Hist}(\text{rHDF}^{S_0}(b')), \text{Hist}(\text{rHDF}'(b'))\}}{2N_{b'}} \\ \text{s.t. } \mathcal{T}_t[\text{tablename}, \text{rHDF}^{S_0}(b')] & \leq c_t^{\text{tablename}} \quad \forall \text{tablename} \in \text{Panel B of Table 2} \\ \mathcal{T}_b[\text{tablename}, \text{rHDF}^{S_0}(b')] & = c_b^{\text{tablename}} \quad \forall \text{tablename} \in \text{Panel A of Table 2.} \end{aligned}$$

Note that the tract-level tables in the *solvar* equation (4.10) appear in inequality constraints. Variables for records in other blocks  $b \neq b'$  within the same tract  $t$  do not appear in this optimization problem for block  $b'$ .

We note that the IP for the initial solution for  $\text{rHDF}^{S_0}$  is a strict relaxation of the constraints used for the reconstruction  $\text{rHDF}_{b,t}$  solving equation (4.4). This implies that the feasible region for  $\text{rHDF}^{S_0}$  is a superset of the feasible region for  $\text{rHDF}_{b,t}$ . Similarly, the *solvar* IP in equation (4.10) also searches for  $\text{rHDF}'$  from a strictly larger solution space. This property implies that  $\max(2\text{cumsolvar}(\text{rHDF}^{S_0}, B_t), 100)$  upper-bounds the *solvar* value for tract  $t$  that an attacker would get using the stronger tract-level constraints. In other words,  $\max(2\text{cumsolvar}(\text{rHDF}^{S_0}, B_t), 100)$  upper-bounds the percentage of records by which any two solutions to  $\text{rHDF}_{b,t}$  can differ because first, the union  $\cup_{b \in B_t} \text{rHDF}^{S_0}(b)$  is a solution to a problem with a strictly larger solution space than  $\text{rHDF}_{b,t}$ , and second,  $2 \sum_{b \in B_t} \text{solvar}(\text{rHDF}^{S_0}, b)$  upper-bounds the percentage of records by which any two solutions to this problem can disagree.

The problem relaxations we performed probably made our upper bound on solution variability much looser. Hence, strengthened (and even more concerning) solution variability bounds may be produced in the future. However, since summing the block-level solution to equation (4.10) and multiplying by 2 is also an upper bound on the exact solution variability for the tract-level problem, the large number of blocks with 0 block-level solution variability will still contribute 0 to the tract-level solution variability in the *agebin* schema. Thus, the variability in these blocks is already bounded by 0 and cannot get tighter. Tracts with 0 tract-level solution variability found in solving the optimization problem (4.10) must also have 0 solution variability in any stronger tract-level IP.

We found that solution variability could be readily computed using the optimization in equation (4.10) for all 6,207,027 blocks with positive population in the 2010 Census tabulations. This demonstrates that attackers have a public, computationally feasible method for independently identifying blocks for which aggregation into tables introduces no additional uncertainty about the underlying microdata beyond the SDL measures that were applied at the record level to generate the HDF. No access to confidential data is required to perform these solution variability calculations. Furthermore, population uniques found in blocks with 0 solution variability are provably population uniques in the HDF, again without using any confidential data. And population uniques using the *agebin* feature are provably population uniques on the exact age feature. Finally, incorporating additional SF1 tables to the ones shown in Table 2 can only decrease solution variability. Since we used only 18 of the 177 census block-level tables and 16 of the 84 census tract-level tables, our

solutions to equation (4.10) are also upper bounds on the solution variability of reconstructions that use additional tables.

## 5. MATCHING AND REIDENTIFICATION METHODOLOGY

To assess the quality of the reconstructed microdata and execute the reidentification experiments we perform several different types of matching between various data sources. Referring again to Figure 1, we now discuss the methodology employed to compute agreement between the reconstructed and confidential data and to measure the success of our reidentification experiments using those reconstructions.

For either  $\text{rHDF}_{b,t}$  or  $\text{rHDF}_b$ , our first-order assessment of the quality of the reconstructed microdata matches these reconstructions directly to both the HDF and CEF. This is not a record linkage assessment. It compares the reconstructed microdata directly to the source microdata for the contingency tables in SF1, namely HDF, and to the source microdata for HDF, namely CEF. We label this step the *agreement match* because it provides measures of agreement in record-level feature values between  $\text{rHDF}_{b,t}$  or  $\text{rHDF}_b$  and the confidential HDF and CEF. After the agreement match, we do record-linkage based reidentification matches to see how accurately an attacker can infer race and ethnicity from the reconstructed microdata. Thus, we link  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  separately to both commercial data and a specially constructed extract from the CEF called  $\text{CEF}_{atkr}$  that includes linking variables (quasi-identifiers) from the schema in equation (4.2) and the person identifier  $pik$  but no other variables—specifically, not *race* or *ethnicity*. These feature sets are shown in the rows COMCRL and  $\text{CEF}_{atkr}$  on Table 1.

By record-linkage of the quasi-identifiers  $\{block, sex, (age \text{ or } agebin)\}$  in reconstructed microdata to attacker databases that include names (feature  $pik$ ), we create *putative reidentifications*. To enhance the attacker’s database, we attach the data on  $\{race, ethnicity\}$  found on  $\text{rHDF}_{b,t}$  or  $\text{rHDF}_b$  to the  $\{pik, block, sex, (age \text{ or } agebin)\}$  information in the attacker’s database—either COMCRL or  $\text{CEF}_{atkr}$ . The feature sets for the records in these putative reidentification databases are shown in the rows labeled Putative  $\text{rHDF}_{b,t}$  and Putative  $\text{rHDF}_b$  in Table 1. Finally, to evaluate the accuracy of the putative reidentifications, and classify *confirmed reidentifications*, we match putative reidentifications to the full CEF, linking on  $\{pik, block, sex, (age \text{ or } agebin)\}$  and comparing the  $\{race, ethnicity\}$  inferred from the reconstructed microdata (attached to a putatively reidentified person) to that person’s actual census responses in the CEF. We label the reidentification *confirmed*, when  $\{pik, block, sex, (age \text{ or } agebin), race, ethnicity\}$  all match in either the schema in equation (4.2) for the feature *age* or the schema in Table 5 for the feature *agebin*. The feature sets for these confirmed reidentifications are shown in the rows labeled Confirmed  $\text{rHDF}_{b,t}$  and Confirmed  $\text{rHDF}_b$  in Table 1. Finally, we use the ratio of confirmed to putative identifications as the measure of precision or accuracy for the attack.

To make the meaning of this exercise as clear as possible, we state the attacker model we are simulating concisely here. The attacker is an entity external to the Census Bureau with no access to the confidential data contained in HDF or CEF. The attacker has access to all published 2010 Census data—every table in SF1, in particular. The attacker selects a subset (possibly the universe) of these tables and performs record-level reconstruction, possibly using the algorithms in this paper. The attacker also has access to an external database that contains name and *address* (or some other personal identifying information sufficient to tag a unique person like Social Security Number) and quasi-identifiers—features that match some of the features in SF1—specifically, census *block* (geocoded from *address*), *sex*, and *age*. Notice that we have explicitly used the same feature set definitions for the attacker’s database as we used in our reconstruction. This is an essential

characteristic of a record-linkage attack—the attacker knows enough about the definitions of the feature set for SF1 to construct quasi-identifiers with the same schemas. The attacker matches the external data to the reconstructed record-level data from SF1 using the matching variables (quasi-identifiers)  $\{block, sex, age\}$  and adds the other variables reconstructed from SF1 to the external database. These added variables can include any feature tabulated in SF1, including those tabulated for housing units and householders because those data can be reconstructed as part of the record for “person 1” or “householder,” the individual who completed the census responses for the persons living in the housing unit. In our experiments the extra variables are  $\{race, ethnicity\}$ .<sup>19</sup>

At this point the attacker is using the information from what we call putative reidentifications as record-level variables on the external database. The attacker may not care about the quality of these putative reidentifications; however, because the solution variability in the schema of our attack is 0 for 70% of all census blocks using just the 34 tables in Table 2, the attacker may be satisfied with the 97 million persons for whom they know with certainty they have exactly the information on the confidential internal database. Alternatively, the attacker can keep adding tables from SF1 until solution variability is 0 for as large a portion of the target population as desired. For all records for which solution variability is 0, the attacker knows with certainty that the data added from SF1 for those persons match the confidential source records exactly. That is, the attacker knows that they have an image of the confidential Hundred-percent Detail File (HDF) that is completely accurate in the schema of the feature set used for SF1 and the attack. Traditional SDL did not anticipate the possibility of reconstructing accurate microdata from published tables. That is the new feature of our experiments. However, the reidentification attacks we simulate using the record-level reconstructed data exactly match the textbook descriptions of such attacks. See, for example, Duncan et al. (2011, Figure 2.1, pp. 56-58).

In our experiments, we use the CEF itself as a labeled database to confirm the accuracy of inferences about  $\{race, ethnicity\}$ . An external attacker would need a similar labeled database to confirm the accuracy of those inferences. It need not be a complete enumeration like the CEF.

---

<sup>19</sup>Implementing additional features in the reconstructed data is outside the scope of this paper; however, it is straightforward to add the feature “relationship to householder.” We sketch the details here. See the documentation for Table P29 Household Type by Relationship (U.S. Census Bureau, 2012). Notice that the universe is “Total Population,” which implies that the marginal total in each of these block-level tables is the block population in Table P1. Create binary variables for the 20 mutually exclusive and exhaustive relationships defined in Table P29: family male householder, family female householder, spouse, biological child, adopted child, stepchild, grandchild, brother or sister, parent, parent-in-law, son-in-law or daughter-in-law, other relatives, nonrelatives, nonfamily male householder living alone, nonfamily male householder not living alone, nonfamily female householder living alone, nonfamily female householder not living alone, nonfamily nonrelatives, group quarters institutionalized person, and group quarters noninstitutionalized person. Add the statistics from Table P29 to the set in Table 2. Add the constraints implied by these tables to the IP in equations (4.4) and (4.10). To further reduce solution variability, if any, in the relationship variables and  $\{race, ethnicity\}$ , add Tables P29A–P29I Household Type by Relationship for major  $\{race, ethnicity\}$  categories. To further reduce the solution variability, if any, in the household population universe, add Table P30. To further reduce the solution variability, if any, for children add Tables P31 and P32. To further reduce the solution variability, if any, for persons ages 65 and older, add Table P34. It is not necessary to add the full variable “relationship to householder” to further reduce solution variability in the features  $\{race, ethnicity\}$ . Using only “lives in household” (all relationships except the last two) and “lives in group quarters” (the last two relationships), use Tables P16A–P16I Population in Households by Age for major  $\{race, ethnicity\}$  categories. Once the relationship “householder” has been reconstructed (all categories that contain the word householder), solution variability for the householder’s  $\{race, ethnicity\}$  can be further reduced by adding Tables P18A–P18I Household Type for major  $\{race, ethnicity\}$  categories. Many tract-level SF1 tables also contain information that can further reduce remaining solution variability.

Small-scale sample surveys or methods like those in Rocher et al. (2019) and Dick et al. (2023) could be used. Or the data steward could allow the publication of data about how accurate those inferences would be, as the Census Bureau is doing by releasing the statistics found in this paper. If those inferences are sufficiently more accurate than well-specified baselines, then the confidentiality protections have failed. Such failure is not a  $\{0,1\}$  event. It is a continuum on  $[0,1]$ . Our methodology calibrates this continuum using the precision of inferences about the features added to the external data from SF1 via the record-linkage attack—specifically, the ratio of confirmed to putative reidentifications. Our vulnerable population is persons who are different from their neighbors on race and ethnicity. We use the census block to define their neighbors. Other vulnerable populations in the 2010 Census include those for whom any characteristic collected on that census differs from their neighbors. See footnote 19 for further elaboration. Our methodology properly distinguishes between vulnerable populations—those where baseline statistical models have low precision and fail to make correct inferences—and nonvulnerable populations—those where baseline statistical models have high precision and generally make correct inferences. We use the results for vulnerable populations to illustrate the confidentiality protection failures in the 2010 Census publications. Specifically, the high reidentification precision rates for vulnerable populations are entirely due to the use of the vulnerable person’s data in the published tables. The most vulnerable persons are population uniques. Delete their data, and the tables that would have contained their responses are completely silent on the risky feature values; that is, the precision of baseline statistical inferences is exactly 0. The vulnerable populations were supposed to be protected by the use of record-level swapping targeting specific population-unique households, but those protections did not recognize how widespread such vulnerable populations were nor how their data could be reconstructed from the ensemble of tables. This confidentiality protection failure can be addressed within a variety of SDL frameworks. We use our reconstruction and reidentification methodology to evaluate three such frameworks: the 2020 Census DAS, which uses a differential privacy framework; enhanced versions of the household swapping framework used for the 1990, 2000 and 2010 Censuses; and the incomplete suppression system used for the 1980 Census.

**5.1. Agreement Match.** Algorithm 1 is the basic matching algorithm used generically as part of the agreement, putative, and confirmation matches. Given two databases and a set of common features, Algorithm 1 matches records on the set of features exactly and without replacement. The algorithm iterates over the rows in the left database ( $L$ ) searching, in order, over the rows in the right database ( $R$ ) to look for the first (if any) record that matches on all the selected features. If a matching record is found, the matching records in the left and right databases are both removed and the algorithm continues to the next record in the left database, again looking for a match in the right database. Notice that an essential feature of this matching algorithm is that every record in the left and right databases is at risk for one, and only one, match. It is not possible for a common record type in, say, the right database to be linked to many records in the left database. Failure to enforce this condition results in spurious claims about match rates as, for example, in Ruggles and Van Riper (2022).

The  $\text{rHDF}_{b,t}$ ,  $\text{rHDF}_b$ , CEF, and HDF have an overlapping feature set that supports the schema in equation (4.2), namely  $\{block, sex, age, race, ethnicity\}$ , as well as the schema in Table 5 supporting IP (4.5) where  $age$  is replaced by  $agebin$ . In order to measure how well reconstructed records match the underlying confidential data in HDF and CEF, we use Algorithm 2 to match the reconstructed microdata to our confidential databases on common features. Algorithm 2 works block-by-block implementing Algorithm 1 in two passes. First it finds all matches using  $\{block, sex, age, race, ethnicity\}$ , and then it finds any remaining matches using  $\{block, sex, agebin, race, ethnicity\}$ . The



**Algorithm 1** Match

---

**Require:** Data  $L$ ,  $R$ , and a set of features  $P$  where  $p = \dim(P)$ , that  $L$  and  $R$  have in common. The notation  $L[l, \{1, \dots, p\}]$  selects row  $l$  and features  $1, \dots, p$  from  $L$  and similarly for  $R[r, \{1, \dots, p\}]$ .

**Returns:** Index  $M$  of link records

**Returns:** Data  $L, R$  reduced to non-matches

**Returns:** Count of matches

```

1: procedure MATCH( $L, R, P$ )
2:   Match  $\leftarrow 0$ 
3:   for  $l \leftarrow 1$  to  $\text{rows}(L)$  do
4:     for  $r \leftarrow 1$  to  $\text{rows}(R)$  do
5:       if  $L[l, \{1, \dots, p\}] = R[r, \{1, \dots, p\}]$  then                                 $\triangleright$  MATCH = TRUE
6:         pop( $l$ );pop( $r$ )                                                                 $\triangleright$  Remove records indexed by  $l$  and  $r$ 
7:          $M \leftarrow (M, \{l, r\})$                                                      $\triangleright$  Append to link index
8:         BREAK                                                                       $\triangleright$  Break out of  $r$  loop
9:       end if
10:    end for
11:  end for
12:  Match  $\leftarrow \text{rows}(M)$                                                              $\triangleright$  Count
13:  return  $L, R, \text{Match}, M$                                                              $\triangleright L$  and  $R$  have been reduced by Match records
14: end procedure

```

---

989 algorithm returns the unmatched records, counts of the matched records in both passes, and indices  
 990 of the matched records in the original database for both passes by census block.

**Algorithm 2** Agreement

---

**Require:** Data  $L$ , with  $n$  records and features  $P = \{\text{block, sex, race, ethnicity, age, agebin}\}$

**Require:** Data  $R$ , with  $m$  records and features  $P = \{\text{block, sex, race, ethnicity, age, agebin}\}$   
 block is the geo identifier on  $L$  and  $R$

```

1: procedure AGREEMENT( $L, R$ )
2:    $P_1 \leftarrow \{\text{block, sex, race, ethnicity, age}\}$                                  $\triangleright$  Matching Features Pass 1
3:    $P_2 \leftarrow \{\text{block, sex, race, ethnicity, agebin}\}$                              $\triangleright$  Matching Features Pass 2
4:   for  $\text{block} \in L$  do
5:      $L_{\text{block}} \leftarrow \text{Select } \text{block} \in L$ 
6:      $R_{\text{block}} \leftarrow \text{Select } \text{block} \in R$ 
7:     ExactAgeMatch[block]  $\leftarrow 0$                                                  $\triangleright$  Indexed by [block]
8:     BinAgeMatch[block]  $\leftarrow 0$                                                    $\triangleright$  Indexed by [block]
9:      $L', R', \text{ExactAgeMatch}[\text{block}], M' \leftarrow \text{MATCH}(L_{\text{block}}, R_{\text{block}}, P_1)$      $\triangleright$  Pass 1
10:     $L'', R'', \text{BinAgeMatch}[\text{block}], M'' \leftarrow \text{MATCH}(L', R', P_2)$              $\triangleright$  Pass 2
11:  end for
12:  return  $M', M'', \text{ExactAgeMatch}, \text{BinAgeMatch}$ 
13: end procedure

```

---

991 **5.2. Reidentification Match.** Our reconstruction-abetted reidentification attack uses the com-  
 992 mon features between the reconstructed database and the attacker database (either COMCRL or  
 993 CEF<sub>atkr</sub>) to attach features previously unknown to the attacker, in this case  $\{\text{race, ethnicity}\}$ , to  
 994 the attacker database by linking on the common features  $\{\text{block, sex, (age or agebin)}\}$ . Thus, the  
 995 attacker learns information about the database members that was previously not available. To  
 996 evaluate the strength of the inference an attacker might achieve from access to improved auxiliary

997 data, we compare the results from the lower-quality commercial data that were acquired by the  
 998 Census Bureau contemporaneously with the 2010 Census with higher-quality attacker database  
 999 formed by extracting  $\{pik, block, sex, age\}$  directly from the CEF, called  $CEF_{atkr}$ . When  $CEF_{atkr}$   
 1000 is the attacker database, we exclude  $pik$  from the putative match linkage, using only the linking  
 1001 features  $\{block, sex, (age \text{ or } agebin)\}$ , as we do with the commercial data. In general, we denote  
 1002 the attacker’s external database as  $D_X$  and the reconstructed database as  $D_R$ . Note that  $D_X$  may  
 1003 have incomplete coverage,  $rows(D_X) < rows(D_R)$  and may contain incorrect information relative  
 1004 to the confidential data.

1005 A successful match between records in  $D_R$  and  $D_X$ , based on the common features  $\{block, sex,$   
 1006  $(age \text{ or } agebin)\}$ , is called a putative reidentification, since the attacker must collect additional in-  
 1007 formation, possibly through independent field work or simulation studies, to verify that the putative  
 1008 match is correct.<sup>20</sup> Our record linkage algorithm for generating putative matches is shown in Algo-  
 1009 rithm 3. Like the agreement match algorithm, Algorithm 3 consists of two passes that first match  
 1010 on  $age$  for the complete input databases and then match on  $agebin$  for the unmatched residual from  
 1011 pass one. The algorithm returns an enhanced attacker external database  $D_{X+}$  consisting of records  
 1012 from  $D_X$  for which a match was found in the reconstructed database with sensitive features  $\{race,$   
 1013  $ethnicity\}$  appended.

1014 Given the enhanced attacker external database  $D_{X+}$ , we next determine if the  $\{race, ethnicity\}$   
 1015 values appended from the reconstructed data match the confidential census responses in the CEF  
 1016 exactly. Algorithm 4 encodes this procedure. Like the agreement and putative reidentification  
 1017 algorithms, Algorithm 4 consists of two passes that first match on  $age$  for the complete input  
 1018 databases and then match on  $agebin$  for the unmatched residual from pass one. Records that meet  
 1019 the matching criteria are called confirmed reidentifications.

---

<sup>20</sup>If the process of classifying the putative reidentifications in the reconstructed data as “correctly matched” or “incorrectly unmatched” to the external database is considered a statistical classifier, then the attacker needs a labeled training sample.

**Algorithm 3** Putative reidentification, using  $D_R$ **Require:** Data  $L = D_R$ , with  $n$  records and features  $P_R = \{\text{block, sex, race, ethnicity, age, agebin}\}$ **Require:** Data  $R = D_X$ , with  $m$  records and features  $P_X = \{\text{pik, block, sex, age, agebin}\}$  $\text{block}$  is the geo identifier on  $L$  and  $R$ 

```

1: procedure PUTATIVE( $L, R$ )
2:    $P_1 \leftarrow \{\text{block, sex, age}\}$  ▷ Pass 1 matching features
3:    $P_2 \leftarrow \{\text{block, sex, agebin}\}$  ▷ Pass 2 matching features
4:    $P_S = \{\text{race, ethnicity}\}$  ▷ Sensitive features
5:   for  $\text{block} \in L$  do
6:      $L_{\text{block}} \leftarrow \text{Select } \text{block} \in L$ 
7:      $R_{\text{block}} \leftarrow \text{Select } \text{block} \in R$ 
8:      $\text{ExactAgeMatch}[\text{block}] \leftarrow 0$  ▷ Indexed by [block]
9:      $\text{BinAgeMatch}[\text{block}] \leftarrow 0$  ▷ Indexed by [block]
10:     $L', R', \text{ExactAgeMatch}[\text{block}], M' \leftarrow \text{MATCH}(L_{\text{block}}, R_{\text{block}}, P_1)$  ▷ Pass 1
11:     $L'', R'', \text{BinAgeMatch}[\text{block}], M'' \leftarrow \text{MATCH}(L', R', P_2)$  ▷ Pass 2
12:  end for
13:  return  $M', M'', \text{ExactAgeMatch}, \text{BinAgeMatch}$ 
14: end procedure
  Attach sensitive features
15:  $D_X^1 \leftarrow D_X \cap_r M' \cap_l D_R[l, P_S]$  ▷ Exact age matches
16:  $D_X^2 \leftarrow D_X \cap_r M'' \cap_l D_R[l, P_S]$  ▷ Bin age matches
17:  $D_{X+} \leftarrow (D_X^1, D_X^2)$ 

```

**Algorithm 4** Confirmed reidentification**Require:** Data  $L = D_{X+}$ , with  $q < n$  records and features  $P_{CEF} = \{\text{pik, block, sex, race, ethnicity, age, agebin}\}$ .**Require:** Data  $R = D_{CEF}$ , with  $n$  records and features  $P_{CEF}$ .

```

1: procedure CONFIRMATION( $L, R$ )
2:    $P_1 \leftarrow \{\text{pik, block, sex, race, ethnicity, age}\}$  ▷ Pass 1 matching features
3:    $P_2 \leftarrow \{\text{pik, block, sex, race, ethnicity, agebin}\}$  ▷ Pass 2 matching features
4:   for  $\text{block} \in L$  do
5:      $L_{\text{block}} \leftarrow \text{Select } \text{block} \in L$ 
6:      $R_{\text{block}} \leftarrow \text{Select } \text{block} \in R$ 
7:      $\text{ExactAgeMatch}[\text{block}] \leftarrow 0$  ▷ Indexed by [block]
8:      $\text{BinAgeMatch}[\text{block}] \leftarrow 0$  ▷ Indexed by [block]
9:      $L', R', \text{ExactAgeMatch}[\text{block}], M' \leftarrow \text{MATCH}(L_{\text{block}}, R_{\text{block}}, P_1)$  ▷ Pass 1
10:     $L'', R'', \text{BinAgeMatch}[\text{block}], M'' \leftarrow \text{MATCH}(L', R', P_2)$  ▷ Pass 2
11:  end for
12:  return  $M', M'', \text{ExactAgeMatch}, \text{BinAgeMatch}$ 
13: end procedure

```

1020 **5.3. Statistical Baselines.** In order to capture privacy-violating (non-LOO) inferences rather  
 1021 than statistical or generalizable (LOO) inferences, the results of the reidentification attack need to  
 1022 be compared to inferences that would be possible in a privacy-preserving counterfactual setting in  
 1023 which the *same* data are provided, except that a target individual's record has been removed. In  
 1024 this case, we would compare inferences made about the removed person from the published 2010  
 1025 Census data to inferences that would be made in the counterfactual world in which the person  
 1026 was removed. Exact comparisons of this sort are difficult because they involve removing a target

individual, re-swapping and re-tabulating the data, performing reconstruction and reidentification to make inferences about the individual, and then repeating this process for every person in the United States, or at least a meaningful subset.

In lieu of explicitly leaving each record out, as in the first-best approach, we develop baselines that focus on small populations (census blocks) and emphasize inferences about persons not matching the modal race/ethnicity in their block. The intuition is that persons with nonmodal  $\{race, ethnicity\}$  and who are unique on  $\{block, sex, age\}$  or  $\{block, sex, agebin\}$ , according to the operative schema, are of particular interest. In these cases, the reconstruction-abetted reidentification attack could not have even identified a corresponding record as a putative reidentification had the target record been absent from the CEF. These cases are not uncommon—fully 44% of all persons in the CEF are unique on these three variables. We posit two “statistical guessing” baselines that generate inferences by using either the modal  $\{race, ethnicity\}$  in a block (MDG, for modal guesser), or by guessing with probabilities proportional to the frequency of each  $\{race, ethnicity\}$  in a block (PRG, for probability guesser). We compare the performance of these statistical baselines to the performance achieved by the reconstruction-abetted reidentification attack. Our statistical baselines simulate the counterfactual world in which statistical (non-privacy-violating) methods based on the CEF are used to generate an inference about a person who had been removed from the CEF.

Using these statistical baselines, we emphasize the analysis of small populations that differ significantly from the people around them because inferences on these target populations are likely to be especially sensitive to the presence or absence of a target person’s record. We attempt to approximate performance in the counterfactual world (removing the target person’s record) by comparing to attackers armed with statistical information. By considering only a small subset of possible inferences and by allowing these statistical guessers to use information that implicitly treats the release of block-level  $race \times ethnicity$  tables even in very low-population blocks as statistical, this approach probably underestimates the true extent of confidentiality violations. However, it is computationally tractable and identifies a class of inferences and a group of target persons for which it is difficult to view the resulting inference precision as anything but a confidentiality violation.

We illustrate these baselines with an example: given the homogeneity of race and ethnicity within blocks, it would be reasonable to use the  $\{race, ethnicity\}$  data from other individuals in a block to make inferences about the target person. For example, suppose a block consisted of 10 people  $\{r_1, \dots, r_{10}\}$ , with the first 9 being White-alone, and the 10<sup>th</sup> person being Asian-alone. All are non-Hispanic.<sup>21</sup> When the target person is  $r_1$ , the attacker in the counterfactual world ( $r_1$ ’s record is removed) would see 8 White-alone individuals and 1 Asian-alone. MDG would predict that the target person is White while PRG would guess randomly in proportion to each type, assigning White-alone with probability 8/9 and Asian-alone with probability 1/9. Alternatively, if the target person is  $r_{10}$ , the attacker in the counterfactual world would see 9 White-alone individuals, and both the modal and proportional guessers would incorrectly guess White-alone. Repeating such an exercise across all individuals would result in a modal guesser achieving an accuracy of 90% (the only mistake coming when the target individual is Asian-alone) while the expected accuracy of the proportional guesser is approximately 81.1%. To simplify the calculations of these baselines, we use upper bounds. An upper bound on the accuracy of the modal guesser is the fraction of the block’s population that reports the modal  $\{race, ethnicity\}$  in the block. The upper bound on the

<sup>21</sup>In Census Bureau nomenclature, White-alone means the individual responded White in the WHITE set of schema 4.2 and did not select any of the other five choices. Similarly, the Asian-alone respondent selected Asian from the ASIAN schema and did not select any of the other five choices. All 10 respondents selected Not Hispanic or Latino in the HISP schema.

1069 accuracy of the proportional guesser is  $\sum_i p_i^2$ , where  $\{p_1, p_2, \dots\}$  are the proportions of the block's  
 1070 population of each *race*  $\times$  *ethnicity* cell.

1071 Note that the modal guesser is targeting overall accuracy and would perform poorly when guess-  
 1072 ing the race and ethnicity of minorities within a block. The proportional guesser would perform  
 1073 better with minorities at the expense of overall accuracy, and so both baselines deserve consid-  
 1074 eration. Comparing the accuracy of reidentification experiments in small, nonmodal populations  
 1075 involving the reconstructed microdata (rHDF<sub>b,t</sub> and rHDF<sub>b</sub>) and the statistical baselines (MDG  
 1076 and PRG) estimates the improved inference about these individual due to the used of their actual  
 1077 census responses in the data—the privacy cost of the individual's participation in the census. In  
 1078 terms of causal inference, the statistical baselines represent alternative estimates of the counterfac-  
 1079 tual world (in which the target person's data were not used in the publications) inference accuracy  
 1080 whereas the inferences from the reconstructed data represent the accuracy of the observed world  
 1081 (in which the target person's data were used in the publications).

1082 There are two additional points worth making. The first is that the feature set  $\{\textit{race}, \textit{ethnicity}\}$   
 1083 can also be inferred using the name of the target individual (in which case, the name needs to  
 1084 be part of the observed world *and* counterfactual inferences). However, since the reconstruction  
 1085 and reidentification algorithms used in this paper do not model this interaction, it is reasonable  
 1086 to omit it from the baseline. What is important for the comparison between the reconstruction  
 1087 and the statistical baseline results is: (1) all else being equal, the estimated privacy cost of being  
 1088 included in the census data publications is the difference in inference accuracy of the reconstruction  
 1089 versus the statistical baseline,<sup>22</sup> and (2) the contrast between the reconstruction and the statistical  
 1090 baseline inferences gives a lower bound on this privacy cost—the actual confidentiality breach could  
 1091 be larger but not smaller.

1092 Furthermore, had the reconstruction used additional variables in the published tables (including  
 1093 household composition), the reconstructed data could have included additional attributes that are  
 1094 much harder to predict using only statistical information than are race and ethnicity. In those cases,  
 1095 the gap between inference due to reidentification and statistical inference would be much larger.  
 1096 Hence, this is another sense in which the experiments we performed understate the true privacy  
 1097 cost.

1098 In order to assess the relative accuracy of reidentifications using either the MDG or PRG, we  
 1099 generate two databases, one containing the modal value of *race*  $\times$  *ethnicity* in the census block (used  
 1100 by MDG) and the other containing one guess per record using the probabilities proportional to the  
 1101 distribution of *race*  $\times$  *ethnicity* in the census block (used by PRG). Specifically, we use the HDF to  
 1102 create a frame of  $\{\textit{block}, \textit{sex}, \textit{agebin}\}$  to which we attach the statistical baseline guesses of  $\{\textit{race},$   
 1103 *ethnicity* $\}$ . For the MDG database, we then compute, for each *block*, the modal *race*  $\times$  *ethnicity*  
 1104 and attach it to each record in the block.<sup>23</sup> For the PRG database, we randomly select a  $\{\textit{race},$   
 1105 *ethnicity* $\}$  pair for each record, guessing each  $\{\textit{race}, \textit{ethnicity}\}$  in proportion to its relative frequency

<sup>22</sup>A large difference between the reconstruction accuracy and the statistical baseline accuracy when less information is used, that is, when name is not used for the race/ethnicity inference, is particularly concerning because it directly indicates that confidentiality has already been breached and that additional information from the census response could be precisely revealed in a larger attack based on all SF1 tables.

<sup>23</sup>Given a tie in the block-level modal  $\{\textit{race}, \textit{ethnicity}\}$  or a block population of 1, we attempt to assign the block-group-level modal value. In the rare event that no block group mode can be assigned, either because of a block-group-level tie or a block group population of 1, we assign the block the national modal  $\{\textit{race}, \textit{ethnicity}\}$ . A similar exercise could be performed using published tables. One could use the tabulations in tables P12 and P14 from SF1 to create a frame of microdata records containing  $\{\textit{block}, \textit{sex}, \textit{agebin}\}$ , then use tables P8 and P9 to compute the block-level MDG modal values.

within the block.<sup>24</sup> We substitute each of these statistical baselines for the reconstructed HDF in the reidentification experiments to generate the baseline statistics. Note that the  $\text{rHDF}_b$ ,  $\text{rHDF}_{b,t}$ , MDG, and PRG databases have identical putative match rates using the binned age schema in Table 5 by construction, since all rely on an identical frame of  $\{block, sex, agebin\}$  and both reconstructions perfectly replicate this frame because tables P12 and P14 are fully saturated for  $\{block, sex, agebin\}$ . The feature sets for MDG and PRG are shown in the the rows so labeled in Table 1.

Finally, we define several reidentification metrics that capture the accuracy of inferences an attacker can make about the target sensitive characteristics. Putative reidentifications are the records for which the attacker attempts to infer  $\{race, ethnicity\}$ . Confirmed reidentifications are the records for which the attacker is correct. The attacker's precision is the ratio of the number of correct inferences to the number of attempted inferences. Thus, we define the putative and confirmed reidentification rates as well as the precision rate as follows:

$$(5.1) \quad \text{Putative Reidentification Rate} = 100 \times \frac{\text{count of putative reidentification records}}{\text{count of attacker records}},$$

$$(5.2) \quad \text{Confirmed Reidentification Rate} = 100 \times \frac{\text{count of confirmed reidentification records}}{\text{count of attacker records}},$$

$$(5.3) \quad \text{Reidentification Precision Rate} = 100 \times \frac{\text{count of confirmed reidentification records}}{\text{count of putative reidentification records}}.$$

We use these statistics to compare our reidentification results with nonstatistical baselines like the HDF itself (i.e., how much better would the reidentification be if the reconstruction were a perfect match to HDF) and with the statistical baselines MDG and PRG. In all cases, the attacker model is the same. The attacker begins with tabular summaries produced from a confidential source, the HDF. Then, the attacker reconstructs record-level images of the persons represented in the tables using either the schema  $\text{rHDF}_{b,t}$  or  $\text{rHDF}_b$  as illustrated in Table 1. Next, the attacker uses a record-level image that contains identifiable names (*pik*, in this work) and linking variables using the same schema as the reconstructed data, as in the COMCRL and  $\text{CEF}_{atkr}$  rows of Table 1, to perform a record-linkage attack that associates the features *race* and *ethnicity* with each record in the attacker database. This step produces a record-level database with the features noted in the putative rows of Table 1. Finally, we assess the accuracy of the attack by linking the putative files back to the original confidential data using the features *pik* and *block* for linkage, but assessing the accuracy by comparing all features in the row CEF in Table 1.

In summary, the principal indicator of a confidentiality breach is that the precision rate in equation (5.3) for inferences based on the reconstructed microdata substantially exceeds the precision rate for inferences based on the statistical baselines. The gain in precision, which we will also call the gain in inference accuracy, from the reconstructed data compared to the statistical baseline need not be infinite to constitute a confidentiality breach. The upper-bound on the precision rate of any inference is the precision of the that inference based on the CEF itself, since we take it as self-evident that releasing every person record in the CEF for the feature set  $\{block, sex, age, race, ethnicity\}$  is a breach of confidentiality.

---

<sup>24</sup>Similarly to MDG, the public tables can be used to proportionally select  $\{race, ethnicity\}$  PRG values.

1142 6. RECONSTRUCTION SOLUTION VARIABILITY IS SO LIMITED THAT SIMULATION ASSESSMENT  
 1143 IS UNNECESSARY

1144 We assess the agreement of the image of HDF embodied in  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  by comparing  
 1145 those reconstructed microdata files to HDF and CEF themselves using Algorithm 2. However, before  
 1146 assessing the agreement accuracy of  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$ , we report results on the solution variability  
 1147 in our reconstruction experiments. If the solutions are highly variable, then simulation assessments  
 1148 like those of Dick et al. (2023) and Rocher et al. (2019) rather than single-reconstruction assessments,  
 1149 as we propose, would be more appropriate. Table 6 shows every fifth percentile of the cumulative  
 1150 distribution of *solvar*, which is always assessed using the  $\{\text{block}, \text{sex}, \text{agebin}, \text{race}, \text{ethnicity}\}$  feature  
 1151 set for the reasons discussed in Section 4.5. The cumulative distribution displayed in the table is  
 1152 over census blocks, not persons. Thus there are  $6,207,027/20 = 310,351$  blocks in each cell of the  
 1153 cumulative distribution, the population of which is shown in the “Population ( $\times 10^{-3}$ )” column.

**Table 6.** Empirical Percentiles for Block-Level Solution Variability

Block Percentile (%)	<i>solvar</i> (%)	Maximum <i>solvar</i> (%)	Population ( $\times 10^{-3}$ )	Cumulative Population ( $\times 10^{-3}$ )	Cumulative <i>solvar</i> (%)	Maximum Cumulative <i>solvar</i> (%)
5	0.0	0.0	6,398	6,398	0.0	0.0
10	0.0	0.0	6,376	12,774	0.0	0.0
15	0.0	0.0	6,381	19,155	0.0	0.0
20	0.0	0.0	6,372	25,527	0.0	0.0
25	0.0	0.0	6,391	31,918	0.0	0.0
30	0.0	0.0	6,376	38,294	0.0	0.0
35	0.0	0.0	6,376	44,670	0.0	0.0
40	0.0	0.0	6,376	51,046	0.0	0.0
45	0.0	0.0	6,381	57,427	0.0	0.0
50	0.0	0.0	6,372	63,799	0.0	0.0
55	0.0	0.0	6,412	70,211	0.0	0.0
60	0.0	0.0	6,376	76,587	0.0	0.0
65	0.0	0.0	6,380	82,967	0.0	0.0
70	0.0	0.0	14,271	97,238	0.1	0.2
75	1.7	3.4	34,272	131,510	0.9	1.8
80	4.7	9.3	28,281	159,790	1.8	3.6
85	7.3	14.6	28,776	188,566	2.9	5.8
90	10.5	21.1	30,319	218,884	4.2	8.4
95	14.6	29.3	36,466	255,351	6.1	12.3
100	21.1	42.1	53,395	308,746	10.0	20.1

Notes: This table is based entirely on public data. All statistics are displayed to full precision. Solution variability is the statistic *solvar* in equation (4.10), which has been sorted in increasing order by census block. Maximum *solvar* is an upper bound on the solution variability of any reconstruction as given in equation (4.7). Cumulative *solvar* is the statistic *cumsolvar* in equation (4.8) when the blocks have been sorted in increasing order of *solvar*. Maximum cumulative *solvar* is an upper bound on the cumulative solution variability of any solution to the  $\text{rHDF}_{b,t}$  reconstruction. Percentiles are defined over blocks, not persons. Block ties in the definition of *solvar* percentiles were broken randomly. Consequently, running the replication package for this table may result in minor variations in the population, cumulative population, and cumulative solution variability columns.



For 70% of all blocks, representing 97,238,000 person records, solution variability is 0. The reconstructed records for those individuals are guaranteed to match their confidential HDF records exactly using the *agebin* schema. The maximum solution variability for any block in the 75<sup>th</sup> quantile is 3.4%. Since there are 34,272,000 people in this quantile, this means that at most 1,165,000 records in this quantile can differ from their confidential source on *race* or *ethnicity*. The maximum cumulative solution variability given any feasible solution for all census blocks, containing all 308,746,000 persons, is just 20.1%. Because this bound applies to any feasible solution and the solution variability IP of equation (4.10) upper-bounds *solvar* even when using additional constraints, in *any* other reconstruction solution for either  $\text{rHDF}_b$  or  $\text{rHDF}_{b,t}$  no more than 20.1% of all records can differ from their HDF record on the value of even a single feature, evaluated on the  $\{\text{block}, \text{sex}, \text{agebin}, \text{race}, \text{ethnicity}\}$  schema, and all the additional variability in solutions for  $\text{rHDF}_{b,t}$ , relative to  $\text{rHDF}_b$  must be within *agebin* categories. Thus, if *agebin* is sufficient for high agreement and reconstruction precision, the additional solution variability of the feature *age* within the feature *agebin* does not matter.

Finally, we note that Abowd and Hawes (2023) and Hawes (2022) report reconstruction agreement and solution variability results based on 32 of the 34 tables shown in Table 2—excluding P8 and P10.<sup>25</sup> When those two tables are omitted, solution variability is 0 for only 65% of blocks (82.9 million persons), demonstrating empirically the mathematical property of the solution variability IP (4.10)—as more tables are added the solutions become less variable. In this case, two tables with additional  $\{\text{race}, \text{ethnicity}\}$  data for adults increased the number of 0 solution variability records by 14.3 million. That is 14.3 million additional people for whom the attacker is certain that the reconstructed record matches the HDF record exactly using the *agebin* schema.

Our solution variability results imply that for much of the U.S. population the record-level image of the features used to create the census tract and block-level data shown in Table 2 is essentially an exact copy of HDF on the binned-age schema. Thus, the SF1 data shown in Table 2 are equivalent to the microdata HDF records for the  $\{\text{block}, \text{sex}, \text{agebin}, \text{race}, \text{ethnicity}\}$  feature set. The release of these microdata was prohibited by the 2010 Census disclosure avoidance rules (McKenna, 2019a). Permission to release the reconstructed HDF was approved in 2022 under clearance number CBDRB-FY22-DSEP-004. The public replication archive for this paper includes a sample of the reconstructed records in 29 tracts with 0 solution variability, all necessary inputs and programs to reconstruct the entire 308,745,538 person records for  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  from public data, and everything required to confirm our solution variability results. We conclude from Table 6 that evaluation of the vulnerability of the reconstructed data to record-linkage attacks can be assessed without using simulation methods. The upper-bound on the 100% confidence interval for any percentage point solution variability statistic  $s$ , when computed on the universe of reconstructed records, reported in these results is  $[\max(0, s - 20.1), \min(100, s + 20.1)]$ . When the statistic  $s$  is calculated on the universe with 0 solution variability, the upper-bound on the 100% confidence interval is  $s \pm 0$ .<sup>26</sup>

Table 7 shows the percent of population by census block size, for all blocks, and for those with 0 reconstruction solution variability. Over 99% of the population in the smallest blocks are in blocks where there is only one set of microdata records consistent with the published tables, meaning that

<sup>25</sup>These results were the basis for presentations the Census Bureau’s Scientific Advisory Committee, whose working group on differential privacy was monitoring the research and implementation decisions underlying the 2020 Census Disclosure Avoidance System.

<sup>26</sup>Because the reconstruction target is a finite database, HDF, and the *solvar* IP in equation 4.10 upper bounds any feasible reconstruction, the meaning of the term 100% confidence interval is that no feasible solution outside the stated confidence interval exists.

**Table 7.** Population Uniques and Solution Variability by Census Block Size

Census Block Size				Zero Solution Variability			
	Blocks	Population ( $\times 10^{-3}$ )	Unique (%)	Count Blocks	Count ( $\times 10^{-3}$ )	Count (%)	Count (%)
1-9	1,823,665	8,070	81.7	1,815,218	8,011	99.5	99.3
10-49	2,671,753	67,598	50.3	2,096,508	48,409	78.5	71.6
50-99	994,513	69,073	26.9	324,641	21,474	32.6	31.1
100-249	540,455	80,021	12.2	67,884	9,156	12.6	11.4
250-499	126,344	42,911	3.4	3,718	1,174	2.9	2.7
500-999	40,492	27,029	0.8	308	196	0.8	0.7
1,000+	9,805	14,043	0.2	105	169	1.1	1.2

Notes: Census Block Size is the population range in the census block. The Blocks, Population, and Zero Solution Variability Count statistics are displayed to full precision because they can be determined entirely from public data. The Unique (%) column is based on the CEF and rounded to no more than four significant digits to conform to disclosure limitation requirements. Unique (%) shows the percentage of total population in the block that are data-defined and unique for values of the feature set  $\{block, sex, agebin\}$ .

a population unique on  $\{block, sex, agebin\}$  is identified with certainty. Even among blocks with population from 10 to 49, 71.6% of individuals are in blocks with unique reconstructed microdata, meaning that in those blocks a population unique on  $\{block, sex, agebin\}$  is also identified with certainty. Among blocks with 50-99 individuals, 0 solution variability blocks are less common, but still substantial. Overall, 70% of all blocks had no solution variability, representing 97,238,000 persons, as shown in Table 6. Since a record that is population unique on the feature set  $\{block, sex, agebin\}$  must also be unique on  $\{block, sex, age\}$ , no access to confidential data is required to learn the uniqueness of the most basic set of quasi-identifiers—residence location, sex, and age—and, therefore, the associated feature values  $\{race, ethnicity\}$  in the confidential HDF. Traditional SDL considers this exposure of population uniqueness in released data *de facto* prohibited disclosure: “[i]f a unit is population unique then disclosure will occur if a snooper knows it is unique” Duncan et al., 2011, pp. 42-43). Swapping the confidential CEF to create the confidential HDF introduces some uncertainty in the inference about the learned feature values  $\{race, ethnicity\}$ , but that uncertainty is upper bounded by the swap rate, which the Office of National Statistics in the United Kingdom has acknowledged by publishing the swap rate and stating that adding additional noise to every tabular summary was also required, effectively mimicking the consequences of the U.S. Census Bureau’s 2020 DAS without using a differential privacy framework (Dove et al., 2021; Office of National Statistics, UK, 2023).

## 7. RECONSTRUCTED DATA STRONGLY AGREE WITH THE CONFIDENTIAL DATA

Having established that (1) there is no solution variability for 97,238,000 records (more than 1/3 of the data-defined records); (2) no more than 20.1% of all records can differ on the value of a single feature in any alternative reconstruction; and, finally, (3) adding tables to the reconstruction cannot increase solution variability and usually decreases it (e.g., adding Tables P8 and P10 raised the percentage of 0-*solvar* blocks from 65% to 70%), we conclude that simulation-based assessments are not required. We perform agreement and reidentification assessments using the methods described in Section 5.

We begin by comparing  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  directly to HDF and CEF. To calibrate this comparison, we also compare HDF to CEF, which measures the agreement between the confidential databases. The agreement of HDF with CEF shows the effects of the record-level statistical disclosure methodology that was applied to create HDF from CEF. It also represents an upper bound on the agreement rate for any reconstructed HDFs compared to the CEF. If our reconstructions were perfect images of the HDF, then their agreement with the CEF would be identical to that of HDF. Any incremental error in the agreement of reconstructed HDFs with the CEF can thus be attributed to reconstruction error.

Agreement results are based on the matching methodology described in Section 5.1. We tabulate the number of records that agree on the reconstructed features relative to the total number of records; that is, we consider all records in HDF and CEF, not just those that are data-defined, when assessing reconstruction agreement. When reporting on matches based on the *agebin* feature, we count the records that matched on either exact age or binned age from Algorithm 2. Therefore, exact-age results always lower bound binned-age results.

Table 8 shows the agreement match results for all census blocks (top panel) and for each of the seven census block-size intervals we considered throughout this work. Note that since HDF-HDF and CEF-CEF comparisons always yield 100% agreement, these rows are not shown. Consider first the HDF-CEF comparison. We find that the error introduced by the 2010 SDL methodology is relatively small. Less than 4% of all person records disagree using either the *age* or *agebin* schema. The reconstruction  $\text{rHDF}_{b,t}$  agrees with the HDF using exact age for 48.5% of records, and using binned age for 95.2% of records. Comparing  $\text{rHDF}_{b,t}$  to CEF decreases the agreement rates only slightly for binned age (from 95.2% to 91.9%) or exact age match (from 48.5% to 46.6%), indicating that many of the reconstructed ages are off by a small number of years, but that this error in the reconstruction is entirely within the narrow bands of the *agebin* schema, implying that reidentification based on binned age will be almost as reliable as using exact age, especially for the population 21 and under, for which the *agebin* schema is the same as the exact age schema.

The  $\text{rHDF}_b$  reconstruction agreement rates with HDF and CEF are all slightly less than the respective  $\text{rHDF}_{b,t}$  agreement rates. Thus, using tract-level information improves the reconstruction accuracy relative to using only block-level tables even when using the binned-age feature. The agreement gain of  $\text{rHDF}_{b,t}$  over  $\text{rHDF}_b$  with respect to the HDF of 2.3 percentage points when comparing with the binned-age feature ( $= 95.2 - 92.9$ ) is entirely an improvement in  $\{\textit{race}, \textit{ethnicity}\}$  matching because there is never any solution variability in the features  $\{\textit{block}, \textit{sex}, \textit{agebin}\}$ —we always find the same the solution for these features once the tables P12 and P14 in Panel A of Table 2 are used because these two tables fully saturate this feature set. The agreement gain with respect to the HDF of 4.3 percentage points ( $= 48.5 - 44.2$ ) can, therefore, be decomposed into 2.3 percentage points of improved agreement on  $\{\textit{race}, \textit{ethnicity}\}$  and 2.0 percentage points of improved agreement on *age* due to the information in the tract-level tables of shown in Panel B Table 2.

TABLE 8. Agreement between Reconstructed HDFs and the Confidential Databases HDF and CEF by Census Block Size

Data ( <i>L-R</i> )	Block Population	Population ( $\times 10^{-3}$ )	Agreement ( $\times 10^{-3}$ )		Agreement (%)	
			Exact Age	Binned Age	Exact Age	Binned Age
HDF-CEF	All	308,746	297,200	297,600	96.3	96.4
$\text{rHDF}_{b,t}$ -CEF	All	308,746	143,800	283,600	46.6	91.9
$\text{rHDF}_b$ -CEF	All	308,746	132,200	276,900	42.8	89.7
$\text{rHDF}_{b,t}$ -HDF	All	308,746	149,600	294,000	48.5	95.2

Table 8 Continued

Data ( $L$ - $R$ )	Block Population	Population ( $\times 10^{-3}$ )	Agreement ( $\times 10^{-3}$ )		Agreement (%)	
			Exact Age	Binned Age	Exact Age	Binned Age
rHDF <sub>b</sub> -HDF	All	308,746	136,500	286,700	44.2	92.9
HDF-CEF	1-9	8,070	5,866	5,973	72.7	74.0
rHDF <sub>b,t</sub> -CEF	1-9	8,070	2,419	5,971	30.0	74.0
rHDF <sub>b</sub> -CEF	1-9	8,070	2,325	5,968	28.8	74.0
rHDF <sub>b,t</sub> -HDF	1-9	8,070	3,492	8,063	43.3	99.9
rHDF <sub>b</sub> -HDF	1-9	8,070	3,275	8,056	40.6	99.8
HDF-CEF	10-49	67,598	63,460	63,580	93.9	94.1
rHDF <sub>b,t</sub> -CEF	10-49	67,598	29,500	62,870	43.6	93.0
rHDF <sub>b</sub> -CEF	10-49	67,598	28,990	62,330	42.9	92.2
rHDF <sub>b,t</sub> -HDF	10-49	67,598	31,810	66,760	47.1	98.8
rHDF <sub>b</sub> -HDF	10-49	67,598	30,860	66,090	45.6	97.8
HDF-CEF	50-99	69,073	66,560	66,630	96.4	96.5
rHDF <sub>b,t</sub> -CEF	50-99	69,073	31,280	64,330	45.3	93.1
rHDF <sub>b</sub> -CEF	50-99	69,073	30,600	63,130	44.3	91.4
rHDF <sub>b,t</sub> -HDF	50-99	69,073	32,560	66,570	47.1	96.4
rHDF <sub>b</sub> -HDF	50-99	69,073	31,540	65,230	45.7	94.4
HDF-CEF	100-249	80,021	78,370	78,420	97.9	98.0
rHDF <sub>b,t</sub> -CEF	100-249	80,021	36,840	73,810	46.0	92.2
rHDF <sub>b</sub> -CEF	100-249	80,021	34,690	71,940	43.4	89.9
rHDF <sub>b,t</sub> -HDF	100-249	80,021	37,590	75,190	47.0	94.0
rHDF <sub>b</sub> -HDF	100-249	80,021	35,160	73,180	43.9	91.4
HDF-CEF	250-499	42,911	42,320	42,340	98.6	98.7
rHDF <sub>b,t</sub> -CEF	250-499	42,911	20,750	39,240	48.3	91.4
rHDF <sub>b</sub> -CEF	250-499	42,911	18,170	37,960	42.3	88.5
rHDF <sub>b,t</sub> -HDF	250-499	42,911	20,970	39,680	48.9	92.5
rHDF <sub>b</sub> -HDF	250-499	42,911	18,270	38,330	42.6	89.3
HDF-CEF	500-999	27,029	26,720	26,740	98.9	98.9
rHDF <sub>b,t</sub> -CEF	500-999	27,029	14,220	24,550	52.6	90.8
rHDF <sub>b</sub> -CEF	500-999	27,029	11,380	23,480	42.1	86.9
rHDF <sub>b,t</sub> -HDF	500-999	27,029	14,310	24,750	52.9	91.6
rHDF <sub>b</sub> -HDF	500-999	27,029	11,410	23,640	42.2	87.5
HDF-CEF	1,000+	14,043	13,930	13,940	99.2	99.3
rHDF <sub>b,t</sub> -CEF	1,000+	14,043	8,835	12,870	62.9	91.7
rHDF <sub>b</sub> -CEF	1,000+	14,043	6,009	12,120	42.8	86.3
rHDF <sub>b,t</sub> -HDF	1,000+	14,043	8,863	12,940	63.1	92.1
rHDF <sub>b</sub> -HDF	1,000+	14,043	6,014	12,170	42.8	86.7

Notes:  $L$  and  $R$  refer to the inputs to Algorithm 2. The denominator in the Agreement (%) column is the Population column in the indicated row. Comparisons to CEF and HDF are rounded to four significant digits to conform to disclosure limitation requirements. Populations are displayed to full precision since only public data were used to compute the block populations. The Block Population column shows the ranges for the populations of the census blocks included in that row.

1258 Next consider how agreement of rHDF<sub>b,t</sub> and rHDF<sub>b</sub> with HDF and CEF varies as a function  
 1259 of census block size (Table 8). Because low-population blocks are much more likely to have had  
 1260 the targeted 2010 Census SDL treatment applied, agreement between the HDF and CEF is only

1261 74.0% in blocks with populations of 1-9 persons. This does not mean the SDL was effective; as  
 1262 we show in Section 8, when a record linkage is made, additional attributes about a record can be  
 1263 accurately learned. Furthermore, we made no attempt to undo household record swaps. Using the  
 1264 binned-age schema,  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  also agree with the CEF for 74.0% of records in the 1-9  
 1265 person block size, as the next two rows of Table 8 show because virtually all persons who live in  
 1266 these low-population blocks have 0 solution variability (see Table 7). For persons living in blocks  
 1267 with population of 10-49, the HDF agrees with the CEF for 94.1% using the binned-age schema.  
 1268  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  agree with the CEF for 93.0% and 92.2%, respectively. However, once again,  
 1269 because the vast majority of these persons have 0 solution variability, the reconstructions agree  
 1270 with the HDF 98.8% and 97.8% respectively. Thus, the certainty with which low-population blocks  
 1271 can be reconstructed—there is almost always only one solution to the reconstruction and that one  
 1272 solution is provably identical to the HDF record—results in extremely high empirical agreement  
 1273 between the reconstructed and confidential HDFs.

1274 As we proceed to larger block populations, we find that the agreement between HDF and CEF  
 1275 increases, reaching 99.3% for blocks with populations of 1,000 or more persons. This reflects the  
 1276 decreasing probability that any SDL treatment was applied to records in those blocks. On the other  
 1277 hand, while not monotonic, agreement of  $\text{rHDF}_{b,t}$  and  $\text{rHDF}_b$  with CEF decreases as block size  
 1278 increases using the binned-age schema, reflecting the effect of increased solution variability as block  
 1279 populations increase (and that no statistical modeling was used to select “realistic” reconstructions  
 1280 rather than algorithmically convenient solutions). However, the agreement of  $\text{rHDF}_{b,t}$  with HDF  
 1281 using the exact-age criterion increases dramatically in the 1,000+ panels because of the increased  
 1282 presence of group quarters residents, where the populations tend to be much more homogeneous on  
 1283 age, in these blocks.

1284 We have two final comments on these reconstruction and solution variability results. First, both  
 1285 reconstruction and solution variability can be computed using only public data, meaning that an  
 1286 attacker would be able to use these methods to target particular blocks for which the reconstruction  
 1287 is unique—access to confidential data is not required to confirm that these records are exact images  
 1288 of the HDF. Second, inferences about persons in low-population blocks tend to be more sensitive  
 1289 to the absence of a record because leaving out a unique or near-unique record type in such blocks  
 1290 is much more likely to change the inference than leaving out one of a large number of records of  
 1291 the same type, say the modal  $\{\text{race}, \text{ethnicity}\}$ . When there is 0 solution variability, as there is  
 1292 in the vast majority of blocks with fewer than 50 people, this effect is even stronger because in  
 1293 these blocks a record unique in  $\text{rHDF}_b$  is provably unique in the HDF, while in blocks with greater  
 1294 solution variability, this may not be the case.

1295 Taken together, the patterns in Table 8 imply that the  $\text{rHDF}_{b,t}$  matches the CEF as well as the  
 1296 actual HDF matches the CEF for smaller blocks, which means that the Census Bureau was correct  
 1297 in considering low-population geographies a significant disclosure risk in microdata but incorrect  
 1298 in assuming that tabular aggregation could mitigate this risk. Thus, Table 8 demonstrates conclu-  
 1299 sively that the 2010 Census disclosure avoidance system was fatally flawed by the failure to use SDL  
 1300 treatments for tabular data that were consistent with rules for microdata.<sup>27</sup> Sampling, aggregating  
 1301 geographic identifiers to populations of 100,000+, and aggregating demographic groups to national  
 1302 populations of 10,000+ probably protected the 2010 Public-Use Microdata Sample (PUMS) ade-  
 1303 quately considering that, unlike the 2000 PUMS, there were no long-form data to include. As we

<sup>27</sup>In other words, continuing with the 2010 technology, instead of designing a new disclosure avoidance system for 2020, would likely have involved both dramatically increasing the swap rate and heavy use of suppression of block level tables.

show in the next section, these reconstructed microdata permit prohibited confidentiality breaches just as the 2010 PUMS would have permitted had the Census Bureau used only its 2010 Census tabular data SDL treatment for the 2010 PUMS.

## 8. REIDENTIFICATION RESULTS

Having demonstrated that it is possible to reconstruct an accurate image of HDF from the publicly released tables, we now analyze the results of experiments that characterize what an attacker could learn from these data. We want to assess the range of possible confidentiality breaches as a function of the quality of the attacker’s external information holding constant the quality of the microdata reconstruction from published tables and the record-linkage algorithms. The COMCRL database described in Section 3.5 has deficiencies in both coverage and accuracy relative to the CEF. Only 36.8% of COMCRL records with valid  $\{pik, block, sex, age\}$  feature values matched a record on the CEF (Table 3). Because we use information from the CEF to characterize vulnerable populations and because confirmation requires that all values of  $\{pik, block, sex, (age or agebin), race, ethnicity\}$  match, this poor agreement between COMCRL and CEF limits the achievable putative and confirmed reidentification rates but does not affect reidentification precision rate. More accurate commercial databases exist today, and other forms of external data are also feasible attacker information—for example, government databases, web-scraped data, informal knowledge from friendships or coworkers. To model an attacker with access to higher quality external data, we use the specially prepared extract from the CEF called  $CEF_{atkr}$  described in Section 5 that includes only  $\{pik, block, sex, age\}$  as the attacker’s data.<sup>28</sup> When using  $CEF_{atkr}$  as the attacker’s data, all data-defined CEF records are potentially at risk of confirmation.

To calibrate the reidentification rates from  $rHDF_{b,t}$  and  $rHDF_b$  as the source of  $\{race, ethnicity\}$ , we also analyze two types alternatives or baselines, each of which provide different insights. First, we use the CEF and HDF themselves as the source of  $\{race, ethnicity\}$ . Using these data as the source of the target characteristics demonstrates how accurate the attacker’s inferences would be if the confidential microdata themselves were released without any SDL treatment (CEF) or using only record-level SDL treatments (HDF) with a naive attacker that does not attempt to undo swaps.<sup>29</sup> Second, as described in Section 5.3, we also incorporate two statistical baselines as the source of  $\{race, ethnicity\}$ . The first, MDG, attaches the within-block modal values of  $\{race, ethnicity\}$  to all records in the block. The second, PRG, randomly assigns  $\{race, ethnicity\}$  in proportion to the share of each pair within the census block. Because the MDG and PRG baselines assign  $\{race, ethnicity\}$  from the HDF matching on  $\{block, sex, agebin\}$  and because  $rHDF_{b,t}$  perfectly replicates the  $\{block, sex, agebin\}$  feature values from HDF, the binned-age putative matches are identical for experiments using  $rHDF_{b,t}$ ,  $rHDF_b$ , MDG, and PRG.<sup>30</sup>

In Section 8.1 we present reidentification metrics for the data-defined national population by census block size. Despite demonstrating high precision on inferences about  $\{race, ethnicity\}$  from reidentifications resulting from augmenting an external database using the reconstructed HDF,

<sup>28</sup>While better informed than an attacker using COMCRL, the  $CEF_{atkr}$  attacker is still not worst-case because we hold constant the methodology used to reconstruct HDF and match to the external data. In particular, we use a straightforward record-linkage attack algorithm without any enhancements. Using strong linkage models, including models that search for a match in nearby blocks, would certainly strengthen the attack.

<sup>29</sup>When the attacker’s external data is  $CEF_{atkr}$ , we only perform the experiment using the HDF as the source of  $\{race, ethnicity\}$ .

<sup>30</sup>When we use COMCRL records that match to the CEF on  $\{pik, block\}$ , putative reidentifications are not identical to those obtained from MDG and PRG.

1341 it is difficult to draw conclusions about confidentiality breaches based on the national block-size  
 1342 statistics. Hence, we consider vulnerable populations in Section 8.2, which presents results for  
 1343 nonmodal persons and contrasts these results with those for modal persons. Then, in Section  
 1344 8.3, we complete the discussion of vulnerable populations by considering nonmodal persons with 0  
 1345 solution variability who are population uniques in the reconstructed HDF (and, hence in the HDF  
 1346 due to the 0 solution variability).

1347 While it is unclear which inferences about individuals are statistical versus privacy-breaching in  
 1348 the overall population, our analysis of vulnerable populations identifies inferences about  $\{race, eth-$   
 1349  $nicity\}$  pairs that are clearly privacy breaches because the improvement in reidentification precision  
 1350 is due primarily (for nonmodal persons) or exclusively (for population unique, 0 solution variabil-  
 1351 ity, nonmodal persons) to the presence of the target individual's data in the published tables. To  
 1352 illustrate the significance of this point, consider the data for the state of Montana in the 2010 SF1.  
 1353 According to SF1 Table P9, 87.8% of Montana residents in 2010 indicated Non-Hispanic White-  
 1354 alone as their race and ethnicity. From this fact alone we can make many high-quality inferences.  
 1355 For a randomly selected COMRCL record in Montana, we expect that record to be Non-Hispanic  
 1356 White-alone with about 88% probability. This does not, however, suggest that publishing a mod-  
 1357 est number of state-level statistics generates prohibited confidentiality violations because although  
 1358 these are inferences about individuals, they are precise because of racial and ethnic homogeneity  
 1359 in Montana and are, thus, predictable on a purely statistical basis. However, our results also show  
 1360 that the single person living in Montana who responded Not Hispanic or Latino, White, American  
 1361 Indian/Alaska Native, Asian, Native Hawaiian/Other Pacific Islander—a rare non-Hispanic 4-race  
 1362 response that is a 0 solution variability population unique on  $\{block, sex, agebin, race, ethnicity\}$ —  
 1363 can be reidentified with precision of 95.2%. That is, the “guess” that this person has the unusual  
 1364 non-Hispanic, 4-race feature value is wrong less than 1 time in 20. Had that person not responded to  
 1365 the 2010 Census, the precision would have been exactly 0 for the modal guesser and, approximately,  
 1366  $1/989,414$  or effectively 0.0% for the proportional guesser. That is, the attacker would “never have  
 1367 guessed” that response. The only reason this unusual person can be geolocated in a block of 15  
 1368 persons and reidentified so precisely in the 2010 Census tables is that the actual response was used  
 1369 in all tables of SF1. Such inferences *are* confidentiality breaches.

1370 The replication archive contains an Excel<sup>TM</sup> workbook (rhdf\_bt\_0solvar\_extract.xlsx) with  
 1371 reconstructed records from 29 census tracts in which every block has 0 solution variability. Tags  
 1372 identify every row that is population unique on  $\{block, sex, agebin\}$  and  $\{block, sex, agebin, race,$   
 1373  $ethnicity\}$  in the spreadsheet. No access to confidential data is required to produce or confirm  
 1374 these tables, and any population unique on *agebin* must also be population unique on *age*. Every  
 1375 population unique in that spreadsheet is known with certainty to be a population unique in the  
 1376 confidential HDF. The only reason the reidentification precision is not 100% is the record-level SDL  
 1377 that was applied to CEF to create HDF. But that SDL treatment was not designed to protect  
 1378 (1) full enumeration microdata files, as opposed to a 10% microdata sample, (2) full enumeration  
 1379 microdata files containing geographic areas with populations as small as 1 person, as opposed to  
 1380 the 100,000 minimum required for microdata samples, or (3) full enumeration files containing  $\{race,$   
 1381  $ethnicity\}$  responses as rare as non-Hispanic, White, American Indian/Alaska Native, Asian, and  
 1382 Native Hawaiian/Other Pacific Islander, which has a national population of only 7,460 as opposed  
 1383 to the 10,000 national population minimum required for microdata samples (McKenna, 2019a).  
 1384 This is a classic failure of composition. Evaluated according to the 2010 Census tabular data rules  
 1385 (McKenna, 2018) the release is “safe.” Evaluated under the 2010 Census microdata rules, it fails  
 1386 catastrophically. But it is exactly the same data release expressed in two mathematically equivalent

1387 representations—34 tabular summaries shown in Table 2 and 308,745,538 microdata records using  
 1388 the same feature set shown in equation (4.2).

1389 Differentiating statistical or generalizable inferences from confidentiality-violating inferences can  
 1390 be subtle. As we described in Section 5.3, in the absence of computational or time constraints,  
 1391 an ideal experiment for estimating the distribution of empirical privacy loss in the 2010 Census  
 1392 publications would iteratively remove each individual’s record, treat it as a target, and repeat  
 1393 the entire set of reconstruction and reidentification experiments, examining inferences about that  
 1394 target person. The intuition behind this approach is especially clear in the case of reidentification.  
 1395 If the target person’s data were not in the confidential database then we could not assert that  
 1396 the feature values we attached to their record in the attacker’s data, either COMRCL or  $\text{CEF}_{\text{atkr}}$ ,  
 1397 were the result of a prohibited reidentification. Indeed, as discussed in Section 2.1, the Census  
 1398 Act (13 U.S. Code §§ 8(b) & 9) specifically identifies the source of the confidential information  
 1399 protected by statute as “information reported by, or on behalf of, any particular respondent,” and  
 1400 “data furnished by any particular establishment or individual,” which reflects the legal focus on  
 1401 data present in internal response databases. The ideal experiment extends this concept, arguing  
 1402 that even if an inference is made about a target person whose record is in the CEF, this inference  
 1403 should not be regarded as confidentiality-violating if that same inference could have been made  
 1404 after removing the target person’s record from the CEF. But, as the Montana example makes clear,  
 1405 if that inference could only have been made because the target person’s record was present in the  
 1406 CEF, that is a confidentiality breach.

1407 Unfortunately, “leaving out” each record in the U.S. population, simulating the 2010 Census  
 1408 SDL treatments, then performing the reconstruction and reidentification attacks for each such  
 1409 record is prohibitively expensive in time and computational resources. To approximate the logic of  
 1410 this ideal experiment, however, we have focused on vulnerable populations—infrequently occurring  
 1411 records that would be very difficult or impossible to reidentify if not for their participation in  
 1412 the 2010 Census. Specifically, we focus on records with  $\{\text{race}, \text{ethnicity}\}$  not equal to the modal  
 1413 value within their block, and which are unique in  $\{\text{block}, \text{sex}, \text{agebin}\}$ . We also further subset to  
 1414 cases for which the attacker can be confident that the reconstructed microdata exactly match the  
 1415 confidential HDF—blocks with 0 solution variability. Accurate inferences about such records in our  
 1416 our experiments would be much more difficult, and often impossible, had the person’s record not  
 1417 been present in the CEF.

1418 **8.1. National Results.** Table 9 presents the statistics for putative and confirmed reidentifications,  
 1419 and for precision rates for all data-defined persons in the 2010 Census for all data-defined persons  
 1420 in COMRCL and  $\text{CEF}_{\text{atkr}}$ . Detailed results by census block size appear in Appendix Table 12,  
 1421 the top panel of which is identical to Table 9. The results in Table 9 are refinements of those first  
 1422 released in 2019 (Abowd, 2019). They show that when the attacker uses the low quality COMRCL  
 1423 data, the reconstruction  $\text{rHDF}_{b,t}$  produces 166,100,000 putative reidentifications (57.9% putative  
 1424 rate for the data-defined population) of which 68,480,000 are confirmed (23.9% confirmation rate  
 1425 for the data-defined population) with a reidentification precision rate of 41.2%. When the attacker  
 1426 uses the high-quality quasi-identifier data in  $\text{CEF}_{\text{atkr}}$ , the reconstruction  $\text{rHDF}_{b,t}$  yields 267,800,000  
 1427 putative reidentifications (97.0% of the data-defined population) of which 208,500,000 are confirmed  
 1428 (75.5% of the data-defined population) with a precision rate of 77.9%.



TABLE 9. All Data-Defined Persons: Putative and Confirmed Reidentifications by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	All	286,700	167,500	82,760	49.4	276,000	276,000	237,500	86.1
HDF	All	286,700	166,100	80,540	48.5	276,000	267,800	228,400	85.3
rHDF <sub>b,t</sub>	All	286,700	166,100	68,480	41.2	276,000	267,800	208,500	77.9
rHDF <sub>b</sub>	All	286,700	166,100	67,450	40.6	276,000	267,800	203,100	75.9
MDG	All	286,700	166,100	76,270	45.9	276,000	267,800	205,100	76.6
PRG	All	286,700	166,100	66,260	39.9	276,000	267,800	177,700	66.3

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. Population for attacker COMRCL is the total number of data-defined records in COMRCL that are also in the CEF universe (see Table 3). Population for attacker CEF<sub>atkr</sub> is the total number of data-defined CEF records.


1429 The Census Bureau released similar reidentification results as part of litigation surrounding  
1430 the 2020 Census and to its Scientific Advisory Committee between 2019 and 2022 (Abowd, 2021;  
1431 Abowd & Hawes, 2023; Hawes, 2022) based on earlier versions of the models presented in this paper.  
1432 Some researchers noted that baselines similar to MDG and PRG could produce reidentifications  
1433 apparently comparable to those of rHDF<sub>b,t</sub> (Francis, 2022; Ruggles & Van Riper, 2022). The  
1434 rows MDG and PRG in the COMRCL panel confirm that claim but only, as we shall see, if  
1435 one ignores nonmodal and vulnerable populations. By construction, these two strategies have  
1436 the same overall putative reidentifications as rHDF<sub>b,t</sub>, and their confirmation and precision rates  
1437 are also comparable. Comparison to statistical baselines at the national level highlights the fact  
1438 that national reidentification rates, while informative about the scale of the match (e.g., 68,480,000  
1439 individuals had confirmed  $\{race, ethnicity\}$  in the COMRCL experiment using rHDF<sub>b,t</sub>), are difficult  
1440 to interpret in terms of privacy loss. The misleading similarity between statistical baselines and  
1441 rHDF<sub>b,t</sub> requires using leave-one-out reasoning to resolve, which we do below. rHDF<sub>b,t</sub> is able  
1442 to reidentify the race and ethnicity of nonmodal individuals that are unique in the linking quasi-  
1443 identifiers  $\{block, sex, agebin\}$  in blocks with 0 solution variability, where MDG and PRG completely  
1444 fail—a much clearer demonstration of privacy loss.<sup>31</sup>

1445 Surprisingly, releasing the CEF itself with the full feature set in Table 1 (except *pik*) would  
1446 produce only relatively modest increase in the putative reidentification rates compared to HDF,  
1447 rHDF<sub>b,t</sub>, rHDF<sub>b</sub> or either baseline, as shown in the first row of Table 9 for both COMRCL and  
1448 CEF<sub>atkr</sub>. As noted in Table 3, COMRCL data did not align well with the data collected in the  
1449 2010 Census. But even if the attacker used high-quality input data, as in CEF<sub>atkr</sub>, releasing  
1450 the CEF (except *pik*) with the feature set in Table 1 would still produce only modestly more  
1451 putative reidentifications, and releasing the HDF with the feature sets shown in Table 1 would  
1452 produce exactly the same putative reidentifications, as rHDF<sub>b,t</sub>, rHDF<sub>b</sub>, or either baseline. From  
1453 the viewpoint of records at risk for record-linkage reidentification, the reconstructed microdata and  
1454 the statistical baselines accurately replicate HDF. The confirmation and precision rates for CEF  
1455 and HDF are marginally higher than those for rHDF<sub>b,t</sub>, rHDF<sub>b</sub> and MDG, and substantially better  
1456 than PRG.

<sup>31</sup>Since this paper is primarily a proof of concept, a larger-scale attack using more tables and reconstructing additional features would result in less solution variability and more population uniques.

1457 **8.2. Detailed Results for Nonmodal and Modal Race-Ethnicity Records by Census**  
 1458 **Block Size.** Figures 3 and 4 summarize the results, by census block size, for the low quality  
 1459 COMCRL and higher quality CEF<sub>atkr</sub> data, respectively. The detailed data are shown in Appendix  
 1460 Tables 12, 13, and 14. The first column of both figures shows the results for all data-defined  
 1461 persons by census block size. As summarized in the national results discussion, except for the lowest  
 1462 population blocks (1 to 9 persons), there are very few discernible differences between the CEF, HDF,  
 1463 rHDF<sub>b,t</sub>, rHDF<sub>b</sub>, MDG, and PRG results. Comparing the results for nonmodal data-defined persons  
 1464 (middle column) with those of modal data-defined persons (last column) reveals the power in the  
 1465 reconstructed microdata vis-à-vis the statistical baselines. There is only one substantive analytic  
 1466 difference between the COMCRL and CEF<sub>atkr</sub> results. Because we use the CEF itself to determine a  
 1467 nonmodal person, the data-defined populations in the COMCRL nonmodal and modal columns are  
 1468 a strict subset of the data-defined population in the all persons column: only the 106,300,000 records  
 1469 in the top left cell of Table 3 can be used to contrast the vulnerable (nonmodal) and nonvulnerable  
 1470 (modal) populations, whereas all 286,700,000 data-defined COMCRL records in the CEF universe  
 1471 can be used for the all persons column. All data-defined persons in the CEF can be studied in the  
 1472 CEF<sub>atkr</sub> results. For both attacker models, the denominators in the nonmodal and modal putative  
 1473 and confirmed reidentification rates from equations (5.1) and (5.2) are the actual at-risk data-  
 1474 defined subpopulations (nonmodal and modal, resp.). The precision rate definition in equation  
 1475 (5.3) is unchanged. An external attacker would have to make inferences from the reconstructed  
 1476 microdata or form independent estimates of the race and ethnicity of the census block to estimate  
 1477 the putative or confirmed reidentification rate, but the external attacker's estimate of the precision  
 1478 rate would still depend only on independent field work using a labeled sample of the attacker's  
 1479 putative reidentification as noted in Section 5.2.

1480 For comparing and contrasting the nonmodal and modal persons results, the interpretation does  
 1481 not depend on the attacker database, so we characterize them generically. In these figures, non-  
 1482 modal data-defined persons are the vulnerable population. Except for blocks with populations of  
 1483 1-9 persons, CEF, HDF, rHDF<sub>b,t</sub>, rHDF<sub>b</sub>, MDG, and PRG putatively reidentify nonmodal persons  
 1484 at essentially the same rates because SF1 Tables P12 and 14 contain all the information used for  
 1485 putative reidentifications. It is the confirmation and precision rates that reveal the contrast with  
 1486 the modal person subpopulation. In blocks with 1-9 persons, the HDF, rHDF<sub>b,t</sub>, and rHDF<sub>b</sub> have  
 1487 essentially identical confirmation and precision rates, whereas the MDG baseline is nearly zero for  
 1488 both confirmation and precision rates, and the PRG baseline is greater than the MDG but sub-  
 1489 stantially less than either rHDF<sub>b,t</sub> or rHDF<sub>b</sub>. As the population in the census block increases, the  
 1490 confirmation and precision rates of rHDF<sub>b,t</sub> and rHDF<sub>b</sub> decline but remain high, much closer to the  
 1491 rates for CEF and HDF than MDG (always essentially zero) and approaching proportional guess-  
 1492 ing only for the most populous census blocks. Even though there are 125 possible nonmodal {*race*,  
 1493 *ethnicity*} combinations, the reidentification precision rate of the reconstructed data is greater than  
 1494 50% for 23,765,000 persons living in census blocks with populations of 1-99 persons (more than  
 1495 1/3 of all nonmodal data-defined persons) compared to essentially 0 for the modal guesser. For  
 1496 this same group, the smallest gain in the reidentification precision rate relative to the proportional  
 1497 guesser is 36.8 percentage points. This enormous gain in accuracy occurs only because the non-  
 1498 modal person's data were used in the SF1 tabulations. When the vulnerable population is defined  
 1499 as persons who differ from the predominant characteristics in small neighborhoods, in this case  
 1500 nonmodal {*race*, *ethnicity*} persons in lower-population census blocks, the statistical baselines ei-  
 1501 ther fail completely (MDG) or fair no better than chance (PRG), but the reconstructed microdata




**Figure 3.** Comparison of Putative Reidentification Rates, Confirmed Reidentification Rates, and Reidentification Precision Rates for COMRCL by Census Block Size

Notes: The denominator used in the first column is the COMRCL Population column in Table 12, which totals to 286,700,000. The denominator in the second column is the COMRCL population in Table 13, and the denominator in the third column is the COMRCL population in Table 14. The denominators in the second and third columns sum to 106,300,000 because only that subset of COMRCL records can be classified as modal and nonmodal from the CEF. See Table 3.

are correct at rates that approach the correctness of the confidential data themselves as the small neighborhood population decreases.

Our interpretation of the mechanism causing the increased precision for vulnerable persons—the use of their specific response in the census tabulations—is further supported by examining the results for modal data-defined persons. In this case, the reidentification precision rates convey the main result. As expected, the modal guesser (MDG) has essentially perfect precision because our modal population was defined using the actual mode in the confidential data, and that is also the mode in the overwhelming majority of published block-level  $\{race, ethnicity\}$  tables, even in the census blocks with population of 1-9 persons, where the MDG precision rate takes its smallest value of 98.7%. But even in this nonvulnerable population, where the deck is deliberately stacked in favor of the modal guesser,  $rHDF_{b,t}$  and  $rHDF_b$  have reidentification precision rates substantially closer to the CEF and HDF than the proportional guesser. In blocks with populations of 1-9 persons, the precision rate of  $rHDF_{b,t}$  is at most 0.3 percentage points worse than HDF, while the precision rate of PRG is at best 4.0 percentage points worse than HDF. As the block population increases, the reidentification precision rates for CEF, HDF,  $rHDF_{b,t}$ , and  $rHDF_b$  all decrease, approaching but remaining greater than the precision rate for PRG. Even in the largest population census blocks, the precision of  $rHDF_{b,t}$  is at worst 3.3 percentage points lower than HDF while the precision of PRG is at best 4.8 percentage points lower than HDF. Even for less vulnerable populations, in this case modal  $\{race, ethnicity\}$  persons living in any size census block, the reconstructed microdata outperform proportional guessing, delivering prediction accuracy closer to the performance of the



**Figure 4.** Comparison of Putative Reidentification Rates, Confirmed Reidentification Rates, and Reidentification Precision Rates for  $CEF_{atkr}$  by Census Block Size

Notes: The denominator used in the first column is the  $CEF_{atkr}$  Population column in Table 12, which totals to 276,000,000. The denominator in the second column is the  $CEF_{atkr}$  population in Table 13, and the denominator in the third column is the  $CEF_{atkr}$  population in Table 14. The denominators in the second and third columns sum to 276,000,000 because all records in  $CEF_{atkr}$  can be classified as modal and nonmodal from the CEF. See Table 3.

confidential data than this statistical baseline. Of course, the modal guesser outperforms even the confidential data in this case because of way it is defined.

**8.3. Results for the Most Vulnerable Populations.** We now discuss the results for the most tightly constrained definition of the vulnerable population—nonmodal data-defined persons living in blocks with 0 solution variability whose reconstructed records are population uniques for  $\{block, sex, agebin\}$ . Panel A of Table 10 shows the results for nonmodal persons living in 0 solution variability blocks and Panel B shows the results for the subset of these persons who are population unique on  $\{block, sex, agebin\}$ . Recalling that population uniqueness on  $\{block, sex, agebin\}$  implies population uniqueness on  $\{block, sex, age\}$  and that 0 solution variability implies that the record in the reconstructed data is provably the same as the record in HDF without referencing any confidential data, Table 10 establishes that the reidentification precision rates of  $rHDF_{b,t}$  and HDF are essentially identical 91.2 versus 93.0 in COMCRL and 95.2 versus 95.6 in  $CEF_{atkr}$ . These reidentification precisions are far in excess of the modal guesser's (2.5 at best) or the proportional guesser's (20.2). Thus, the correct  $\{race, ethnicity\}$  has been exposed for more than 19 of 20 persons in the population of nonmodal, 0-solvar,  $\{block, sex, age\}$  uniques—essentially the same exposure as publishing the HDF itself, and only five percentage points worse than publishing the CEF itself. Statistical baselines are either almost always wrong or wrong for 4 of 5 persons in this vulnerable population. These results definitively show that the published SF1 tables result in confidentiality breaches since the high statistical precision of the reconstructed microdata is only possible because the target person's data were used in the SF1 tabulations. If HDF was unsafe to release under the

2010 Census disclosure limitation framework, then the Summary File 1 statistics in Table 2 were also unsafe to release.

TABLE 10. Putative Reidentifications, Confirmed Reidentifications, and Precision Rates for Nonmodal Persons in Blocks with Zero Solution Variability

Data Set	Population ( $\times 10^{-3}$ )	Attacker: COMRCL			Attacker: CEF <sub>atkr</sub>		
		Putative ( $\times 10^{-3}$ )	Confirm ( $\times 10^{-3}$ )	Precision (%)	Putative ( $\times 10^{-3}$ )	Confirm ( $\times 10^{-3}$ )	Precision (%)
		Panel A: Nonmodal Persons					
CEF	6,517	1,993	1,633	81.9	6,517	5,727	87.9
HDF	6,517	1,716	1,278	74.5	5,189	4,209	81.1
rHDF <sub>b,t</sub>	6,517	1,638	1,009	61.6	5,305	3,634	68.5
rHDF <sub>b</sub>	6,517	1,598	914	57.2	5,304	3,369	63.5
MDG	6,517	1,716	33	1.9	5,189	88	1.7
PRG	6,517	1,716	274	16.0	5,189	890	17.2
rMDF <sub>b,t</sub>	6,517	649	103	15.8	1,866	352	18.9
MDF	6,517	649	103	15.8	1,866	353	18.9
rSWAPLo <sub>b,t</sub>	6,517	1,813	1,236	68.1	6,242	4,693	75.2
rSWAPHi <sub>b,t</sub>	6,517	1,336	680	50.9	4,270	2,482	58.1
		Panel B: Nonmodal Uniques on {block, sex, agebin}					
CEF	3,364	856	834	97.4	3,364	3,364	100.0
HDF	3,364	673	625	93.0	2,418	2,311	95.6
rHDF <sub>b,t</sub>	3,364	614	560	91.2	2,418	2,301	95.2
rHDF <sub>b</sub>	3,364	593	537	90.6	2,418	2,237	92.5
MDG	3,364	673	21	3.2	2,418	61	2.5
PRG	3,364	673	136	20.2	2,418	488	20.2
rMDF <sub>b,t</sub>	3,364	212	42	19.8	671	147	21.8
MDF	3,364	212	42	19.7	671	147	21.8
rSWAPLo <sub>b,t</sub>	3,364	750	710	94.7	3,194	3,111	97.4
rSWAPHi <sub>b,t</sub>	3,364	513	371	72.2	2,014	1,568	77.9

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. The rows labeled rMDF<sub>b,t</sub> and MDF (gray highlight) are the analogues of rHDF<sub>b,t</sub> and HDF, respectively, when the 2020 Census DAS is applied to the 2010 CEF. The rows labeled rSWAPLO<sub>b,t</sub> and rSWAPHi<sub>b,t</sub> (medium gray highlight) are the analogues of rHDF<sub>b,t</sub> when alternative swapping parameters are used. See Section 10.

## 9. THE 2010 CENSUS STATISTICAL DISCLOSURE LIMITATION FRAMEWORK DID NOT MEET THE CENSUS BUREAU'S OWN STANDARDS

The results of our experiment show that it is possible to create an extremely accurate reconstruction (95% binned-age agreement, see Table 8) of the underlying HDF microdata from publicly available sources, effectively undoing any confidentiality protection resulting from releasing tabular summaries instead of releasing the same features as a microdata extract of the universe of HDF person records. There was no reconstruction solution variability for 70% of populated blocks, meaning that the reconstructed records in rHDF<sub>b,t</sub> were the exact image of the records in HDF for the feature set {block, sex, agebin, race, ethnicity}. For these blocks, housing-unit swapping and synthetic data for the group quarters population are the only sources of uncertainty about their correctness relative to the CEF. These SDL measures do affect the accuracy of the reconstruction relative to the CEF, especially in the blocks with the smallest population sizes (74% agreement

in blocks with population size of 0-9), but the accuracy is still very high overall (and could be higher for attackers who attempt to undo the swapping). When the reconstructed data are linked to an external dataset, an attacker can learn extra characteristics about members of their dataset that they previously did not know, and could not learn statistically, with very high accuracy for select subgroups. The attacker’s successful inference depends on several factors. First, the more accurately the external dataset matches the linking variables  $\{block, sex, age\}$ , the more records the attacker will successfully link and the better the inference about the value of the other census responses will be. In our experiment, only about 40% of the records in our low quality commercial data were correct matches to the CEF on these linking variables. Consequently, even though we could make a large number of putative matches, many were not confirmed—not because of incorrect inference on the unknown characteristics  $\{race, ethnicity\}$ , but because the characteristics on the external dataset were inaccurate quasi-identifiers. In our experiments using a much more accurate external database (either the CEF<sub>atkr</sub> or the subset of records in the commercial database that matched the CEF) the confirmation and precision rates were much higher. As the accuracy of the external data improves, the success of our attack improves, indicating that any conclusions based on the relatively low quality of commercial name and address databases in 2010 should be tempered by the improved quality of such data by 2020.

Our reconstruction-abetted reidentification attack was much more accurate in successfully inferring the  $\{race, ethnicity\}$  of records with a value that was different than the most common (modal)  $\{race, ethnicity\}$  in the block in comparison with the baseline inferential methods of guessing the modal  $\{race, ethnicity\}$  and guessing the  $\{race, ethnicity\}$  with probability proportional to publicly released counts. It also vastly outperformed the baseline methods when making inferences about records that were unique and had nonmodal  $\{race, ethnicity\}$ , facts that the attacker could infer exactly in blocks with zero solution variability without consulting any confidential data. Therefore, while it is possible to make accurate inferences with these baseline methods when statistical information is used, the reconstruction-abetted reidentification attack exposes the vulnerability of the confidentiality protections by permitting accurate inferences on persons with statistically uncommon and rare characteristics. The accurate inference of the race and ethnicity of a person who is a population unique is only possible because that person’s record was available in rHDF<sub>b,t</sub>. Such an inference is nonstatistical using the framework laid out in Section 5. Data swapping marginally reduced the number of records in the rHDF<sub>b,t</sub> at risk for a putative match, but it had no discernible effect on the precision of nonstatistical inferences for the vast majority of records.

The conclusion from this analysis is that the disclosure avoidance system applied to the 2010 Census did not meet the requirements for approval set forth by the Census Bureau’s Data Stewardship Executive Policy (DSEP) Committee for 2010 Census publications and, in light of current algorithmic and computational capabilities, it is not viable for future use. The results of the this experiment motivated the Census Bureau to change the SDL methods used for the 2020 Census (Abowd, 2018). Instead of record swapping, synthetic group quarters data, and aggregation, the Bureau used differentially private mechanisms for all tabulations from the 2020 Census Abowd et al., 2022. Had the Census Bureau continued to use the 2010 technology for 2020, it would have had to use the same rules for microdata as for tabular data, likely resulting in a much higher swap rate and a large amount of suppression of block-level data.

1598 10. THE 2020 CENSUS STATISTICAL DISCLOSURE LIMITATION SYSTEM ADDRESSED THE  
1599 FAILURES OF THE 2010 SYSTEM

1600 Our final discussion addresses whether any SDL method can simultaneously defend against  
1601 reidentification attacks and other nonstatistical uses while allowing publication of data that are  
1602 fit for use in the primary applications. Christ et al. (2022) demonstrated that the Census Bureau's  
1603 differentially private disclosure avoidance system could provide fitness-for-use in the redistricting  
1604 application comparable to swapping but with superior confidentiality protection. They also noted  
1605 that "[s]wapping places a disproportionate privacy burden on minority groups," while differential  
1606 privacy protections apply to all sub-populations. These results, which we confirm in this paper,  
1607 are in contrast to the erroneous conclusions drawn by Kenny et al. (2021) who calculated percent-  
1608 age changes incorrectly for small populations and failed to distinguish between generalizable and  
1609 privacy-violating inferences (Jarmin et al., 2023). Wright and Irinata (2021) demonstrated that  
1610 the 2020 Census Redistricting Data (P.L. 94-171) Summary File was fit for use in redistricting and  
1611 scrutiny under Section 2 of the 1965 Voting Rights Act.

1612 On October 20, 2022, DSEP approved the final production settings for the 2020 Census disclosure  
1613 avoidance system as applied to the Demographic and Housing Characteristics (DHC) File, the  
1614 successor to the 2010 Summary File 1 used in this paper. DHC was produced using an extension  
1615 of the algorithms described in Abowd et al. (2022) that includes the 2020 Census version of the  
1616 tables used in this paper. The statistical summaries presented for the DSEP decision included an  
1617 analysis of the effectiveness of the same reconstruction-abetted reidentification attack studied here  
1618 based on the 2010 Census. The analysis compared the confidentiality protections from the original  
1619 SF1 tables shown in Tables 2, 3 and 4 with the protection afforded by the differentially private  
1620 disclosure avoidance system, when executed at the DHC production settings applied to the 2010  
1621 Census data, and the protection afforded by housing unit-level data swapping at rates of 5% and  
1622 50%, i.e., swapping 5% or half of all housing units to a new location in a different block, tract, or  
1623 elsewhere in the state. See Appendix C for details.

1624 Table 11 shows the agreement rates overall and by census block size between the 2010 CEF and

- 1625 • HDF,
- 1626 •  $\text{rHDF}_b$ ,
- 1627 •  $\text{rHDF}_{b,t}$ ,
- 1628 •  $\text{rMDF}_{b,t}$ —reconstructed Microdata Detail File (MDF), (Abowd et al., 2022), the produc-  
1629 tion version output of the differentially private DAS for the DHC when applied to 2010  
1630 Census data and processed into the equivalents of the Table 2 statistics,
- 1631 • MDF—actual MDF from the same 2020 DAS output; i.e., not processed into tables, so  
1632 there is no reconstruction of the microdata—these are the actual microdata from which  
1633 DHC was tabulated,
- 1634 •  $\text{rSWAPHi}_{b,t}$ —the results of the 50% swap-rate experiment when process through our reconstruction-  
1635 abetted reidentification attack,
- 1636 •  $\text{rSWAPLo}_{b,t}$ —the results of the 5% swap-rate experiment when similarly processed.

1637 The  $\text{rMDF}_{b,t}$ , MDF, and  $\text{rSWAPHi}_{b,t}$  reduce the agreement with the 2010 CEF substantially, with  
1638 the  $\text{rMDF}_{b,t}$  and MDF reducing agreement more than  $\text{rSWAPHi}_{b,t}$ . The  $\text{rSWAPLo}_{b,t}$  agrees with  
1639 the CEF at essentially the same rate as  $\text{rHDF}_{b,t}$  except for blocks with populations of 1-9 persons,  
1640 where HDF,  $\text{rHDF}_{b,t}$ , and  $\text{rHDF}_b$  all agree with the CEF for 74.0% of records using binned age  
1641 while  $\text{rSWAPLo}_{b,t}$  agrees with 94.9% of these records. The experimental swap methodology did  
1642 not single-out low population blocks for relatively greater swapping.

TABLE 11. Selected Reconstruction Agreement Statistics with Comparisons to Output from the 2020 Census Disclosure Avoidance System and Specially Swapped Versions of the CEF Using the 2010 Census as Input by Census Block Size

Data ( $L - R$ in Algorithm 2)	Block Population Range	Population ( $\times 10^{-3}$ )	Agreement ( $\times 10^{-3}$ )		Agreement (%)	
			Exact Age	Binned Age	Exact Age	Binned Age
HDF-CEF	All	308,746	297,200	297,600	96.3	96.4
rHDF <sub>b,t</sub> -CEF	All	308,746	143,800	283,600	46.6	91.9
rHDF <sub>b</sub> -CEF	All	308,746	132,200	276,900	42.8	89.7
rMDF <sub>b,t</sub> -CEF	All	308,746	58,520	113,100	18.9	36.6
MDF-CEF	All	308,746	75,950	113,300	24.6	36.7
rSWAPLO <sub>b,t</sub> -CEF	All	308,746	144,500	281,200	46.8	91.1
rSWAPHi <sub>b,t</sub> -CEF	All	308,746	100,800	193,200	32.7	62.6
HDF-CEF	1-9	8,070	5,866	5,973	72.7	74.0
rHDF <sub>b,t</sub> -CEF	1-9	8,070	2,419	5,971	30.0	74.0
rHDF <sub>b</sub> -CEF	1-9	8,070	2,325	5,968	28.8	74.0
rMDF <sub>b,t</sub> -CEF	1-9	8,070	232	647	2.9	8.0
MDF-CEF	1-9	8,070	276	647	3.4	8.0
rSWAPLO <sub>b,t</sub> -CEF	1-9	8,070	3,278	7,660	40.6	94.9
rSWAPHi <sub>b,t</sub> -CEF	1-9	8,070	1,803	4,280	22.3	53.0
HDF-CEF	10-49	67,598	63,460	63,580	93.9	94.1
rHDF <sub>b,t</sub> -CEF	10-49	67,598	29,500	62,870	43.6	93.0
rHDF <sub>b</sub> -CEF	10-49	67,598	28,990	62,330	42.9	92.2
rMDF <sub>b,t</sub> -CEF	10-49	67,598	4,999	12,330	7.4	18.2
MDF-CEF	10-49	67,598	6,216	12,320	9.2	18.2
rSWAPLO <sub>b,t</sub> -CEF	10-49	67,598	30,320	63,370	44.9	93.8
rSWAPHi <sub>b,t</sub> -CEF	10-49	67,598	18,110	38,330	26.8	56.7
HDF-CEF	50-99	69,073	66,560	66,630	96.4	96.5
rHDF <sub>b,t</sub> -CEF	50-99	69,073	31,280	64,330	45.3	93.1
rHDF <sub>b</sub> -CEF	50-99	69,073	30,600	63,130	44.3	91.4
rMDF <sub>b,t</sub> -CEF	50-99	69,073	8,350	18,830	12.1	27.3
MDF-CEF	50-99	69,073	10,670	18,820	15.5	27.2
rSWAPLO <sub>b,t</sub> -CEF	50-99	69,073	31,190	63,300	45.2	91.6
rSWAPHi <sub>b,t</sub> -CEF	50-99	69,073	20,200	41,180	29.2	59.6
HDF-CEF	100-249	80,021	78,370	78,420	97.9	98.0
rHDF <sub>b</sub> -CEF	100-249	80,021	34,690	71,940	43.4	89.9
rHDF <sub>b,t</sub> -CEF	100-249	80,021	36,840	73,810	46.0	92.2
rMDF <sub>b,t</sub> -CEF	100-249	80,021	15,030	30,810	18.8	38.5
MDF-CEF	100-249	80,021	19,750	30,790	24.7	38.5
rSWAPLO <sub>b,t</sub> -CEF	100-249	80,021	36,310	71,880	45.4	89.8
rSWAPHi <sub>b,t</sub> -CEF	100-249	80,021	25,740	50,530	32.2	63.2
HDF-CEF	250-499	42,911	42,320	42,340	98.6	98.7
rHDF <sub>b</sub> -CEF	250-499	42,911	18,170	37,960	42.3	88.5
rHDF <sub>b,t</sub> -CEF	250-499	42,911	20,750	39,240	48.3	91.4
rMDF <sub>b,t</sub> -CEF	250-499	42,911	12,220	22,570	28.5	52.6
MDF-CEF	250-499	42,911	16,290	22,600	38.0	52.7
rSWAPLO <sub>b,t</sub> -CEF	250-499	42,911	20,470	38,250	47.7	89.2
rSWAPHi <sub>b,t</sub> -CEF	250-499	42,911	15,830	29,030	36.9	67.7
HDF-CEF	500-999	27,029	26,720	26,740	98.9	98.9
rHDF <sub>b,t</sub> -CEF	500-999	27,029	14,220	24,550	52.6	90.8
rHDF <sub>b</sub> -CEF	500-999	27,029	11,380	23,480	42.1	86.9



Table 11 Continued

Data ( $L - R$ in Algorithm 2)	Block Population Range	Population ( $\times 10^{-3}$ )	Agreement ( $\times 10^{-3}$ )		Agreement (%)	
			Exact Age	Binned Age	Exact Age	Binned Age
rMDF <sub><math>b,t</math></sub> -CEF	500-999	27,029	10,280	17,210	38.0	63.7
MDF-CEF	500-999	27,029	13,540	17,310	50.1	64.0
rSWAPLO <sub><math>b,t</math></sub> -CEF	500-999	27,029	14,090	24,060	52.1	89.0
rSWAPHI <sub><math>b,t</math></sub> -CEF	500-999	27,029	11,480	19,130	42.5	70.8
HDF-CEF	1,000+	14,043	13,930	13,940	99.2	99.3
rHDF <sub><math>b,t</math></sub> -CEF	1,000+	14,043	8,835	12,870	62.9	91.7
rHDF <sub><math>b</math></sub> -CEF	1,000+	14,043	6,009	12,120	42.8	86.3
rMDF <sub><math>b,t</math></sub> -CEF	1,000+	14,043	7,407	10,670	52.8	76.0
MDF-CEF	1,000+	14,043	9,204	10,820	65.5	77.0
rSWAPLO <sub><math>b,t</math></sub> -CEF	1,000+	14,043	8,798	12,720	62.7	90.6
rSWAPHI <sub><math>b,t</math></sub> -CEF	1,000+	14,043	7,678	10,730	54.7	76.4


Notes: Counts rounded to four significant digits, except block populations, to conform to disclosure limitation requirements. Agreement percentages use the block populations in that row as the base. The rows labeled rMDF <sub>$b,t$</sub>  and MDF (light gray highlight) are the analogues of rHDF <sub>$b,t$</sub>  and HDF, resp., when the 2020 Census DAS is applied to the 2010 CEF. Rows labeled rSWAPLO <sub>$b,t$</sub>  and rSWAPHI <sub>$b,t$</sub>  (medium gray highlight) are the results of applying the full reconstruction-abetted reidentification attack to the specially swapped versions of HDF described in the main text.

Figures 5 and 6 compare the putative reidentification, confirmed reidentification, and reidentification precision rates by census block size when the attacker is COMCRL or CEF<sub>atkr</sub>, respectively. Their interpretation is identical to the interpretation of Figures 3 and 4. Detailed statistics can be found in Appendix Tables 15, 16, and 17.

Only the output of the 2020 DAS (rMDF <sub>$b,t$</sub>  and MDF) and rSWAPHI <sub>$b,t$</sub>  succeed in reducing putative reidentification rates because only those SDL treatments introduces substantial noise in the quasi-identifiers  $\{block, sex, agebin\}$ . Without noise in those quasi-identifiers, putative reidentification rates will always be very close to those of the CEF.

The second important feature of Figures 5 and 6 is the very low, nearly uniform by block size, reidentification precision rates for rMDF <sub>$b,t$</sub>  and MDF for the nonmodal data-defined persons (middle column). These are the only SDL treatments shown in the figures that accomplish this reduction. As the data in Appendix Table 16 show, the precision rate for nonmodal persons never exceeds 26.4% and averages 20.1% to 20.4%. An attacker using the methods in this paper would be wrong four times in five guessing the  $\{race, ethnicity\}$  from either the reconstructed MDF, rMDF <sub>$b,t$</sub> , or the MDF itself. This is essentially the same as the failure rate on nonmodal persons for the PRG statistical baseline, 16.0% to 16.7%, shown in Appendix Table 13.

Table 7 contains the final piece of evidence that the 2020 DAS effectively countered reconstruction-abetted reidentification attacks as we have modeled them here. For the nonmodal persons living in 0 solution variability blocks who are population unique on  $\{block, sex, agebin\}$  (Panel B), the reidentification precision rates of rMDF <sub>$b,t$</sub>  and MDF vary between 19.7% and 21.8%, essentially identical to the precision rates for nonmodal persons in general. Neither the low nor high swap rate experiments deliver precision rates for this vulnerable population below 72.2%. An attacker using rSWAPHI <sub>$b,t$</sub>  and our methods would be correct about the population unique nonmodal  $\{race, ethnicity\}$  approximately three times out of four, even though 50% of the housing unit records have been swapped.




**Figure 5.** Comparison of Putative Reidentification Rates, Confirmed Reidentification Rates, and Reidentification Precision Rates for Alternative Disclosure Limitation Implementations Applied to the 2010 Census Edited File for Attacker COMCRL by Census Block Size

Notes: The denominator used in the first column is the COMCRL Population column in Table 15, which totals to 286,700,000. The denominator in the second column is the COMCRL population in Table 16, and the denominator in the third column is the COMCRL population in Table 17. The denominators in the second and third columns sum to 106,300,000 because only that subset of COMCRL records can be classified as modal and nonmodal from the CEF. See Table 3.

1668 The replication archive also contains an Excel<sup>TM</sup> (rmdf\_bt\_0solva\_extract.xlsx) workbook with  
 1669 reconstructed records from the same 29 census tracts in which every block has 0 solution variability  
 1670 for  $rHDF_{b,t}$  that are shown in rhdf\_bt\_0solvar\_extract.xlsx. Tags also identify every row that is  
 1671 population unique on  $\{block, sex, agebin\}$  and  $\{block, sex, agebin, race, ethnicity\}$  in the spread-  
 1672 sheet. Inspection of the record-level data in these two workbooks shows how the DAS reduced both  
 1673 putative reidentification and precision rates.

1674 Because we have demonstrated that the tabular and microdata formats for publishing data  
 1675 processed by the 2020 DAS are properly protected either when reconstructed from DHC tables into  
 1676  $rMDF_{b,t}$  or as the MDF itself, both could be safely released. The 2020 DAS demonstrably fixes the  
 1677 inconsistency flaw in the 2010 Census SDL framework.

1678 We have only considered the ability of the 2020 DAS to defend against reconstruction-abetted  
 1679 reidentification attacks; however, both the redistricting and DHC data products were extensively  
 1680 tuned for accuracy. These results are available in other sources (Abowd et al., 2022; Cumings-  
 1681 Menon et al., 2023; U.S. Census Bureau, 2023a) and in the replication archive for this paper. The  
 1682 low swap rate experiment has accuracy comparable to SF1. The high swap rate experiment has  
 1683 accuracy far worse than the production DHC on most statistics. The replication archive for this  
 1684 paper also contains the complete set of accuracy metrics for these swap experiments.



**Figure 6.** Comparison of Putative Reidentification Rates, Confirmed Reidentification Rates, and Reidentification Precision Rates for Alternative Disclosure Limitation Implementations Applied to the 2010 Census Edited File for Attacker  $CEF_{atkr}$  by Census Block Size

Notes: The denominator used in the first column is the  $CEF_{atkr}$  Population column in Table 15, which totals to 276,000,000. The denominator in the second column is the  $CEF_{atkr}$  population in Table 16, and the denominator in the third column is the  $CEF_{atkr}$  population in Table 17. The denominators in the second and third columns sum to 276,000,000 because all records in  $CEF_{atkr}$  can be classified as modal and nonmodal from the CEF. See Table 3.

1685 The other feasible alternative to the 2020 DAS was a variant of the suppression methods used in  
 1686 the 1980 Census. Suppression can defend against an important subset of reconstruction attacks—  
 1687 isolating the records of population uniques; however, successful suppression systems, such as the  
 1688 one used for economic censuses (Cox, 1995), require both primary and complementary suppression.  
 1689 Appendix D lays out the rules used for the 1980 Census as we adapted them to testing suppression  
 1690 for the 2020 Census. Only primary and whole table suppression were used. Without complementary  
 1691 suppression there is no provable defense against reconstruction of population unique records. We  
 1692 considered only the four primary tables in the P.L. 94-171 Redistricting Data Summary File (P8–  
 1693 P11 in Summary File 1). Appendix Tables 18 and 19 show that the use of just the 1980 Census  
 1694 primary suppression rules would have resulted in zeroing out up to 83.8% of the cells in these  
 1695 tables, suppressing up to 87.7% of the block-level redistricting tables, and suppressing 38.7% of the  
 1696 other block-level tables in the 2010 SF1. Suppression destroys the redistricting use case—missing  
 1697 block-level tables prevent the creation of new voting districts, which have unknown boundaries at  
 1698 the time of data publication. The new districts must have approximately equal populations and be  
 1699 drawn in compliance with Section 2 of the 1965 Voting Rights Act. This limitation of suppression  
 1700 was known in 1980 and constituted one of the main reasons for using swapping in the 1990 Census  
 1701 data (McKenna, 2018).

## 11. CONCLUSIONS

This paper directly addresses the concept at the heart of traditional statistical disclosure limitation: the claim that as long as there is some uncertainty regarding whether or not a particular respondent's data were used in a particular statistic the agency has provided "plausible deniability." We establish that the 2010 Census attacker does not need access to the confidential data to know (1) that the record is an exact copy of the confidential HDF (using the 38-age-bin schema) and (2) that the record is a population unique on the quasi-identifiers  $\{block, sex, age\}$  used for a classic record-linkage attack. While this is strictly true for "only" 97 million persons, adding more tables and more features can only increase this number. If the reconstructed microdata meet the conditions for a microdata-based record-linkage attack, then such an attack must be defended in the SDL framework. Therefore, the plausible deniability argument turns on whether the 2010 Census aggregation and swapping were adequate. We argued here that they were not. In particular, if the released tabular data have reidentification precision rates that are essentially identical to the original confidential data, then either those data could have been released without aggregation, which the Census Bureau has consistently argued would violate Title 13, or the tabular data are too disclosive, which is what we conclude. The burden of proof now lies with traditional SDL to defend the status quo or accept the consequences of our research.

This paper has also demonstrated that the decision to replace the SDL system used for the 2010 Census was based on sound scientific evidence that those methods would fail if applied to the 2020 Census and/or would lead to unacceptable data accuracy loss. First, we demonstrated that based on only 5 billion of the 150 billion statistics published from the 2010 Census, the confidential microdata from the tabulation input file, the Hundred-percent Detail File, could be recreated with at least 95% accuracy on the schema used for all block-level data. This image of the 2010 HDF,  $rHDF_{b,t}$ , fails three contemporaneous confidentiality requirements for the 2010 Census: (i) it is not a sample; (ii) the minimum population in the geographic identifier is 1 person, not 100,000; (iii) the minimum national population for cells in one-dimensional marginals is less than 10,000. Similar criteria are still in place for public-use microdata samples for other Census Bureau household surveys. Second, we demonstrated that the Census Bureau was correct to insist on minimum populations in microdata for both the geographic identifiers and demographic characteristics because for more than 70% of all blocks, the records in  $rHDF_{b,t}$  are provably identical to their counterparts in the HDF using the binned-age schema; hence, there is no confidentiality protection from aggregation over the geographic identifier population. Third, we demonstrated that  $rHDF_{b,t}$  could be used to make high-precision confidentiality-violating inferences: (i) the reidentification precision rate on inferences for nonmodal vulnerable populations is at least 62% and at worst 95% whereas the best precision rate for scientific inferences in vulnerable populations is 32%, and a modal guesser never exceeds 9% precision. Finally, we demonstrated that the differentially private SDL methods applied to the 2020 DHC, the successor to the 2010 SF1, successfully counter this reconstruction-abetted reidentification attack by greatly reducing the putative reidentification rates and by limiting the precision rates on nonmodal vulnerable populations to at most 26.4%. Although such a demonstration does not mean the public 2020 Census data are protected against an arbitrary attack into the indefinite future, it does mean that they are substantially better protected than they would have been had the methods applied to the 2010 Census been used.

**Disclosure Statement.** The research presented in this article was initiated, funded and supervised by the U.S. Census Bureau. All authors were either employees or contractors of the Census Bureau while performing their contributions.

1747 **Disclaimer and Acknowledgments.** The views and opinions expressed in this paper are those  
 1748 of the authors and not the U.S. Census Bureau. Research was conducted under Project ID: P-  
 1749 7502798. John Abowd, Simson Garfinkel, Ramy Tadros, and Lars Vilhuber worked in their personal  
 1750 capacities and without access to any confidential data after leaving the Census Bureau (Abowd,  
 1751 Garfinkel, and Vilhuber) and Galois (Tadros), respectively, to assist in preparing the manuscript  
 1752 for publication. Statistics reported were released under DRB Clearance numbers CBDRB-FY20-  
 1753 DSEP-001, CBDRB-FY22-DSEP-003, CBDRB-FY22-DSEP-004, and CBDRB-FY23-0152.

1754 **Data availability.** The public replication archive is located at [https://github.com/uscensusbureau/](https://github.com/uscensusbureau/recon_replication)  
 1755 [recon\\_replication](https://github.com/uscensusbureau/recon_replication). The archive contains all tables in this paper in Excel<sup>TM</sup> format. The archive  
 1756 also contains pointers to the official versions of all public data used in this paper, the complete code  
 1757 base, and a description of the workflow that meets current scientific best practices as defined by  
 1758 the American Economic Association <https://aeadataeditor.github.io/>. Census Bureau Data Stew-  
 1759 ardship Policy DS-027 [https://www2.census.gov/foia/ds\\_policies/ds027.pdf](https://www2.census.gov/foia/ds_policies/ds027.pdf) permitted the editor  
 1760 and referees of journals that reviewed this work to independently verify the correctness of the  
 1761 calculations done on the confidential 2010 Census and commercial data used in this paper.

## 1762 **Contributions.**

- 1763 • Conceptualization: JMA, TA, SLG, DK, PL, LV
- 1764 • Data curation: NG, RAR, LV
- 1765 • Formal Analysis: TA, SLG, DK, PL
- 1766 • Methodology: JMA, TA, RA, DD, SD, SLG, NG, DK, PL, EL, SM, RAR, RNT, LV
- 1767 • Investigation: DD, SD, SLG, NG, DK, PL, EL, SM, RAR, RNT, LV
- 1768 • Software: TA, DD, SD, SLG, NG, PL, EL, SM, RAR, RNT, LV
- 1769 • Supervision: JMA
- 1770 • Writing – original draft: JMA, RA, SLG, NG, DK, PL, RAR, LV
- 1771 • Writing – review & editing: JMA, TA, RA, DD, SD, SLG, NG, DK, PL, EL, SM, RAR,
- 1772 RNT, LV

1773

## APPENDIX A. DETAILED TABLES REFERENCED IN SECTION 8

TABLE 12. All Data-Defined Persons: Putative and Confirmed Reidentifications by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	All	286,700	167,500	82,760	49.4	276,000	276,000	237,500	86.1
HDF	All	286,700	166,100	80,540	48.5	276,000	267,800	228,400	85.3
rHDF <sub>b,t</sub>	All	286,700	166,100	68,480	41.2	276,000	267,800	208,500	77.9
rHDF <sub>b</sub>	All	286,700	166,100	67,450	40.6	276,000	267,800	203,100	75.9
MDG	All	286,700	166,100	76,270	45.9	276,000	267,800	205,100	76.6
PRG	All	286,700	166,100	66,260	39.9	276,000	267,800	177,700	66.3
CEF	1-9	10,180	3,470	2,976	85.8	7,373	7,373	7,357	99.8
HDF	1-9	10,180	2,862	2,303	80.5	7,373	5,517	5,427	98.4
rHDF <sub>b,t</sub>	1-9	10,180	2,862	2,201	76.9	7,373	5,517	5,402	97.9
rHDF <sub>b</sub>	1-9	10,180	2,862	2,196	76.7	7,373	5,517	5,395	97.8
MDG	1-9	10,180	2,862	2,228	77.9	7,373	5,517	5,193	94.1
PRG	1-9	10,180	2,862	2,170	75.8	7,373	5,517	5,054	91.6
CEF	10-49	70,300	34,250	23,300	68.0	61,820	61,820	60,350	97.6
HDF	10-49	70,300	33,730	22,430	66.5	61,820	58,630	56,840	96.9
rHDF <sub>b,t</sub>	10-49	70,300	33,730	19,600	58.1	61,820	58,630	54,540	93.0
rHDF <sub>b</sub>	10-49	70,300	33,730	19,430	57.6	61,820	58,630	53,840	91.8
MDG	10-49	70,300	33,730	20,870	61.9	61,820	58,630	50,620	86.3
PRG	10-49	70,300	33,730	19,010	56.4	61,820	58,630	46,250	78.9
CEF	50-99	66,980	38,160	21,200	55.6	62,760	62,760	58,450	93.1
HDF	50-99	66,980	37,980	20,780	54.7	62,760	60,970	56,440	92.6
rHDF <sub>b,t</sub>	50-99	66,980	37,980	17,120	45.1	62,760	60,970	51,230	84.0
rHDF <sub>b</sub>	50-99	66,980	37,980	16,860	44.4	62,760	60,970	49,880	81.8
MDG	50-99	66,980	37,980	18,980	50.0	62,760	60,970	48,170	79.0
PRG	50-99	66,980	37,980	16,500	43.5	62,760	60,970	41,990	68.9
CEF	100-249	71,870	45,320	20,440	45.1	71,410	71,410	61,190	85.7
HDF	100-249	71,870	45,250	20,240	44.7	71,410	70,400	60,030	85.3
rHDF <sub>b,t</sub>	100-249	71,870	45,250	16,660	36.8	71,410	70,400	52,650	74.8
rHDF <sub>b</sub>	100-249	71,870	45,250	16,350	36.1	71,410	70,400	50,890	72.3
MDG	100-249	71,870	45,250	18,940	41.9	71,410	70,400	52,190	74.1
PRG	100-249	71,870	45,250	16,120	35.6	71,410	70,400	44,310	62.9
CEF	250-499	36,740	24,680	8,923	36.2	37,660	37,660	28,480	75.6
HDF	250-499	36,740	24,670	8,878	36.0	37,660	37,400	28,140	75.3
rHDF <sub>b,t</sub>	250-499	36,740	24,670	7,608	30.8	37,660	37,400	24,940	66.7
rHDF <sub>b</sub>	250-499	36,740	24,670	7,459	30.2	37,660	37,400	24,090	64.4
MDG	250-499	36,740	24,670	8,886	36.0	37,660	37,400	26,520	70.9
PRG	250-499	36,740	24,670	7,409	30.0	37,660	37,400	22,050	59.0
CEF	500-999	21,620	15,090	4,416	29.3	23,270	23,270	15,250	65.5
HDF	500-999	21,620	15,090	4,398	29.2	23,270	23,180	15,110	65.2
rHDF <sub>b,t</sub>	500-999	21,620	15,090	3,898	25.8	23,270	23,180	13,700	59.1
rHDF <sub>b</sub>	500-999	21,620	15,090	3,809	25.3	23,270	23,180	13,230	57.1
MDG	500-999	21,620	15,090	4,664	30.9	23,270	23,180	15,370	66.3
PRG	500-999	21,620	15,090	3,748	24.9	23,270	23,180	12,430	53.6

Table 12 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	1,000+	8,976	6,510	1,510	23.2	11,670	11,670	6,432	55.1
HDF	1,000+	8,976	6,510	1,505	23.1	11,670	11,650	6,403	55.0
rHDF <sub>b,t</sub>	1,000+	8,976	6,510	1,380	21.2	11,670	11,650	5,986	51.4
rHDF <sub>b</sub>	1,000+	8,976	6,510	1,339	20.6	11,670	11,650	5,779	49.6
MDG	1,000+	8,976	6,510	1,699	26.1	11,670	11,650	7,056	60.6
PRG	1,000+	8,976	6,510	1,305	20.1	11,670	11,650	5,576	47.9
PRG	1,000+	8,976	6,510	1,305	20.1	11,670	11,650	5,576	47.9

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. Population for attacker COMRCL is the total number of data-defined records in COMRCL that are also in the CEF universe (see Table 3). Population for attacker CEF<sub>atkr</sub> is the total number of data-defined CEF records.

TABLE 13. Nonmodal Data-Defined Persons: Putative and Confirmed Re-identifications by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	All	17,320	15,330	9,746	63.6	65,850	65,850	42,070	63.9
HDF	All	17,320	14,780	8,967	60.7	65,850	62,530	38,120	61.0
rHDF <sub>b,t</sub>	All	17,320	13,910	6,147	44.2	65,850	62,810	27,180	43.3
rHDF <sub>b</sub>	All	17,320	13,680	5,514	40.3	65,850	62,810	23,990	38.2
MDG	All	17,320	14,780	170	1.2	65,850	62,530	580	0.9
PRG	All	17,320	14,780	2,473	16.7	65,850	62,530	10,000	16.0
CEF	1-9	150	146	143	97.9	480	480	472	98.3
HDF	1-9	150	91	81	89.2	480	276	249	90.2
rHDF <sub>b,t</sub>	1-9	150	88	75	85.4	480	279	240	86.0
rHDF <sub>b</sub>	1-9	150	87	74	84.4	480	279	236	84.7
MDG	1-9	150	91	8	9.0	480	276	20	7.2
PRG	1-9	150	91	29	32.3	480	276	88	31.8
CEF	10-49	2,733	2,537	2,242	88.4	9,545	9,545	8,713	91.3
HDF	10-49	2,733	2,250	1,865	82.9	9,545	7,971	6,904	86.6
rHDF <sub>b,t</sub>	10-49	2,733	2,099	1,435	68.4	9,545	8,084	5,777	71.5
rHDF <sub>b</sub>	10-49	2,733	2,058	1,344	65.3	9,545	8,082	5,397	66.8
MDG	10-49	2,733	2,250	59	2.6	9,545	7,971	184	2.3
PRG	10-49	2,733	2,250	444	19.7	9,545	7,971	1,587	19.9
CEF	50-99	3,957	3,558	2,748	77.2	13,740	13,740	11,200	81.5
HDF	50-99	3,957	3,411	2,527	74.1	13,740	12,790	10,060	78.6
rHDF <sub>b,t</sub>	50-99	3,957	3,143	1,688	53.7	13,740	12,900	7,221	56.0
rHDF <sub>b</sub>	50-99	3,957	3,080	1,525	49.5	13,740	12,900	6,422	49.8
MDG	50-99	3,957	3,411	47	1.4	13,740	12,790	157	1.2
PRG	50-99	3,957	3,411	576	16.9	13,740	12,790	2,111	16.5
CEF	100-249	5,055	4,457	2,797	62.8	18,670	18,670	12,460	66.8
HDF	100-249	5,055	4,400	2,700	61.4	18,670	18,210	11,870	65.2

Table 13 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
rHDF <sub>b,t</sub>	100-249	5,055	4,116	1,706	41.4	18,670	18,260	7,645	41.9
rHDF <sub>b</sub>	100-249	5,055	4,045	1,496	37.0	18,670	18,260	6,553	35.9
MDG	100-249	5,055	4,400	35	0.8	18,670	18,210	132	0.7
PRG	100-249	5,055	4,400	706	16.0	18,670	18,210	2,798	15.4
CEF	250-499	2,703	2,328	1,063	45.6	10,970	10,970	5,275	48.1
HDF	250-499	2,703	2,320	1,047	45.1	10,970	10,870	5,142	47.3
rHDF <sub>b,t</sub>	250-499	2,703	2,219	687	31.0	10,970	10,880	3,337	30.7
rHDF <sub>b</sub>	250-499	2,703	2,188	591	27.0	10,970	10,880	2,807	25.8
MDG	250-499	2,703	2,320	12	0.5	10,970	10,870	51	0.5
PRG	250-499	2,703	2,320	359	15.5	10,970	10,870	1,586	14.6
CEF	500-999	1,807	1,536	537	35.0	7,846	7,846	2,735	34.9
HDF	500-999	1,807	1,534	532	34.7	7,846	7,812	2,690	34.4
rHDF <sub>b,t</sub>	500-999	1,807	1,490	383	25.7	7,846	7,813	1,945	24.9
rHDF <sub>b</sub>	500-999	1,807	1,474	331	22.5	7,846	7,813	1,664	21.3
MDG	500-999	1,807	1,534	6	0.4	7,846	7,812	28	0.4
PRG	500-999	1,807	1,534	236	15.4	7,846	7,812	1,116	14.3
CEF	1,000+	914	771	216	28.1	4,602	4,602	1,213	26.4
HDF	1,000+	914	770	215	28.0	4,602	4,595	1,203	26.2
rHDF <sub>b,t</sub>	1,000+	914	757	174	22.9	4,602	4,595	1,017	22.1
rHDF <sub>b</sub>	1,000+	914	750	154	20.5	4,602	4,595	911	19.8
MDG	1,000+	914	770	2	0.2	4,602	4,595	8	0.2
PRG	1,000+	914	770	122	15.9	4,602	4,595	717	15.6

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. COMRCL and CEF<sub>atkr</sub> use only data-defined records. Only the 106,300,000 records in COMRCL that match CEF on the feature set  $\{pik, block, sex, agebin\}$  (see Table 3) can be used to identify a nonmodal person. For each attacker, the column “Population” shows the number of at-risk records.

TABLE 14. Modal Data-Defined Persons: Putative and Confirmed Reidentifications by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	All	88,930	77,620	73,010	94.1	210,100	210,100	195,400	93.0
HDF	All	88,930	76,300	71,570	93.8	210,100	205,200	190,300	92.7
rHDF <sub>b,t</sub>	All	88,930	69,260	62,330	90.0	210,100	204,900	181,300	88.5
rHDF <sub>b</sub>	All	88,930	69,070	61,940	89.7	210,100	204,900	179,100	87.4
MDG	All	88,930	76,300	76,100	99.7	210,100	205,200	204,500	99.7
PRG	All	88,930	76,300	63,790	83.6	210,100	205,200	167,700	81.7
CEF	1-9	2,901	2,836	2,833	99.9	6,893	6,893	6,886	99.9
HDF	1-9	2,901	2,243	2,222	99.1	6,893	5,241	5,177	98.8
rHDF <sub>b,t</sub>	1-9	2,901	2,151	2,126	98.8	6,893	5,239	5,163	98.5
rHDF <sub>b</sub>	1-9	2,901	2,149	2,123	98.8	6,893	5,239	5,159	98.5



Table 14 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Con- firmed ( $\times 10^{-3}$ )	Preci- sion (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Con- firmed ( $\times 10^{-3}$ )	Preci- sion (%)
MDG	1-9	2,901	2,243	2,220	99.0	6,893	5,241	5,173	98.7
PRG	1-9	2,901	2,243	2,141	95.4	6,893	5,241	4,966	94.8
CEF	10-49	23,020	21,330	21,050	98.7	52,270	52,270	51,630	98.8
HDF	10-49	23,020	20,880	20,570	98.5	52,270	50,660	49,930	98.6
rHDF <sub>b,t</sub>	10-49	23,020	18,830	18,170	96.5	52,270	50,550	48,760	96.5
rHDF <sub>b</sub>	10-49	23,020	18,780	18,090	96.3	52,270	50,550	48,450	95.8
MDG	10-49	23,020	20,880	20,810	99.7	52,270	50,660	50,440	99.6
PRG	10-49	23,020	20,880	18,570	88.9	52,270	50,660	44,660	88.2
CEF	50-99	21,680	19,170	18,450	96.3	49,020	49,020	47,250	96.4
HDF	50-99	21,680	18,990	18,250	96.1	49,020	48,180	46,380	96.3
rHDF <sub>b,t</sub>	50-99	21,680	16,810	15,430	91.8	49,020	48,070	44,010	91.5
rHDF <sub>b</sub>	50-99	21,680	16,760	15,340	91.5	49,020	48,080	43,460	90.4
MDG	50-99	21,680	18,990	18,940	99.7	49,020	48,180	48,010	99.7
PRG	50-99	21,680	18,990	15,930	83.9	49,020	48,180	39,880	82.8
CEF	100-249	22,380	19,010	17,640	92.8	52,740	52,740	48,730	92.4
HDF	100-249	22,380	18,940	17,540	92.6	52,740	52,200	48,150	92.3
rHDF <sub>b,t</sub>	100-249	22,380	17,100	14,960	87.5	52,740	52,140	45,000	86.3
rHDF <sub>b</sub>	100-249	22,380	17,060	14,860	87.1	52,740	52,150	44,330	85.0
MDG	100-249	22,380	18,940	18,900	99.8	52,740	52,200	52,060	99.7
PRG	100-249	22,380	18,940	15,410	81.4	52,740	52,200	41,510	79.5
CEF	250-499	10,920	8,901	7,860	88.3	26,690	26,690	23,200	86.9
HDF	250-499	10,920	8,885	7,831	88.1	26,690	26,520	23,000	86.7
rHDF <sub>b,t</sub>	250-499	10,920	8,278	6,921	83.6	26,690	26,510	21,610	81.5
rHDF <sub>b</sub>	250-499	10,920	8,250	6,868	83.3	26,690	26,510	21,280	80.3
MDG	250-499	10,920	8,885	8,874	99.9	26,690	26,520	26,470	99.8
PRG	250-499	10,920	8,885	7,049	79.3	26,690	26,520	20,460	77.1
CEF	500-999	5,873	4,668	3,879	83.1	15,430	15,430	12,510	81.1
HDF	500-999	5,873	4,663	3,866	82.9	15,430	15,370	12,420	80.8
rHDF <sub>b,t</sub>	500-999	5,873	4,447	3,516	79.1	15,430	15,370	11,760	76.5
rHDF <sub>b</sub>	500-999	5,873	4,426	3,477	78.5	15,430	15,370	11,570	75.3
MDG	500-999	5,873	4,663	4,658	99.9	15,430	15,370	15,340	99.8
PRG	500-999	5,873	4,663	3,512	75.3	15,430	15,370	11,310	73.6
CEF	1,000+	2,147	1,699	1,293	76.1	7,066	7,066	5,219	73.9
HDF	1,000+	2,147	1,699	1,290	76.0	7,066	7,056	5,200	73.7
rHDF <sub>b,t</sub>	1,000+	2,147	1,653	1,206	73.0	7,066	7,056	4,969	70.4
rHDF <sub>b</sub>	1,000+	2,147	1,643	1,185	72.1	7,066	7,056	4,868	69.0
MDG	1,000+	2,147	1,699	1,697	99.9	7,066	7,056	7,048	99.9
PRG	1,000+	2,147	1,699	1,183	69.6	7,066	7,056	4,859	68.9

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. COMRCL and CEF<sub>atkr</sub> use only data-defined records. Only the 106,300,000 records in COMRCL that match CEF on the feature set  $\{pik, block, sex, agebin\}$  (see Table 3) can be used to identify a modal person. For each attacker, the column “Population” shows the number of at-risk records.

TABLE 15. All Data-Defined Persons: Putative and Confirmed Reidentifications Using the 2020 Disclosure Avoidance System Applied to the 2010 Census and Using Specially Swapped Versions of the 2010 Census Edited File by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	All	286,700	167,500	82,760	49.4	276,000	276,000	237,500	86.1
HDF	All	286,700	166,100	80,540	48.5	276,000	267,800	228,400	85.3
rHDF <sub>b,t</sub>	All	286,700	166,100	68,480	41.2	276,000	267,800	208,500	77.9
MDF	All	286,700	112,100	32,790	29.3	276,000	130,800	82,510	63.1
rMDF <sub>b,t</sub>	All	286,700	112,100	32,380	28.9	276,000	130,800	81,670	62.5
rSWAPLo <sub>b,t</sub>	All	286,700	166,200	68,440	41.2	276,000	266,700	207,900	78.0
rSWAPHi <sub>b,t</sub>	All	286,700	154,300	50,600	32.8	276,000	207,100	140,000	67.6
<hr/>									
CEF	1-9	10,180	3,470	2,976	85.8	7,373	7,373	7,357	99.8
HDF	1-9	10,180	2,862	2,303	80.5	7,373	5,517	5,427	98.4
rHDF <sub>b,t</sub>	1-9	10,180	2,862	2,201	76.9	7,373	5,517	5,402	97.9
MDF	1-9	10,180	894	260	29.1	7,373	785	584	74.5
rMDF <sub>b,t</sub>	1-9	10,180	894	260	29.1	7,373	785	584	74.4
rSWAPLo <sub>b,t</sub>	1-9	10,180	3,345	2,719	81.3	7,373	7,016	6,966	99.3
rSWAPHi <sub>b,t</sub>	1-9	10,180	2,273	1,564	68.8	7,373	4,038	3,900	96.6
<hr/>									
CEF	10-49	70,300	34,250	23,300	68.0	61,820	61,820	60,350	97.6
HDF	10-49	70,300	33,730	22,430	66.5	61,820	58,630	56,840	96.9
rHDF <sub>b,t</sub>	10-49	70,300	33,730	19,600	58.1	61,820	58,630	54,540	93.0
MDF	10-49	70,300	15,470	4,966	32.1	61,820	14,950	10,770	72.0
rMDF <sub>b,t</sub>	10-49	70,300	15,470	4,939	31.9	61,820	14,950	10,720	71.7
rSWAPLo <sub>b,t</sub>	10-49	70,300	33,610	19,530	58.1	61,820	58,970	55,000	93.3
rSWAPHi <sub>b,t</sub>	10-49	70,300	28,270	12,870	45.5	61,820	38,790	33,100	85.3
<hr/>									
CEF	50-99	66,980	38,160	21,200	55.6	62,760	62,760	58,450	93.1
HDF	50-99	66,980	37,980	20,780	54.7	62,760	60,970	56,440	92.6
rHDF <sub>b,t</sub>	50-99	66,980	37,980	17,120	45.1	62,760	60,970	51,230	84.0
MDF	50-99	66,980	22,360	6,954	31.1	62,760	23,180	15,570	67.2
rMDF <sub>b,t</sub>	50-99	66,980	22,360	6,896	30.8	62,760	23,180	15,450	66.7
rSWAPLo <sub>b,t</sub>	50-99	66,980	37,790	16,900	44.7	62,760	60,180	50,480	83.9
rSWAPHi <sub>b,t</sub>	50-99	66,980	34,510	12,280	35.6	62,760	44,300	32,500	73.4
<hr/>									
CEF	100-249	71,870	45,320	20,440	45.1	71,410	71,410	61,190	85.7
HDF	100-249	71,870	45,250	20,240	44.7	71,410	70,400	60,030	85.3
rHDF <sub>b,t</sub>	100-249	71,870	45,250	16,660	36.8	71,410	70,400	52,650	74.8
MDF	100-249	71,870	32,330	9,745	30.1	71,410	36,710	23,600	64.3
rMDF <sub>b,t</sub>	100-249	71,870	32,330	9,628	29.8	71,410	36,710	23,370	63.7
rSWAPLo <sub>b,t</sub>	100-249	71,870	45,130	16,470	36.5	71,410	69,080	51,450	74.5
rSWAPHi <sub>b,t</sub>	100-249	71,870	43,060	12,930	30.0	71,410	55,870	35,980	64.4
<hr/>									
CEF	250-499	36,740	24,680	8,923	36.2	37,660	37,660	28,480	75.6
HDF	250-499	36,740	24,670	8,878	36.0	37,660	37,400	28,140	75.3
rHDF <sub>b,t</sub>	250-499	36,740	24,670	7,608	30.8	37,660	37,400	24,940	66.7
MDF	250-499	36,740	20,800	5,974	28.7	37,660	25,640	15,840	61.8
rMDF <sub>b,t</sub>	250-499	36,740	20,800	5,875	28.3	37,660	25,640	15,640	61.0
rSWAPLo <sub>b,t</sub>	250-499	36,740	24,670	7,558	30.6	37,660	36,850	24,500	66.5
rSWAPHi <sub>b,t</sub>	250-499	36,740	24,320	6,338	26.1	37,660	32,110	18,630	58.0

Table 15 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Preci- sion (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Preci- sion (%)
CEF	500-999	21,620	15,090	4,416	29.3	23,270	23,270	15,250	65.5
HDF	500-999	21,620	15,090	4,398	29.2	23,270	23,180	15,110	65.2
rHDF <sub>b,t</sub>	500-999	21,620	15,090	3,898	25.8	23,270	23,180	13,700	59.1
MDF	500-999	21,620	13,920	3,540	25.4	23,270	18,820	10,700	56.9
rMDF <sub>b,t</sub>	500-999	21,620	13,920	3,463	24.9	23,270	18,820	10,540	56.0
rSWAPLo <sub>b,t</sub>	500-999	21,620	15,110	3,892	25.8	23,270	22,980	13,560	59.0
rSWAPHi <sub>b,t</sub>	500-999	21,620	15,220	3,391	22.3	23,270	20,940	10,850	51.8
CEF	1,000+	8,976	6,510	1,510	23.2	11,670	11,670	6,432	55.1
HDF	1,000+	8,976	6,510	1,505	23.1	11,670	11,650	6,403	55.0
rHDF <sub>b,t</sub>	1,000+	8,976	6,510	1,380	21.2	11,670	11,650	5,986	51.4
MDF	1,000+	8,976	6,299	1,346	21.4	11,670	10,700	5,450	50.9
rMDF <sub>b,t</sub>	1,000+	8,976	6,299	1,314	20.9	11,670	10,700	5,357	50.1
rSWAPLo <sub>b,t</sub>	1,000+	8,976	6,524	1,379	21.1	11,670	11,610	5,958	51.3
rSWAPHi <sub>b,t</sub>	1,000+	8,976	6,690	1,233	18.4	11,670	11,010	5,044	45.8

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements. The row rMDF<sub>b,t</sub> (light gray highlight) uses the full reconstruction-abetted reidentification attack on 2010 Census data processed using the 2020 Disclosure Avoidance System with final production parameters and reported using the same tabular schema as the 2010 Census Summary File 1. The row MDF (light gray highlight) implements only the reidentification attack using the Microdata Detail File created from the 2010 Census as input. The rows rSWAPLo<sub>b,t</sub> and rSWAPHi<sub>b,t</sub> (medium gray highlight) implement the full reconstruction-abetted reidentification attack using the specially swapped versions of the 2010 CEF described in the main text.

TABLE 16. Nonmodal Data-Defined Persons: Putative and Confirmed Reidentifications Using the 2020 Disclosure Avoidance System Applied to the 2010 Census and Using Specially Swapped Versions of the 2010 Census Edited File by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Preci- sion (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Preci- sion (%)
CEF	All	17,320	15,330	9,746	63.6	65,850	65,850	42,070	63.9
HDF	All	17,320	14,780	8,967	60.7	65,850	62,530	38,120	61.0
rHDF <sub>b,t</sub>	All	17,320	13,910	6,147	44.2	65,850	62,810	27,180	43.3
MDF	All	17,320	8,782	1,795	20.4	65,850	35,360	7,192	20.3
rMDF <sub>b,t</sub>	All	17,320	8,778	1,775	20.2	65,850	35,380	7,108	20.1
rSWAPLo <sub>b,t</sub>	All	17,320	14,130	6,456	45.7	65,850	63,920	28,720	44.9
rSWAPHi <sub>b,t</sub>	All	17,320	12,240	4,235	34.6	65,850	51,600	17,170	33.3
CEF	1-9	150	146	143	97.9	480	480	472	98.3
HDF	1-9	150	91	81	89.2	480	276	249	90.2
rHDF <sub>b,t</sub>	1-9	150	88	75	85.4	480	279	240	86.0
MDF	1-9	150	18	5	26.4	480	56	14	25.5
rMDF <sub>b,t</sub>	1-9	150	18	5	26.2	480	56	14	25.4
rSWAPLo <sub>b,t</sub>	1-9	150	135	127	94.3	480	457	432	94.6

Table 16 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Preci- sion (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Preci- sion (%)
rSWAPHi <sub>b,t</sub>	1-9	150	80	68	85.2	480	264	229	86.5
CEF	10-49	2,733	2,537	2,242	88.4	9,545	9,545	8,713	91.3
HDF	10-49	2,733	2,250	1,865	82.9	9,545	7,971	6,904	86.6
rHDF <sub>b,t</sub>	10-49	2,733	2,099	1,435	68.4	9,545	8,084	5,777	71.5
MDF	10-49	2,733	745	160	21.5	9,545	2,404	538	22.4
rMDF <sub>b,t</sub>	10-49	2,733	745	160	21.5	9,545	2,405	535	22.3
rSWAPLo <sub>b,t</sub>	10-49	2,733	2,256	1,645	72.9	9,545	9,110	6,920	76.0
rSWAPHi <sub>b,t</sub>	10-49	2,733	1,633	921	56.4	9,545	6,017	3,647	60.6
CEF	50-99	3,957	3,558	2,748	77.2	13,740	13,740	11,200	81.5
HDF	50-99	3,957	3,411	2,527	74.1	13,740	12,790	10,060	78.6
rHDF <sub>b,t</sub>	50-99	3,957	3,143	1,688	53.7	13,740	12,900	7,221	56.0
MDF	50-99	3,957	1,550	322	20.8	13,740	5,147	1,087	21.1
rMDF <sub>b,t</sub>	50-99	3,957	1,550	321	20.7	13,740	5,148	1,079	21.0
rSWAPLo <sub>b,t</sub>	50-99	3,957	3,176	1,751	55.1	13,740	13,180	7,583	57.5
rSWAPHi <sub>b,t</sub>	50-99	3,957	2,595	1,067	41.1	13,740	9,708	4,149	42.7
CEF	100-249	5,055	4,457	2,797	62.8	18,670	18,670	12,460	66.8
HDF	100-249	5,055	4,400	2,700	61.4	18,670	18,210	11,870	65.2
rHDF <sub>b,t</sub>	100-249	5,055	4,116	1,706	41.4	18,670	18,260	7,645	41.9
MDF	100-249	5,055	2,636	538	20.4	18,670	9,668	1,981	20.5
rMDF <sub>b,t</sub>	100-249	5,055	2,636	533	20.2	18,670	9,673	1,958	20.2
rSWAPLo <sub>b,t</sub>	100-249	5,055	4,101	1,700	41.4	18,670	18,080	7,585	42.0
rSWAPHi <sub>b,t</sub>	100-249	5,055	3,637	1,156	31.8	18,670	14,680	4,557	31.0
CEF	250-499	2,703	2,328	1,063	45.6	10,970	10,970	5,275	48.1
HDF	250-499	2,703	2,320	1,047	45.1	10,970	10,870	5,142	47.3
rHDF <sub>b,t</sub>	250-499	2,703	2,219	687	31.0	10,970	10,880	3,337	30.7
MDF	250-499	2,703	1,772	354	20.0	10,970	7,502	1,493	19.9
rMDF <sub>b,t</sub>	250-499	2,703	1,771	350	19.8	10,970	7,506	1,471	19.6
rSWAPLo <sub>b,t</sub>	250-499	2,703	2,213	679	30.7	10,970	10,750	3,270	30.4
rSWAPHi <sub>b,t</sub>	250-499	2,703	2,085	527	25.3	10,970	9,442	2,237	23.7
CEF	500-999	1,807	1,536	537	35.0	7,846	7,846	2,735	34.9
HDF	500-999	1,807	1,534	532	34.7	7,846	7,812	2,690	34.4
rHDF <sub>b,t</sub>	500-999	1,807	1,490	383	25.7	7,846	7,813	1,945	24.9
MDF	500-999	1,807	1,337	268	20.0	7,846	6,361	1,234	19.4
rMDF <sub>b,t</sub>	500-999	1,807	1,336	262	19.6	7,846	6,364	1,217	19.1
rSWAPLo <sub>b,t</sub>	500-999	1,807	1,489	381	25.6	7,846	7,755	1,916	24.7
rSWAPHi <sub>b,t</sub>	500-999	1,807	1,451	329	22.7	7,846	7,118	1,467	20.6
CEF	1,000+	914	771	216	28.1	4,602	4,602	1,213	26.4
HDF	1,000+	914	770	215	28.0	4,602	4,595	1,203	26.2
rHDF <sub>b,t</sub>	1,000+	914	757	174	22.9	4,602	4,595	1,017	22.1
MDF	1,000+	914	723	148	20.5	4,602	4,224	844	20.0
rMDF <sub>b,t</sub>	1,000+	914	722	144	20.0	4,602	4,225	834	19.7
rSWAPLo <sub>b,t</sub>	1,000+	914	757	173	22.9	4,602	4,582	1,012	22.1
rSWAPHi <sub>b,t</sub>	1,000+	914	756	166	22.0	4,602	4,368	880	20.2

Table 16 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements.

COMRCL and CEF<sub>atkr</sub> use only data-defined records. See notes to Table 13 for details of the universe for nonmodal data-defined persons in the COMRCL data. The column “Population” for each attacker is the number of at-risk records. The row rMDF<sub>b,t</sub> (light gray highlight) uses the full reconstruction-abetted reidentification attack on 2010 Census using the 2020 Disclosure Avoidance System with final production data processed parameters and reported using the same tabular schema as the 2010 Census Summary File 1. The row MDF (light gray highlight) implements only the reidentification attack using the Microdata Detail File created from the 2010 Census as input. The rows rSWAPLo<sub>b,t</sub> and rSWAPHi<sub>b,t</sub> (medium gray highlight) implement the full reconstruction-abetted reidentification attack using the specially swapped versions of the 2010 CEF described in the main text.

TABLE 17. Modal Data-Defined Persons: Putative and Confirmed Reidentifications Using the 2020 Disclosure Avoidance System Applied to the 2010 Census and Using Specially Swapped Versions of the 2010 Census Edited File by Census Block Size

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Popu- lation ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
CEF	All	88,930	77,620	73,010	94.1	210,100	210,100	195,400	93.0
HDF	All	88,930	76,300	71,570	93.8	210,100	205,200	190,300	92.7
rHDF <sub>b,t</sub>	All	88,930	69,260	62,330	90.0	210,100	204,900	181,300	88.5
MDF	All	88,930	37,350	30,990	83.0	210,100	95,410	75,320	78.9
rMDF <sub>b,t</sub>	All	88,930	37,220	30,600	82.2	210,100	95,400	74,560	78.2
rSWAPLo <sub>b,t</sub>	All	88,930	68,950	61,990	89.9	210,100	202,800	179,200	88.4
rSWAPHi <sub>b,t</sub>	All	88,930	56,500	46,360	82.1	210,100	155,500	122,800	79.0
CEF	1-9	2,901	2,836	2,833	99.9	6,893	6,893	6,886	99.9
HDF	1-9	2,901	2,243	2,222	99.1	6,893	5,241	5,177	98.8
rHDF <sub>b,t</sub>	1-9	2,901	2,151	2,126	98.8	6,893	5,239	5,163	98.5
MDF	1-9	2,901	317	256	80.7	6,893	729	570	78.2
rMDF <sub>b,t</sub>	1-9	2,901	317	255	80.5	6,893	729	569	78.1
rSWAPLo <sub>b,t</sub>	1-9	2,901	2,602	2,592	99.6	6,893	6,558	6,533	99.6
rSWAPHi <sub>b,t</sub>	1-9	2,901	1,535	1,496	97.5	6,893	3,773	3,672	97.3
CEF	10-49	23,020	21,330	21,050	98.7	52,270	52,270	51,630	98.8
HDF	10-49	23,020	20,880	20,570	98.5	52,270	50,660	49,930	98.6
rHDF <sub>b,t</sub>	10-49	23,020	18,830	18,170	96.5	52,270	50,550	48,760	96.5
MDF	10-49	23,020	5,714	4,805	84.1	52,270	12,540	10,230	81.6
rMDF <sub>b,t</sub>	10-49	23,020	5,707	4,779	83.7	52,270	12,540	10,190	81.2
rSWAPLo <sub>b,t</sub>	10-49	23,020	18,550	17,880	96.4	52,270	49,860	48,080	96.4
rSWAPHi <sub>b,t</sub>	10-49	23,020	13,230	11,950	90.3	52,270	32,770	29,450	89.9
CEF	50-99	21,680	19,170	18,450	96.3	49,020	49,020	47,250	96.4
HDF	50-99	21,680	18,990	18,250	96.1	49,020	48,180	46,380	96.3
rHDF <sub>b,t</sub>	50-99	21,680	16,810	15,430	91.8	49,020	48,070	44,010	91.5
MDF	50-99	21,680	7,942	6,632	83.5	49,020	18,030	14,480	80.3

Table 17 Continued

Data Set	Block Size	Attacker: COMRCL				Attacker: CEF <sub>atkr</sub>			
		Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)	Population ( $\times 10^{-3}$ )	Putative ( $\times 10^{-3}$ )	Confirmed ( $\times 10^{-3}$ )	Precision (%)
rMDF <sub>b,t</sub>	50-99	21,680	7,929	6,575	82.9	49,020	18,030	14,370	79.7
rSWAPLo <sub>b,t</sub>	50-99	21,680	16,550	15,150	91.6	49,020	47,000	42,890	91.3
rSWAPHi <sub>b,t</sub>	50-99	21,680	13,420	11,210	83.5	49,020	34,590	28,360	82.0
CEF	100-249	22,380	19,010	17,640	92.8	52,740	52,740	48,730	92.4
HDF	100-249	22,380	18,940	17,540	92.6	52,740	52,200	48,150	92.3
rHDF <sub>b,t</sub>	100-249	22,380	17,100	14,960	87.5	52,740	52,140	45,000	86.3
MDF	100-249	22,380	10,980	9,207	83.8	52,740	27,050	21,620	79.9
rMDF <sub>b,t</sub>	100-249	22,380	10,950	9,095	83.1	52,740	27,040	21,410	79.2
rSWAPLo <sub>b,t</sub>	100-249	22,380	16,930	14,770	87.2	52,740	51,000	43,870	86.0
rSWAPHi <sub>b,t</sub>	100-249	22,380	14,850	11,770	79.3	52,740	41,190	31,420	76.3
CEF	250-499	10,920	8,901	7,860	88.3	26,690	26,690	23,200	86.9
HDF	250-499	10,920	8,885	7,831	88.1	26,690	26,520	23,000	86.7
rHDF <sub>b,t</sub>	250-499	10,920	8,278	6,921	83.6	26,690	26,510	21,610	81.5
MDF	250-499	10,920	6,724	5,620	83.6	26,690	18,140	14,350	79.1
rMDF <sub>b,t</sub>	250-499	10,920	6,689	5,525	82.6	26,690	18,130	14,170	78.2
rSWAPLo <sub>b,t</sub>	250-499	10,920	8,237	6,879	83.5	26,690	26,100	21,230	81.3
rSWAPHi <sub>b,t</sub>	250-499	10,920	7,609	5,811	76.4	26,690	22,670	16,400	72.3
CEF	500-999	5,873	4,668	3,879	83.1	15,430	15,430	12,510	81.1
HDF	500-999	5,873	4,663	3,866	82.9	15,430	15,370	12,420	80.8
rHDF <sub>b,t</sub>	500-999	5,873	4,447	3,516	79.1	15,430	15,370	11,760	76.5
MDF	500-999	5,873	4,067	3,272	80.5	15,430	12,450	9,468	76.0
rMDF <sub>b,t</sub>	500-999	5,873	4,039	3,201	79.3	15,430	12,450	9,319	74.9
rSWAPLo <sub>b,t</sub>	500-999	5,873	4,439	3,511	79.1	15,430	15,230	11,640	76.4
rSWAPHi <sub>b,t</sub>	500-999	5,873	4,236	3,062	72.3	15,430	13,820	9,383	67.9
CEF	1,000+	2,147	1,699	1,293	76.1	7,066	7,066	5,219	73.9
HDF	1,000+	2,147	1,699	1,290	76.0	7,066	7,056	5,200	73.7
rHDF <sub>b,t</sub>	1,000+	2,147	1,653	1,206	73.0	7,066	7,056	4,969	70.4
MDF	1,000+	2,147	1,603	1,198	74.8	7,066	6,477	4,606	71.1
rMDF <sub>b,t</sub>	1,000+	2,147	1,591	1,169	73.5	7,066	6,476	4,523	69.8
rSWAPLo <sub>b,t</sub>	1,000+	2,147	1,653	1,205	72.9	7,066	7,030	4,945	70.3
rSWAPHi <sub>b,t</sub>	1,000+	2,147	1,617	1,066	65.9	7,066	6,641	4,164	62.7

Notes: Counts rounded to four significant digits to conform to disclosure limitation requirements.

COMRCL and CEF<sub>atkr</sub> use only data-defined records. See notes to Table 14 for details of the universe for nonmodal data-defined persons in the COMRCL data. The column “Population” for each attacker is the number of at-risk records. The row rMDF<sub>b,t</sub> (light gray highlight) uses the full reconstruction-abetted reidentification attack on 2010 Census using the 2020 Disclosure Avoidance System with final production data processed parameters and reported using the same tabular schema as the 2010 Census Summary File 1. The row MDF (light gray highlight) implements only the reidentification attack using the Microdata Detail File created from the 2010 Census as input. The rows rSWAPLo<sub>b,t</sub> and rSWAPHi<sub>b,t</sub> (medium gray highlight) implement the full reconstruction-abetted reidentification attack using the specially swapped versions of the 2010 CEF described in the main text.

the swapping experiment code supporting the study of reconstruction-abetted reidentification using variants of the 2010 swapping algorithm. The 2010 swapping algorithm includes a match key and geographic constraints. The match key gives the aspects of the household that must be identical among any pair of swapped households. The algorithm used here is more flexible than the actual 2010 swapping algorithm with respect to geography: it favors swapping households within particular geographic boundaries, but it will allow some percentage of swaps outside of those boundaries.

Our testing algorithm retains the general framework of the 2010 swapping algorithm but uses additional randomness to widen the range of possible swaps. For the match key, we use a noisy version of the household size (number of people), so that households that agree on the match key will sometimes differ in size by  $\pm 1$  or 2. We also create a noisy version of the household's geography and attempt to swap records that agree on those noisy values, thus deliberately creating swaps across geographic boundaries and controlling the frequencies of such swaps. The swap header file, which controls the overall swap target rate, includes the settings for the perturbations in household size and geography. The 2010 algorithm also prioritizes households for swapping based on measures of their risk of being reidentified. Our testing algorithm gives every household equal probability of being swapped.

The match key is *noisy household size*. We add discrete noise from the set  $\{-1,0,1\}$  to household size and then use the noisy household size as the swapping match key. Households are randomly assigned to one of three groups:

- No change in household size
- Household size increase by 1 person
- Household size decrease by 1 person

The noisy household groups are assigned randomly based on probabilities specified before running the code. For example, if we want 50% of records to keep the same household size value, 25% to increase by 1, and 25% to decrease by 1, then we randomly assign records to groups such that each record has a 50% chance of being assigned group 1, 25% chance of being assigned group 2, and 25% chance of being assigned group 3. The noisy household size is then used in the match key. Variables used in the match key must match exactly between swapped records. Households retain their original size. The noisy household sizes are used only to facilitate the swapping and may be discarded after the swapping is performed.

Assigning 100% of households to group 1 and 0% to the other groups tunes the noise to zero and reverts to the original 2010 version of household size in the match key. This scheme only allows households to swap with other households that are different in size by at most 2. This change to the swap protocol eliminates the block-level population invariant, making the swapping more comparable to the DAS treatment of population.

We explored three different noise distributions:

- 0% probability of decreasing by 1 person, 100% probability of staying the same, 0% probability of increasing by 1 person,
- 25% probability of decreasing by 1 person, 50% probability of staying the same, 25% probability of increasing by 1 person,
- 10% probability of decreasing by 1 person, 80% probability of staying the same, 10% probability of increasing by 1 person,
- 40% probability of decreasing by 1 person, 20% probability of staying the same, 40% probability of increasing by 1 person.

We also created *noisy pseudo-geographies* for the swapping experiments. For the purpose of determining swaps, each household also receives a noisy pseudo-geography. First, we split the

households in the state randomly into groups 1, 2 and 3, based on i.i.d. draws from a discrete distribution on these three values with predetermined probabilities (for example, 50% in group 1, 30% in group 2, 20% in group 3). For households in group 1, the pseudo-tract is equal to the household's actual tract. For households in group 2, group households into counties. Within each county, randomly permute the tract of group 2 households, and assign a pseudo-tract based on the permutation (e.g., the first household's pseudo-tract is the first tract in the permuted list of tracts). A household's pseudo-county is equal to the household's original county. For households in group 3, randomly permute the list of tracts of group 3 households within state, and assign pseudo-tract based on that permutation (e.g., the first household's pseudo-tract is the first tract in the permuted list of tracts). Each household's pseudo-county is the county associated with its pseudo-tract. For all groups, also retain the original tract and county. Under this scheme, each pseudo-tract has the same number of housing units as the corresponding original geography. The pseudo-geography algorithm used the following probabilities for assigning groups 1, 2 and 3:

- Tract unperturbed (group 1) 100%, tract perturbed within county (group 2) 0%, tract perturbed within state (group 3) 0% (household size unperturbed)
- Group 1 30%, group 2 40%, group 3 30%,
- Group 1 50%, group 2 30%, group 3 20%,
- Group 1 50%, group 2 10%, group 3 40%.

When the swapping algorithm is run, swaps are between households within the same pseudo-tract whenever possible; when that's not possible, swaps are between households within the same pseudo-county (regardless, swap households only if they have the same value for the match key, i.e., the same perturbed household size bin). Smaller match keys allow for higher swap rates within geography; the pseudo-tract construct will allow more swaps outside of actual tract with these smaller keys. Pseudo-geographies are discarded after the algorithm has been run unless needed for auditing, as their only purpose is to facilitate swapping. Tuning the probabilities with which households are assigned to each group allows us to control the approximate probabilities of swapping within and across different geographic levels (the probabilities are a function of the group proportions and the sizes of different geographic levels).

The results labeled  $\text{rSWAPLo}_{b,t}$  in the main text used a 5% swap rate, the (0%, 100%, 0%) household size noise parameters (household size was not perturbed), and the (100%, 0%, 0%) pseudo-geography parameters (all swaps were within tract). The results labeled  $\text{rSWAPHi}_{b,t}$  in the main text used a 50% swap rate, the (25%, 50%, 25%) household size noise parameters, and the (30%, 40%, 30%) pseudo-geography parameters.

#### APPENDIX D. THE EFFECTS OF THE 1980 SUPPRESSION RULES IF APPLIED TO THE 2010 CENSUS SUMMARY FILE 1

To study the suppression rules as implemented in the 1980 Census, we had to coarsen the 63-category race feature. Using the full set of race categories would have resulted in nearly all tables suppressed. We implemented coarsening based on the Office of Management and Budget (1997) version of Statistical Policy Directive 15 as adopted in 1997 by the Department of Justice Voting Section at that time for use in the redistricting that followed the 2000 Census. The coarsened race categories are:

- White alone
- Black alone or in combination with White
- Asian alone or in combination with White
- Native Hawaiian or other Pacific Islander alone or in combination with White



- 1869       • American Indian or Alaska Native alone or in combination with White
- 1870       • Some other race alone or in combination with White
- 1871       • Two or more races, except as explicitly noted in the categories above

1872 We used the same Hispanic or Latino feature as in the 2010 Census:

- 1873       • Hispanic or Latino
- 1874       • Not Hispanic or Latino

1875 The rules for the P.L. 94-171 Redistricting Data Summary File were:

- 1876       • Table Suppression: Whole tables were suppressed (not published) for geographies with  
1877       between 1 and 14 persons in any of the race/ethnicity groups; applied to
  - 1878       – Redistricting Table P3 (SF1 Table P10) Race for the Population 18 Years and Over,  
1879       and
  - 1880       – Redistricting Table P4 (SF1 Table P11) Hispanic or Latino, and not Hispanic or  
1881       Latino, by Race for the Population 18 Years and Over
- 1882       • Cell Suppression: Cell counts of 1 or 2 were replaced by 0; applied to
  - 1883       – Redistricting Table P1 (SF1 Table P8) Race
  - 1884       – Redistricting Table P2 (SF1 Table P9) Hispanic or Latino, and not Hispanic or Latino  
1885       by Race
- 1886       • Additional Summary File 1 (SF1) Tables
  - 1887       – Table Suppression: For all person-level tables, whole tables that are not dedicated  
1888       solely to race and ethnicity data were suppressed if their geographies had total pop-  
1889       ulations between 1 and 14 persons

**Table 18.** 1980 Primary Cell Suppression Rules Applied to Selected Tables from the 2010 Census

Geography	Total Cells	Cells Changed to Zero	Percentage of Cells Changed
Panel A: P.L. 94-171 Table P1 (SF1 P8)			
Race			
National	7	0	0.0
State	357	0	0.0
County	22,001	530	2.4
Tract	507,717	28,024	5.5
Block Group	1,518,048	153,914	10.1
Block	43,449,189	3,538,888	8.1
Panel B: P.L. 94-171 Table P2 (SF1 P9)			
Hispanic or Latino, and Not Hispanic or Latino by Race			
National	14	0	0.0
State	714	0	0.0
County	44,002	2,987	6.8
Tract	1,015,434	110,081	10.8
Block Group	3,036,096	440,539	14.5
Block	86,898,378	5,071,570	5.8
Panel C: P.L. 94-171 Table P3 (SF1 P10)			
Race For The Population 18 Years and Over			
National	1	0	0.0
State	51	0	0.0
County	3,143	1,610	51.2
Tract	72,531	61,177	84.3
Block Group	216,864	207,643	95.7
Block	6,206,505	5,204,047	83.8
Panel D: P.L. 94-171 Table P4 (SF1 P11)			
Hispanic or Latino, and not Hispanic or Latino by Race for the Population 18 Years and Over			
National	14	0	0.0
State	714	0	0.0
County	44,002	4,078	9.3
Tract	1,015,434	146,400	14.4
Block Group	3,036,096	533,314	17.6
Block	86,891,070	5,822,712	6.7

Notes: The four tables shown here are the basic redistricting data tables in the 1980 format (U.S. Census Bureau, 2006) using table numbers from the 2010 Census. The 1980-format tables are equivalent to the fully saturated table  $\{\text{age under 18, age 18+}\} \times \{\text{Hispanic or Latino, Not Hispanic or Latino}\} \times \{\text{7-category race variable}\}$ , which has 28 total interior cells. This is much less sparse than the official 2010 P.L. 94-171 redistricting tables, where the 7-category race variable used here was replaced with a 63-category race variable, creating a fully saturated contingency table with 252 interior cells (U.S. Census Bureau, 2012, SF1 table numbering). The vast majority of the official 2010 redistricting data would have failed the primary suppression tests shown here.

**Table 19.** 1980 Primary Table Suppression Rules Applied to Selected Tables from the 2010 Census

Geography	Total Tables	Suppressed Tables	Percentage of Tables Suppressed
Panel A: P.L. 94-171 Table P3 (SF1 P10)			
Race For The Population 18 Years and Over			
National	1	0	0.0
State	51	0	0.0
County	3,143	1,610	51.2
Tract	72,531	61,177	84.3
Block Group	216,864	207,643	95.7
Block	6,206,505	5,204,047	83.8
Panel B: P.L. 94-171 Table P4 (SF1 P11)			
Hispanic or Latino, and not Hispanic or Latino by Race for the Population 18 Years and Over			
National	1	0	0.0
State	51	0	0.0
County	3,143	2,645	84.2
Tract	72,531	72,346	99.7
Block Group	216,864	216,759	100.0
Block	6,206,505	5,445,153	87.7
Panel C: Geographies Meeting Criteria for Person Table Suppression in 2010 Summary File 1			
National	1	0	0.0
State	51	0	0.0
County	3,143	0	0.0
Tract	72,531	131	0.2
Block Group	216,864	204	0.1
Block	6,207,027	2,401,802	38.7

Notes: The two redistricting tables shown here use the 1980 table suppression rules applied to tables defined in the 2010 SF1. P.L. 94-171. The SF1 table shows the number of geographies that would fail the 1980 population threshold for including any table that does not have race or ethnicity as a margin. Tables P3 and P4 have been reformatted to 1980 specifications as noted in Table 18.

- 1891 Abowd, J. M. (2018). The U.S. Census Bureau adopts differential privacy. *Proceedings of the 24th*  
1892 *ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 2867–  
1893 2867. <https://doi.org/10.1145/3219819.3226070>
- 1894 Abowd, J. M. (2019). Staring down the database reconstruction theorem [Presentation to the 2019  
1895 Annual Meetings of the American Association for the Advancement of Science, talk: [https://bpb-us-e1.wpmucdn.com/blogs.cornell.edu/dist/4/7616/files/2019/04/2019-02-16-](https://bpb-us-e1.wpmucdn.com/blogs.cornell.edu/dist/4/7616/files/2019/04/2019-02-16-Abowd-AAAS-Talk-Saturday-330-500-session-FINAL-as-delivered-2jr4lzb.pdf)  
1896 [Abowd-AAAS-Talk-Saturday-330-500-session-FINAL-as-delivered-2jr4lzb.pdf](https://bpb-us-e1.wpmucdn.com/blogs.cornell.edu/dist/4/7616/files/2019/04/2019-02-16-Abowd-AAAS-Talk-Saturday-330-500-session-FINAL-as-delivered-2jr4lzb.pdf), slides:  
1897 [https://bpb-us-e1.wpmucdn.com/blogs.cornell.edu/dist/4/7616/files/2019/04/2019-](https://bpb-us-e1.wpmucdn.com/blogs.cornell.edu/dist/4/7616/files/2019/04/2019-02-16-Abowd-AAAS-Slides-Saturday-330-500-session-FINAL-as-delivered-1iqsdg2.pdf)  
1898 [02-16-Abowd-AAAS-Slides-Saturday-330-500-session-FINAL-as-delivered-1iqsdg2.pdf](https://bpb-us-e1.wpmucdn.com/blogs.cornell.edu/dist/4/7616/files/2019/04/2019-02-16-Abowd-AAAS-Slides-Saturday-330-500-session-FINAL-as-delivered-1iqsdg2.pdf),  
1899 retrieved October 11, 2023].
- 1901 Abowd, J. M. (2021). Second Declaration, Civ. A. No. 1:21-cv-01361 (ABJ), in *Fair Lines Amer-*  
1902 *ica Foundation, Inc., v. United States Department of Commerce*, Appendix B [Retrieved

- December 6, 2023]. <https://www2.census.gov/about/policies/foia/records/disclosure-avoidance/appendix-b-summary-of-simulated-reconstruction-abetted-re-identification-attack.pdf>
- Abowd, J. M., Ashmead, R., Cumings-Menon, R., Garfinkel, S., Heineck, M., Heiss, C., Johns, R., Kifer, D., Leclerc, P., Machanavajjhala, A., Moran, B., Sexton, W., Spence, M., & Zhuravlev, P. (2022). The 2020 Census Disclosure Avoidance System TopDown Algorithm. *Harvard Data Science Review, Special Issue 2*. <https://doi.org/10.1162/99608f92.529e3cb9>
- Abowd, J. M., & Hawes, M. B. (2023). Confidentiality protection in the 2020 US Census of Population and Housing. *Annual Review of Statistics and Its Application*, 10(1), 119–144. <https://doi.org/10.1146/annurev-statistics-010422-034226>
- American Cancer Society. (undated). *History of the cancer prevention studies*. Retrieved September 29, 2023, from <https://www.cancer.org/research/population-science/cancer-prevention-and-survivorship-research-team/acs-cancer-prevention-studies/history-cancer-prevention-study.html>
- Ayoz, K., Ayday, E., & Cicek, A. E. (2021). Genome reconstruction attacks against genomic data-sharing beacons. *Proceedings on Privacy Enhancing Technologies. Privacy Enhancing Technologies Symposium, 2021*, 28. <https://doi.org/10.2478/popets-2021-0036>
- Brown, J. D., Cohen, S. R., Denoeux, G., Dorinski, S., Heggeness, M. L., Lieberman, C., McBride, L., Murray-Close, M., Qin, H., Ross, A. E., Sandler, D. H., Warren, L., & Yi, M. (2023). *Real-Time 2020 Administrative Record Census Simulation* (tech. rep.) (Retrieved October 7, 2023). U.S. Census Bureau. <https://www2.census.gov/programs-surveys/decennial/2020/program-management/evaluate-docs/EAE-2020-admin-records-experiment.pdf>
- Childs, J. H., Fobia, A. C., King, R., & Morales, G. (2019). Trust and Credibility in the U.S. Federal Statistical System. *Survey Methods: Insights from the Field*. <https://doi.org/10.13094/SMIF-2019-00001>
- Childs, J. H., Eggleston, C., & Fobia, A. C. (2020). Measuring Privacy and Accuracy Concerns for 2020 Census Data Dissemination [retrieved September 29, 2023]. [https://www.bigsurv.org/bigsurv20/uploads/25/82/Childs\\_BigSurv20\\_Paper\\_10.15.2020.pdf](https://www.bigsurv.org/bigsurv20/uploads/25/82/Childs_BigSurv20_Paper_10.15.2020.pdf)
- Childs, J. H., King, R., & Fobia, A. (2015). Trust and Credibility in the U.S. Federal Statistical System. *Survey Practice*, 8(5). <https://doi.org/10.29115/SP-2015-0024>
- Childs, J. H., Willson, S., Martinez, S. W., Rasmussen, L., & Wroblewski, M. (2012). Development of the Federal Statistical System Public Opinion Survey [Retrieved September 29, 2023]. *JSM Proceedings Survey Research Methods Section*. [http://www.asasrms.org/Proceedings/y2012/Files/400242\\_500695.pdf](http://www.asasrms.org/Proceedings/y2012/Files/400242_500695.pdf)
- Christ, M., Radway, S., & Bellovin, S. (2022). Differential Privacy and Swapping: Examining De-Identification’s Impact on Minority Representation and Privacy Preservation in the U.S. Census. *2022 IEEE Symposium on Security and Privacy (SP)*, 457–472. <https://doi.ieeecomputersociety.org/10.1109/SP46214.2022.9833668>.
- Cox, L. (1995). Network models for complementary cell suppression. *Journal of the American Statistical Association*, 90(432), 1453–62. <https://doi.org/10.2307/2291538>
- Cumings-Menon, R., Ashmead, R., Kifer, D., Leclerc, P., Spence, M., Zhuravlev, P., & Abowd, J. M. (2023). *Disclosure Avoidance for the 2020 Census Demographic and Housing Characteristics File* (tech. rep.). U.S. Census Bureau.
- Dick, T., Dwork, C., Kearns, M., Liu, T., Roth, A., Vietrie, G., & Wu, Z. S. (2023). Confidence-ranked reconstruction of census microdata from published statistics. *Proceedings of the National Academy of Sciences of the United States of America*, 120(8), e2218605120. <https://doi.org/10.1073/pnas.2218605120>
- Dinur, I., & Nissim, K. (2003). Revealing information while preserving privacy. *Proceedings of the Twenty-second ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems*, 202–210. <https://doi.org/10.1145/773153.773173>

- Dove, I., Blanchard, S., & Spicer, K. (2021). Applying Cell-Key Perturbation to 2021 Census Outputs [Retrieved December 8, 2023]. <https://analysisfunction.civilservice.gov.uk/wp-content/uploads/2017/01/ExN-Disclosure-control-methodology-in-2021-Census-outputs-Spicer-Blanchard-Dove-ONS.docx>
- Duncan, G. T., Elliot, M., & Salazar-González, J.-J. (2011). *Statistical Confidentiality Principles and Practice*. Springer New York. <https://doi.org/10.1007/978-1-4419-7802-8>
- Dwork, C. (2011). A firm foundation for private data analysis. *Communications of the ACM*, 54(1), 86–95. <https://doi.org/10.1145/1866739.1866758>
- Dwork, C., & Lei, J. (2009). Differential privacy and robust statistics. *Proceedings of the Forty-First Annual ACM Symposium on Theory of Computing*, 371–380. <https://doi.org/10.1145/1536414.1536466>
- Dwork, C., & Roth, A. (2014). *The Algorithmic Foundations of Differential Privacy* [Also published as “Foundations and Trends in Theoretical Computer Science” Vol. 9, Nos. 3–4 (2014) 211–407.]. now publishers, Inc.
- Dwork, C., Smith, A., Steinke, T., & Ullman, J. (2017). Exposed! a survey of attacks on private data. *Annual Review of Statistics and Its Application*, 4(1), 61–84. <https://doi.org/10.1146/annurev-statistics-060116-054123>
- Elliot, M., & Domingo-Ferrer, J. (2018). The future of statistical disclosure control. <https://doi.org/10.48550/ARXIV.1812.09204>
- Favato, D. F., Coutinho, G., Alvim, M. S., & Fernandes, N. (2022). A novel reconstruction attack on foreign-trade official statistics, with a Brazilian case study. *arXiv preprint*. <https://doi.org/10.48550/arXiv.2206.06493>
- Francis, P. (2022). A Note on the Misinterpretation of the US Census Re-identification Attack [retrieved 12/09/2023]. <https://doi.org/10.48550/ARXIV.2202.04872>
- Garfinkel, S. (2015). *De-Identification of Personal Information* (Internal Report No. 8053). National Institute of Standards and Technology. <https://doi.org/10.6028/NIST.IR.8053>
- Garfinkel, S. (2023). Legacy statistical disclosure limitation techniques were not an option for the 2020 US Census of Population and Housing. *Journal of Official Statistics*, 39(3), 399–410. <https://doi.org/10.2478/JOS-2023-0018>
- Garfinkel, S., Abowd, J. M., & Martindale, C. (2018). Understanding Database Reconstruction Attacks on Public Data. *acmqueue*, 16(5). <https://queue.acm.org/detail.cfm?id=3295691>
- Garfinkel, S., Near, J., Dajani, A., Singer, P., & Guttman, B. (2023). *De-Identifying Government Datasets: Techniques and Governance* (tech. rep.). NIST. <https://doi.org/10.6028/NIST.SP.800-188>
- Hammond, E. C., & Horn, D. (1954). The relationship between human smoking habits and death rates: A follow-up study of 187,866 men. *JAMA*, 155(15), 1316–28. <https://doi.org/10.1001/jama.1954.03690330020006>
- Harris-Kojetin, B. A., Alvey, W. L., Carlson, L., Cohen, S. B., Cohen, S. H., Cox, L. H., Fay, R. E., Fecso, R., Fixler, D., Gates, G., Graubard, B., Iwig, W., Kennickell, A., Kirkendall, N. J., Schechter, S., Schmitt, R. R., Seastrom, M., Sirken, M. G., Spruill, N. L., ... Groves, R. (2005, December). *Statistical policy working paper 22: Report on statistical disclosure limitation methodology* (Research Report) (Retrieved September 29, 2023). U.S. Federal Committee on Statistical Methodology. <https://www.fcsm.gov/assets/files/docs/spwp22WithFrontNote.pdf>
- Hawes, M. B. (2022). *Reconstruction and Re-identification of the Demographic and Housing Characteristics File (DHC)* [Census Scientific Advisory Committee Meeting]. Retrieved September 29, 2023, from <https://www2.census.gov/about/partners/cac/sac/meetings/2022-09/presentation-reconstruction-and-re-identification-of-dhc-file.pdf>
- Hotz, V. J., Bollinger, C. R., Komarova, T., Manski, C. F., Moffitt, R. A., Nekipelov, D., Sojourner, A., & Spencer, B. D. (2022). Balancing data privacy and usability in the federal statistical

- system. *Proceedings of the National Academy of Sciences*, 119(31), e2104906119. <https://doi.org/10.1073/pnas.2104906119>
- Hundepool, A., Domingo-Ferrer, J., Franconi, L., Giessing, S., Nordholt, E. S., Spicer, K., & de Wolf, P.-P. (2012). *Statistical Disclosure Control*. Wiley. <https://doi.org/10.1002/9781118348239>
- Imbens, G. W., & Rubin, D. B. (2015). *Causal Inference for Statistics, Social, and Biomedical Sciences: An Introduction*. Cambridge University Press.
- Jarmin, R. S., Abowd, J. M., Ashmead, R., Cumings-Menon, R., Goldschlag, N., Hawes, M. B., Keller, S. A., Kifer, D., Leclerc, P., Reiter, J. P., Rodríguez, R. A., Schmutte, I., Velkoff, V. A., & Zhuravlev, P. (2023). An In-Depth Examination of Requirements for Disclosure Risk Assessment [In press]. *Proceedings of the National Academy of Sciences*. <https://doi.org/10.1073/pnas.2220558120>
- Kenny, C. T., Kuriwaki, S., McCartan, C., Rosenman, E. T. R., Simko, T., & Imai, K. (2021). The use of differential privacy for census data and its impact on redistricting: The case of the 2020 u.s. census. *Science Advances*, 7(41), eabk3283. <https://doi.org/10.1126/sciadv.abk3283>
- Kifer, D. (2015). On estimating the swapping rate for categorical data. *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 557–566. <https://doi.org/10.1145/2783258.2783369>
- Kifer, D., Abowd, J. M., Ashmead, R., Cumings-Menon, R., Leclerc, P., Machanavajjhala, A., Sexton, W., & Zhuravlev, P. (2022). *Bayesian and Frequentist Semantics for Common Variations of Differential Privacy: Applications to the 2020 Census* (tech. rep.). arxiv.org. <https://doi.org/10.48550/arXiv.2209.03310>
- Layne, M., Wagner, D., & Rothhaas, C. (2014). *Estimating record linkage false match rate for the person identification validation system* (tech. rep. No. 2014-02) (retrieved September 29, 2023). Census Bureau - Center for Administrative Records Research and Applications. <https://www.census.gov/content/dam/Census/library/working-papers/2014/adrm/carra-wp-2014-02.pdf>
- McKenna, L. (2018). *Disclosure Avoidance Techniques Used for the 1970 through 2010 Decennial Censuses of Population and Housing*. Retrieved September 29, 2023, from <https://www2.census.gov/ces/wp/2018/CES-WP-18-47.pdf>
- McKenna, L. (2019a). *Disclosure Avoidance Techniques Used for the 1960 Through 2010 Decennial Censuses of Population and Housing Public Use Microdata Samples*. Retrieved September 29, 2023, from <https://www2.census.gov/adrm/CED/Papers/CY19/2019-04-McKenna-Six%20Decennial%20Censuses.pdf>
- McKenna, L. (2019b). *U.S. Census Bureau Reidentification Studies*. Retrieved September 29, 2023, from <https://www2.census.gov/adrm/CED/Papers/CY19/2019-04-Reidentification%20studies-20210331FinRed.pdf>
- Muralidhar, K. (2022). *A Re-examination of the Census Bureau Reconstruction and Reidentification Attack* (tech. rep.). SSRN. <https://doi.org/10.2139/ssrn.4103758>
- Muralidhar, K., & Domingo-Ferrer, J. (2023). Database reconstruction is not so easy and is different from reidentification. *Journal of Official Statistics*, 39(3), 381–398. <https://doi.org/NationalAcademiesofSciences,Engineering,andMedicin10.2478/jos-2023-0017>
- National Academies of Sciences, Engineering, and Medicine. (2021). *Principles and Practices for a Federal Statistical Agency: Seventh Edition*. The National Academies Press. <https://doi.org/10.17226/25885>
- Ochoa, S., Rasmussen, J., Robson, C., & Salib, M. (2002, August). *Reidentification of individuals in chicago's homicide database: A technical and legal study* (tech. rep.) (Retrieved September 29, 2023). Massachusetts Institute of Technology. [https://www.researchgate.net/profile/Jamie-Rasmussen-2/publication/2838440\\_Reidentification\\_of\\_Individuals\\_in\\_Chicago's\\_Homicide\\_Database\\_A\\_Technical\\_and\\_Legal\\_Study/links/02e7e5285993363394000000/](https://www.researchgate.net/profile/Jamie-Rasmussen-2/publication/2838440_Reidentification_of_Individuals_in_Chicago's_Homicide_Database_A_Technical_and_Legal_Study/links/02e7e5285993363394000000/s_Homicide_Database_A_Technical_and_Legal_Study/links/02e7e5285993363394000000/)



- 2053        [Reidentification-of-Individuals-in-Chicagos-Homicide-Database-A-Technical-and-Legal-](#)  
 2054        [Study.pdf](#)
- 2055    Office of Management and Budget. (1997, October). *Revisions to the Standards for the Classification*  
 2056        *of Federal Data on Race and Ethnicity (Statistical Policy Directive No. 15)* [Retrieved  
 2057        September 29, 2023]. [https://obamawhitehouse.archives.gov/omb/fedreg\\_1997standards](https://obamawhitehouse.archives.gov/omb/fedreg_1997standards)
- 2058    Office of National Statistics, UK. (2023). Protecting personal data in Census 2021 results [Re-  
 2059        trieved November 29, 2023]. [https://www.ons.gov.uk/peoplepopulationandcommunity/](https://www.ons.gov.uk/peoplepopulationandcommunity/populationandmigration/populationestimates/methodologies/protectingpersonaldataincensus2021results)  
 2060        [populationandmigration/populationestimates/methodologies/protectingpersonaldataincensus2021results](https://www.ons.gov.uk/peoplepopulationandcommunity/populationandmigration/populationestimates/methodologies/protectingpersonaldataincensus2021results)
- 2061    Rastogi, S., & O'Hara, A. (2012, November). *2010 Census Match Study* (Report No. CPEX-247).  
 2062        U.S. Census Bureau. Retrieved September 29, 2023, from [https://www2.census.gov/](https://www2.census.gov/programs-surveys/decennial/2010/program-management/5-review/cpe/2010-cpe-247.pdf)  
 2063        [programs-surveys/decennial/2010/program-management/5-review/cpe/2010-cpe-](https://www2.census.gov/programs-surveys/decennial/2010/program-management/5-review/cpe/2010-cpe-247.pdf)  
 2064        [247.pdf](https://www2.census.gov/programs-surveys/decennial/2010/program-management/5-review/cpe/2010-cpe-247.pdf)
- 2065    Rocher, L., Hendrickx, J., & de Montjoye, Y. (2019). Estimating the success of re-identifications  
 2066        in incomplete datasets using generative models. *Nature Communications*, 10. [https://doi.](https://doi.org/10.1038/s41467-019-10933-3)  
 2067        [org/10.1038/s41467-019-10933-3](https://doi.org/10.1038/s41467-019-10933-3)
- 2068    Rossiter, K. (2011). *What are census blocks?* Retrieved September 29, 2023, from [https://www.](https://www.census.gov/newsroom/blogs/random-samplings/2011/07/what-are-census-blocks.html)  
 2069        [census.gov/newsroom/blogs/random-samplings/2011/07/what-are-census-blocks.html](https://www.census.gov/newsroom/blogs/random-samplings/2011/07/what-are-census-blocks.html)
- 2070    Ruggles, S., & Van Riper, D. (2022). The Role of Chance in the Census Bureau Database Re-  
 2071        construction Experiment. *Population Research and Policy Review*, 41(3), 781–788. [https:](https://doi.org/10.1007/s11113-021-09674-3)  
 2072        [//doi.org/10.1007/s11113-021-09674-3](https://doi.org/10.1007/s11113-021-09674-3)
- 2073    Statistics Canada. (2016, December). *Statistics Canada Policy on the Use of Administrative Data*  
 2074        *Obtained under the Statistics Act*. Retrieved September 29, 2023, from [https://www.](https://www.statcan.gc.ca/en/about/policy/admin_data)  
 2075        [statcan.gc.ca/en/about/policy/admin\\_data](https://www.statcan.gc.ca/en/about/policy/admin_data)
- 2076    Sweeney, L. (2011). *Patient identifiability in pharmaceutical marketing data* (tech. rep.) (Retrieved  
 2077        September 29, 2023). Harvard University, Cambridge, MA, WP-1015. [https://dataprivacylab.](https://dataprivacylab.org/projects/identifiability/pharma1.html)  
 2078        [org/projects/identifiability/pharma1.html](https://dataprivacylab.org/projects/identifiability/pharma1.html)
- 2079    U.S. Census Bureau. (2006). *Census of Population and Housing [United States], 1980: P.L. 94-171*  
 2080        *Population Counts* (tech. rep.) (ICPSR 7854). Inter-University Consortium for Political  
 2081        and Social Research. <https://doi.org/10.3886/ICPSR07854.v1>
- 2082    U.S. Census Bureau. (2012). *2010 Census Summary File 1 —Technical Documentation* (tech. rep.)  
 2083        (retrieved September 29, 2023). Department of Commerce, Economics and Statistics Ad-  
 2084        ministration. [https://www2.census.gov/programs-surveys/decennial/2010/technical-](https://www2.census.gov/programs-surveys/decennial/2010/technical-documentation/complete-tech-docs/summary-file/sf1.pdf)  
 2085        [documentation/complete-tech-docs/summary-file/sf1.pdf](https://www2.census.gov/programs-surveys/decennial/2010/technical-documentation/complete-tech-docs/summary-file/sf1.pdf)
- 2086    U.S. Census Bureau. (2023a). 2010 Summary Metrics Production Settings Demonstration Data  
 2087        Product Suite (including PPMF) Version 2023-04-03 [Retrieved December 7, 2023]. [https:](https://www2.census.gov/programs-surveys/decennial/2020/program-management/data-product-planning/2010-demonstration-data-products/04-Demonstration_Data_Products_Suite/2023-04-03/2023-04-03_Detailed_Summary_Metrics.xlsx)  
 2088        [//www2.census.gov/programs-surveys/decennial/2020/program-management/data-](https://www2.census.gov/programs-surveys/decennial/2020/program-management/data-product-planning/2010-demonstration-data-products/04-Demonstration_Data_Products_Suite/2023-04-03/2023-04-03_Detailed_Summary_Metrics.xlsx)  
 2089        [product-planning/2010-demonstration-data-products/04-Demonstration\\_Data\\_Products\\_](https://www2.census.gov/programs-surveys/decennial/2020/program-management/data-product-planning/2010-demonstration-data-products/04-Demonstration_Data_Products_Suite/2023-04-03/2023-04-03_Detailed_Summary_Metrics.xlsx)  
 2090        [Suite/2023-04-03/2023-04-03\\_Detailed\\_Summary\\_Metrics.xlsx](https://www2.census.gov/programs-surveys/decennial/2020/program-management/data-product-planning/2010-demonstration-data-products/04-Demonstration_Data_Products_Suite/2023-04-03/2023-04-03_Detailed_Summary_Metrics.xlsx)
- 2091    U.S. Census Bureau. (2023b). *American National Standards Institute (ANSI), Federal Information*  
 2092        *Processing Series (FIPS), and Other Standardized Geographic Codes*. Retrieved September  
 2093        29, 2023, from <https://www.census.gov/library/reference/code-lists/ansi.html>
- 2094    Villa Ross, C. A. (2023). *Uses of Decennial Census Programs Data in Federal Funds Distribution:*  
 2095        *Fiscal Year 2021* (tech. rep.) (retrieved September 25, 2023). U.S. Census Bureau. [https:](https://www2.census.gov/library/working-papers/2023/decennial/census-data-federal-funds-fy-2021.pdf)  
 2096        [//www2.census.gov/library/working-papers/2023/decennial/census-data-federal-funds-](https://www2.census.gov/library/working-papers/2023/decennial/census-data-federal-funds-fy-2021.pdf)  
 2097        [fy-2021.pdf](https://www2.census.gov/library/working-papers/2023/decennial/census-data-federal-funds-fy-2021.pdf)
- 2098    Wagner, D., & Layne, M. (2014). *The Person Identification Validation System (PVS): Applying*  
 2099        *the Center for Administrative Records Research and Applications' Record Linkage Software*  
 2100        (tech. rep. No. 2014-01) (retrieved September 29, 2023). Census Bureau - Center for Ad-  
 2101        ministrative Records Research and Applications. [https://www.census.gov/content/dam/](https://www.census.gov/content/dam/Census/library/working-papers/2014/adrm/carra-wp-2014-01.pdf)  
 2102        [Census/library/working-papers/2014/adrm/carra-wp-2014-01.pdf](https://www.census.gov/content/dam/Census/library/working-papers/2014/adrm/carra-wp-2014-01.pdf)

- 2103 Wasserman, L. (2010). *All of Nonparametric Statistics*. Springer.
- 2104 Willenborg, L., & de Waal, T. (2000). *Elements of statistical disclosure control*. Springer. [https:](https://doi.org/10.1007/978-1-4613-0121-9)
- 2105 [//doi.org/10.1007/978-1-4613-0121-9](https://doi.org/10.1007/978-1-4613-0121-9)
- 2106 Wright, T., & Irinata, K. (2021, August). *Empirical Study of Two Aspects of the TopDown Algo-*
- 2107 *rithm Output for Redistricting: Reliability & Variability* (tech. rep. No. SSS2021-02) (re-
- 2108 trieved September 29, 2023). U.S. Census Bureau. [https://www.census.gov/content/dam/](https://www.census.gov/content/dam/Census/library/working-papers/2021/adrm/SSS2021-02.pdf)
- 2109 [Census/library/working-papers/2021/adrm/SSS2021-02.pdf](https://www.census.gov/content/dam/Census/library/working-papers/2021/adrm/SSS2021-02.pdf)
- 2110 Ye, J., Borovykh, A., Hayou, S., & Shokri, R. (2023). Leave-one-out distinguishability in machine
- 2111 learning. <https://doi.org/10.48550/arXiv.2309.17310>