Promo Finder: User Manual

How to run it, and where every API key goes

Divyansh Gupta Roll No: 230382

November 5, 2026

App: `promo-finder-divyansh.streamlit.app` Code: `github.com/usegitdivyansh/promo-finder`

1 What it does

Promo Finder reads the timestamped screenplays of a microdrama and returns a ranked list of promo clips (20 to 60 s each). Every promo lists its segments in order (episode, start and end time), the hook, the cliffhanger and one line on why it works. It does not edit video: an editor reviews the list and cuts the clips.

There are two ways to use it:

	Web app	**Command line**
Best for	Trying it, demos, small shows	Full shows, repeated runs, the interview rerun
Setup	None, just open the link	Python 3.11 and a clone of the repo
Where the key goes	Sidebar field, for that session only	A `.env` file in the project folder
Caching	Per session only	Saved to disk, reruns are cheap

2 Getting an API key

The pipeline calls a language model, so you need a key from a model provider. **OpenRouter is the tested and recommended option**: one key gives access to many models, including the default one (DeepSeek V4.1 Flash).

2.1 OpenRouter (recommended)

1. Sign in at `openrouter.ai` and add a few dollars of credit on the **Credits** page. A full 50 episode show costs about $0.54.
2. Open **Settings, Privacy** and switch **off** every option that lets endpoints train on, log or publish your prompts. Do this before running confidential scripts.
3. Open `openrouter.ai/settings/keys`, click **New key**, give it a name and **set a credit limit** (for example $2). The limit caps the damage if the key ever leaks.
4. Copy the key straight away. It starts with `sk-or-v1-` and is shown only once.

2.2 Google Gemini (optional)

Create a key at `aistudio.google.com/apikey`; it starts with `AIza`. The free tier is fine for testing on made-up shows, but its daily request limit can be very low (one model allowed only 20 requests a day, and a show needs about 170 calls), and free tier prompts may be used to improve Google's products. **Don't use the free tier for confidential scripts.**

Key safety. Never paste a key into a chat, an email, a screenshot or a file you commit to git. If a key is ever exposed, delete it on the provider's site and create a new one. The app never saves your key, and `.env` is excluded from git.

3 Using the web app

1. Open `promo-finder-divyansh.streamlit.app`. If it has been idle it may take a moment to wake up.
2. **No key yet?** Click **Demo mode: see it on a made-up show**. It loads saved results instantly, costs nothing and shows every feature.
3. **Fill in the sidebar:**

Field	What to enter
Provider	**OpenRouter** (the tested provider)
Model name	Default `deepseek/deepseek-v4.1-flash`. To use a stronger model, paste its exact ID from `openrouter.ai/models`.
API key	Your key. It stays in this browser session, goes straight to the provider and is cleared after the run.
Spend cap per run (USD)	The run stops before any call that would go over it. Default $1. Use $0.10 for a 5 episode test.
Options	Extra run settings such as the number of promos.

4. **Upload the screenplays:** one file per episode, or a single zip. Accepted formats are TXT, MD, PDF, DOCX, JSON, FOUNTAIN, SRT and ZIP, up to 30 MB per file. Each episode needs a timestamp on every line (for example `[01:12]`).

5. Check the **cost estimate** shown after upload, then click **Run** and keep the tab open. A 5 episode show takes about 10 minutes and about $0.09.
6. **Read the results:**
   - **Summary strip:** episodes processed, promos found, rules passed and the cost of this run.
   - **Promo cards:** rank, template, duration bar, the hook in bold, the cliffhanger in italics and colour coded score chips (green 8 and up, gold 6 to 8, red below 6).
   - **Timeline:** one bar per episode with the promo's cut points highlighted, plus the exact times.
   - **Phone preview:** the promo's lines in order, as a viewer would see them.
   - **Downloads:** `promos.json`, `promos.csv` (opens in Excel), `report.html` with the script lines for every cut, and a zip of all raw outputs.

Large shows. For a full 50 episode show the command line is more reliable: its cache is saved to disk, so an interrupted run can resume without paying again.

4 Using the command line

4.1 One time setup

```
git clone https://github.com/usegitdivyansh/promo-finder.git
cd promo-finder
pip install -r requirements.txt
```

Then create the key file. Copy `.env.example` to `.env` (Windows: `copy .env.example .env`; Mac or Linux: `cp .env.example .env`) and open it in a text editor:

```
GEMINI_API_KEY=
OPENROUTER_API_KEY=sk-or-v1-your-key-here
```

One key per line, no quotes, no spaces. Only fill in the providers you use. Save the file and check it is really named `.env`, not `.env.txt` (Windows: `dir -Force`).

4.2 Choosing the model

The model lives in one place: the `strong` slot on line 6 of `config.yaml`. Every step, the fallback and confidential mode follow it.

```
strong:  "openrouter/deepseek/deepseek-v4.1-flash"
```

To swap models, change only this line. On the command line the name includes the provider prefix (`openrouter/...` or `gemini/...`); in the web app you pick the provider separately and type the name without it. A model with no known price is charged a safe default against the spend cap, never treated as free.

4.3 Running

Command	What it does
`python run.py --input data/show1 --out raw_outputs/show1`	Full pipeline on a folder of screenplays (steps 1 to 9 plus the baseline).
`python run.py --input tests/fixtures/sample_show --mock`	Offline test with saved responses. No key, no cost.
`python run.py ...  --from step5`	Resume from a later step, reusing everything before it.
`python -m src.check_rules --run raw_outputs/show1`	Recheck every hard rule on a finished run.
`streamlit run app.py`	Start the web app on your own computer.

Put confidential screenplays in `data/` (it is git ignored). Results land in `raw_outputs/<name>/`: one folder per step (`01_parsed` to `09_final`), `usage.jsonl` with tokens and cost per call, and the final `promos.json`, `promos.csv` and `report.html` in `09_final/`.

5 Cost guide

Show size (DeepSeek V4.1 Flash)	Approx. cost	Suggested spend cap
5 episodes (test)	$0.09	$0.10 to $0.20
50 episodes (full show)	$0.54	$1.00
100 shows of 50 episodes	$54	per show cap

OpenRouter has billed about 1.57 times the listed token price, and the app's estimate already includes that margin. Stronger models cost more per token, so test them on a small show first.

6 Troubleshooting

Problem	Fix
401 "User not found" or "invalid key"	The key is wrong, deleted or copied incompletely. Create a new key and paste the whole thing. The app stops on the first call when this happens.
429 or "rate limit"	The provider's limit was hit. The pipeline backs off and retries; on Gemini's free tier the daily cap may be used up, so switch to OpenRouter.
Run stops with "spend cap"	Working as intended. Raise the cap, or resume from the last step on the command line.
Run button greyed out	Upload at least one screenplay and enter an API key.
Key not found on the command line	The file is named `.env.txt`, or the key line has spaces or quotes.
Fewer promos than expected	The tool drops anything scoring under 60 instead of padding the list. Short shows naturally give fewer promos.
Episode skipped	It failed to parse (for example, missing timestamps). The run continues and the log names the episode.

7 Privacy and confidentiality

- The public repo and app contain no Kuku content: only code, prompts, tests and two made-up shows.
- Keep real scripts in `data/`, and keep `data/`, `cache/`, `raw_outputs/` and `.env` out of git (already in `.gitignore`).
- Use a paid model tier with training and logging switched off for confidential scripts.
- Share raw outputs by private link, never in a public repo.

Divyansh Gupta, Roll No 230382. Promo Finder is an independent assignment project, not a Kuku product.