

version: '3.9'

services:

gluetun:

```
image: qmcgaw/gluetun
container_name: gluetun
cap_add:
  - NET_ADMIN
devices:
  - /dev/net/tun:/dev/net/tun
ports:
  - 6881:6881
  - 6881:6881/udp
  - 8085:8085 # qbittorrent
  - 8080:8080 # amarr
  - 4711:4711 # amule
  - 4712:4712 # amule remote gui, webserver, cmd ...
  - 4662:4662 # amule ed2k tcp
  - 4665:4665/udp # amule ed2k global search udp (tcp port +3)
  - 4672:4672/udp # amule ed2k udp
volumes:
  - {pathto}/gluetun:/gluetun
environment:
  - VPN_SERVICE_PROVIDER=cyberghost
  - VPN_TYPE=openvpn
  - OPENVPN_USER={myuser}
  - OPENVPN_PASSWORD={mypassword}
  - OPENVPN_KEY={mykey}
  - OPENVPN_CERT={mycert}
  - TZ=America/Vancouver
  - UPDATER_PERIOD=24h
restart: always
```

qbittorrent:

```
image: lscr.io/linuxserver/qbittorrent
container_name: qbittorrent
network_mode: "service:gluetun"
environment:
  - PUID=501
  - PGID=20
  - TZ=America/Vancouver
  - WEBUI_PORT=8085
volumes:
  - {pathto}/qbittorrent:/config
  - {pathto}/download:/qbittorrent/download
depends_on:
  - gluetun
restart: always
```

```
sonarr:
  image: lscr.io/linuxserver/sonarr:latest
  container_name: sonarr
  ports:
    - 8989:8989
  environment:
    - PUID=501
    - PGID=20
    - TZ=America/Vancouver
  volumes:
    - {pathto}/sonarr/data:/config
    - {pathto}/TV SHOWS:/tv
    - {pathto}/download:/qbittorrent/download
  restart: unless-stopped
```

```
radarr:
  image: lscr.io/linuxserver/radarr:latest
  container_name: radarr
  ports:
    - 7878:7878
  environment:
    - PUID=501
    - PGID=20
    - TZ=America/Vancouver
  volumes:
    - {pathto}/radarr/data:/config
    - {pathto}/MOVIES:/movies
    - {pathto}/download:/qbittorrent/download
  restart: unless-stopped
```

```
prowlarr:
  image: lscr.io/linuxserver/prowlarr:latest
  container_name: prowlarr
  ports:
    - 9696:9696
  environment:
    - PUID=501
    - PGID=20
    - TZ=America/Vancouver
  volumes:
    - {pathto}/prowlarr/data:/config
  restart: unless-stopped
```

```
overseerr:
  image: lscr.io/linuxserver/overseerr:latest
  container_name: overseerr
  ports:
    - 5055:5055
  environment:
    - PUID=501
```

- PGID=20
- TZ=America/Vancouver

volumes:

- {pathto}/overseerr/config:/config

restart: unless-stopped

amule:

image: minnyres/amule-dlp:latest

container_name: amule

network_mode: "service:gluetun"

environment:

- PUID=501
- PGID=20
- TZ=America/Vancouver
- WEBUI=bootstrap

volumes:

- {pathto}/amule:/home/amule/.aMule
- {pathto}/amule_download:/incoming
- {pathto}/amule_download/temp:/temp

restart: unless-stopped

depends_on:

- gluetun

amarr:

image: vexdev/amarr:latest

container_name: amarr

network_mode: "service:gluetun"

environment:

- AMULE_HOST=ad1b64b40fe2 # tried setting this to amule but didn't work
- AMULE_PORT=4711
- AMULE_PASSWORD=amuleweb-passwd
- AMULE_FINISHED_PATH={pathto}/amule_download:/incoming

volumes:

- {pathto}/amarr/config:/config