

API Reference

Miro API

API Version: 1.0

INDEX

1. AUDIT	5
1.1 GET /audit/logs	5
2. BOARD-USER-CONNECTIONS	6
2.1 GET /board-user-connections/{id}	6
2.2 DELETE /board-user-connections/{id}	7
2.3 PATCH /board-user-connections/{id}	7
3. BOARDS	9
3.1 GET /boards	9
3.2 GET /boards/{id}	10
3.3 PATCH /boards/{id}	10
3.4 GET /boards/{id}/user-connections	12
3.5 POST /boards/{id}/share	13
3.6 GET /boards/{id}/widgets/{widgetId}	14
3.7 DELETE /boards/{id}/widgets/{widgetId}	15
3.8 PATCH /boards/{id}/widgets/{widgetId}	15
3.9 POST /boards/{id}/widgets	16
3.10 GET /boards/{id}/widgets/	17
4. OAUTH	19
4.1 POST /oauth/token	19
4.2 POST /oauth/revoke	19
5. OAUTH-TOKEN	21
5.1 GET /oauth-token	21
6. TEAM-USER-CONNECTIONS	22
6.1 GET /team-user-connections/{id}	22
6.2 DELETE /team-user-connections/{id}	22
6.3 PATCH /team-user-connections/{id}	23
7. TEAMS	24
7.1 GET /teams/{id}/boards	24
7.2 GET /teams/{id}	25
7.3 PATCH /teams/{id}	26
7.4 GET /teams/{id}/user-connections	27
7.5 GET /teams/{id}/user-connections/me	28
7.6 POST /teams/{id}/invite	28
8. USERS	30
8.1 GET /users/{id}	30
8.2 GET /users/me	30
8.3 PATCH /users/me	31

9. {TYPE}	33
9.1 GET /{type}/{id}/picture	33
9.2 POST /{type}/{id}/picture	33
9.3 DELETE /{type}/{id}/picture	34

Security and Authentication

SECURITY SCHEMES

KEY	TYPE	DESCRIPTION
sec0	oauth2	

API

1. AUDIT

1.1 GET /audit/logs

Get logs

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
*createdAfter	date	yyyy-MM-ddThh:mm:ss.SSSZ
*createdBefore	date	yyyy-MM-ddThh:mm:ss.SSSZ
limit	int32	Max value is 500
offset	int32	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{  
}
```

2. BOARD-USER-CONNECTIONS

2.1 GET /board-user-connections/{id}

Get Board User Connection

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type      string
  role      string
  user {
    type string
    name string
    id   string
  }
  modifiedAt string
  modifiedBy {
    type string
    name string
    id   string
  }
  createdAt  string
  createdBy {
    type string
    name string
    id   string
  }
  id        string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

2.2 DELETE /board-user-connections/{id}

Delete Board User Connection

REQUEST

No request parameters

RESPONSE

STATUS CODE - 204: 204

RESPONSE MODEL - application/json

```
{
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

2.3 PATCH /board-user-connections/{id}

Update Board User Connection

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```
{
  role string Value can be "viewer", "commenter", "editor", "owner"
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  role string
  user {
    type string
    name string
    id string
  }
}
```

```
}
modifiedAt string
modifiedBy {
  type string
  name string
  id string
}
createdAt string
createdBy {
  type string
  name string
  id string
}
id string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

3. BOARDS

3.1 GET /boards

Create Board

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```
{
  name          string  DEFAULT:Untitled
                  Name for the board that you are creating. The board name can have up to 60 characters.</br>Default:
                  `Untitled`
  description   string
  sharingPolicy string  DEFAULT:{ "access" : "private", "teamAccess" : "private" }
                  **sharingPolicy.access** can be `private`, `view`, `comment` </br> **sharingPolicy.teamAccess** can be
                  `private`, `view`, `comment`, `edit`
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type          string
  viewLink      string
  id            string
  name          string
  description   string
  picture       undefined
  currentUserConnection {
    type string
    role string
    user {
      type string
      name string
      id  string
    }
    id string
  }
  owner {
    type string
    name string
    id  string
  }
  sharingPolicy {
    access      string
    teamAccess string
  }
}
```

```
    }
    modifiedAt string
    modifiedBy {
      type string
      name string
      id string
    }
    createdAt string
    createdBy {
      type string
      name string
      id string
    }
  }
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

3.2 GET /boards/{id}

Get Board

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

3.3 PATCH /boards/{id}

Update Board

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```
{
  name          string  DEFAULT:Untitled
  description    string
  sharingPolicy string  DEFAULT:{ "access" : "private", "teamAccess" : "private" }
                                     **sharingPolicy.access** can be `private`, `view`, `comment` </br>
                                     **sharingPolicy.teamAccess** can be `private`, `view`, `comment`, `edit`
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type          string
  viewLink      string
  id            string
  name          string
  description    string
  picture       undefined
  currentUserConnection {
    type string
    role string
    user {
      type string
      name string
      id string
    }
    id string
  }
  owner {
    type string
    name string
    id string
  }
  sharingPolicy {
    access      string
    teamAccess string
  }
  modifiedAt    string
  modifiedBy {
    type string
    name string
    id string
  }
  createdAt     string
}
```

```

    createdBy {
      type string
      name string
      id string
    }
  }
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

3.4 GET /boards/{id}/user-connections

Get Board members

Retrieves a list of team members who have access to the selected board.

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
limit	int32	
offset	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```

{
  type string
  limit integer DEFAULT:0
  offset integer DEFAULT:0
  size integer DEFAULT:0
  data [{
    Array of object:
    type string
    role string
    user {
      type string
      name string
      id string
    }
    modifiedAt string
    modifiedBy {
      type string

```

```

        name string
        id string
    }
    createdAt string
    createdBy {
        type string
        name string
        id string
    }
    id string
}]
nextLink undefined
prevLink undefined
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

3.5 POST /boards/{id}/share

Share Board

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

REQUEST BODY - application/json

```

{
  emails*           [string]
  role*             string      Value can be `viewer`, `commenter`, `editor`
  message           string      The message which will be sent to users. This parameter is optional.
  teamInvitationStrategy string  DEFAULT:off
                                     Value can be `invite_when_required`, `off`. This parameter is optional. Value `off` will be
                                     used by default.
}

```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```

{
  type      string
  limit     integer  DEFAULT:0
  offset    integer  DEFAULT:0
  size      integer  DEFAULT:0
  data [ {
    Array of object:
      type      string
      role      string

```

```

    user {
      type string
      name string
      id string
    }
    modifiedAt string
    modifiedBy {
      type string
      name string
      id string
    }
    createdAt string
    createdBy {
      type string
      name string
      id string
    }
    id string
  }]
  nextLink undefined
  prevLink undefined
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

3.6 GET /boards/{id}/widgets/{widgetId}

Get Widget

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	board id
*widgetId	string	widget id

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```

{
  type string
  scale integer DEFAULT:0
  y integer DEFAULT:0
  x integer DEFAULT:0
  id integer DEFAULT:0
  date string
  createdBy {
    type string

```

```

    name string
    id string
  }
  modifiedAt string
  modifiedBy {
    type string
    name string
    id string
  }
  createdAt string
  description string
  style {
    backgroundColor string
  }
  title string
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

3.7 DELETE /boards/{id}/widgets/{widgetId}

Delete Widgets

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	board id
*widgetId	string	widget id

RESPONSE

STATUS CODE - 204: 204

RESPONSE MODEL - application/json

```

{
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

3.8 PATCH /boards/{id}/widgets/{widgetId}

Update Widget

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	board id
*widgetId	string	widget id

REQUEST BODY - application/json

```
{
  RAW_BODY string Partial widget representation
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  scale integer DEFAULT:0
  y integer DEFAULT:0
  x integer DEFAULT:0
  id integer DEFAULT:0
  createdBy {
    type string
    name string
    id string
  }
  modifiedAt string
  modifiedBy {
    type string
    name string
    id string
  }
  createdAt string
  date string
  description string
  style {
    backgroundColor string
  }
  title string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

3.9 POST /boards/{id}/widgets

Create Widget

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	board id

REQUEST BODY - application/json

```
{
  RAW_BODY string DEFAULT:{ "type": "card", "title": "Simple card" }
  widget representation, paste json from the example to try
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  scale integer DEFAULT:0
  y integer DEFAULT:0
  x integer DEFAULT:0
  id integer DEFAULT:0
  date string
  title string
  style {
    backgroundColor string
  }
  createdAt string
  createdBy {
    type string
    name string
    id string
  }
  modifiedAt string
  modifiedBy {
    type string
    name string
    id string
  }
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

3.10 GET /boards/{id}/widgets/

List All Widgets

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
widgetType	string	Filter widgets by type

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type          string
  data [{
    Array of object:
      type          string
      scale         number      DEFAULT:0
      y             number      DEFAULT:0
      x             integer     DEFAULT:0
      text          string
      style {
        backgroundColor string
        fontAutoSize  boolean  DEFAULT:true
        fontFamily    string
        fontSize      integer  DEFAULT:0
        lineHeight    number  DEFAULT:0
        textAlign     string
        textAlignVertical string
      }
      id            integer     DEFAULT:0
      createdBy {
        type string
        name string
        id  string
      }
      modifiedAt    string
      modifiedBy {
        type string
        name string
        id  string
      }
      createdAt     string
    }]
  size            integer     DEFAULT:0
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

4. OAUTH

4.1 POST /oauth/token

Step 3: Exchange authorization code with access token

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
*grant_type	string	Always set the value for this parameter to `authorization_code`.
client_id	string	The Client ID of the app that is requesting for user authorization. For information on how to obtain the client ID, see [Create authorization request link](ref:create-authorization-request-link)
*client_secret	string	App client secret. **The client secret must be kept confidential.**
*code	string	Paste the authorization code that was provided as the code parameter value in the redirect URI.
*redirect_uri	string	Paste the redirect URI. The URI must match the original redirect URI that was used when requesting the authorization (including slash at the end).

HEADER PARAMETERS

NAME	TYPE	DESCRIPTION
Accept	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  user_id      string
  expires_in   integer DEFAULT:0
  team_id      string
  access_token string
  scope        string
  refresh_token string
  token_type   string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

4.2 POST /oauth/revoke

Revoke token

Revoking an access token means that the access token will no longer work. When an access token is revoked, the refresh token is also revoked and no longer valid. This does not uninstall the application for the user.

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
*access_token	string	Paste the access token that you want to revoke.

RESPONSE

STATUS CODE - 204: 204

RESPONSE MODEL - application/json

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{  
}
```

5. OAUTH-TOKEN

5.1 GET /oauth-token

Get access token context

Get information about an access token, such as the token type, scopes, team, user, token creation date and time, and the user who created the token.

REQUEST

No request parameters

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  team {
    type string
    name string
    id string
  }
  createdBy {
    type string
    name string
    id string
  }
  scopes [string]
  organization {
    type string
    name string
    id string
  }
  user {
    type string
    name string
    id string
  }
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

6. TEAM-USER-CONNECTIONS

6.1 GET /team-user-connections/{id}

Get Team User Connection

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  user {
    type string
    name string
    id string
  }
  role string
  id string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

6.2 DELETE /team-user-connections/{id}

Delete Team User Connection

REQUEST

No request parameters

RESPONSE

STATUS CODE - 204: 204

RESPONSE MODEL - application/json

```
{
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

6.3 PATCH /team-user-connections/{id}

Update Team User Connection

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```
{
  role string Values can be `non_team`,`member` or `admin`
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  user {
    type string
    name string
    id string
  }
  role string
  id string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

7. TEAMS

7.1 GET /teams/{id}/boards

Get Current User Boards

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	
limit	int32	
offset	int32	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type      string
  limit     integer   DEFAULT:0
  offset    integer   DEFAULT:0
  size      integer   DEFAULT:0
  nextLink  undefined
  prevLink  undefined
  data [ {
    Array of object:
      type      string
      viewLink   string
      id         string
      name       string
      description string
      picture    undefined
      currentUserConnection {
        type  string
        role  string
        user {
          type string
          name string
          id  string
        }
      }
      id  string
    }
  ]
  owner {
    type string
  }
}
```



```

        name string
        id string
    }
    sharingPolicy {
        access string
        teamAccess string
    }
    modifiedAt string
    modifiedBy {
        type string
        name string
        id string
    }
    createdAt string
    createdBy {
        type string
        name string
        id string
    }
}
}]
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

7.2 GET /teams/{id}

Get Team

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```

{
  type string
  picture undefined
  name string
  modifiedBy {
    type string
  }
}

```

```

    name string
    id string
  }
  modifiedAt string
  createdAt string
  createdBy {
    type string
    name string
    id string
  }
  id string
}

```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```

{
}

```

7.3 PATCH /teams/{id}

Update Team

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```

{
  name string
}

```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```

{
  type string
  picture undefined
  name string
  modifiedBy {
    type string
    name string
    id string
  }
  modifiedAt string
}

```

```
    createdAt string
    createdBy {
      type string
      name string
      id string
    }
    id string
  }
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

7.4 GET /teams/{id}/user-connections

List all Team Members

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	
limit	int32	
offset	int32	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  limit integer DEFAULT:0
  offset integer DEFAULT:0
  size integer DEFAULT:0
  nextLink undefined
  prevLink undefined
  data [{
    Array of object:
    type string
    user {
      type string
      name string
      id string
    }
    role string
  }
}
```

```
    id    string
  }}
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

7.5 GET /teams/{id}/user-connections/me

Get Team Current User Connection

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	Team ID

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type string
  user {
    type string
    name string
    id string
  }
  role string
  id string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

7.6 POST /teams/{id}/invite

Invite To Team

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

REQUEST BODY - application/json

```
{  
  emails [string]  
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
[{  
  Array of object:  
  type string  
  user {  
    type string  
    name string  
    id string  
  }  
  role string  
  id string  
}]
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{  
}
```

8. USERS

8.1 GET /users/{id}

Get User

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*id	string	

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type      string
  role      string
  email     string
  industry  string
  createdAt string
  company   string
  picture {
    type     string
    imageUrl string
    id       string
  }
  name      string
  state     string
  id        string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

8.2 GET /users/me

Get Current User

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type      string
  role      string
  email     string
  industry  string
  createdAt string
  company   string
  picture {
    type     string
    imageUrl string
    id       string
  }
  name      string
  state     string
  id        string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

8.3 PATCH /users/me

Update Current User

REQUEST

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```
{
  name string
}
```

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
```

```
type      string
role      string
email     string
industry  string
createdAt string
company   string
picture {
  type     string
  imageUrl string
  id       string
}
name      string
state     string
id        string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

9. {TYPE}

9.1 GET /{type}/{id}/picture

Get Picture

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*type	string	Type of picture's parental object (must be one of ``boards``, ``users``, ``teams``)
id	string	Identifier of picture's parental object ([User Object](#user-object), [Board Object](#board-object) or [Team Object](#account-object))

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
redirect	string	
size	int32	Must be one of ``26``, ``44``, ``50``, ``140``, ``180``, ``210``, ``420``.

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type      string
  imageUrl  string
  id        string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

9.2 POST /{type}/{id}/picture

Create or Update Picture

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*type	string	Type of picture's parental object (must be one of ``boards``, ``users``, ``teams``)
id	string	Identifier of picture's parental object ([User Object](#user-object), [Board Object](#board-object) or [Team Object](#account-object))

NAME	TYPE	DESCRIPTION
*id	string	Identifier of picture's parental object ([User Object](ref:user-object), [Board Object](ref:board-object) or [Team Object](ref:team-object))

QUERY PARAMETERS

NAME	TYPE	DESCRIPTION
fields	string	

REQUEST BODY - application/json

```
{
  image* string
}
```

HEADER PARAMETERS

NAME	TYPE	DESCRIPTION
Content-Type	string	Must be ``multipart/form-data``

RESPONSE

STATUS CODE - 200: 200

RESPONSE MODEL - application/json

```
{
  type      string
  imageUrl  string
  id        string
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{
}
```

9.3 DELETE /{type}/{id}/picture

Delete Picture

REQUEST

PATH PARAMETERS

NAME	TYPE	DESCRIPTION
*type	string	Type of picture's parental object (must be one of ``boards``, ``users``, ``teams``)
id	string	Identifier of picture's parental object ([User Object](ref:user-object), [Board Object](ref:board-object) or [Team Object](ref:team-object))

RESPONSE

STATUS CODE - 204: 204

RESPONSE MODEL - application/json

```
{  
}
```

STATUS CODE - 400: 400

RESPONSE MODEL - application/json

```
{  
}
```
