Network challenges

09:14 video · English narration · Guide-linked examples


Learn with the book

1. Distinguish five network measures

2. Calculate the effect of delay

3. Choose a response to the actual problem

Keep the 96-page Blue Impulse study guide open. Its printed page numbers match the PDF viewer. The screenshots in this tutorial are exact crops from that book.



Guide pages: 56, 59, 61, 62, 63, 74, 88.

How to use this PDF

Follow the timestamp at the top of each lesson page to find the matching video section. Read the book excerpt, work through the teaching text, and stop at each question before reading the answer. The complete narration is included here, with separate editable scripts and subtitle files in the package.

Practice file: BlueImpulse_Demonstrations.py
Requires Python 3.9+ and no extra packages. The source guide, scripts, subtitle sidecars, and editable video project are included in the tutorial package.

Why can fast Wi-Fi still feel slow?

Video 00:00–00:39 / Study guide page 62

Four problems to distinguish

Metric	What it tells you
Bandwidth / capacity	How much data a link can carry per second.
Throughput	The successful transfer rate actually achieved.
Latency	How long a transfer or response takes.
Jitter / loss	Variation in delay / missing packets.

Exact excerpt from the Blue Impulse study guide

Have you ever wondered why a connection advertised as fast can still make a video call freeze or a controller respond late?

The advertised rate describes only part of the journey. Delay, variation, loss, and shared demand also matter.

Open your Blue Impulse study guide at page sixty-two, Capacity is not responsiveness.

We will use that page to diagnose problems instead of treating every network problem as a need for more bandwidth.

Then we will calculate the effect of delay using the book's example on page seventy-four.

Today's route

Video 00:39–01:14 / Study guide page 62

Four problems to distinguish

Metric	What it tells you
Bandwidth / capacity	How much data a link can carry per second.
Throughput	The successful transfer rate actually achieved.
Latency	How long a transfer or response takes.
Jitter / loss	Variation in delay / missing packets.

Exact excerpt from the Blue Impulse study guide

Today you will distinguish bandwidth, throughput, latency, jitter, and packet loss.

You will use a numerical example to connect delay with a physical consequence.


You will choose responses such as compression, fewer round trips, buffering, or local control for specific problems.

Welcome to the tutorial on network challenges by Blue Impulse.

Keep a calculator or paper ready. Every book example has a page citation, and the tutorial PDF includes the practice answers.

Name the problem before fixing it

Video 01:14–01:56 / Study guide page 62



Four problems to distinguish

Metric	What it tells you
Bandwidth / capacity	How much data a link can carry per second.
Throughput	The successful transfer rate actually achieved.
Latency	How long a transfer or response takes.
Jitter / loss	Variation in delay / missing packets.

Exact excerpt from the Blue Impulse study guide

Read the table at the top of page sixty-two. Bandwidth describes how much data a link can carry per second.

Throughput is the successful transfer rate actually achieved. It can be lower than the link's capacity.

Latency is how long a transfer or response takes. Jitter is variation in that delay.

Packet loss means some packets do not arrive as expected.

These measures answer different questions. A connection can carry a lot of data and still take a long time to respond.

When describing an experiment, specify what you measured: one-way delay, round-trip delay, or complete task response time.

Use the road analogy

Video 01:56–02:42 / Study guide page 62

Four problems to distinguish

Metric	What it tells you
Bandwidth / capacity	How much data a link can carry per second.
Throughput	The successful transfer rate actually achieved.
Latency	How long a transfer or response takes.
Jitter / loss	Variation in delay / missing packets.

Exact excerpt from the Blue Impulse study guide

Use the guide's road analogy. A wider road can carry more cars at once, like greater bandwidth.

How many cars actually arrive each second is closer to throughput.

How long one journey takes is closer to latency. Uneven arrival times illustrate jitter, while missing deliveries illustrate loss.

Widening a road does not shorten the distance to the destination or remove every queue.

Likewise, increasing link capacity does not erase propagation time, server processing, or unnecessary back-and-forth exchanges.

The analogy helps separate the ideas, but measure the actual network before deciding which factor dominates.

Shared demand changes the result

Video 02:42–03:27 / Study guide page 56

Collision detection and avoidance

CSMA/CD	CSMA/CA
Historically used on shared, half-duplex Ethernet.	Used by Wi-Fi to manage shared radio access.
Listen, transmit, detect collision, back off and retry.	Listen, wait/back off, transmit and use acknowledgements.
Modern switched full-duplex Ethernet has no collisions on the link.	RTS/CTS is an optional mechanism, not a compulsory step every time.

Exact excerpt from the Blue Impulse study guide

Now connect page sixty-two with the media and contention discussion on page fifty-six.

Wireless devices may share a medium, compete for transmission time, and experience interference.

Heavy demand can create queues. Retransmissions after loss can use more capacity and add delay.


Modern switched full-duplex Ethernet should not be described as suffering the old shared-hub collision model.

The useful diagnosis depends on the network technology, the traffic, and the end-to-end path.

Try testing near the access point, with fewer competing transfers, and at different times before blaming one advertised number.

Reliability has a timing cost

Video 03:27–04:20 / Study guide page 59



The four-layer TCP/IP model

Layer	Responsibility	Examples
Application	Application messages and services.	HTTP, DNS, SMTP
Transport	Communication between application endpoints.	TCP, UDP
Internet	IP addressing and routing between networks.	IPv4, IPv6, ICMP
Link	Local network delivery and access to the medium.	Ethernet, Wi-Fi

Exact excerpt from the Blue Impulse study guide

Page fifty-nine explains TCP and IP. IP routes packets, while TCP can provide an ordered, reliable byte stream.

Reliability can require acknowledgements and retransmission, so recovery may add delay.

A transport choice does not by itself guarantee an application deadline or protect every message from an attacker.

Some applications prefer timely delivery and handle missing data themselves. Others need complete, correctly ordered transfer.

Read the application's requirements before selecting a protocol or interpreting a performance measurement.

Pages sixty-three through sixty-five discuss security separately. Confidentiality, integrity, and availability are distinct from simply having a fast link.

What happens during the delay?

Video 04:20–05:24 / Study guide page 74

Illustrative delay distance at 30 m/s

Delay before response	Distance travelled
500 ms = 0.500 s	30 × 0.500 = 15 metres
50 ms = 0.050 s	30 × 0.050 = 1.5 metres
5 ms = 0.005 s	30 × 0.005 = 0.15 metres

Exact excerpt from the Blue Impulse study guide

Turn to page seventy-four. The guide uses a constant speed of thirty metres per second for an illustrative calculation.

Distance travelled during delay equals speed multiplied by delay. First convert milliseconds into seconds.

Five hundred milliseconds is zero point five seconds. Thirty times zero point five gives fifteen metres.

Fifty milliseconds is zero point zero five seconds. That gives one point five metres.

Five milliseconds is zero point zero zero five seconds. That gives zero point one five metres.


Watch the three distances grow from the same starting point. We changed delay while keeping speed fixed.

These are distances before a response begins, not complete stopping distances and not safety guarantees.

Sensing, processing, actuation, and physical braking can contribute additional delay or distance in a real system.

Real-time means a deadline

Video 05:24–06:13 / Study guide page 74



Exact excerpt from the Blue Impulse study guide

Read the first paragraph on page seventy-four. A real-time system must respond within a specified deadline.

Real-time does not simply mean very fast. Correctness includes whether the result arrives in time for its task.

Missing a hard deadline can violate the system's requirements. Missing a soft deadline reduces quality of service.

Moving a computation locally may remove some communication delay, but does not automatically guarantee a safe outcome.

Use this distinction when evaluating a remote controller: what is its deadline, and what happens if the response is late?

A good average is insufficient when the important problem is an occasional deadline miss.

Match the remedy to the symptom

Video 06:13–07:04 / Study guide page 62

Four problems to distinguish

Metric	What it tells you
Bandwidth / capacity	How much data a link can carry per second.
Throughput	The successful transfer rate actually achieved.
Latency	How long a transfer or response takes.
Jitter / loss	Variation in delay / missing packets.

Exact excerpt from the Blue Impulse study guide

Return to the final paragraph on page sixty-two and match each response to a problem.

When capacity is limited, compress or summarise suitable data. When round trips dominate, reduce unnecessary exchanges.

Timestamps help detect stale measurements. A playback buffer can smooth jitter, but the buffer adds delay.


Reconnect logic and redundancy can improve resilience, while designed local control reduces dependence on an unavailable remote link.

Page eighty-eight reminds us that growing a system adds load and coordination challenges, not just more devices.

Every remedy has a trade-off. Diagnose, change one factor, and measure again using the metric that matters.

Calculate a new delay

Video 07:04–07:56 / Study guide page 74



Exact excerpt from the Blue Impulse study guide

Your turn. At thirty metres per second, how far does an object travel during a two hundred millisecond delay?

Convert the units before multiplying. Take a few seconds, or pause the video to work it out.

Two hundred milliseconds is zero point two seconds. Thirty times zero point two is six metres.

This is only distance during the delay. It does not include the rest of a real stopping process.

Now consider a separate question: would adding a playback buffer always help a time-critical controller? No, because buffering adds delay.

The right network design depends on the task, not a single universally best setting.

Pause first: 30 m/s × 200 ms = ?
Check: 30 × 0.200 = 6 metres during delay

Measure the whole task

Video 07:56–08:45 / Study guide page 62

Four problems to distinguish

Metric	What it tells you
Bandwidth / capacity	How much data a link can carry per second.
Throughput	The successful transfer rate actually achieved.
Latency	How long a transfer or response takes.
Jitter / loss	Variation in delay / missing packets.

Exact excerpt from the Blue Impulse study guide

Let's recap page sixty-two. Capacity is the limit, throughput is achieved transfer, latency is delay, jitter is variation, and loss is missing data.

Our page seventy-four demonstration gave fifteen, one point five, and zero point one five metres during three different delays.

Those numbers illustrate timing; they are not total stopping distances.


Use the road analogy to keep the measures distinct, then replace the analogy with an actual measurement.

For practice, describe a slow application, name the metric you would test, and justify one targeted improvement.

Run the supporting delay calculator to check a second speed and explain the units in your answer.

Blue Impulse study guide

Video 08:45–09:14 / Study guide page 1



This tutorial was taught from the Blue Impulse study guide, especially pages fifty-six, fifty-nine, sixty-two, seventy-four, and eighty-eight.

The original cover on screen credits the book we used throughout the lesson.

Keep the companion tutorial PDF, subtitles, narration, and delay calculator for revision.

Blue Impulse study guide. Measure the whole task, then choose the fix.