

Analysis of Optical Modes

A Finite Difference Approach

James Delaney

Supervised by: Prof. Frank Peters

Department of Physics
University College Cork

April 2017

Overview

The main goals of this project are as follows.

Overview

The main goals of this project are as follows.

- Develop a numerical algorithm to model an EM field in a simple waveguide structure in 1D and extend this to solve for more complex waveguides

Overview

The main goals of this project are as follows.

- Develop a numerical algorithm to model an EM field in a simple waveguide structure in 1D and extend this to solve for more complex waveguides
- Generalise this algorithm to 2D

Overview

The main goals of this project are as follows.

- Develop a numerical algorithm to model an EM field in a simple waveguide structure in 1D and extend this to solve for more complex waveguides
- Generalise this algorithm to 2D
- Gain a solid understanding of waveguides, their operation and their importance

Overview

The main goals of this project are as follows.

- Develop a numerical algorithm to model an EM field in a simple waveguide structure in 1D and extend this to solve for more complex waveguides
- Generalise this algorithm to 2D
- Gain a solid understanding of waveguides, their operation and their importance
- Study how the structure of a waveguide affects the distribution of the EM field within it

Introduction to Waveguides

What are waveguides?

Introduction to Waveguides

What are waveguides?

In order to understand and analyse electromagnetic (EM) modes we must first understand what is meant by a waveguide.

Introduction to Waveguides

What are waveguides?

In order to understand and analyse electromagnetic (EM) modes we must first understand what is meant by a waveguide.

In a very simple sense, a waveguide is exactly that, a structure that guides waves.

Rather than allowing the wave energy to diffuse in all directions a waveguide confines the wave, and thus its energy, allowing the transfer of energy over distances not possible without a waveguide.



Introduction to Waveguides


The typical example of a waveguide is the optical fibre. Optical fibres use the confinement property of waveguides to transfer information over very large distances at high speeds.

Introduction to Waveguides

The typical example of a waveguide is the optical fibre.

Optical fibres use the confinement property of waveguides to transfer information over very large distances at high speeds.

A simple way of visualising the operation of an optical fibre is through ray diagram.




However in order to fully understand the behaviour of an EM field in a waveguide we must think of it as a field rather than a simple ray

Introduction to Waveguides

The typical example of a waveguide is the optical fibre.

Optical fibres use the confinement property of waveguides to transfer information over very large distances at high speeds.

A simple way of visualising the operation of an optical fibre is through ray diagram.



However in order to fully understand the behaviour of an EM field in a waveguide we must think of it as a field rather than a simple ray

Optical Modes

Once a wave is confined in a structure, it no longer acts as a simple planar wave. A wave in a waveguide must now satisfy specific boundary conditions.

Optical Modes

Once a wave is confined in a structure, it no longer acts as a simple planar wave. A wave in a waveguide must now satisfy specific boundary conditions.


This necessity to satisfy boundary conditions means that the distribution of the field inside the structure is restricted to certain patterns.

Optical Modes

Once a wave is confined in a structure, it no longer acts as a simple planar wave. A wave in a waveguide must now satisfy specific boundary conditions.

This necessity to satisfy boundary conditions means that the distribution of the field inside the structure is restricted to certain patterns.

These allowed patterns are called **modes** and they can be thought of as analogous to the discretisation of a particle wavepacket in potential.



Numerical Approach

This project focuses on the application of numerical methods to study the modal structure of an EM field in certain waveguides.

Numerical Approach

This project focuses on the application of numerical methods to study the modal structure of an EM field in certain waveguides.

Why is this approach important?

Numerical Approach

This project focuses on the application of numerical methods to study the modal structure of an EM field in certain waveguides.

Why is this approach important?

- This approach is crucial in understanding the behaviour of an EM field in a waveguide mainly because there is no analytical modal solution for higher than 1D.

Numerical Approach

This project focuses on the application of numerical methods to study the modal structure of an EM field in certain waveguides.

Why is this approach important?

- This approach is crucial in understanding the behaviour of an EM field in a waveguide mainly because there is no analytical modal solution for higher than 1D.
- Numerical techniques allow us to study this field in a very scalable way.

Finite Difference Methods

There are several different methods that can be used in the numerical analysis of this problem.

The most popular two methods are Finite Element Methods (FEM) and Finite Difference Methods (FDM).

The choice generally depends on the problem being studied

Finite Difference Methods

There are several different methods that can be used in the numerical analysis of this problem.

The most popular two methods are Finite Element Methods (FEM) and Finite Difference Methods (FDM).

The choice generally depends on the problem being studied

This project focuses completely on FD methods.

This is due to there being no major benefit in using FE methods over FDMs for this particular system and FD methods tend to require less of a mathematical foundation to implement efficiently.

Wave Equation

From electrodynamics we know that interacting electric and magnetic fields oscillate and can be described by a wave equation.

Wave Equation

From electrodynamics we know that interacting electric and magnetic fields oscillate and can be described by a wave equation.

From Maxwell's equations it can be shown that in a medium with a relative permittivity ϵ_r and a relative permeability $\mu_r = 1$, the electric and magnetic fields are governed by the following equations.

$$\nabla^2 \mathbf{E} + \nabla \left(\frac{\nabla \epsilon_r}{\epsilon_r} \cdot \mathbf{E} \right) + k_0^2 \epsilon_r \mathbf{E} = 0 \quad (1)$$


$$\nabla^2 \mathbf{H} + \frac{\nabla \epsilon_r}{\epsilon_r} \times (\nabla \times \mathbf{H}) + k_0^2 \epsilon_r \mathbf{H} = 0 \quad (2)$$

1D Slab Waveguide

In order to get a firm grasp on the operation of a waveguide we will take the simplest case. A symmetric 1D slab wave guide.

1D Slab Waveguide


In order to get a firm grasp on the operation of a waveguide we will take the simplest case. A symmetric 1D slab waveguide.



This waveguide is chosen as it has a continuous permittivity except at the boundaries between media. This allows for the great simplification of letting $\nabla \epsilon_r = 0$.

1D Slab Waveguide

In order to get a firm grasp on the operation of a waveguide we will take the simplest case. A symmetric 1D slab wave guide.



This waveguide is chosen as it has a continuous permittivity except at the boundaries between media. This allows for the great simplification of letting $\nabla \epsilon_r = 0$.

This waveguide also captures the fundamental properties of a waveguide with minimal complexity.

TE and TM Modes

When we talk about allowed modes there are two main types we are interested in; what are known as Transverse Electric (TE) and Transverse Magnetic (TM) modes. TE modes have no electric field in the direction of propagation $E_z = 0$ and TM modes have no magnetic field in the direction of propagation $H_z = 0$.

TE and TM Modes

When we talk about allowed modes there are two main types we are interested in; what are known as Transverse Electric (TE) and Transverse Magnetic (TM) modes. TE modes have no electric field in the direction of propagation $E_z = 0$ and TM modes have no magnetic field in the direction of propagation $H_z = 0$.

Using Maxwell's equations for EM waves.

$$\nabla \times \mathbf{E} = -i\omega\mu_0\mathbf{H} \quad (3)$$

$$\nabla \times \mathbf{H} = i\omega\epsilon_0\epsilon_r\mathbf{E} \quad (4)$$

Allows the vector wave equations (1) and (2) to be simplified to a scalar form.

Scalar Wave Equations

$$\frac{d^2 E_y}{dx^2} + k_0^2 (\epsilon_r - n_{eff}^2) E_y = 0 \quad (5)$$

$$\frac{d^2 H_y}{dx^2} + k_0^2 (\epsilon_r - n_{eff}^2) H_y = 0 \quad (6)$$

The above equations can be solved quite easily analytically and using the boundary condition that the tangential component of both fields are continuous across the boundary between lossless dielectrics yields solutions that vary sinusoidally within guide and decay exponentially outside.

Scalar Wave Equations

$$\frac{d^2 E_y}{dx^2} + k_0^2 (\epsilon_r - n_{eff}^2) E_y = 0 \quad (5)$$

$$\frac{d^2 H_y}{dx^2} + k_0^2 (\epsilon_r - n_{eff}^2) H_y = 0 \quad (6)$$

The above equations can be solved quite easily analytically and using the boundary condition that the tangential component of both fields are continuous across the boundary between lossless dielectrics yields solutions that vary sinusoidally within guide and decay exponentially outside.

The parameter n_{eff} is called the 'effective index' and is very important in the confinement of waves. It will be discussed in the next slide.

Effective Index

The effective index n_{eff} is defined as the ratio between the wave vector in a vacuum and the component of the wave vector in the direction of propagation in the given medium, in this case $n_{eff} = \frac{k_0}{k_z}$ where $k_0 = nk$ is the wave vector in a vacuum of light being used.

Effective Index


The effective index n_{eff} is defined as the ratio between the wave vector in a vacuum and the component of the wave vector in the direction of propagation in the given medium, in this case $n_{eff} = \frac{k_0}{k_z}$ where $k_0 = nk$ is the wave vector in a vacuum of light being used.

This is very well illustrated using the ray diagram approach.

Effective Index

The effective index n_{eff} is defined as the ratio between the wave vector in a vacuum and the component of the wave vector in the direction of propagation in the given medium, in this case $n_{eff} = \frac{k_0}{k_z}$ where $k_0 = nk$ is the wave vector in a vacuum of light being used.

This is very well illustrated using the ray diagram approach.



Analytical Solutions to 1D Case

Below are the analytical solutions to the first two TE modes using light of wavelength $\lambda = 1.55\mu m$ confined in guide of width $2a = 4\mu m$.





Figure: First two TE modes

Finite Difference Approximation

Now that we have an analytical solution we want to design an algorithm to numerically compute the solution and compare results.


The numerical method we used is called the Finite Difference (FD) method.

Finite Difference Approximation

Now that we have an analytical solution we want to design an algorithm to numerically compute the solution and compare results.

The numerical method we used is called the Finite Difference (FD) method.

There are several ways to implement this method but all are based on using local Taylor Expansions to approximate derivatives at discrete points on the interval of interest.



Finite Difference Approximation

As we just need to approximate second order derivatives we are going to use the central difference method.

This is called 'central' as it works by taking Taylor expansions a step h either side of each discrete point on the interval.

$$E_y(x + h) = E_y(x) + E'_y(x)h + \frac{E''_y(x)}{2}h^2 + O(h^3)$$

$$E_y(x - h) = E_y(x) - E'_y(x)h + \frac{E''_y(x)}{2}h^2 - O(h^3)$$

Finite Difference Approximation

As we are dealing with discrete points, we will treat the field as discrete rather than continuous, labelling each point as $E_p = E_y(x_0 + ph)$, where x_0 is some starting point.

Finite Difference Approximation

As we are dealing with discrete points, we will treat the field as discrete rather than continuous, labelling each point as $E_p = E_y(x_0 + ph)$, where x_0 is some starting point.

Adding the two Taylor expansions and rearranging yields the following approximation to the second derivative.

Finite Difference Approximation

As we are dealing with discrete points, we will treat the field as discrete rather than continuous, labelling each point as $E_p = E_y(x_0 + ph)$, where x_0 is some starting point.

Adding the two Taylor expansions and rearranging yields the following approximation to the second derivative.

$$E_p'' = \frac{1}{h^2} (E_{p+1} - 2E_p + E_{p-1})$$

Finite Difference Approximation

If we make the substitution into our scalar wave equation and rearrange, we are left with a linear equation in E .

$$\frac{E_{p+1}}{(k_0 h)^2} + \frac{E_{p-1}}{(k_0 h)^2} + \left(n_p^2 - \frac{2}{(k_0 h)^2} \right) E_p = n_{eff}^2 E_p \quad (7)$$

Finite Difference Approximation

If we make the substitution into our scalar wave equation and rearrange, we are left with a linear equation in E .

$$\frac{E_{p+1}}{(k_0 h)^2} + \frac{E_{p-1}}{(k_0 h)^2} + \left(n_p^2 - \frac{2}{(k_0 h)^2} \right) E_p = n_{eff}^2 E_p \quad (7)$$

Although, this equation is just for the TE mode in 1D, the concept behind the method remains the same for higher dimensions and is independent of the mode.

Finite Difference Approximation

If we make the substitution into our scalar wave equation and rearrange, we are left with a linear equation in E .

$$\frac{E_{p+1}}{(k_0 h)^2} + \frac{E_{p-1}}{(k_0 h)^2} + \left(n_p^2 - \frac{2}{(k_0 h)^2} \right) E_p = n_{eff}^2 E_p \quad (7)$$

Although, this equation is just for the TE mode in 1D, the concept behind the method remains the same for higher dimensions and is independent of the mode.

If we choose there to be n points this method gives us n linear equations which can then be written in the form of the eigenvalue equation.

Finite Difference Approximation

If we make the substitution into our scalar wave equation and rearrange, we are left with a linear equation in E .

$$\frac{E_{p+1}}{(k_0 h)^2} + \frac{E_{p-1}}{(k_0 h)^2} + \left(n_p^2 - \frac{2}{(k_0 h)^2} \right) E_p = n_{eff}^2 E_p \quad (7)$$

Although, this equation is just for the TE mode in 1D, the concept behind the method remains the same for higher dimensions and is independent of the mode.

If we choose there to be n points this method gives us n linear equations which can be then written in the form of the eigenvalue equation.

$$\tilde{\mathbf{A}}\mathbf{E} = n_{eff}^2 \mathbf{E}$$

Reduction to Eigenvalue Equation

As the interval we are dealing with was quite a lot larger than the guide itself, boundary conditions were chosen such that the field went to zero at the interval boundary.

Reduction to Eigenvalue Equation

As the interval we are dealing with was quite a lot larger than the guide itself, boundary conditions were chosen such that the field went to zero at the interval boundary.

Therefore the finite difference matrix $\tilde{\mathbf{A}}$ has the form

$$\tilde{\mathbf{A}} = \begin{bmatrix} n_0^2 - \frac{2}{(k_0 h)^2} & \frac{1}{(k_0 h)^2} & 0 & \dots & 0 \\ \frac{1}{(k_0 h)^2} & n_1^2 - \frac{2}{(k_0 h)^2} & \frac{1}{(k_0 h)^2} & \dots & 0 \\ \vdots & \vdots & \ddots & \ddots & \vdots \\ \vdots & \vdots & \frac{1}{(k_0 h)^2} & n_{n-1}^2 - \frac{2}{(k_0 h)^2} & \frac{1}{(k_0 h)^2} \\ 0 & \dots & 0 & \frac{1}{(k_0 h)^2} & n_n^2 - \frac{2}{(k_0 h)^2} \end{bmatrix}$$

Solving Eigenvalue Problem

As this is a symmetric tridiagonal matrix it isn't very computationally complex and is easily solvable on a standard laptop.

If we compare the first two TE modes with the analytical results we can see that they agree very well.

Analytical vs Numerical Comparison




Figure: Comparison of first two TE modes for numerical (top) and analytical (bottom) solutions

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

In the 1D case, the ability of the guide to carry more than one mode is due to three things

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

In the 1D case, the ability of the guide to carry more than one mode is due to three things

- The wavelength of the light being guided

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

In the 1D case, the ability of the guide to carry more than one mode is due to three things

- The wavelength of the light being guided
- The width of the waveguide

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

In the 1D case, the ability of the guide to carry more than one mode is due to three things

- The wavelength of the light being guided
- The width of the waveguide
- The difference in refractive index across the boundary between media

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

If we consider the case of a particle in a square well, these properties are analogous to:

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

If we consider the case of a particle in a square well, these properties are analogous to:

- The energy of the particle

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

If we consider the case of a particle in a square well, these properties are analogous to:

- The energy of the particle
- The width of the well

QM Comparison

So far we have discussed the first two TE modes. There are in fact several possible modes for the waveguide geometry we have discussed.

If we consider the case of a particle in a square well, these properties are analogous to:

- The energy of the particle
- The width of the well
- The height of the well walls (potential step)

QM Comparison

This comparison is made very clear if we compare the case of the quantum harmonic oscillator with a wave in a parabolic waveguide.

QM Comparison



This comparison is made very clear if we compare the case of the quantum harmonic oscillator with a wave in a parabolic waveguide.

Plotting the effective indices for different modes in the parabolic waveguide we can see the stark similarities with the energy levels in QM harmonic oscillator.

QM Comparison

This comparison is made very clear if we compare the case of the quantum harmonic oscillator with a wave in a parabolic waveguide.



Plotting the effective indices for different modes in the parabolic waveguide we can see the stark similarities with the energy levels in QM harmonic oscillator.



QM Comparison

This comparison is made very clear if we compare the case of the quantum harmonic oscillator with a wave in a parabolic waveguide.

Plotting the effective indices for different modes in the parabolic waveguide we can see the stark similarities with the energy levels in QM harmonic oscillator.



Note: here a wide waveguide was used to make the comparison clearer

Extension to 2D

So far we have just looked at simple waveguides in 1D as this acts very well as an introduction to waveguides and their fundamental properties. However, for practical applications the numerical methods we have demonstrated so far need to be applicable to higher dimensions.

Extension to 2D

So far we have just looked at simple waveguides in 1D as this acts very well as an introduction to waveguides and their fundamental properties. However, for practical applications the numerical methods we have demonstrated so far need to be applicable to higher dimensions.

As mentioned previously, once we reach two dimensions there is no longer an analytical solution the field distribution in a waveguide. There are approximate methods, but these tend to be limited to certain geometries and so we are very reliant on numerical methods to understand the operation of waveguides in higher dimensions

Extension to 2D

So far we have just looked at simple waveguides in 1D as this acts very well as an introduction to waveguides and their fundamental properties. However, for practical applications the numerical methods we have demonstrated so far need to be applicable to higher dimensions.

As mentioned previously, once we reach two dimensions there is no longer an analytical solution the field distribution in a waveguide. There are approximate methods, but these tend to be limited to certain geometries and so we are very reliant on numerical methods to understand the operation of waveguides in higher dimensions

Semivectorial Wave Equations

Before applying the finite difference method in 2D, we must first define the governing equations.

Semivectorial Wave Equations

Before applying the finite difference method in 2D, we must first define the governing equations.

The equations used in 2D are very once again simplifications of the general vector wave equations (1) and (2) shown at the beginning of the presentation.

Semivectorial Wave Equations

Before applying the finite difference method in 2D, we must first define the governing equations.

The equations used in 2D are very once again simplifications of the general vector wave equations (1) and (2) shown at the beginning of the presentation.

In the 2D case we don't allow $\nabla \epsilon_r = 0$, instead we assume that the components of the fields are decoupled.

This leads to what are known as the semivectorial wave equations

Semivectorial Wave Equations

In order to clarify this explanation, we will just discuss the semivectorial equation for the E_x field in what is now called the Quasi-TE mode (due to the decoupling assumption)

$$\frac{\partial^2 E_x}{\partial x^2} + \frac{\partial}{\partial x} \left(\frac{1}{\epsilon_r} \frac{\partial \epsilon_r}{\partial x} E_x \right) + \frac{\partial^2 E_x}{\partial y^2} + (k_0^2 \epsilon_r - \beta^2) E_x = 0$$


Here the term β is used by convention to represent the component of the wave vector in the direction of propagation k_z .

2D Finite Difference Method

The finite difference method in two dimensions works in the exact same way as in the 1D case but now more care is needed as we need to consider 4 points around each discrete field point (2 in either direction)

2D Finite Difference Method

The finite difference method in two dimensions works in the exact same way as in the 1D case but now more care is needed as we need to consider 4 points around each discrete field point (2 in either direction)



2D Finite Difference Method

Applying the same central difference approximations at each point adjacent to (p, q) we are left with an equation of the form.

$$\alpha_l E_{p-1,q} + \alpha_r E_{p+1,q} + \alpha_t E_{p,q-1} + \alpha_b E_{p,q+1} \\ + \alpha_c E_{p,q} + (k_0^2 \epsilon_r(p, q) - \beta^2) E_{p,q} = 0$$

2D Finite Difference Method

$$\begin{aligned}\alpha_l &= \frac{1}{(\delta x)^2} \frac{2\epsilon_r(p-1, q)}{\epsilon_r(p, q) + \epsilon_r(p-1, q)} \\ \alpha_r &= \frac{1}{(\delta x)^2} \frac{2\epsilon_r(p+1, q)}{\epsilon_r(p, q) + \epsilon_r(p+1, q)} \\ \alpha_t &= \frac{1}{(\delta y)^2} \\ \alpha_b &= \frac{1}{(\delta y)^2} \\ \alpha_c &= -\frac{4}{(\delta x)^2} + \alpha_l + \alpha_r - \alpha_t - \alpha_b\end{aligned}$$

Implementation of 2D FD Method

As we are now dealing with a 2D system, our matrix will be in four dimensions. In order implement this on a computer we need to be able to formulate the system in way that is compatible with our eigenvalue formulation.

Implementation of 2D FD Method

As we are now dealing with a 2D system, our matrix will be in four dimensions. In order implement this on a computer we need to be able to formulate the system in way that is compatible with our eigenvalue formulation.

$$\tilde{\mathbf{A}}\mathbf{E} = \beta^2\mathbf{E}$$

Implementation of 2D FD Method

As we are now dealing with a 2D system, our matrix will be in four dimensions. In order implement this on a computer we need to be able to formulate the system in way that is compatible with our eigenvalue formulation.

$$\tilde{\mathbf{A}}\mathbf{E} = \beta^2\mathbf{E}$$

This is done by letting the vector \mathbf{E} be of the form

$$\mathbf{E} = (E_{00} \quad E_{01} \quad E_{02} \quad \dots \quad E_{10} \quad E_{11} \quad \dots \quad E_{nn})^T$$

Implementation of 2D FD Method

The easiest way to think of this is by defining the node number $r = pN_y + q$, where (p, q) define a discrete point in our matrix and N_y is the number of points in the y mesh.

Implementation of 2D FD Method

The easiest way to think of this is by defining the node number $r = pN_y + q$, where (p, q) define a discrete point in our matrix and N_y is the number of points in the y mesh.

Using this node formulation we can rewrite the multipliers α_i in terms of node points.

Our new multipliers are given by:

$$\alpha_l \leftrightarrow a_{r,r-N_y}$$

$$\alpha_r \leftrightarrow a_{r,r+N_y}$$

$$\alpha_t \leftrightarrow a_{r,r-1}$$

$$\alpha_b \leftrightarrow a_{r,r+1}$$

$$\alpha_c + k_0^2 \epsilon_r(p, q) \leftrightarrow a_{r,r}$$

2D Finite Difference Matrix

$$\tilde{\mathbf{A}} = \begin{bmatrix} a_{0,0} & a_{0,1} & 0 & \dots & 0 & a_{0,N_y} & 0 & \dots & 0 \\ a_{1,0} & a_{1,1} & a_{1,2} & \dots & \dots & 0 & a_{1,1+N_y} & 0 & \vdots \\ \vdots & \ddots & \ddots & \ddots & \vdots & \vdots & \vdots & \vdots & \vdots \\ \vdots & a_{r,r-N_y} & \dots & a_{r,r-1} & a_{r,r} & a_{r,r+1} & \dots & a_{r,r+N_y} & \dots \\ \vdots & \vdots & \vdots & \ddots & \ddots & \ddots & \vdots & \vdots & \vdots \\ \vdots & \vdots & \vdots & \ddots & \ddots & \ddots & \vdots & \vdots & \vdots \\ 0 & \dots & \dots & 0 & a_{N,N-N_y} & 0 & \dots & a_{N,N-N_y} & a_{N,N} \end{bmatrix}$$

2D solutions

The waveguide of interest is known as a ridge waveguide and it has the following form.




Figure: Rib waveguide 2D slice

Solutions to Modes in a Rib Waveguide

In order to solve for the modes in this distribution, we first had to load a matrix with relative permittivities at each point on the waveguide's 2D face.

Solutions to Modes in a Rib Waveguide

In order to solve for the modes in this distribution, we first had to load a matrix with relative permittivities at each point on the waveguide's 2D face.

Then the problem could be solve using the FD method described previously.




Solutions to Modes in a Rib Waveguide

In order to solve for the modes in this distribution, we first had to load a matrix with relative permittivities at each point on the waveguide's 2D face.

Then the problem could be solve using the FD method described previously.

On the next slide are the first possible modes for two rib waveguides with different scales.

Solutions to Modes in a Rib Waveguide




Level of Confinement with Waveguide Size

In order for a mode to be guided, it's effective index n_{eff} needs to be between the refractive indices of the core and the cladding (similar to the particle energy being less than the potential in a QM well).

Level of Confinement with Waveguide Size

In order for a mode to be guided, it's effective index n_{eff} needs to be between the refractive indices of the core and the cladding (similar to the particle energy being less than the potential in a QM well).

Visualising how the effective index changes with the 'size' of the waveguide is much clearer in 1D and so a plot of n_{eff} vs width (1D) is shown below.



Summary

The main goals of this project were completed. We were able to:

Summary

The main goals of this project were completed. We were able to:

- Develop numerical algorithms to solve for the allowed modes in arbitrarily complex 1D and 2D waveguide
- Compare our numerical result with the 1D analytical solutions
- Understand the confinement of an EM field in a waveguide in terms of the quantum well analogy

Summary

The main goals of this project were completed. We were able to:

- Develop numerical algorithms to solve for the allowed modes in arbitrarily complex 1D and 2D waveguide
- Compare our numerical result with the 1D analytical solutions
- Understand the confinement of an EM field in a waveguide in terms of the quantum well analogy

There is still plenty of interesting work that can be done on this topic, including:

Summary

The main goals of this project were completed. We were able to:

- Develop numerical algorithms to solve for the allowed modes in arbitrarily complex 1D and 2D waveguide
- Compare our numerical result with the 1D analytical solutions
- Understand the confinement of an EM field in a waveguide in terms of the quantum well analogy

There is still plenty of interesting work that can be done on this topic, including:

- Incorporating a variable step size into the numerical algorithms (particularly the 2D case)
- Carry out an analysis of how the dimensions of the 2D waveguide affect the n_{eff} as we did for the 1D case
- Move the code to an object-orientated style to allow for easier modification

Questions

