Stage 2

Overview :-

Nessus is a vulnerability scanner developed by Tenable, Inc. It is a remote scanner, meaning that it does not need to be installed on the target host to scan it. Nessus works by sending a variety of probes to the target host in order to identify vulnerabilities. These probes can include network traffic, operating system commands, and application requests.

Nessus uses a plugin-based architecture. Plugins are small pieces of code that are designed to identify specific vulnerabilities. There are over 1200 plugins available for Nessus, covering a wide range of vulnerabilities in operating systems, applications, and network devices.

When Nessus scans a host, it first uses a discovery plugin to identify the operating system and services running on the host. Once the host has been discovered, Nessus runs a series of plugins to test for vulnerabilities. For each vulnerability that Nessus finds, it provides a detailed report that includes the severity of the vulnerability, the steps to reproduce the vulnerability, and the steps to remediate the vulnerability.

Nessus can be used to scan a variety of targets, including single hosts, networks, and web applications. It can also be used to scan specific ports and services. Nessus can be configured to run scans on a schedule or manually.

Here is a step-by-step explanation of how Nessus works:

1. Nessus connects to the target host using a variety of protocols, including TCP, UDP, and ICMP.
2. Nessus sends a series of probes to the target host in order to identify its operating system and services.
3. Nessus runs a series of plugins to test for vulnerabilities.
4. Nessus generates a report that includes the severity of each vulnerability, the steps to reproduce the vulnerability, and the steps to remediate the vulnerability.

Nessus is a valuable tool for security professionals who need to identify and remediate vulnerabilities in their networks. It is easy to use and provides comprehensive reports that can be used to prioritise remediation efforts.

Here are some of the benefits of using Nessus:

- Comprehensive vulnerability coverage: Nessus has over 1200 plugins available, covering a wide range of vulnerabilities in operating systems, applications, and network devices.

- Easy to use: Nessus has a user-friendly interface that makes it easy to configure and run scans.
- Comprehensive reporting: Nessus provides detailed reports that include the severity of each vulnerability,the steps to reproduce the vulnerability, and the steps to remediate the vulnerability.
- Scalability: Nessus can be used to scan a variety of targets, including single hosts, networks, and web applications.
- Flexibility: Nessus can be configured to run scans on a schedule or manually.

Nessus is a powerful tool that can be used to improve the security of any network. It is a valuable asset for any security professional.

Target Website:- http://testfire.net/

Target ip address:- 65.61.137.117

List of vulnerability –

s.no	Vulnerability name	Severity	plugins
1	TLS Version 1.0 Protocol Detection	MEDIUM	104743
2	TLS Version 1.1 Protocol Deprecated	MEDIUM	157288
3	SSL/TLS Diffie-Hellman Modulus<= 1024 Bits (Logjam)	LOW	83875
4	ICMP Timestamp Request Remote Date Disclosure	INFO	10114
5	Additional DNS Hostnames	INFO	46180
6	Apache Tomcat Detection	INFO	39446

7	Common Platform Enumeration (CPE)	INFO	45590
8	Device Type	INFO	54615

REPORT:-

1) Vulnerability Name:-104743 - TLS Version 1.0 Protocol Detection

severity : -MEDIUM

Plugin:-104743

Port :- 443

Description:- The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

Solution:- Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Business Impact::- Continued use of TLS 1.0's encryption, known for its inherent cryptographic flaws, exposes the organization to heightened security risks, increasing the likelihood of data breaches and cyberattacks. This vulnerability jeopardizes compliance with industry standards, specifically PCI DSS v3.2, which mandates the complete cessation of TLS 1.0 use. Non- compliance risks regulatory penalties and erodes customer trust. Moreover, endpoints that lack support for TLS 1.2 and higher will experience impaired functionality with major web browsers and vendors, potentially leading to lost business opportunities and damage to the organization's reputation. Addressing this vulnerability is imperative to mitigate these multifaceted risks and maintain a secure and trustworthy online presence.

2) Vulnerability Name: - 157288 - TLS Version 1.1 Protocol Deprecated

Severity: - MEDIUM

Plugin: - 157288

Port: - 443

Description: - The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1 As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

Solution: - Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Business Impact: -The continued use of TLS 1.1 with its lack of support for modern cipher suites and advanced encryption methods jeopardizes the organization's security posture, increasing vulnerability to cyber threats and potential data breaches. Additionally, endpoints not upgraded to support TLS 1.2 and higher will encounter compatibility issues with major web browsers and vendors, impacting user experience and potentially leading to missed business opportunities. Swift remediation of this vulnerability is essential to mitigate security risks and ensure seamless interactions with web browsers and vendors, preserving the organization's reputation and operational efficiency.

3) Vulnerability Name: - 83875 - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

Severity: - LOW

Plugin: - 83875

Port: - 443

Description: - The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party may be able to find the shared secret in a short amount of time (depending on modulus size and attacker resources). This may allow an attacker to recover the plaintext or potentially violate the integrity of connections.

Solution: - Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

Business Impact: - Allowing SSL/TLS connections with weak Diffie-Hellman moduli raises security concerns. An attacker with sufficient resources and computing power could compromise the shared secret relatively quickly, potentially leading to the decryption of sensitive data or the violation of connection integrity. While the severity is low, the risk of data breaches and integrity compromise should not be underestimated, and it is essential to address this vulnerability to maintain data security and user trust.

4) Vulnerability Name: - 10114 - ICMP Timestamp Request Remote Date Disclosure

Severity: - INFO

Plugin: - 10114

Port: - 0

Description: - The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution: - Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Business Impact: -This does not pose an immediate threat to business operations or data security. This vulnerability allows external parties to request the system's date and time information remotely. While it does not present a significant risk, it could potentially be used by attackers for reconnaissance purposes. Therefore, it is advisable to address this vulnerability as part of a broader security posture to reduce the risk of unauthorized data gathering and protect against potential future threats.

5) Vulnerability Name: - 46180 - Additional DNS Hostnames

Severity: - INFO

Plugin: - 46180

Port: - 0

Description: - Hostnames different from the current hostname have been collected by miscellaneous plugins. Nessus has generated a list of hostnames that point to the remote host. Note that these are only the alternate hostnames for hosts discovered on a web server.

Different web servers may be hosted on name-based virtual hosts.

Solution: - If you want to test them, re-scan using the special vhost syntax, such as :

www.example.com [192.0.32.10]

Business Impact: -This does not pose an immediate threat to business operations or data security. It indicates the discovery of hostnames that are associated with the remote host, particularly in cases of web servers utilizing name-based virtual hosts. While not a security risk on its own, it could be useful for understanding the server's configuration and infrastructure.

Organizations should consider this information as part of their network documentation but do not need to take immediate action to mitigate it as a security threat.

6) Vulnerability Name: - 39446 - Apache Tomcat Detection

Severity: - INFO

Plugin: - 39446

Port: - 80

Description: -Nessus was able to detect a remote Apache Tomcat web server.

Solution: - n/a

Business Impact: -Is an informational finding that identifies the presence of a remote Apache Tomcat web server. While this information itself does not indicate a security threat or impact on business operations, it can be useful for network administrators and security professionals to be aware of the technologies in use on their network. Understanding the presence of an Apache Tomcat server can be valuable for maintaining and securing web applications, but it does not require immediate action to mitigate a security risk.

7) Vulnerability Name: - 45590 - Common Platform Enumeration (CPE)

Severity: - INFO

Plugin: - 45590

Port: - 0

Description: - By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

Solution: - n/a

Business Impact: - This provides insights into hardware and software products identified on a host through a Nessus scan. It reports CPE matches, which are standardized identifiers for these products. This information is valuable for asset management and inventory purposes. While it doesn't signify a security threat, it aids administrators in understanding the components within their network, contributing to effective resource management and facilitating future system maintenance.

8) Vulnerability Name: - Device Type

Severity: - INFO

Plugin: - 54615

Port: - 0

Description: - Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution: -

Business Impact: - It allows for the identification of the remote system type, such as a printer, router, or general-purpose computer, based on the remote operating system. While this doesn't pose a direct security threat, it offers valuable insights for network administrators to better understand and classify the devices in their network. This information aids in network management, optimization, and ensures that the right security measures are in place for each device type.