Multi-Annotator Consensus Modeling and Topological Decomposition for Solar Filament Instance Segmentation

A Solution to the Solar Filament Segmentation Challenge 2026

Sayandeep Dutta
SRM Institute of Science and Technology
Kattankulathur, India
sd2122@srmist.edu.in

ABSTRACT

This report outlines our solution to the Solar Filament Segmentation Challenge 2026, targeting instance segmentation of solar filaments in GONG H-α observations. The MAGFiLO benchmark exhibits high inter-observer variability across independent annotator passes, complex topological merging of adjacent structures, and strict zero-overlap constraints evaluated under Panoptic Quality. We propose a multi-stage framework coupling deep multi-backbone representations with topological post-processing. Our pipeline integrates a five-fold ConvNeXt ensemble with residual U-Net models, applies multi-annotator consensus filtering to suppress spurious singleton noise, decomposes conjoined filaments via geodesic distance bottleneck splitting, and enforces greedy disjoint mask allocation. On the 139-image multi-annotator benchmark, our method achieves a Panoptic Quality of 0.7341 (0.8000 Segmentation Quality, 0.9177 Recognition Quality) and obtains 0.62 on the public leaderboard (Rank 2).

1 INTRODUCTION

This report goes over the details of our submitted solution to the Solar Filament Segmentation Challenge 2026 [2]. The challenge, launched on July 10, 2026, is organized by the Earth-Space AI Research (ESAIR) Lab[1]. This challenge utilizes the MAGFiLO dataset for evaluation of the segmentation algorithms [1].

Instance segmentation in the MAGFiLO benchmark presents three core operational challenges:

(1) **Inter-Observer Variability**: Ground-truth annotations are provided by multiple independent expert passes (one to three annotators per observation). Annotators exhibit marked divergence regarding faint barb boundaries and structural endpoints.
(2) **Topological Agglomeration**: Nearby physical filaments frequently touch or connect through diffuse plasma bridges, causing models to predict conjoined instances.
(3) **Asymmetric Metric Penalties**: Evaluation computes Panoptic Quality (PQ = SQ $\times$ RQ) across all annotator passes independently. Predicting a high-confidence consensus filament earns multiple True Positive credits ($+k$ TP), whereas predicting an uncorroborated single-observer guess generates False Positive penalties across the remaining non-matching passes.

Our approach models filament segmentation through consensus-guided optimization. We combine complementary backbones with explicit topological decomposition, boundary calibration, and greedy disjoint allocation. Source code and reproduction pipelines are available on GitHub[2].

2 METHODOLOGY

Our methodology comprises five modular stages: image preprocessing, multi-backbone representation learning, consensus filtering, topological blob decomposition, and boundary-calibrated disjoint encoding (Figure 1).

2.1 Data Pipeline and Pre-Processing

GONG observations consist of 2048×2048 grayscale H-α images subject to station-dependent illumination shifts, limb darkening, and atmospheric blurring. We apply three standardized operations:

- **Solar Disk Extraction**: Gaussian smoothing ($\sigma = 15$) and Otsu thresholding establish the solar limb boundary ($R_\odot \approx 0.47 \min(H, W)$). Off-limb pixels are zeroed.
- **Contrast Normalization**: Contrast Limited Adaptive Histogram Equalization (CLAHE) with clip limit 2.5 and tile grid 16×16 enhances subtle absorption channels against the photosphere.
- **Adaptive Background Masking**: Local intensity percentiles within the disk identify dark candidate proposal seeds below the 8.5th percentile.

2.2 Multi-Backbone Network Architecture

We deploy an ensemble of complementary neural network backbones to maximize feature diversity:

- **Five-Fold ConvNeXt Ensemble**: ConvNeXt backbones [5] pre-trained on ImageNet and fine-tuned on native solar patches. Large 7×7 depthwise kernels capture elongated, curvilinear filament spines.

[1] www.esairlab.com/

Kaggle Competition, 2026, kaggle.com/competitions/filament-segmentation-2026
2026.

[2] https://github.com/usersamhere/kaggle-dummy




Figure 1: End-to-end processing and inference pipeline. Full-disk 2048×2048 GONG observations undergo contrast normalization and solar disk masking, followed by multi-backbone inference, annotator consensus filtering, topological split decomposition, and greedy disjoint allocation.

- **Residual U-Net**: A symmetrical U-Net [6] with a ResNet-34 encoder [3], preserving fine-grained boundary transitions and small fragments.
- **Native-Resolution Base U-Net**: A fully convolutional baseline producing full-disk candidate probability maps at native resolution.

2.3 Cross-Validation and Optimization

The training corpus contains 707 observation dates comprising 1,154 individual annotator records. Because multiple records share identical timestamps, naive random sampling induces data leakage. We partition data into five folds grouped strictly by observation date: all annotator passes for a timestamp reside exclusively within train or validation splits. Training minimizes a compound objective:

$$\mathcal{L} = \mathcal{L}_{\text{BCE}} + \alpha\mathcal{L}_{\text{Dice}} + \beta\mathcal{L}_{\text{Boundary}} \tag{1}$$

with $\alpha = 1.0$ and $\beta = 0.5$, penalizing contour divergence along thin filament edges under spatial and photometric augmentations.

2.4 Multi-Annotator Consensus Formulation

Let an image possess K annotator sets $\{G_1, \ldots, G_K\}$, where each set contains n_k ground-truth instances. The official metric evaluates each predicted mask P_j against each annotator independently:

$$\text{PQ} = \frac{\sum_{(g,p)\in \text{TP}} \text{IoU}(g,p)}{|\text{TP}| + \frac{1}{2}|\text{FP}| + \frac{1}{2}|\text{FN}|} \tag{2}$$

with match condition $\text{IoU}(g,p) > 0.5$.

When a prediction aligns with a consensus region corroborated by m annotators ($m \leq K$), it yields m True Positive increments ($+m$ TP) and zero False Positives. Conversely, predicting a candidate reflecting a solitary annotator's subjective guess risks matching zero instances in the remaining $K-1$ annotators, accumulating up to $K-1$ False Positives. Therefore, candidates are accepted only when satisfying ensemble consensus thresholding:

$$\mathcal{M}_{\text{consensus}} = \mathbb{I}\left(\frac{1}{M}\sum_{m=1}^{M}\sigma(F_m(x)) \geq \tau_{\text{consensus}}\right) \tag{3}$$

where $\tau_{\text{consensus}} = 0.45$, filtering out uncorroborated single-observer noise.

2.5 Topological Blob Decomposition

A major challenge in solar filament segmentation is filament agglomeration: nearby filaments joined by diffuse bridges merge into an oversized single instance. In evaluation, such merged blobs match at most one ground-truth structure while triggering False Negatives for neighboring bodies.

We develop the Golden Blob Split algorithm. For candidate regions exceeding area $A_{\text{blob}} > 4000\,\text{px}^2$, we evaluate distance transform ridge extrema and cross-backbone activations. When independent branches (e.g., ConvNeXt and ResNet-34) exhibit bimodal component activations with mutual IoU > 0.80, the blob is partitioned along its geodesic bottleneck into discrete sub-filaments. In benchmark evaluations, this resolved conjoined configurations (e.g., observation `20111015063134Lh`) into two confirmed instances with 0.8588 inter-model agreement.




Figure 2: Qualitative segmentation comparisons on GONG test observations. Individual annotator ground truths are displayed in distinct colors, with model predictions overlaid in red. The model captures multi-annotator consensus contours while resolving separate filament instances.

2.6 Boundary Calibration and Disjoint Encoding

Conservative thresholding can truncate narrow filament tails. For candidates displaying truncation relative to consensus spine activations, we apply guided morphological dilation along the medial skeleton. Boundary calibration optimizes Segmentation Quality (SQ = 0.8000) while maintaining margins below error saturation levels.

Competition rules require predicted instances within an image to be strictly disjoint. We enforce disjointness through confidence-ordered greedy allocation:

$$\tilde{P}_j = P_j \setminus \bigcup_{i<j} \tilde{P}_i \tag{4}$$

Final masks are encoded into column-major (Fortran-order) Run-Length Encoded (RLE) bitstrings adhering to the Microsoft COCO specification [4].

3 EVALUATION

3.1 Evaluation Protocol and Metrics

Our evaluation replicates the official competition scoring script on 139 benchmark observations containing multi-annotator ground-truth layers. The metric suite tracks:

- **Segmentation Quality (SQ)**: Mean IoU over matched pairs (IoU > 0.5).
- **Recognition Quality (RQ)**: $\frac{|\mathrm{TP}|}{|\mathrm{TP}|+0.5|\mathrm{FP}|+0.5|\mathrm{FN}|}$.
- **Panoptic Quality (PQ)**: The aggregate product PQ = SQ × RQ.

Table 1: Validation performance across developmental milestones on the 139-observation benchmark.

Iteration	TP	FP	FN	SQ	RQ
V13 (Baseline U-Net)	1371	247	259	0.7765	0.8442
V18 (ResNet-34)	1441	166	189	0.7861	0.8903
V27 (Dual Ensemble)	1457	172	173	0.7949	0.8941
V55 (Consensus)	1505	145	125	0.7925	0.9177
V60 (Calibrated)	1505	145	125	0.7973	0.9177
V80 (Apex)	1505	145	125	0.8000	0.9177
V102 (Champion)	**1509**	**151**	**121**	**0.7996**	**0.9173**

3.2 Quantitative Results and Ablations

Table 1 summarizes validation metrics across development milestones on the 139 benchmark observations.

The progression illustrates key performance drivers:

(1) **Multi-Backbone Diversity (V13 to V27)**: Combining ConvNeXt and ResNet-34 backbones decreased False Positives from 247 to 172 and improved SQ from 0.7765 to 0.7949.

(2) **Consensus Filtering (V27 to V55)**: Suppressing isolated single-annotator noise eliminated 27 False Positives and gained 48 True Positives, raising RQ from 0.8941 to 0.9177.

(3) **Calibration and Decomposition (V60 to V80)**: Topological blob splitting and contour calibration improved SQ to 0.8000, yielding validation PQ of 0.7341.

(4) **Dual-Model Corroboration (V88 to V102)**: Admitting validated novel filaments with $> 88\%$ mutual




Figure 3: Quantitative performance evaluation. (a) Progression of Panoptic Quality (PQ), Segmentation Quality (SQ), Recognition Quality (RQ), and public leaderboard scores across iterations. (b) Pairwise IoU probability density over True Positive pairs, demonstrating boundary consistency centered at SQ $= 0.8000$**.**

ConvNeXt/U-Net agreement added confirmed structures (1,396 final instances) while preserving sub-0.8000 SQ limits, securing Rank 2 Worldwide (0.62 PQ).

Figure 3(a) illustrates validation metric progression alongside public leaderboard gains. Figure 3(b) details the empirical pairwise IoU distribution on True Positive pairs, confirming high boundary stability.

3.3 Discussion and Limitations

Multi-annotator consensus modeling provides effective protection against spurious False Positive penalties while capturing high-confidence filament structures. Moreover, the Golden Blob Split algorithm handles filament agglomeration that standard single-model detectors fail to resolve. Matching degree analysis indicates that over 94% of predicted instances achieve clean $1:1$ correspondence with annotator records.

The primary limitation involves very faint barbs near the solar limb, where extreme limb darkening attenuates contrast. Disagreements among annotators on faint endpoints also create residual label ambiguity. Future work could incorporate magnetic field extrapolation along polarity inversion lines to guide topological continuity.

4 ACKNOWLEDGMENT

The organization of the Filament Segmentation Challenge 2026 is partially supported by the U.S. National Science Foundation (NSF) under Grant No. 2209912 and 2433781, directorate for Computer and Information Science and Engineering (CSE), and Office of Advanced Cyberinfrastructure (OAC), and Grant No. 2511630, AST Division Of Astronomical Sciences and MPS Directorate for Mathematical and Physical Sciences.

The Filament Segmentation Challenge 2026 is sponsored by the U.S. National Science Foundation (NSF) National Solar Observatory (NSO).

This work utilizes GONG data obtained by the NSO Integrated Synoptic Program, managed by the National Solar Observatory, which is operated by the Association of Universities for Research in Astronomy (AURA), Inc. under a cooperative agreement with the National Science Foundation and with contribution from the National Oceanic and Atmospheric Administration. The GONG network of instruments is hosted by the Big Bear Solar Observatory, High Altitude Observatory, Learmonth Solar Observatory, Udaipur Solar Observatory, Instituto de Astrofísica de Canarias, and Cerro Tololo Interamerican Observatory.

REFERENCES

[1] Azim Ahmadzadeh, Rohan Adhyapak, Kartik Chaurasiya, Laxmi Alekhya Nagubandi, V. Aparna, Petrus C. Martens, Alexei Pevtsov, Luca Bertello, Alexander Pevtsov, Naomi Douglas, Samuel McDonald, Apaar Bawa, Eugene Kang, Riley Wu, Dustin J. Kempton, Aya Abdelkarem, Patrick M. Copeland, and Sri Harsha Seelamneni. 2024. A dataset of manually annotated filaments from H-alpha observations. In *Nature Scientific Data (Nature Scientific Data, Vol. 11)*. Springer, Article 1031, 1031 pages. https://doi.org/10.1038/s41597-024-03876-y

[2] Azim Ahmadzadeh, Dustin J. Kempton, Qin Li, and Alexei A. Pevtsov. 2026. Solar Filament Segmentation Challenge 2026. https://kaggle.com/competitions/filament-segmentation-2026. Kaggle.

[3] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep Residual Learning for Image Recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. 770–778.

[4] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C. Lawrence Zitnick. 2014. Microsoft COCO: Common Objects in Context. In *European Conference on Computer Vision (ECCV)*. 740–755.

[5] Zhuang Liu, Hanzi Mao, Chao-Yuan Wu, Christoph Feichtenhofer, Trevor Darrell, and Saining Xie. 2022. A ConvNet for the 2020s. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 11976–11986.

[6] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. 2015. U-Net: Convolutional Networks for Biomedical Image Segmentation. In *Medical Image Computing and Computer-Assisted Intervention (MICCAI)*. 234–241.