

# The Ultimate Guide To D2L Webservices & INGRESS Integration

Mazhar Malik, GerogiaVIEW Information Technology Services October 25, 2107



## Summary:

- INGRESS
- Webservices
- Brightspace by D2L Webservices
- Security
- Recommendations
- Common Mistakes and Errors
- Demo
- Question & Comments



# Intra-Georgia Registration Sharing System (INGRESS)





### INGRESS:


- INGRESS was developed by Information Technology Services
- Integrates with the Ellucian Banner student information system and the Brightspace by D2L learning management system (LMS)
- Processes cross-institutional registrations
- Supports centralized seat management
- Automates the creation of online courses & enrollments in LMS using XML & Webservices




# INGRESS: Concept/Data Flow








# Webservices



Webservices are nothing more than a request & response mechanism that allows a client to remotely & securely access/modify data over http/https protocol.



## HTTP Request/Response





Web Server

HTTP Response



## RESTful Request/Response

HTTP Request (GET/POST/PUT/DELETE)

Service Consumer



Service Provider

HTTP Response



# Webservices: Request Methods

Request Method Type	Action
GET	Access DATA
POST	Create DATA
PUT	Update DATA
DELETE	Delete DATA



## JSON: JavaScript Object Notation

```
"OrgDefinedId": <string>,
    "FirstName": <string>,
    "MiddleName": <string>,
    "LastName": <string>,
    "ExternalEmail": <string> | null,
    "UserName": <string>,
    "RoleId": <number>,
    "IsActive": <boolean>,
    "SendCreationEmail": <boolean>
}
```



## Brightspace by D2L Webservices



# Brightspace by D2L Webservices:

- RESTful APIs (Representational State Transfer)
  - Uses XML or JSON to send and receive data
  - Simply calls services via URL path
  - Transfer is over HTTPS Protocol
- ID/Key Auth
  - Key Hashed Message Authentication Code (HMAC-SHA256)
  - Application ID / Key
  - User ID / Key
- JSON Data Structure (JavaScript Object Notation)
- Reference: <a href="http://docs.valence.desire2learn.com/reference.html">http://docs.valence.desire2learn.com/reference.html</a>
- HTTP URLS: <a href="http://docs.valence.desire2learn.com/http-routingtable.html">http://docs.valence.desire2learn.com/http-routingtable.html</a>



## JSON: JavaScript Object Notation

```
"OrgDefinedId": <string>,
    "FirstName": <string>,
    "MiddleName": <string>,
    "LastName": <string>,
    "ExternalEmail": <string> | null,
    "UserName": <string>,
    "RoleId": <number>,
    "IsActive": <boolean>,
    "SendCreationEmail": <boolean>
}
```



## Requirements:

- Developer:)
- Webserver (Apache, IIS etc.)
- Get Application ID / Key from D2L
  - Open Helpdesk Ticket with ITS
  - One ID / Key Per Application Per Environment
  - Make Sure Application Shows Up Under Extensibility Management Area and is Enabled
- Choose a Client Library & Download
  - C#, JAVA, Javascript, PHP, Python
  - Includes all the APIs and libraries (PHP, JAVA, JavaScript, C#) to create apps
  - Check version requirements. (e.g PHP 5.x is required)
  - http://docs.valence.desire2learn.com/clients/index.html



## Requirements:

- Unzip and Copy Files to Webserver Root Directory
- Create User Account In D2L Org
- Set User Permissions in D2L Org
- Authenticate with D2L Org to Get User ID / Key
- Use port https protocol (Port 443)
- SSL Certificate for Webserver
- http://127.0.0.1/rockeagle/php/samples/
   GettingStartedSample/index.php
- https://apitesttool.desire2learnvalence.com/




$\overline{\mathbf{w}}$		lib
		D2LAppContext.php
		D2LAppContextFactory.php
		D2LConstants.php
		D2LHostSpec.php
		D2LSigner.php
		D2LUserContext.php
		D2LAppContext.php
		ID2LUserContext.php
		UserOpSecurityParameters.php
		LICENSE
		README.md
$\overline{\mathbb{A}}$		samples
	$\overline{\mathbf{w}}$	GettingStartedSample
		authenticateUser.php
		acert.pem
		config.php
		doRequest.php
		index.php
		README.md
		sample.js




Iost:	valence.desire2learn.com	Port:	443	HTTPS
App ID:	G9nUpvbZQyiPrk3um2YAkQ	App Key:	ybZu7fm_JKJTFwKEHfoZ7Q	
ote: to a	uthenticate against the test server, y	ou can user	username "sampleapiuser" and	password "Tisabiiif".
uthentic	ate			
lanually	set credentials			
Example	es: Get Versions			
zampie				
	WhoAmI			
	Create User			
lethod:	• GET POST PUT DE	LETE		
ction:	OCET CTOST CTOT OPE	LLIL		











## Generating HTTP Request:

- Host Name of Brightspace by D2L Org
- Port (https 443)
- Application ID / Key
- User ID / Key
- Webservices Call (Action/URL)
- Webservices Call Method

• GET (Retrieve)

POST (Create)

• PUT (Update)

• DELETE (Delete)

JSON Data (POST & PUT)

- http://docs.valence.desire2learn.com/http-routingtable.html
- http://docs.valence.desire2learn.com/reference.html




## Generating HTTP Request:

```
require_once '../../lib/D2LAppContextFactory.php';
$host = From the database;
                                               //goqa.view.usg.edu
                                               // 443
$port = From the database;
$scheme = From the database;
                                               // https
                                               // Application ID provided by D2L
$appId = From the database;
                                               // Application Key provided by D2L
$appKey = From the database;
                                               // User ID generated by goga.view.usg.edu
$userId = From the database;
$userKey = From the database;
                                               // User Key generated by goga.view.usg.edu
$data = $_GET['data'];
                                               // data to post
$apiMethod = $_GET['apiMethod'];
                                               // GET | POST | PUT | DELETE
$authContextFactory = new D2LAppContextFactory();
$authContext = $authContextFactory->createSecurityContext($appId, $appKey);
$hostSpec = new DZLHostSpec($host, $port, $scheme);
$opContext = $authContext->createUserContextFromHostSpec($hostSpec, $userId, $userKey);
$uri = $opContext->createAuthenticatedUri($_GET['apiRequest'], $_GET['apiMethod']);
```

```
// create curl resource
$ch = curl_init();
// Sets multiple options for a cURL session
$options = array(
    CURLOPT_RETURNTRANSFER -> true,
                                                           //return the transfer as a string
    CURLOPT_CAINFO -> getcwd().'/cacert.pem',
                                                           //The name of a file holding one or more certificates for verification
    CURLOPT_URL, $ur1,
                                                           // set the URL
   >;
curl_setopt_array($ch, $options);
switch($apiMethod) {
    case 'POST':
                                                               // POST is used to create
        curl_setopt($ch, CURLOPT_CUSTOMREQUEST, "POST");
                                                               // set custom request method
        curl_setopt(Sch, CURLOPT_HTTPHEADER, array(
                                                               //An array of HTTP header fields to set
            'Content-Type: application/json',
            'Content-Length: ' . strlen($data))
        curl_setopt($ch, CURLOPT_POSTFIELDS, $data);
                                                               // data to post in a HTTP "POST" operation.
        break:
    case 'PUT':
                                                               // PUT is used for updates
        curl_setopt($ch, CURLOPT_CUSTOMREQUEST, "PUT");
                                                               // set custom request method
        curl_setopt($ch, CURLOFT_HTTPHEADER, array(
                                                               //An array of HTTP header fields to set
            "Content-Type: application/json".
            'Content-Length: ' . strlen($data))
        curl_setopt(Sch, CURLOPT_POSTFIELDS, Sduta);
                                                               // data to post in a HTTP "POST" operation.
        break;
    case 'DELETE':
        curl_setopt($ch, CURLOPT_CUSTOMREQUEST, "DELETE");
                                                               // set custom request method
        break;
    case 'GET':
                                                               // GET is used to retrieve
        break;
// Execute the given cURL request $response contains the output string
$response = curl_exec($ch);
$httpCode = curl_getinfo($ch, CURLINFO_HTTP_CODE);
                                                                                // Last received HTTP code
$contentType = curl_getinfo($ch, CURLINFO_CONTENT_TYPE);
                                                                               // Type on content returned
$responseCode = SopContext->handleResult($response, $httpCode, $contentType); // evaluate the response code
if ($responseCode == D2LUserContext::RESULT_OKAY) {
    // parse JSON data
} else {
   // do something with error
curl_close($ch):
```



# Security




# Security:

- Always Start with DEV environment
- Application & User ID / Key (Keep it safe. DO NOT Share.)
- Always use SSL and https
- Regularly patch servers (webserver, database)
- Open server ports that are needed
- Always Create a Separate User Account
- Always Set Appropriate Permissions
- User ID / Key Expires After 180 days
- Revoke User Access
- Disable Application in D2L
- Application Review with Georgia VIEW




## Revoke Application Access:





## Disable Application:







- Save following info in the Database
  - App & User ID/Key
  - Hostname, Port, Scheme
  - OrgUnit IDs for D2L Org, Course Offerings, Sections, Users, Semester, Template (Org Unit Editor)
  - Unique Role IDs (Roles and Permissions)
  - D2L Webservices API version
  - Date of User ID/Key Expiration (180 days)
  - TLS version to use



#### Org Unit Editor

**New Org Unit** 

Recycle Bin

More Actions 💙

Jump To: Homepage | Course Admin

Georgia Online Virtual Instruction Enterprise Wide (6624)

#### Semester

August 2015 (313725)

CPS Development (7228)

- CPS Testing (7226)
- Fall 2013 (6668)
- Fall 2014 (7808)
- Fall 2015 (362394)

#### Fall 2013 (6668)

Properties ~

Name: Fall 2013

Code: 20142

Type: Semester


Path: /content/20142/


Parent Georgia Online Virtual Instruction Enterprise Wide (6624)

S:



Semester is set to displayed for CreateCourse under "Form Elements"





- Keep track of No. of Webservices Calls
- Keep track of failed calls and a mechanism to alert
- Time App takes to make a call & get a response
- Create a special user for making webservices Calls
- Mechanism to alert when User ID/Keys are about to expire
- Developer Tools
  - Firebug (<a href="http://getfirebug.com/">http://getfirebug.com/</a>)
  - Live HTTP Header (Firefox, Chrome)
  - Web Developer (Firefox, Chrome)



- https://community.brightspace.com/s/topic/ 0TO610000000JdlGAE/api
- https://stackoverflow.com/questions/tagged/valence
- http://docs.valence.desire2learn.com/reference.html
- http://docs.valence.desire2learn.com/http-routingtable.html
- http://docs.valence.desire2learn.com/clients/index.html
- https://apitesttool.desire2learnvalence.com/



## Common Mistakes & Errors




## Common Mistakes

- Incorrect Action/URL
- Incorrect Host name
- Incorrect Method type, (GET, PUT, POST, DELETE)
- Malformed JSON Data
- Incorrect Server or Client Time
- Invalid Application ID/Key
- Expired User ID/Key
- Insufficient User Permissions
- Application Not Enabled in LMS under Manage Extensibility



# Common Errors:

Response Code	Definition	Cause & Solution
200	Success	All good
302	Redirect	Check App and User ID/Key, Authentication
403	Forbidden	Check Permission
404	Not found	Check OrgUnitID, Action URL
400	Bad Request	Check JSON Format, Action, Method




# Demo



#### Demo: List

- 1. Retrieve Latest & Supported Versions
- 2. Retrieve Org Information
- 3. Retrieve Org Structure
- 4. Retrieve Role List
- 5. Create New User
- 6. Retrieve User Data
- 7. Update User
- 8. Create New Template
- 9. Create Course Offering
- 10. User Enrollment in Course

http://127.0.0.1/rockeagle/php/samples/GettingStartedSample/demo.php



#### Demo 1: Retrieve Versions

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Method:

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/versions/

GET



### Demo 1: Response

```
"ProductCode": "le",
        "LatestVersion": "1.4",
        "SupportedVersions": [
            "1.0",
            "1.1",
            "1.2",
            "1.3",
            "1.4"
    },
        "ProductCode": "lp",
        "LatestVersion": "1.4",
        "SupportedVersions": [
            "1.0",
            "1.1",
            "1.2",
            "1.3",
            "1.4"
    },
{
        "ProductCode": "lti",
        "LatestVersion": "1.1",
        "SupportedVersions": [
            "1.1"
]
```



# Demo 2: Retrieve Org Info.

- Host Name:
- · Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/organization/info

1.0

/d2l/api/lp/1.0/organization/info

GET



# Demo 2: Response

```
{
    "Identifier": "6624",
    "Name": "Georgia Online Virtual Instruction Enterprise Wide"
}
```



# Demo 3: Retrieve Org Structure

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/orgstructure/ (orgUnitId)/children/

1.0

/d2l/api/lp/1.0/orgstructure/6624/children/

GET



# Demo 3: Response

```
"Identifier": "6986",
    "Name": "ITS",
    "Code": "ITStest",
    "Type": {
        "Id": 119,
        "Code": "Department",
        "Name": "Department"
},
    "Identifier": "7226",
    "Name": "CPS Testing",
    "Code": "cpstest",
    "Type": {
        "Id": 5,
        "Code": "Semester",
        "Name": "Semester"
```



#### Demo 4: Retrieve Role List

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/roles/

1.0

/d2l/api/lp/1.0/roles/

GET



### Demo 4: Response

```
"Identifier": "156",
    "DisplayName": "Instructor",
    "Code": "Instructor"
},
    "Identifier": "157",
    "DisplayName": "Student",
    "Code": "Student"
},
    "Identifier": "240",
    "DisplayName": "Demo Student",
    "Code": null
},
    "Identifier": "481",
    "DisplayName": "Tutor",
    "Code": null
},
    "Identifier": "483",
    "DisplayName": "Teaching Assistant",
    "Code": null
```



#### Demo 5: Create New User

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- · Method:
- JSON Data

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/users/

1.0

/d2l/api/lp/1.0/users/

POST



#### Demo 5: Create New User

```
"OrgDefinedId": <string>,
    "FirstName": <string>,
    "MiddleName": <string>,
    "LastName": <string>,
    "ExternalEmail": <string> | null,
    "UserName": <string>,
    "RoleId": <number>,
    "IsActive": <boolean>,
    "SendCreationEmail": <boolean>
}
```

```
"OrgDefinedId": "rockeagle",
   "FirstName": "Rock",
   "MiddleName": "",
   "LastName": "Eagle",
   "ExternalEmail": "mazhar.malik@usg.edu",
   "UserName": "rockeagle",
   "RoleId": "157",
   "IsActive": "true",
   "SendCreationEmail": "false"
}
```




### Demo 5: Response

```
"OrgId": 6624,
"UserId": 469948,
"FirstName": "Rock",
"MiddleName": "",
"LastName": "Eagle",
"UserName": "rockeagle",
"ExternalEmail": "mazhar.malik@usg.edu",
"OrgDefinedId": "rockeagle",
"UniqueIdentifier": "rockeagle",
"Activation": {
    "IsActive": true
"DisplayName": "Rock Eagle"
```



#### Demo 5: Result in LMS





#### Demo 6: Retrieve User

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/users/ (userld)

1.0


/d2l/api/lp/1.0/users/469948

GET



### Demo 6: Response

```
"OrgId": 6624,
"UserId": 469948,
"FirstName": "Rock",
"MiddleName": "",
"LastName": "Eagle",
"UserName": "rockeagle",
"ExternalEmail": "mazhar.malik@usg.edu",
"OrgDefinedId": "rockeagle",
"UniqueIdentifier": "rockeagle",
"Activation": {
    "IsActive": true
"DisplayName": "Rock Eagle"
```



### Demo 7: Update User

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:
- JSON Data

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/users/(userld)

1.0

/d2l/api/lp/1.0/users/469948

PUT



### Demo 7: Update User

```
"OrgDefinedId": <string>,
    "FirstName": <string>,
    "MiddleName": <string>,
    "LastName": <string>,
    "ExternalEmail": <string>,
    "UserName": <string>,
    "Activation": { <composite:User.UserActivationData> }
}
```

```
{
   "OrgDefinedId": "rockeagle",
   "FirstName": "Rock",
   "MiddleName": "",
   "LastName": "Eagle",
   "ExternalEmail": "rock.eagle@usg.edu",
   "UserName": "rockeagle",
        "Activation": {
            "IsActive": true
        }
}
```




### Demo 7: Response

```
"OrgId": 6624,
"UserId": 469948,
"FirstName": "Rock",
"MiddleName": "",
"LastName": "Eagle",
"UserName": "rockeagle",
"ExternalEmail": "rock.eagle@usg.edu",
"OrgDefinedId": "rockeagle",
"UniqueIdentifier": "rockeagle",
"Activation": {
    "IsActive": true
},
"DisplayName": "Rock Eagle"
}
```



#### Demo 7: Result in LMS





### Demo 8: Create Template

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:
- JSON Data

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/coursetemplates/

1.0

/d2l/api/lp/1.0/coursetemplates/

POST



### Demo 8: Create Template

```
"Name": <string>,
    "Code": <string>,
    "Path": <string>,
    "ParentOrgUnitIds": [ <number:D2LID>, ... ]
```

```
{
"Name": "Rock Eagle Template",
"Code": "template.rockeagle",
"Path": "",
"ParentOrgUnitIds": ["6986"]
}
```



# Demo 8: Response

```
"Identifier": "508797",
    "Code": "template.rockeagle",
    "Name": "Rock Eagle Template",
    "Path": "/content/enforced/508797-template.rockeagle/"
}
```



#### Demo 8: Result in LMS

	Offerings	Templates		
Find Cou	rse Templates			
The following fields will be searched: Templat Template Path	e Code, Template Name, Department, and	d		
Search For: rock	earch			
Paging: Show 25 courses per pa	ge			
	Displaying Results 1 to	1 of 1		
Delete Selected				
Template Code	Template Name_▲	Department	Creation Date	
template.rockeagle	Rock Eagle Template	ITS	Oct 20, 2015 8:15 AM	Ù
		·		
				_
Back Back				



### Demo 9: Create Course Offering

- Host Name:
- · Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:
- JSON Data

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/courses/

1.0

/d2l/api/lp/1.0/courses/

POST



# Demo 9: Create Course Offering

```
"Name": <string>,
    "Code": <string>,
    "Path": <string>,
    "CourseTemplateId": <number:D2LID>,
    "SemesterId": <number:D2LID> | null,
    "StartDate": <string:UTCDateTime> | null,
    "EndDate": <string:UTCDateTime> | null,
    "LocaleId": <number:D2LID> | null,
    "ForceLocale": <boolean>,
    "ShowAddressBook": <boolean>,
```

```
"Name": "Rock Eagle 2015",
    "Code": "CO.rockeagle",
    "Path": "",
    "CourseTemplateId": "508797",
    "SemesterId": null,
    "StartDate": null,
    "EndDate": null,
    "LocaleId": null,
    "ForceLocale": false,
    "ShowAddressBook": false
}
```



### Demo 9: Response

```
"Identifier": "508798",
"Name": "Rock Eagle 2015",
"Code": "CO.rockeagle",
"IsActive": true,
"Path": "/content/enforced/508798-CO.rockeagle/",
"StartDate": null,
"EndDate": null,
"CourseTemplate": {
    "Identifier": "508797",
    "Name": "Rock Eagle Template",
    "Code": "template.rockeagle"
},
"Semester": null,
"Department": {
    "Identifier": "6986",
    "Name": "ITS",
    "Code": "ITStest"
```



### Demo 9: Result in LMS

Find Course Offerings  The following fields will be searched: Offering Code, Offering Name, Department, and Offering Path  Search For: rock Search  Paging: Show 25 courses per page  Search Options  Only courses available after October 20 2015 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			
Search For: rock Search Paging: Show 25 courses per page  Search Options  Only courses available after October 0 20 0 2015 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			
Paging: Show 25 courses per page  Search Options  Only courses available after October 0 20 0 2015 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0			
Search Options  Only courses available after October © 20 © 2015 ©  Only courses available before October © 27 © 2015 ©  With this user Administrator ©  Displaying Results 1 to 1 of 1			
Only courses available after October © 20 © 2015 ©  Only courses available before October © 27 © 2015 ©  With this user Administrator ©  Displaying Results 1 to 1 of 1			
October © 20 © 2015 © III Only courses available before October © 27 © 2015 © III With this user Administrator © Displaying Results 1 to 1 of 1			
Only courses available before October © 27 © 2015 ©  With this user Administrator ©  Displaying Results 1 to 1 of 1			
□ With this user Administrator  □ Displaying Results 1 to 1 of 1			
Displaying Results 1 to 1 of 1			
Offering Code Offering Name▲	Department	Creation Date	
CO.rockeagle Rock Eagle 2015		Oct 20, 2015 8:23 AM	Ĥ
Back			



#### Demo 10: User Enrollment

- Host Name:
- Port:
- Application ID:
- Application Key:
- User ID:
- User Key:
- Action/URL (ref):
- Learning Platform:
- Action/URL:
- Method:
- JSON Data

goqaview.usg.edu

443

\*\*\*\*\*\*

\*\*\*\*\*\*

uNg-v0qO5TR4yrbk0FqpoR

wblLFBSIeKvxB3Twt-zxCY

/d2l/api/lp/(version)/enrollments/

1.0

/d2l/api/lp/1.0/enrollments/

POST



#### Demo 10: User Enrollment

```
"OrgUnitId": <number:D2LID>,

"UserId": <number:D2LID>,

"RoleId": <number:D2LID>
}
```

```
{
    "OrgUnitId": "508798",
    "UserId": "469948",
    "RoleId": "157"
}
```




# Demo 10: Response

```
{
    "OrgUnitId": 508798,
    "UserId": 469948,
    "RoleId": 157,
    "IsCascading": false
}
```



#### Demo 10: Result in LMS





Questions / Comments

mazhar.malik@usg.edu

https://github.com/usg-mmalik/RockEagle2017.git