

# OrdexAxe Third Party Client Rest Api Design

# General Formats

## 1. Base Url

- **Sandbox** : <https://sandbox.rst-api.orderaxe.com> (<https://sandbox.rst-api.orderaxe.com>)
- **Live** : <https://rst-api.ordexaxe.com> (<https://rst-api.ordexaxe.com>)

## 2. Request Formats

- o Request Body : JSON String
- o Headers : Authorization [Bearer JWT Token] ,Content-Type [application/json;charset=UTF-8]
- o Methods :
  - **GET** : Used for fetching records.
  - **POST** : Used for updating records.
  - **PUT** : Used for creating records.

### 3. Resonse Formats

- o Reponse Type : Plain JSON text.
- o Headers : Content-Type [application/json;charset=UTF-8]
- o Codes :
  - **200 : OK** Denotes successfull operation.
  - **201 : Failed** Denotes failed operation.
  - **400 : Bad Request** Parameters are invalid or incomplete.
  - **404 : Resource not found** Not a valid resource path.
  - **401 : Unauthorized** Authorization not provided.
  - **403 : Forbidden** Authorization not valid/Expired.
  - **405 : Method not allowed** Http method not supported for accessed resource.

#### 4. Client Authentication

- o JWT token issued by Valid ClientId and Signed by corresponding Client Sec.

## Resources

## Generate JWT

- New JWT token :

- Request :

```
POST {{URL}}/script/generateJwt
Content-Type: application/json
Body:
{
  "clientId":"t-t-limited-74771ac3-a477-4338-8cdb-7ffd3d567236",
  "clientSecret":"d8a2c9e51eda62c39b3b774449b62f855ce18697d5a98ed198c1d7918f8fae17"
}
```

- Reponse :

```

...
HTTP/1.1 200 OK
Content-Type: application/json
Body: {
  "token": "Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpc3MiOiJ0LXQtbGltaxR1ZC03NDc3MWFjMy1hNdc3LTQzMzgtOGNkYi03ZmZl
}
...

```

- Notes : The clientId & clientSecret will be provided by Order Axe This token validity is life time. You can generate another token, if you want.

## Distributors

- **New Distributors Sync :**

- Request :

```
PUT {{URL}}/tpc/v1/distributors
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "data":[ // Maximum of 500 records
    {
      "id" : <ClientDataObjId>, // Required
      "name":"Distributor 1", // Required
      "email":"dist1@test.com",
      "phone":"91-9876543210",
      "address":{
        "address_line1": "Address 1",
        "address_line2": "Address 2",
        "address_line3": "Address 3", // Merge address_line3 with address_line2 in DB
        "city": "City",
        "state": "State",
        "country": "India",
        "zip": "zip_code",
      }
    },...
  ]
}
```

- **Reponse :**

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status":"success/partial_success/failed",
  "message":"All Records Inserted/Invalid Client Id/ Some of data objects already exists"
  "failed_insert_ids" : [<ClientDataObjId1>,<ClientDataObjId2>,..]
}
```

- **Distributors Updates Sync :**

- Request :

```

POST {{URL}}/tpc/v1/distributors
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "data":[ // Maximum of 500 records
    {
      "id" : <ClientDataObjId>, // Required
      "name":"Distributor 1", // Required
      "email":"dist1@test.com",
      "address":{
        "address_line1": "Address 1",
        "address_line2": "Address 2",
        "address_line3": "Address 3", // Merge address_line3 with address_line2 in DB
        "city": "City",
        "state": "State",
        "country": "India",
        "zip": "zip_code",
      }
    },...
  ]
}

```

◦ **Reponse :**

```

HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status":"success/failed",
  "message":"All Records Updated/Invalid Client Id/ Some of data objects not exists"
  "failed_update_ids" : [<ClientDataObjId1>,<ClientDataObjId2>,...]
}

```

- **Notes :** Our sales team will activate distributors. After activation you will able to add retailers.

## Retailers

• **New Retailers Sync :**

◦ **Request :**

```

...
PUT {{URL}}/tpc/v1/retailers
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "data":[    // Maximum of 500 records
    {
      "id" : <ClientDataObjId>,    // Required
      "name":"Retailer 1",        // Required
      "email":"Retailer@test.com",
      "phone":"91-9876543210",
      "address":{
        "address_line1": "Address 1",
        "address_line2": "Address 2",
        "address_line3": "Address 3",    // Merge address_line3 with address_line2 in DB
        "city": "City",
        "state": "State",
        "country": "India",
        "zip": "zip_code",
      },
      "distributor_id" : <ClientDataObjId>,
    },...
  ]
}
...

```

■ Reponse :

```

HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status":"success/partial_success/failed",
  "message":"All Records Inserted/Invalid Client Id/ Some of data objects already exists/Some of distributor data ob
  "failed_insert_ids" : [<ClientDataObjId1>,<ClientDataObjId2>,...]
}

```

• Retailers Updates Sync :

◦ Request :

```

POST {{URL}}/tpc/v1/retailers
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "data":[ // Maximum of 500 records
    {
      "id" : <ClientDataObjId>, // Required
      "name":"Retailer 1", // Required
      "email":"Retailer@test.com",
      "phone":"91-9876543210",
      "address":{
        "address_line1": "Address 1",
        "address_line2": "Address 2",
        "address_line3": "Address 3", // Merge address_line3 with address_line2 in DB
        "city": "City",
        "state": "State",
        "country": "India",
        "zip": "zip_code",
      },
      "distributor_id" : <ClientDataObjId>,
    },...
  ]
}

```

◦ Reponse :

```

HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status":"success/partial_success/failed",
  "message":"All Records Updated/Invalid Client Id/ Some of data objects not exists/Some of distributor data objects not exists",
  "failed_update_ids" : [<ClientDataObjId1>,<ClientDataObjId2>,...]
}

```

## Products && Variants Add

- **Add Product With Variations :**

◦ Request :

```

POST {{URL}}/tpc/v1/products
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "third_party_obj_id": "994",
  "name": "Product Name 03",
  "short_description": "Product Desc 03",
  "sku": "ProductDesc03",
  "wsp": 999,
  "description": [
    {
      "key": "Title 1",
      "value": "CM1"
    },
    ...
  ],
  "variations": [
    {
      "third_party_obj_id": "999",
      "barcode": "QWERY1234567890",
      "size": "XL",
      "color": "GREEN",
      "fit": "STANDARD",
      "mrp": 123,
      "wsp": 123,
      "quantity": 50,
      "trashed": true
    },
    ...
  ]
}

```

◦ Reponse :

```

HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "product": {
    "_id": "6410f3cab32df507eec6b5a3",
    "third_party_obj_id": "994"
  },
  "variations": [
    {
      "_id": "6410f3cab32df507eec6b5a5",
      "third_party_obj_id": "999"
    },
    {
      "_id": "6410f3cab32df507eec6b5a6",
      "third_party_obj_id": "998"
    }
  ]
}

```

• Add Product without Variations :

◦ Request :

```
POST {{URL}}/tpc/v1/products
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "third_party_obj_id": "994",
  "name": "Product Name 03",
  "short_description": "Product Desc 03",
  "sku": "ProductDesc03",
  "wsp": 999,
  "description": [
    {
      "key": "Title 1",
      "value": "CM1"
    },
    ...
  ],
  "has_variation": false
}
```

◦ Reponse :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "variations": [
    {
      "_id": "6410f3cab32df507eec6b5a5",
      "third_party_obj_id": "999"
    },
    {
      "_id": "6410f3cab32df507eec6b5a6",
      "third_party_obj_id": "998"
    }
  ]
}
```

• Add Product Variations :

◦ Request :

```
PUT {{URL}}/tpc/v1/products/{{productId}}/variations
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "variations": [
    {
      "third_party_obj_id": "999",
      "barcode": "QWERY1234567890",
      "size": "XL",
      "color": "GREEN",
      "fit": "STANDARD",
      "mrp": 123,
      "wsp": 123,
      "quantity": 50,
    },
    ...
  ]
}
```

◦ Reponse :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "variations": [
    {
      "_id": "6410f3cab32df507eec6b5a5",
      "third_party_obj_id": "999"
    },
    {
      "_id": "6410f3cab32df507eec6b5a6",
      "third_party_obj_id": "998"
    }
  ]
}
```

- **Update Product Details :**

- Request :

```
PUT {{URL}}/tpc/v1/products/{{productId}}
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "name": "Polo Mens T-shirt",
  "short_description": "Polo Mens T-shirt",
  "wsp": 999,
  "description": [
    {
      "key": "Title 1",
      "value": "CM1"
    },
    {
      "key": "Title 2",
      "value": "Description 2"
    },
    {
      "key": "Title 3",
      "value": "Description 3"
    }
  ],
  "has_variation": true
}
```

- Reponse :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "message": [ ]
}
```

- **Update Product Variations :**

- Request :



```
PUT {{URL}}/tpc/v1/products/{{productId}}/variations/{{variationId}}
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "barcode": "qasdfg1",
  "size": "XL",
  "color": "WHITE",
  "fit": "LOOSE",
  "mrp": 299,
  "wsp": 199,
  "quantity": 50
}
```

◦ Reponse :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "message": [ ]
}
```

◦ Notes :

For updating inventory you can send only quantity.

• **Update Product Status :**

◦ Request :

```
DELETE {{URL}}/tpc/v1/products/{{productId}}
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "status": "active"
}
```

◦ Reponse :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "message": [ ]
}
```

• **Update Product Variations Status/Delete :**

◦ Request :

```
DELETE {{URL}}/tpc/v1/products/{{productId}}/variations/{{variationId}}
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "status": "active"
}
```

◦ Reponse :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
  "message": [ ]
}
```

## Orders

- **Fetch Order Reports :**

- Request :

```
...
GET {{URL}}/tpc/v1/orders?timestamp=0
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
```

- Reponse :

```
...
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "success/failed",
  "data": [ ]
}
...
```

- Notes timestamp=0 will give you orders from the start. After syncing you have to save max submitted\_on date to get next orders.

## Retailers

- **Update Retailer Id in Order Axe :**

- Request :

```
PUT {{URL}}/tpc/v1/retailers/{{64affc03405e01469757f1f8}} (order axe retailer id)
Authorization: Bearer <jwt_auth_token>
Content-Type: application/json
Body:
{
  "third_party_obj_id": "994" (third party customer exp id)
}
```

- Reponse Success :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Success",
}
```

- Reponse Failure :

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Failure",
  "message": "Invalid retailer Id"
}
```

- **Reponse Failure :**

```
HTTP/1.1 200 OK
Content-Type: application/json
Body:
{
  "status": "Failure",
  "message": "Client Id already exist"
}
```

- **Notes :**

In case of retailer added from order axe platform. You have to send order axe Retailer Id (you will get this in order response )