

Booking Links & Embedding Guide

How to deep-link and embed the online booking widget on easydriving.ca using URL query strings.

Booking origin: <https://booking.easydriving.ca/book> · Updated June 2026

1. The basics

The public booking page lives at `/book` on the booking domain. Its starting state is controlled entirely through **URL query-string parameters** — no code changes are needed to point a button or link at a specific location, service, package, language, or tab.

Parameters can be combined freely with `&`. Anything you don't set falls back to a sensible default (English, the location picker, the Services tab).

2. Parameter reference

Parameter	Values	What it does	Default
<code>center</code>	a location slug <code>laval</code> , <code>kirkland</code> , <code>henri-bourassa</code>	Preselects the location and opens directly on the service/package picker.	Show the location picker
<code>service</code>	a service slug e.g. <code>driving-lesson</code>	Preselects a single service and jumps straight to choosing a date & time.	—
<code>package</code> NEW	a package slug e.g. <code>road-test-prep</code>	Opens directly in the multi-session package booking flow. Takes precedence over <code>service</code> if both are present.	—
<code>tab</code> NEW	<code>packages</code>	Opens the picker on the Packages tab instead of Services. (The tab bar only appears when the chosen location actually offers packages.)	<code>services</code>
<code>lang</code>	<code>fr</code> / <code>en</code>	Sets the interface language.	<code>en</code>
<code>embed</code>	<code>1</code>	Hides the page header/site chrome — use this when loading the page inside an iframe.	Full page

Slugs. The exact `center`, `service` and `package` slugs come from the Admin Portal (each item's URL slug). The examples below use the seeded demo slugs; confirm production slugs before publishing links.

3. Scenarios

A · Link to the whole booking page

When: a generic "Book online" button. The customer picks location → service themselves.

```
<!-- starts on the location picker, English, Services tab -->  
https://booking.easydriving.ca/book
```

B • Preselect a location

When: a page that is specific to one branch (e.g. the Laval location page).

```
/book?center=laval
```

C • Jump straight to one service

When: a "Book a driving lesson" call-to-action. Goes right to date & time.

```
/book?center=laval&service=driving-lesson
```

D • Jump straight into a package NEW

When: promoting a bundle such as the Road Test Prep package. Opens the multi-session flow.

```
/book?center=laval&package=road-test-prep
```

E • Open the picker on the Packages tab NEW

When: you want customers to browse packages first, but still choose which one.

```
<!-- location preselected, picker opens on the Packages tab -->  
/book?center=kirkland&tab=packages
```

F • French deep link

When: linking from a French page. Add `lang=fr` to any of the above.

```
/book?center=laval&service=road-test-package&lang=fr  
/book?center=laval&package=road-test-prep&lang=fr&tab=packages
```

4. Ready-to-paste link examples

Goal	URL (append to https://booking.easydriving.ca)
Book — Laval, road test package	<code>/book?center=laval&service=road-test-package</code>
Book — Kirkland, car rental	<code>/book?center=kirkland&service=car-rental</code>
Book — Henri-Bourassa, driving lesson	<code>/book?center=henri-bourassa&service=driving-lesson</code>
Book — Road Test Prep package NEW	<code>/book?center=laval&package=road-test-prep</code>
Browse packages at Laval NEW	<code>/book?center=laval&tab=packages</code>
French · Laval road test package	<code>/book?center=laval&service=road-test-package&lang=fr</code>

As an HTML button/link

```
<a href="https://booking.easydriving.ca/book?center=laval&package=road-test-prep">
  Book the SAAQ Road Test Prep package
</a>
```

5. Embedding with an iframe

To embed the widget inside a page on easydriving.ca, add `embed=1` (hides the header) and combine it with any of the parameters above. The Pages content-security policy already allows framing by `https://easydriving.ca`, `https://www.easydriving.ca`, and the booking origin itself.

Example — embed the Packages tab for one location

```
<iframe
  src="https://booking.easydriving.ca/book?center=laval&tab=packages&embed=1"
  title="Easy Driving booking"
  style="width:100%;min-height:850px;border:0"
  loading="lazy">
</iframe>
```

Example — embed a single service, in French

```
<iframe
  src="https://booking.easydriving.ca/book?center=kirkland&service=car-rental&lang=fr&embed=1"
  title="Réservation Easy Driving"
  style="width:100%;min-height:850px;border:0"
  loading="lazy">
</iframe>
```

Before launch: test the iframe height on mobile, keyboard behaviour on form fields, and scrolling. Increase `min-height` if the package flow (which is taller) gets clipped.

6. Precedence & behaviour notes

- `package` wins over `service`. If both are supplied, the package flow opens.
- `tab=packages` is only honoured when packages exist for the selected location; otherwise the page shows Services (the tab bar is hidden).
- Switching tabs updates the URL in the browser, so the customer can copy/share the link they're looking at.
- Defaults: no `lang` → English; no `tab` → Services; no `center` → the location picker.
- Order doesn't matter — `?service=x¢er=y` is the same as `?center=y&service=x`.