

Lab # 5: More Control Statements

EC-102 – Computer Systems and Programming

Usman Ayub Sheikh


School of Mechanical and Manufacturing Engineering (SMME),
National University of Sciences and Technology (NUST)

October 2, 2015

- 1 More Decision Statements
 - The `switch` Statement
 - The `break` Statement
- 2 Solved Example
- 3 Exercise

The switch Statement - Introduction

- Large decision tree
- All the decisions depend on the value of the same variable
- May be used instead of nested if...else statement



© <http://www.tipsntracks.com>

The switch Statement - Syntax

```
1 switch(n)
2 {
3     case 1:
4         statement 1;
5         statement 2;
6         break;
7
8     case 2:
9         statement 1;
10        statement 2;
11        break;
12
13    case 3:
14        statement;
15        break;
16
17    default:
18        statement;
19 }
```

- The keyword `switch` is followed by a switch variable in parentheses (Line 1)
- Braces are used to delimit all case statements
- Each case keyword is followed by a constant which is not in parentheses but is followed by a colon (Lines 3, 8 and 13)
- The data type of the case constants should match that of the switch variable
- `default` keyword gives the switch construction a way to take an action if the value of the variable does not match any of the case constants (Line 17)

The break Statement


- Causes the entire `switch` statement to exit
- Control goes to the first statement following the end of the `switch` construction

Solved Example

Algorithm

- 1 Start
- 2 Declare variable grade
- 3 Read value of grade
- 4 If grade is 'A' then display 'Excellent!'
- 5 Else if grade is 'B' or 'C' then display 'Well done'
- 6 Else if grade is 'D' then display 'You passed'
- 7 Else if grade is 'F' then display 'Better try again'
- 8 Else display 'Invalid grade'
- 9 Stop

Flowchart



Solved Example

```
1 #include <iostream>
2 using namespace std;
3
4 int main ()
5 {
6     char grade;
7     cout << "Enter a grade (eg. A, B etc): ";
8     cin >> grade;
9     switch(grade)
10    {
11        case 'A' :
12            cout << "Excellent!" << endl;
13            break;
14        case 'B' :
15        case 'C' :
16            cout << "Well done" << endl;
17            break;
18        case 'D' :
19            cout << "You passed" << endl;
20            break;
```

Solved Example

```
21     case 'F' :  
22         cout << "Better try again" << endl;  
23         break;  
24     default :  
25         cout << "Invalid grade" << endl;  
26     }  
27     return 0;  
28 }
```


Exercise

Develop a basic calculator using `switch` statement which is capable of performing addition, subtraction, multiplication and division

- Ask the user to enter two numbers and the type of arithmetic operation to be performed
- Use `char` data type for the variable handling the operator