
Appendix A

Practices and Solutions

Usman Qamar (usman.qamar@live.com) has a non-transferable
license to use this Student Guide.

Table of Contents

Practices for Lesson 1	4
Practice 1-2: Reviewing the Database Architecture	5
Practices for Lesson 2	6
Practice 2-1: Configuring ARCHIVELOG Mode	6
Practice 2-2: Resizing the Flash Recovery Area.....	8
Practice 2-3: Verifying the Backup Destination	12
Practice 2-4: Configuring the Retention Policy	15
Practices for Lesson 3	16
Practice 3-1: Creating a Recovery Catalog	16
Practice 3-2: Creating the Recovery Catalog Owner.....	24
Practice 3-3: Creating the Recovery Catalog.....	25
Practice 3-4: Registering a Database in the Recovery Catalog.....	26
Practice 3-5: Backing up the Recovery Catalog	29
Practices for Lesson 4	33
Practice 4-1: Setting the Date and Time Format for RMAN.....	33
Practice 4-2: Enabling Control File Autobackup.....	35
Practice 4-3: Configuring Devices for Backup	37
Practices for Lesson 5	39
Practice 5-1: Creating Fast Incremental Backups.....	39
Practice 5-2: Cross-Checking Backups.....	42
Practice 5-3: Listing Backup Files and Creating Archival Backup	47
Practices for Lesson 6	58
Practice 6-1: Backing up the Database	58
Practice 6-2: Recovering from the Loss of a Data File.....	61
Practice 6-3: Recovering from the Loss of all Control Files	66
Practice 6-4: Recovering from the Loss of a Redo Log Group	71
Practices for Lesson 7	75
Practice 7-1: Recovering Image Copies.....	75
Practice 7-2: Performing Fast Recovery	83
Practices for Lesson 8	90
Practice 8-1: Monitoring RMAN Jobs	90
Practices for Lesson 9	93
Practice 9-1: Diagnostic Scenario	94
Practice 9-2: Repairing Block Corruption	109
Practices for Lesson 10	116
Practice 10-1: Flashback Transaction Backout.....	117
Practices for Lesson 11	118
Practice 11-1: Using Flashback Data Archive	119
Practice 11-2: Using the Recycle Bin	133
Practices for Lesson 12	138
Practice 12-1: Flashback Database	139
Practices for Lesson 13	146
Practice 13-1: Using Automatic Memory Management	147
Practices for Lesson 14	166

Practice 14-1: Monitoring Services	166
Practices for Lesson 15	174
Practice 15-1: Using Automatic SQL Tuning.....	175
Practices for Lesson 16	195
Practice 16-1: Managing Resources.....	196
Practices for Lesson 17	213
Practice 17-1: Creating Scheduler Components	214
Practice 17-2: Creating Lightweight Scheduler Jobs.....	227
Practice 17-3: Monitoring the Scheduler	232
Practices for Lesson 18	240
Practice 18-1: Managing Storage.....	241
Practices for Lesson 19	259
Practice 19-1: Managing Space for the Database	260
Practices for Lesson 20	261
Practice 20-1: Duplicating a Database.....	262

Practices for Lesson 1

The paper practices for this lesson are embedded in the lesson itself, to facilitate reviewing the database architecture for yourself and in class. Below are possible answers.

Practice 1-1: Reviewing the Database Architecture

For page 1-3: **Naming the Core Components of an Oracle Database Server**

- 1) The two main components of a basic Oracle Database system: instance and database.
- 2) The Instance consists of memory structures and background processes.
- 3) The three major structures in Oracle Database server architecture are: memory structures, process structures and storage structures.
- 4) A session is a connection between the user login and the database instance.
- 5) The graphic on slide 1-4 is the answer to the task on slide 1-3

For page 1-7: **Naming the Memory Structures of an Oracle Database**

- 1) Which are the components of the PGA: stack space and user global area.
- 2) Name the main components of the SGA:
 - Shared pool
 - Database buffer cache
 - Redo log buffer
 - Large pool
 - Java pool
 - Streams pool
 - Keep buffer pool
 - Recycle buffer pool
 - nK buffer pool
- 3) The graphic on slide 1-8 is the answer to the task on slide 1-7.

For page 1-14: **Adding Process Names**

- 1) The DBWn process writes the dirty buffers to the data files.
- 2) The LGWR process writes the redo entries to the online redo log files.
- 3) The CKPT process writes checkpoint information in the control file and each data file header.
- 4) The SMON process performs recovery on instance startup.
- 5) The PMON process performs process recovery when a user process fails.
- 6) The RECO process resolves in-doubt distributed transactions.
- 7) The ARCn processes copy redo log files to a designated storage device.

Practices for Lesson 2

General Practice Note: To reduce clutter in the output, product banners, space lines and other repeating information is only shown when they first appear. Later, they are removed to not distract from the essence of a practice.

Practice 2-1: Configuring ARCHIVELOG Mode

In this practice, you configure your database to archive redo logs before reusing them.

- 1) Set up the environment for the ORCL database, using the oraenv script, and enter `orcl` when prompted for `ORACLE_SID`. If it is already set up for `orcl` (that is, you see `orcl` in the brackets), press Enter.

Note: This command is a period, followed by a space, and then the oraenv script name.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1 is
/u01/app/oracle
```

- 2) Use `labs` as your working directory. Unless otherwise indicated, always work from that directory.

```
$ cd ~/labs
```

- 3) Determine the archive mode your database is running in now.

```
$ sqlplus / as sysdba
SQL*Plus: Release 11.2.0.1.0 Production on Tue Jul 21 14:32:29
2009

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -
Production
With the Partitioning, Automatic Storage Management, OLAP,
Data Mining and Real Application Testing options

SQL> archive log list
Database log mode No Archive Mode
Automatic archival Disabled
Archive destination USE_DB_RECOVERY_FILE_DEST
Oldest online log sequence 6
Current log sequence 8
SQL>
```

Note that it is running in NOARCHIVELOG mode.

Practice 2-1: Configuring ARCHIVELOG Mode (continued)

- 4) Because you can change the ARCHIVELOG mode only when the database is mounted, shut down the database.

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

- 5) Mount the database.

```
SQL> startup mount
ORACLE instance started.

Total System Global Area  481259520 bytes
Fixed Size                  1337324 bytes
Variable Size              339740692 bytes
Database Buffers           134217728 bytes
Redo Buffers                5963776 bytes
Database mounted.
SQL>
```

- 6) Alter the database to use ARCHIVELOG mode.

```
SQL> alter database archivelog;

Database altered.

SQL>
```

- 7) Open the database.

```
SQL> alter database open;

Database altered.

SQL>
```

Practice 2-2: Resizing the Flash Recovery Area

In this practice, you enlarge the Flash Recovery Area.

- 1) Determine how big the Flash Recovery Area is now.

```
SQL> show parameter recovery_file_dest_size
```

NAME	TYPE	VALUE
db_recovery_file_dest_size	big integer	4062M

```
SQL>
```

Note that it is 4062 MB or 4 GB in size.

- 2) How big *could* the Flash Recovery Area be?
 - a) Determine where the Flash Recovery Area is located.

```
SQL> show parameter recovery_file_dest
```

NAME	TYPE	VALUE
db_recovery_file_dest	string	+FRA
db_recovery_file_dest_size	big integer	4062

```
SQL>
```

Note that the Flash Recovery Area is in the FRA disk group.

Do not exit from your SQL*Plus session.


- 3) Use the `https://<hostname>:1158/em` URL to log into Enterprise Manager, as the SYS user with the `oracle_4U` password, and connect as SYSDBA.

Note: The first time that you are using a newly configured machine, you may be asked to add a security exception. The exact formulation and number of pages depends on your web browser. Follow the prompts and add the exception in the training environment.

Note 2: Also if Enterprise Manager shows, that the database is down, wait a minute and refresh the page. (This can occur due to the time intervals in which the database agent works.)

- 4) On the database home page, click the `+ASM_<hostname>` link.

Practice 2-2: Resizing the Flash Recovery Area (continued)



The screenshot shows the 'General' tab of the Oracle Enterprise Manager interface. At the top, there is a green upward-pointing arrow and two buttons: 'Shutdown' and 'Black Out'. Below these, the instance status is 'Up'. The 'Up Since' time is 'Jul 8, 2009 9:07:20 PM GMT+07:00'. The 'Instance Name' is 'orcl', the 'Version' is '11.2.0.1.0', the 'Host' is 'edrsr37p1.us.oracle.com', the 'Listener' is 'LISTENER_edrsr37p1.us.orac...', and the 'ASM' is '+ASM_edrsr37p1.us.oracle.com'. A 'View All Properties' link is at the bottom right.

General

Shutdown Black Out

Status **Up**

Up Since **Jul 8, 2009 9:07:20 PM GMT+07:00**

Instance Name **orcl**

Version **11.2.0.1.0**

Host **edrsr37p1.us.oracle.com**

Listener **LISTENER_edrsr37p1.us.orac...**

ASM **+ASM_edrsr37p1.us.oracle.com**

[View All Properties](#)

- 5) Click the Disk Groups tab.




The screenshot shows the 'Automatic Storage Management: +ASM_edrsr37p1.us.oracle.com' page. The 'Disk Groups' tab is selected, indicated by a mouse cursor. Other tabs include 'Home', 'Performance', 'Configuration', 'Users', and 'ASM Cluster File System'.

Automatic Storage Management: +ASM_edrsr37p1.us.oracle.com

Home Performance **Disk Groups** Configuration Users ASM Cluster File System

- 6) If prompted for ASM login credentials, enter `sys` as username and `oracle_4U` as password. Connect as `SYSASM`, click “Save as Preferred Credential”, and then click Login.



The screenshot shows the 'Automatic Storage Management Login' dialog box. The 'Username' field contains 'sys', the 'Password' field is masked with dots, the 'Connect String' is 'edrsr37p1.us.oracle.com:1521:+ASM', and the 'Connect As' dropdown is set to 'SYSASM'. The 'Save as Preferred Credential' checkbox is checked. 'Cancel' and 'Login' buttons are at the bottom right.

Automatic Storage Management Login

Username

Password

Connect String

Connect As

☒ Save as Preferred Credential

Cancel Login

- 7) When the disk group list appears, note the Usable Free column for the FRA disk group.

Practice 2-2: Resizing the Flash Recovery Area (continued)

Automatic Storage Management: +ASM_edrsr37p1.us.oracle.com Logged in As SYS / SYSASM

Home Performance **Disk Groups** Configuration Users ASM Cluster File System

Create Mount All Dismount All

Mount Dismount Rebalance Check Delete

Select All | Select None

Select	Name	State	Redundancy	Size (GB)	Used (GB)	Used (%)	Usable Free (GB)	Member Disks
<input type="checkbox"/>	DATA	MOUNTED	NORMAL	9.00	3.50	38.92	2.31	4
<input type="checkbox"/>	FRA	MOUNTED	EXTERN	9.00	0.11	1.25	8.89	4

TIP The usable free space specifies the amount of space that can be safely used for data. A value above zero means that redundancy can be properly restored after a disk failure.

TIP Mount All and Dismount All operation will only mount and dismount the disk groups specified in the Auto Mount Disk Groups parameter.

Note that the FRA disk group has enough usable free space to enlarge the Flash Recovery Area considerably, although your displayed values may be a little different.

8) Change the Flash Recovery Area size to 6 GB.

- Navigate to Database > Availability > Recovery Settings and change the Flash Recovery Area Size to 6 GB.

Flash Recovery

This database is using a flash recovery area. The chart shows space used by each file type that is not reclaimable by Oracle. Performing backups to tertiary storage is one way to make space reclaimable. Usable Flash Recovery Area includes free and reclaimable space.

Flash Recovery Area Location: +FRA

Flash Recovery Area Size: 6 GB

Flash Recovery Area Size must be set when the location is set.

Non-reclaimable Flash Recovery Area (B) 0

Reclaimable Flash Recovery Area (B) 0

Free Flash Recovery Area (GB) 3.97

- Click Show SQL, and note the SQL that will be run. This is important to know because if the Flash Recovery Area is having sizing problems, you may not be able to run Enterprise Manager to change it.

```
ALTER SYSTEM SET db_recovery_file_dest_size = 6442450944 SCOPE=BOTH
```

- Click Return, and then click Apply.

Practice 2-2: Resizing the Flash Recovery Area (continued)

- 9) Verify the size of the Flash Recovery Area by using SQL*Plus. Then exit your SQL*Plus session.

```
SQL> show parameter recovery_file_dest_size
```

NAME	TYPE	VALUE
db_recovery_file_dest_size	big integer	6G

```
SQL> exit
```

```
Disconnected from Oracle Database 11g Enterprise Edition  
Release 11.2.0.1.0 - Production  
With the Partitioning, Automatic Storage Management, OLAP,  
Data Mining  
and Real Application Testing options
```

Practice 2-3: Verifying the Backup Destination

In this practice, you test the backup destination to see where backups are written.

Use the oraenv script to ensure you are still using the orcl instance in your terminal session.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 1) Start RMAN.

```
$ rman target /

Recovery Manager: Release 11.2.0.1.0 - Production on Tue Jul
21 14:52:20 2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All
rights reserved.

connected to target database: ORCL (DBID=1220535480)
RMAN>
```

- 2) See if the control files are automatically backed up.

```
RMAN> show CONTROLFILE AUTOBACKUP;

using target database control file instead of recovery catalog
RMAN configuration parameters for database with db_unique_name
ORCL are:
CONFIGURE CONTROLFILE AUTOBACKUP OFF; # default

RMAN>
```

Note that automatic backup is not enabled.

- 3) Configure RMAN to automatically back up the control file when any backups are done.

```
RMAN> configure controlfile autobackup on;

new RMAN configuration parameters:
CONFIGURE CONTROLFILE AUTOBACKUP ON;
new RMAN configuration parameters are successfully stored

RMAN>
```

- 4) List the database files in your schema, to understand which file you back up in the next task.

```
RMAN> report schema;

Report of database schema for database with db_unique_name
ORCL

List of Permanent Datafiles
```

Practice 2-3: Verifying the Backup Destination (continued)

```
=====
File Size(MB) Tablespace          RB segs Datafile Name
-----
1      680      SYSTEM              YES
+DATA/orcl/datafile/system.256.692754557
2      590      SYSAUX                NO
+DATA/orcl/datafile/sysaux.257.692754559
3      100      UNDOTBS1              YES
+DATA/orcl/datafile/undotbs1.258.692754561
4       5      USERS                  NO
+DATA/orcl/datafile/users.259.692754561
5      100      EXAMPLE                NO
+DATA/orcl/datafile/example.265.692754837

List of Temporary Files
=====
File Size(MB) Tablespace          Maxsize(MB) Tempfile Name
-----
1      28      TEMP                    32767      +DATA/orcl/temp01.dbf

RMAN>
```

Note: If you are not connected to the recovery catalog, the RB segs column contains *** as a value. It contains the YES and NO values when you are connected to the recovery catalog.

5) Which tablespace is stored in file 5?

Answer: The EXAMPLE tablespace

6) Take a backup of data file 5, and note where the backup is written, then exit.

```
RMAN> backup datafile 5;

Starting backup at 21-JUL-09
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=55 device type=DISK
channel ORA_DISK_1: starting full datafile backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
input datafile file number=00005
name=+DATA/orcl/datafile/example.265.692754837
channel ORA_DISK_1: starting piece 1 at 21-JUL-09
channel ORA_DISK_1: finished piece 1 at 21-JUL-09
piece
handle=+FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t14535
8_0.260.692808839 tag=TAG20090721T145358 comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:15
```

Practice 2-3: Verifying the Backup Destination (continued)

```
Finished backup at 21-JUL-09

Starting Control File and SPFILE Autobackup at 21-JUL-09
piece
handle=+FRA/orcl/autobackup/2009_07_21/s_692808854.261.6928088
57 comment=NONE
Finished Control File and SPFILE Autobackup at 21-JUL-09
RMAN>
RMAN> exit
```

Note that the backup file is written to the FRA.

Practice 2-4: Configuring the Retention Policy

In this practice, you change the retention policy for backups.

Note that the default retention policy in Oracle Database 11g Release 2 is already set to redundancy 1. So this practice is for training purposes only.

- 1) Use the oraenv script to ensure that you are still using the ORCL instance in your terminal session.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 2) Return to the RMAN session (or if you closed it, start a new one) and show the current retention policy setting.

```
$ rman target /
RMAN> show retention policy;

RMAN configuration parameters for database with db_unique_name
ORCL are:
CONFIGURE RETENTION POLICY TO REDUNDANCY 1; # default
RMAN>
```

- 3) If your redundancy is 1, go to step 5 and exit. If your redundancy had another value, change it to ensure that one copy of each file is backed up.

```
RMAN> configure retention policy to redundancy 1;

old RMAN configuration parameters:
CONFIGURE RETENTION POLICY TO NONE;
new RMAN configuration parameters:
CONFIGURE RETENTION POLICY TO REDUNDANCY 1;
new RMAN configuration parameters are successfully stored
RMAN>
```

- 4) Check the retention policy setting again.

```
RMAN> show retention policy;

RMAN configuration parameters for database with db_unique_name
ORCL are:
CONFIGURE RETENTION POLICY TO REDUNDANCY 1;
```

- 5) Exit RMAN.

```
RMAN> exit

Recovery Manager complete.
```

Practice 3-1: Creating a Recovery Catalog

In this practice, you create a recovery catalog.

- 1) Use DBCA to start the process of creating a recovery catalog database.

```
$ dbca
```

- 2) On the Welcome page, click Next.
- 3) On the Operations page, select the Create a Database option, and then click Next.
- 4) On the Database Templates page, leave the default of General Purpose or Transaction Processing, and then click Next.
- 5) On the Database Identification page, enter the name of the recovery catalog database. Use **rcat.example.com** as the Global Database Name. Then click Next.

An Oracle database is uniquely identified by a Global Database Name, typically of the form "name.domain".

Global Database Name:

A database is referenced by at least one Oracle instance which is uniquely identified from any other instance on this computer by an Oracle System Identifier (SID).

SID:

- 6) On the Management Options page, deselect the Configure Enterprise Manager option, and then click the Automatic Maintenance Tasks tab.

Enterprise Manager Automatic Maintenance Tasks

☐ Configure Enterprise Manager

☐ Register with Grid Control for centralized management

Management Service:

☒ Configure Database Control for local management

- 7) On the Automatic Maintenance Tasks page, deselect "Enable automatic maintenance tasks" and then click Next.

Practice 3-1: Creating a Recovery Catalog (continued)

Enterprise Manager

Automatic Maintenance Tasks

Oracle Database 11g provides the ability to automatically manage maintenance tasks such as optimizer statistics collection and proactive advisor reports. These tasks are run in a predefined maintenance window and their CPU consumption is throttled to prevent them from interfering with normal user work. The default maintenance windows are 10:00 PM - 2:00 AM on weekdays, and all weekend long. These defaults can be changed using Enterprise Manager at any time.

☐ Enable automatic maintenance tasks

- 8) On the Database Credentials page, select the option Use the Same Administrative Password for All Accounts. Then enter **oracle_4U** in the password fields and click Next.



For security reasons, you must specify passwords for the following user accounts in the new database.

☐ Use Different Administrative Passwords

User Name	Password	Confirm Password
SYS		
SYSTEM		

☒ Use the Same Administrative Password for All Accounts

Password:

Confirm Password:

Cancel


Help

Back

Next


- 9) On the Database File Locations Page, select **Automatic Storage Management (ASM)** as Storage Type. Click Use Common Location for All Database Files and then use the Browse button to select the **+DATA** disk group, and click OK.

Practice 3-1: Creating a Recovery Catalog (continued)




10) Then click Next.

11) On the Recovery Configuration page, select **Specify Flash Recovery Area**, use the Browse button to select the **+FRA** diskgroup (click OK) and ensure that the Flash Recovery Area Size is **4062 M Bytes**. Then click Next.




12) On the Database Content page, confirm that the Sample Schemas option is not selected, and then click Next.

Practice 3-1: Creating a Recovery Catalog (continued)



- 13) On the Initialization Parameter page, set the memory size to **303 MB**, click **Use Automatic Memory Management**, and then click the Character Sets tab.



- 14) Click **Use Unicode (AL32UTF8)** and then click Next.

Practice 3-1: Creating a Recovery Catalog (continued)

Memory Sizing Character Sets Connection Mode

Database Character Set

☐ Use the default

The default character set for this database is based on the language setting of this operating system: WE8MSWIN1252.

☒ Use Unicode (AL32UTF8)

Setting character set to Unicode (AL32UTF8) enables you to store multiple language groups.

☐ Choose from the list of character sets

Database Character Set: AL32UTF8 - Unicode UTF-8 Universal character set

☒ Show recommended character sets only

National Character Set: AL16UTF16 - Unicode UTF-16 Universal character set

Default Language: American

Default Territory: United States

All Initialization Parameters...

Back Next

15) If the Security Settings page appears, keep the defaults, and then click Next.

16) On the Database Storage page, review the configuration, and then click Next.

Database Configuration Assistant, Step 10 of 11 : Database Storage


Storage

- Controlfile
- Datafiles**
- Redo Log Groups

	File Name	File Directory
1	system01....	+DATA/{DB_UNIQUE_NAME}/
2	sysaux01....	+DATA/{DB_UNIQUE_NAME}/
3	undotbs01...	+DATA/{DB_UNIQUE_NAME}/
4	users01.dbf	+DATA/{DB_UNIQUE_NAME}/
5	temp01.dbf	+DATA/{DB_UNIQUE_NAME}/

17) On the Creation Options page, make sure that Create Database is the only option selected, and then click Finish.

Practice 3-1: Creating a Recovery Catalog (continued)



18) Review the Confirmation page, and then click OK to start the database creation process.

Practice 3-1: Creating a Recovery Catalog (continued)

The following operations will be performed:
A database called "rcat" will be created.

Database Details:

Create Database – Summary

Database Configuration Summary

Global Database Name: rcat.example.com
Database Configuration Type: Oracle Restart Enabled Single Instance
SID: rcat
Management Option Type: None
Storage Type: Automatic Storage Management (ASM)
Memory Configuration Type: Automatic Memory Management

Database Configuration Details

Database Components


Component	Selected
Oracle JVM	true
Oracle Text	true
Oracle XML DB	true

Save as an HTML file...


OK Cancel Help

19) The Database Creation Assistant now creates the database.

Practice 3-1: Creating a Recovery Catalog (continued)



20) When the Database Configuration Assistant finishes running, view the final page, and then click Exit.



Practice 3-2: Creating the Recovery Catalog Owner

In this practice, you configure the recovery catalog database with a user ID and appropriate privileges, and register a database.

- 1) Use SQL*Plus to configure the recovery catalog database. Connect to it as SYS to the RCAT database.

```
$ sqlplus sys as sysdba  
Enter password: oracle_4U@rcat    <<<not displayed  
SQL>
```

- 2) Create a tablespace named RCAT to hold the repository data. Make it 15 MB in size.

```
SQL> CREATE TABLESPACE rcat DATAFILE '+DATA/rcat01.dbf' SIZE 15M;  
Tablespace created.  
SQL>
```

- 3) Create a user who will own the recovery catalog data. Name the user RCATOWNER. The default tablespace should be the RCAT tablespace, and the user should have unlimited quota on that tablespace.

```
SQL> CREATE USER rcatowner IDENTIFIED BY "oracle_4U"  
2  DEFAULT TABLESPACE rcat QUOTA unlimited on rcat;  
User created.  
SQL>
```

- 4) Grant the RECOVERY_CATALOG_OWNER role to the RCATOWNER user.

```
SQL> GRANT recovery_catalog_owner to rcatowner;  
Grant succeeded.  
SQL> exit
```


Practice 3-3: Creating the Recovery Catalog

In this practice, you create the recovery catalog inside the recovery catalog database you have prepared.

- 1) Connect to the recovery catalog database using RMAN. Log in as the recovery catalog owner you just created.

```
$ rman catalog rcatowner@rcat

Recovery Manager: Release 11.2.0.1.0 - Production on Fri Jul
10 19:54:04 2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All
rights reserved.

recovery catalog database Password:oracle_4U <<<not displayed
connected to recovery catalog database

RMAN>
```

- 2) Create the recovery catalog. This command may take several minutes to complete.

```
RMAN> create catalog;

recovery catalog created

RMAN> exit
```

Practice 3-4: Registering a Database in the Recovery Catalog

In this practice, you register the ORCL database in the recovery catalog that you have just created.

- 1) Set up the environment for the ORCL database.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 2) Connect to the target database (to be registered) and the recovery catalog database using RMAN.

```
$ rman target / catalog rcatowner@rcat

Recovery Manager: Release 11.2.0.1.0 - Production on Tue Jul
21 15:30:32 2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All
rights reserved.

connected to target database: ORCL (DBID=1220535480)
recovery catalog database Password:oracle_4U <<<not displayed
connected to recovery catalog database

RMAN>
```

- 3) Register the database in the catalog.

```
RMAN> register database;

database registered in recovery catalog
starting full resync of recovery catalog
full resync complete

RMAN> exit
```

- 4) Register the recovery catalog to be used by Enterprise Manager.

- a) In EM, navigate to Availability > Recovery Catalog Settings.
- b) Click Add Recovery Catalog.

☒ Use Control File

Keep RMAN Records (days) Specify how long to keep RMAN records in the control file before they can be reused.

☐ Use Recovery Catalog

Recovery Catalog

- c) Enter the following information, then click Next:

Practice 3-4: Registering a Database in the Recovery Catalog (continued)

Host: <your_hostname>
Port: 1521
SID: rcat
Recovery Catalog Username: rcatowner
Recovery Catalog Password: oracle_4U

Database Instance: orcl.example.com > Recovery Catalogs >

Cancel Next

Add Recovery Catalog: Database

Specify the host, port, and SID of a database with an existing recovery catalog along with the recovery catalog username and password. The recovery catalog should be stored in a dedicated database that is on a different disk than the target database. Protect the recovery catalog by backing it up.

* Host edrsr37p1

* Port 1521

* SID rcat

* Recovery Catalog Username rcatowner

* Recovery Catalog Password

d) On the Review page, click Finish.

Add Recovery Catalog: Review

The recovery catalog database will be configured in Enterprise Manager.

Recovery Catalog Database edrsr37p1:1521:rcat

Recovery Catalog User rcatowner

Cancel Finish

e) Back on the Recovery Catalog Settings page, select Use Recovery Catalog. Make sure that the recovery catalog you just registered is selected in the drop-down list, and enter the following values:

Recovery Catalog Username: rcatowner
Recovery Catalog Password: oracle_4U

Username: oracle
Password: oracle

Practice 3-4: Registering a Database in the Recovery Catalog (continued)

☐ Use Control File

Keep RMAN Records (days) Specify how long to keep RMAN records in the control file before they can be reused.

☒ Use Recovery Catalog

Recovery Catalog

* Recovery Catalog Username

* Recovery Catalog Password

Host username and password is required if your database is not registered with the selected catalog.

* Username

* Password

☒ Save as Preferred Credential

f) Click Save as Preferred Credential and then click OK.

Practice 3-5: Backing up the Recovery Catalog

In this practice, you configure the retention policy for the recovery catalog and back up your recovery catalog itself.

- 1) Set up the environment for the ORCL database.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 2) Start RMAN, use the recovery catalog database as the target, with no catalog specified.

```
$ rman target sys@rcat

target database Password: oracle_4U <<< not displayed
connected to target database: RCAT (DBID= 464959795)

RMAN>
```

- 3) Make sure that the retention policy for the recovery catalog is set to redundancy greater than 1. If it is not, set it to at least 2.

```
RMAN> show retention policy;

using target database control file instead of recovery catalog
RMAN configuration parameters for database with db_unique_name
RCAT are:
CONFIGURE RETENTION POLICY TO REDUNDANCY 1; # default

RMAN> configure retention policy to redundancy 2;

new RMAN configuration parameters:
CONFIGURE RETENTION POLICY TO REDUNDANCY 2;
new RMAN configuration parameters are successfully stored

RMAN>
```

- 4) Try to back up the database.

```
RMAN> backup database;

Starting backup at 18-JUL-07
ORACLE error from target database:
ORA-00258: manual archiving in NOARCHIVELOG mode must identify
log

using target database control file instead of recovery catalog
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=137 device type=DISK
specification does not match any archived log in the recovery
catalog
backup cancelled because all files were skipped
```

Practice 3-5: Backing up the Recovery Catalog (continued)

```

Finished backup at 18-JUL-07

Starting backup at 18-JUL-07
using channel ORA_DISK_1
channel ORA_DISK_1: starting full datafile backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
RMAN-00571:
=====
RMAN-00569: ===== ERROR MESSAGE STACK FOLLOWS
=====
RMAN-00571:
=====
RMAN-03002: failure of backup plus archivelog command at
07/18/2007 22:55:45
ORA-19602: cannot backup or copy active file in NOARCHIVELOG
mode

RMAN>

```

Note that you cannot back up an open database that is not in ARCHIVELOG mode. The recovery catalog database should be run in ARCHIVELOG mode for maximum availability.

5) Exit RMAN.

```
RMAN> exit
```

6) First, set up the environment for the RCAT database and then run the `rcat_to_archivelog.sh` script to change the recovery catalog database to run in ARCHIVELOG mode.

```

$ . oraenv
ORACLE_SID = [orcl] ? rcat

$ cd ~/labs
$ ./rcat_to_archivelog.sh
Database closed.
Database dismounted.
ORACLE instance shut down.
ORACLE instance started.

Total System Global Area  263639040 bytes
Fixed Size                  1299164 bytes
Variable Size              230690084 bytes
Database Buffers           25165824 bytes
Redo Buffers                6483968 bytes
Database mounted.

Database altered.
Database altered.
$

```

Practice 3-5: Backing up the Recovery Catalog (continued)

- 7) Set up the environment for the ORCL database.

```
$ . oraenv
ORACLE_SID = [rcat] ? orcl
```

- 8) Log in to RMAN again, as in the preceding step.

```
$ rman target sys@rcat

target database Password: oracle_4U <<< not displayed
connected to target database: RCAT (DBID= 464959795)

RMAN>
```

- 9) Back up the recovery catalog database. This time the operation should be successful.

```
RMAN> backup database;

Starting backup at 21-JUL-09
using target database control file instead of recovery catalog
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=40 device type=DISK
channel ORA_DISK_1: starting full datafile backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
input datafile file number=00001 name=+DATA/rcat/system01.dbf
input datafile file number=00002 name=+DATA/rcat/sysaux01.dbf
input datafile file number=00003 name=+DATA/rcat/undotbs01.dbf
input datafile file number=00005 name=+DATA/rcat01.dbf
input datafile file number=00004 name=+DATA/rcat/users01.dbf
channel ORA_DISK_1: starting piece 1 at 21-JUL-09
channel ORA_DISK_1: finished piece 1 at 21-JUL-09
piece
handle=+FRA/rcat/backupset/2009_07_21/nnndf0_tag20090721t15532
5_0.263.692812405 tag=TAG20090721T155325 comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:02:37
channel ORA_DISK_1: starting full datafile backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
including current control file in backup set
including current SPFILE in backup set
channel ORA_DISK_1: starting piece 1 at 21-JUL-09
channel ORA_DISK_1: finished piece 1 at 21-JUL-09
piece
handle=+FRA/rcat/backupset/2009_07_21/ncsnf0_tag20090721t15532
5_0.264.692812569 tag=TAG20090721T155325 comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:03
Finished backup at 21-JUL-09

RMAN> exit
```

Practice 3-5: Backing up the Recovery Catalog (continued)

- 10) Run the `disable_asynch_io.sh` script to disable asynchronous input/output (I/O). After altering the system, the database is restarted. This improves performance on the following labs:

```
$ ~/labs/disable_asynch_io.sh
Setting up ORCL environment.
ORACLE_SID = [orcl] ? The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1 is
/u01/app/oracle

SQL*Plus: Release 11.2.0.1.0 Production on Tue Jul 21 15:58:51
2009

Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -
Production
With the Partitioning, Automatic Storage Management, OLAP,
Data Mining
and Real Application Testing options

SQL>
System altered.

SQL>
System altered.

SQL> Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> ORACLE instance started.

Total System Global Area 481259520 bytes
Fixed Size 1337324 bytes
Variable Size 360712212 bytes
Database Buffers 113246208 bytes
Redo Buffers 5963776 bytes
Database mounted.
Database opened.
SQL> Disconnected from Oracle Database 11g Enterprise Edition
Release 11.2.0.1.0 - Production
With the Partitioning, Automatic Storage Management, OLAP,
Data Mining
and Real Application Testing options
```


Practice 4-1: Setting the Date and Time Format for RMAN

In this practice, you set the date/time format that RMAN uses for displaying timestamps.

- 1) Set the NLS_LANG and NLS_DATE_FORMAT variables such that RMAN includes time information in any timestamp values. Add the following two lines to the ~oracle/.bashrc file. Then exit all of your terminal windows. This ensures that when you create new ones, these settings will be in effect.

```
export NLS_LANG=american_american.al32utf8
export NLS_DATE_FORMAT="yyyy-mm-dd:hh24:mi:ss"
```

- 2) Start a new terminal window, and verify the settings by starting RMAN and listing the backups of the recovery catalog database.

- a) Set up the environment for the ORCL database.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- b) Log in to RMAN.

```
$ rman target sys@rcat

target database Password: oracle_4U <<< not displayed
connected to target database: RCAT (DBID= 464959795)
```

- c) List the backups, and note the timestamp format.

```
RMAN> list backup;
using target database control file instead of recovery catalog

List of Backup Sets
=====

BS Key   Type LV Size          Device Type Elapsed Time Completion
Time
----- -- --
1        Full  9.36M      DISK            00:00:06      2009-07-
21:15:42:05
        BP Key: 1   Status: AVAILABLE Compressed: NO   Tag:
TAG20090721T154159
        Piece Name:
+FRA/rcat/backupset/2009_07_21/ncsnf0_tag20090721t154159_0.262
.692811721
        SPFILE Included: Modification time: 2009-07-21:15:32:47
        SPFILE db_unique_name: RCAT
```

Practice 4-1: Setting the Date and Time Format for RMAN (continued)

```
Control File Included: Ckp SCN: 803770          Ckp time: 2009-  
07-21:15:41:59  
  
.  
.  
.  
RMAN>
```

Note: Because the output of the RMAN commands can be quite long, consider using the RMAN SPOOL LOG command to direct the output to your specified file.

Practice 4-2: Enabling Control File Autobackup

In this practice, you configure RMAN to back up the control file and SPFILE each time it takes a backup of anything in the RCAT database.

- 1) In the same recovery catalog RMAN session, make sure that control file autobackup is enabled.

```
RMAN> show controlfile autobackup;

RMAN configuration parameters for database with db_unique_name
RCAT are:
CONFIGURE CONTROLFILE AUTOBACKUP OFF; # default

RMAN>
```

- 2) Enable control file autobackup.

```
RMAN> configure controlfile autobackup on;

new RMAN configuration parameters:
CONFIGURE CONTROLFILE AUTOBACKUP ON;
new RMAN configuration parameters are successfully stored

RMAN>
```

- 3) Verify that it is enabled by backing up the archive logs for the recovery catalog. Then exit RMAN.

```
RMAN> backup archivelog all;

Starting backup at 2009-07-21:16:22:10
current log archived
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=47 device type=DISK
channel ORA_DISK_1: starting archived log backup set
channel ORA_DISK_1: specifying archived log(s) in backup set
input archived log thread=1 sequence=5 RECID=1 STAMP=692814135
channel ORA_DISK_1: starting piece 1 at 2009-07-21:16:22:18
channel ORA_DISK_1: finished piece 1 at 2009-07-21:16:22:21
piece
handle=+FRA/rcat/backupset/2009_07_21/annnf0_tag20090721t16221
6_0.266.692814139 tag=TAG20090721T162216 comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:04
Finished backup at 2009-07-21:16:22:21

Starting Control File and SPFILE Autobackup at 2009-07-
21:16:22:21
piece
handle=+FRA/rcat/autobackup/2009_07_21/s_692814141.267.6928141
45 comment=NONE
Finished Control File and SPFILE Autobackup at 2009-07-
21:16:22:28
```

Practice 4-2: Enabling Control File Autobackup (continued)

```
RMAN> exit
```

Note that the control file and SPFILE are automatically backed up now.

Practice 4-3: Configuring Devices for Backup

In this practice, you configure a tape device for use in making backups.

Note: This channel definition is used in the RMAN monitoring and tuning practice. Therefore, steps 1-4 are mandatory; step 5 (performing a backup) is recommended, but optional.

- 1) Make sure the SID variable is set to ORCL.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 2) Start RMAN by connecting to the ORCL as the target database and using the recovery catalog database.

```
$ rman target / catalog rcatowner@rcat

recovery catalog database Password: oracle_4U <<<not displayed>
RMAN>
```

- 3) Show all configuration settings to see whether there are any tape devices defined.

```
RMAN> show all;

RMAN configuration parameters for database with db_unique_name
ORCL are:
CONFIGURE RETENTION POLICY TO REDUNDANCY 1; # default
CONFIGURE BACKUP OPTIMIZATION OFF; # default
CONFIGURE DEFAULT DEVICE TYPE TO DISK; # default
CONFIGURE CONTROLFILE AUTOBACKUP ON;
CONFIGURE CONTROLFILE AUTOBACKUP FORMAT FOR DEVICE TYPE DISK
TO '%F'; # default
CONFIGURE DEVICE TYPE DISK PARALLELISM 1 BACKUP TYPE TO
BACKUPSET; # default
CONFIGURE DATAFILE BACKUP COPIES FOR DEVICE TYPE DISK TO 1; #
default
CONFIGURE ARCHIVELOG BACKUP COPIES FOR DEVICE TYPE DISK TO 1;
# default
CONFIGURE MAXSETSIZE TO UNLIMITED; # default
CONFIGURE ENCRYPTION FOR DATABASE OFF; # default
CONFIGURE ENCRYPTION ALGORITHM 'AES128'; # default
CONFIGURE COMPRESSION ALGORITHM 'BASIC' AS OF RELEASE
'DEFAULT' OPTIMIZE FOR LOAD TRUE ; # default
CONFIGURE ARCHIVELOG DELETION POLICY TO NONE; # default
CONFIGURE SNAPSHOT CONTROLFILE NAME TO
'/u01/app/oracle/product/11.2.0/dbhome_1/dbs/snapcf_orcl.f'; #
default

RMAN>
```

Note that there are no tape devices.

- 4) Define a channel for a tape device that uses the test interface. This actually writes to disk in the /tape directory.

Practice 4-3: Configuring Devices for Backup (continued)

```
RMAN> configure channel device type sbt
2> parms='SBT_LIBRARY=oracle.disksbt,ENV=(BACKUP_DIR=/tape)';

new RMAN configuration parameters:
CONFIGURE CHANNEL DEVICE TYPE 'SBT_TAPE' PARMS
'SBT_LIBRARY=oracle.disksbt,ENV=(BACKUP_DIR=/tape)';
new RMAN configuration parameters are successfully stored
starting full resync of recovery catalog
full resync complete

RMAN>
```

- 5) Perform a backup to the tape device to make sure it works. Back up the USERS tablespace. Then exit RMAN.

```
RMAN> backup device type sbt tablespace users;

Starting backup at 2009-07-21:16:32:09
allocated channel: ORA_SBT_TAPE_1
channel ORA_SBT_TAPE_1: SID=53 device type=SBT_TAPE
channel ORA_SBT_TAPE_1: WARNING: Oracle Test Disk API
channel ORA_SBT_TAPE_1: starting full datafile backup set
channel ORA_SBT_TAPE_1: specifying datafile(s) in backup set
input datafile file number=00004
name=+DATA/orcl/datafile/users.259.692754561
channel ORA_SBT_TAPE_1: starting piece 1 at 2009-07-
21:16:32:10
channel ORA_SBT_TAPE_1: finished piece 1 at 2009-07-
21:16:32:11
piece handle=05kkn0sa_1_1 tag=TAG20090721T163210 comment=API
Version 2.0,MMS Version 8.1.3.0
channel ORA_SBT_TAPE_1: backup set complete, elapsed time:
00:00:01
Finished backup at 2009-07-21:16:32:11

Starting Control File and SPFILE Autobackup at 2009-07-
21:16:32:11
piece handle=c-1220535480-20090721-02 comment=API Version
2.0,MMS Version 8.1.3.0
Finished Control File and SPFILE Autobackup at 2009-07-
21:16:32:16

RMAN> exit
```

Note that it uses a channel called ORA_SBT_TAPE_1 to perform the backup.

Practice 5-1: Creating Fast Incremental Backups

In this practice, you enable block change tracking so that you can make incremental backups more quickly.

- 1) Use Enterprise Manager Database Control to configure backup optimization and enable block change tracking. Allow a default block change tracking file to be used.
 - a) From the Database home page of EM, navigate to Availability > Backup Settings > Policy, and enable backup optimization and block change tracking.

Database Instance: [orcl.us.oracle.com](#) >

Backup Settings

[Device](#) [Backup Set](#) **Policy**

Backup Policy

☒ Automatically backup the control file and server parameter file (SPFILE) with every backup and database structural change

Autobackup Disk Location

An existing directory or diskgroup name where the control file and server parameter file will be backed up. If you do not specify a location, the files will be backed up to the flash recovery area location.

☒ Optimize the whole database backup by skipping unchanged files such as read-only and offline datafiles that have been backed up

☒ Enable block change tracking for faster incremental backups

Block Change Tracking File

Specify a location and file, otherwise an Oracle managed file will be created in the database area.

- b) Click OK.
- c) If you see the following error, you have not entered the operating system credentials. Continue with the following steps if that is the case.

✖ Validation Error

Examine and correct the following errors, then retry the operation:


Error - Please specify a username.


- d) Scroll to the bottom of the page, and enter `oracle` as username and `oracle` as password. Also, select the option to save this as the preferred credential.


Practice 5-1: Creating Fast Incremental Backups (continued)

Host Credentials

To save the backup settings, supply operating system login credentials to access the target database.

 Username

 Password

 Save as Preferred Credential

e) Click OK.

- 2) Make sure that the ORACLE_SID variable is set to ORCL.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 3) Log in to RMAN and create an incremental level 0 backup.

```
$ rman target / catalog rcatowner@rcat

recovery catalog database Password: oracle_4U <<<not displayed

RMAN> backup incremental level 0 database plus archivelog;

starting full resync of recovery catalog
full resync complete
.
.
.
piece
handle=+FRA/orcl/backupset/2009_07_21/annnf0_tag20090721t19055
7_0.273.692823957 tag=TAG20090721T190557 comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:03
Finished backup at 21-JUL-09

Starting Control File and SPFILE Autobackup at 21-JUL-09
piece
handle=+FRA/orcl/autobackup/2009_07_21/s_692823962.274.6928239
65 comment=NONE
Finished Control File and SPFILE Autobackup at 21-JUL-09

RMAN>
```

- 4) Now that you have a level 0 incremental backup, you can take advantage of block change tracking to make fast incremental backups. Take a level 1 incremental backup.

```
RMAN> backup incremental level 1 database plus archivelog;

Starting backup at 21-JUL-09
current log archived
using channel ORA_DISK_1
.
.
```


Practice 5-1: Creating Fast Incremental Backups (continued)

```
.  
Finished Control File and SPFILE Autobackup at 21-JUL-09  
RMAN>
```

- 5) In another terminal window, make sure you are at the ~/labs directory.

```
$ cd ~/labs
```

- 6) Review and execute the query_block_count.sh script to query V\$BACKUP_DATAFILE to see how many of the blocks were read for creating the level 1 incremental backup.

```
$ cat query_block_count.sh  
export ORACLE_SID=orcl  
sqlplus / as sysdba <<-EOI  
  select file#, avg(datafile_blocks),  
         avg(blocks_read),  
         avg(blocks_read/datafile_blocks) * 100 as  
PCT_READ_FOR_BACKUP,  
         avg(blocks)  
  from v\backup_datafile  
 where used_change_tracking = 'YES'  
    and incremental_level > 0  
    group by file#;  
quit  
EOI  
  
$ ./query_block_count.sh  
  
SQL>  2      3      4      5      6      7      8  
      FILE# AVG(DATAFILE_BLOCKS) AVG(BLOCKS_READ)  
PCT_READ_FOR_BACKUP AVG(BLOCKS)  
-----  
-----  
          1              87040              173  
.198759191              34  
          2              75520              957  
1.26721398             344  
          5              12800               1  
.0078125              1  
          4              640               1  
.15625              1  
          3              12800             311  
2.4296875              96  
$
```

Note that the percentage of blocks read for making the backup is very low in most cases, and sometimes very close to zero.

Practice 5-2: Cross-Checking Backups

In this practice, you cross-check backups against the recovery catalog, identifying and deleting any backups that are obsolete.

- 1) Make sure that you are at the ~/labs directory, and that the ORACLE_SID variable is set to ORCL.

```
$ cd ~/labs
$ . oraenv
ORACLE_SID = [orcl] ? orcl
```

- 2) Use the RMAN session from the previous practice or start RMAN. Make sure that you connect to both your target database and the recovery catalog database.

```
$ rman target / catalog rcatowner@rcat

connected to target database: ORCL (DBID=1220535480)
recovery catalog database Password: oracle_4U <<<not displayed
connected to recovery catalog database

RMAN>
```

- 3) List backups of data file 5, noting the entry corresponding to the example data file.

```
RMAN> list backup of datafile 5;
```

BS Key	Type	LV	Size	Device	Type	Elapsed Time	Completion Time
37	Full		68.99M	DISK		00:00:13	2009-07-21:14:54:11
BP Key: 40 Status: AVAILABLE Compressed: NO Tag: TAG20090721T145358							
Piece Name:							
+FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t145358_0.260.692808839							
List of Datafiles in backup set 37							
File	LV	Type	Ckp SCN	Ckp Time	Name		
5		Full	908595	2009-07-21:14:53:59			
+DATA/orcl/datafile/example.265.692754837							

BS Key	Type	LV	Size	Device	Type	Elapsed Time	Completion Time
172	Incr	0	1.07G	DISK		00:02:47	2009-07-21:19:05:44
BP Key: 176 Status: AVAILABLE Compressed: NO Tag: TAG20090721T190255							
Piece Name:							
+FRA/orcl/backupset/2009_07_21/nnndn0_tag20090721t190255_0.271.692823777							
List of Datafiles in backup set 172							
File	LV	Type	Ckp SCN	Ckp Time	Name		
5	0	Incr	924152	2009-07-21:19:02:57			
+DATA/orcl/datafile/example.265.692754837							

BS Key	Type	LV	Size	Device	Type	Elapsed Time	Completion Time
237	Incr	1	3.74M	DISK		00:00:02	2009-07-21:19:10:35

Practice 5-2: Cross-Checking Backups (continued)

```
BP Key: 241    Status: AVAILABLE    Compressed: NO    Tag:
TAG20090721T191031
Piece Name:
+FRA/orcl/backupset/2009_07_21/nnndn1_tag20090721t191031_0.277.692824233
List of Datafiles in backup set 237
File LV Type Ckp SCN    Ckp Time    Name
-----
5      1    Incr 924953    2009-07-21:19:10:33
+DATA/orcl/datafile/example.265.692754837
RMAN>
```

Take note of the only backup that is a full backup of data file 5. Also note that the “Piece Name” is the name of the ASM file where the backup file resides.

- 4) In an OS terminal window, delete the backup set file. Start a separate terminal session, so the RMAN session can stay connected. Use the +ASM environment variables, review and execute the `rm_asm_file.sh` script to do this. Supply YOUR full “Piece Name” as an argument to the script.

```
$ . oraenv
ORACLE_SID = [orcl] ? +ASM

$ cat rm_asm_file.sh
export ORACLE_SID=+ASM
asmcmd <<-EOI
    rm -f $1
    exit
EOI
Exit

./rm_asm_file.sh \
> +FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t145358_0.260.692808839
ASMCMD> ASMCMD> $
$
```

- 5) In your still connected RMAN session, list the backups again, and look for the backup that corresponds to the example data file.

```
RMAN> list backup of datafile 5;

List of Backup Sets
=====

BS Key    Type LV Size          Device Type Elapsed Time Completion Time
-----
37        Full  68.99M    DISK          00:00:13    2009-07-21:14:54:11
BP Key: 40    Status: AVAILABLE    Compressed: NO    Tag:
TAG20090721T145358
Piece Name:
+FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t145358_0.260.692808839
List of Datafiles in backup set 37
File LV Type Ckp SCN    Ckp Time    Name
-----
```

Practice 5-2: Cross-Checking Backups (continued)

```

5          Full 908595      2009-07-21:14:53:59
+DATA/orcl/datafile/example.265.692754837

BS Key   Type LV Size          Device Type Elapsed Time Completion Time
-----
172      Incr 0   1.07G          DISK          00:02:47      2009-07-21:19:05:44
        BP Key: 176   Status: AVAILABLE   Compressed: NO   Tag:
TAG20090721T190255
        Piece Name:
+FRA/orcl/backupset/2009_07_21/nnndn0_tag20090721t190255_0.271.692823777
  List of Datafiles in backup set 172
  File LV Type Ckp SCN      Ckp Time          Name
  ----
5         0   Incr 924152      2009-07-21:19:02:57
+DATA/orcl/datafile/example.265.692754837

BS Key   Type LV Size          Device Type Elapsed Time Completion Time
-----
237      Incr 1   3.74M          DISK          00:00:02      2009-07-21:19:10:35
        BP Key: 241   Status: AVAILABLE   Compressed: NO   Tag:
TAG20090721T191031
        Piece Name:
+FRA/orcl/backupset/2009_07_21/nnndn1_tag20090721t191031_0.277.692824233
  List of Datafiles in backup set 237
  File LV Type Ckp SCN      Ckp Time          Name
  ----
5         1   Incr 924953      2009-07-21:19:10:33
+DATA/orcl/datafile/example.265.692754837

RMAN>

```

Note that the backups are still listed as before. That is because the repository is not aware of the fact that the file for the backup piece is missing.

- 6) Cross-check the backup sets to make the recovery catalog aware of the missing backup file.

```

RMAN> crosscheck backupset;

allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=48 device type=DISK
allocated channel: ORA_SBT_TAPE_1
channel ORA_SBT_TAPE_1: SID=57 device type=SBT_TAPE
channel ORA_SBT_TAPE_1: WARNING: Oracle Test Disk API
crosschecked backup piece: found to be 'EXPIRED'
backup piece
handle=+FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t14535
8_0.260.692808839 RECID=1 STAMP=692808839
crosschecked backup piece: found to be 'AVAILABLE'.
.
.
.

RMAN>

```

Note that the backup in question has expired.

Practice 5-2: Cross-Checking Backups (continued)

- 7) Delete all the expired backup sets.

```
RMAN> delete expired backupset;

using channel ORA_DISK_1
using channel ORA_SBT_TAPE_1

List of Backup Pieces
BP Key   BS Key   Pc#   Cp#   Status   Device Type Piece Name
-----
40       37       1     1     EXPIRED   DISK
+FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t145358_0.260
.692808839

Do you really want to delete the above objects (enter YES or
NO)? YES
deleted backup piece
backup piece
handle=+FRA/orcl/backupset/2009_07_21/nnndf0_tag20090721t14535
8_0.260.692808839 RECID=1 STAMP=692808839
Deleted 1 EXPIRED objects

RMAN>
```

- 8) List the backup sets again. See that the backup you just deleted is no longer listed.

```
RMAN> list backup of datafile 5;

List of Backup Sets
=====

BS Key   Type LV Size          Device Type Elapsed Time Completion
Time
-----
172      Incr 0  1.07G             DISK           00:02:47      2009-07-
21:19:05:44
        BP Key: 176      Status: AVAILABLE  Compressed: NO   Tag:
TAG20090721T190255
        Piece Name:
+FRA/orcl/backupset/2009_07_21/nnndn0_tag20090721t190255_0.271
.692823777
        List of Datafiles in backup set 172
        File LV Type Ckp SCN      Ckp Time          Name
        -----
         5      0   Incr 924152       2009-07-21:19:02:57
+DATA/orcl/datafile/example.265.692754837

BS Key   Type LV Size          Device Type Elapsed Time Completion
Time
```

Practice 5-2: Cross-Checking Backups (continued)

```
-----  
-----  
237      Incr 1   3.74M      DISK      00:00:02      2009-07-  
21:19:10:35  
      BP Key: 241      Status: AVAILABLE      Compressed: NO      Tag:  
TAG20090721T191031  
      Piece Name:  
+FRA/orcl/backupset/2009_07_21/nnndn1_tag20090721t191031_0.277  
.692824233  
      List of Datafiles in backup set 237  
      File LV Type Ckp SCN      Ckp Time      Name  
      ---- -- ----  
      5      1      Incr 924953      2009-07-21:19:10:33  
+DATA/orcl/datafile/example.265.692754837  
  
RMAN>
```

Practice 5-3: Listing Backup Files and Creating Archival Backup

In this practice, you list backup files.

- 1) Continue to use the RMAN session from the previous practice, and generate a report of all the obsolete backup files.

```

RMAN> report obsolete;

RMAN retention policy will be applied to the command
RMAN retention policy is set to redundancy 1
Report of obsolete backups and copies
Type                                Key      Completion Time      Filename/Handle
-----
Backup Set                          38       2009-07-21:14:54:16
  Backup Piece                      41       2009-07-21:14:54:16
+FRA/orcl/autobackup/2009_07_21/s_692808854.261.692808857
Backup Set                          68       2009-07-21:16:29:17
  Backup Piece                      71       2009-07-21:16:29:17 03kkn0mt_1_1
Backup Set                          77       2009-07-21:16:29:22
  Backup Piece                      79       2009-07-21:16:29:22 c-1220535480-
20090721-01
Backup Set                          93       2009-07-21:16:32:10
  Backup Piece                      96       2009-07-21:16:32:10 05kkn0sa_1_1
Archive Log                        151      2009-07-21:17:49:04
+FRA/orcl/archivelog/2009_07_21/thread_1_seq_9.268.692819337
Backup Set                         105      2009-07-21:16:32:14
  Backup Piece                     107      2009-07-21:16:32:14 c-1220535480-
20090721-02
Archive Log                        163      2009-07-21:19:02:49
+FRA/orcl/archivelog/2009_07_21/thread_1_seq_10.269.692823767
Backup Set                         171      2009-07-21:19:02:53
  Backup Piece                     175      2009-07-21:19:02:53
+FRA/orcl/backupset/2009_07_21/annnf0_tag20090721t190251_0.270
.692823773
Backup Set                         205      2009-07-21:19:06:06
  Backup Piece                     207      2009-07-21:19:06:06
+FRA/orcl/autobackup/2009_07_21/s_692823962.274.692823965
RMAN>

```

Your list of files might look different. - What can you deduce about these backup files, given that the retention policy is set to REDUNDANCY 1?

- 2) Which backups would be considered obsolete if the retention policy were set to redundancy of 2, instead of 1? Answer this without changing the retention policy.

```

RMAN> report obsolete redundancy 2;

Report of obsolete backups and copies
Type                                Key      Completion Time      Filename/Handle
-----
Backup Set                          38       2009-07-21:14:54:16

```

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

```
Backup Piece      41      2009-07-21:14:54:16
+FRA/orcl/autobackup/2009_07_21/s_692808854.261.692808857
Backup Set        68      2009-07-21:16:29:17
Backup Piece      71      2009-07-21:16:29:17 03kkn0mt_1_1
Backup Set        77      2009-07-21:16:29:22
Backup Piece      79      2009-07-21:16:29:22 c-1220535480-
20090721-01
Backup Set        105     2009-07-21:16:32:14
Backup Piece      107     2009-07-21:16:32:14 c-1220535480-
20090721-02

RMAN>
```

Note that far fewer backups are obsolete in this hypothetical report. That is because with an increased redundancy, more of the backups are required. This command is run without affecting the retention policy.

3) Delete all obsolete backups.

```
RMAN> delete noprompt obsolete;

RMAN retention policy will be applied to the command
RMAN retention policy is set to redundancy 1
using channel ORA_DISK_1
using channel ORA_SBT_TAPE_1
Deleting the following obsolete backups and copies:
Type              Key      Completion Time      Filename/Handle
-----
Backup Set        38      2009-07-21:14:54:16
Backup Piece      41      2009-07-21:14:54:16
+FRA/orcl/autobackup/2009_07_21/s_692808854.261.692808857
Backup Set        68      2009-07-21:16:29:17
Backup Piece      71      2009-07-21:16:29:17 03kkn0mt_1_1
Backup Set        77      2009-07-21:16:29:22
.
.
.

deleted backup piece
backup piece handle=05kkn0sa_1_1 RECID=5 STAMP=692814730
deleted backup piece
backup piece handle=c-1220535480-20090721-02 RECID=6
STAMP=692814734
Deleted 4 objects

RMAN>
```


Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

Note: Your number of objects may be different, depending on repetitions of practice steps.

- 4) List the backup archivelog files that could be used to recover to a point in time one hour ago.

Note: You may need to adjust the following SYSDATE expression to see some results that differ from the list command that does not use a SYSDATE qualifier at all. For example, try 'sysdate-05/60/24' to indicate 5 minutes ago.

```

RMAN> list backup of archivelog until time 'sysdate-1/24';

List of Backup Sets
=====

BS Key    Size          Device Type Elapsed Time Completion Time
-----
-
191        1.05M        DISK          00:00:01    2009-07-
21:19:05:58
          BP Key: 197    Status: AVAILABLE Compressed: NO Tag:
TAG20090721T190557
          Piece Name:
+FRA/orcl/backupset/2009_07_21/annnf0_tag20090721t190557_0.273
.692823957

List of Archived Logs in backup set 191
Thrd Seq      Low SCN      Low Time          Next SCN      Next
Time
-----
1      11          924126        2009-07-21:19:02:46 924627        2009-
07-21:19:05:53

BS Key    Size          Device Type Elapsed Time Completion Time
-----
-
236        277.00K        DISK          00:00:01    2009-07-
21:19:10:29
          BP Key: 240    Status: AVAILABLE Compressed: NO Tag:
TAG20090721T191028
          Piece Name:
+FRA/orcl/backupset/2009_07_21/annnf0_tag20090721t191028_0.276
.692824229

List of Archived Logs in backup set 236
Thrd Seq      Low SCN      Low Time          Next SCN      Next
Time
-----
```

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

```

-----
1      12      924627      2009-07-21:19:05:53 924928      2009-
07-21:19:10:26

BS Key   Size      Device Type Elapsed Time Completion Time
-----
-
258      7.50K      DISK      00:00:01      2009-07-
21:19:10:39
          BP Key: 264      Status: AVAILABLE      Compressed: NO      Tag:
TAG20090721T191037
          Piece Name:
+FRA/orcl/backupset/2009_07_21/annnf0_tag20090721t191037_0.279
.692824239

List of Archived Logs in backup set 258
Thrd Seq      Low SCN      Low Time      Next SCN      Next
Time
-----
1      13      924928      2009-07-21:19:10:26 924960      2009-
07-21:19:10:36

RMAN>

```

- 5) List the image copies of the single data file in the USERS tablespace.
 - a) Report on the schema to find out which data file number belongs to the USERS tablespace.

```

RMAN> report schema;

Report of database schema for database with db_unique_name
ORCL

List of Permanent Datafiles
=====
File Size(MB) Tablespace      RB segs Datafile Name
-----
1      680      SYSTEM      YES
+DATA/orcl/datafile/system.256.692754557
2      590      SYSAUX      NO
+DATA/orcl/datafile/sysaux.257.692754559
3      100      UNDOTBS1     YES
+DATA/orcl/datafile/undotbs1.258.692754561
4      5      USERS      NO
+DATA/orcl/datafile/users.259.692754561

```

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

```

5      100      EXAMPLE      NO
+DATA/orcl/datafile/example.265.692754837

List of Temporary Files
=====
File Size(MB) Tablespace      Maxsize(MB) Tempfile Name
-----
1      28      TEMP      32767
+DATA/orcl/tempfile/temp.264.692754825
RMAN>

```

Note that the file in question is data file number 4.

b) List any image copies of data file number 4.

```

RMAN> list copy of datafile 4;

specification does not match any datafile copy in the repository

RMAN>

```

Note that, in this case, there is no image copy of this file.

6) Delete any data file 4 image copies that exist.

Note: You may not have any.

```

RMAN> delete copy of datafile 4;

released channel: ORA_DISK_1
released channel: ORA_SBT_TAPE_1
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=105 device type=DISK
List of Datafile Copies
=====

Key      File S Completion Time      Ckp SCN      Ckp Time
-----
115      4      A 2009-05-27:21:08:45 1917108      2009-05-
27:20:50:57
      Name: /tmp/users_copy.dat

Do you really want to delete the above objects (enter YES or
NO)? yes

RMAN> list copy of datafile 4;

specification does not match any datafile copy in the
repository

```

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

```
RMAN>
```

- 7) To simplify your training environment, disable control file autobackup for the next few steps.

```
RMAN> configure controlfile autobackup off;
```

```
old RMAN configuration parameters:
CONFIGURE CONTROLFILE AUTOBACKUP ON;
new RMAN configuration parameters:
CONFIGURE CONTROLFILE AUTOBACKUP OFF;
new RMAN configuration parameters are successfully stored
starting full resync of recovery catalog
full resync complete
```

```
RMAN>
```

- 8) Make an image file backup of data file 4.

```
RMAN> backup as copy datafile 4;
```

```
Starting backup at 2009-07-21:20:27:25
released channel: ORA_SBT_TAPE_1
using channel ORA_DISK_1
channel ORA_DISK_1: starting datafile copy
input datafile file number=00004
name=+DATA/orcl/datafile/users.259.692754561
output file name=+FRA/orcl/datafile/users.274.692828845
tag=TAG20090721T202725 RECID=2 STAMP=692828849
channel ORA_DISK_1: datafile copy complete, elapsed time:
00:00:07
Finished backup at 2009-07-21:20:27:32
```

```
RMAN>
```

- 9) Make another image copy of the data file, but make this one an archival backup.

```
RMAN> backup as copy datafile 4 keep forever;
```

```
Starting backup at 2009-07-21:20:28:30
current log archived

using channel ORA_DISK_1
backup will never be obsolete
archived logs required to recover from this backup will be
backed up
channel ORA_DISK_1: starting datafile copy
input datafile file number=00004
name=+DATA/orcl/datafile/users.259.692754561
```

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

```
RMAN-00571:
=====
RMAN-00569: ===== ERROR MESSAGE STACK FOLLOWS
=====
RMAN-00571:
-----
RMAN-03002: failure of backup command at 07/21/2009 20:28:34
ORA-19811: cannot have files in DB_RECOVERY_FILE_DEST with
keep_attributes
RMAN>
```

Note that the backup command failed. This is because a backup with the KEEP attribute (an archival backup) cannot be written to the Flash Recovery Area. Allowing this has the potential of causing the Flash Recovery Area to quickly run out of space, forcing you to specify a different location.

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

- 10) Create an archival backup with a FORMAT clause that causes the backup to be written to the /tmp directory.

```
RMAN> backup keep forever as copy datafile 4 format
'/tmp/bu_%d_%s_%p.dbf';

Starting backup at 2009-07-21:20:31:14
current log archived

using channel ORA_DISK_1
backup will never be obsolete
archived logs required to recover from this backup will be
backed up
channel ORA_DISK_1: starting datafile copy
input datafile file number=00004
name=+DATA/orcl/datafile/users.259.692754561
output file name=/tmp/bu_ORCL_17_1.dbf tag=TAG20090721T203114
RECID=3 STAMP=692829077
channel ORA_DISK_1: datafile copy complete, elapsed time:
00:00:03
.
.
.
piece handle=/tmp/bu_ORCL_20_1.dbf tag=TAG20090721T203114
comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:01
Finished backup at 2009-07-21:20:31:29

RMAN>
```

- 11) See if there are any obsolete backups. (If you repeat practice steps you might have obsolete ones.)

```
RMAN> report obsolete;

RMAN retention policy will be applied to the command
RMAN retention policy is set to redundancy 1
no obsolete backups found

RMAN>
```

- 12) Create another (nonarchive) backup of data file 4.

```
RMAN> backup as copy datafile 4;

Starting backup at 2009-07-21:20:33:52
using channel ORA_DISK_1
channel ORA_DISK_1: starting datafile copy
```

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

```
input datafile file number=00004
name=+DATA/orcl/datafile/users.259.692754561
output file name=+FRA/orcl/datafile/users.261.692829233
tag=TAG20090721T203352 RECID=4 STAMP=692829233
channel ORA_DISK_1: datafile copy complete, elapsed time:
00:00:01
Finished backup at 2009-07-21:20:33:54

RMAN>
```

- 13) Report on the obsolete backups.

```
RMAN> report obsolete;

RMAN retention policy will be applied to the command
RMAN retention policy is set to redundancy 1
Report of obsolete backups and copies
Type                                Key      Completion Time      Filename/Handle
-----
Datafile Copy                      349      2009-07-21:20:27:29
+FRA/orcl/datafile/users.274.692828845

RMAN>
```

Note that the first backup taken is now obsolete.

- 14) For an alternate view of the backups, in EM, navigate to Availability > Manage Current Backups > Image Copies.
- 15) Ensure that the username and password of oracle/oracle are in the host credentials section at the bottom of the page, and then at the upper-right corner of the page, click Delete All Obsolete.
- 16) When the Specify Job Parameters page appears, click Show RMAN Script.

Delete All Obsolete: Specify Job Parameters

An Enterprise Manager job will be created to perform the operation you chose on all backup sets and image copies. Please specify the parameters to run the job.

✚ Job Name

✚ Job Description

Note that the script issues the DELETE NOPROMPT OBSOLETE command. Click OK.

- 17) Click Submit Job.
- 18) After the job is submitted, click View Job.

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

Manage Current Backups

Catalog Additional Files Crosscheck All Delete All Obsolete Delete All Expired

Job submission succeeded.
 Job Bkp_Mgmt_orcl.us.oracle.com_000001 was successfully submitted for the Delete All Obsolete operation. It will be executed at the scheduled time.
[View Job](#)

- 19) When the job status is Running, use your browser's Reload button until the job status appears as Succeeded. Then navigate back to the backup listing page for image copies (Database > Availability > Manage Current Backups > Image Copies).

Results

Crosscheck Change to Unavailable Delete Validate

Select All | Select None

Select	Key	Name	File Type	Tag	Completion Time	Status	Keep
<input type="checkbox"/>	4	+FRA/orcl/datafile /users.288.695437683	DATAFILE	TAG20090821T010801	Aug 21, 2009 1:08:02 AM	AVAILABLE	NO
<input type="checkbox"/>	3	/tmp/bu_ORCL_23_1.dbf	DATAFILE	TAG20090821T010402	Aug 21, 2009 1:04:06 AM	AVAILABLE	Forever

- 20) Note that there are now only two backups of data file 4. The obsolete one has been deleted because it was the third of three, and the retention policy is set to 1, meaning there need only be two backups of any given file. (Remember the archival backup is not counted.)

Results

Crosscheck Change to Unavailable Delete Validate

Select All | Select None

Select	Key	Name	File Type	Tag	Completion Time	Status	Keep
<input type="checkbox"/>	467	+FRA/orcl/datafile /users.261.692829233	DATAFILE	TAG20090721T203352	Jul 21, 2009 8:33:53 PM	AVAILABLE	NO
<input type="checkbox"/>	415	/tmp/bu_ORCL_17_1.dbf	DATAFILE	TAG20090721T203114	Jul 21, 2009 8:31:17 PM	AVAILABLE	Forever

- 21) Click the Backup Sets tab on this page. What archival backup sets appear there? Why are they there?

Results

Crosscheck Change to Unavailable Delete Validate

Select All | Select None

Select	Key	Tag	Completion Time	Contents	Device Type	Status	Keep	Pieces
<input type="checkbox"/>	438	TAG20090721T203114	Jul 21, 2009 8:31:28 PM	CONTROLFILE	DISK	AVAILABLE	Forever	1
<input type="checkbox"/>	437	TAG20090721T203114	Jul 21, 2009 8:31:26 PM	ARCHIVED LOG	DISK	AVAILABLE	Forever	1
<input type="checkbox"/>	410	TAG20090721T203114	Jul 21, 2009 8:31:19 PM	SPFILE	DISK	AVAILABLE	Forever	1

Practice 5-3: Listing Backup Files and Creating Archival Backup (continued)

Answer: These archival backup sets are here because they were taken as a byproduct of taking the data file image copy as an archival backup. When the data file archival backup was taken, control file autobackup was enabled, which causes the control file and the SPFILE to be backed up. Also, any archive redo logs that are required to recover the image copy are taken. Because the image copy was an archival backup, every other file that is backed up as a part of that backup task is also an archival backup.

22) Enable the automatic backup of the control file again and exit RMAN.

```
RMAN> configure controlfile autobackup on;  
RMAN> exit
```

Practice 6-1: Backing up the Database

In this practice, you create a cold backup of the `rcat` database.

Because ASM does not expose its files to the operating system, you create backups to a regular file system destination, so that you can setup various learning situations in the following practices.

Note: The `RCAT` database is in the `ARCHIVE` log mode, and is capable of performing an inconsistent backup. In this exercise though, you will perform a consistent cold backup.

- 1) Create the `/home/oracle/BACKUP` directory to hold backup files.

```
$ cd
$ pwd
/home/oracle
$ mkdir BACKUP
```

- 2) Make sure that your environment is pointing at the `rcat` database.

```
$. oraenv
ORACLE_SID = [+ASM] ? rcat
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1 is
/u01/app/oracle
$
```

- 3) Shut down the database with the `IMMEDIATE` option, then mount it.

```
$ sqlplus / as sysdba

SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.

SQL> startup mount
ORACLE instance started.

Total System Global Area  318046208 bytes
Fixed Size                  1336244 bytes
Variable Size             251661388 bytes
Database Buffers           58720256 bytes
Redo Buffers                6328320 bytes
```

Practice 6-1: Backing up the Database (continued)

```
Database mounted.  
SQL> exit
```

- 4) Make a whole database image copy backup into the \$HOME/BACKUP directory using RMAN commands.

```
$ rman target /  
  
Recovery Manager: Release 11.2.0.1.0 - Production on Tue Jul 21  
22:26:33 2009  
  
Copyright (c) 1982, 2009, Oracle and/or its affiliates. All rights  
reserved.  
  
connected to target database: RCAT (DBID=464959795, not open)  
  
RMAN> backup database format '/home/oracle/BACKUP/cold_%U';  
  
Starting backup at 2009-07-29:08:11:12  
using target database control file instead of recovery catalog  
allocated channel: ORA_DISK_1  
channel ORA_DISK_1: SID=1 device type=DISK  
channel ORA_DISK_1: starting full datafile backup set  
channel ORA_DISK_1: specifying datafile(s) in backup set  
input datafile file number=00001  
name=+DATA/rcat/datafile/system.267.692935353  
input datafile file number=00002  
name=+DATA/rcat/datafile/sysaux.268.692935357  
input datafile file number=00003  
name=+DATA/rcat/datafile/undotbs1.269.692935357  
input datafile file number=00005  
name=+DATA/rcat/datafile/rcat.277.692937003  
input datafile file number=00004  
name=+DATA/rcat/datafile/users.270.692935359  
channel ORA_DISK_1: starting piece 1 at 2009-07-29:08:11:13  
channel ORA_DISK_1: finished piece 1 at 2009-07-29:08:13:08  
piece handle=/home/oracle/BACKUP/cold_0fklb6h1_1_1  
tag=TAG20090729T081113 comment=NONE  
channel ORA_DISK_1: backup set complete, elapsed time: 00:01:55  
Finished backup at 2009-07-29:08:13:08  
  
Starting Control File and SPFILE Autobackup at 2009-07-29:08:13:09  
piece handle=+FRA/rcat/autobackup/2009_07_29/s_693475040.330.693475991  
comment=NONE  
Finished Control File and SPFILE Autobackup at 2009-07-29:08:13:16  
RMAN> exit
```

- 5) Open the RCAT database.

```
$ . oraenv  
ORACLE_SID = [rcat] ? rcat  
sqlplus / as sysdba  
  
SQL> alter database open;  
  
Database altered.
```

Practice 6-1: Backing up the Database (continued)

6) Use the ALTER DATABASE command to back up the control file as a trace file.

```
SQL> alter database backup controlfile to trace as  
'/home/oracle/BACKUP/trace_control.bck';
```

```
Database altered.
```

```
SQL> exit
```

7) View the content of the /home/oracle/BACKUP directory.

```
$ ls -l /home/oracle/BACKUP
```

```
total 1100568
```

```
-rw-r----- 1 oracle dba 1125867520 Jul 29 08:12 cold_0fklb6h1_1_1
```

```
-rw-r--r-- 1 oracle dba          6601 Jul 29 08:18 trace_control.bck
```

```
$
```

Practice 6-2: Recovering from the Loss of a Data File

Because ASM does not expose its files to the operating system, you create tablespaces with data files in a regular file system destination, so that you can setup various learning situations in the following practices.

In the ORCL database, you create the BR_TBS tablespace with the CUSTOMERS table.

- 1) Log into the ORCL instance with SQL*Plus as the SYS user.

```
$ . oraenv
ORACLE_SID = [rcat] ? orcl

$ sqlplus / as sysdba

SQL>
```

- 2) Create the BR_TBS tablespace with the CUSTOMERS table.

```
SQL> CREATE TABLESPACE br_tbs
      DATAFILE '/home/oracle/BACKUP/br01.dbf' SIZE 25M;

Tablespace created.

SQL> CREATE TABLE customers tablespace br_tbs
      AS SELECT * FROM sh.customers;

Table created.

SQL>
```

- 3) Find out the number of your new data file and back up the data files to the /home/oracle/BACKUP directory. (You might find it useful to keep the SQL*Plus window open and start the RMAN session in another terminal window, but it is not mandatory.)

```
$ . oraenv
ORACLE_SID = [+ASM] ? orcl

$ rman target / catalog rcatowner@rcat

connected to target database: ORCL (DBID=1220535480)
recovery catalog database Password: oracle_4U <<<not displayed
connected to recovery catalog database

RMAN> report schema;
starting full resync of recovery catalog
full resync complete
Report of database schema for database with db_unique_name ORCL

List of Permanent Datafiles
=====
File Size(MB) Tablespace          RB segs Datafile Name
```

Practice 6-2: Recovering from the Loss of a Data File (continued)

```
-----  
1      690      SYSTEM      YES  
+DATA/orcl/datafile/system.256.692754557  
2      610      SYSAUX      NO  
+DATA/orcl/datafile/sysaux.257.692754559  
3      100      UNDOTBS1    YES  
+DATA/orcl/datafile/undotbs1.258.692754561  
4       5       USERS      NO  
+DATA/orcl/datafile/users.259.692754561  
5      100      EXAMPLE     NO  
+DATA/orcl/datafile/example.265.692754837
```

```
6       25      BR_TBS      NO  
/home/oracle/BACKUP/br01.dbf
```

List of Temporary Files

```
=====  
File Size(MB) Tablespace      Maxsize(MB) Tempfile Name  
-----  
--  
1      28      TEMP          32767  
+DATA/orcl/tempfile/temp.264.692754825
```

```
RMAN> backup as copy datafile 6 format  
'/home/oracle/BACKUP/br_%d_%s_%p.dbf';
```

```
Starting backup at 2009-07-29:08:38:47  
allocated channel: ORA_DISK_1  
channel ORA_DISK_1: SID=29 device type=DISK  
channel ORA_DISK_1: starting datafile copy  
input datafile file number=00006  
name=/home/oracle/BACKUP/br01.dbf  
output file name=/home/oracle/BACKUP/br_ORCL_22_1.dbf  
tag=TAG20090729T083848 RECID=5 STAMP=693477530  
channel ORA_DISK_1: datafile copy complete, elapsed time:  
00:00:03  
Finished backup at 2009-07-29:08:38:51
```

```
Starting Control File and SPFILE Autobackup at 2009-07-  
29:08:38:51  
piece  
handle=+FRA/orcl/autobackup/2009_07_29/s_693477533.332.693477535  
comment=NONE  
Finished Control File and SPFILE Autobackup at 2009-07-  
29:08:38:54  
RMAN>
```

- 4) To simulate the passage of time, and to make sure that this data is not cached in the buffer cache, perform the following steps and exit from SQL*Plus.

```
SQL> alter system switch logfile;  
  
System altered;
```

Practice 6-2: Recovering from the Loss of a Data File (continued)

```
SQL> alter system checkpoint;
System altered.
SQL> alter system switch logfile;
System altered
SQL> exit
```

5) Delete the data file belonging to the BR_TBS tablespace (**not** the backup).

```
$ cd ~/BACKUP
$ ls -l br*
-rw-r----- 1 oracle dba 26222592 Jul 22 20:57 br01.dbf
-rw-r----- 1 oracle dba 26222592 Jul 22 20:52 br_ORCL_22_1.dbf
$ rm br01.dbf
$ ls -l br*
-rw-r----- 1 oracle dba 26222592 Jul 22 20:52 br_ORCL_22_1.dbf
$
```

6) Now log back in to the database, flush the buffer cache and try to access the data in the CUSTOMERS table.

```
$ sqlplus / as sysdba

SQL> alter system flush buffer_cache;
System altered.

SQL> select count(*) from sys.customers;
select count(*) from sys.customers

ERROR at line 1:
ORA-01116: error in opening database file 6
ORA-01110: data file 6: '/home/oracle/BACKUP/br01.dbf'
ORA-27041: unable to open file
Linux Error: 2: No such file or directory
Additional information: 3
```

7) Knowing you are going to have to restore this file, you now take it offline, and exit from SQL*Plus.

```
SQL> alter database datafile 6 offline;

Database altered.

SQL> exit
```

Practice 6-2: Recovering from the Loss of a Data File (continued)

- 8) Now navigate to your \$HOME/BACKUP directory, to find what backups you have of the data file. Then choose the most recent, and copy *YOUR* file into where the live one should be.

```
$ cd /home/oracle/BACKUP/

$ ls -al
total 1126216
drwxr-xr-x  2 oracle oinstall          4096 Jul 29 08:42 .
drwxrwxrwx 24 oracle oinstall          4096 Jul 29 08:02 ..
-rw-r----- 1 oracle dba             26222592 Jul 29 08:38 br_ORCL_22_1.dbf
-rw-r----- 1 oracle dba          1125867520 Jul 29 08:12 cold_0fklb6h1_1_1
-rw-r--r--  1 oracle dba              6601 Jul 29 08:18 trace_control.bck

$ cp br_ORCL_22_1.dbf br01.dbf
$ ls -l
-rw-r----- 1 oracle oinstall  26222592 Jul 29 08:38 br01.dbf
-rw-r----- 1 oracle dba       26222592 Jul 29 08:38 br_ORCL_22_1.dbf
-rw-r----- 1 oracle dba       1125867520 Jul 29 08:12 cold_0fklb6h1_1_1
-rw-r--r--  1 oracle dba        6601 Jul 29 08:18 trace_control.bck
```

- 9) Now log in to SQL*Plus and try to bring the file online.

```
$ sqlplus / as sysdba

SQL> alter database datafile 6 online;
alter database datafile 6 online
*
ERROR at line 1:
ORA-01113: file 6 needs media recovery
ORA-01110: data file 6: '/home/oracle/BACKUP/br01.dbf'
```

- 10) The data file cannot be brought online as it is too old and, therefore, you need to perform media recovery to roll it forward.

```
SQL> recover datafile 6;
Media recovery complete.
SQL>
```

- 11) Now try to bring the data file online.

```
SQL> alter database datafile 6 online;

Database altered.
```

- 12) Try again to access the sys.customers table, and then exit SQL*Plus.

```
SQL> select count(*) from sys.customers;

COUNT(*)
-----
```


Practice 6-2: Recovering from the Loss of a Data File (continued)

```
55500
```

```
SQL> exit
```

- 13) For the ORCL database, confirm that the control file is automatically backed up and that the backup retention is set to 1 (if not, modify it), take a database backup and delete obsolete files (in preparation for the following practices).

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl

$ rman target / catalog rcatowner@rcat

connected to target database: ORCL (DBID=1220535480)
recovery catalog database Password: oracle_4U <<<not displayed
connected to recovery catalog database

RMAN> show retention policy;

RMAN configuration parameters for database with db_unique_name
ORCL are:
CONFIGURE RETENTION POLICY TO REDUNDANCY 1; # default
RMAN>
RMAN> backup database;
Starting backup
.
.
.
RMAN>

RMAN> delete noprompt obsolete;
RMAN retention policy will be applied to the command
.
.
.
RMAN> exit
$
```

Practice 6-3: Recovering from the Loss of all Control Files

This practice makes use of the ORCL database and the recovery catalog. You will simulate the loss of all control files, and then restore the control files and recover the database.

- 1) Connect to the ORCL database and make a binary backup of the control file.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$ sqlplus / as sysdba

SQL> alter database backup controlfile to
'/home/oracle/BACKUP/ctrl.bkp';
Database altered.
```

- 2) Identify the current control files for the ORCL database. You need to know them in one of the following tasks. Then shutdown the ORCL database to allow the control files to be deleted and exit SQL*Plus.

```
SQL> select name from v$controlfile;

NAME
-----
+DATA/orcl/controlfile/current.260.692879691
+FRA/orcl/controlfile/current.256.692879691

SQL> shutdown immediate;
Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> exit
```

- 3) Set the environment to the ASM instance and run the asmcmd utility to delete the two control files identified above.

Note: The names of your control files may be different. Delete **YOUR** control files.

```
$ . oraenv
ORACLE_SID = [orcl] ? +ASM
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/grid is
/u01/app/oracle

$ asmcmd rm +DATA/orcl/controlfile/current.260.692879691
$ asmcmd rm +FRA/orcl/controlfile/current.256.692879691
```

- 4) Set the environment back to the ORCL database and attempt to start up the database.

```
$ . oraenv
ORACLE_SID = [+ASM] ? orcl
```

Practice 6-3: Recovering from the Loss of all Control Files (continued)

```
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1 is
/u01/app/oracle

$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Wed Jul 29 10:03:55
2009
Copyright (c) 1982, 2009, Oracle. All rights reserved.

Connected to an idle instance.

SQL> startup
ORACLE instance started.

Total System Global Area  418484224 bytes
Fixed Size                  1336908 bytes
Variable Size              268437940 bytes
Database Buffers           142606336 bytes
Redo Buffers                6103040 bytes
ORA-00205: error in identifying control file, check alert log for
more info

SQL> exit
```

- 5) Using RMAN, connect to the ORCL target database, to the RCAT catalog database, and restore the control file from the autobackup.

```
$ rman target / catalog rcatowner@rcat

Recovery Manager: Release 11.2.0.1.0 - Production on Wed Jul 29
10:06:22 2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All
rights reserved.

connected to target database: ORCL (not mounted)
recovery catalog database Password: oracle_4U <<<not displayed
connected to recovery catalog database

RMAN> restore controlfile from autobackup;

Starting restore at 2009-07-29:10:06:48
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=27 device type=DISK

recovery area destination: +FRA
database name (or database unique name) used for search: ORCL
```

Practice 6-3: Recovering from the Loss of all Control Files (continued)

```
channel ORA_DISK_1: AUTOBACKUP
+fra/ORCL/AUTOBACKUP/2009_07_29/s_693478885.335.693478885 found
in the recovery area
channel ORA_DISK_1: looking for AUTOBACKUP on day: 20090729
channel ORA_DISK_1: restoring control file from AUTOBACKUP
+fra/ORCL/AUTOBACKUP/2009_07_29/s_693478885.335.693478885
channel ORA_DISK_1: control file restore from AUTOBACKUP complete
output file name=+DATA/orcl/controlfile/current.260.693482811
output file name=+FRA/orcl/controlfile/current.256.693482813
Finished restore at 2009-07-29:10:06:54/
```

6) Mount the restored control file and attempt to open the database.

```
RMAN> alter database mount;
database mounted
released channel: ORA_DISK_1
RMAN> alter database open resetlogs;
RMAN-00571:
=====
RMAN-00569: ===== ERROR MESSAGE STACK FOLLOWS
=====
RMAN-00571:
=====
RMAN-03002: failure of alter db command at 07/29/2009 10:08:45
ORA-01152: file 1 was not restored from a sufficiently old backup
ORA-01110: data file 1:
'+DATA/orcl/datafile/system.256.692879503'
```

7) Because the control files have been restored, the database must be recovered.

```
RMAN> recover database;
Starting recover at 2009-07-29:10:08:58
Starting implicit crosscheck backup at 2009-07-29:10:08:58
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=27 device type=DISK
Crosschecked 12 objects
Finished implicit crosscheck backup at 2009-07-29:10:09:00

Starting implicit crosscheck copy at 2009-07-29:10:09:00
using channel ORA_DISK_1
Crosschecked 4 objects
Finished implicit crosscheck copy at 2009-07-29:10:09:01
searching for all files in the recovery area
cataloging files...
cataloging done
List of Cataloged Files
=====
File Name:
+fra/ORCL/AUTOBACKUP/2009_07_29/s_693478885.335.693478885
using channel ORA_DISK_1
```

Practice 6-3: Recovering from the Loss of all Control Files (continued)

```
starting media recovery
```

```
archived log for thread 1 with sequence 59 is already on disk as  
file +DATA/orcl/onlinelog/group_2.262.692879707  
archived log file name=+DATA/orcl/onlinelog/group_2.262.692879707  
thread=1 sequence=59  
media recovery complete, elapsed time: 00:00:01  
Finished recover at 2009-07-29:10:09:05
```

8) Attempt to open the database with the RESETLOGS option after recovery.

```
RMAN> alter database open resetlogs;
```

```
database opened  
new incarnation of database registered in recovery catalog  
starting full resync of recovery catalog  
full resync complete
```

9) Perform a full database backup and delete obsolete files to be prepared for future labs.

```
RMAN> backup database;
```

```
Starting backup at 2009-07-29:10:49:21  
allocated channel: ORA_DISK_1  
channel ORA_DISK_1: SID=46 device type=DISK  
channel ORA_DISK_1: starting full datafile backup set  
channel ORA_DISK_1: specifying datafile(s) in backup set  
input datafile file number=00002  
name=+DATA/orcl/datafile/sysaux.257.692879505  
channel ORA_DISK_1: starting piece 1 at 2009-07-29:10:49:22  
channel ORA_DISK_1: finished piece 1 at 2009-07-29:10:50:18  
piece  
handle=+FRA/orcl/backupset/2009_07_29/nnndf0_tag20090729t104922_0  
.340.693485363 tag=TAG20090729T104922 comment=NONE  
channel ORA_DISK_1: backup set complete, elapsed time: 00:00:56  
channel ORA_DISK_1: starting full datafile backup set  
channel ORA_DISK_1: specifying datafile(s) in backup set  
input datafile file number=00001  
name=+DATA/orcl/datafile/system.256.692879503  
channel ORA_DISK_1: starting piece 1 at 2009-07-29:10:50:22  
channel ORA_DISK_1: finished piece 1 at 2009-07-29:10:52:04  
piece  
handle=+FRA/orcl/backupset/2009_07_29/nnndf0_tag20090729t104922_0  
.341.693485425 tag=TAG20090729T104922 comment=NONE  
channel ORA_DISK_1: backup set complete, elapsed time: 00:01:42  
channel ORA_DISK_1: starting full datafile backup set  
channel ORA_DISK_1: specifying datafile(s) in backup set  
input datafile file number=00006  
name=/home/oracle/BACKUP/br01.dbf
```

Practice 6-3: Recovering from the Loss of all Control Files (continued)

```
input datafile file number=00003
name=+DATA/orcl/datafile/undotbs1.258.692879507
input datafile file number=00004
name=+DATA/orcl/datafile/users.259.692879509
input datafile file number=00005
name=+DATA/orcl/datafile/example.265.692879765
channel ORA_DISK_1: starting piece 1 at 2009-07-29:10:52:11
channel ORA_DISK_1: finished piece 1 at 2009-07-29:10:52:57
piece
handle=+FRA/orcl/backupset/2009_07_29/nnndf0_tag20090729t104922_0
.342.693485537 tag=TAG20090729T104922 comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time: 00:00:46
Finished backup at 2009-07-29:10:52:57

Starting Control File and SPFILE Autobackup at 2009-07-
29:10:52:57
piece
handle=+FRA/orcl/autobackup/2009_07_29/s_693485589.343.693485603
comment=NONE
Finished Control File and SPFILE autobackup at 2009-07-29:10:53

RMAN> delete noprompt obsolete;
. . .

RMAN> exit
```

Practice 6-4: Recovering from the Loss of a Redo Log Group

This practice makes use of the ORCL database. You will delete the current redo log files, and see the effect this has on the database.

- 1) Log in to the ORCL database using SQL*Plus, and run the redo_view.sql query to gather information about your redo logs.

```
$ sqlplus / as sysdba
```

```
SQL> @redo_view.sql
```

```
SQL> set linesize 120
```

```
SQL> col member format a43
```

```
SQL> col status format a10
```

```
SQL> select l.group#, l.sequence#, l.archived,
2 l.status, f.member
3 from v$log l, v$logfile f
4 where l.group#=f.group#;
```

GROUP#	SEQUENCE#	ARC	STATUS	MEMBER
3	0	YES	UNUSED	+DATA/orcl/onlinelog/group_3.263.692879721
3	0	YES	UNUSED	+FRA/orcl/onlinelog/group_3.259.692879727
2	0	YES	UNUSED	+DATA/orcl/onlinelog/group_2.262.692879707
2	0	YES	UNUSED	+FRA/orcl/onlinelog/group_2.258.692879715
1	1	NO	CURRENT	+DATA/orcl/onlinelog/group_1.261.692879693
1	1	NO	CURRENT	+FRA/orcl/onlinelog/group_1.257.692879701

6 rows selected.
SQL>

- 2) From this it can be seen in our example that log group 1 is the current log group. Your current redo log group may be different from the one shown. Note the exact group names of your current group. You need the names during the next step.

Determine the current redo log group for your database, and then delete its member files with the asmcmd utility. You must shutdown the database in order to delete files that are in use in an ASM disk group.

```
SQL> shutdown immediate
```

```
Database closed.
```

```
Database dismounted.
```

```
ORACLE instance shut down.
```

Practice 6-4: Recovering from the Loss of a Redo Log Group (continued)

```
SQL> exit
```

```
$ . oraenv
ORACLE_SID = [orcl] ? +ASM
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/grid is
/u01/app/oracle
$ asmcmd rm +DATA/orcl/onlinelog/group_1.261.692879693
$ asmcmd rm +FRA/orcl/onlinelog/group_1.257.692879701
```

- 3) Attempt to start the ORCL database and observe what happens. Then exit your SQL*Plus session.

```
$ . oraenv
ORACLE_SID = [+ASM] ? orcl
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1 is
/u01/app/oracle
$ sqlplus / as sysdba

SQL*Plus: Release 11.2.0.1.0 Production on Tue Aug 4 03:07:48
2009
Copyright (c) 1982, 2009, Oracle. All rights reserved.
Connected to an idle instance.

SQL> startup
ORACLE instance started.

Total System Global Area 481259520 bytes
Fixed Size 1337352 bytes
Variable Size 411043832 bytes
Database Buffers 62914560 bytes
Redo Buffers 5963776 bytes
Database mounted.
ORA-03113: end-of-file on communication channel
Process ID: 29445
Session ID: 1 Serial number: 5
SQL> exit
```

- 4) Display the last section of the alert log to find out more details related to the failure in starting the ORCL instance.

```
$ tail /u01/app/oracle/diag/rdbms/orcl/orcl/trace/alert_orcl.log
ORA-15012: ASM file '+FRA/orcl/onlinelog/group_1.257.692879701'
does not exist
ORA-00312: online log 1 thread 1:
'+DATA/orcl/onlinelog/group_1.261.692879693'
ORA-17503: ksfdopn:2 Failed to open file
+DATA/orcl/onlinelog/group_1.261.692879693
```


Practice 6-4: Recovering from the Loss of a Redo Log Group (continued)

```
ORA-15012: ASM file '+DATA/orcl/onlinelog/group_1.261.692879693'
does not exist
Errors in file
/u01/app/oracle/diag/rdbms/orcl/orcl/trace/orcl_ora_15563.trc:
ORA-00313: open failed for members of log group 1 of thread
ORA-00312: online log 1 thread 1:
'+DATA/orcl/onlinelog/group_1.261.692879693'
ORA-00312: online log 1 thread 1:
'+FRA/orcl/onlinelog/group_1.257.692879701'
USER (ospid: 15563): terminating the instance due to error 313
Instance terminated by USER, pid = 15563
```

As you can observe, the instance terminates due to missing all the members of your log group.

- 5) Log into SQL*Plus as SYSDBA, start up and mount the ORCL instance. Query the V\$LOG view to determine which log group is the current group and whether its files have been archived already.

```
$ sqlplus / as sysdba

SQL> startup mount
ORACLE instance started.

Total System Global Area 481259520 bytes
Fixed Size 1337352 bytes
Variable Size 411043832 bytes
Database Buffers 62914560 bytes
Redo Buffers 5963776 bytes
Database mounted.

SQL> select group#,status,archived from v$log;
```

GROUP#	STATUS	ARC
1	CURRENT	NO
3	UNUSED	YES
2	UNUSED	YES

- 6) If you clear **YOUR** missing log file group, then this will re-create the missing log files.

```
SQL> alter database clear logfile group 1;
alter database clear logfile group 1
*
ERROR at line 1:
ORA-00350: log 1 of instance orcl (thread 1) needs to be archived
ORA-00312: online log 1 thread 1:
'+DATA/orcl/onlinelog/group_1.261.693969247'
```

Practice 6-4: Recovering from the Loss of a Redo Log Group (continued)

```
ORA-00312: online log 1 thread 1:
'+FRA/orcl/onlinelog/group_1.257.693969255'
```

This is because the logfile has been deleted, and therefore cannot be archived. Because the log file has not been archived, lgwr is not allowed to overwrite it, even if the file no longer exists.

- 7) Because the logfile group has not been archived, you must use the keyword “unarchived” in the command. Open the database and exit SQL*Plus.

```
SQL> alter database clear unarchived logfile group 1;
Database altered.

SQL> alter database open;
Database altered.

SQL> exit
```

- 8) Perform a backup of the ORCL database including archive logs to be ready for future labs.

```
$ rman target / catalog rcatowner@rcat

Recovery Manager: Release 11.2.0.1.0 - Production on Wed Jul 29
10:49:07 2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All
rights reserved.

connected to target database: ORCL (DBID=1220660426)
recovery catalog database Password: oracle_4U <<<not displayed
connected to recovery catalog database

RMAN> backup database plus archivelog;
...
Finished backup at 20-AUG-09

Starting Control File and SPFILE Autobackup at 20-AUG-09
piece
handle=+FRA/orcl/autobackup/2009_08_20/s_695409765.279.695409767
comment=NONE
Finished Control File and SPFILE Autobackup at 20-AUG-09

RMAN> delete noprompt obsolete;
...

Deleted 2 objects

RMAN> exit
```

Note: Your number of deleted objects will most likely be different.

Practice 7-1: Recovering Image Copies

In this practice, you recover an image copy of a file to the current SCN, to allow faster recovery time later. You create a new tablespace called APPRAISAL, which has one table in it. After creating it initially with a small amount of data, you take an incremental backup of it. Then you add many rows and take another incremental backup. At that point, you have an image copy of the APPRAISAL tablespace and also an incremental backup of it. Because you need to recover the tablespace later, you recover the image copy so that it is as up-to-date as the last incremental backup. This is done without going to the expense of creating a new image copy.

- 1) Make sure you are at the ~/labs directory and run the `create_appraisal_ts.sh` script to create a new tablespace called APPRAISAL.

```
$ cd ~/labs
$ ./create_appraisal_ts.sh
Tablespace created.
Table created.
$
```

- 2) Make a level 1 backup of the tablespace, to be used for image copy recovery. If no level 1 exists yet, it will actually create a level 0 incremental backup. This takes several minutes.

```
$ rman target / catalog rcatowner@rcat
Recovery Manager: Release 11.2.0.1.0 - Production on Wed Jul 29
10:49:07 2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All rights
reserved.

connected to target database: ORCL (DBID=1220660426)
recovery catalog database Password: oracle_4U <<<not displayed
connected to recovery catalog database

RMAN> backup incremental level 1 for recover of copy with tag
'app_incr' database;

Starting backup at 2009-08-05:03:00:24
starting full resync of recovery catalog
full resync complete
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=58 device type=DISK
no parent backup or copy of datafile 1 found
no parent backup or copy of datafile 2 found
no parent backup or copy of datafile 5 found
no parent backup or copy of datafile 3 found
```

Practice 7-1: Recovering Image Copies (continued)

```

no parent backup or copy of datafile 6 found
no parent backup or copy of datafile 7 found
no parent backup or copy of datafile 4 found
channel ORA_DISK_1: starting datafile copy
input datafile file number=00001
name=+DATA/orcl/datafile/system.260.694050517
output file name=+FRA/orcl/datafile/system.301.694062029
tag=APP_INCR RECID=6 STAMP=694062094
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:01:16
channel ORA_DISK_1: starting datafile copy
input datafile file number=00002
name=+DATA/orcl/datafile/sysaux.266.694050521
output file name=+FRA/orcl/datafile/sysaux.300.694062109
tag=APP_INCR RECID=7 STAMP=694062216
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:01:56
channel ORA_DISK_1: starting datafile copy
input datafile file number=00005
name=+DATA/orcl/datafile/example.259.694050813
output file name=+FRA/orcl/datafile/example.298.694062227
tag=APP_INCR RECID=8 STAMP=694062237
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:00:15
channel ORA_DISK_1: starting datafile copy
input datafile file number=00003
name=+DATA/orcl/datafile/undotbs1.278.694050521
output file name=+FRA/orcl/datafile/undotbs1.297.694062243
tag=APP_INCR RECID=9 STAMP=694062251
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:00:15
channel ORA_DISK_1: starting datafile copy
input datafile file number=00006 name=/home/oracle/BACKUP/br01.dbf
output file name=+FRA/orcl/datafile/br_tbs.296.694062259
tag=APP_INCR RECID=10 STAMP=694062265
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:00:21
channel ORA_DISK_1: starting datafile copy
input datafile file number=00007
name=+DATA/orcl/datafile/appraisal.256.694061937
output file name=+FRA/orcl/datafile/appraisal.295.694062283
tag=APP_INCR RECID=11 STAMP=694062285
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:00:08
channel ORA_DISK_1: starting datafile copy
input datafile file number=00004
name=+DATA/orcl/datafile/users.264.694050521
output file name=+FRA/orcl/datafile/users.294.694062289 tag=APP_INCR
RECID=12 STAMP=694062289
channel ORA_DISK_1: datafile copy complete, elapsed time: 00:00:03
Finished backup at 2009-08-05:03:04:51

Starting Control File and SPFILE Autobackup at 2009-08-05:03:04:51
piece
handle=+FRA/orcl/autobackup/2009_08_05/s_694062294.292.694062307
comment=NONE
Finished Control File and SPFILE Autobackup at 2009-08-05:03:05:09

RMAN>

```

- 3) In a separate terminal window, perform some DML on the table in the APPRAISAL tablespace. Use the emp_inserts.sh script.

Practice 7-1: Recovering Image Copies (continued)

```
$ cd ~/labs
$ ./emp_inserts.sh

107 rows created.

Commit complete.

214 rows created.

Commit complete.

$
```

- 4) List the copy of the APPRAISAL tablespace to see its SCN.

```
RMAN> list copy of tablespace appraisal;

List of Datafile Copies
=====

Key          File S Completion Time      Ckp SCN      Ckp Time
-----
1975         7      A 2009-08-05:03:04:45 853719      2009-08-
05:03:04:39
              Name: +FRA/orcl/datafile/appraisal.295.694062283
              Tag: APP_INCR
RMAN>
```

- 5) Run the script to perform more transactions on the table that resides in the APPRAISAL tablespace.

```
$ ./emp_inserts.sh

428 rows created.

Commit complete.

856 rows created.

Commit complete.

$
```

- 6) Perform another level 1 backup. This one will indeed be a level 1 because you already have a level 0.

```
RMAN> backup incremental level 1 for recover of copy with tag
'app_incr' database;

Starting backup at 2009-08-05:03:25:48
using channel ORA_DISK_1
```

Practice 7-1: Recovering Image Copies (continued)

```
channel ORA_DISK_1: starting incremental level 1 datafile
backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
input datafile file number=00001
name=+DATA/orcl/datafile/system.260.694050517
channel ORA_DISK_1: starting piece 1 at 2009-08-05:03:25:49
channel ORA_DISK_1: finished piece 1 at 2009-08-05:03:25:50
piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.285.69
4063549 tag=APP_INCR comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:01
channel ORA_DISK_1: starting incremental level 1 datafile
backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
input datafile file number=00002
name=+DATA/orcl/datafile/sysaux.266.694050521
channel ORA_DISK_1: starting piece 1 at 2009-08-05:03:25:51
channel ORA_DISK_1: finished piece 1 at 2009-08-05:03:25:54
piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.284.69
4063551 tag=APP_INCR comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:03
channel ORA_DISK_1: starting incremental level 1 datafile
backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
input datafile file number=00006
name=/home/oracle/BACKUP/br01.dbf
input datafile file number=00003
name=+DATA/orcl/datafile/undotbs1.278.694050521
input datafile file number=00004
name=+DATA/orcl/datafile/users.264.694050521
input datafile file number=00005
name=+DATA/orcl/datafile/example.259.694050813
input datafile file number=00007
name=+DATA/orcl/datafile/appraisal.256.694061937
channel ORA_DISK_1: starting piece 1 at 2009-08-05:03:25:54
channel ORA_DISK_1: finished piece 1 at 2009-08-05:03:25:55
piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.277.69
4063555 tag=APP_INCR comment=NONE
channel ORA_DISK_1: backup set complete, elapsed time:
00:00:01
Finished backup at 2009-08-05:03:25:55

Starting Control File and SPFILE Autobackup at 2009-08-
05:03:25:55
piece
handle=+FRA/orcl/autobackup/2009_08_05/s_694063556.261.6940635
57 comment=NONE
```

Practice 7-1: Recovering Image Copies (continued)

```
Finished Control File and SPFILE Autobackup at 2009-08-
05:03:25:59
RMAN>
```

- 7) List **and note** the SCN of the APPRAISAL tablespace incremental backup (not the image copy).

```
RMAN> list backup of tablespace appraisal;

List of Backup Sets
=====

BS Key   Type LV Size          Device Type Elapsed Time Completion
Time
-----
2036     Incr 1   2.24M          DISK          00:00:00      2009-08-
05:03:25:54
        BP Key: 2041   Status: AVAILABLE   Compressed: NO   Tag:
APP_INCR
        Piece Name:
+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.277.694063555
  List of Datafiles in backup set 2036
  File LV Type Ckp SCN      Ckp Time          Name
  ----
  7      1  Incr 855661    2009-08-05:03:25:54
+DATA/orcl/datafile/appraisal.256.694061937
RMAN>
```

- 8) Use the incremental backup to recover the APPRAISAL tablespace image copy.

```
RMAN> recover copy of tablespace appraisal with tag
'app_incr';

Starting recover at 2009-08-05:03:29:20
using channel ORA_DISK_1
channel ORA_DISK_1: starting incremental datafile backup set
restore
channel ORA_DISK_1: specifying datafile copies to recover
recovering datafile copy file number=00007
name=+FRA/orcl/datafile/appraisal.288.694063519
channel ORA_DISK_1: reading from backup piece
+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.277.694063555
channel ORA_DISK_1: piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.277.69
4063555 tag=APP_INCR
channel ORA_DISK_1: restored backup piece 1
channel ORA_DISK_1: restore complete, elapsed time: 00:00:01
Finished recover at 2009-08-05:03:29:21

Starting Control File and SPFILE Autobackup at 2009-08-
05:03:29:21
```

Practice 7-1: Recovering Image Copies (continued)

```
piece
handle=+FRA/orcl/autobackup/2009_08_05/s_694063763.260.6940637
63 comment=NONE
Finished Control File and SPFILE Autobackup at 2009-08-
05:03:29:26
RMAN>
```

- 9) List the SCN for the APPRAISAL tablespace image copy. What is it now?

```
RMAN> list copy of tablespace appraisal;
```

```
List of Datafile Copies
```

```
=====
```

Key	File S	Completion Time	Ckp SCN	Ckp Time
2090	7	A 2009-08-05:03:29:20	855661	2009-08-05:03:25:54
Name: +FRA/orcl/datafile/appraisal.288.694063519				
Tag: APP_INCR				

```
RMAN>
```

Note that it is now equal to the SCN of the last incremental backup.

- 10) Recover all the data file image copies in the database based on the most recent incremental backup.

```
RMAN> recover copy of database with tag 'app_incr';
```

```
Starting recover at 2009-08-05:03:33:29
using channel ORA_DISK_1
no copy of datafile 7 found to recover
channel ORA_DISK_1: starting incremental datafile backup set
restore
channel ORA_DISK_1: specifying datafile copies to recover
recovering datafile copy file number=00001
name=+FRA/orcl/datafile/system.291.694063333
channel ORA_DISK_1: reading from backup piece
+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.285.694063549
channel ORA_DISK_1: piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.285.69
4063549 tag=APP_INCR
channel ORA_DISK_1: restored backup piece 1
channel ORA_DISK_1: restore complete, elapsed time: 00:00:01
channel ORA_DISK_1: starting incremental datafile backup set
restore
channel ORA_DISK_1: specifying datafile copies to recover
recovering datafile copy file number=00002
name=+FRA/orcl/datafile/sysaux.316.694063393
channel ORA_DISK_1: reading from backup piece
+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.284.694063551
```


Practice 7-1: Recovering Image Copies (continued)

```
channel ORA_DISK_1: piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.284.69
4063551 tag=APP_INCR
channel ORA_DISK_1: restored backup piece 1
channel ORA_DISK_1: restore complete, elapsed time: 00:00:01
channel ORA_DISK_1: starting incremental datafile backup set
restore
channel ORA_DISK_1: specifying datafile copies to recover
recovering datafile copy file number=00003
name=+FRA/orcl/datafile/undotbs1.290.694063491
recovering datafile copy file number=00004
name=+FRA/orcl/datafile/users.283.694063527
recovering datafile copy file number=00005
name=+FRA/orcl/datafile/example.307.694063477
recovering datafile copy file number=00006
name=+FRA/orcl/datafile/br_tbs.289.694063517
channel ORA_DISK_1: reading from backup piece
+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.277.694063555
channel ORA_DISK_1: piece
handle=+FRA/orcl/backupset/2009_08_05/nnndn1_app_incr_0.277.69
4063555 tag=APP_INCR
channel ORA_DISK_1: restored backup piece 1
channel ORA_DISK_1: restore complete, elapsed time: 00:00:01
Finished recover at 2009-08-05:03:33:33

Starting Control File and SPFILE Autobackup at 2009-08-
05:03:33:33
piece
handle=+FRA/orcl/autobackup/2009_08_05/s_694064014.262.6940640
15 comment=NONE
Finished Control File and SPFILE Autobackup at 2009-08-
05:03:33:37
RMAN>
```

- 11) View the SCNs of all the image copies now. They should all be, at the most, equal to the latest incremental backup.

```
RMAN> list copy;

specification does not match any control file copy in the
repository
List of Datafile Copies
=====
```

Key	File S	Completion Time	Ckp SCN	Ckp Time
2144	1	A 2009-08-05:03:33:30	855654	2009-08-05:03:25:49
Name: +FRA/orcl/datafile/system.291.694063333				
Tag: APP_INCR				

Practice 7-1: Recovering Image Copies (continued)

```

2145      2      A 2009-08-05:03:33:31 855657      2009-08-
05:03:25:51
          Name: +FRA/orcl/datafile/sysaux.316.694063393
          Tag: APP_INCR

2149      3      A 2009-08-05:03:33:32 855661      2009-08-
05:03:25:54
          Name: +FRA/orcl/datafile/undotbs1.290.694063491
          Tag: APP_INCR

2148      4      A 2009-08-05:03:33:32 855661      2009-08-
05:03:25:54
          Name: +FRA/orcl/datafile/users.283.694063527
          Tag: APP_INCR

1491      4      A 2009-08-05:02:19:40 847825      2009-08-
05:02:19:40
          Name: +FRA/orcl/datafile/users.299.694059581
          Tag: TAG20090805T021940

1436      4      A 2009-08-05:02:18:41 847727      2009-08-
05:02:18:41
          Keep: BACKUP_LOGS      Until: FOREVER
          Name: /tmp/bu_ORCL_17_1.dbf
          Tag: TAG20090805T021838

2146      5      A 2009-08-05:03:33:32 855661      2009-08-
05:03:25:54
          Name: +FRA/orcl/datafile/example.307.694063477
          Tag: APP_INCR

2147      6      A 2009-08-05:03:33:32 855661      2009-08-
05:03:25:54
          Name: +FRA/orcl/datafile/br_tbs.289.694063517
          Tag: APP_INCR

1641      6      A 2009-08-05:02:24:21 848546      2009-08-
05:02:24:20
          Name: /home/oracle/BACKUP/br_ORCL_23_1.dbf
          Tag: TAG20090805T022420

2090      7      A 2009-08-05:03:29:20 855661      2009-08-
05:03:25:54
          Name: +FRA/orcl/datafile/appraisal.288.694063519
          Tag: APP_INCR

RMAN>

```

Practice 7-2: Performing Fast Recovery

In this practice, you take advantage of the Flash Recovery Area to perform a fast recovery of a data file.

Note: The data file numbers in your database may differ from what is shown here.

- 1) Use the RMAN session from the previous practice and take the APPRAISAL data file offline.

```
RMAN> sql "alter tablespace appraisal offline";

sql statement: alter tablespace appraisal offline
starting full resync of recovery catalog
full resync complete

RMAN>
```

- 2) Use the SWITCH command to replace the data file from the flash recovery area.
 - a) Determine the name of the data file that is currently associated with the APPRAISAL tablespace.

```
RMAN> report schema;

Report of database schema for database with db_unique_name
ORCL

List of Permanent Datafiles
=====
File Size(MB) Tablespace          RB segs Datafile Name
-----
1      680      SYSTEM              YES      +DATA/orcl/datafile/system.260.694050517
2      570      SYSAUX                NO       +DATA/orcl/datafile/sysaux.266.694050521
3      85       UNDOTBS1              YES      +DATA/orcl/datafile/undotbs1.278.694050521
4      5        USERS                NO       +DATA/orcl/datafile/users.264.694050521
5      100      EXAMPLE              NO       +DATA/orcl/datafile/example.259.694050813
6      25       BR_TBS                NO       /home/oracle/BACKUP/br01.dbf
7      25       APPRAISAL             NO       +DATA/orcl/datafile/appraisal.256.694061937

List of Temporary Files
=====
File Size(MB) Tablespace          Maxsize(MB) Tempfile Name
-----
1      28       TEMP                  32767     +DATA/orcl/tempfile/temp.265.694050795
```

Practice 7-2: Performing Fast Recovery (continued)

Note that there is only one data file for the tablespace. In this case, it is data file number 7. You can use that data file number, instead of the tablespace name, in the upcoming set of commands.

b) Confirm that you have an image copy for data file 7 that you can switch to.

```
RMAN> list copy of datafile 7;
```

```
List of Datafile Copies
```

```
=====
```

Key	File	S	Completion Time	Ckp SCN	Ckp Time
-----	------	---	-----------------	---------	----------

----	----	-	-----	-----	-----
------	------	---	-------	-------	-------

2090	7	A	2009-08-05:03:29:20	855661	2009-08-05:03:25:54
------	---	---	---------------------	--------	---------------------

Name: +FRA/orcl/datafile/appraisal.288.694063519

Tag: APP_INCR

```
RMAN>
```

c) Switch to that copy of the image file.

```
RMAN> switch datafile 7 to copy;
```

```
datafile 7 switched to datafile copy  
"+FRA/orcl/datafile/appraisal.288.694063519"  
starting full resync of recovery catalog  
full resync complete
```

```
RMAN>
```

d) Recover data file 7.

```
RMAN> recover datafile 7;
```

```
Starting recover at 2009-08-05:03:43:34  
using channel ORA_DISK_1
```

```
starting media recovery  
media recovery complete, elapsed time: 00:00:01
```

```
Finished recover at 2009-08-05:03:43:35
```

```
RMAN>
```

3) Bring the APPRAISAL tablespace back online.

```
RMAN> sql "alter tablespace appraisal online";
```

```
sql statement: alter tablespace appraisal online  
starting full resync of recovery catalog  
full resync complete
```

```
RMAN>
```

Practice 7-2: Performing Fast Recovery (continued)

- 4) Report the schema to note the file name for the APPRAISAL tablespace.

```
RMAN> report schema;

Report of database schema for database with db_unique_name
ORCL

List of Permanent Datafiles
=====
File Size(MB) Tablespace          RB segs Datafile Name
-----
1      680      SYSTEM              YES
+DATA/orcl/datafile/system.260.694050517
2      570      SYSAUX                NO
+DATA/orcl/datafile/sysaux.266.694050521
3       85      UNDOTBS1              YES
+DATA/orcl/datafile/undotbs1.278.694050521
4        5      USERS                NO
+DATA/orcl/datafile/users.264.694050521
5      100      EXAMPLE              NO
+DATA/orcl/datafile/example.259.694050813
6       25      BR_TBS                NO
/home/oracle/BACKUP/br01.dbf
7       25      APPRAISAL             NO
+FRA/orcl/datafile/appraisal.288.694063519

List of Temporary Files
=====
File Size(MB) Tablespace          Maxsize(MB) Tempfile Name
-----
1       28      TEMP                  32767
+DATA/orcl/tempfile/temp.265.694050795

RMAN>
```

Note that you are now using the Flash Recovery Area data file as the open data file for the online tablespace.

- 5) Determine what happened to the original data file.

List the image copies for data file 7, to see if it is listed.

```
RMAN> list copy of datafile 7;

List of Datafile Copies
=====

Key          File S Completion Time          Ckp SCN          Ckp Time
-----
---
```

Practice 7-2: Performing Fast Recovery (continued)

```
2248      7      A 2009-08-05:03:42:49 856719      2009-08-
05:03:39:13
      Name: +DATA/orcl/datafile/appraisal.256.694061937
```

Note that it is still there and is listed now as an image copy. But, the reason for switching was because this data file was considered to be on a damaged disk, or the data file itself was corrupted.

- 6) In a separate terminal window, make sure you are at the ~/labs directory.

```
$ cd ~/labs
```

- 7) Remember that the reason for switching was because this data file was considered to be on a damaged disk, or the data file itself was corrupted in some way. So, run the `rm_asm_file.sh` script to delete the file. But first, you must ensure that you are pointing to the +ASM instance.

```
$ . oraenv
ORACLE_SID = [orcl] ? +ASM
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/grid is
/u01/app/oracle
$ asmcmd rm +DATA/orcl/datafile/appraisal.256.694061937
```

- 8) Eventually, you want to refrain from using the Flash Recovery Area as storage for active data files. By now, the hardware or corruption problem has been remedied, so switch the data file back to the original location.

- a) Back up the data file, specifying the DATA ASM disk group, using the DATAFILE template.

```
RMAN> backup as copy to destination '+DATA(datafile)' datafile
7;

Starting backup at 2009-08-05:03:49:30
using channel ORA_DISK_1
channel ORA_DISK_1: starting datafile copy
input datafile file number=00007
name=+FRA/orcl/datafile/appraisal.288.694063519
output file name=+DATA/orcl/datafile/appraisal.256.694064971
tag=TAG20090805T034930 RECID=28 STAMP=694064971
channel ORA_DISK_1: datafile copy complete, elapsed time:
00:00:03
Finished backup at 2009-08-05:03:49:33

Starting Control File and SPFILE Autobackup at 2009-08-
05:03:49:33
piece
handle=+FRA/orcl/autobackup/2009_08_05/s_694064975.295.6940649
77 comment=NONE
Finished Control File and SPFILE Autobackup at 2009-08-
05:03:49:42
RMAN>
```

Practice 7-2: Performing Fast Recovery (continued)

b) Take the data file offline.

```
RMAN> sql "alter database datafile 7 offline";

sql statement: alter database datafile 7 offline

RMAN>
```

c) Switch the data file to the newly made copy.

```
RMAN> switch datafile 7 to copy;

datafile 7 switched to datafile copy
"+DATA/orcl/datafile/appraisal.256.694064971"
starting full resync of recovery catalog
full resync complete

RMAN>
```

d) Report the schema to confirm that the data file location has changed.

```
RMAN> report schema;

Report of database schema for database with db_unique_name
ORCL
```

List of Permanent Datafiles

=====

File	Size(MB)	Tablespace	RB segs	Datafile Name
1	680	SYSTEM	YES	+DATA/orcl/datafile/system.260.694050517
2	570	SYS_AUX	NO	+DATA/orcl/datafile/sysaux.266.694050521
3	85	UNDOTBS1	YES	+DATA/orcl/datafile/undotbs1.278.694050521
4	5	USERS	NO	+DATA/orcl/datafile/users.264.694050521
5	100	EXAMPLE	NO	+DATA/orcl/datafile/example.259.694050813
6	25	BR_TBS	NO	/home/oracle/BACKUP/br01.dbf

7	25	APPRAISAL	NO	+DATA/orcl/datafile/appraisal.256.694064971
---	----	-----------	----	---

List of Temporary Files

=====

File	Size(MB)	Tablespace	Maxsize(MB)	Tempfile Name
1	28	TEMP	32767	+DATA/orcl/tempfile/temp.265.694050795

Practice 7-2: Performing Fast Recovery (continued)

- 9) Recover the data file.

```
RMAN> recover datafile 7;

Starting recover at 2009-08-05:03:53:27
using channel ORA_DISK_1

starting media recovery
media recovery complete, elapsed time: 00:00:00

Finished recover at 2009-08-05:03:53:27
RMAN>
```

- 10) Bring the data file online.

```
RMAN> sql "alter database datafile 7 online";

sql statement: alter database datafile 7 online

RMAN>
```

- 11) Cross-check the image copy backups and remove the obsolete data file 7 image copy.
Exit RMAN when finished.

```
RMAN> crosscheck copy;

released channel: ORA_DISK_1
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=58 device type=DISK
specification does not match any control file copy in the
repository
validation succeeded for datafile copy
datafile copy file
name=+FRA/orcl/datafile/system.291.694063333 RECID=21
STAMP=694064010
..
validation failed for datafile copy
datafile copy file
name=+DATA/orcl/datafile/appraisal.256.694061937 RECID=27
STAMP=694064569
..
name=+FRA/orcl/archivelog/2009_08_05/thread_1_seq_2.326.694061
513 RECID=21 STAMP=694061513
validation succeeded for archived log
archived log file
name=+FRA/orcl/archivelog/2009_08_05/thread_1_seq_3.311.694061
747 RECID=22 STAMP=694061750
Crosschecked 29 objects

RMAN> list expired copy;

specification does not match any archived log in the
repository
```


Practice 7-2: Performing Fast Recovery (continued)

List of Datafile Copies

=====

Key	File	S	Completion Time	Ckp SCN	Ckp Time
-----	------	---	-----------------	---------	----------

2248	7	X	2009-08-05:03:42:49	856719	2009-08-05:03:39:13
------	---	---	---------------------	--------	---------------------

Name: +DATA/orcl/datafile/appraisal.256.694061937

RMAN> **delete expired copy;**

released channel: ORA_DISK_1

allocated channel: ORA_DISK_1

channel ORA_DISK_1: SID=58 device type=DISK

specification does not match any control file copy in the repository

specification does not match any archived log in the repository

List of Datafile Copies

=====

Key	File	S	Completion Time	Ckp SCN	Ckp Time
-----	------	---	-----------------	---------	----------

2248	7	X	2009-08-05:03:42:49	856719	2009-08-05:03:39:13
------	---	---	---------------------	--------	---------------------

Name: +DATA/orcl/datafile/appraisal.256.694061937

Do you really want to delete the above objects (enter YES or NO)? **YES**

deleted datafile copy

datafile copy file

name=+DATA/orcl/datafile/appraisal.256.694061937 RECID=27

STAMP=694064569

Deleted 1 EXPIRED objects

RMAN> **exit**

Practice 8-1: Monitoring RMAN Jobs

In this practice, you execute a long-running RMAN job and monitor its progress to determine how much longer it is expected to run.

- 1) Point to the ORCL instance, invoke RMAN and delete all obsolete backups. You need to perform a cross-check first, so that the repository is up-to-date.

```
$ . oraenv
orcl
$ rman target / catalog rcatowner@rcat
recovery catalog database Password: oracle_4U <<<not displayed

RMAN> crosscheck backup;
. . .
RMAN> delete noprompt obsolete;
. . .
```

- 2) Open a second terminal window. Change to the labs directory and point to the 20cl instance. Invoke SQL*Plus and connect as SYSDBA. You use this second session to monitor a database backup.

```
$ . oraenv
orcl
$ sqlplus / as sysdba
```

- 3) Return to your first terminal window. In your RMAN session, begin a database backup to the tape device.

```
RMAN> backup device type sbt database;

Starting backup at 2009-08-05:04:23:41
released channel: ORA_DISK_1
allocated channel: ORA_SBT_TAPE_1
channel ORA_SBT_TAPE_1: SID=47 device type=SBT_TAPE
channel ORA_SBT_TAPE_1: WARNING: Oracle Test Disk API
channel ORA_SBT_TAPE_1: starting full datafile backup set
channel ORA_SBT_TAPE_1: specifying datafile(s) in backup set
input datafile file number=00001
name=+DATA/orcl/datafile/system.260.694050517
channel ORA_SBT_TAPE_1: starting piece 1 at 2009-08-
05:04:23:42
channel ORA_SBT_TAPE_1: finished piece 1 at 2009-08-
05:04:24:37
piece handle=20klt7qe_1_1 tag=TAG20090805T042342 comment=API
Version 2.0,MMS Ver
sion 8.1.3.0...
```

Practice 8-1: Monitoring RMAN Jobs (continued)

- 4) Use your SQL*Plus session to monitor the progress of the database backup by querying the V\$SESSION_LONGOPS view. By using this view, you can determine whether the backup is progressing normally or hanging. If the backup is progressing normally, the TIME_REMAINING column should be decreasing. Execute the query_longops2.sql script a few times to query V\$SESSION_LONGOPS. Since the script contains multiple SELECT statements, you cannot enter slash to rerun the script. You must type or paste the script name for each run. Each time you should see the TIME_REMAINING value decreasing for the SID associated with the backup task. The detail data section pertains to individual channel openings and closings. The aggregate data section describes the entire RMAN job progress.

```
SQL> @query_longops2.sql

Detail Data
-----
Detail Progress Information (per file)

      SID START_TIME          ELAPSED_SECONDS TIME_REMAINING
-----
      40 2009-08-05:05:12:19          20          24

Aggregate Data
-----
Aggregate Progress Information

      SID  SERIAL#  CONTEXT          SOFAR  TOTALWORK  %_COMPLETE
-----
      21      934      4          43999  236000    18.64

SQL> @query_longops2.sql

Detail Data
-----
Detail Progress Information (per file)

      SID START_TIME          ELAPSED_SECONDS TIME_REMAINING
-----
      40 2009-08-05:05:13:26          12          35

Aggregate Data
-----
Aggregate Progress Information

      SID  SERIAL#  CONTEXT          SOFAR  TOTALWORK  %_COMPLETE
-----
      21      934      4          131039  236000    55.53
```

Practice 8-1: Monitoring RMAN Jobs (continued)

5) Exit your RMAN and SQL sessions.

6) Run the `cleanup_archivelogs.sh` script to back up and remove archivelog files. This takes several minutes to run.

```
$ cd ~/labs
$ ./cleanup_archivelogs.sh
```

7) Run the `cleanup_tape_dir.sh` script to remove files from the `/tape` directory.

```
$ ./cleanup_tape_dir.sh
```

Practices for Lesson 9

In this lesson you learn about diagnosing and repairing block corruption.
In these practices, you employ various diagnostic capabilities to solve errors.

Practice 9-1: Diagnostic Scenario

In this optional practice, you create a data dictionary corruption that you analyze using Support Workbench and ADRCI. *If you begin this practice, you must complete it.*

- 1) Execute the `hm_setup.sh` script from the `labs` subdirectory. This script corrupts the data dictionary.

```
$ . oraenv
orcl
$ cd ~/labs
$ cat hm_setup.sh
#!/bin/bash

cd /home/oracle/labs

sqlplus / as sysdba <<EOF

set echo on
create table scott.tabjmw(c number) tablespace users;
variable obj number;

begin
select object_id into :obj from dba_objects where
owner='SCOTT' and object_name='TABJMW';
end;
/
print obj;
update tab$ set cols=1001 where obj#=:obj;
commit;
EOF

$ ./hm_setup.sh

SQL> SQL> SQL>
Table created.

SQL> SQL> SQL>      2      3      4
PL/SQL procedure successfully completed.

SQL>
      OBJ
-----
      74657


SQL>
1 row updated.

SQL>
Commit complete.

$
```

Practice 9-1: Diagnostic Scenario (continued)

- 2) Use EM to trigger a health check on the data dictionary.
 - a) From the Database home page (connected as the SYS user), click Advisor Central at the bottom of the page in the Related Links section.
 - b) On the Advisor Central page, click the Checkers tab.
 - c) On the Checker tabbed page, click Dictionary Integrity Check.



- d) On the Run Dictionary Integrity Check page, specify a Run Name: DictCheck and click OK.

Run Dictionary Integrity Check

Checks dictionary integrity

Options

Specify the following parameters in order to run this checker.

Parameter	Value	Description
Run Name	DictCheck	The run name parameter is used to identify this run.
Timeout (sec)		The time allocated for this run before its forced to stop.
TABLE_NAME		Table name
CHECK_MASK		Check mask

Cancel OK

- e) Back to the Advisor Central Checkers page, you should see a Confirmation message indicating that your check ran successfully.
 - f) Select your DictCheck run and click Details.

Results

Details

Select	Checker Name	Run Name	Run Type	Status	Start Time ▾	End Time
<input checked="" type="radio"/>	Dictionary Integrity Check	DictCheck	Manual	Completed	July 22, 2009 11:12:55 PM GMT+07:00	July 22, 2009 11:13:01 PM GMT+07:00
<input type="radio"/>	DB Structure Integrity Check	HM_RUN_1	Reactive	Completed	July 20, 2009 11:52:28 PM GMT+07:00	July 20, 2009 11:52:29 PM GMT+07:00

- g) This takes you to the Run Details Findings tabbed page, where you can see some Data Corruption. In particular, you should see the following finding: “SQL dictionary health check: invalid column number 8 on object TAB\$ failed.”

Practice 9-1: Diagnostic Scenario (continued)

Select	Description	Priority	Damage Translation	Incident ID	Status ▾	Time Detected
<input type="checkbox"/>	All Findings					
<input type="checkbox"/>	SQL dictionary health check: invalid column number 8 on object TAB\$ failed	Critical	Damaged rowid is AAAAAACAABAAAUfPAAC - description: Object SCOTT.TABJMW is referenced		Open	July 22, 2009 11:12:56 PM GMT+07:00

The corruption should correspond to a row in TAB\$ that references SCOTT.TABJMW.

- 3) How would you get a report about the previous finding using SQL*Plus?

```
$ sqlplus / as sysdba

SQL> set long 100000
SQL> set pages 999

SQL> select dbms_hm.get_run_report('DictCheck') from dual;

DBMS_HM.GET_RUN_REPORT('DICTCHECK')
-----
Basic Run Information
Run Name                : DictCheck

Run Id                  : 481

Check Name               : Dictionary I
ntegrity Check
Mode                    : MANUAL

Status                  : COMPLETED

Start Time               : 2009-07-22
23:12:55.920739 +07:00
End Time                 : 2009-07-22 23:13:01.5127
11 +07:00
Error Encountered       : 0

Source Incident Id      : 0

Number of Incidents Created : 0

Input Paramters for the Run
TABLE_NAME=ALL_CORE_TABLES
CHECK_MASK=ALL

Run Findings And Recommendations
Finding

Finding Name           : Dictionary Inconsistency

Finding ID             : 482
```


Practice 9-1: Diagnostic Scenario (continued)

```

Type           : FAILURE

Status          : OPEN

Priority         : CRITICAL

Message         : SQL dictionary health check: i
nvalid column number 8 on
                  object TAB$ failed

Message         : Damaged rowid is AAAAACAABAAU
fPAAC - description: Object
                  SCOTT.TABJMW is referenced

SQL>

```

- 4) Navigate to your EM Home page. What do you observe in the Alerts section?

You should see a new critical alert (Data Failure) for the previously detected corruption in the Alerts section of the Home page. *(It may take a while to appear.)*

Alerts				
Category		All	Go	Critical ✖ 1 Warning ⚠ 1
Severity	Category	Name	Impact	Message
✖	Data Failure	Data Failure Detected		Checker run found 1 new persistent data failures.
⚠	User Audit	Audited User		User SYS logged on from edrsr37p1.us.oracle.com.
				Alert Triggered
				Jul 22, 2009 11:15:07 PM
				Jul 22, 2009 11:20:28 PM

- 5) Flush your shared pool and buffer cache first, and then exit and reconnect as the SYS user.

```

$ sqlplus / as sysdba
SQL> alter system flush shared_pool;
System altered.

SQL>
SQL> alter system flush buffer_cache;
System altered.

SQL> exit

```

```
$ sqlplus / as sysdba
```

- 6) From a SQL*Plus session connected as the SYS user, execute the following statement: `select * from scott.tabjmw;`
Question: What do you observe?

```

SQL> select * from scott.tabjmw;

select * from scott.tabjmw
*
ERROR at line 1:

```

Practice 9-1: Diagnostic Scenario (continued)

```
ORA-03113: end-of-file on communication channel
Process ID: 14872
Session ID: 66 Serial number: 6259
SQL>
```

Answer: At first the session seems to hang, then the ORA-03113 error is displayed.

- 7) Use EM to investigate the previous problem.
 - a) From the EM Home page, you should see one active incident. Click the Active Incident link. If not, click Software and Support. On the Software and Support tabbed page, click Support Workbench in the Support section.

Diagnostic Summary

ADDM Findings	5
Period Start Time	Jul 22, 2009 10:00:33 PM GMT+07:00
Alert Log	No ORA- errors
Active Incidents	1
Key SQL Profiles	

[Database Instance Health](#)

- b) On the Support Workbench Problems tabbed page, you should see a new Active Incident whose description is similar to ORA 7445 [qcstda()+690].

Select All Select None Show All Details Hide All Details									
Select Details	ID	Description	Number Of Incidents	Last Incident	Last Comment	Active	Packaged	SR#	
<input type="checkbox"/>	1	ORA 7445 [qcstda()+690]	1	July 22, 2009 11:27:26 PM GMT+07:00		Yes	No		

- c) Click the “+” icon in the Details column for this problem.
 - d) This shows you the corresponding first-time incident.
 - e) Make a note of the incident number (In this screenshot it is 8729).
 - f) Click that incident number.

Select Details	ID	Description	Number Of Incidents	Last Incident	Last Comment	Active	Packaged	SR#	
<input type="checkbox"/>	1	ORA 7445 [qcstda()+690]	1	July 22, 2009 11:27:26 PM GMT+07:00		Yes	No		

Incidents (1)

8729	ORA-7445 [qcstda()+690] [SIGSEGV] [ADDR:0x0] [PC:0x9D93D68] [Address not ma ...]	July 22, 2009 11:27:26 PM GMT+07:00
------	--	-------------------------------------

- g) This takes you to the corresponding Incident Details page.
 - h) On the Incident Details page, in the Application Information section, you can see the cause the incident. It is: "select * from scott.tabjmw".

Practice 9-1: Diagnostic Scenario (continued)

Incident Details: 8729 Page Refreshed July 22, 2009 11:34:16 PM GMT+07:00 [Refresh](#)



Summary

Problem Key	ORA-7445 [qcstda()+690] [SIGSEGV] [ADDR:0x0] [PC:0x9D93D68] [Address not mapped to object]	Data Dumped	Yes
Status	Ready	ECID	Unknown
Active	Yes	Correlation Keys	SID = 66.6259, Procid = 41.90 PQ = (0, 1248280045), Client Procid = oracle@edrs37p1.us.oracle.com (TNS V1-V3).14872_3707568
Timestamp	July 22, 2009 11:27:26 PM GMT+07:00	Purge Date	August 21, 2009 11:27:26 PM GMT+07:00 (Purging Enabled) Disable Purging
Impact	Unknown		
Source	System Generated		

Application Information

SQL ID	f18d4qk7w52s7
SQL Text	select * from scott.tabjmw
User	SYS
Module	sqlplus@edrs37p1.us.oracle.com (TNS V1-V3)
Action	Unknown

[Dump Files](#) [Checker Findings](#) [Additional Diagnostics](#)

File Name	Size (MB)	Timestamp	Path	View Contents
orcl_ora_14872_i8729.trc	9.33	July 22, 2009 11:28:43 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_8729	
orcl_ora_14872.trc	< 0.01	July 22, 2009 11:28:43 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/trace	

You can also see two dump files generated from the Dump Files tabbed page. The first one corresponds to the incident dump file and is located in the ADR directory /u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_nnnn. The second one is the classical corresponding trace file located in /u01/app/oracle/diag/rdbms/orcl/orcl/trace.

- h) Click the eyeglasses icon in the View Contents column for the incident trace (first row).
- i) If you did not save your Host credentials previously, then the Host Credentials page is displayed. Enter oracle as username and enter oracle as password, then click Continue.
- 8) On the Contents page, you see the structured trace information. Expand the incident_dump and custom_assert_dump nodes.

Practice 9-1: Diagnostic Scenario (continued)

Contents: orcl_ora_14872_i8729.trc

File /u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_8729/orcl_ora_14872_i8729.trc
Modified July 22, 2009 11:28:43 PM GMT+07:00
Size 9.33 MB

Trace files are for Oracle internal use only.

Trace Map

A Trace Map provides a table of contents for a dump file.
TIP Select a section to see its detailed trace records below.

Details

Expand All | Collapse All

/u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_8729/orcl_ora_14872_i8729.trc

Error Stack:

incident_dump:===== Dump for incident 8729 (ORA 7445 [qcstda() +690]) =====

custom_assert_dump:----- Beginning of Customized Incident Dump(s) -----

----- Session Cached Cursor Dump -----

Select to expand

pinned_buffer_history:----- Pinned Buffer History -----

plsql_runtime_state:----- PL/SQL Runtime State -----

archival_runtime_state:----- Archival Runtime State -----

recovery_context_info:----- Recovery Context Info -----

sql_control_block:----- SQL Control Block -----

- 9) Then click the “current sql statement” link.

/u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_8729/orcl_ora_14872_i8729.trc

Error Stack:

incident_dump:===== Dump for incident 8729 (ORA 7445 [qcstda() +690]) =====

custom_assert_dump:----- Beginning of Customized Incident Dump(s) -----

current_sql_statement:----- Current SQL Statement for this session (sql_id=f18d4gk7w52s7) -----

call_stack_dump:----- Call Stack Trace -----

- 10) This prints the culprit SQL statement in the window below the Trace Map.

----- Current SQL Statement for this session (sql_id=f18d4gk7w52s7) -----
select * from scott.tabjmw

- 11) Click OK.

- 12) On the Incident Details page again, click the Problem Key link.

Summary

Problem Key	ORA-7445 [qcstda() +690] [SIGSEGV] [ADDR:0x0] [PC:0x9D93D68] [Address not mapped to object]
Status	Ready
Active	Yes

- 13) On the Problem Details page, click Edit to the right of the SR field.

- 14) Enter 1234 in the SR Number pop-up window that appears and click OK. It is assumed that you already opened an SR (1234) with MetaLink.

Practice 9-1: Diagnostic Scenario (continued)

Problem Details: ORA 7445 [qcstda()+690]

Page Refreshed July 22, 2009 11:4

Summary

SR#	--	Edit
Bug#	--	Edit
Active	Yes	
Packaged	No	
Number of Incidents	1	

Last Dumped Incident

The page at https://edrsr37p1.us.oracle.co...

Please enter a Service Request Number (SR)

1234

OK **Cancel**

15) You should now see the SR number on the Problem Details page.

16) Click the Activity Log tab.

17) This takes you to the Activity Log tabbed page, on which you can now see your last action on the problem. You can optionally enter a comment here. (If you do, click Add Comment to save your comment.)

Incidents **Activity Log**

Comment: This is a test comment fot SR 1234 **Add Comment**

User	Action	Description	Timestamp
SYS	Comment	Set SR : 1234	July 22, 2009 11:52:33 PM GMT+07:00

18) Back to your terminal window, locate your incident and your health check report in ADR. (Your incident number may be different.)

```
$ cd $ORACLE_BASE/diag/rdbms/orcl/orcl

$ ls
alert  cdump  hm  incident  incpkg  ir  lck  metadata  stage
sweep  trace
$ cd incident
$ ls -la
total 12
drwxr-x--- 3 oracle dba 4096 Jul 22 23:27 .
drwxr-x--- 13 oracle dba 4096 Jul 20 23:49 ..
drwxr-xr-x 2 oracle dba 4096 Jul 22 23:27 incdir_8729

$ cd incdir_8729

$ ls
orcl_ora_14872_i8729.trc  orcl_ora_14872_i8729.trm

$ cd ../..
$ ls
alert  cdump  hm  incident  incpkg  ir  lck  metadata  stage
sweep  trace
```

Practice 9-1: Diagnostic Scenario (continued)

```
$ cd hm
$ ls
HMREPORT_DictCheck.hm
$ cd ..
$
```

19) Use ADRCI to locate your incident and problem information.

```
$ adrci

ADRCI: Release 11.2.0.0.2 - Beta on Thu Jun 4 20:14:32 2009
ADRCI: Release 11.2.0.1.0 - Production on Thu Jul 23 01:04:39
2009

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All
rights reserved.

ADR base = "/u01/app/oracle"
adrci> set homepath diag/rdbms/orcl/orcl

adrci> show homes
ADR Homes:
diag/rdbms/orcl/orcl
adrci> show incidents
ADR Home = /u01/app/oracle/diag/rdbms/orcl/orcl:
*****
*****
INCIDENT_ID          PROBLEM_KEY
CREATE_TIME
-----
8729                  ORA 7445 [qcstda()+690]
2009-07-22 23:27:26.129000 +07:00
1 rows fetched
adrci>
```

20) Use Enterprise Manager to package your problem quickly.

21) From the Problem Details page, click Quick Package in the Investigate and Resolve section.

Problem Details: ORA 7445 [qcstda()+690]

Page Refreshed July 22, 2009 11:57:19 PM GMT+07:00 [Refresh](#)

Summary	
SR#	1234 Edit
Bug#	-- Edit
Active	Yes
Packaged	No
Number of Incidents	1

Investigate and Resolve

[Go to My Oracle Support](#) [Quick Package](#)

[Self Service](#) [Oracle Support](#)

Assess Damage

[Run Checkers](#)

[Database Instance Health](#)

Practice 9-1: Diagnostic Scenario (continued)

- 22) On the Quick Packaging: Create New Package page, leave the default package name (something similar to ORA7445qc_20090723011838) and select No for “Send to Oracle Support” entry.

Quick Packaging: Create New Package

Target **orcl.us.oracle.com** Logged in As **SYS**

Problems Selected **ORA 7445 [qcstda()+690]**

Use quick packaging to generate an upload file for a single problem and send it to Oracle with default options. If Oracle Configuration set up, the upload file will still be created but it will not be sent to Oracle.

* Package Name

Package Description

Send to Oracle Support ☒ Yes ☐ No

My Oracle Support Username

My Oracle Support Password

Customer Support Identifier (CSI)

Country

Create new Service Request (SR) ☒ Yes ☐ No

- 23) When the page is refreshed, click Next.

Quick Packaging: Create New Package

Target **orcl.us.oracle.com** Logged in As **SYS**

Problems Selected **ORA 7445 [qcstda()+690]**

Use quick packaging to generate an upload file for a single problem and send it to Oracle with default options. If Oracle Configuration set up, the upload file will still be created but it will not be sent to Oracle.

* Package Name

Package Description

Send to Oracle Support ☐ Yes ☒ No

- 24) On the Quick Packaging: View Contents page, you can see the list of incidents that are part of this package. There should be only one incident in your case. Click Next.

Quick Packaging: View Contents

Target **orcl.us.oracle.com** Logged in As **SYS**

Problems Selected **ORA 7445 [qcstda()+690]** Service Request Number (SR#)

Package Name **ORA7445qc_20090723011838** Total Size (uncompressed) **9.45 MB**

Incidents to be Packaged

ID	Type	Problem ID	Description	Size (MB)	Timestamp
8729	Main	1	ORA-7445 [qcstda()+690] [SIGSEGV] [ADDR:0x0] [PC:0x9D93D68] [Address not mapped to object]	9.45	July 22, 2009 11:27:26 PM GMT+07:00

- 25) On the Quick Packaging: View Manifest page, look at the package name and the path.

Practice 9-1: Diagnostic Scenario (continued)

Quick Packaging: View Manifest

Target: **orcl.us.oracle.com** Logged in As: **SYS**

Problems Selected: **ORA 7445 [qcstda()+690]** Service Request Number (SR#):

Package Name: **ORA7445qc_20090723011838** Total Size (uncompressed): **9.45 MB**

Path: **/u01/app/oracle/diag/rdbms/orcl/orcl/incpkg/pkg_1/seq_1/manifest_1_1.txt**

Manifest for package 1

Manifest details

Buttons: Cancel, Back, Step 3 of 4, Next

26) Click Next.

27) On the Quick Packaging: Schedule page, ensure Immediately is selected and click Submit.

Quick Packaging: Schedule

Target: **orcl.us.oracle.com** Logged in As: **SYS**

Problems Selected: **ORA 7445 [qcstda()+690]** Service Request Number (SR#):

Package Name: **ORA7445qc_20090723011838** Total Size (uncompressed): **9.45 MB**

Larger upload files may take longer to generate and send to Oracle.

☒ Immediately

☐ Later

Buttons: Cancel, Back, Step 4 of 4, Submit

28) The Processing: Generating Upload File for Package page appears. Wait until it is finished.

29) On the Confirmation page, you should see something similar to: "Generating an upload file for package: ORA7445qc_20090723011838 has failed."

Confirmation

Generating an upload file for package: ORA7445qc_20090723011838 has failed.

Button: OK

30) Click OK.

31) On the Problem Details page, click the Activity Log tab.

32) Back to the Problem Details Activity Log tabbed page, you should now see two new entries in the log reporting about the package creation for this problem.

Incidents Activity Log				
Comment				Add Comment
User	Action	Description	Timestamp	
SYS	Package	Failed to create physical file : packageId = 1	July 23, 2009 1:26:09 AM GMT+07:00	
SYS	Comment	Created package : Id = 1 Name = ORA7445qc_20090723011838	July 23, 2009 1:21:36 AM GMT+07:00	

33) In the Summary section, click Yes to the right of the Packaged entry.

34) This takes you to the Packages page, from where you can see your package.

Select	Name	Status	Type	Description	Main Problem Keys
<input checked="" type="checkbox"/>	ORA7445qc_20090723011838	Active		ORA 7445 [qcstda()+690]	July 23, 2009 1:21:35 AM GMT+07:00

Practice 9-1: Diagnostic Scenario (continued)

35) Select your package, and click View.

Package Details: ORA7445qc_20090723011838

Page Refreshed July 23, 2009 1:31:59 AM GMT+07:00 [Refresh](#)
[Customize Package](#)

Summary

Status	Active	Finish Contents Preparation
Type	Main	
Total Size (uncompressed)	12.24 MB	
Incremental Size (uncompressed)	0.1 MB	
Created	July 23, 2009 1:21:35 AM GMT+07:00	
Description	N/A	
Problems in Package	ORA 7445 [qcstda()+690]	
Incidents Previously Excluded by User	0	
Files Excluded by User	0	

[Incidents](#) [Files](#) [Activity Log](#)

ID	Type	Problem ID	Description	Size (MB)	Timestamp
8729	Main	1	ORA-7445 [qcstda()+690] [SIGSEGV] [ADDR:0x0] [PC:0x9D93D68] [Address not mapped to object]		0 July 22, 2009 11:27:26 PM GMT+07:00

This takes you to the Package Details page, where you can see the package details.

36) Click the Files tab.

[Incidents](#) [Files](#) [Activity Log](#)

View [Full Package Contents](#)

Previous 1-25 of 50 Next 25

Source Name	Size (MB)	Has Data	User	Timestamp	Path	View
Incident orcl_ora_14872_i8729.trm	0.11	No		July 22, 2009 11:28:43 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_8729	
Incident orcl_ora_14872_i8729.trc	9.33	No		July 22, 2009 11:28:43 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/incident/incdir_8729	View
Common orcl_ora_14872.trc	< 0.01	No		July 22, 2009 11:28:43 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/trace	View
Common orcl_ora_14872.trm	< 0.01	No		July 22, 2009 11:28:43 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/trace	
Common manifest_1_1.xml	0.01	No		July 23, 2009 1:26:03 AM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/incpkg/pkg_1/seq_1	
Common manifest_1_1.html	0.01	No		July 23, 2009 1:26:03 AM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/incpkg/pkg_1/seq_1	
Common manifest_1_1.txt	0.02	No		July 23, 2009 1:26:04 AM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/incpkg/pkg_1/seq_1	
Common log.xml	0.37	No		July 22, 2009 11:28:46 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/alert	
Common alert_orcl.log	0.07	No		July 22, 2009 11:28:46 PM GMT+07:00	/u01/app/oracle/diag/rdbms/orcl/orcl/alert	

On the Files tabbed page, you can now see the Full Package Content view.

37) Use ADRCI to determine the list of existing packages.

```
$ adrci

ADRCI: Release 11.1.0.5.0 - Beta on Thu May 24 07:57:13 2007
```


Practice 9-1: Diagnostic Scenario (continued)

```
begin
select object_id into :obj from dba_objects where
owner='SCOTT' and object_name='TABJMW';
end;
/
print obj;
update tab$ set cols=1 where obj#=:obj;
commit;
EOF
$ ./hm_fix.sh
SQL> SQL> SQL>      2      3      4
PL/SQL procedure successfully completed.

SQL>
      OBJ
-----
      74657

SQL>
1 row updated.

SQL>
Commit complete.
$
```

39) Use Enterprise Manager to close your incident.

40) On the Package Details page, click the “problem” link to the right of the “Problems in Package” field in the Summary section.

Summary	
Status	Active Finish Contents Preparation
Type	Main
Total Size (uncompressed)	12.24 MB
Incremental Size (uncompressed)	0.1 MB
Created	July 23, 2009 1:21:35 AM GMT+07:00
Description	N/A
Problems in Package	ORA 7445 [gcstda() +690]
Incidents Previously Excluded by User	0
Files Excluded by User	0

41) On the Problem Details Incidents tabbed page, select your incident and click Close.

Practice 9-1: Diagnostic Scenario (continued)

Incidents
Activity Log

Status: Open Incidents
Data Dumped: Yes
Go

View
Close

[Select All](#) | [Select None](#) | [Show All Details](#) | [Hide All Details](#)

Select	Details	ID	Description	Data Dumped	Active	Status	Timestamp
<input checked="" type="checkbox"/>	Show	8729	ORA-7445 [qcstda()+690] [SIGSEGV] [ADDR:0x0] [PC:0x9D93D68] [Address not mapped to object]	Yes	Yes	Ready	July 22, 2009 11:27:26 PM GMT+07:00

42) On the Confirmation page, click Yes.

Practice 9-2: Repairing Block Corruption

- 1) To set up this block corruptions practice, use a terminal window, navigate to the \$HOME/labs directory, and execute the bc_setup.sh script. This script creates a tablespace called BCTBS and a user called BC. The tablespace is then populated. A backup of the new tablespace is performed.

Take a few moments to inspect each script actions before executing it. As usual you point to the orcl instance.

```
$ cd ~/labs
$ . oraenv
ORACLE_SID = [orcl] ? orcl

$ cat bc_setup.sh
#!/bin/bash
# For training purpose only
# Run as oracle OS user

sqlplus -S /nolog > /tmp/setup.log 2>&1 <<EOF
connect / as sysdba

-- CLEANUP from previous run
DROP USER bc CASCADE;

DROP TABLESPACE bctbs INCLUDING CONTENTS AND DATAFILES;

-- Create tablespace
CREATE TABLESPACE bctbs
DATAFILE '/home/oracle/BACKUP/bctbs01.dbf' SIZE 10M
SEGMENT SPACE MANAGEMENT MANUAL;

-- Create user
CREATE USER bc IDENTIFIED BY oracle_4U
DEFAULT TABLESPACE bctbs
QUOTA UNLIMITED ON bctbs;

GRANT CREATE SESSION TO bc;

-- create table and populate
-- be sure table is at least 2 blocks long
CREATE TABLE bc.bccopy
TABLESPACE bctbs
AS SELECT * FROM HR.EMPLOYEES;

INSERT INTO bc.bccopy
SELECT * FROM bc.bccopy;

INSERT INTO bc.bccopy
SELECT * FROM bc.bccopy;
EOF
```

Practice 9-2: Repairing Block Corruption (continued)

```
#-- Create backup of the bctbs tablespace

rman target / > /tmp/rman.log 2>&1 <<EOF

BACKUP AS COPY TABLESPACE bctbs;
EOF

#-- update the table
sqlplus -S /nolog >> /tmp/setup.log 2>&1 <<EOF
connect / as sysdba

UPDATE bc.bccopy SET salary = salary+1;

COMMIT;

EOF
```

```
$ ./bc_setup.sh
```

- 2) Log into SQL*Plus as the SYS user and execute the bc_critical script, which corrupts the data file. Enter your displayed block number.

```
$ sqlplus / as sysdba

SQL> @bc_critical
Connected.

  FILE_NO  BLOCK_NO
-----
         7      129

System altered.

'Enter Block number when prompted'
Enter value for block_no: 129
0+1 records in
0+1 records out
80 bytes (80 B) copied, 6.1724e-05 seconds, 1.3 MB/s
0+1 records in
0+1 records out
79 bytes (79 B) copied, 5.7166e-05 seconds, 1.4 MB/s

SELECT * from bc.bccopy
      *
ERROR at line 1:
ORA-01578: ORACLE data block corrupted (file # 7, block # 129)
ORA-01110: data file 7: '/home/oracle/BACKUP/bctbs01.dbf'

SQL>
```

Practice 9-2: Repairing Block Corruption (continued)

- 3) Use RMAN to back up the TBSBC tablespace. What happens?

```
$ rman target / nocatalog
RMAN> backup tablespace bctbs;

Starting backup at 2009-07-23:16:21:16
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=1 device type=DISK
channel ORA_DISK_1: starting full datafile backup set
channel ORA_DISK_1: specifying datafile(s) in backup set
input datafile file number=00007
name=/home/oracle/BACKUP/bctbs01.dbf
channel ORA_DISK_1: starting piece 1 at 2009-07-23:16:21:16
RMAN-00571:
=====
RMAN-00569: ===== ERROR MESSAGE STACK FOLLOWS
=====
RMAN-00571:
=====
RMAN-03009: failure of backup command on ORA_DISK_1 channel at
07/23/2009 16:21:23
ORA-19566: exceeded limit of 0 corrupt blocks for file
/home/oracle/BACKUP/bctbs01.dbf

RMAN> exit
```

The backup fails upon encountering the first corrupt block.

- 4) Use the RMAN `list failure` command to provide details about the errors.

```
$ rman target / nocatalog

Recovery Manager: Release 11.1.0.6.0 - Production on Mon Aug
27 09:49:50 2007

connected to target database: ORCL (DBID=1158576740)

RMAN> list failure detail;

RMAN> List of Database Failures
=====

Failure ID Priority Status      Time Detected      Summary
-----
562          HIGH      OPEN          2009-07-23:16:11:04 Datafile 7:
'/home/oracle/BACKUP/bctbs01.dbf' contains one or more corrupt
blocks
Impact: Some objects in tablespace BCTBS might be
unavailable
List of child failures for parent failure ID 562
Failure ID Priority Status      Time Detected      Summary
```

Practice 9-2: Repairing Block Corruption (continued)

```
-----  
571          HIGH      OPEN      2009-07-23:16:11:05 Block 130  
in datafile 7: '/home/oracle/BACKUP/bctbs01.dbf' is media  
corrupt  
Impact: Object BCCOPY owned by BC might be unavailable  
565          HIGH      OPEN      2009-07-23:16:11:04 Block 129  
in datafile 7: '/home/oracle/BACKUP/bctbs01.dbf' is media  
corrupt  
Impact: Object BCCOPY owned by BC might be unavailable
```

Note: Do not close this RMAN session.

- 5) Alternatively, in another terminal window, you can query the V\$IR_FAILURE view to view details about the failure:

```
$ sqlplus / as sysdba  
SQL> set pages 999  
SQL> select failure_id, time_detected, description, impacts  
from V$IR_FAILURE where impacts like '%BC%';  
  
FAILURE_ID TIME_DETECTED  
-----  
DESCRIPTION  
-----  
IMPACTS  
-----  
-----  
562 2009-07-23:16:11:04  
Datafile 7: '/home/oracle/BACKUP/bctbs01.dbf' contains one or  
more corrupt block  
s  
Some objects in tablespace BCTBS might be unavailable  
  
565 2009-07-23:16:11:04  
Block 129 in datafile 7: '/home/oracle/BACKUP/bctbs01.dbf' is  
media corrupt  
Object BCCOPY owned by BC might be unavailable  
  
571 2009-07-23:16:11:05  
Block 130 in datafile 7: '/home/oracle/BACKUP/bctbs01.dbf' is  
media corrupt  
Object BCCOPY owned by BC might be unavailable  
  
SQL>  
SQL> exit
```


Practice 9-2: Repairing Block Corruption (continued)

- 6) Continue in your RMAN session. Execute the RMAN `advise failure all` command to view recovery options.

```
RMAN> advise failure all;
List of Database Failures
=====

Failure ID Priority Status      Time Detected      Summary
-----
562          HIGH      OPEN      2009-07-23:16:11:04 Datafile 7:
'/home/oracle/BACKUP/bctbs01.dbf' contains one or more corrupt
blocks

analyzing automatic repair options; this may take some time
using channel ORA_DISK_1
allocated channel: ORA_SBT_TAPE_1
channel ORA_SBT_TAPE_1: SID=24 device type=SBT_TAPE
channel ORA_SBT_TAPE_1: WARNING: Oracle Test Disk API
analyzing automatic repair options complete

Mandatory Manual Actions
=====
no manual actions available

Optional Manual Actions
=====
no manual actions available

Automated Repair Options
=====
Option Repair Description
-----
1          Recover multiple corrupt blocks in datafile 7
  Strategy: The repair includes complete media recovery with
no data loss
  Repair script:
/u01/app/oracle/diag/rdbms/orcl/orcl/hm/reco_3952673413.hm

RMAN>
```

Note: An `advise failure` command **must** precede a repair command. So, do not execute other commands, but continue with the next step.

Practice 9-2: Repairing Block Corruption (continued)

- 7) Continue in your RMAN session and execute the RMAN repair failure command. Enter **YES**, when asked if you want to execute the repair.

Note: Your actual script name is most likely different than the example.

```
RMAN> repair failure;

Strategy: The repair includes complete media recovery with no
data loss
Repair script:
/u01/app/oracle/diag/rdbms/orcl/orcl/hm/reco_3952673413.hm

contents of repair script:
  # block media recovery for multiple blocks
  recover datafile 7 block 129 to 130;

Do you really want to execute the above repair (enter YES or
NO)? YES
executing repair script

Starting recover at 2009-07-23:16:35:34
using channel ORA_DISK_1
using channel ORA_SBT_TAPE_1

ORA-01013: user requested cancel of current operatio
channel ORA_SBT_TAPE_1: restoring block(s) from datafile copy
+FRA/orcl/datafile/bctbs.296.692986085

starting media recovery
media recovery complete, elapsed time: 00:00:03

Finished recover at 2009-07-23:16:35:38
repair failure complete

RMAN>
```

- 8) List all failures in RMAN. There should be none.

```
RMAN> list failure all;

no failures found that match specification

RMAN> exit
```

- 9) To clean up the practice environment, run the `bc_cleanup.sh` script from the `$HOME/labs` directory.

```
$ cat bc_cleanup.sh
#!/bin/bash
# For training purpose only
#-- Cleanup the tablespace, and user from the corrupt blocks
```

Practice 9-2: Repairing Block Corruption (continued)

```
sqlplus -S /nolog > /tmp/cleanup.lo 2>&1 <<EOF
connect / as sysdba

-- CLEANUP from previous run
DROP USER bc CASCADE;

DROP TABLESPACE bctbs INCLUDING CONTENTS AND DATAFILES;

EXIT;
EOF
$ ./bc_cleanup.sh
```

Flashback Transaction Backout is a logical recovery option to roll back a specific transaction and dependent transactions while the database remains online. A dependent transaction is related by a write-after-write (WAW) relationship, in which a transaction modifies the same data that was changed by the target transaction, or a primary-key constraint relationship, in which a transaction reinserts the primary-key value that was deleted by the target transaction. Flashback Transaction utilizes undo and the redo generated for undo blocks to create and execute a compensating transaction for reverting the affected data to its original state.

Practice 10-1: Flashback Transaction Backout

In this practice, you view a demonstration of backing out erroneous transactions.

- 1) Click the oracle's Home icon on your desktop.
- 2) Navigate to the `/home/oracle/demos/fbt_backout` directory.
- 3) Double-click the `fbt_backout_viewlet_swf.html` file.
- 4) In the Run or Display window, click Display and view the presentation.
- 5) Use the controls at the bottom of the viewlet window to start, pause and stop the presentation, as suits your personal learning style.
- 6) Uninterrupted viewing of the demos takes about ten minutes. When you have finished viewing the presentation, close your Web browser window.

Practices for Lesson 11

These practices cover the use of Flashback Data Archive.

Practice 11-1: Using Flashback Data Archive

In this practice, you use Oracle Total Recall.

- 1) Log into SQL*Plus as the SYS user and execute the flada_setup script from the \$HOME/labs directory. The setup script creates a second undo tablespace, a small FLA_TBS1 tablespace, and the ARCHIVE_ADMIN user with the oracle_4U password. The password is case-sensitive by default. Take a few moments to inspect the script before executing it.

```
$ sqlplus / as sysdba

SQL> @flada_setup
Connected.
SQL> set serveroutput on
SQL> -- set verify on
SQL> set term on
SQL> set lines 200
SQL> set pages 44
SQL> set pause on
SQL>
SQL> /*== Create a tablespace for your flashback data archive
==*/
SQL> DROP TABLESPACE fla_tbs1 INCLUDING CONTENTS
2 /
DROP TABLESPACE fla_tbs1 INCLUDING CONTENTS
*
ERROR at line 1:
ORA-00959: tablespace 'FLA_TBS1' does not exist

SQL> CREATE SMALLFILE TABLESPACE fla_tbs1
2 DATAFILE '$HOME/BACKUP/fla_tbs01.dbf'
3 SIZE 10M REUSE AUTOEXTEND ON NEXT 640K MAXSIZE 32767M
4 NOLOGGING EXTENT MANAGEMENT LOCAL SEGMENT SPACE
MANAGEMENT AUTO
5 /
Tablespace created.
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL>
SQL> /*== Create a second undo tablespace for testing ==*/
SQL> DROP TABLESPACE undotbs2 INCLUDING CONTENTS
2 /
DROP TABLESPACE undotbs2 INCLUDING CONTENTS
*
ERROR at line 1:
ORA-00959: tablespace 'UNDOTBS2' does not exist

SQL> CREATE SMALLFILE UNDO TABLESPACE undotbs2
2 DATAFILE '$HOME/BACKUP/undotbs02.dbf'
3 SIZE 105M REUSE AUTOEXTEND ON NEXT 5120K MAXSIZE 32767M
```

Practice 11-1: Using Flashback Data Archive (continued)

```
4 /

Tablespace created.

SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL> /*== Create an ARCHIVE_ADMIN user like the HR user ==*/
SQL> /*== with FLA_TBS1 default tablespace ==*/
SQL> CREATE USER ARCHIVE_ADMIN PROFILE DEFAULT IDENTIFIED BY
"oracle_4U"
2 DEFAULT TABLESPACE FLA_TBS1 TEMPORARY TABLESPACE TEMP
3 ACCOUNT UNLOCK;

User created.

SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL> GRANT ALTER SESSION TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT CREATE DATABASE LINK TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT CREATE SEQUENCE TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT CREATE SESSION TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT CREATE SYNONYM TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT CREATE VIEW TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT UNLIMITED TABLESPACE TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT EXECUTE ON SYS.DBMS_STATS TO ARCHIVE_ADMIN;
Grant succeeded.

SQL> GRANT CONNECT, RESOURCE TO ARCHIVE_ADMIN;
Grant succeeded.
SQL>
SQL> /*== Setup for Flashback Data Archive completed ==*/
SQL> /*== The ARCHIVE_ADMIN user has the password: oracle_4U
==*/
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...
SQL>
```


Practice 11-1: Using Flashback Data Archive (continued)

- 2) To give the ARCHIVE_ADMIN user administrative privileges for creating, maintaining, and dropping flashback data archives, execute the following command as the SYS user:

```
GRANT FLASHBACK ARCHIVE ADMINISTER TO archive_admin;
```

```
$ sqlplus / as sysdba
SQL> GRANT FLASHBACK ARCHIVE ADMINISTER TO archive_admin;

Grant succeeded.

SQL> exit
```

- 3) In SQL*Plus, connect as the ARCHIVE_ADMIN user with the ARCHIVE_ADMIN password.

Note: The password is case-sensitive; the username is not case-sensitive.

```
$ sqlplus archive_admin
Enter password: oracle_4U <<< not displayed

SQL>
```

- 4) To create a flashback data archive, execute the following command:

```
CREATE FLASHBACK ARCHIVE fla1
TABLESPACE fla_tbs1
QUOTA 10M
RETENTION 1 YEAR
/
```

Entering the command is recommended for better retention, but if typing is a difficulty, you can also execute the `flada_create.sql` script.

```
SQL> CREATE FLASHBACK ARCHIVE fla1
TABLESPACE fla_tbs1
QUOTA 10M
RETENTION 1 YEAR
/ 2 3 4 5

Flashback archive created.

SQL>
```

- 5) Give the privilege to use the FLA1 archive to the HR user, by executing the following command:

```
GRANT FLASHBACK ARCHIVE on FLA1 to HR;
```

```
SQL> GRANT FLASHBACK ARCHIVE on FLA1 to HR;

Grant succeeded.

SQL>
```

Practice 11-1: Using Flashback Data Archive (continued)

- 6) You now switch to the role of a flashback archive user. Connect as the HR user with the oracle_4U password. To enable this flashback data archive for the EMPLOYEES table, execute the following command:

```
ALTER TABLE hr.employees FLASHBACK ARCHIVE fl1;
```

```
SQL> connect HR
Enter password: oracle_4U <<< not displayed
Connected.
SQL> ALTER TABLE hr.employees FLASHBACK ARCHIVE fl1;

Table altered.

SQL>
```

- 7) To view and increase the salary of Mr. Fox three times by 1000, execute the flada_dml script as the HR user. This produces activity in the flashback data archive.

```
SQL> @flada_dml
SQL> REM "*****"
SQL> REM "For demo purposes ONLY: Flashback Data Archive "
SQL>
SQL> set echo on
SQL> set serveroutput on
SQL> -- set verify on
SQL> set term on
SQL> set lines 200
SQL> set pages 44
SQL> set pause on pause "Press [Enter] to continue..."
SQL>
SQL> /*== Query the current salary for Mr. Fox ==*/
SQL>
SQL> SELECT employee_id, last_name, salary
2 FROM hr.employees
3 WHERE last_name = 'Fox'
4 /
Press [Enter] to continue...

EMPLOYEE_ID LAST_NAME SALARY
-----
170 Fox 9600

1 row selected.

SQL>
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL>
SQL> /*== Increase the salary three times by 1000 ==*/
SQL>
SQL> UPDATE hr.employees
```

Practice 11-1: Using Flashback Data Archive (continued)

```

2  SET salary = salary + 1000
3  WHERE last_name = 'Fox'
4  /

1 row updated.

SQL> COMMIT
2  /

Commit complete.

SQL> UPDATE hr.employees
2  SET salary = salary + 1000
3  WHERE last_name = 'Fox'
4  /

1 row updated.

SQL> COMMIT
2  /

Commit complete.

SQL> UPDATE hr.employees
2  SET      salary = salary + 1000
3  WHERE   last_name = 'Fox'
4  /

1 row updated.

SQL> COMMIT
2  /

Commit complete.

SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL>
SQL> /*== Query the up-to-date value for Mr. Fox ==*/
SQL>
SQL> SELECT employee_id, last_name, salary
2  FROM   hr.employees
3  WHERE  last_name = 'Fox'
4  /
Press [Enter] to continue...

EMPLOYEE_ID LAST_NAME                SALARY
-----
          170 Fox                12600

1 row selected.

```

Practice 11-1: Using Flashback Data Archive (continued)

```
SQL>
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL>
SQL> set pause off
SQL>
```

- 8) To query the internal name of the archive table, execute the following command:

```
SELECT * FROM USER_FLASHBACK_ARCHIVE_TABLES;
```

```
SQL> SELECT * FROM USER_FLASHBACK_ARCHIVE_TABLES;
```

TABLE_NAME	OWNER_NAME
------------	------------

FLASHBACK_ARCHIVE_NAME	
------------------------	--

ARCHIVE_TABLE_NAME	
--------------------	--

EMPLOYEES	HR
-----------	----

FLA1	
------	--

SYS_FBA_HIST_73137	
--------------------	--

1 row selected.

```
SQL>
```

- 9) To ensure that the following queries use the archive tables, and not the undo, switch the undo tablespaces and drop the old one. As a SYS user, assign **UNDOTBS2** as the current undo tablespace, by using Enterprise Manager > Server > Automatic Undo Management > “Change Tablespace” button, selecting the UNDOTBS2 tablespace, and clicking OK, or by executing the following commands:

```
connect / as sysdba
```

```
ALTER SYSTEM SET UNDO_TABLESPACE=UNDOTBS2;
```

```
DROP TABLESPACE UNDOTBS1;
```

```
SQL> connect / as sysdba
```

```
Connected.
```

```
SQL> ALTER SYSTEM SET UNDO_TABLESPACE=UNDOTBS2;
```

```
System altered.
```

```
SQL> DROP TABLESPACE UNDOTBS1;
```

```
Tablespace dropped.
```

Note: If you execute the DROP command too quickly, while internal processing still occurs, you might receive an ORA-30013 error. Wait several minutes and try again.

Practice 11-1: Using Flashback Data Archive (continued)

- 10) As the HR user, choose a time after the creation of the flashback data archive and before you executed the erroneous DML. To view Mr. Fox's employee record as of that time, execute the following query (replace '15' MINUTE with your chosen historic date, format examples: '50' SECOND, '10' DAY, '5' MONTH):

Note: You receive an ORA-1466 error, if the time you specify a time before the flashback data archive was started. Reduce the time to a smaller interval and try again. If you still see the salary of 12600, increase your time interval.

```
SELECT employee_id, last_name, salary
FROM   hr.employees AS OF TIMESTAMP
       (SYSTIMESTAMP - INTERVAL '15' MINUTE)
WHERE  last_name = 'Fox';
```

Entering the command is recommended for better retention and selecting the right time interval, but if typing is a difficulty, you can also execute the flada_sel.sql script.

```
SQL> connect hr
Enter password: oracle_4U <<< not displayed
Connected.
SQL> SELECT employee_id, last_name, salary
       2 FROM hr.employees AS OF TIMESTAMP
       3 (SYSTIMESTAMP - INTERVAL '15' MINUTE)
       4 WHERE last_name = 'Fox';

EMPLOYEE_ID LAST_NAME SALARY
-----
170 Fox 9600
1 row selected.
SQL>
```

- 11) As the HR user, you realize that the recent updates were mistakes. To revert to the original values for your chosen historic date (for example, ten minutes ago), execute the following command (replace '15' MINUTE with your chosen historic date):

```
UPDATE hr.employees
SET salary = (SELECT salary FROM hr.employees
              AS OF TIMESTAMP (SYSTIMESTAMP - INTERVAL '15' MINUTE)
              WHERE last_name = 'Fox')
WHERE last_name = 'Fox';
```

Entering the command is recommended for better retention and selecting the right time interval, but if typing is a difficulty, you can also execute the flada_upd.sql script.

```
SQL> UPDATE hr.employees
       2 SET salary = (SELECT salary FROM hr.employees
       3 AS OF TIMESTAMP (SYSTIMESTAMP - INTERVAL '15' MINUTE)
       4 WHERE last_name = 'Fox')
```

Practice 11-1: Using Flashback Data Archive (continued)

```
5 WHERE last_name = 'Fox';

1 row updated.

SQL>
```

- 12) From your SQL*Plus session, connect to the database as the SYS user and list the data dictionary views available to you. Execute the flada_list1.sql file:

```
SQL> connect / as sysdba
Connected.
SQL> @flada_list1
SQL> REM "*****"
SQL> REM "For demo purposes ONLY:"
SQL>
SQL> connect / as sysdba
Connected.
SQL>
SQL> set echo on
SQL> set serveroutput on
SQL> -- set verify on
SQL> set term on
SQL> set lines 200
SQL> set pages 44
SQL> set pause on pause "Press [Enter] to continue ..."
SQL>
SQL> /*== To list the available data dictionary views ==*/
SQL>
SQL> SELECT table_name
2 FROM dict
3 WHERE table_name LIKE '%FLASHBACK_ARCHIVE%'
4 /
Press [Enter] to continue ...

TABLE_NAME
-----
DBA_FLASHBACK_ARCHIVE
DBA_FLASHBACK_ARCHIVE_TABLES
DBA_FLASHBACK_ARCHIVE_TS
USER_FLASHBACK_ARCHIVE
USER_FLASHBACK_ARCHIVE_TABLES

SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL>
SQL> col FLASHBACK_ARCHIVE_NAME format A25
SQL> col ARCHIVE_TABLE_NAME format A20
SQL> col TABLE_NAME format A12
SQL> col OWNER_NAME format A10
SQL>
SQL> DESC dba_flashback_archive
```

Practice 11-1: Using Flashback Data Archive (continued)

```

Name
Null?      Type
-----
-----
-----
-----
OWNER_NAME
VARCHAR2(30)
FLASHBACK_ARCHIVE_NAME
NOT NULL VARCHAR2(255)
FLASHBACK_ARCHIVE#
NOT NULL NUMBER
RETENTION_IN_DAYS
NOT NULL NUMBER
CREATE_TIME
TIMESTAMP(9)
LAST_PURGE_TIME
TIMESTAMP(9)
STATUS
VARCHAR2(7)

SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL>
SQL> /*== To query the time when the flashback data archive(s)
have been created ==*/
SQL>
SQL> SELECT flashback_archive_name, create_time, status
2      FROM dba_flashback_archive
3      /
Press [Enter] to continue ...

FLASHBACK_ARCHIVE_NAME      CREATE_TIME
STATUS
-----
-----
FLA1                          05-JUN-09 11.06.09.000000000 PM

SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL>
SQL> DESC dba_flashback_archive_ts
Name
Null?      Type
-----
-----
-----
FLASHBACK_ARCHIVE_NAME
NOT NULL VARCHAR2(255)

```

Practice 11-1: Using Flashback Data Archive (continued)

```
FLASHBACK_ARCHIVE#
NOT NULL NUMBER
TABLESPACE_NAME
NOT NULL VARCHAR2(30)
QUOTA_IN_MB
VARCHAR2(40)
```

SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL>
SQL> /*== To list the tablespace(s), which are used for
flashback data archives ==*/
SQL>
SQL> SELECT *
2 FROM dba_flashback_archive_ts
3 /
Press [Enter] to continue ...

FLASHBACK_ARCHIVE_NAME	FLASHBACK_ARCHIVE#	TABLESPACE_NAME	QUOTA_IN_MB
FLA1	1	FLA_TBS1	10

SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL>
SQL> DESC dba_flashback_archive_tables

Name	Null?	Type
TABLE_NAME		NOT NULL VARCHAR2(30)
OWNER_NAME		NOT NULL VARCHAR2(30)
FLASHBACK_ARCHIVE_NAME		NOT NULL VARCHAR2(255)
ARCHIVE_TABLE_NAME		VARCHAR2(53)
STATUS		VARCHAR2(8)

SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

Practice 11-1: Using Flashback Data Archive (continued)

```
SQL>
SQL> /*== Query the table name(s), the owner name(s), and ==*/
SQL> /*== the internal "history" table name(s) of the
flashback data archive ==*/
SQL>
SQL> SELECT *
      2 FROM   dba_flashback_archive_tables
      3 /
Press [Enter] to continue ...
```

TABLE_NAME	OWNER_NAME	FLASHBACK_ARCHIVE_NAME	ARCHIVE_TABLE_NAME
EMPLOYEES	HR	FLA1	SYS_FBA_HIST_73137

```
SQL>
SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL> clear columns
SQL>
```

- 13) As the HR user (with the `oracle_4U` password), list the `FLASHBACK_ARCHIVE` data dictionary tables, which are accessible to you. You can execute the `flada_list2` script, if you prefer not enter the commands directly.

```
SQL> connect hr
Enter password: oracle_4U <<< not displayed
Connected.
SQL> @flada_list2

SQL> SELECT table_name
      2 FROM   dict
      3 WHERE  table_name LIKE '%FLASHBACK_ARCHIVE%'
      4 /
Press [Enter] to continue ...
```

TABLE_NAME
USER_FLASHBACK_ARCHIVE
USER_FLASHBACK_ARCHIVE_TABLES

```
SQL> pause Press [Enter] to continue ...
Press [Enter] to continue ...

SQL> exit
$
```

- 14) To practice additional flashback data archive maintenance tasks, perform the following steps: Log into SQL*Plus as the `ARCHIVE_ADMIN` user.

```
$ sqlplus ARCHIVE_ADMIN
Enter password: oracle_4U <<< not displayed
```

Practice 11-1: Using Flashback Data Archive (continued)

```
SQL>
```

- 15) Data in the flashback data archive is automatically purged when the retention time expires. However, you can also purge data explicitly with the following command to purge data older than two minutes:

```
ALTER FLASHBACK ARCHIVE fla1 PURGE BEFORE TIMESTAMP  
(SYSTIMESTAMP - INTERVAL '2' MINUTE);
```

```
SQL> ALTER FLASHBACK ARCHIVE fla1 PURGE BEFORE  
TIMESTAMP(SYSTIMESTAMP - INTERVAL '2' MINUTE);
```

```
Flashback archive altered.
```

```
SQL>
```

- 16) Execute the flada_tbs2.sql script to create an additional 10 MB tablespace as the SYS user.

```
SQL> @flada_tbs2
```

```
Connected.
```

```
SQL> set serveroutput on
```

```
SQL> -- set verify on
```

```
SQL> set term on
```

```
SQL> set lines 200
```

```
SQL> set pages 44
```

```
SQL> set pause on
```

```
SQL>
```

```
SQL> /*== Create another tablespace ==*/
```

```
SQL>
```

```
SQL> DROP TABLESPACE fla_tbs2 INCLUDING CONTENTS
```

```
2 /
```

```
DROP TABLESPACE fla_tbs2 INCLUDING CONTENTS
```

```
*
```

```
ERROR at line 1:
```

```
ORA-00959: tablespace 'FLA_TBS2' does not exist
```

```
SQL>
```

```
SQL> CREATE SMALLFILE TABLESPACE fla_tbs2
```

```
2 DATAFILE '$HOME/BACKUP/fla_tbs02.dbf'
```

```
3 SIZE 10M REUSE AUTOEXTEND ON NEXT 640K MAXSIZE 32767M
```

```
4 NOLOGGING EXTENT MANAGEMENT LOCAL SEGMENT SPACE
```

```
MANAGEMENT AUTO
```

```
5 /
```

```
Tablespace created.
```

```
SQL> pause Press [Enter] to continue...
```

```
Press [Enter] to continue...
```

```
SQL>
```

Practice 11-1: Using Flashback Data Archive (continued)

- 17) As the ARCHIVE_ADMIN user, add 5 MB of the FLA_TBS2 tablespace to the FLA1 flashback data archive.

```
SQL> connect ARCHIVE_ADMIN
Enter password: oracle_4U <<< not displayed
Connected.
SQL> ALTER FLASHBACK ARCHIVE fla1 ADD TABLESPACE fla_tbs2
QUOTA 5M;

Flashback archive altered.

SQL>
```

- 18) All tables in one specific flashback data archive have the same retention time. Change the retention time of the FLA1 flashback data archive to two years.

```
SQL> ALTER FLASHBACK ARCHIVE fla1 MODIFY RETENTION 2 YEAR;

Flashback archive altered.

SQL>
```

- 19) As the ARCHIVE_ADMIN user, drop the FLA1 flashback data archive.

Note: Dropping a flashback data archive includes dropping the internal tamper-proofed history table. You cannot drop this table directly due to auditing and security requirements. Dropping a flashback data archive does not drop the tablespaces in which they are stored, because the tablespaces might contain other data.

```
SQL> DROP FLASHBACK ARCHIVE fla1;

Flashback archive dropped.

SQL>
```

- 20) Wait a minute or two and connect as SYS user; clean up your environment by executing the flada_cleanup.sql script.

```
SQL> @flada_cleanup
SQL> REM Execute this script script for training purposes only
SQL> REM Undo Cleanup for Flashback Data Archive
SQL> REM Execute script as SYSDBA
SQL>
SQL> set echo on
SQL> set serveroutput on
SQL> set term on
SQL> set lines 200
SQL> set pause on
SQL>
SQL> connect / as sysdba
Connected.
SQL> set echo off

Tablespace created.
```

Practice 11-1: Using Flashback Data Archive (continued)

```
SQL>
SQL> ALTER SYSTEM SET UNDO_TABLESPACE=undotbs1
      2  /

System altered.

SQL> DROP TABLESPACE fla_tbs1 INCLUDING CONTENTS
      2  /

Tablespace dropped.

SQL> DROP TABLESPACE fla_tbs2 INCLUDING CONTENTS
      2  /

Tablespace dropped.

SQL>
SQL> DROP TABLESPACE undotbs2 INCLUDING CONTENTS
      2  /

Tablespace dropped.

SQL> host rm -f $HOME/BACKUP/fla_tbs01.dbf

SQL> host rm -f $HOME/BACKUP/fla_tbs02.dbf

SQL> host rm -f $HOME/BACKUP/undotbs02.dbf

SQL> prompt Flashback Data Archive cleanup complete.
Flashback Data Archive cleanup complete.
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL> exit
```

Note: If you execute the DROP command too quickly while internal processing is still occurring, you might receive an ORA-30013 error. Wait and try again.

Practice 11-2: Using the Recycle Bin

In this practice you use the recycle bin to restore dropped objects. You can do this with SQL commands or with Enterprise Manager. *For the former, perform steps 1 through 4. For the latter, perform step 1, and then steps 5 through 11.*

- 1) This workshop scenario simulates loss of data. Point to the `orcl` instance. To introduce the problem, change directory to `$HOME/labs` and run the `recyclebin_lab.sh` as shown:

```
$ cd $HOME/labs
$. oraenv
ORACLE_SID = [orcl] ? orcl

$ ./recyclebin_lab.sh
SQL> SQL>
Table dropped.

SQL> SQL> select * from hr.departments
          *
ERROR at line 1:
ORA-00942: table or view does not exist

SQL> select * from hr.departments
          *
ERROR at line 1:
ORA-00942: table or view does not exist

SQL> select * from hr.departments
          *
ERROR at line 1:
ORA-00942: table or view does not exist
```

- 2) The lab script drops the `HR.DEPARTMENTS` table including indexes, restraints, and so on. Query the `DBA_RECYCLE_BIN` view to confirm this.

```
$ sqlplus / as sysdba
SQL> COL OWNER FORMAT A5
SQL> SELECT owner, original_name, droptime
FROM dba_recyclebin WHERE owner = 'HR';
```

OWNER	ORIGINAL_NAME	DROPTIME
HR	DEPT_ID_PK	2009-06-06:15:31:05
HR	DEPARTMENTS	2009-06-06:15:31:05
HR	DEPT_LOCATION_IX	2009-06-06:15:31:04

- 3) Use Flashback Table to restore the dropped objects. You can use Flashback Table through Enterprise Manager or through SQL*Plus. To flash back the table using Enterprise Manager, go to step 5.

Practice 11-2: Using the Recycle Bin (continued)

```
SQL> FLASHBACK TABLE hr.departments TO BEFORE DROP;
```

Flashback complete.

```
SQL>
```

- 4) Perform a select operation against the HR.DEPARTMENTS table to confirm the success of the Flashback Table operation, then exit

```
SQL> SELECT * FROM hr.departments;
```

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
10	Administration	200	1700
20	Marketing	201	1800
30	Purchasing	114	1700

...

```
SQL> exit
```

- 5) The HR.DEPARTMENTS table can also be flashed back using Enterprise Manager.
- 6) Log in as the SYS user with the oracle_4U password and connect as SYSDBA.
- 7) In EM, navigate to Schema > Tables.
- 8) Click the Recycle Bin button, enter HR in the Schema Name field and click Go.

Recycle Bin

When you drop a table from a non-system, locally managed tablespace, Oracle does not immediately reclaim the space associated with the table. Oracle places the table and any associated objects in the Recycle Bin, where, in case the table was dropped in error, it can be recovered (Flashback Drop) at a later time.

Search

Schema Name

Table

Results

[Select All](#) | [Select None](#) | [Expand All](#) | [Collapse All](#)

Select	Object Name	Schema	Recovery Scope	Tablespace	Drop Time	Create Time	Size	Operation
<input type="checkbox"/>	Recycle Bin							<input type="button" value="View Content"/>

- 9) Click the + icon before DEPARTMENTS, to see the dependant objects.

Practice 11-2: Using the Recycle Bin (continued)

Recycle Bin

When you drop a table from a non-system, locally managed tablespace, Oracle does not immediately reclaim the space associated with the table. Oracle places the table and any associated objects in the Recycle Bin, where, in case the table was dropped in error, it can be recovered (Flashback Drop) at a later time.

Search

Schema Name: Table:

Results

Select	Object Name	Schema	Recovery Scope	Tablespace	Drop Time	Create Time	Size	Operation
<input type="checkbox"/>	Recycle Bin							<input type="button" value="View Content"/>
<input checked="" type="checkbox"/>	DEPARTMENTS	HR	TABLE	EXAMPLE	2009-06-06:15:36:53	2009-05-14:22:40:29.8		<input type="button" value="View Content"/>
<input type="checkbox"/>	"BIN\$a6nUbymfDf7gQLmLiSMWzA==\$0"	HR	INDEX	EXAMPLE	2009-06-06:15:36:53	2009-05-14:22:40:29.8		<input type="button" value="View Content"/>
<input type="checkbox"/>	"BIN\$a6nUbymgDf7gQLmLiSMWzA==\$0"	HR	INDEX	EXAMPLE	2009-06-06:15:36:53	2009-05-14:22:40:29.8		<input type="button" value="View Content"/>

- 10) Select DEPARTMENTS from the list and click the Flashback Drop button.

Dropped Objects Selection **Rename** Review

Perform Object Level Recovery: Rename

Recovery Scope: **Tables** Step 2 of 3

Operation Type: **Flashback Dropped Tables**

Specify a new name for the dropped tables.

Table Owner	Table Name	New Name
HR	DEPARTMENTS	DEPARTMENT

- 11) The Perform Object Level Recovery: Rename page allows you to rename the restored object. Accept the default or original name and click Next.

Perform Object Level Recovery: Review

Recovery Scope: **Tables** Step 3 of 3

Operation Type: **Flashback Dropped Tables**

The following shows the tables and dependent objects that will be flashed back.

Impact Analysis

The following tables will be flashed back.

- Table Name: HR.DEPARTMENTS
New Name: DEPARTMENTS
The dependent objects that will be flashed back:
INDEX: HR. "BIN\$a6nUbymfDf7gQLmLiSMWzA==\$0"
New Name: "BIN\$a6nUbymfDf7gQLmLiSMWzA==\$0"
INDEX: HR. "BIN\$a6nUbymgDf7gQLmLiSMWzA==\$0"
New Name: "BIN\$a6nUbymgDf7gQLmLiSMWzA==\$0"

- 12) On the Review page, inspect the Impact Analysis. Note that the table and dependent objects are to be restored and note the names they will be restored to.

Practice 11-2: Using the Recycle Bin (continued)

SQL

FLASHBACK TABLE HR. "BIN\$a6npM+E5uR/gQLmLiSMYDQ==\$0" TO BEFORE DROP

OK

13) Optionally, click the Show SQL button, review the SQL and click OK.

Perform Object Level Recovery: Review

Recovery Scope: **Tables** Cancel Show SQL Back Step 3 of 3 Submit

Operation Type: **Flashback Dropped Tables**

The following shows the tables and dependent objects that will be flashed back.

Impact Analysis

The following tables will be flashed back.

1. Table Name: HR.DEPARTMENTS
 New Name: DEPARTMENTS
 The dependent objects that will be flashed back:
 INDEX: HR.DEPT_LOCATION_IX
 New Name: DEPT_LOCATION_IX
 INDEX: HR.DEPT_ID_PK
 New Name: DEPT_ID_PK

Return to Perform Recovery Cancel Show SQL Back Step 3 of 3 Submit

Database | Setup | Preferences | Help | Logout

14) Click Submit.

Confirmation

The selected tables, HR.DEPARTMENTS, have been flashed back from the recycle bin.

OK

15) Click OK on the Confirmation page.

16) To view table data in EM:

- Click the Tables breadcrumb.
- Enter HR as Schema and click Go.
- Select the DEPARTMENTS table, then the View Data Actions, and click Go to execute the action.

Edit		View		Delete With Options		Actions		View Data		Go	
Select	Schema	Table Name	Tablespace	Partitioned	Rows	Last Analyze					
<input type="radio"/>	HR	COUNTRIES	EXAMPLE	NO	25	May 14, 2009 10:40:28 PM GMT+07:00					
<input checked="" type="radio"/>	HR	DEPARTMENTS	EXAMPLE	NO	27	May 14, 2009 10:40:29 PM GMT+07:00					

Practice 11-2: Using the Recycle Bin (continued)

17) After confirming that the data are restored, click OK. Then exit EM.

Database Instance: [orcl.us.oracle.com](#) > [Tables](#) > Logged in As SYS

View Data for Table: HR.DEPARTMENTS

[Refine Query](#) [OK](#)

Query

```
SELECT "DEPARTMENT_ID", "DEPARTMENT_NAME", "MANAGER_ID",  
"LOCATION_ID" FROM "HR"."DEPARTMENTS"
```

Result

Previous 1-25 of 27 Next 2

DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
10	Administration	200	1700
20	Marketing	201	1800
30	Purchasing	114	1700
40	Human Resources	203	2400

Practices for Lesson 12

In this lesson you learn to flash back an entire database.

Background: In this scenario, the HR reorganization job runs prematurely, and you must undo its changes. The changes are such that you are not sure what tables are involved. So, you decide (now that flashback logging has been enabled) to use Flashback Database instead of performing a recovery.

Practice 12-1: Flashback Database

Flash back an entire database. Unless specified otherwise, you should log in as the SYS user as SYSDBA through SQL*Plus or Database Control.

- 1) Using Enterprise Manager, turn on flashback logging for your database (enable Flashback Database).
 - a) In Database Control, click the Availability tab, and then the Recovery Settings link in the Backup/Recovery Setup region.
 - b) Scroll down and select the Enable Flashback Database check box. Click Apply. On the Confirmation page, click Yes to proceed with the database shutdown.

Flash Recovery

This database is using a flash recovery area. The chart shows space used by each file type that is not reclaimable by Oracle. Performing backups to tertiary storage is one way to make space reclaimable. Usable Flash Recovery Area includes free and reclaimable space.

Flash Recovery Area Location 

Flash Recovery Area Size Flash Recovery Area Size must be set when the location is set.

Non-reclaimable Flash Recovery Area (GB) **1.68**

Reclaimable Flash Recovery Area (MB) **6**

Free Flash Recovery Area (GB) **8.31**

☒ **Enable Flashback Database***
Flashback database can be used for fast database point-in-time recovery, as it returns the database to a prior point-in-time without restoring files. Flashback is the preferred point-in-time recovery method in the recovery wizard when appropriate. The flash recovery area must be set to enable flashback database.

- c) On the Confirmation page, click Yes to restart your database.
- d) On the Restart Database: Specify Host and Target Database Credentials, ensure that oracle is entered as username and as password. Then click OK.
- e) Optionally, on the Restart Database: Confirmation page, click Show SQL, review the SQL and click Return.

Practice 12-1: Flashback Database (continued)

```
Show SQL

SHUTDOWN immediate
STARTUP mount
ALTER DATABASE FLASHBACK ON
ALTER DATABASE OPEN READ WRITE

The startup command will use a temporary file as pfile with the following
init.ora parameters:

spfile='+DATA/orcl/spfileorcl.ora'
```

- f) Click Yes on the Restart Database: Confirmation page.
- g) Click Refresh and wait for the database to restart. (If you receive an internal error, just click OK and then again Refresh.) - You may need to click Refresh several times.
- 2) After the database has been restarted with flashback logging enabled, note the lowest SCN of the database
 - a) On the Database home page, click the Flashback Time link in the High Availability section. [45]
 - b) On the Recovery Settings page, at the bottom of the Flash Recovery section, note the Lowest SCN [[46r]] (1136492 in this example).
- 3) Alternatively, you can view and note the current SCN of the database by querying the V\$DATABASE view.

Note: You will need the SCN later.

SCN: _____

- a) Enter the following:

```
$ cd $HOME/labs
$ sqlplus / as sysdba
SQL> SELECT current_scn FROM v$database;

CURRENT_SCN
-----
      1137367
```

- 4) Note the sum of the salaries in the HR.EMPLOYEES table and the count of the rows in the JOB_HISTORY table.

```
SQL> SELECT SUM(salary) FROM hr.employees;

SUM(SALARY)
-----
```

Practice 12-1: Flashback Database (continued)

```
691416

SQL> SELECT COUNT(*) FROM hr.job_history;

COUNT(*)
-----
10
```

5) To perform some HR reorganization updates, .

- a) Connect as HR user with the oracle_4U password.
- b) Execute the flb_db_txn.sql script.

```
SQL> connect hr
Enter password: oracle_4U <<< not displayed
Connected.
SQL> @flb_db_txn.sql
SQL>
SQL> update employees set department_id = 90 where job_id =
'IT_PROG';

5 rows updated.

SQL>
SQL> update employees e set salary = least(e.salary,(select
(min_salary + max_salary)/2 * 1.10 from jobs j where j.job_id
= e.job_id)) where job_id not like 'AD_%';

103 rows updated.

SQL>
SQL> commit;

Commit complete.

SQL>
```

6) As the SYS user, note the current SCN in the database again, and also the salary sum and the JOB_HISTORY row count.

Note that these values are different from what was queried in steps 2 and 3.

```
SQL> connect / as sysdba
Connected.
SQL> SELECT current_scn FROM v$database;

CURRENT_SCN
-----
```

Practice 12-1: Flashback Database (continued)

```
1137586

SQL> SELECT SUM(salary) FROM hr.employees;

SUM(SALARY)
-----
 679092.4

SQL> SELECT COUNT(*) FROM hr.job_history;

COUNT(*)
-----
      15

SQL>
```

- 7) Using RMAN, flash back the database to the first SCN value noted in step 2 (1137367 in this example).

- a) Shut down and then mount the database by entering the following:

```
SQL> SHUTDOWN IMMEDIATE
Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> STARTUP MOUNT
ORACLE instance started.

Total System Global Area 481259520 bytes
Fixed Size                1337324 bytes
Variable Size             385878036 bytes
Database Buffers          88080384 bytes
Redo Buffers              5963776 bytes
Database mounted.
SQL> exit
```

- b) If you have any RMAN open, close them. Then log in to RMAN again.

```
$ rman target / nocatalog
connected to target database: ORCL (DBID=1220535480, not open)
using target database control file instead of recovery catalog

RMAN>
```

- c) At the RMAN prompt, enter the FLASHBACK DATABASE command, and supply the SCN number recorded in step 2:

```
RMAN> FLASHBACK DATABASE TO SCN=1137367;

Starting flashback at 2009-07-23:21:05:29
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=27 device type=DISK
```

Practice 12-1: Flashback Database (continued)

```
allocated channel: ORA_SBT_TAPE_1
channel ORA_SBT_TAPE_1: SID=28 device type=SBT_TAPE
channel ORA_SBT_TAPE_1: WARNING: Oracle Test Disk API

starting media recovery
media recovery complete, elapsed time: 00:00:03

Finished flashback at 2009-07-23:21:05:34

RMAN>
```

- 8) Before opening the database for read and write operations, verify that the database was flashed back to the correct SCN by looking at the contents of the tables and seeing that they are back to what was noted in step 3.

- a) Logged into SQL*Plus as SYSDBA, enter the following command to open the database in read-only mode:

```
SQL> alter database open read only;
Database altered.
```

- b) Enter the following at the SQL prompt to determine the salary sum for the EMPLOYEES table.

```
SQL> SELECT SUM(salary) FROM hr.employees;

SUM(SALARY)
-----
691416
```

- 9) Open the database for read and write operations. You have to use the RESETLOGS keyword.

- a) Shut down the database:

```
SQL> shutdown immediate
Database closed.
Database dismounted.
ORACLE instance shut down.
```

- b) Start up the database in the MOUNT state:

```
SQL> startup mount
ORACLE instance started.

Total System Global Area 481259520 bytes
Fixed Size 1337324 bytes
Variable Size 385878036 bytes
Database Buffers 88080384 bytes
```

Practice 12-1: Flashback Database (continued)

```
Redo Buffers                    5963776 bytes
Database mounted.
SQL>
```

c) Open the database in read/write mode with resetlogs:

```
SQL> alter database open resetlogs;

Database altered.
```

(The command might take a while to execute.)

- 10) At this point you can familiarize yourself with the flashback-related V\$ views. To see time values, alter your session to display hours, minutes, and seconds with any date values.

```
SQL> ALTER SESSION SET NLS_DATE_FORMAT="yyyy-mm-dd
hh24:mi:ss";
```

- 11) Query the V\$FLASHBACK_DATABASE_LOG view and determine the lowest SCN that the database can be flashed back to. Record your answer here: _____

```
SQL> set wrap off
SQL> select * from v$FLASHBACK_DATABASE_LOG;

OLDEST_FLASHBACK_SCN OLDEST_FLASHBACK_TI RETENTION_TARGET
FLASHBACK_SIZE
-----
-----
1136492 2009-07-23 20:47:17 1440
16384000
SQL>
```

- 12) View the overhead associated with flashback logging and related operations by querying V\$FLASHBACK_DATABASE_STAT. What is the average number of bytes of flashback data written per minute during this time interval?

```
SQL> select * from V$FLASHBACK_DATABASE_STAT;

truncating (as requested) before column
ESTIMATED_FLASHBACK_SIZE

OLDEST_FLASHBACK_SCN OLDEST_FLASHBACK_TI RETENTION_TARGET
FLASHBACK_SIZE
-----
-----
1136492 2009-07-23 20:47:17 1440
16384000
SQL> select * from V$FLASHBACK_DATABASE_STAT;
```


Practice 12-1: Flashback Database (continued)

```
truncating (as requested) before column
ESTIMATED_FLASHBACK_SIZE

BEGIN_TIME          END_TIME          FLASHBACK_DATA
DB_DATA  REDO_DATA
-----
2009-07-23 21:07:56 2009-07-23 21:12:13          4538368
0      1372160
SQL>
```

In the example above, the answer is 4538368 / (21:07 - 21:12) which is 907673 bytes per minute. Your numbers may vary slightly.

- 13) Determine the current size of stored flashback data by querying V\$FLASHBACK_DATABASE_LOG. Record your answer here: _____.

```
SQL> SELECT flashback_size FROM V$FLASHBACK_DATABASE_LOG;

FLASHBACK_SIZE
-----
24576000
```

Note: Your results will probably vary slightly from those shown here.

- 14) To turn off the flashback database functionality, execute the following command.

```
SQL> ALTER DATABASE FLASHBACK OFF;
Database altered.
SQL> exit
```

Note: The command might take a couple of minutes to execute.

In this practice, you use Automatic Memory Management to show that you no longer need to manually modify `SGA_TARGET` and `PGA_AGGREGATE_TARGET`. You observe the memory distribution when you run an expensive parallel query that consumes a lot of SGA memory.

Practice 13-1: Using Automatic Memory Management

In this practice, you use the various new memory management capabilities.

- 1) For your `orcl` database, navigate into the `labs` directory, turn off archiving, and stop Enterprise Manager Database Control.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$ cd ~/labs
$ ./orcl_to_noarchivelog.sh
Database closed.
Database dismounted.
ORACLE instance shut down.
ORACLE instance started.

Total System Global Area  481259520 bytes
Fixed Size                  1337352 bytes
Variable Size              373295096 bytes
Database Buffers          100663296 bytes
Redo Buffers                5963776 bytes
Database mounted.

Database altered.

Database altered.

$ emctl stop dbconsole
Oracle Enterprise Manager 11g Database Control Release
11.2.0.0.2
Copyright (c) 1996, 2009 Oracle Corporation. All rights
reserved.
https://edrsr37p1.us.oracle.com:1158/em/console/aboutApplicati
on
Stopping Oracle Enterprise Manager 11g Database Control ...
... Stopped.
$
```

- 2) **Make a copy of your SPFILE**, logged in to SQL*Plus for the `orcl` instance as the `SYS` user with the `oracle_4U` password.

```
$ sqlplus / as sysdba
SQL> CREATE PFILE='/tmp/initorcl.ora.bak' FROM SPFILE;

File created.
SQL>
```

Practice 13-1: Using Automatic Memory Management (continued)

- 3) Still connected as the SYS user in SQL*Plus, set the following parameters to the given value in your SPFILE only! Use the amm_parameters.sql file located in your /home/oracle/labs directory.

```
_PX_use_large_pool = TRUE
_memory_broker_stat_interval = 5
_memory_management_tracing = 31
parallel_execution_message_size = 36864
parallel_max_servers = 200
parallel_adaptive_multi_user = FALSE
processes = 200
sga_target = 0
pga_aggregate_target = 0
memory_target = 300M
```

```
SQL> @amm_parameters
SQL> alter system set "_PX_use_large_pool" = TRUE
SCOPE=SPFILE;

System altered.

SQL> alter system set "_memory_broker_stat_interval" = 5
SCOPE=SPFILE;

System altered.

SQL> alter system set "_memory_management_tracing" = 31
SCOPE=SPFILE;

System altered.

SQL> alter system set "parallel_execution_message_size" =
36864 SCOPE=SPFILE;

System altered.

SQL> alter system set "parallel_max_servers" = 200
SCOPE=SPFILE;

System altered.

SQL> alter system set "parallel_adaptive_multi_user" = FALSE
SCOPE=SPFILE;

System altered.

SQL> alter system set "processes" = 200 SCOPE=SPFILE;

System altered.

SQL> alter system set "pga_aggregate_target" = 0 SCOPE=SPFILE;
```

Practice 13-1: Using Automatic Memory Management (continued)

```
System altered.

SQL> alter system set "sga_target" = 0 SCOPE=SPFILE;

System altered.

SQL> alter system set "memory_target" = 300M SCOPE=SPFILE;

System altered.

SQL>
```

4) Execute the amm_setup.sql script.

- a) Drop and recreate the TBSSGA and MYTEMP tablespaces and the AMM DBA user for whom they are defaults. Then press Enter to continue.

```
SQL> @amm_setup.sql
SQL> REM "***** "
SQL> REM "For training purposes ONLY, execute as the oracle OS
user
SQL>
SQL> set echo on
SQL> set serveroutput on
SQL> set term on
SQL> set lines 200
SQL> set pages 44
SQL> set pause on pause "Press [Enter] to continue..."
SQL>

SQL> drop tablespace tbssga including contents and datafiles;
drop tablespace tbssga including contents and datafiles
*
ERROR at line 1:
ORA-00959: tablespace 'TBSSGA' does not exist

SQL>
SQL> create tablespace tbssga datafile '+DATA' size 20m;

Tablespace created.

SQL>
SQL> drop tablespace mytemp including contents and datafiles;
drop tablespace mytemp including contents and datafiles
*
ERROR at line 1:
ORA-00959: tablespace 'MYTEMP' does not exist
```

Practice 13-1: Using Automatic Memory Management (continued)

```
SQL>
SQL> create temporary tablespace mytemp tempfile '+DATA' size
40m reuse;

Tablespace created.
SQL>
SQL> drop user amm cascade;
drop user amm cascade
      *
ERROR at line 1:
ORA-01918: user 'AMM' does not exist

SQL>
SQL> create user amm identified by "oracle_4U"
      2 default tablespace tbssga
      3 temporary tablespace mytemp;

User created.

SQL>
SQL> grant connect,resource,dba to amm;

Grant succeeded.
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...
```

- b) To view the current memory components, query the `V$MEMORY_DYNAMIC_COMPONENTS` view by pressing Enter to continue the script.

```
SQL>
SQL>
SQL> SELECT substr(COMPONENT, 0, 10) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US
      2 FROM v$memory_dynamic_components
      3 WHERE CURRENT_SIZE!=0;
Press [Enter] to continue...
```

- c) View the query result by pressing Enter to continue the script.

```
SQL> column COMP format a10
SQL>
SQL> SELECT substr(COMPONENT, 0, 10) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US
      2 FROM v$memory_dynamic_components
      3 WHERE CURRENT_SIZE!=0;
Press [Enter] to continue...

COMP                CS                US
-----
-----
```

Practice 13-1: Using Automatic Memory Management (continued)

```
shared poo 167772160      0
large pool  4194304       0
java pool   4194304       0
SGA Target  289406976     0
DEFAULT bu  104857600     0
PGA Target  192937984     0

6 rows selected.

SQL> pause Press [Enter] to continue...
Press [Enter] to continue...

SQL>
```

- 5) Log in as the AMM user with the oracle_4U password, recreate the TABSGA table and insert rows by pressing Enter to continue the script.

```
SQL> connect amm
Enter password: oracle_4U <<< not displayed
Connected.
SQL> @amm_setup2.sql
SQL> REM "*****"
SQL> REM "For training purposes ONLY"
SQL> REM Connected as the AMM user with the oracle_4U
password
SQL> set serveroutput on
SQL> set term on
SQL> set lines 200
SQL> set pages 44
SQL> set pause on pause "Press [Enter] to continue..."
SQL> drop table tabsga purge;
drop table tabsga purge
*
ERROR at line 1:
ORA-00942: table or view does not exist

SQL>
SQL> create table tabsga(a number, b number) tablespace
tbssga;

Table created.

SQL>
SQL> begin
2   for i in 1..100000 loop
3       insert into tabsga values (i, i);
4   end loop;
5 end;
6 /
```

Practice 13-1: Using Automatic Memory Management (continued)

PL/SQL procedure successfully completed.

SQL> commit;

Commit complete.

SQL> pause Press [Enter] to continue...

Press [Enter] to continue...

- a) Modify the TABSGA table to “parallel 64”, create a TESTPGA procedure (which creates a workload) by pressing Enter to continue the script.

SQL>

SQL> alter table tabsga parallel 64;

Table altered.

SQL>

SQL> create or replace procedure testpga(psize number) as

2 begin

3 declare

4 TYPE nAllotment_tabtyp IS TABLE OF char(2048) INDEX BY
BINARY_INTEGER;

5 myarray nAllotment_tabtyp;

6 begin

7 for i in 1..psize loop

8 myarray(i) := to_char(i);

9 end loop;

10 end;

11 end;

12 /

Procedure created.

SQL> pause Press [Enter] to continue...

Press [Enter] to continue...

- b) Confirm that there are no errors and query the dynamic memory components again by pressing Enter to continue the script.

SQL> show errors

No errors.

SQL>

SQL> SELECT substr(COMPONENT, 0, 10) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US

2 FROM v\$memory_dynamic_components

3 WHERE CURRENT_SIZE!=0;

Press [Enter] to continue...

- c) To view the query results, press Enter to continue the script.

COMP	CS	US
-----	-----	-----

Practice 13-1: Using Automatic Memory Management (continued)

```
shared poo 167772160      0
large pool  4194304       0
java pool   4194304       0
SGA Target  289406976     0
DEFAULT bu  104857600     0
PGA Target  192937984     0
```

6 rows selected.

SQL>

SQL> pause Press [Enter] to exit the script...

Press [Enter] to exit the script...

d) Exit the script, but remain in the SQL*Plus session.

```
SQL> set pause off
```

```
SQL>
```

- 6) Connect as SYSDBA in your SQL*Plus session, shut down and start your database instance and then connect again as the AMM user with the `oracle_4U` password:

```
SQL> connect / as sysdba
```

Connected.

```
SQL> shutdown immediate
```

Database closed.

Database dismounted.

ORACLE instance shut down.

```
SQL>
```

```
SQL> STARTUP
```

ORACLE instance started.

```
Total System Global Area 313860096 bytes
```

```
Fixed Size 1336204 bytes
```

```
Variable Size 209718388 bytes
```

```
Database Buffers 96468992 bytes
```

```
Redo Buffers 6336512 bytes
```

Database mounted.

Database opened.

```
SQL>
```

```
SQL> connect amm
```

Enter password: `oracle_4U` <<< not displayed

Connected.

```
SQL>
```

- 7) As the AMM user, determine the current settings for the various memory buffers as well as the list of resized operations that were done since you started your instance.

a) You can use the `amm_components.sql` script for that purpose.

```
SQL> @amm_components.sql
```

```
SQL> set serveroutput on
```

```
SQL> set term on
```

Practice 13-1: Using Automatic Memory Management (continued)

```
SQL> set lines 200
SQL> set pages 100
SQL> set heading on
SQL> column comp format a18
SQL> column final_size format 999999999
SQL> column oper_type format a9
SQL> set pause on pause "Press [Enter] to continue..."
SQL>
SQL> SELECT substr(COMPONENT, 0, 18) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US
2   FROM v$memory_dynamic_components
3  WHERE CURRENT_SIZE!=0;
Press [Enter] to continue...
```

b) To view the query result, press Enter to continue the script.

COMP	CS	US
shared pool	83886080	0
large pool	4194304	0
java pool	4194304	0
SGA Target	188743680	0
DEFAULT buffer cac	88080384	0
PGA Target	125829120	0

6 rows selected.

```
SQL> pause Press [Enter] to continue...
Press [Enter] to continue...
```

c) View the memory components (ordered by descending START_TIME) by pressing Enter to continue the script.

```
SQL> SELECT substr(COMPONENT,0,20) comp, FINAL_SIZE,
OPER_TYPE, OPER_MODE, status
2   FROM v$memory_resize_ops
3  ORDER BY START_TIME desc;
Press [Enter] to continue...
```

d) To view the query result, press Enter to continue the script.

COMP	FINAL_SIZE	OPER_TYPE	OPER_MODE	STATUS
shared pool	83886080	GROW	IMMEDIATE	COMPLETE
DEFAULT buffer cac	88080384	SHRINK	IMMEDIATE	COMPLETE
DEFAULT buffer cac	92274688	SHRINK	IMMEDIATE	COMPLETE
shared pool	79691776	GROW	IMMEDIATE	COMPLETE
large pool	4194304	GROW	IMMEDIATE	COMPLETE
java pool	4194304	STATIC		COMPLETE
streams pool	0	STATIC		COMPLETE
SGA Target	188743680	STATIC		COMPLETE
PGA Target	125829120	STATIC		COMPLETE
DEFAULT buffer cac	96468992	STATIC	IMMEDIATE	COMPLETE

Practice 13-1: Using Automatic Memory Management (continued)

```

DEFAULT buffer cac 100663296 STATIC IMMEDIATE COMPLETE
ASM Buffer Cache 0 STATIC COMPLETE
DEFAULT buffer cac 104857600 STATIC COMPLETE
DEFAULT buffer cac 104857600 STATIC IMMEDIATE COMPLETE
DEFAULT 2K buffer 0 STATIC COMPLETE
DEFAULT 4K buffer 0 STATIC COMPLETE
DEFAULT 8K buffer 0 STATIC COMPLETE
DEFAULT 16K buffer 0 STATIC COMPLETE
DEFAULT 32K buffer 0 STATIC COMPLETE
KEEP buffer cache 0 STATIC COMPLETE
RECYCLE buffer cac 0 STATIC COMPLETE
large pool 4194304 STATIC COMPLETE
shared pool 67108864 STATIC COMPLETE
shared pool 71303168 GROW IMMEDIATE COMPLETE
shared pool 75497472 GROW IMMEDIATE COMPLETE
DEFAULT buffer cac 96468992 INITIALIZ IMMEDIATE COMPLETE
ING

```

26 rows selected.

SQL> pause Press [Enter] to exit the script...

Press [Enter] to exit the script...

SQL> set pause off

SQL>

SQL>

- 8) Remain connected as the AMM user in your SQL*Plus session and execute the following query. Immediately after that, determine the component sizes and resized operations. You can use query1.sql script for that purpose. What do you observe?

```

select /*+ PARALLEL(s 24) */ count(*) from (select /*+
parallel(s 24) */ * from tabsga s group by a);

```

- a) Execute the amm_query1.sql script. You can see that the large pool has a much bigger size while the buffer cache is smaller. This memory transfer was automatically done by the system.

SQL> @amm_query1.sql

```

SQL> select /*+ PARALLEL(s 24) */ count(*) from (select /*+
parallel(s 24) */ * from tabsga s group by a);

```

COUNT(*)

100000

SQL>

SQL> column COMP format a12

SQL>

```

SQL> select substr(COMPONENT, 0, 10) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US from v$memory_dynamic_components where
CURRENT_SIZE!=0;

```

Practice 13-1: Using Automatic Memory Management (continued)

COMP	CS	US
shared poo	88080384	0
large pool	83886080	0
java pool	4194304	0
SGA Target	188743680	0
DEFAULT bu	4194304	0
PGA Target	125829120	0

6 rows selected.

SQL>

SQL> select substr(COMPONENT, 0, 10) COMP, FINAL_SIZE,
OPER_TYPE, OPER_MODE, status from v\$memory_resize_ops order by
START_TIME;

COMP	FINAL_SIZE	OPER_TYPE	OPER_MODE	STATUS
shared poo	67108864	STATIC		COMPLETE
shared poo	71303168	GROW	IMMEDIATE	COMPLETE
shared poo	75497472	GROW	IMMEDIATE	COMPLETE
large pool	4194304	GROW	IMMEDIATE	COMPLETE
large pool	4194304	STATIC		COMPLETE
java pool	4194304	STATIC		COMPLETE
streams po	0	STATIC		COMPLETE
SGA Target	188743680	STATIC		COMPLETE
ASM Buffer	0	STATIC		COMPLETE
DEFAULT bu	104857600	STATIC	IMMEDIATE	COMPLETE
DEFAULT bu	104857600	STATIC		COMPLETE
DEFAULT bu	100663296	STATIC	IMMEDIATE	COMPLETE
DEFAULT bu	96468992	STATIC	IMMEDIATE	COMPLETE
DEFAULT bu	96468992	INITIALIZ ING	IMMEDIATE	COMPLETE
DEFAULT 2K	0	STATIC		COMPLETE
DEFAULT 4K	0	STATIC		COMPLETE
DEFAULT 8K	0	STATIC		COMPLETE
DEFAULT 16	0	STATIC		COMPLETE
DEFAULT 32	0	STATIC		COMPLETE
KEEP buffe	0	STATIC		COMPLETE
RECYCLE bu	0	STATIC		COMPLETE
PGA Target	125829120	STATIC		COMPLETE
DEFAULT bu	92274688	SHRINK	IMMEDIATE	COMPLETE
shared poo	79691776	GROW	IMMEDIATE	COMPLETE
DEFAULT bu	88080384	SHRINK	IMMEDIATE	COMPLETE
shared poo	83886080	GROW	IMMEDIATE	COMPLETE
DEFAULT bu	83886080	SHRINK	DEFERRED	COMPLETE
shared poo	88080384	GROW	DEFERRED	COMPLETE
DEFAULT bu	79691776	SHRINK	IMMEDIATE	COMPLETE
large pool	8388608	GROW	IMMEDIATE	COMPLETE

Practice 13-1: Using Automatic Memory Management (continued)

DEFAULT bu	67108864	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	71303168	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	75497472	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	62914560	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	58720256	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	54525952	SHRINK	IMMEDIATE COMPLETE
large pool	12582912	GROW	IMMEDIATE COMPLETE
large pool	16777216	GROW	IMMEDIATE COMPLETE
large pool	20971520	GROW	IMMEDIATE COMPLETE
large pool	29360128	GROW	IMMEDIATE COMPLETE
large pool	33554432	GROW	IMMEDIATE COMPLETE
large pool	25165824	GROW	IMMEDIATE COMPLETE
DEFAULT bu	29360128	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	25165824	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	20971520	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	16777216	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	16777216	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	12582912	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	8388608	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	33554432	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	37748736	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	41943040	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	46137344	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	50331648	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	54525952	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	4194304	SHRINK	IMMEDIATE COMPLETE
large pool	79691776	GROW	IMMEDIATE COMPLETE
large pool	75497472	GROW	IMMEDIATE COMPLETE
large pool	71303168	GROW	IMMEDIATE COMPLETE
large pool	71303168	GROW	IMMEDIATE COMPLETE
large pool	67108864	GROW	IMMEDIATE COMPLETE
large pool	62914560	GROW	IMMEDIATE COMPLETE
large pool	58720256	GROW	IMMEDIATE COMPLETE
large pool	54525952	GROW	IMMEDIATE COMPLETE
large pool	50331648	GROW	IMMEDIATE COMPLETE
large pool	46137344	GROW	IMMEDIATE COMPLETE
large pool	41943040	GROW	IMMEDIATE COMPLETE
large pool	37748736	GROW	IMMEDIATE COMPLETE
large pool	33554432	GROW	IMMEDIATE COMPLETE
large pool	83886080	GROW	IMMEDIATE COMPLETE

70 rows selected.

SQL>

SQL>

- 9) Redo the same thing as in the previous step, but this time use the following query. You can use amm_query2.sql script for that purpose. What do you observe?

Possible Answer: The same trend continues.

SQL> @amm_query2.sql

Practice 13-1: Using Automatic Memory Management (continued)

```
SQL> select /*+ PARALLEL(s 25) */ count(*) from (select /*+
parallel(s 25) */ * from tabsga s group by a);
```

```
COUNT(*)
```

```
-----
```

```
100000
```

```
SQL>
```

```
SQL> column COMP format a12
```

```
SQL>
```

```
SQL> select substr(COMPONENT, 0, 10) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US from v$memory_dynamic_components where
CURRENT_SIZE!=0;
```

COMP	CS	US
shared poo	88080384	0
large pool	83886080	0
java pool	4194304	0
SGA Target	188743680	0
DEFAULT bu	4194304	0
PGA Target	125829120	0

```
6 rows selected.
```

```
SQL>
```

```
SQL> select substr(COMPONENT, 0, 10) COMP, FINAL_SIZE,
OPER_TYPE, OPER_MODE, status from v$memory_resize_ops order by
START_TIME;
```

COMP	FINAL_SIZE	OPER_TYPE	OPER_MODE	STATUS
shared poo	67108864	STATIC		COMPLETE
shared poo	71303168	GROW	IMMEDIATE	COMPLETE
shared poo	75497472	GROW	IMMEDIATE	COMPLETE
large pool	4194304	GROW	IMMEDIATE	COMPLETE
large pool	4194304	STATIC		COMPLETE
java pool	4194304	STATIC		COMPLETE
streams po	0	STATIC		COMPLETE
SGA Target	188743680	STATIC		COMPLETE
ASM Buffer	0	STATIC		COMPLETE
DEFAULT bu	104857600	STATIC	IMMEDIATE	COMPLETE
DEFAULT bu	104857600	STATIC		COMPLETE
DEFAULT bu	100663296	STATIC	IMMEDIATE	COMPLETE
DEFAULT bu	96468992	STATIC	IMMEDIATE	COMPLETE
DEFAULT bu	96468992	INITIALIZ	IMMEDIATE	COMPLETE
		ING		
DEFAULT 2K	0	STATIC		COMPLETE

Practice 13-1: Using Automatic Memory Management (continued)

DEFAULT 4K	0	STATIC	COMPLETE
DEFAULT 8K	0	STATIC	COMPLETE
DEFAULT 16	0	STATIC	COMPLETE
DEFAULT 32	0	STATIC	COMPLETE
KEEP buffer	0	STATIC	COMPLETE
RECYCLE buffer	0	STATIC	COMPLETE
PGA Target	125829120	STATIC	COMPLETE
DEFAULT buffer	92274688	SHRINK	IMMEDIATE COMPLETE
shared pool	79691776	GROW	IMMEDIATE COMPLETE
DEFAULT buffer	88080384	SHRINK	IMMEDIATE COMPLETE
shared pool	83886080	GROW	IMMEDIATE COMPLETE
DEFAULT buffer	83886080	SHRINK	DEFERRED COMPLETE
shared pool	88080384	GROW	DEFERRED COMPLETE
DEFAULT buffer	79691776	SHRINK	IMMEDIATE COMPLETE
large pool	8388608	GROW	IMMEDIATE COMPLETE
DEFAULT buffer	67108864	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	71303168	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	75497472	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	62914560	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	58720256	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	54525952	SHRINK	IMMEDIATE COMPLETE
large pool	12582912	GROW	IMMEDIATE COMPLETE
large pool	16777216	GROW	IMMEDIATE COMPLETE
large pool	20971520	GROW	IMMEDIATE COMPLETE
large pool	29360128	GROW	IMMEDIATE COMPLETE
large pool	33554432	GROW	IMMEDIATE COMPLETE
large pool	25165824	GROW	IMMEDIATE COMPLETE
DEFAULT buffer	29360128	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	25165824	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	20971520	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	16777216	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	16777216	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	12582912	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	8388608	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	33554432	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	37748736	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	41943040	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	46137344	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	50331648	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	54525952	SHRINK	IMMEDIATE COMPLETE
DEFAULT buffer	4194304	SHRINK	IMMEDIATE COMPLETE
large pool	79691776	GROW	IMMEDIATE COMPLETE
large pool	75497472	GROW	IMMEDIATE COMPLETE
large pool	71303168	GROW	IMMEDIATE COMPLETE
large pool	71303168	GROW	IMMEDIATE COMPLETE
large pool	67108864	GROW	IMMEDIATE COMPLETE
large pool	62914560	GROW	IMMEDIATE COMPLETE
large pool	58720256	GROW	IMMEDIATE COMPLETE
large pool	54525952	GROW	IMMEDIATE COMPLETE
large pool	50331648	GROW	IMMEDIATE COMPLETE

Practice 13-1: Using Automatic Memory Management (continued)

```
large pool      46137344 GROW      IMMEDIATE COMPLETE
large pool      41943040 GROW      IMMEDIATE COMPLETE
large pool      37748736 GROW      IMMEDIATE COMPLETE
large pool      33554432 GROW      IMMEDIATE COMPLETE
large pool      83886080 GROW      IMMEDIATE COMPLETE
```

```
70 rows selected.
SQL>
```

- 10) Still connected as the AMM user from your SQL*Plus session, execute the following command and, immediately afterward, determine the memory component sizes and the list of resize operations. You can use amm_query3.sql for that purpose. What do you observe?

Possible Answer: The same style of growing and shrinking of the memory components.

```
SQL> @amm_query3.sql
SQL> exec testpga(500000);

PL/SQL procedure successfully completed.

SQL>
SQL> column COMP format a12
SQL>
SQL> select substr(COMPONENT, 0, 10) COMP, CURRENT_SIZE CS,
USER_SPECIFIED_SIZE US from v$memory_dynamic_components where
CURRENT_SIZE!=0;
```

COMP	CS	US
shared poo	88080384	0
large pool	83886080	0
java pool	4194304	0
SGA Target	188743680	0
DEFAULT bu	4194304	0
PGA Target	125829120	0

```
6 rows selected.
```

```
SQL>
SQL> select substr(COMPONENT, 0, 10) COMP, FINAL_SIZE,
OPER_TYPE, OPER_MODE, status from v$memory_resize_ops order by
START_TIME;
```

COMP	FINAL_SIZE	OPER_TYPE	OPER_MODE	STATUS
DEFAULT bu	96468992	INITIALIZING	IMMEDIATE	COMPLETE

Practice 13-1: Using Automatic Memory Management (continued)

RECYCLE bu	0	STATIC	COMPLETE
KEEP buffe	0	STATIC	COMPLETE
DEFAULT 32	0	STATIC	COMPLETE
shared poo	75497472	GROW	IMMEDIATE COMPLETE
shared poo	71303168	GROW	IMMEDIATE COMPLETE
shared poo	67108864	STATIC	COMPLETE
large pool	4194304	STATIC	COMPLETE
large pool	4194304	GROW	IMMEDIATE COMPLETE
java pool	4194304	STATIC	COMPLETE
streams po	0	STATIC	COMPLETE
SGA Target	188743680	STATIC	COMPLETE
PGA Target	125829120	STATIC	COMPLETE
DEFAULT bu	96468992	STATIC	IMMEDIATE COMPLETE
DEFAULT bu	100663296	STATIC	IMMEDIATE COMPLETE
ASM Buffer	0	STATIC	COMPLETE
DEFAULT bu	104857600	STATIC	COMPLETE
DEFAULT bu	104857600	STATIC	IMMEDIATE COMPLETE
DEFAULT 2K	0	STATIC	COMPLETE
DEFAULT 4K	0	STATIC	COMPLETE
DEFAULT 8K	0	STATIC	COMPLETE
DEFAULT 16	0	STATIC	COMPLETE
DEFAULT bu	92274688	SHRINK	IMMEDIATE COMPLETE
shared poo	79691776	GROW	IMMEDIATE COMPLETE
DEFAULT bu	88080384	SHRINK	IMMEDIATE COMPLETE
shared poo	83886080	GROW	IMMEDIATE COMPLETE
shared poo	88080384	GROW	DEFERRED COMPLETE
DEFAULT bu	83886080	SHRINK	DEFERRED COMPLETE
DEFAULT bu	79691776	SHRINK	IMMEDIATE COMPLETE
large pool	8388608	GROW	IMMEDIATE COMPLETE
DEFAULT bu	75497472	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	71303168	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	67108864	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	62914560	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	58720256	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	54525952	SHRINK	IMMEDIATE COMPLETE
large pool	12582912	GROW	IMMEDIATE COMPLETE
large pool	16777216	GROW	IMMEDIATE COMPLETE
large pool	20971520	GROW	IMMEDIATE COMPLETE
large pool	25165824	GROW	IMMEDIATE COMPLETE
large pool	29360128	GROW	IMMEDIATE COMPLETE
large pool	33554432	GROW	IMMEDIATE COMPLETE
DEFAULT bu	37748736	SHRINK	IMMEDIATE COMPLETE
large pool	75497472	GROW	IMMEDIATE COMPLETE
DEFAULT bu	46137344	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	50331648	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	54525952	SHRINK	IMMEDIATE COMPLETE
large pool	83886080	GROW	IMMEDIATE COMPLETE
large pool	79691776	GROW	IMMEDIATE COMPLETE
DEFAULT bu	4194304	SHRINK	IMMEDIATE COMPLETE

Practice 13-1: Using Automatic Memory Management (continued)

DEFAULT bu	8388608	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	12582912	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	16777216	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	16777216	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	20971520	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	25165824	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	29360128	SHRINK	IMMEDIATE COMPLETE
DEFAULT bu	33554432	SHRINK	IMMEDIATE COMPLETE
large pool	33554432	GROW	IMMEDIATE COMPLETE
large pool	37748736	GROW	IMMEDIATE COMPLETE
large pool	41943040	GROW	IMMEDIATE COMPLETE
large pool	46137344	GROW	IMMEDIATE COMPLETE
large pool	50331648	GROW	IMMEDIATE COMPLETE
large pool	54525952	GROW	IMMEDIATE COMPLETE
large pool	58720256	GROW	IMMEDIATE COMPLETE
large pool	62914560	GROW	IMMEDIATE COMPLETE
large pool	67108864	GROW	IMMEDIATE COMPLETE
large pool	71303168	GROW	IMMEDIATE COMPLETE
large pool	71303168	GROW	IMMEDIATE COMPLETE
DEFAULT bu	41943040	SHRINK	IMMEDIATE COMPLETE

70 rows selected.

```
SQL> exit
$
```

- 11) From a terminal window, restart Enterprise Manager Database Control.

```
$ emctl start dbconsole


Oracle Enterprise Manager 11g Database Control Release
11.2.0.1.0
Copyright (c) 1996, 2009 Oracle Corporation. All rights
reserved.
https://edrsr37p1.us.oracle.com:1158/em/console/aboutApplicati
on
Starting Oracle Enterprise Manager 11g Database Control
..... started.
-----
-----
Logs are generated in directory
/u01/app/oracle/product/11.2.0/dbhome_1/edrsr37p1.us.oracle.co
m_orcl/sysman/log
$
```

- 12) In Enterprise Manager look at the memory variations that happened during this lab.
What do you observe?

- a) Logged into Enterprise Manager as the SYSDBA, click the Server tab.

Practice 13-1: Using Automatic Memory Management (continued)

- 13) On the Server tabbed page, click Memory Advisors in the Database Configuration section.
- 14) On the Memory Advisors page, look at the first two graphics.
- 15) You should see modifications of the memory components in the second graph, that the large pool grew and shrank.



- 16) Logout and exit from Enterprise Manager.
- 17) To clean up your environment, shut down your database instance, restore the original SPFILE, turn on archiving and restart your orcl database instance. To do all that, execute the amm_cleanup.sh script.

```
$ cd ~/labs
$ ./amm_cleanup.sh
Oracle Enterprise Manager 11g Database Control Release
11.2.0.1.0
Copyright (c) 1996, 2009 Oracle Corporation. All rights
reserved.
https://edrsr37p1.us.oracle.com:1158/em/console/aboutApplicati
on
Stopping Oracle Enterprise Manager 11g Database Control ...
... Stopped.

SQL*Plus: Release 11.2.0.1.0 Production on Thu Sep 3 19:21:43
2009

Copyright (c) 1982, 2009, Oracle. All rights reserved.
```

Practice 13-1: Using Automatic Memory Management (continued)

```
Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.1.0 -
Production
With the Partitioning, Automatic Storage Management, OLAP,
Data Mining
and Real Application Testing options

SQL> SQL>
User dropped.

SQL>
Tablespace dropped.

SQL>
Tablespace dropped.

SQL> SQL> Database closed.
Database dismounted.
ORACLE instance shut down.
SQL>
File created.

SQL> SQL> ORACLE instance started.

Total System Global Area  481259520 bytes
Fixed Size                  1337352 bytes
Variable Size              373295096 bytes
Database Buffers           100663296 bytes
Redo Buffers                5963776 bytes
Database mounted.
SQL>
Database altered.

SQL>
Database altered.

SQL> Disconnected from Oracle Database 11g Enterprise Edition
Release 11.2.0.1.0 - Production
With the Partitioning, Automatic Storage Management, OLAP,
Data Mining
and Real Application Testing options
Oracle Enterprise Manager 11g Database Control Release
11.2.0.1.0
Copyright (c) 1996, 2009 Oracle Corporation. All rights
reserved.
https://edrsr37p1.us.oracle.com:1158/em/console/aboutApplicati
on
```

Practice 13-1: Using Automatic Memory Management (continued)

```
Starting Oracle Enterprise Manager 11g Database Control
..... started.
-----
----
Logs are generated in directory
/u01/app/oracle/product/11.2.0/dbhome_1/edrsr37p1.us.oracle.co
m_orcl/sysman/log
$
```

Practice 14-1: Monitoring Services

In your database there are several running applications. You want to monitor the resources that are being used by each application. Create a service configuration for each application or application function that uses your database.

In this practice, you create the following configuration in the `orcl` database:

Service Name	Usage	Response Time (sec)– Warning/Critical
SERV1	Client service	0.4, 1.0

- 1) Use the `DBMS_SERVICE` package to create a service called `SERV1`. Then make sure that you add your service name to your `tnsnames.ora` file.
 - a) The recommended method for adding a service name to the `tnsnames.ora` file is to use Net Manager. For this exercise, execute the `sv1_add.sh` script. Review the `tnsnames.ora` file at `$ORACLE_HOME/network/admin` to confirm that the following lines are included. Substitute the output of the `hostname` command for `<hostname>` below.

```
SERV1 =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)
      (HOST = <hostname>.ua.oracle.com)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = SERV1.example.com)
    )
  )
```

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$ cd /home/oracle/labs
$ ./sv1_add.sh
edrsr37p1.us.oracle.com
$
```

- b) Use the `DBMS_SERVICE.CREATE_SERVICE` procedure to create a service. (The command is entered on one line.)

```
$ sqlplus / as sysdba
```

Practice 14-1: Monitoring Services (continued)

```
SQL> EXEC
DBMS_SERVICE.CREATE_SERVICE('SERV1','SERV1.example.com')

PL/SQL procedure successfully completed.

SQL> exit;
```

- 2) After you have created your services, try connecting to your database by using your service name. What happens? Why?

Answer: You cannot connect using your service because although it is defined, it is not started on your instance. You can verify this by looking at the SERVICE_NAME initialization parameter and by looking at the services known to the listener.

```
$ lsnrctl services
LSNRCTL for Linux: Version 11.2.0.1.0 - Production on 26-JUL-
2009 16:23:46

Copyright (c) 1991, 2009, Oracle. All rights reserved.

Connecting to (ADDRESS=(PROTOCOL=tcp)(HOST=)(PORT=1521))
Services Summary...
Service "+ASM" has 1 instance(s).
  Instance "+ASM", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:10098 refused:0 state:ready
    LOCAL SERVER
Service "orcl.us.oracle.com" has 1 instance(s).
  Instance "orcl", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:3657 refused:0 state:ready
    LOCAL SERVER
Service "orclXDB.us.oracle.com" has 1 instance(s).
  Instance "orcl", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "D000" established:0 refused:0 current:0 max:1022
state:ready
    DISPATCHER <machine: edrsr37p1.us.oracle.com, pid:
6610>

(ADDRESS=(PROTOCOL=tcp)(HOST=edrsr37p1.us.oracle.com)(PORT=296
69))
Service "rcat.example.com" has 1 instance(s).
  Instance "rcat", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:3 refused:0 state:ready
    LOCAL SERVER
Service "rcatXDB.example.com" has 1 instance(s).
```

Practice 14-1: Monitoring Services (continued)

```
Instance "rcat", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "D000" established:0 refused:0 current:0 max:1022
state:ready
    DISPATCHER <machine: edrsr37p1.us.oracle.com, pid:
20809>

(ADDRESS=(PROTOCOL=tcp)(HOST=edrsr37p1.us.oracle.com)(PORT=620
66))
The command completed successfully
$
```

```
$ sqlplus / as sysdba
```

```
SQL> show parameter service
```

NAME	TYPE	VALUE
-----	-----	-----
service_names	string	orcl.oracle.com

```
SQL> connect system@SERV1
```

```
Enter password: oracle_4U <<< not displayed
```

```
ERROR:
```

```
ORA-12514: TNS:listener does not currently know of service
requested in connect descriptor
```

```
Warning: You are no longer connected to ORACLE.
```

```
SQL>
```

- 3) How would you make sure that you can connect using your service? Do it and connect to your instance by using your service.

Answer: You must start your service on your instance.

```
$ connect / as sysdba
```

```
Connected.
```

```
SQL> show parameter service
```

NAME	TYPE	VALUE
-----	-----	-----
service_names	string	orcl.us.oracle.com

```
SQL> EXEC DBMS_SERVICE.START_SERVICE('SERV1')
```

```
PL/SQL procedure successfully completed.
```

```
SQL> show parameter service
```

NAME	TYPE	VALUE
-----	-----	-----

Practice 14-1: Monitoring Services (continued)

```
service_names          string          SERV1.us.oracle.com

SQL> host lsnrctl services
LSNRCTL for Linux: Version 11.2.0.1.0 - Production on 26-JUL-
2009 16:30:36

Copyright (c) 1991, 2009, Oracle. All rights reserved.

Connecting to (ADDRESS=(PROTOCOL=tcp)(HOST=)(PORT=1521))
Services Summary...
Service "+ASM" has 1 instance(s).
  Instance "+ASM", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:10105 refused:0 state:ready
    LOCAL SERVER
Service "SERV1.example.com" has 1 instance(s).
  Instance "orcl", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:0 refused:0 state:ready
    LOCAL SERVER
Service "orcl.us.oracle.com" has 1 instance(s).
  Instance "orcl", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:0 refused:0 state:ready
    LOCAL SERVER
Service "orclXDB.us.oracle.com" has 1 instance(s).
  Instance "orcl", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "D000" established:0 refused:0 current:0 max:1022
state:ready
    DISPATCHER <machine: edrsr37p1.us.oracle.com, pid:
6610>

(ADDRESS=(PROTOCOL=tcp)(HOST=edrsr37p1.us.oracle.com)(PORT=296
69))
Service "rcat.example.com" has 1 instance(s).
  Instance "rcat", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "DEDICATED" established:3 refused:0 state:ready
    LOCAL SERVER
Service "rcatXDB.example.com" has 1 instance(s).
  Instance "rcat", status READY, has 1 handler(s) for this
service...
  Handler(s):
    "D000" established:0 refused:0 current:0 max:1022
state:ready
```

Practice 14-1: Monitoring Services (continued)

```
DISPATCHER <machine: edrsr37p1.us.oracle.com, pid:
20809>

(ADDRESS=(PROTOCOL=tcp)(HOST=edrsr37p1.us.oracle.com)(PORT=620
66))
The command completed successfully

SQL>
```

```
SQL> connect system@SERV1
Enter password: oracle_4U <<< not displayed

Connected.
SQL> exit
```

- 4) Execute the `sv1_load.sh` script as SYSDBA. This script creates a new SV_USER user. Then you connect to your instance as this user and the SERV1 service. Create workload activity by executing the `sv1_load2.sql` script. If this script finishes before you completed the next step, then use the `sv1_sel.sql` script to executes the following query:

```
SELECT COUNT(*) FROM DBA_OBJECTS,DBA_OBJECTS,DBA_OBJECTS

$ cd ~/labs
$ ./sv1_load.sh

SQL> SQL> SQL> SQL> SQL> drop user sv_user cascade
*
ERROR at line 1:
ORA-01918: user 'SV_USER' does not exist

SQL> SQL> 2 3
User created.

SQL> SQL>
Grant succeeded.
$
```

Note: Do not wait for the script to complete before proceeding to the next step.


```
$ sqlplus sv_user@SERV1
Enter password: oracle_4U <<< not displayed
Connected.

SQL> @sv1_load2.sql
SQL> DECLARE
2 t number;
3 BEGIN
4 for i in 1..2000 loop
5 select count(*) into t from dba_objects;
6 end loop;
```

Practice 14-1: Monitoring Services (continued)

```
7  END ;  
8  /
```


- 5) After the execution starts, access the EM Top Consumers page from the Performance tabbed page, and check if SERV1 is using more resources. Also, check the statistics on your service with V\$SERVICE_STATS from a SQL*Plus session connected as SYSDBA.
- a) On the home page, click the Performance tab. Towards the bottom of the Performance page, click the Services tab.



An Active Session graph with the activity aggregated by service name is displayed. The network service name of each connection is recorded as a separate service. So all the connections made without a service name are aggregated, as are all the connections made as SERV1.

- b) Click the Top Consumers link in the Additional Monitoring Links section. Refresh the Top Consumers Overview page several times.


Practice 14-1: Monitoring Services (continued)



The names and number of services listed in the Top Services Graph depends on the number and type of connections to the database.

- c) You can also see the detailed statistics by navigating to the Top Services tab > SERV1 link > Statistics tab.

Practice 14-1: Monitoring Services (continued)



- 6) If the sv1_load2.sql script finishes before you completed this step, then use the sv1_sel.sql script to continue creating a workload. – When you completed the tasks, make sure that you stop your running workload by pressing Ctrl + C in your terminal window.

```
SQL> @sv1_sel.sql
SQL> select count(*) from dba_objects,dba_objects,dba_objects
      *
ERROR at line 1:
ORA-01013: user requested cancel of current operation
SQL> exit
```


Practices for Lesson 15

By default, Automatic SQL Tuning executes automatically during each nightly maintenance window. For this practice, you simulate the execution of Automatic SQL Tuning, and explore its results


Practice 15-1: Using Automatic SQL Tuning

In this practice, you manually launch Automatic SQL Tuning to automatically tune a small application workload. You then investigate the outcomes and configuration possibilities.

- 1) In EM, navigate to Server > Automated Maintenance Tasks (in the Oracle Scheduler section).
 - a) To check if the task settings are enabled, click Configure, (no matter if the status is Enabled or Disabled).




- b) Toggle Enabled and Disabled, then click Show SQL when the Global Status is Enabled.



- c) Review the command and click Return.

```
BEGIN
dbms_auto_task_admin.enable();
END;
```

- d) On the Automated Maintenance Tasks Configuration page, click Apply.
 - e) Click the Configure button next to Automatic SQL Tuning.
 - f) Select Yes for “Automatic Implementation of SQL Profiles” and click Show SQL.



- g) Review the command and click Return.

Practice 15-1: Using Automatic SQL Tuning (continued)

```
BEGIN
dbms_sqltune.set_auto_tuning_task_parameter( 'ACCEPT_SQL_PROFILES', 'TRUE');
END;
```

h) On the Automatic SQL Tuning Settings page, click Apply.

You should receive a success message.

- 2) In a terminal window connected as the oracle user, point to the ORCL instance, review and execute the `ast_setup.sh` script. This script creates the AST user, turns off automatic maintenance tasks, and drops any existing profiles on queries executed by the AST user.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$ cat ast_setup.sh
#!/bin/bash
# For training only - execute as oracle OS user

sqlplus / as sysdba <<EOF!
set echo on

drop user ast cascade;
create user ast identified by "oracle_4U";
grant dba to ast;

alter system flush shared_pool;
--
-- Turn off AUTOTASK
--
alter system set "_enable_automatic_maintenance"=0;
--
-- Clear out old executions of auto-sqltune
--
exec
dbms_sqltune.reset_tuning_task('SYS_AUTO_SQL_TUNING_TASK');

--
-- Drop any profiles on AST queries
--
declare
  cursor prof_names is
    select name from dba_sql_profiles where sql_text like
'%AST%';
begin
  for prof_rec in prof_names loop
    dbms_sqltune.drop_sql_profile(prof_rec.name);
  end loop;
end;
/
```


Practice 15-1: Using Automatic SQL Tuning (continued)

```
EOF!  
$
```

```
$ ./ast_setup.sh  
  
SQL> SQL> SQL> drop user ast cascade  
*  
ERROR at line 1:  
ORA-01918: user 'AST' does not exist  
  
SQL>  
User created.  
  
SQL>  
Grant succeeded.  
  
SQL> SQL>  
System altered.  
  
SQL> SQL> SQL> SQL>  
System altered.  
  
SQL> SQL> SQL> SQL> SQL>  
PL/SQL procedure successfully completed.  
  
SQL> SQL> SQL> SQL> SQL> 2 3 4 5 6 7 8  
9  
PL/SQL procedure successfully completed.  
  
SQL> SQL>  
$
```

- 3) In preparation for the practice, you should log in as the AST user with the `oracle_4U` password and execute a workload. Execute the `ast_workload_stream.sql` script. This script executes, multiple times a query that is not correctly optimized. The query in question uses hints that force the optimizer to pick a suboptimal execution plan. The script executes for approximately 30 to 60 seconds. (*Output has been reduced to minimize clutter.*)

```
$ sqlplus ast  
Enter password: oracle_4U <<< not displayed  
SQL> @ast_workload_stream.sql  
Sun Aug 2 23:31:33 GMT-7 2009  
no rows selected  
no rows selected  
no rows selected  
.  
.  
.  
no rows selected  
no rows selected
```

Practice 15-1: Using Automatic SQL Tuning (continued)

```
Sun Aug  2 23:31:55 GMT-7 2009
SQL> exit
$
```

- 4) Automatic SQL Tuning is implemented using an automated task that runs during maintenance windows. However, you are not going to wait for the next maintenance window to open. This might take too long. Instead, you will force the opening of your next maintenance window now. This will automatically trigger the Automatic SQL Tuning task. Review and execute the `ast_run.sh` script to do that. The script's execution takes about ten minutes (most likely).

```
$ cat ast_run.sh
#!/bin/bash
# For training only - execute as oracle OS user
date

sqlplus / as sysdba <<EOF!
set echo on
set serveroutput on

exec dbms_workload_repository.create_snapshot;

variable window varchar2(20);
begin
  select upper(to_char(sysdate,'fmday'))||'_WINDOW' into
:window from dual;
end;
/
print window;
--
-- Open the corresponding maintenance window, but with other
clients disabled
--
alter system set "_enable_automatic_maintenance"=1
/
exec dbms_auto_task_admin.disable( -
  'auto optimizer stats collection', null, :window);

exec dbms_auto_task_admin.disable( -
  'auto space advisor', null, :window);

exec dbms_scheduler.open_window(:window, null, true);

--
-- Close the maintenance window when sqltune is done
--
exec dbms_lock.sleep(60);

declare
  running number;
```

Practice 15-1: Using Automatic SQL Tuning (continued)

```

begin
  loop
    select count(*)
    into   running
    from   dba_advisor_executions
    where  task_name = 'SYS_AUTO_SQL_TUNING_TASK' and
           status = 'EXECUTING';
    if (running = 0) then
      exit;
    end if;
    dbms_lock.sleep(60);
  end loop;
  dbms_scheduler.close_window(:window);
end;
/
alter system set "_enable_automatic_maintenance"=0
/

-- Re-enable the other guys so they look like they are enabled
in EM.
-- Still they will be disabled because we have set the
underscore.
--

exec dbms_auto_task_admin.enable( -
  'auto optimizer stats collection', null, :window);

exec dbms_auto_task_admin.enable( -
  'auto space advisor', null, :window);

EOF!

date

$

```

```

$ ./ast_run.sh
Sun Aug  2 23:42:54 GMT-7 2009

SQL> SQL> SQL> SQL>
PL/SQL procedure successfully completed.

SQL> SQL> SQL> 2 3 4
PL/SQL procedure successfully completed.

SQL>
WINDOW
-----
SUNDAY_WINDOW

SQL> SQL> SQL> SQL> SQL> 2

```

Practice 15-1: Using Automatic SQL Tuning (continued)

```
System altered.

SQL> >
PL/SQL procedure successfully completed.

SQL> SQL> >
PL/SQL procedure successfully completed.

SQL> SQL>
PL/SQL procedure successfully completed.

SQL> SQL> SQL> SQL> SQL>
PL/SQL procedure successfully completed.

SQL> SQL>      2      3      4      5      6      7      8      9     10     11
12     13     14     15     16     17
PL/SQL procedure successfully completed.

SQL>      2
System altered.

SQL> SQL> SQL> SQL> SQL> SQL> >
PL/SQL procedure successfully completed.

SQL> SQL> >
PL/SQL procedure successfully completed.

SQL> SQL>
Sun Aug  2 23:43:57 GMT-7 2009
$
```

Some of your output, like the WINDOW, may look different.

- 5) Execute the `ast_workload_stream.sh` script again. What do you observe?
 - a) You should see that the execution time for `ast_workload_stream.sh` is much faster than the original execution. This is probably due to the fact that Automatic SQL Tuning implemented a profile for your statement automatically.

```
$ sqlplus ast
Enter password: oracle_4U <<< not displayed
SQL> @ast_workload_stream.sql
Sun Aug  2 23:48:54 GMT-7 2009
no rows selected
no rows selected
no rows selected
.
.
.
no rows selected
no rows selected

Sun Aug  2 23:49:16 GMT-7 2009
```

Practice 15-1: Using Automatic SQL Tuning (continued)

```
SQL> exit
$
```

- 6) Logged in as the AST user, force the creation of an AWR snapshot.

```
$ sqlplus ast
Enter password: oracle_4U <<< not displayed
SQL> set echo on
SQL> exec dbms_workload_repository.create_snapshot;
PL/SQL procedure successfully completed.

SQL> exit
$
```


- 7) How can you confirm that a SQL Profile was automatically implemented?

- In Enterprise Manager, navigate to Server > Automated Maintenance Tasks (Oracle Scheduler) > Automatic SQL Tuning.
- On the Automatic SQL Tuning summary page, view the tuning results.

Automatic SQL Tuning Result Summary
The Automatic SQL Tuning runs during system maintenance windows as an automated maintenance task, searching for ways to improve the execution plans of high-load SQL statements.

Task Status
Automatic SQL Tuning (SYS_AUTO_SQL_TUNING_TASK) is currently **Enabled** [Configure](#)
Automatic Implementation of SQL Profiles is currently **Enabled** [Configure](#)
Key SQL Profiles **0**

The task has already run in one maintenance window and has results ready to be viewed.



- Look at the graphs on the Automatic SQL Tuning Result Summary page. (If you do not see any graphs, return to step 5, execute the work load twice, then continue with step 6 and 7.)
- Focus on understanding the pie chart and the bar graph next to it. You should be able to get a feeling for the general findings breakdown, as well as the number of SQL profiles implemented by the task.

Practice 15-1: Using Automatic SQL Tuning (continued)

e) Click View Report to see a detailed SQL-level report.

Automatic SQL Tuning Result Details: All Analyzed SQLs
 Begin Date Aug 3, 2009 6:33:49 PM (UTC+07:00) End Date Aug 3, 2009 6:45:38 PM (UTC+07:00)

Recommendations
 Only profiles that significantly improve SQL performance were implemented.
 (View Recommendations) (Implement All SQL Profiles)

Select SQL Text	Parsing Schema	SQL ID	Weekly DB Time Benefitted	Per-Execution % Benefit	Statistics	SQL Profile	Index	Restructure SQL	Alternative Plan	Miscellaneous	Timed Out	Error	Date
<input checked="" type="radio"/> select /*+ USE_NL(s c) FULL(s) FULL(c) A...	AST	by9m5m697zh19	50.81	98		98%	90%						8/3/2009 6:33:49 PM
<input type="radio"/> SELECT :B1 TASK_ID, F.FINDING_ID FINDING...	DBSNMP	a839qb13tqkr	1.26	88	✓	(88%)	✓	✓	✓				8/3/2009 6:33:49 PM
<input type="radio"/> INSERT INTO MGMT_METRICS_RAW(COLLECTION...	SYSMAN	6amygb1ygg2y7			✓								8/3/2009 6:33:49 PM

Legend ✓ Recommended ✓ Implemented


f) Find and select the SQL that ran in the AST schema. Note the green check mark meaning that the profile was implemented.

g) Click the View Recommendations button.

Select Recommendation
 Original Explain Plan (Annotated)
 (Implement)

Select	Type	Findings	Recommendations	Rationale	Benefit (%)	Other Statistics	New Explain Plan	Compare Explain Plans
<input checked="" type="radio"/>	SQL A	Profile potentially better execution plan was found for this statement.	The SQL profile "SYS_SQLPROF_0122e0099ab30000" currently has status "ENABLED".	SQL profile "SYS_SQLPROF_0122e0099ab30000" was created automatically for this statement.	98.47			
<input type="radio"/>	Index	The execution plan of this statement can be improved by creating one or more indices.	Consider running the Access Advisor to improve the physical schema design or creating the recommended index SH.SALES("CUST_ID")	Creating the recommended indices significantly improves the execution plan of this statement. However, it might be preferable to run "Access Advisor" using a representative SQL workload as opposed to a single statement. This will allow to get comprehensive index recommendations which takes into account index maintenance overhead and additional space consumption.	90.98			

h) Click the Compare Explain Plans eyeglass icon for the SQL Profile entry.



Practice 15-1: Using Automatic SQL Tuning (continued)

- i) Scroll down the page.

Original Explain Plan (Annotated)										
Indicates an adjustment from the original plan by the SQL Tuning Advisor Plan Hash Value 4005616876										
Expand All Collapse All										
Operation	Line ID	Object	Object Type	Order	Rows	Bytes	Cost	Time	CPU Cost	I/O Cost
SELECT STATEMENT	0			6		0.013	893	11	269,312,608	885
HASH GROUP BY	1			5		0.013	893	11	269,312,608	885
NESTED LOOPS	2			4		0.013	892	11	236,425,824	885
TABLE ACCESS FULL	3	SH.CUSTOMERS	TABLE	1		0.005	405	5	21,682,460	404
PARTITION RANGE ALL	4			3		0.008	488	6	214,743,360	481
TABLE ACCESS FULL	5	SH.SALES	TABLE	2		0.008	488	6	214,743,360	481

New Explain Plan With SQL Profile										
Plan Hash Value 3070788227										
Expand All Collapse All										
Operation	Line ID	Object	Object Type	Order	Rows	Bytes	Cost	Time	CPU Cost	I/O Cost
SELECT STATEMENT	0			8		0.013	55	1	33,327,052	54
HASH GROUP BY	1			7		0.013	55	1	33,327,052	54
NESTED LOOPS	2			6		0.013	54	1	440,260	54
PARTITION RANGE ALL	3			4		0.008	54	1	438,310	54
TABLE ACCESS BY LOCAL INDEX ROWID	4	SH.SALES	TABLE	3		0.008	54	1	438,310	54
BITMAP CONVERSION TO ROWIDS	5			2						
BITMAP INDEX RANGE SCAN	6	SH.SALES_CUST_BIX	INDEX (BITMAP)	1						
INDEX UNIQUE SCAN	7	SH.CUSTOMERS_PK	INDEX (UNIQUE)	5		0.005	0	1	1,950	0

- j) Look at the old and new explain plans for the query.
- k) Then click the “Recommendations for SQL ID” locator link (the last of the breadcrumbs on top of the page) to return to the previous screen.

SQL Text	
<pre>select /*+ USE_NL(s c) FULL(s) FULL(c) AST */ c.cust_id, sum(s.quantity_sold) from sh.sales s, sh.customers c where s.cust_id = c.cust_id and c.cust_id < 2 group by c.cust_id</pre>	

- l) Investigate a SQL profile. While still on the “Recommendations for SQL_ID” page, click the SQL text to go to the SQL Details page for this SQL.

Statistics	Activity	Plan	Plan Control	Tuning History	SQL Monitoring
----------------------------	--------------------------	----------------------	------------------------------	-----------------------	--------------------------------

SQL Tuning History

The following SQL tuning tasks provide the recommendations to tune this SQL statement.

Advisor Task Name	Advisor Task Owner	Task Completion
SYS_AUTO_SQL_TUNING_TASK	SYS	Aug 3, 2009 6:34:13 PM

ADDM Findings for this SQL during historic period

Finding Name	Occurrences (during selected historical period)
--------------	---

Practice 15-1: Using Automatic SQL Tuning (continued)

- m) On the SQL Details - Tuning History page note the link to SYS_AUTO_SQL_TUNING_TASK that is there to show that the SQL was tuned by this tuning task.
- n) Click the Plan Control tab.

SQL Profiles and SQL Patches

A SQL Profile contains additional information(auxillary statistics) that aids the optimizer to select the optimal execution plan of a particular SQL statement. A SQL Patch is automatically generated to workaround an error or performance problem for a single SQL statement.

Change Category Delete Disable/Enable


Select	Name	Type	Category	Status	Created
<input checked="" type="radio"/>	SYS_SQLPROF_0122e0099ab30000	AUTO	DEFAULT	ENABLED	Aug 3, 2009 6:34:01 PM

SQL Plan Baseline

A SQL Plan Baseline is an execution plan deemed to have acceptable performance for a given SQL statement.

Select	Name	Fix	Accept	Auto Purge	Enabled	Created
--------	------	-----	--------	------------	---------	---------

- o) Note that a profile was created automatically for this SQL. The type of AUTO means it was automatically created.
- p) Click the Statistics tab to take a look at the execution history for this SQL.



- q) Depending on the speed of your machine, you may not see two hash values. If that is the case, ignore this step and the following one. Select Real Time: Manual Refresh from the View Data and then each of possible two Plan Hash Values from the corresponding drop-down list. Choose one after the other and wait for the page to refresh each time.

Practice 15-1: Using Automatic SQL Tuning (continued)

- r) Depending on the speed of your environment, you should see one statement with a relatively high elapsed time per execution, and one with very low elapsed time per execution. This shows the improved plan. If you select All from the Plan Hash Values drop-down list, you might not be able to see the execution corresponding to the statement after tuning on the Summary graph. This might be because the workload was too short to execute.
- 8) Generate a text report for more in-depth information. From the command line, execute `ast_task_report.sh` script. What do you observe?
 - a) Notice the first queries that fetch execution name and object number from the advisor schema, followed by the final query that gets the text report. In the text report, look for the section about the SQL profile finding and peruse the Validation Results section. This shows you the execution statistics observed during test-execute and allows you to get more of a feeling about the profile's quality. You can also use the `report_auto_tuning_task` API to get reports that span multiple executions of the task.

```
$ cat ast_task_report.sh
#!/bin/bash
# For training only - execute as oracle OS user

sqlplus / as sysdba <<EOF!
set echo on
set long 1000000000
set longchunksize 1000
set serveroutput on

--
-- Check the execution names
--
alter session set nls_date_format = 'MM/DD/YYYY HH24:MI:SS';

select execution_name, status, execution_start
from   dba_advisor_executions
where  task_name = 'SYS_AUTO_SQL_TUNING_TASK'
order by execution_start;

variable last_exec varchar2(30);

begin
  select max(execution_name) keep (dense_rank last order by
execution_start)
  into   :last_exec
  from   dba_advisor_executions
  where  task_name = 'SYS_AUTO_SQL_TUNING_TASK';
end;
/

print :last_exec

--
```

Practice 15-1: Using Automatic SQL Tuning (continued)

```
-- Find the object ID for query AST with sql_id by9m5m597zh19
--
variable obj_id number;

begin
  select object_id
  into   :obj_id
  from   dba_advisor_objects
  where  task_name = 'SYS_AUTO_SQL_TUNING_TASK' and
         execution_name = :last_exec and
         type = 'SQL' and
         attr1 = 'by9m5m597zh19';

end;
/

print :obj_id

--
-- Get a text report to drill down on this one query
--
set pagesize 0
select dbms_sqltune.report_auto_tuning_task(
       :last_exec, :last_exec, 'TEXT', 'TYPICAL', 'ALL', :obj_id)
from dual;

EOF!

$
```

```
$ ./ast_task_report.sh

SQL> SQL> SQL> SQL> SQL> SQL> SQL> SQL>
Session altered.

SQL> SQL>      2      3      4
EXECUTION_NAME                                STATUS      EXECUTION_START
-----
EXEC_176                                COMPLETED    08/03/2009 18:33:49

SQL> SQL> SQL> SQL>      2      3      4      5      6      7
PL/SQL procedure successfully completed.

SQL> SQL>
LAST_EXEC
-----
EXEC_176

SQL> SQL> SQL> SQL> SQL> SQL> SQL>      2      3      4      5      6
7      8      9     10
PL/SQL procedure successfully completed.
```

Practice 15-1: Using Automatic SQL Tuning (continued)

```

SQL> SQL>
      OBJ_ID
-----
          3

SQL> SQL> SQL> SQL> SQL> SQL>      2      3  GENERAL INFORMATION
SECTION
-----
-----
Tuning Task Name                      :
SYS_AUTO_SQL_TUNING_TASK
Tuning Task Owner                      : SYS
Workload Type                         : Automatic High-Load
SQL Workload
Scope                                 : COMPREHENSIVE
Global Time Limit(seconds)            : 3600
Per-SQL Time Limit(seconds)           : 1200
Completion Status                     : COMPLETED
Started at                           : 08/03/2009 18:33:49
Completed at                          : 08/03/2009 18:34:13
Number of Candidate SQLs              : 3
Cumulative Elapsed Time of SQL (s)    : 53
-----
-----
Object ID      : 3
Schema Name:  AST
SQL ID         : by9m5m597zh19
SQL Text       : select /*+ USE_NL(s c) FULL(s) FULL(c) AST */
c.cust_id,
               sum(s.quantity_sold) from sh.sales s,
sh.customers c where
               s.cust_id = c.cust_id and c.cust_id < 2 group by
c.cust_id
-----
-----
FINDINGS SECTION (2 findings)
-----
-----
1- SQL Profile Finding (see explain plans section below)
-----
A potentially better execution plan was found for this
statement.
SQL profile "SYS_SQLPROF_0122e0099ab30000" was created
automatically for
this statement.

Recommendation (estimated benefit: 98.47%)
-----

```

Practice 15-1: Using Automatic SQL Tuning (continued)

```
- An automatically-created SQL profile is present on the
system.
  Name:      SYS_SQLPROF_0122e0099ab30000
  Status:    ENABLED

Validation results
-----
The SQL profile was tested by executing both its plan and
the original plan
and measuring their respective execution statistics. A plan
may have been
only partially executed if the other could be run to
completion in less time.
```

	Original Plan	With SQL Profile	%
Improved	-----	-----	---

Completion Status:	COMPLETE	COMPLETE	
Elapsed Time(us):	191076	208	
99.89 %			
CPU Time(us):	160775	200	
99.87 %			
User I/O Time(us):	0	0	
Buffer Gets:	2541	39	
98.46 %			
Physical Read Requests:	0	0	
Physical Write Requests:	0	0	
Physical Read Bytes:	0	0	
Physical Write Bytes:	0	0	
Rows Processed:	0	0	
Fetches:	0	0	
Executions:	1	1	

Notes

1. The original plan was first executed to warm the buffer cache.
2. Statistics for original plan were averaged over next 4 executions.
3. The SQL profile plan was first executed to warm the buffer cache.
4. Statistics for the SQL profile plan were averaged over next 9 executions.

2- Index Finding (see explain plans section below)

The execution plan of this statement can be improved by creating one or more indices.

Recommendation (estimated benefit: 90.98%)

Practice 15-1: Using Automatic SQL Tuning (continued)

```
-----
- Consider running the Access Advisor to improve the
physical schema design
  or creating the recommended index.
  create index SH.IDX$$_00010001 on SH.SALES("CUST_ID");
```

Rationale

```
-----
Creating the recommended indices significantly improves
the execution plan
of this statement. However, it might be preferable to run
"Access Advisor"
using a representative SQL workload as opposed to a single
statement. This
will allow to get comprehensive index recommendations
which takes into
account index maintenance overhead and additional space
consumption.
```

EXPLAIN PLANS SECTION

```
-----
1- Original With Adjusted Cost
```

```
-----
Plan hash value: 4005616876
```

```
-----
| Id | Operation | Name | Rows | Bytes |
Cost (%CPU)| Time |
| Pstart| Pstop |
-----
| 0 | SELECT STATEMENT | | 1 | 13 |
893 (1) | 00:00:1
1 | | |
| 1 | HASH GROUP BY | | 1 | 13 |
893 (1) | 00:00:1
1 | | |
| 2 | NESTED LOOPS | | 1 | 13 |
892 (1) | 00:00:1
1 | | |
| * 3 | TABLE ACCESS FULL | CUSTOMERS | 1 | 5 |
405 (1) | 00:00:0
5 | | |
| 4 | PARTITION RANGE ALL | | 1 | 8 |
488 (2) | 00:00:0
```

Practice 15-1: Using Automatic SQL Tuning (continued)

```

6 |      1 |      28 |
|* 5 |      TABLE ACCESS FULL | SALES      |      1 |      8 |
488  (2) | 00:00:0
6 |      1 |      28 |
-----
-----
-----

Predicate Information (identified by operation id):
-----

      3 - filter("C"."CUST_ID"<2)
      5 - filter("S"."CUST_ID"<2 AND "S"."CUST_ID"="C"."CUST_ID")

2- Using SQL Profile
-----
Plan hash value: 3070788227

-----
-----

| Id | Operation | Name | | | |
|---|---|---|---|---|---|
| Rows | Bytes | Cost (%CPU) | Time | Pstart | Pstop |
|-----|-----|-----|-----|-----|-----|
-----
| 0 | SELECT STATEMENT | |
| 1 |      13 | |
55 (2) | 00:00:01 | |
| 1 | HASH GROUP BY | |
| 1 |      13 | |
55 (2) | 00:00:01 | |
| 2 | NESTED LOOPS | |
| 1 |      13 | |
54 (0) | 00:00:01 | |
| 3 | PARTITION RANGE ALL | |
| 1 |      8 | |
54 (0) | 00:00:01 | 1 | 28 |
| 4 | TABLE ACCESS BY LOCAL INDEX ROWID | SALES |
| 1 |      8 | |
54 (0) | 00:00:01 | 1 | 28 |
| 5 | BITMAP CONVERSION TO ROWIDS | | |
| | | |
|* 6 | BITMAP INDEX RANGE SCAN | SALES_CUST_BIX |
| | | 1 | 28 |
|* 7 | INDEX UNIQUE SCAN | CUSTOMERS_PK |
| 1 |      5 | |
0 (0) | 00:00:01 | |

```

Practice 15-1: Using Automatic SQL Tuning (continued)

Predicate Information (identified by operation id):

```

6 - access("S"."CUST_ID"<2)
    filter("S"."CUST_ID"<2)
7 - access("S"."CUST_ID"="C"."CUST_ID")
    filter("C"."CUST_ID"<2)

```

3- Using New Indices

Plan hash value: 1871796534

Id	Operation	Name
Rows	Bytes	
Cost (%CPU)	Time	Pstart Pstop
0	SELECT STATEMENT	
1	13	
5	(0) 00:00:01	
1	SORT GROUP BY NOSORT	
1	13	
5	(0) 00:00:01	
2	NESTED LOOPS	
3	NESTED LOOPS	
1	13	
5	(0) 00:00:01	
* 4	INDEX RANGE SCAN	CUSTOMERS_PK
1	5	
2	(0) 00:00:01	
* 5	INDEX RANGE SCAN	IDX\$\$_00010001
1		
2	(0) 00:00:01	
6	TABLE ACCESS BY GLOBAL INDEX ROWID	SALES
1	8	
3	(0) 00:00:01	ROWID ROWID

Predicate Information (identified by operation id):

Practice 15-1: Using Automatic SQL Tuning (continued)

```

4 - access("C"."CUST_ID"<2)
5 - access("S"."CUST_ID"="C"."CUST_ID")
   filter("S"."CUST_ID"<2)


```

```

SQL> SQL>
$

```

- 9) Investigate how to configure Automatic SQL Tuning with Enterprise Manager.
 - a) Logged into Enterprise Manager as the SYS user, navigate to Server > Automated Maintenance Tasks.
 - b) The chart here shows times in the past when each client was executed, and times in the future when they are scheduled to run again.



- c) Modify the graph's begin and end points with the widgets in the upper right.
- d) Click the Configure button.

Window	Optimizer Statistics Gathering	Segment Advisor	Automatic SQL Tuning
MONDAY_WINDOW	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>


Practice 15-1: Using Automatic SQL Tuning (continued)

On the Automated Maintenance Tasks Configuration page, you can disable individual clients and change which windows they run in.

- e) Disable the Automatic SQL Tuning client entirely and click Show SQL.

```
BEGIN
dbms_auto_task_admin.disable(client_name => 'sql tuning advisor',
operation => NULL, window_name => NULL);
END;
```

- f) Review the commands and then click Return.
- g) On the Automated Maintenance Tasks Configuration page, click Apply. You should receive a success message.
- h) Click the Automated Maintenance Tasks locator link.

Task Name
Optimizer Statistics Gathering
Segment Advisor
Automatic SQL Tuning


- i) Notice the forbidden sign right next to the task name.
- j) Click Configure.

Show SQL
Revert
Apply

Automated Maintenance Tasks Configuration

Global Status ☒ Enabled ☐ Disabled

Task Settings

Optimizer Statistics Gathering	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled	Configure
Segment Advisor	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled	
Automatic SQL Tuning	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled	Configure

- k) Enable the task again.

```
BEGIN
dbms_auto_task_admin.enable(client_name => 'sql tuning advisor',
operation => NULL, window_name => NULL);
END;
```

- l) Optionally, click Show SQL, review the commands and then click Return.
- m) Then click Apply to enable Automatic SQL Tuning. You should receive a success message.
- n) Navigate to the Automatic SQL Tuning page. If you are on the Automated Maintenance Tasks Configuration page, click the Configure button for Automatic SQL Tuning.

Practice 15-1: Using Automatic SQL Tuning (continued)

Automatic SQL Tuning Settings

Maximum Time Spent Per SQL During Tuning (sec)

Automatic Implementation of SQL Profiles ☐ Yes ☒ No

Maximum SQL Profiles Implemented Per Execution

Maximum SQL Profiles Implemented (Overall)

- o) On the Automatic SQL Tuning Settings page, select No in front of the “Automatic Implementation of SQL Profiles” field, and click Show SQL.

```
BEGIN
dbms_sqltune.set_auto_tuning_task_parameter( 'ACCEPT_SQL_PROFILES',
'FALSE' );
END;
```

- p) Review the command, click Return, and then click Apply. You should receive a success message.

- 10) OPTIONAL: You can investigate how to configure Automatic SQL Tuning using PL/SQL looking at the following script: `ast_manual_config.sh` and script.

Note: In your case, the task executes quickly because the workload to take into account is really small. However, you could use the `ast_interrupt_task.sh` script from another session to stop the task, should it last too long.

You received complaints that certain batch jobs are using too many system resources and that a specific user is known to start data warehouse processes during regular business hours. You decide to use the Database Resource Manager for better system-resource utilization and control.

Your first effort to balance the situation includes creating an APPUSER consumer group and assigning it to the default DEFAULT_PLAN resource plan. You then map a couple of Oracle users and your major OS user to resource groups. Activate the resource plan and test your assignments. Regularly click Show SQL to review all statements that are new to you.

Practice 16-1: Managing Resources

In this practice, you create an APPUSER consumer group and assign it to the default DEFAULT_PLAN resource plan. Then you map a couple of Oracle users and your major OS user to resource groups. Activate the resource plan and test your assignments.

Log in as the SYS user (with oracle_4U password, connect as SYSDBA) and perform the necessary tasks through Enterprise Manager Database Control or through SQL*Plus. All scripts for this practice are in the /home/oracle/labs directory.

Whenever you open a new terminal window, execute the oraenv script to set environment variables for the orcl database.

- 1) Using Enterprise Manager Database Control, create a resource group called APPUSER. At this point, do not add users to the group.
 - a) In Enterprise Manager, select Server > Consumer Groups (in the Resource Manager section).
 - b) On the Consumer Groups page, click the Create button.

Database Instance: orcl.us.oracle.com > Consumer Groups > Logged in As SYS

Create Resource Consumer Group

Show SQL Cancel OK

General Roles

Consumer Groups are user sessions that are grouped together based on resource processing requirements. Each Consumer Group definition specifies the users and roles that are allowed to switch into this Consumer Group.

* Consumer Group:

Description:

Scheduling Policy:

Users permitted to run in this Consumer Group

Add

Select User	Admin Option
No items found	

- c) Enter APPUSER as Consumer Group and ensure that the Scheduling Policy is set to Round Robin.

Question 1: What does the ROUND-ROBIN parameter value mean?

Possible Answer: ROUND-ROBIN indicates that CPU resources are fairly allocated to the APPUSER consumer group, according to the active resource plan directives.

- d) Optionally, click Show SQL, review the statements, and then click Return

Practice 16-1: Managing Resources (continued)

Show SQL

```

BEGIN
dbms_resource_manager.clear_pending_area();
dbms_resource_manager.create_pending_area();
dbms_resource_manager.create_consumer_group(consumer_group => ?, comment => ? ,
cpu_mth => ?);
dbms_resource_manager.submit_pending_area();
END;

```

Return

The bind variables are not displayed for security reasons.

- e) On the Create Resource Consumer Group page, click OK to create the consumer group.
- f) A confirmation message appears and the new consumer group is displayed. After confirming its creation, click the “Database Instance:orcl.us.oracle.com” link.

Database Instance: [orcl.us.oracle.com](#) > Logged in As SYS

Confirmation
The object has been created successfully

Consumer Groups

Search


Object Name

By default, the search returns all uppercase matches beginning with the string you entered. To run an exact or case-sensitive match, double quote the search string. You can use the wildcard symbol (%) in a double quoted string.

Select	Consumer Group	Mandatory	Description
<input checked="" type="radio"/>	APPUSER	NO	
<input type="radio"/>	AUTO_TASK_CONSUMER_GROUP	NO	System maintenance task consumer group
<input type="radio"/>	BATCH_GROUP	NO	Consumer group for batch operations
<input type="radio"/>	DEFAULT_CONSUMER_GROUP	YES	Consumer group for users not assigned to any consumer group

- 2) Add the APPUSER and LOW_GROUP consumer groups to the DEFAULT_PLAN resource plan. Change the level 3 CPU resource allocation percentages: 60% for the APPUSER consumer group and 40% for the LOW_GROUP consumer group.
 - a) In Enterprise Manager, select Server > Plans.
 - b) On the Resource Plans page, select DEFAULT_PLAN and click the Edit button.
 - c) Click Modify.
 - d) On the Select Groups/Subplans page, move APPUSER and LOW_GROUP to the “Resource Allocations.”

Practice 16-1: Managing Resources (continued)



- e) Click OK.
- f) Enter 60 for APPUSER Level 3 and 40 for LOW_GROUP Level 3.
- g) Click Show SQL.

```
DECLARE
spfileValue VARCHAR2(1000);
scopeValue VARCHAR2(10) := 'MEMORY';
planName VARCHAR2(100) :=?;
BEGIN
dbms_resource_manager.clear_pending_area();
dbms_resource_manager.create_pending_area();
dbms_resource_manager.create_plan_directive(
    plan => ?,
    group_or_subplan => ?,
    comment => ?,
    mgmt_p1 => ?, mgmt_p2 => ?, mgmt_p3 => ?, mgmt_p4 => ?,
    mgmt_p5 => ?, mgmt_p6 => ?, mgmt_p7 => ?, mgmt_p8 => ? ,
    parallel_degree_limit_p1 => ? ,
    switch_io_reqs => ? ,
    switch_io_megabytes => ?
,
    active_sess_pool_p1 => ?,
    queueing_p1 => ?,
    switch_group => ?,
    switch_time => ?,
    switch_estimate => case ? when 'false' then false when
'true' then true else false end,
    max_est_exec_time=> ?,
    undo_pool => ? ,
    max_idle_time => ?,
    max_idle_blocker_time => ?,
    switch_for_call => case ? when 'false' then false when
'true' then true else false end
);
dbms_resource_manager.create_plan_directive(
    plan => ?,
    group_or_subplan => ?,
    comment => ?,
    mgmt_p1 => ?, mgmt_p2 => ?, mgmt_p3 => ?, mgmt_p4 => ?,
    mgmt_p5 => ?, mgmt_p6 => ?, mgmt_p7 => ?, mgmt_p8 => ? ,
```

Practice 16-1: Managing Resources (continued)

```
parallel_degree_limit_pl => ? ,
switch_io_reqs => ? ,
switch_io_megabytes => ?
,
active_sess_pool_pl => ? ,
queueing_pl => ? ,
switch_group => ? ,
switch_time => ? ,
switch_estimate => case ? when 'false' then false when
'true' then true else false end ,
max_est_exec_time => ? ,
undo_pool => ? ,
max_idle_time => ? ,
max_idle_blocker_time => ? ,
switch_for_call => case ? when 'false' then false when
'true' then true else false end
);
dbms_resource_manager.submit_pending_area();
select value into spfileValue from v$parameter where name =
'spfile';
IF spfileValue IS NOT NULL then
EXECUTE IMMEDIATE
'alter system set resource_manager_plan = '||planName||' scope
=BOTH';
END IF;
dbms_resource_manager.switch_plan( plan_name => ? , sid => ? ,
allow_scheduler_plan_switches => FALSE );
END;
```

h) Review the code, then click Return.

Modify							
Group/Subplan	Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7
APPUSER			60				
LOW_GROUP			40				
ORA\$AUTOTASK_SUB_PLAN		5					
ORA\$DIAGNOSTICS		5					
OTHER_GROUPS		90					
SYS_GROUP	95						
General Parallelism Session Pool Undo Pool Threshold Idle Time							

- i) On the Edit Resource Plan: DEAFULT_PLAN page, click Apply to assign the APPUSER and the LOW_GROUP consumer groups to the DEFAULT_PLAN resource plan. (You activate this plan later.)
- j) You should receive a message, that your update was successful.

Practice 16-1: Managing Resources (continued)

- 3) Configure Consumer Group Mappings, so that the HR Oracle user belongs to the APPUSER consumer group, and the SCOTT user to the LOW_GROUP consumer group. For the SCOTT user, confirm that his ORACLE_USER attribute has a higher priority than the CLIENT_OS_USER attribute.

- a) In Enterprise Manager, select Server > Consumer Group Mappings.
- b) Select Oracle User and click the “Add Rule for Selected Type” button.

Add Rule for Selected Type				
Select	Priority	View	Value	Consumer Group
<input type="radio"/>		1 Service Module and Action	No Mappings Specified	
<input type="radio"/>		2 Service and Module	No Mappings Specified	
<input type="radio"/>		3 Module and Action	No Mappings Specified	
<input type="radio"/>		4 Module	No Mappings Specified	
<input type="radio"/>		5 Service	No Mappings Specified	
<input checked="" type="radio"/>		6 Oracle User	SYS, SYSTEM	SYS_GROUP

- c) On the Consumer Group Mappings page, ensure that APPUSER is selected as “Selected Consumer Group.”

Consumer Group Mappings

Use a mapping rule to automatically assign sessions to specific consumer groups by setting up mappings between session attributes and consumer groups.

Selected Consumer Group

Oracle User

Available Oracle User

ANONYMOUS
APEX_030200

Selected Oracle User

HR

- d) Move the HR user into the Selected Oracle User region, and then click OK.
- e) You should receive a success message. On the Consumer Group Mappings General page, click Show SQL.

Practice 16-1: Managing Resources (continued)

[Show SQL](#)
Return

```

BEGIN
dbms_resource_manager.clear_pending_area();
dbms_resource_manager.create_pending_area();
dbms_resource_manager.set_consumer_group_mapping(
    dbms_resource_manager.oracle_user,
    'HR',
    'APPUSER'
);
dbms_resource_manager.submit_pending_area();
END;

```

- f) Review the statements and click Return.
- g) Click Apply to assign the HR user to the APPUSER consumer group.

Update Message

Consumer Group Mappings has been modified successfully

Consumer Group Mappings

[Show SQL](#)
[Revert](#)
[Apply](#)

General
Priorities

Create rules to enable the resource manager to automatically assign sessions to consumer groups

View All

Add Rule for Selected Type

Select	Priority	View	Value	Consumer Group	Remove
<input type="radio"/>	1	Service Module and Action	No Mappings Specified		
<input type="radio"/>	2	Service and Module	No Mappings Specified		
<input type="radio"/>	3	Module and Action	No Mappings Specified		
<input type="radio"/>	4	Module	No Mappings Specified		
<input type="radio"/>	5	Service	No Mappings Specified		
<input checked="" type="radio"/>	6	Oracle User	<div>HR</div> <div>SYS, SYSTEM</div>	<div>APPUSER</div> <div>SYS_GROUP</div>	<div></div> <div></div>

- h) Select Oracle User again, and click the “Add Rule for Selected Type” button.

Practice 16-1: Managing Resources (continued)

Consumer Group Mappings

Use a mapping rule to automatically assign sessions to specific consumer groups by setting up mappings between session attributes and consumer groups.

Selected Consumer Group: **LOW_GROUP**

Oracle User

Available Oracle User

- ANONYMOUS
- APEX_030200

Selected Oracle User

- SCOTT

Move

Cancel OK

- i) Select LOW_GROUP from the Selected Consumer Group drop-down list, and move SCOTT into the Selected Oracle User area, and then click OK.
- j) You should receive a success message (but do not yet apply your changes.) On the Consumer Group Mappings page, click the Priorities tab.

Consumer Group Mappings

Show SQL Revert Apply

General **Priorities**


Reorder the list of mappings to set priorities. Mappings at the top of the list receive the highest priority. In order to decide between conflicting mappings, you can establish a priority ordering of the attributes from most important to least important. The priority of each attribute is set to a unique integer from 1 to 10.

Attribute Mappings

- Service Module and Action
- Service and Module
- Module and Action
- Module
- Service
- Oracle User**
- Client Program
- Client OS User
- Client Machine

- k) Confirm that “Oracle User” has a higher priority than “Client OS User.”
- l) Click Apply to assign the SCOTT user to the LOW_GROUP consumer group. You should receive a success message.
- 4) Configure Consumer Group Mappings so that the oracle OS user belongs to the SYS_GROUP consumer group.
 - a) Return to the Consumer Group Mappings –General page.
 - b) Select Client OS User and click the “Add Rule for Selected Type” button.

Practice 16-1: Managing Resources (continued)



Selected Consumer Group: **SYS_GROUP**

Client OS User


Currently connected Client OS User:

Selected Client OS User: **oracle**

Move

- c) Select SYS_GROUP from the Selected Consumer Group drop-down list, move oracle into the Selected Client OS User area, and click OK.

You should receive a success message.



Show SQL

```
BEGIN
dbms_resource_manager.clear_pending_area();
dbms_resource_manager.create_pending_area();
dbms_resource_manager.set_consumer_group_mapping(
    dbms_resource_manager.client_os_user,
    'oracle',
    'SYS_GROUP'
);
dbms_resource_manager.submit_pending_area();
END;
```

- d) Optionally, click Show SQL, review the statements, and click Return.

Practice 16-1: Managing Resources (continued)

Consumer Group Mappings

Show SQL
Revert
Apply

General
Priorities

Create rules to enable the resource manager to automatically assign sessions to consumer groups

View: All

Add Rule for Selected Type

Select	Priority	View	Value	Consumer Group	Remove
<input type="radio"/>	1	Service Module and Action	No Mappings Specified		
<input type="radio"/>	2	Service and Module	No Mappings Specified		
<input type="radio"/>	3	Module and Action	No Mappings Specified		
<input type="radio"/>	4	Module	No Mappings Specified		
<input type="radio"/>	5	Service	No Mappings Specified		
<input type="radio"/>	6	Oracle User	<div>SCOTT </div> <div>HR </div> <div>SYS, SYSTEM </div>	<div>LOW_GROUP</div> <div>APPUSER</div> <div>SYS_GROUP</div>	<div></div> <div></div> <div></div>
<input type="radio"/>	7	Client Program	No Mappings Specified		
<input checked="" type="radio"/>	8	Client OS User	oracle	SYS_GROUP	
<input type="radio"/>	9	Client Machine	No Mappings Specified		

e) Click Apply to assign the oracle OS user to the SYS_GROUP consumer group.

You should receive a success message.

- 5) Assign the PM Oracle user to the following consumer groups: APPUSER, LOW_GROUP, and SYS_GROUP.
 - a) In Enterprise Manager, select Server > Users (in the Security section).
 - b) Select the PM user and click the Edit button.

Practice 16-1: Managing Resources (continued)

Edit User: PM

Actions: Create Like Go Show SQL Revert Apply

General Roles System Privileges Object Privileges Quotas Consumer Group Privileges Proxy Users

Name **PM**

Profile DEFAULT

Authentication Password

Enter Password •••••

Confirm Password •••••

For Password choice, the role is authorized via password.

☐ Expire Password now

Default Tablespace USERS

Temporary Tablespace TEMP

Status ☐ Locked ☒ Unlocked

- Click the Consumer Groups Privileges tab. If you see an error regarding the password for the PM user, enter oracle_4U in both the password fields.
- Click the Edit List button.
- Move the APPUSER, LOW_GROUP, and SYS_GROUP consumer groups to Selected Consumer Groups and click OK.

Edit User: PM

Actions: Create Like Go Show SQL Revert Apply

General Roles System Privileges Object Privileges Quotas **Consumer Group Privileges** Proxy Users

Resource consumer groups are groups of users, or sessions, that are grouped together based on their processing needs. If a user is granted permission to switch to a particular consumer group, then that user can switch their current consumer group to the new consumer group.

Edit List

Consumer Group	Admin Option
APPUSER	<input type="checkbox"/>
LOW_GROUP	<input type="checkbox"/>
SYS_GROUP	<input type="checkbox"/>

Default Consumer Group None

- Click Show SQL.

Practice 16-1: Managing Resources (continued)

[Show SQL](#)Return

```
BEGIN
    dbms_resource_manager_privs.grant_switch_consumer_group(
        grantee_name => 'PM',
        consumer_group => 'APPUSER',
        grant_option => FALSE
    );
END;
BEGIN
    dbms_resource_manager_privs.grant_switch_consumer_group(
        grantee_name => 'PM',
        consumer_group => 'LOW_GROUP',
        grant_option => FALSE
    );
END;
BEGIN
    dbms_resource_manager_privs.grant_switch_consumer_group(
        grantee_name => 'PM',
        consumer_group => 'SYS_GROUP',
        grant_option => FALSE
    );
END;
```

g) Review the statements and click Return.

h) Click Apply to assign the PM user to these consumer groups.

You should receive a success message.

6) Activate the DEFAULT_PLAN resource plan.

a) In Enterprise Manager, select Server > Plans.

b) On the Resource Plans page, select DEFAULT_PLAN, select Activate from the Actions drop-down list, and click Go.



Confirmation

Are you sure you want to activate Resource Plan DEFAULT_PLAN?

c) Click Yes to confirm your activation.

You should see a success message.

7) Test the consumer group mappings. Start two SQL*Plus sessions: the first with the system/oracle_4U@orcl connect string and the second with the scott/oracle_4U@orcl connect string.

a) As the oracle user in a terminal window, execute the oraenv script to set environment variables for the orcl database.

Practice 16-1: Managing Resources (continued)

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$
```

Your output may be different depending on your previously executed tasks.

- b) To start a SQL*Plus session with the `system/oracle_4U@orcl` connect string and to set your SQL prompt to “FIRST,” enter:

```
$ sqlplus system@orcl
Enter password: oracle_4U <<< not displayed

SQL> SET SQLPROMPT "FIRST>"
FIRST>
```

- c) As the `oracle` user in a terminal window, execute the `oraenv` script to set environment variables for the `orcl` database.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$
```

Your output may be different depending on your previously executed tasks.

- d) To start a SQL*Plus session with the `scott/oracle_4U@orcl` connect string and to set your SQL prompt to “SECOND,” enter:

```
$ sqlplus scott@orcl
Enter password: oracle_4U <<< not displayed

SQL> SET SQLPROMPT "SECOND>"
SECOND>
```

- e) In your FIRST SQL*Plus session, enter:

```
FIRST>@query_rsc_groups.sql

SCHEMANAME                                RESOURCE_CONSUMER_GROUP
-----
--
DBSNMP                                     OTHER_GROUPS
DBSNMP                                     OTHER_GROUPS
DBSNMP                                     OTHER_GROUPS
SCOTT                                      LOW_GROUP

FIRST>
```

- f) **Question:** To which consumer group does the SCOTT user belong?

Answer: SCOTT is in the LOW_GROUP consumer group.

Note: Your output for this step (and the following steps) may not look exactly like the output shown. The information of concern here is for the specific users being mentioned.

Practice 16-1: Managing Resources (continued)

- g) In the SECOND terminal window, connect as the PM user with the oracle_4U password:

```
SECOND>connect pm@orcl
Enter password: oracle_4U <<< not displayed

Connected.
SECOND>
```

- h) In your FIRST SQL*Plus session, enter “/” to execute the previous SQL statement again.

```
FIRST>/

SCHEMANAME                                RESOURCE_CONSUMER_GROUP
-----
-
DBSNMP                                     OTHER_GROUPS
DBSNMP                                     OTHER_GROUPS
DBSNMP                                     OTHER_GROUPS
PM                                         SYS_GROUP

FIRST>
```

- i) **Question:** To which consumer group does the PM user belong?

Answer: PM is in the SYS_GROUP consumer group.

- j) In the SECOND terminal window, connect as the OE user with the oracle_4U password::

```
SECOND>connect oe@orcl
Enter password: oracle_4U <<< not displayed

Connected.
SECOND>
```

- k) In your FIRST SQL*Plus session, enter “/” to execute the previous SQL statement again.

```
FIRST>/

SCHEMANAME                                RESOURCE_CONSUMER_GROUP
-----
-
DBSNMP                                     OTHER_GROUPS
DBSNMP                                     OTHER_GROUPS
DBSNMP                                     OTHER_GROUPS
OE                                         OTHER_GROUPS

FIRST> exit
```

- l) Exit both the SQL*Plus sessions.


Practice 16-1: Managing Resources (continued)

- m) *Question:* When testing your OE Oracle user, you notice that OE is in the OTHER_GROUPS consumer group. Why is that?

Possible Answer: The OE user is not explicitly assigned to another consumer resource group.

- 8) Revert to your original configuration by deactivating the DEFAULT_PLAN resource group, locking accounts, undoing all consumer group mappings, and finally by deleting the APPUSER resource group.

- a) To deactivate the DEFAULT_PLAN resource plan in Enterprise Manager, select Server > Plans.



Select	Plan	Status	Description	Scheduler Windows
<input type="radio"/>	APPQOS_PLAN		Plan for Application QOS Management that provides a fixed set of allocations to the consumer groups that Application QOS uses to manage workload resource allocation.	
<input type="radio"/>	DEFAULT_MAINTENANCE_PLAN		Default plan for maintenance windows that prioritizes SYS_GROUP operations and allocates the remaining 5% to diagnostic operations and 25% to automated maintenance operations.	MONDAY_WINDOW TUESDAY_WINDOW WEDNESDAY_WINDOW THURSDAY_WINDOW FRIDAY_WINDOW SUNDAY_WINDOW SATURDAY_WINDOW
<input checked="" type="radio"/>	DEFAULT_PLAN	ACTIVE	Default, basic, pre-defined plan that prioritizes SYS_GROUP operations and allocates minimal resources for automated maintenance and	

- b) On the Resource Plans page, select the DEFAULT_PLAN, select Deactivate from the Actions drop-down list, and click Go.

- c) Click Yes to confirm your deactivation.

You should receive a success message.

- d) To reconfigure or undo all consumer group mappings, review and execute the rsc_cleanup.sh script from your working directory:

```
$ cat rsc_cleanup.sh
# Oracle Database 11g: Administration Workshop II
# Oracle Server Technologies - Curriculum Development
#
# ***Training purposes only***
# ***Not appropriate for production use***
#
# This script supports the Resource Manager practice session.
# Start this script connected as OS user: oracle.

sqlplus "/ as sysdba" << EOF
```

Practice 16-1: Managing Resources (continued)

```
PROMPT undo lab step 5

BEGIN
    dbms_resource_manager_privs.revoke_switch_consumer_group(
        revokee_name => 'PM',
        consumer_group => 'APPUSER'
    );
END;
/
BEGIN
    dbms_resource_manager_privs.revoke_switch_consumer_group(
        revokee_name => 'PM',
        consumer_group => 'LOW_GROUP'
    );
END;
/
BEGIN
    dbms_resource_manager_privs.revoke_switch_consumer_group(
        revokee_name => 'PM',
        consumer_group => 'SYS_GROUP'
    );
END;
/
PROMPT undo lab step 4

BEGIN
    dbms_resource_manager.clear_pending_area();
    dbms_resource_manager.create_pending_area();
    dbms_resource_manager.set_consumer_group_mapping(
        dbms_resource_manager.client_os_user,
        'ORACLE',
        NULL
    );
    dbms_resource_manager.submit_pending_area();
END;
/
PROMPT undo lab step 3

BEGIN
    dbms_resource_manager.clear_pending_area();
    dbms_resource_manager.create_pending_area();
    dbms_resource_manager.set_consumer_group_mapping(
        dbms_resource_manager.oracle_user,
        'HR',
        NULL
    );
    dbms_resource_manager.set_consumer_group_mapping(
        dbms_resource_manager.oracle_user,
        'SCOTT',
        NULL
    );
END;
```

Practice 16-1: Managing Resources (continued)

```

dbms_resource_manager.set_consumer_group_mapping(
    dbms_resource_manager.oracle_user,
    'SYS',
    NULL
);
dbms_resource_manager.set_consumer_group_mapping(
    dbms_resource_manager.oracle_user,
    'SYSTEM',
    NULL
);
dbms_resource_manager.submit_pending_area();
END;
/
PROMPT  undo lab step 2

BEGIN
dbms_resource_manager.clear_pending_area();
dbms_resource_manager.create_pending_area();
dbms_resource_manager.delete_plan_directive('DEFAULT_PLAN',
'APPUSER');
dbms_resource_manager.delete_plan_directive('DEFAULT_PLAN',
'LOW_GROUP');
dbms_resource_manager.submit_pending_area();
dbms_resource_manager.switch_plan( plan_name => '', sid =>
'orcl', allow_scheduler_plan_switches => FALSE );
END;
/
exit
EOF

```

```
$ ./rsc_cleanup.sh
```

```

SQL> SQL> SQL> undo lab step 5
SQL> SQL> 2      3      4      5      6      7
PL/SQL procedure successfully completed.

SQL> 2      3      4      5      6      7
PL/SQL procedure successfully completed.

SQL> 2      3      4      5      6      7
PL/SQL procedure successfully completed.

SQL> undo lab step 4
SQL> SQL> 2      3      4      5      6      7      8      9      10      11
PL/SQL procedure successfully completed.

SQL> undo lab step 3
SQL> SQL> 2      3      4      5      6      7      8      9      10      11
12     13     14     15     16     17     18     19     20     21     22     23     24
25     26

```

Practice 16-1: Managing Resources (continued)

```
PL/SQL procedure successfully completed.
```

```
SQL> undo lab step 2
```

```
SQL> SQL> 2      3      4      5      6      7      8      9
```

```
PL/SQL procedure successfully completed.
```

```
$
```

- e) To delete the APPUSER resource group in Enterprise Manager, select Server > Consumer Groups.



- f) On the Consumer Groups page, select APPUSER and click the Delete button.

- g) Confirm your deletion by clicking Yes.

You should receive a success message.

- h) Exit Enterprise Manager and close all terminal windows.

Practices for Lesson 17

In these practices, you explore Oracle Scheduler capabilities.

Practice 17-1: Creating Scheduler Components

In this practice, you use Enterprise Manager Database Control to create Scheduler objects in the ORCL database instance and automate tasks.

While logged in to the database as the HR user in Database Control, create a simple job that runs a SQL script:

- General:

Name: CREATE_LOG_TABLE_JOB

Owner: HR

Description: Create the SESSION_HISTORY table for the next part of this practice

Logging Level: RUNS

Command Type: PL/SQL

PL/SQL Block: BEGIN execute immediate('create table session_history(snap_time TIMESTAMP WITH LOCAL TIME ZONE, num_sessions NUMBER)'); END;

- Schedule:

Repeating: Do not Repeat

Start: Immediately

- Options:


No special options

1) As the SYS user, grant CONNECT, RESOURCE, and DBA roles to the HR user.

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl

$ sqlplus / as sysdba
Connected.
SQL> grant connect, resource, dba to hr;
Grant succeeded.
```

2) Log in to Enterprise Manager Database Control as the HR user with the oracle_4U password.



3) To create a job, navigate to Server > Jobs (in the Oracle Scheduler region).

a) On the Scheduler Jobs page, click the Create button.

b) On the Create Job - General page, enter and confirm the following values:

Name: CREATE_LOG_TABLE_JOB

Schema: HR

Practice 17-1: Creating Scheduler Components (continued)

Enabled: Yes

Description: Create the SESSION_HISTORY table

Logging Level: Log job runs only (RUNS)

Command Type: PL/SQL Block

PL/SQL Block:

```
begin
  execute immediate
    ('create table session_history(
      snap_time TIMESTAMP WITH LOCAL TIME ZONE,
      num_sessions NUMBER)');
end;
```

Database Instance: orcl.example.com > Scheduler Jobs > Logged in As HR

Create Job

[Show SQL](#) [Cancel](#) [OK](#)

General **Schedule** **Options**

* Name:

* Schema:

Enabled: ☒ Yes ☐ No

Description:

Logging Level: [Specify logging requirements for the job](#)

Job Class: [Create Job Class](#)

Auto Drop: [Specify whether the job should be dropped after completion](#)

Restartable: [Specify whether the job can be restarted manually or in the event of failure](#)

Destination: Credential Name:

[Command](#)

Select the command type for the job, then enter the command requirements.

Command Type: **PL/SQL Block** [Change Command Type](#)

```
begin
  execute immediate
    ('create table session_history(
      snap_time TIMESTAMP WITH LOCAL TIME ZONE,
      num_sessions NUMBER)');
end;
```

PL/SQL

c) On the Schedule folder tab, enter and confirm the following values:

Timezone: *Your_local_timezone*

Repeating: Do not Repeat

Start: Immediately

Practice 17-1: Creating Scheduler Components (continued)

General Schedule Options

Schedule Type: Standard

Time Zone: Etc/GMT-7

Repeating

Repeat: Do Not Repeat

Start

Immediately

Show SQL

d) Click Show SQL if you want to view the SQL statement defining your job.

```
BEGIN
sys.dbms_scheduler.create_job(
  job_name => 'HR"."CREATE_LOG_TABLE_JOB"',
  job_type => 'PLSQL_BLOCK',
  job_action => 'begin
    execute immediate
      (''create table session_history(
        snap_time TIMESTAMP WITH LOCAL TIME ZONE,
        num_sessions NUMBER)'');
  end;
',
  start_date => systimestamp at time zone 'Etc/GMT-7',
  job_class => 'DEFAULT_JOB_CLASS',
  comments => 'Create the SESSION_HISTORY table',
  auto_drop => FALSE,
  enabled => TRUE);
END;
```

e) Review the statements (Your time zone might be different.) and click Return.

f) Click OK to create the job.

Practice 17-1: Creating Scheduler Components (continued)

Confirmation Job HR.CREATE_LOG_TABLE_JOB has been created successfully								
Scheduler Jobs Page Refreshed Jul 31, 2009 2:48:14 PM GMT+07:00 Refresh Create								
All Running History								
View Job Definition Edit Job Definition Delete Run Now Create Like								
Select	Name	Schema	Scheduled Date	Last Run Date	Last Run Status	Enabled	Job Class	Previous Runs
<input checked="" type="radio"/>	MGMT_STATS_CONFIG_JOB	ORACLE_OCM	Aug 1, 2009 1:01:01 AM -07:00	Not Scheduled	SCHEDULED	✓	DEFAULT_JOB_CLASS	0
<input type="radio"/>	MGMT_CONFIG_JOB	ORACLE_OCM	MAINTENANCE_WINDOW_GROUP	Jul 30, 2009 8:00:07 AM -07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	1
<input type="radio"/>	RLM\$SCHDNEGACTION	EXFSYS	Jul 31, 2009 3:37:27 PM +07:00	Jul 31, 2009 2:39:50 PM +07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	6
<input type="radio"/>	RLM\$EVTCLANUP	EXFSYS	Jul 31, 2009 1:11:30 AM -07:00	Jul 31, 2009 12:39:50 AM -07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	6
<input type="radio"/>	CREATE_LOG_TABLE_JOB	HR	now running	Jul 31, 2009 2:48:14 PM +07:00	RUNNING	✓	DEFAULT_JOB_CLASS	0

- g) If the job does not appear on the Scheduler Jobs page, click the Refresh button until it succeeds. – Also, you may not see it “running”, but already with the Last Run Status of SUCCEEDED.
- 4) Create a program called LOG_SESS_COUNT_PRGM that logs the current number of database sessions into a table. Use the following code:

```

DECLARE
  sess_count  NUMBER;
BEGIN
  SELECT COUNT(*) INTO sess_count FROM V$SESSION;
  INSERT INTO session_history VALUES (sysimestamp,
    sess_count);
  COMMIT;
END;

```

- a) Logged into Enterprise Manager as the HR user, navigate to Server > Programs or click the Programs in the Related Links section on the Scheduler Jobs page.

Related Links		
Chains	Global Attributes	Job Classes
Programs	Schedules	Window Groups
Windows		

- b) On the Scheduler Programs page, click the Create button.
- c) On the Create Program page, enter and confirm the following values:

Name: LOG_SESS_COUNT_PRGM
 Schema: HR
 Enabled: Yes

Practice 17-1: Creating Scheduler Components (continued)

Type: PLSQL_BLOCK

Source:

```
DECLARE
sess_count    NUMBER;
BEGIN
SELECT COUNT(*) INTO sess_count FROM V$SESSION;
INSERT INTO session_history VALUES (systimestamp,
sess_count);
COMMIT;
END;
```

Create Program

Name: LOG_SESS_COUNT_PRGM

Schema: HR

Enabled: ☒ Yes ☐ No

Description:

Type: PLSQL_BLOCK

Source:

```
DECLARE
sess_count    NUMBER;
BEGIN
SELECT COUNT(*) INTO sess_count FROM V$SESSION;
INSERT INTO session_history VALUES (systimestamp, sess_count);
COMMIT;
END;
```

Show SQL Cancel OK

d) Click Show SQL.

```
BEGIN
DBMS_SCHEDULER.CREATE_PROGRAM(
program_name=>'HR"."LOG_SESS_COUNT_PRGM',
program_action=>'DECLARE
sess_count    NUMBER;
BEGIN
SELECT COUNT(*) INTO sess_count FROM V$SESSION;
INSERT INTO session_history VALUES (systimestamp, sess_count);
COMMIT;
END;
',
program_type=>'PLSQL_BLOCK',
number_of_arguments=>0,
comments=>' ',
enabled=>TRUE);
END;
```

e) Review the statements, and then click Return.

f) Click OK to create the program.

Practice 17-1: Creating Scheduler Components (continued)

<input type="radio"/>	<u>LOG_SESS_COUNT_PRGM</u>	HR	<input checked="" type="checkbox"/>	PLSQL_BLOCK
-----------------------	----------------------------	----	-------------------------------------	-------------

You should see the program on the Scheduler Programs page.

- 5) Create a schedule named SESS_UPDATE_SCHED owned by HR that executes every three seconds. Use SQL*Plus and the DBMS_SCHEDULER.CREATE_SCHEDULE procedure to create the schedule.

```
BEGIN
  DBMS_SCHEDULER.CREATE_SCHEDULE (
    schedule_name => 'SESS_UPDATE_SCHED',
    start_date => SYSTIMESTAMP,
    repeat_interval => 'FREQ=SECONDLY;INTERVAL=3',
    comments => 'Every three seconds');
END;
/
```

Return to Enterprise Manager Database Control and verify that the SESS_UPDATE_SCHED schedule was created.

Hint: You may have to refresh the page for the Schedule to appear.

- a) In a terminal window, enter:

```
$ sqlplus hr
Enter password: oracle_4U <<< not displayed
```

- b) In your SQL*Plus session, enter:

```
BEGIN
  DBMS_SCHEDULER.CREATE_SCHEDULE (
    schedule_name => 'SESS_UPDATE_SCHED',
    start_date => SYSTIMESTAMP,
    repeat_interval => 'FREQ=SECONDLY;INTERVAL=3',
    comments => 'Every three seconds');
END;
/
PL/SQL procedure successfully completed.
```

- c) In Enterprise Manager, select Server > Schedules.
- d) Verify that the SESS_UPDATE_SCHED schedule has been created. (You may have to refresh the page for the Schedule to appear.)

Practice 17-1: Creating Scheduler Components (continued)

Scheduler Schedules					
Page Refreshed Jul 31, 2009 2:56:53 PM GMT+07:00					
<div> <div>Edit</div> <div>View</div> <div>Delete</div> <div>Create Like</div> </div> <div> <div>Refresh</div> <div>Create</div> </div>					
Select	Name	Schema	Start Date	End Date	Description
<input checked="" type="radio"/>	BSLN_MAINTAIN_STATS_SCHED	SYS	Jul 12, 2009 12:00:00 AM -07:00		Pre-defined schedule for computing moving window baseline statistics
<input type="radio"/>	FILE_WATCHER_SCHEDULE	SYS			
<input type="radio"/>	DAILY_PURGE_SCHEDULE	SYS			
<input type="radio"/>	SESS_UPDATE_SCHED	HR	Jul 31, 2009 2:56:31 PM +07:00		Every three seconds

- 6) Using Enterprise Manager Database Control, create a job named LOG_SESSIONS_JOB that uses the LOG_SESS_COUNT_PRGM program and the SESS_UPDATE_SCHED schedule. Make sure that the job uses FULL logging.

a) In Enterprise Manager, select Server > Jobs, and then click the Create button.

b) On the Create Job page, enter and confirm the following values:

Name: LOG_SESSIONS_JOB

Owner: HR

Enabled: Yes

Description: Count sessions with HR.LOG_SESS_COUNT_PRGM

Logging level: Log everything (FULL)

c) Click Change Command Type, and on the Select Command Option page, select Program Name, and enter HR.LOG_SESS_COUNT_PRGM in the field next to it, or use the Lookup (flashlight) icon to select the program.

Select Command Option

Cancel

OK

Choose an existing program or specify an in-line program for execution. Program offers code re-usability and performance benefits over an in-line program.

☒ Program Name

Create Program

☐ PL/SQL

☐ Stored Procedure

☐ Executable

☐ Chain

Create Chain

d) Click OK.

Practice 17-1: Creating Scheduler Components (continued)

General **Schedule** **Options**

Name: LOG_SESSIONS_JOB

Schema: HR

Enabled: ☒ Yes ☐ No

Description: Count sessions with HR.LOG_SESS_COUNT_PRGM

Logging Level: Log everything (FULL)

Job Class: DEFAULT_JOB_CLASS

Auto Drop: FALSE

Restartable: FALSE

Destination:
 Destination and Credential Name only apply for jobs of type executable. For Destination specify the host:port of the machine on which the external job will run if the job is running remotely. For Credential Name specify the credential to use to run the external job.

Command

Select the command type for the job, then enter the command requirements.

Command Type: **Program**
 Program Name: **HR.LOG_SESS_COUNT_PRGM**

- e) Back on the Create Job page, click the Schedule tab.
- f) Change the Schedule Type to “Use Pre-Defined Schedule,” and select the HR.SESS_UPDATE_SCHED schedule by using the flashlight icon.

General **Schedule** **Options**

Schedule Type: Use Pre-defined Schedule

Select an existing schedule.

Schedule: HR SESS_UPDATE_SCHED

General

Name: SESS_UPDATE_SCHED

Schema: HR

Description: Every three seconds

Schedule Attributes

Repeat By Seconds

Interval (Seconds): 3

Available to Start: Jul 31, 2009 2:56:31 PM GMT +07:00

Not Available After:

- g) Click Show SQL.

Practice 17-1: Creating Scheduler Components (continued)

```
BEGIN
sys.dbms_scheduler.create_job(
job_name => '"HR"."LOG_SESSIONS_JOB"',
program_name => '"HR"."LOG_SESS_COUNT_PRGM"',
schedule_name => '"HR"."SESS_UPDATE_SCHED"',
job_class => '"DEFAULT_JOB_CLASS"',
comments => 'Count sessions with HR.LOG_SESS_COUNT_PRGM',
auto_drop => FALSE,
enabled => FALSE);
sys.dbms_scheduler.set_attribute( name => '"HR"."LOG_SESSIONS_JOB"',
attribute => 'logging_level', value => DBMS_SCHEDULER.LOGGING_FULL);
sys.dbms_scheduler.enable( '"HR"."LOG_SESSIONS_JOB"' );
END;
```

- h) Review the statements and then click Return.
- i) On the Create Job page, click OK to create the job.

You should receive a success message and see the job on the Scheduler Jobs page.

Select	Name	Schema	Scheduled Date	Last Run Date	Last Run Status	Enabled	Job Class	Previous Runs
<input checked="" type="radio"/>	MGMT_STATS_CONFIG_JOB	ORACLE_OCM	Aug 1, 2009 1:01:01 AM -07:00	Not Scheduled	SCHEDULED	✓	DEFAULT_JOB_CLASS	0
<input type="radio"/>	MGMT_CONFIG_JOB	ORACLE_OCM	MAINTENANCE_WINDOW_GROUP	Jul 30, 2009 8:00:07 AM -07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	1
<input type="radio"/>	RLM\$SCHDNAGACTION	EXFSYS	Jul 31, 2009 3:37:27 PM +07:00	Jul 31, 2009 2:39:50 PM +07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	6
<input type="radio"/>	RLM\$EVTCLANUP	EXFSYS	Jul 31, 2009 1:11:30 AM -07:00	Jul 31, 2009 12:39:50 AM -07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	6
<input type="radio"/>	LOG_SESSIONS_JOB	HR	Jul 31, 2009 3:05:34 PM +07:00	Jul 31, 2009 3:05:31 PM +07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	29

Note that it quickly accumulates previous runs, because it executes every three seconds.

- 7) In your SQL*Plus session, check the HR.SESSION_HISTORY table for rows.
 - a) Enter:

```
SQL> SELECT * FROM SESSION_HISTORY ORDER BY snap_time;
```

Your result looks different but the second values should be three seconds apart:

```
SNAP_TIME
-----
NUM_SESSIONS
-----
31-JUL-09 03.07.55.101299 PM
          41
```

Practice 17-1: Creating Scheduler Components (continued)

31-JUL-09 03.07.58.099194 PM
41

Question: If there are rows in the table, are the time stamps three seconds apart?

Answer: Yes, there are rows. Yes, the time stamps are three seconds apart.

- 8) Use Enterprise Manager Database Control to alter the SESS_UPDATE_SCHED schedule from every three seconds to every three minutes. Then use SQL*Plus to verify that the rows are now being added every three minutes: query the HR.SESSION_HISTORY table, ordered by the SNAP_TIME column.

- In Enterprise Manager, select Server > Schedules.
- Click the SESS_UPDATE_SCHED link.
- On the View Schedule page, click Edit.
- Change the description to “Every three minutes.”
- Change Available to Start to Immediately.
- Change the value in the Repeat drop-down list from By Seconds to **By Minutes**.

Edit Schedule: HR.SESS_UPDATE_SCHED

Name **SESS_UPDATE_SCHED**
Schema **HR**
Description

Schedule Attributes

Time Zone

Schedule Type

Repeating

Repeat

Interval (Minutes)

Available to Start

☒ Immediately

- g) Ensure that the interval is 3 and then click Show SQL.

Practice 17-1: Creating Scheduler Components (continued)

```
BEGIN
sys.dbms_scheduler.set_attribute( name => '"HR"."SESS_UPDATE_SCHED"', attribute =>
'repeat_interval', value => 'FREQ=MINUTELY;INTERVAL=3');
sys.dbms_scheduler.set_attribute( name => '"HR"."SESS_UPDATE_SCHED"', attribute =>
'start_date', value => systimestamp at time zone '+7:00');
sys.dbms_scheduler.set_attribute( name => '"HR"."SESS_UPDATE_SCHED"', attribute =>
'comments', value => 'Every three minutes');
END;
```

h) Review the statements, click Return, and then click Apply.

You should receive a success message.

- 9) In your SQL*Plus session, query the HR.SESSION_HISTORY table, ordered by the SNAP_TIME column. (Wait for three minutes after you update the schedule.) Enter:

```
SQL> SELECT * FROM HR.SESSION_HISTORY ORDER BY snap_time;
```

Your result looks different (but the minute values should be three minutes apart):

SNAP_TIME			

NUM_SESSIONS			

31-JUL-09	03.10	39.185103	PM
	41		
31-JUL-09	03.13	38.927866	PM
	41		

- 10) **This is your mandatory cleanup task.** Use Enterprise Manager to drop the LOG_SESSIONS_JOB and CREATE_LOG_TABLE_JOB jobs, the LOG_SESS_COUNT_PRGM program, and the SESS_UPDATE_SCHED schedule. Use SQL*Plus to drop the SESSION_HISTORY table, and exit from your session.

Note: Make sure that you do not delete the wrong schedule.

- a) In Enterprise Manager, select Server > Jobs.

Practice 17-1: Creating Scheduler Components (continued)

View Job Definition Edit Job Definition Delete Run Now Create Like					
Select	Name	Schema	Scheduled Date	Last Run Date	Last Run Status
<input type="radio"/>	MGMT_STATS_CONFIG_JOB	ORACLE_OCM	Aug 1, 2009 1:01:01 AM -07:00	Not Scheduled	SCHEDULED
<input type="radio"/>	MGMT_CONFIG_JOB	ORACLE_OCM	MAINTENANCE_WINDOW_GROUP	Jul 30, 2009 8:00:07 AM -07:00	SCHEDULED
<input type="radio"/>	RLM\$SCHDNEGACTION	EXFSYS	Jul 31, 2009 3:37:27 PM +07:00	Jul 31, 2009 2:39:50 PM +07:00	SCHEDULED
<input type="radio"/>	RLM\$EVTCLANUP	EXFSYS	Jul 31, 2009 1:11:30 AM -07:00	Jul 31, 2009 12:39:50 AM -07:00	SCHEDULED
<input checked="" type="radio"/>	LOG_SESSIONS_JOB	HR	Jul 31, 2009 3:05:34 PM +07:00	Jul 31, 2009 3:05:31 PM +07:00	SCHEDULED
<input type="radio"/>	CREATE_LOG_TABLE_JOB	HR	Not Scheduled	Jul 31, 2009	SUCCEEDED

b) With the LOG_SESSIONS_JOB job selected, click the Delete button.



Confirmation

Are you sure you want to delete Job HR.LOG_SESSIONS_JOB?

☒ Drop the job and stop any running instance.
☐ If there is a running instance of this job, it will not be dropped.

- c) Select “Drop the job and stop any running instance,” and then click Yes.
- d) Go back to the Scheduler Jobs page, select CREATE_LOG_TABLE_JOB, and click Delete. Select “Drop the job and stop any running instance,” and then click Yes.
- e) Click the Database Instance breadcrumb at the upper-left corner of the page to return to the Server page. Then click Programs.




LOG_SESS_COUNT_PRGM HR ✓ PLSQL_BLOCK

f) With the LOG_SESS_COUNT_PRGM program selected, click the Delete button. Click Yes to confirm.

Practice 17-1: Creating Scheduler Components (continued)

- g) Click Schedules in the Related Links section
- h) With the SESS_UPDATE_SCHED schedule selected, click the Delete button.
Make sure that you do not delete the wrong schedule.



Confirmation

Are you sure you want to delete Schedule Attributes HR.SESS_UPDATE_SCHED?

☐ Drop the schedule and all the dependent objects will be disabled.

☒ If there are dependent objects, it will not be dropped.

No Yes

- i) Select “If there are dependent objects, it will not be dropped,” and then click Yes to confirm.
- j) In your SQL*Plus session as the HR user, delete the SESSION_HISTORY table, and then exit the session. Enter:

```
SQL> DROP TABLE session_history PURGE;
Table dropped.

SQL> EXIT
```

Practice 17-2: Creating Lightweight Scheduler Jobs

In this optional practice, you create and run a lightweight scheduler job. View the metadata for a lightweight scheduler job. Navigate to your \$HOME/labs directory.

- 1) Create a job template for the lightweight job. The template must be a PL/SQL procedure or a PL/SQL block. Run the `cr_test_log.sql` script to create the `test_log` table. Then run `prog_1.sql`. The `prog_1.sql` script in the \$HOME/labs directory creates a job template.

Note: The job template has a subset of the attributes of a scheduler program. Most of the attributes of a template cannot be changed for the job.

- a) Navigate to the labs directory.

```
$ cd ~/labs
$
```

- b) Execute the `cr_test_log.sql` and `prog_1.sql` scripts as the system user. The password for the system user is `oracle_4U`.

```
$ sqlplus system
Enter password: oracle_4U <<< not displayed

SQL> @cr_test_log.sql
SQL> -- cleanup previous runs
SQL> -- you will see an error the first time this script is
run
SQL> drop table system.test_log;
drop table system.test_log
*
ERROR at line 1:
ORA-00942: table or view does not exist

SQL>
SQL> -- create a table to hold timing information
SQL>
SQL> create table system.test_log
2  (job_type          VARCHAR2(10),
3  timemark           VARCHAR2(10),
4  act_time           TIMESTAMP with TIME ZONE)
5  /

Table created.
```

```
SQL> @prog_1.sql
SQL> REM For training only
SQL> set echo on
SQL>
SQL> BEGIN
2  -- This will produce an error the first
3  -- time it is run since PROG_1 does not exist
4
```

Practice 17-2: Creating Lightweight Scheduler Jobs (continued)

```
5  DBMS_SCHEDULER.DROP_PROGRAM (
6      program_name          => ' "SYSTEM"."PROG_1" ' );
7  END;
8  /
BEGIN
*
ERROR at line 1:
ORA-27476: "SYSTEM.PROG_1" does not exist
ORA-06512: at "SYS.DBMS_ISCHED", line 27
ORA-06512: at "SYS.DBMS_SCHEDULER", line 61
ORA-06512: at line 5

SQL> BEGIN
2  DBMS_SCHEDULER.CREATE_PROGRAM(
3      program_name=>' "SYSTEM"."PROG_1" '
4      ,program_action=>'DECLARE
5          time_now DATE;
6          BEGIN
7              INSERT INTO test_log
VALUES(' 'LWT' ' , ' 'DONE' ' ,SYSTIMESTAMP);
8          END; '
9      , program_type=>'PLSQL_BLOCK'
10     , number_of_arguments=>0,
11     comments=>'Insert a timestamp into the test_log'
12     ,enabled=>TRUE);
13 END;
14 /
.
PL/SQL procedure successfully completed.
SQL>
```

- 2) Create a lightweight job, using the PL/SQL API. The job will run the my_prog template daily with an interval of 2, starting immediately.
- Note:** EM does not expose the JOB_STYLE setting at this time.
- a) Logged into SQL*Plus as the system user, execute the my_lwt_job.sql script.

```
SQL> @my_lwt_job.sql
SQL> REM For training only
SQL> set echo on
SQL> BEGIN
2      -- the drop procedure will give an error the first
time
3      -- this script is run
4      sys.DBMS_SCHEDULER.DROP_JOB('my_lwt_job');
5  END;
6  /
BEGIN
*
```

Practice 17-2: Creating Lightweight Scheduler Jobs (continued)

```
ERROR at line 1:
ORA-27475: "SYSTEM.MY_LWT_JOB" must be a job
ORA-06512: at "SYS.DBMS_ISCHED", line 213
ORA-06512: at "SYS.DBMS_SCHEDULER", line 651
ORA-06512: at line 4
```

```
SQL>
SQL> DECLARE
  2     jobname VARCHAR2(30);
  3 BEGIN
  4 -- Create the Job
  5 jobname := 'my_lwt_job';
  6 sys.dbms_scheduler.create_job(
  7     job_name => '"SYSTEM"."MY_LWT_JOB"',
  8     program_name => '"SYSTEM"."PROG_1"',
  9     job_class => '"DEFAULT_JOB_CLASS"',
 10     job_style => 'LIGHTWEIGHT',
 11     repeat_interval => 'FREQ=DAILY;INTERVAL=2',
 12     comments => 'Lightweight job',
 13     enabled => TRUE);
 14 END;
 15 /
```

PL/SQL procedure successfully completed.

```
SQL>
```

- 3) Check the Scheduler metadata views `USER_SCHEDULER_JOBS`, `_PROGRAMS`, `DBA_JOBS`. Select `JOB_NAME`, `JOB_STYLE`, and `PROGRAM_NAME` from `USER_SCHEDULER_JOBS`.

```
SQL> COL program_name format a12
SQL> SELECT job_name, job_style, program_name FROM
USER_SCHEDULER_JOBS;
```

JOB_NAME	JOB_STYLE	PROGRAM_NAME
MY_LWT_JOB	LIGHTWEIGHT	PROG_1

- 4) Check the Enterprise Manager Scheduler Jobs page, find the `MY_LWT_JOB`, and view the attributes.
- a) Log into Enterprise Manager as the `SYSTEM` user with the `oracle_4U` password.

Practice 17-2: Creating Lightweight Scheduler Jobs (continued)

* User Name
 * Password
 Connect As

- b) Navigate to the Scheduler Jobs page. Then click the History tab.
- c) View the history of MY_LWT_JOB.

All Running History					
Purge All Logs					
View Job Status Purge Log View Job Definition					
Previous 1-25 of 156 Next 25					
Select	Status	Name	Schema	Completion Date	Run Duration (minutes)
<input checked="" type="radio"/>	✓	MY_LWT_JOB	SYSTEM	Jul 31, 2009 4:02:48 PM +07:00	0.0

- d) Click the Job Name to view the job attributes.

General		Schedule	Options
Name	MY_LWT_JOB	Repeat By Days	Raise Events None
Schema	SYSTEM	Interval (Days) 2	Maximum Run Duration None (minutes)
Enabled	TRUE	Repeat Time	Priority
Description	None	Available to Start Jul 31, 2009 4:02:48 PM Etc/GMT-7	Schedule Limit (minutes) None
Logging Level	No logging (OFF)	Not Available	Maximum Runs None
Job Class	DEFAULT_JOB_CLASS	After	Maximum Failures None
Auto Drop	TRUE		Job Weight None
Restartable	FALSE		Instance TRUE
Destination			Stickiness <small>For use in RAC. If instance_stickiness is set to TRUE, the Oracle Scheduler will attempt to execute the job on the same instance as the previous run</small>
Credential Name			

- e) Click OK.
- 5) On the Scheduler Jobs, All page, delete the MY_LWT_JOB job
- a) Navigate to the Scheduler Jobs, All page, select the MY_LWT_JOB job and click Delete.

Practice 17-2: Creating Lightweight Scheduler Jobs (continued)

All Running History									
View Job Definition Edit Job Definition Delete Run Now Create Like									
Select	Name	Schema	Scheduled Date	Last Run Date	Last Run Status	Enabled	Job Class	Previous Runs	
<input type="radio"/>	MGMT_STATS_CONFIG_JOB	ORACLE_OCM	Aug 1, 2009 1:01:01 AM -07:00	Not Scheduled	SCHEDULED	✓	DEFAULT_JOB_CLASS	0	
<input type="radio"/>	MGMT_CONFIG_JOB	ORACLE_OCM	MAINTENANCE_WINDOW_GROUP	Jul 30, 2009 8:00:07 AM -07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	1	
<input type="radio"/>	RLM\$SCHDNEGACTION	EXFSYS	Jul 31, 2009 4:35:03 PM +07:00	Jul 31, 2009 3:37:27 PM +07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	7	
<input type="radio"/>	RLM\$EVTCLANUP	EXFSYS	Jul 31, 2009 2:11:30 AM -07:00	Jul 31, 2009 1:11:30 AM -07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	7	
<input checked="" type="radio"/>	MY_LWT_JOB	SYSTEM	Aug 2, 2009 4:02:48 PM +07:00	Jul 31, 2009 4:02:48 PM +07:00	SCHEDULED	✓	DEFAULT_JOB_CLASS	1	

b) On the Confirmation page, select “Drop the job and any running instance.” Click Yes.

Confirmation

Are you sure you want to delete Job SYSTEM.MY_LWT_JOB?

☒ Drop the job and stop any running instance.
 ☐ If there is a running instance of this job, it will not be dropped.

Practice 17-3: Monitoring the Scheduler

Background: Because your job tasks are regularly increasing, you decide to automate routine tasks. You first monitor existing scheduler elements, and then you create scheduler components and test them.

In this practice, use Enterprise Manager Database Control to define and monitor the Scheduler and automate tasks. Click Show SQL regularly to review all statements that are new to you.

Log in as the SYS user (with oracle_4U password, connect as SYSDBA) or as HR user (with oracle_4U password, connect as Normal), as indicated. Perform the necessary tasks either through Enterprise Manager Database Control or through SQL*Plus. All scripts for this practice are in the /home/oracle/labs directory.

- 1) Log in to Enterprise Manager Database Control as the SYS user with the oracle_4U password, connect as SYSDBA, and check the following roles for the HR user:

- CONNECT role
- RESOURCE role
- DBA role

Because you are going to use the HR user to administer jobs through Database Control, you need to make sure that HR is registered as a possible administrator.

- a) In Enterprise Manager, navigate to Server > Users (in the Security section).
- b) On the Users page, select the HR user and click Edit.
- c) On the Edit User page, click the Roles tab.

ORACLE Enterprise Manager 11g Database Control

Database Instance: orcl.example.com > Users > Logged in As SYS

Edit User: HR

Actions: Create Like [v] Go Show SQL Revert Apply

General Roles System Privileges Object Privileges Quotas Consumer Group Privileges Proxy Users

Edit List

Role	Admin Option	Default
CONNECT	<input type="checkbox"/>	<input checked="" type="checkbox"/>
DBA	<input type="checkbox"/>	<input checked="" type="checkbox"/>
RESOURCE	<input type="checkbox"/>	<input checked="" type="checkbox"/>

- d) If the roles are not yet selected, then click the Edit List button on the right side of the page. On the Modify Roles page, make sure that the DBA, CONNECT, and RESOURCE roles are selected. Click OK, then click Apply.
- e) Click the Setup link in the upper-right region of the page.

Practice 17-3: Monitoring the Scheduler (continued)

ORACLE Enterprise Manager 11g Database Control

Setup Preferences Help Logout

Enterprise Manager Configuration | Management Services and Repository | Agents

Overview of Setup

Setup allows you to access general Enterprise Manager configuration and system monitoring functions. Depending on the system and target privileges that have been granted, you can access setup functions for the following administrative area(s):

Enterprise Manager Configuration: lets you perform administrative operations such as adding new Administrators, managing Monitoring Templates, and establishing Blackouts. Your administrator privileges determine which configuration operations are displayed. See [Introduction to Setting Up Enterprise Manager](#) for more information.

Management Services and Repository: lets you monitor system performance and access diagnostic information for the Oracle Management Services and Management Repository. You can view:

- The overall health of Enterprise Manager.
- The status and performance of the Repository DBMS Jobs that handle Enterprise Manager's maintenance and monitoring functionality.
- The health and configuration of all Management Services.
- Performance errors for the DBMS jobs and Management Service components (Repository Metrics).

See [Monitoring The Management System](#) for more information.

Agents: lets you view general configuration, status, and performance information of the Oracle Management Agents that have been installed and configured for managed hosts. See [About Oracle Management Agents](#) for more information.

Only Super Administrators can access Setup functions for all administrative areas.

f) On the Enterprise Manager Configuration page, click the Administrators link.

Administrators

Administrators are database users who can login to Enterprise Manager to perform management tasks like set Blackouts, email notification schedules.

Page Refreshed Jul 31, 2009 4:51:05 PM GMT+07:00 Refresh

Search Go

View Edit Subscribe to Rules Delete Create

Select	Name	Access
<input checked="" type="radio"/>	SYS	Super Administrator
<input type="radio"/>	SYSMAN	Repository Owner
<input type="radio"/>	SYSTEM	Super Administrator

g) On the Administrators page, click the Create button.

Practice 17-3: Monitoring the Scheduler (continued)

Create Administrator: Properties

* Name:

E-mail Address:

Specify one or more e-mail addresses separated by a comma or space. If you are entering these for the first time, they will be used to create a default 24x7 notification schedule for this Administrator.

Administrator Privilege:

☒ Grant SELECT_CATALOG_ROLE

[Cancel](#) [Review](#)

h) On the Create Administrators: Properties page, enter HR as Name, ensure that the Grant SELECT_CATALOG_ROLE is selected and click Review.

i) On the Create Administrator HR: Review page, click the Finish button.

You should receive a success message

ORACLE Enterprise Manager 11g Database Control

Setup Preferences Help Logout

Enterprise Manager Configuration | Management Services and Repository | Agents

Overview of Setup

Administrators

Notification Methods

Patching Setup

Blackouts

Management Pack Access

Monitoring Templates

Corrective Action Library

Confirmation
Administrator HR was created successfully

Administrators
Administrators are database users who can login to Enterprise Manager to perform management tasks like set Blackouts, email notification schedules.

Page Refreshed Jul 31, 2009 4:55:16 PM GMT+07:00 [Refresh](#)

Search [Go](#)

[View](#) [Edit](#) [Subscribe to Rules](#) [Delete](#) | [Create](#)

Select Name	Access
<input checked="" type="radio"/> HR	Administrator
<input type="radio"/> SYS	Super Administrator
<input type="radio"/> SYSMAN	Repository Owner
<input type="radio"/> SYSTEM	Super Administrator

j) Click the Logout link at the upper-right corner of the page.

2) Log in to Enterprise Manager Database Control as the HR user. On the Server tabbed page, click the Jobs link in the Database Scheduler region. Are there any jobs?

a) Click the Login button to log in as the HR user.

b) Enter HR as username, oracle_4U as password, Connect As Normal, and click Login.

c) In Enterprise Manager, navigate to Server > Jobs.

Practice 17-3: Monitoring the Scheduler (continued)

Database Instance: orcl.example.com > Logged in As HR

Scheduler Jobs Page Refreshed Jul 31, 2009 4:58:29 PM GMT+07:00 [Refresh](#) [Create](#)

[All](#) [Running](#) [History](#)

[View Job Definition](#) [Edit Job Definition](#) [Delete](#) [Run Now](#) [Create Like](#)

Select	Name	Schema	Scheduled Date	Last Run Date	Last Run Status	Enabled	Job Class	Previous Runs
<input checked="" type="radio"/>	MGMT_STATS_CONFIG_JOB	ORACLE_OCM	Aug 1, 2009 1:01:01 AM -07:00	Not Scheduled	SCHEDULED	<input checked="" type="checkbox"/>	DEFAULT_JOB_CLASS	0
<input type="radio"/>	MGMT_CONFIG_JOB	ORACLE_OCM	MAINTENANCE_WINDOW_GROUP	Jul 30, 2009 8:00:07 AM -07:00	SCHEDULED	<input checked="" type="checkbox"/>	DEFAULT_JOB_CLASS	1
<input type="radio"/>	RLM\$SCHDNEGACTION	EXFSYS	Jul 31, 2009 5:32:39 PM +07:00	Jul 31, 2009 4:35:03 PM +07:00	SCHEDULED	<input checked="" type="checkbox"/>	DEFAULT_JOB_CLASS	8
<input type="radio"/>	RLM\$EVTCLANUP	EXFSYS	Jul 31, 2009 3:11:30 AM -07:00	Jul 31, 2009 2:11:30 AM -07:00	SCHEDULED	<input checked="" type="checkbox"/>	DEFAULT_JOB_CLASS	8

[All](#) [Running](#) [History](#)

Related Links

[Chains](#) [Global Attributes](#) [Job Classes](#)
[Programs](#) [Schedules](#) [Window Groups](#)
[Windows](#)

Question: Are there any jobs?

Possible Answer: There are some jobs.

- Click Programs in the Related Links section.

Database Instance: orcl.example.com > Logged in As HR

Scheduler Programs [Create](#)

Following are the programs that define what are to be executed in the jobs.

[View](#) [Edit](#) [Delete](#) [Create Like](#) [Go](#)

Select	Name	Schema	Enabled	Type	Description
<input checked="" type="radio"/>	HS_PARALLEL_SAMPLING	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	
<input type="radio"/>	JDM_BUILD_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for building a mining model using JDM API
<input type="radio"/>	JDM_EXPLAIN_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for explain using JDM API
<input type="radio"/>	JDM_EXPORT_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for exporting a mining model using JDM API
<input type="radio"/>	JDM_IMPORT_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for importing a mining model using JDM API
<input type="radio"/>	JDM_PREDICT_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for predict using JDM API
<input type="radio"/>	JDM_PROFILE_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for profile using JDM API
<input type="radio"/>	JDM_SQL_APPLY_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for applying a mining model using JDM API
<input type="radio"/>	JDM_TEST_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for testing a mining model using JDM API
<input type="radio"/>	JDM_XFORM_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for transformation using JDM API
<input type="radio"/>	JDM_XFORM_SEQ_PROGRAM	SYS	<input checked="" type="checkbox"/>	STORED_PROCEDURE	Used for transformation sequence task using JDM API
<input type="radio"/>	PROG_1	SYSTEM	<input checked="" type="checkbox"/>	PLSQL_BLOCK	Insert a timestamp into the test_log

[View](#) [Edit](#) [Delete](#) [Create Like](#) [Go](#)

Related Links

[Chains](#) [Global Attributes](#) [Job Classes](#)
[Jobs](#) [Schedules](#) [Window Groups](#)
[Windows](#)

Question: Are there any existing programs?

Practice 17-3: Monitoring the Scheduler (continued)

Answer: There are some existing programs.

- 4) Click Schedules in the Related Links section.

Database Instance: orcl.example.com > Logged in As HR

Scheduler Schedules Page Refreshed Jul 31, 2009 5:03:10 PM GMT+07:00 [Refresh](#) [Create](#)

[Edit](#) [View](#) [Delete](#) [Create Like](#)

Select	Name	Schema	Start Date	End Date	Description
<input checked="" type="radio"/>	BSLN_MAINTAIN_STATS_SCHED	SYS	Jul 12, 2009 12:00:00 AM -07:00		Pre-defined schedule for computing moving window baseline statistics
<input type="radio"/>	FILE_WATCHER_SCHEDULE	SYS			
<input type="radio"/>	DAILY_PURGE_SCHEDULE	SYS			

Related Links

[Chains](#)
[Jobs](#)
[Windows](#)

[Global Attributes](#)
[Programs](#)

[Job Classes](#)
[Window Groups](#)

Question: Are there any existing schedules?

Answer: There are three schedules: BSLN_MAINTAIN_STATS_SCHED, FILE_WATCHER_SCHEDULE and DAILY_PURGE_SCHEDULE.

- 5) Click Windows in the Related Links section. Review the Scheduler Windows page in Enterprise Manager. Are there any existing windows? Which resource plan is associated with each window?

Database Instance: orcl.example.com > Logged in As HR

Scheduler Windows [Create](#)

Following are the system windows that specify resource usage limits based on time-duration windows.

[View](#) [Edit](#) [Delete](#) [Create Like](#) [Go](#)

Select	Name	Resource Plan	Enabled	Next Open Date	End Date	Duration (min)	Active	Description
<input checked="" type="radio"/>	WEEKNIGHT_WINDOW					480	FALSE	Weeknight window - for compatibility only
<input type="radio"/>	WEEKEND_WINDOW					2880	FALSE	Weekend window - for compatibility only
<input type="radio"/>	FRIDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			240	FALSE	Friday window for maintenance tasks
<input type="radio"/>	SATURDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			1200	FALSE	Saturday window for maintenance tasks
<input type="radio"/>	SUNDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			1200	FALSE	Sunday window for maintenance tasks
<input type="radio"/>	MONDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			240	FALSE	Monday window for maintenance tasks
<input type="radio"/>	TUESDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			240	FALSE	Tuesday window for maintenance tasks
<input type="radio"/>	WEDNESDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			240	FALSE	Wednesday window for maintenance tasks
<input type="radio"/>	THURSDAY_WINDOW	DEFAULT_MAINTENANCE_PLAN	✓			240	FALSE	Thursday window for maintenance tasks

Practice 17-3: Monitoring the Scheduler (continued)

Question 1: Are there any existing windows? Are any enabled?

Answer: There are several windows. All are enabled except WEEKNIGHT_WINDOW and WEEKEND_WINDOW.

- 6) Click the MONDAY_WINDOW link. Answer the questions, then click OK.

The screenshot shows the Oracle Enterprise Manager interface for configuring a scheduler window. The breadcrumb trail is "Database Instance: orcl.example.com > Scheduler Windows > View Window: MONDAY_WINDOW". The user is logged in as "As HR". The window configuration details are as follows:

Property	Value
Name	MONDAY_WINDOW
Resource Plan	DEFAULT_MAINTENANCE_PLAN
Enabled	TRUE
Priority	LOW
Description	Monday window for maintenance tasks

Below the configuration details is the "Schedule" section:

Property	Value
Repeat	By Weeks
Interval (Weeks)	1
Days of Week	Monday
Repeat Time	Hour:10 Minute:00 Second:00 PM
Duration (min)	4 hour(s) 0 minute(s)
Available to Start	
Not Available After	

Buttons for "Edit", "OK", and "Cancel" are located in the top right corner. The "Hour:10" and "4 hour(s)" values are highlighted with red and blue boxes, respectively.

Question 1: At which time does this window open?

Possible Answer: 10 PM

Question 2: For how long does it stay open?

Possible Answer: for 4 hours

- 7) Click Job Classes in the Related Links section and review them.

Practice 17-3: Monitoring the Scheduler (continued)

Database Instance: [orcl.example.com](#) > Scheduler Job Classes Logged in As HR

Page Refreshed Jul 31, 2009 5:17:06 PM GMT+07:00 [Refresh](#)

A job class defines the resource consumer group in which a job will run. Using a resource plan in a window, a DBA can allocate resources among different resource groups and between different job classes. [Create](#)

[Edit](#) [View](#) [Delete](#) [Create Like](#)

Select	Name	Logging Level	Log Retention Period (Days)	Resource Consumer Group	Service Name	Description
<input checked="" type="radio"/>	DEFAULT_JOB_CLASS	RUNS				This is the default job class.
<input type="radio"/>	DBMS_JOB\$	OFF				This is the job class for jobs created through DBMS_JOB.
<input type="radio"/>	ORA\$AT_JCURG_OS	FULL	1000000	ORA\$AUTOTASK_URGENT_GROUP		auto optimizer stats collection
<input type="radio"/>	ORA\$AT_JCNRM_OS	FULL	1000000	ORA\$AUTOTASK_STATS_GROUP		auto optimizer stats collection
<input type="radio"/>	ORA\$AT_JCMED_OS	FULL	1000000	ORA\$AUTOTASK_MEDIUM_GROUP		auto optimizer stats collection
<input type="radio"/>	ORA\$AT_JCURG_SA	FULL	1000000	ORA\$AUTOTASK_URGENT_GROUP		auto space advisor
<input type="radio"/>	ORA\$AT_JCNRM_SA	FULL	1000000	ORA\$AUTOTASK_SPACE_GROUP		auto space advisor
<input type="radio"/>	ORA\$AT_JCMED_SA	FULL	1000000	ORA\$AUTOTASK_MEDIUM_GROUP		auto space advisor
<input type="radio"/>	ORA\$AT_JCURG_SQ	FULL	1000000	ORA\$AUTOTASK_URGENT_GROUP		sql tuning advisor
<input type="radio"/>	ORA\$AT_JCNRM_SQ	FULL	1000000	ORA\$AUTOTASK_SQL_GROUP		sql tuning advisor
<input type="radio"/>	ORA\$AT_JCMED_SQ	FULL	1000000	ORA\$AUTOTASK_MEDIUM_GROUP		sql tuning advisor
<input type="radio"/>	AQ\$_PROPAGATION_JOB_CLASS	RUNS				Default job class for AQ\$

Question 1: Are there any existing job classes?

Possible Answer: There are many job classes.

Question 2: Which resource consumer group is associated with the DEFAULT_JOB_CLASS job class?

Possible Answer: None.

- 8) On the Scheduler Job classes page, click the ORA\$AT_JCURG_OS link.

Database Instance: [orcl.example.com](#) > Scheduler Job Classes > View Job Class: [ORA\\$AT_JCURG_OS](#) Logged in As HR

[Edit](#) [OK](#)

Name **ORA\$AT_JCURG_OS**

Logging Level **Log everything (FULL)**

Log Retention Period (Days) **1000000**

Resource Consumer Group **ORA\$AUTOTASK_URGENT_GROUP**

Service Name

Description **auto optimizer stats collection**

[OK](#)

Question 1: Which resource consumer group is associated with the job class?

Possible Answer: ORA\$AT_JCURG_OS is associated with ORA\$AUTOTASK_URGENT_GROUP.

Practice 17-3: Monitoring the Scheduler (continued)

Question 2: For which task is this job class used?

Possible Answer: For automatic optimizer statistics collection

- 9) Click OK, and then exit Enterprise Manager.

Practices for Lesson 18

Background: To prepare for an upcoming merger, you want to set the warning and critical thresholds to a lower value than the default. Ensure that you receive early warnings to give you more time to react. When you finish your test case, drop the tablespace that you used.

Practice 18-1: Managing Storage

Access the `orcl` database as the SYS user (with the `oracle_4U` password, connect as SYSDBA) and perform the necessary tasks through Enterprise Manager Database Control or through SQL*Plus. All scripts for this practice are in the `/home/oracle/labs` directory.

- 1) Using the `DBMS_SERVER_ALERT.SET_THRESHOLD` procedure, reset the databasewide threshold values for the Tablespace Space Usage metric. Connect to a SQL*Plus session and execute the following procedure:

```
$ . oraenv
ORACLE_SID = [orcl] ? orcl
$ cd ~/labs
$ sqlplus / as sysdba
SQL> exec DBMS_SERVER_ALERT.SET_THRESHOLD(-
dbms_server_alert.tablespace_pct_full,-
NULL,NULL,NULL,NULL,1,1,NULL,-
dbms_server_alert.object_type_tablespace,NULL);
> > >
PL/SQL procedure successfully completed.

SQL>
```

- 2) From your SQL*Plus session, check the databasewide threshold values for the Tablespace Space Usage metric using the following command:

```
SQL> SELECT warning_value,critical_value
FROM   dba_thresholds
WHERE  metrics_name='Tablespace Space Usage'
AND    object_name IS NULL;

WARNING_VALUE
-----
CRITICAL_VALUE
-----
85
97
```

- 3) Create a new tablespace called `TBSALERT` with a 120 MB file called `tbsalert.dbf`. Make sure that this tablespace is locally managed and uses Automatic Segment Space Management. Do *not* make it autoextensible, and do *not* specify any thresholds for this tablespace. Use Enterprise Manager Database Control to create it. If this tablespace already exists in your database, drop it first, including its files.
 - a) Logged into Enterprise Manager as the SYS user, navigate to Server > Tablespaces.

Practice 18-1: Managing Storage (continued)

Tablespaces
Object Type: Tablespace

Search
Enter an object name to filter the data that is displayed in your results set.
Object Name
By default, the search returns all uppercase matches beginning with the string you entered. To run an exact or case-sensitive match, double quote the search string. You can use the wildcard symbol (%) in a double quoted string.

Selection Mode Single

Actions Add Datafile

Select	Name	Allocated Size(MB)	Space Used(MB)	Allocated Space Used(%)	Auto Extend	Allocated Free Space(MB)	Status	Datafiles	Type	Extent Management	Segment Management
<input checked="" type="radio"/>	EXAMPLE	100.0	78.8	<div><div></div></div> 78.8	YES	21.2	✓	1	PERMANENT	LOCAL	AUTO
<input type="radio"/>	SYSAUX	590.0	556.6	<div><div></div></div> 94.3	YES	33.4	✓	1	PERMANENT	LOCAL	AUTO
<input type="radio"/>	SYSTEM	680.0	675.6	<div><div></div></div> 99.3	YES	4.4	✓	1	PERMANENT	LOCAL	MANUAL
<input type="radio"/>	TEMP	28.0	0.0	<div><div></div></div> 0.0	YES	28.0	✓	1	TEMPORARY	LOCAL	MANUAL
<input type="radio"/>	UNDOTBS1	105.0	8.6	<div><div></div></div> 8.2	YES	96.4	✓	1	UNDO	LOCAL	MANUAL
<input type="radio"/>	USERS	7.5	4.1	<div><div></div></div> 54.2	YES	3.4	✓	1	PERMANENT	LOCAL	AUTO

Total Allocated Size (GB) **1.48** ✓ Online ✗ Offline Read Only
Total Used (GB) **1.29**
Total Allocated Free Space (GB) **0.18**

- Click the Create button.
- Enter TBSALERT as the name, and click the Add button in the Datafiles region.
- Enter or confirm the following values, then click Continue

Name	Value
Storage Type	Automatic Storage Management
Disk Group	DATA
Template	DATAFILE
Alias name	tbsalert
File Size	120 MB
Reuse Existing File	TRUE
AUTOEXTEND	FALSE

Practice 18-1: Managing Storage (continued)

Database Instance: orcl.example.com > Tablespaces > Logged in As SYS

Add Datafile

Cancel Continue

Storage Type: Automatic Storage Management

* DiskGroup: DATA

Template: DATAFILE

Alias Directory:

Alias Name: tbsalert

Tablespace: TBSALERT

File Size: 120 MB

☒ Reuse Existing File

Storage

☐ Automatically extend datafile when full (AUTOEXTEND)

Increment: KB

Maximum File Size: ☒ Unlimited ☐ Value MB

TIP Changes made on this page will NOT take effect until you click "OK" button on the Tablespace page.

e) Click Continue

Create Tablespace

Show SQL Cancel OK

Information
Modification to the datafile will not take effect until you click "OK" button.

General Storage

* Name: TBSALERT

Extent Management	Type	Status
<input checked="" type="radio"/> Locally Managed	<input checked="" type="radio"/> Permanent	<input checked="" type="radio"/> Read Write
<input type="radio"/> Dictionary Managed	<input type="checkbox"/> Set as default permanent tablespace	<input type="radio"/> Read Only
	<input type="checkbox"/> Encryption Encryption Options	<input type="radio"/> Offline

f) On the Create tablespace page, click Show SQL.

Database Instance: orcl.example.com > Tablespaces > Create Tablespace > Logged in As SYS

Show SQL

Return

```
CREATE SMALLFILE TABLESPACE "TBSALERT" DATAFILE '+DATA(DATAFILE)/tbsalert' SIZE 120M REUSE LOGGING EXTENT MANAGEMENT LOCAL SEGMENT SPACE MANAGEMENT AUTO
```

g) Review the SQL and then click Return.

Practice 18-1: Managing Storage (continued)

h) Click OK to create the tablespace. You should receive a success message.

Select	Name	Allocated Size(MB)	Space Used(MB)	Allocated Space Used(%)	Auto Extend	Allocated Free Space(MB)	Status	Datafiles	Type	Extent Management	Segment Management
<input checked="" type="radio"/>	EXAMPLE	100.0	78.8	78.8	YES	21.2	✓	1	PERMANENT	LOCAL	AUTO
<input type="radio"/>	SYSAUX	590.0	556.6	94.3	YES	33.4	✓	1	PERMANENT	LOCAL	AUTO
<input type="radio"/>	SYSTEM	680.0	675.6	99.3	YES	4.4	✓	1	PERMANENT	LOCAL	MANUAL
<input type="radio"/>	TBSALERT	120.0	1.0	0.8	NO	119.0	✓	1	PERMANENT	LOCAL	AUTO
<input type="radio"/>	TEMP	28.0	0.0	0.0	YES	28.0	✓	1	TEMPORARY	LOCAL	MANUAL
<input type="radio"/>	UNDOTBS1	105.0	8.6	8.2	YES	96.4	✓	1	UNDO	LOCAL	MANUAL
<input type="radio"/>	USERS	7.5	4.1	54.2	YES	3.4	✓	1	PERMANENT	LOCAL	AUTO

- 4) In Enterprise Manager, change the Tablespace Space Usage thresholds of the TBSALERT tablespace. Set its warning level to 55 percent and its critical level to 70 percent.

<div>EditViewDeleteActionsAdd DatafileGo</div>							
<div>Edit</div>							
Select	Name ▲	Allocated Size(MB)	Space Used(MB)	Allocated Space Used(%)	Auto Extend	Allocated Free Space(MB)	Status
<input type="radio"/>	EXAMPLE	100.0	78.8	<div><div></div></div> 78.8	YES	21.2	✓
<input type="radio"/>	SYSAUX	590.0	558.0	<div><div></div></div> 94.6	YES	32.0	✓
<input type="radio"/>	SYSTEM	680.0	675.6	<div><div></div></div> 99.4	YES	4.4	✓
<input checked="" type="radio"/>	TBSALERT	120.0	1.0	<div><div></div></div> 0.8	NO	119.0	✓

- a) On the Tablespace page, select TBSALERT, click Edit, and then click Thresholds.

Edit Tablespace: TBSALERT

Actions Add Datafile Go Show SQL Revert Apply

General Storage **Thresholds**

Available Space (MB) 120.00
Space Used (MB) 1.00

Space Used (%) 0.83
Available Free Space (MB) 119.00

Tablespace Full Metric Thresholds

Monitor the fullness of the tablespace using either of the metrics below.

Space Used (%)

A warning or critical alert will be generated if the percentage of space used exceeds the corresponding threshold.

☐ Use Database Default Thresholds **Modify**
Warning (%) 85
Critical (%) 97

☒ Specify Thresholds
Warning (%) 55
Critical (%) 70

☐ Disable Thresholds

Free Space (MB)

A warning or critical alert will be generated if the remaining free space falls below the corresponding threshold. This metric is especially useful for large tablespaces.

☒ Use Database Default Thresholds **Modify**
Warning (MB) Not Defined
Critical (MB) Not Defined

☐ Specify Thresholds
Warning (MB)
Critical (MB)

☐ Disable Thresholds

Practice 18-1: Managing Storage (continued)

- b) Select Specify Thresholds, and enter 55 as Warning (%) and 70 as Critical (%) under the Space Used section. Then click Show SQL.

```
Database Instance: orcl.example.com > Tablespaces > Edit Tablespace: TBSALERT > Logged in As SYS
Show SQL
Return
BEGIN DEMS_SERVER_ALERT.SET_THRESHOLD(9000,4,'55',4,'70',1,1,NULL,5,'TBSALERT'); END;
```

- c) Review the statement and click Return.
- d) On the Edit Tablespace: TBSALERT, click Apply to modify the threshold values.

You should receive a success message.

- 5) Return to your SQL*Plus session and check the new threshold values for the TBSALERT tablespace. In your SQL*Plus session, enter:

```
SQL> select warning_value,critical_value
from dba_thresholds
where metrics_name='Tablespace Space Usage' and
object_name='TBSALERT';
```

```
WARNING_VALUE
```

```
-----
```

```
CRITICAL_VALUE
```

```
-----
```

```
55
```

```
70
```

- 6) In your SQL*Plus session, query the reason and resolution columns from DBA_ALERT_HISTORY for the TBSALERT tablespace.

```
SQL> select reason,resolution
from dba_alert_history
where object_name='TBSALERT';
```

The result should be (if you are repeating this practice, look at the last row):

```
REASON
```

```
RESOLUT
```

```
-----
```

```
---
```

```
Threshold is updated on metrics "Tablespace Space Usage"
cleared
```

```
SQL> exit
```

```
$
```

Practice 18-1: Managing Storage (continued)

- 7) From the labs directory, review and execute the `seg_advsr_setup.sh` script that creates and populates new tables in the TBSALERT tablespace.

```
$ cd ~/labs
$ cat seg_advsr_setup.sh

#!/bin/sh
# For training only, execute as oracle OS user

sqlplus /nolog <<EOF
connect / as sysdba
alter system set disk_asynch_io = FALSE scope = spfile;
shutdown immediate;
startup
set echo on
create table employees1 tablespace tbsalert as select * from
hr.employees;
create table employees2 tablespace tbsalert as select * from
hr.employees;
create table employees3 tablespace tbsalert as select * from
hr.employees;
create table employees4 tablespace tbsalert as select * from
hr.employees;
create table employees5 tablespace tbsalert as select * from
hr.employees;

alter table employees1 enable row movement;
alter table employees2 enable row movement;
alter table employees3 enable row movement;
alter table employees4 enable row movement;
alter table employees5 enable row movement;

BEGIN
FOR i in 1..10 LOOP
    insert into employees1 select * from employees1;
    insert into employees2 select * from employees2;
    insert into employees3 select * from employees3;
    insert into employees4 select * from employees4;
    insert into employees5 select * from employees5;
    commit;
END LOOP;
END;
/
insert into employees1 select * from employees1;
insert into employees2 select * from employees2;
insert into employees3 select * from employees3;
commit;
exit
EOF
$
```

```
$ ./seg_advsr_setup.sh
```

```
SQL> Connected.
SQL>
System altered.
```

Practice 18-1: Managing Storage (continued)

```
SQL> Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> ORACLE instance started.

Total System Global Area  481259520 bytes
Fixed Size                  1337324 bytes
Variable Size              385878036 bytes
Database Buffers           88080384 bytes
Redo Buffers                5963776 bytes
Database mounted.
Database opened.
SQL> SQL>
Table created.
SQL>
Table created.
SQL>
Table created.
SQL>
Table created.
SQL>
Table created.
SQL> SQL>
Table altered.
SQL>
Table altered.
SQL>
Table altered.
SQL>
Table altered.
SQL> SQL>  2      3      4      5      6      7      8      9     10     11
PL/SQL procedure successfully completed.
SQL>
109568 rows created.
SQL>
109568 rows created.
SQL>
109568 rows created.
SQL>
Commit complete.
SQL>
```

- 8) Check the fullness level of the TBSALERT tablespace by using Database Control or SQL*Plus. The current level should be around 60%. Wait a few minutes and check that the warning level is reached for the TBSALERT tablespace. *(If you are too fast and receive errors, just use your browser's Refresh button, or select your destination again.)*

a) Logged into SQL*Plus as the SYS user, enter:

```
$ sqlplus / as sysdba
```

Practice 18-1: Managing Storage (continued)

```
SQL> select sum(bytes) *100 /125829120
      from dba_extents
      where tablespace_name='TBSALERT';

SUM(BYTES)*100/125829120
-----
                        60

SQL>
```

b) Enter the following query. Your results should be similar to the following:





```
SQL> select reason
      from dba_outstanding_alerts
      where object_name='TBSALERT';

REASON
-----
Tablespace [TBSALERT] is [60 percent] full



SQL>
```

Note: If your result is: no rows selected, wait a little longer and repeat the query.

c) In Enterprise Manager on the Tablespaces page, see Used (%).

Select	Name	Allocated Size(MB)	Space Used(MB)	Allocated Space Used(%)	Auto Extend	Allocated Free Space(MB)	Status
<input checked="" type="radio"/>	EXAMPLE	100.0	78.8	 78.8	YES	21.2	✓
<input type="radio"/>	SYSAUX	590.0	556.6	 94.3	YES	33.4	✓
<input type="radio"/>	SYSTEM	680.0	675.6	 99.3	YES	4.4	✓
<input type="radio"/>	TBSALERT	120.0	73.0	 60.8	NO	47.0	✓

d) Navigate to the Database home page. You should see the new alert in the Space Summary section. It might take several minutes for the alert to appear.

Space Summary	
Database Size (GB)	1.465
Problem Tablespaces 	1
Segment Advisor Recommendations	0
Policy Violations 	0
Dump Area Used (%)	87

9) In your SQL*Plus session, execute the inserts below to add more data to TBSALERT. Wait a few moments and view the critical level in both the database and Database Control. Verify that TBSALERT fullness is around 75%.

a) Execute the following commands:

Practice 18-1: Managing Storage (continued)

```
SQL> insert into employees4 select * from employees4;
109568 rows created.
SQL> commit;
SQL> insert into employees5 select * from employees5;
109568 rows created.
SQL> commit;
SQL>
```

- b) Wait a few minutes and view the critical level in both the database and Database Control. Verify that TBSALERT fullness is around 75%. In SQL*Plus, enter:

```
SQL> select sum(bytes) *100 /125829120
from dba_extents
where tablespace_name='TBSALERT';














SUM(BYTES)*100/125829120
-----
                          75
```

- c) Check the outstanding alerts. You may need to wait a few minutes.

```
SQL> select reason, message_level
from dba_outstanding_alerts
where object_name='TBSALERT';

REASON                                     MESSAGE_LEVEL
-----
Tablespace [TBSALERT] is [75 percent] full      1
```

- d) In Enterprise Manager, navigate to Server > Tablespaces page, and review Used (%).

Select	Name 	Allocated Size(MB)	Space Used(MB)	Allocated Space Used(%)	Auto Extend	Allocated Free Space(MB)	Status
	EXAMPLE	100.0	78.8	 78.8	YES	21.2	
	SYSAUX	590.0	558.4	 94.6	YES	31.6	
	SYSTEM	680.0	675.6	 99.4	YES	4.4	
	TBSALERT	120.0	91.0	 75.8	NO	29.0	

- e) Navigate to the Database home page. You should see the new alert in the Space Summary region. It will take several minutes for the change in status to take effect. Note the red flag instead of the yellow one.

Practice 18-1: Managing Storage (continued)

Diagnostic Summary		Space Summary		High Availability	
ADDMM Findings		Database Size (GB)	1.465	Console Oracle Restart	Enabled
Alert Log		Problem Tablespaces	✗ 1	Instance Recovery Time (sec)	16
Active Incidents		Segment Advisor Recommendations	0	Last Backup	✗ Jul 30, 2009 9:26:05 PM
Key SQL Profiles		Policy Violations	✓ 0	Usable Flash Recovery Area (%)	74.32
Database Instance Health		Dump Area Used (%)	87	Flashback Database Logging	Disabled
Alerts					
Category		All		Go	
Severity		Critical		✗ 1	
Category		Warning		! 1	
Severity	Category	Name	Impact	Message	Alert Triggered
✗	Tablespaces Full	Tablespace Space Used (%)		Tablespace TBSALERT is 75 percent full	Jul 31, 2009 10:04:17 PM


- 10) In your SQL*Plus session, execute the following delete statements to delete rows from tables in TBSALERT. These statements will take several minutes to complete. Then exit your SQL*Plus session.

```
SQL> delete employees1;
219136 rows deleted.
SQL> commit;
Commit complete.
SQL> delete employees2;
219136 rows deleted.
SQL> commit;
Commit complete.
SQL> delete employees3;
219136 rows deleted
SQL> commit;
Commit complete.
SQL> exit
$
```

- 11) Now, run the Segment Advisor for the TBSALERT tablespace in Enterprise Manager. Make sure that you run the Advisor in Comprehensive mode without time limitation. Accept and implement its recommendations. After the recommendations have been implemented, check whether the fullness level of TBSALERT is below 55%.

- a) From the Database home page, select Advisor Central under Related Links and then click Segment Advisor.

Practice 18-1: Managing Storage (continued)



The screenshot shows the 'Segment Advisor: Scope' page in Oracle Database. At the top, there is a progress bar with four steps: Scope (selected), Objects, Schedule, and Review. Below the progress bar, the page title is 'Segment Advisor: Scope'. The database is 'orcl.example.com' and the user is 'SYS'. There are buttons for 'Cancel', 'Step 1 of 4', and 'Next'. A section titled 'Automatic Segment Advisor Information' provides details about the Automatic Segment Advisor job. Below this, there is a section for 'Segment Advisor Recommendations' with two radio buttons: 'Tablespaces' (selected) and 'Schema Objects'. An 'Overview' section on the right explains the segment advisor's function.

Scope Objects Schedule Review

Segment Advisor: Scope

Database orcl.example.com Logged In As SYS Cancel Step 1 of 4 Next

Automatic Segment Advisor Information

Beginning in Oracle Database 10.2, Oracle provides an Automatic Segment Advisor job which automatically detects segment issues. Any segment issues that have already been detected can be viewed using the link below.

Segment Advisor Recommendations


You can get advice on shrinking segments for individual schema objects or entire tablespaces.

☒ Tablespaces
☐ Schema Objects

Overview

The segment advisor determines whether objects have unused space that can be released, taking estimated future space requirements into consideration. The estimated future space calculation is based on historical trends.


- On the Segment Advisor: Scope page, select Tablespaces and click Next.
- On the Segment Advisor: Objects page, click Add, select TBSALERT. Click OK and then click Show Advanced Options.
- In the Options section, click Limited and enter 30 for Time Limit (mins)



The screenshot shows the 'Segment Advisor: Tablespaces' page. The database is 'orcl.example.com' and the user is 'SYS'. There are buttons for 'Cancel', 'Back', 'Step 2 of 4', 'Next', 'Submit', and 'Add'. A table lists the tablespaces. The 'TBSALERT' tablespace is selected. Below the table, there is an 'Options' section with a 'Hide Advanced Options' link. The 'Time Limit for Analysis' section has two radio buttons: 'Unlimited' and 'Limited' (selected). The 'Time Limit (mins)' is set to 30. The 'Advisory Results Retention (days)' is set to 30.

Segment Advisor: Tablespaces

Database orcl.example.com Logged In As SYS Cancel Back Step 2 of 4 Next Submit Add

Name	Type	Extent Management	Segment Space Management	Size (MB)	Used (MB)	Used (%)	Remove
TBSALERT	PERMANENT	LOCAL	AUTO	120.00	91.00	75.83	

Options

[Hide Advanced Options](#)

Time Limit for Analysis

☐ Unlimited
☒ Limited

Time Limit (mins)

Advisory Results Retention (days)

- Then click Next.

Practice 18-1: Managing Storage (continued)

Scope Objects **Schedule** Review

Segment Advisor: Schedule

Database **orcl.example.com** Logged In As **SYS** Cancel Back Step 3 of 4 Next Submit

TIP This operation may be resource-intensive and should be scheduled during off-peak hours.

Task Information

* Task Name	SEGMENTADV_5033431
Task Description	Get shrink advice based on object growth trend

Schedule

Schedule Type Standard

Time Zone Etc/GMT-7

Repeating

Repeat Do Not Repeat

Start

☒ Immediately

f) On the Segment Advisor: Schedule page, make sure Immediately is selected. Select your proper timezone and click Next.

g) On the Segment Advisor: Review page, click Show SQL.

```
Create task and objects script
DECLARE
taskname varchar2(100);
taskdesc varchar2(128);
task_id number;
object_id number;
timeLimit varchar2(25);
numDaysToRetain varchar2(25);
objectName varchar2(100);
objectType varchar2(100);

BEGIN
taskname := 'SEGMENTADV_5033431';
taskdesc := 'Get shrink advice based on object growth trend';
numDaysToRetain := '30';
dbms_advisor.create_task('Segment Advisor', ?, taskname, taskdesc
, NULL);
dbms_advisor.create_object(taskname, 'TABLESPACE', 'TBSALERT',
' ', ' ', NULL, object_id);
dbms_advisor.set_task_parameter(taskname, 'RECOMMEND_ALL',
'TRUE');
timeLimit := '1800';
dbms_advisor.set_task_parameter(taskname, 'TIME_LIMIT',
timeLimit);
```

Practice 18-1: Managing Storage (continued)

```
dbms_advisor.set_task_parameter(taskname, 'DAYS_TO_EXPIRE',  
numDaysToRetain);  
  
END;  
  
Execute task script  
DECLARE  
taskname varchar2(100);  
BEGIN  
taskname := 'SEGMENTADV_5033431';  
dbms_advisor.reset_task(taskname);  
dbms_advisor.execute_task(taskname);  
END;
```

h) Review the statements and click Return.

Segment Advisor: Review

Database **orcl.example.com** Logged In As **SYS** [Cancel](#) [Show SQL](#) [Back](#) [Step 4 of 4](#) [Submit](#)

Task Name **SEGMENTADV_5033431**
Task Description **Get shrink advice based on object growth trend**
Time Limit for Analysis (mins) **30**
Advisory Results Retention (days) **30**

Selected Objects

Tablespace	Type
TBSALERT	PERMANENT

i) Back on the Segment Advisor: review page, the Submit button.

j) This takes you back to the Advisor Central page. Click the `SEGMENTADV_XXXXXX` link in the Name column.

k) On the Segment Advisor Task page, click the Recommendation Details button .

Segment Advisor Recommendations

Oracle uses the Automatic Segment Advisor job to detect segment issues regularly within maintenance windows. The following table contains the minimum reclaimable space summary for the evaluated segments in that tablespace. The recommendations come from the most recent runs of automatic and user-scheduled segment advisor jobs. Oracle recommends shrinking, reorganizing or compressing these segments to release unused space. Select the Recommendation Details button to view and implement the recommendations.

View
[All Recommendations](#)

[Recommendation Details](#)

Select	Tablespace	Recommendations	Tablespace Size (MB)	Evaluated Space (%)	Reclaimable Space (MB)	Extent Management	Segment Space Management
<input checked="" type="radio"/>	TBSALERT	3	120.00	75.00	46.70	LOCAL	AUTO

Related Links

Advisor Central	Automated Maintenance Tasks
Run Segment Advisor Manually	Chained Row Analysis
Job Scheduler	

Practice 18-1: Managing Storage (continued)

- l) If needed, click your browser's Refresh button until you see recommendations for the TBSALERT tablespace.
- m) Click Recommendation Details.

Recommendation Details for Tablespace: TBSALERT

View **All Recommendations**

Oracle uses the Automatic Segment Advisor job to detect segment issues regularly within maintenance windows. The following table contains the reclaimable space information for the evaluated segments in the selected tablespace. The recommendations come from the most recent runs of automatic and user-scheduled segment advisor jobs. Oracle recommends shrinking, reorganizing or compressing these segments to release unused space. Select the segment to implement the recommendation.

Schema Recommendation
 Segment Minimum
 Partition Reclaimable
 Space (MB)

[Select All](#) | [Select None](#)

Select	Schema	Segment	Recommendation	Reclaimable Space (MB)	Allocated Space (MB)	Used Space (MB)	Segment Type
<input checked="" type="checkbox"/>	SYS	EMPLOYEES1	<input type="button" value="Shrink"/>	15.57	18.00	2.43	TABLE
<input checked="" type="checkbox"/>	SYS	EMPLOYEES2	<input type="button" value="Shrink"/>	15.57	18.00	2.43	TABLE
<input checked="" type="checkbox"/>	SYS	EMPLOYEES3	<input type="button" value="Shrink"/>	15.57	18.00	2.43	TABLE

- n) Click the Select All link and then click the Shrink button.

Shrink Segment: Options

The shrink operation compacts fragmented space and, optionally, frees the space. The shrink operation will take some time and will be scheduled as a job.

☒ Compact Segments and Release Space
 This will first compact the segments and then release the recovered space to the tablespace. During the short space release phase, any cursors referencing this segment may be invalidated and queries on the segment could be affected.

☐ Compact Segments
 Compacting will compact segment data without releasing the recovered space. After compacting the data, the recovered space can be quickly released by running Compact Segments and Release Space.

- o) On the Shrink Segment: Options page, make sure that you click the "Compact Segments and Release Space" option button. Click Show SQL.

```
alter table "SYS"."EMPLOYEES1" shrink space
alter table "SYS"."EMPLOYEES2" shrink space
alter table "SYS"."EMPLOYEES3" shrink space
```

- p) Review the statements and click Return.

Practice 18-1: Managing Storage (continued)

Shrink Segment: Options

The shrink operation compacts fragmented space and, optionally, frees the space. The shrink operation will take some time and will be scheduled as a job. Show SQL Cancel Implement

☒ **Compact Segments and Release Space**
This will first compact the segments and then release the recovered space to the tablespace. During the short space release phase, any cursors referencing this segment may be invalidated and queries on the segment could be affected.

☐ **Compact Segments**
Compacting will compact segment data without releasing the recovered space. After compacting the data, the recovered space can be quickly released by running Compact Segments and Release Space.

q) On the Shrink Segment: Options page, click Implement.

Shrink Segment: Schedule Cancel Submit

TIP This operation may be resource-intensive and should be scheduled during off-peak hours.

Job Information

* Job Name:
Job Description:

Schedule

Schedule Type:

Time Zone:

Repeating

Repeat:

Start

☒ Immediately

r) On the Shrink Segment: Schedule page, click the Submit button.

All Running History									
View Job Status Stop Run View Job Definition Edit Job Definition Delete									
Select	Status	Name	Schema	Start Date	Elapsed Time (seconds)	CPU Used (seconds)	Session ID	Resource Consumer Group	Previous Runs
<input checked="" type="radio"/>		SQLSCRIPT_3083233	SYS	Jul 31, 2009 10:36:37 PM +07:00	2.45	.04	58	SYS_GROUP	0

s) On the Scheduler Jobs page, click the [SQLSCRIPT_nnn](#) link.

Practice 18-1: Managing Storage (continued)

General	Schedule	Options
Name SQLSCRIPT_3083233	Repeat Do Not Repeat	Raise Events None
Schema SYS	Start Jul 31, 2009	Maximum Run Duration None (minutes)
Enabled FALSE	Date 10:36:37 PM	Priority Medium
Description None	Etc/GMT-7	Schedule Limit None (minutes)
Logging Log job runs only		Maximum Runs None
Level (RUNS)		Maximum Failures None
Job Class DEFAULT_JOB_CLASS		Job Weight 1
Auto Drop FALSE		Instance TRUE
Restartable FALSE		Stickiness For use in RAC. If instance_stickiness is set to TRUE, the Oracle Scheduler will attempt to execute the job on the same instance as the previous run
Destination		
Credential Name		

Command
Command Type PL/SQL Block
PL/SQL
<pre> begin EXECUTE IMMEDIATE 'alter table "SYS"."EMPLOYEES1" shrink space'; EXECUTE IMMEDIATE 'alter table "SYS"."EMPLOYEES2" shrink space'; EXECUTE IMMEDIATE 'alter table "SYS"."EMPLOYEES3" shrink space'; end; </pre>

Operation Detail			
View			
Select	Log ID	Log Date	Status
<input checked="" type="radio"/>	340	Jul 31, 2009 10:36:47 PM +07:00	SUCCEEDED

- t) On the View Job page, scroll to the bottom of the page. Under Operation Detail, you should see that the job succeeded. (If it's still running, use your browser's Refresh button). Then click OK.

- 12) Wait a few minutes and check that there are no longer any outstanding alerts for the TBSALERT tablespace. Then navigate to the Database home page. You should see Problem Tablespaces: 0.

Space Summary	
Database Size (GB)	1.415
Problem Tablespaces	0
Segment Advisor Recommendations	3
Space Violations	0
Dump Area Used (%)	72

- 13) Retrieve the history of the TBSALERT Tablespace Space Usage metric for the last 24 hours.
- a) On the Database home page, select All Metrics in the Related Links region.

Practice 18-1: Managing Storage (continued)

Tablespaces Full	Some	Server Generated
Tablespace Free Space (MB)	Not Set	
Tablespace Space Used (%)	Set	

- b) Expand the Tablespaces Full category, and click the Tablespace Space Used (%) link.

Tablespace Space Used (%)	
Page Refreshed Jul 31, 2009 10:46:09 PM GMT+07:00	
View Data Real Time: Manual Refresh ▼	
Tablespace Name ▲	Current Value
EXAMPLE	0.24
SYSAUX	1.71
SYSTEM	2.06
TBSALERT	30.99
TEMP	0
UNDOTBS1	0.03
USERS	0.01

- c) Make sure that you select Real Time: Manual Refresh from the View Data drop-down list. Then click the TBSALERT link.
- d) This takes you to the Tablespace Space Used (%): Tablespace Name TBSALERT page. Select “Last 24 hours” from the View Data drop-down list.

Alert History		
Comment for Most Recent Alert		
Severity	Timestamp ▼	Message
✓	Jul 31, 2009 10:44:20 PM	Tablespace TBSALERT is 30 percent full
✗	Jul 31, 2009 10:04:17 PM	Tablespace TBSALERT is 75 percent full
✓	Jul 31, 2009 9:49:29 PM	Tablespace TBSALERT is 0 percent full

- e) View entries in the Alert History.
- 14) Reset the databasewide default thresholds from the Tablespace Space Usage metric for
- On the Tablespace Space Used (%): Tablespace Name TBSALERT page, click the Edit Tablespace link in the related Links section.
 - This opens the Edit Tablespace: TBSALERT page. Click the Thresholds tab.
 - Click Use Database Default Thresholds option in the Space Used (%) section. Then click Show SQL.

Practice 18-1: Managing Storage (continued)

Show SQL

Return

```
BEGIN DBMS_SERVER_ALERT.SET_THRESHOLD(9000,NULL,NULL,NULL,NULL,1,1,NULL,5,'TBSALERT');
END;
```

- d) Review the statement and click return.
- e) On the Edit Tablespace: TBSALERT, Thresholds page, click the Apply button.
You should receive a success message.

15) **Note: This is your mandatory cleanup step.** Because you have finished with your test case, view and execute the `seg_advsrcleanup.sh` script from the `labs` directory to drop your TBSALERT tablespace.

```
$ cat seg_advsrcleanup.sh
#!/bin/sh
# For training only, execute as oracle OS user

sqlplus /nolog <<EOF
connect / as sysdba
alter system set disk_asynch_io = TRUE scope = spfile;
shutdown immediate;
startup
drop tablespace tbsalert including contents and datafiles;
exit
EOF
$
```

```
$ ./seg_advsrcleanup.sh
SQL> Connected.
SQL>
System altered.

SQL> Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> ORACLE instance started.

Total System Global Area  481259520 bytes
Fixed Size                  1337324 bytes
Variable Size              385878036 bytes
Database Buffers           88080384 bytes
Redo Buffers                5963776 bytes
Database mounted.
Database opened.
SQL>
Tablespace dropped.

SQL>
$
```

Practices for Lesson 19

Physical disks with 4 KB-sectors are now available. Although this largely concerns only the operating system, the Oracle server is aware of them and uses them automatically when you create new databases.

However, as a DBA you might have databases, which were created on 512-bytes disks. In this practice, you learn about how to perform an offline migration from 512-bytes disks to 4 KB-sector disks.

Practice 19-1: Managing Space for the Database

In this practice, you view a demonstration of using 4 KB-sector disks. The focus is on performing an offline migration of redo log groups from 512-bytes to 4 KB-sector disks.

- 1) Click the Oracle's Home icon on your desktop.
- 2) Navigate to the `/home/oracle/demos/4kb_disks` directory.
- 3) Double-click the `4kb_disks_viewlet_swf.html` file.
- 4) In the Run or Display window, click Display and view the presentation.
- 5) Use the controls at the bottom of the viewlet window to start, pause and stop the presentation, as suits your personal learning style.
- 6) Uninterrupted viewing of the demos takes about ten minutes. When you have finished viewing the presentation, close your Web browser window.

Practices for Lesson 20

Background: You are responsible for an active database that cannot be shut down. It is running in ARCHIVELOG mode. Now you are requested to duplicate this database, for testing purposes.

To setup a working environment for your duplicated database, you:

- Add two disks to your DATA disk group.
- Ensure that the orcl source database is in ARCHIVELOG mode with a 7 GB fast recovery area.
- Set up dbtest as the net service name for your planned dbtest database.
- Use Oracle Net Manager to configure the LISTENER with the dbtest and orcl database services.
- Clone a database by using RMAN. Start the duplication process in Enterprise Manager.
- Test access


Practice 20-1: Duplicating a Database

In this practice, you clone a database and use additional utilities to setup a working environment. To simulate this environment, assume that your active database is `orcl` (which is stored in ASM).

- 1) Before you start cloning your database, add the last two ASM disks to the DATA disk group.
 - a) From a graphical terminal window, connected as user `oracle`, set up your environment to use the `+ASM` instance, and execute `asmca`.

```
$ . oraenv
ORACLE_SID = [orcl] ? +ASM
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/grid is
/u01/app/oracle
$
$ asmca
```

- b) On the Configure ASM: Disk Groups subpage, select DATA disk group.
- c) Right click.



- d) Select Add disks.

<input checked="" type="checkbox"/>	ORCL:ASMDISK12	PROVISIONED	2304
<input checked="" type="checkbox"/>	ORCL:ASMDISK13	PROVISIONED	2304

- e) On the Add Disks page, select both `ORCL:ASMDISK12` and `ORCL:ASMDISK13`.
- f) Click OK.

Practice 20-1: Duplicating a Database (continued)



- g) On the information window that appears, click OK.
 - h) Back to the Configure ASM: Disk Groups subpage, click Exit.
 - i) On the ASM Configuration Assistant window, click Yes.
- 2) Check the ASM activities and wait until the rebalance operation is finished:
- a) Log in to Enterprise Manager as user SYS.



- b) On the Home page, click the +ASM link in the General section.
- c) On the ASM Home page, click the Disk Groups tab.
- d) You may have to log in to the ASM instance if you have not previously done it and saved credentials:
 - On the Automatic Storage Management Login page, enter SYS in the Username field, oracle_4U in the Password field, and SYSASM in the Connect As field.
 - Select Save as Preferred Credential. Then click Login.

Practice 20-1: Duplicating a Database (continued)

Home Performance **Disk Groups** Configuration Users ASM Cluster File System

Create Mount All Dismount All

Mount Dismount Rebalance Check Delete

Select All | Select None

Select	Name	State	Redundancy	Size (GB)	Used (GB)	Used (%)	Usable Free (GB)	Member Disks
<input type="checkbox"/>	DATA	MOUNTED	NORMAL	18.00	10.33	57.37	3.02	8
<input type="checkbox"/>	FRA	MOUNTED	EXTERN	9.00	7.63	84.83	1.37	4

TIP The usable free space specifies the amount of space that can be safely used for data. A value above zero means that redundancy can be properly restored after a disk failure.

TIP Mount All and Dismount All operation will only mount and dismount the disk groups specified in the Auto Mount Disk Groups parameter.

e) On the Disk Groups sub page, click the DATA link.

Disk Group: DATA

General Performance Templates Files Access Control Volumes

General

Name: DATA
State: MOUNTED
Redundancy: NORMAL
Total Size (GB): 18
Pending Operations: 1
Allocation Unit (MB): 1

Advanced Attributes

Database Compatibility: 10.1.0.0.0
ASM Compatibility: 11.2.0.0.0
ASM Volume Compatibility: 3.6
Disk Repair Time (Hours): Disabled
Smart Scan Capability: Disabled
File Access Control: Disabled

Current Disk Group Usage (GB)

Disk Group Daily Space Usage History (Last 7 Days)

Member Disks

View: By Disk Go Add

Resize Online Offline Recover Bad Blocks Remove

Select All | Select None

Select	Disk	Failure Group	Path	Library	Read/Write Errors	State	Mode	Size (GB)	Used (GB)	Used (%)	Failgroup Type
<input type="checkbox"/>	ASMDISK1	ASMDISK1	ORCL:ASMDISK1	ASM LIBRARY - GENERIC LINUX, VERSION 2.0.4 (KABI_V2)	0	NORMAL	✓	2.25	1.33	59.29	REGULAR

f) On the Disk Group: DATA page, click at the Pending Operations field in the General section.

Pending Operations: DATA

Data Retrieved Aug 1, 2009 11:24:16 PM GMT+07:00 Refresh Real Time: Manual Refresh Refresh

Operation Type	Status	Desired Power	Actual Power	Operation Rate (Units per minute)	% Complete	Remaining Time (minutes)
REBAL	RUN	1	1	225	67.02	4

g) Click Refresh and **Wait until the rebalance operation is finished.**

h) Then click the database tab.

- 3) To ensure that you are pointing to the orcl database and that this database is in ARCHIVELOG mode with a 7 GB fast recovery area, execute the rman_archive.log.sh script from a terminal window in your working directory.

```
$ . oraenv
ORACLE_SID = [+ASM] ? orcl
The Oracle base for
ORACLE_HOME=/u01/app/oracle/product/11.2.0/dbhome_1 is
/u01/app/oracle
```


Practice 20-1: Duplicating a Database (continued)

```

$ ./rman_archivelog.sh
*****
For demo purposes ONLY:
  * Enable ARCHIVELOG mode for database

The script may appear to hang at the SQL prompt
when the database is shutting down and being
opened. Wait a few minutes and it should progress.
*****

SQL> SQL>
System altered.

SQL> SQL> Database closed.
Database dismounted.
ORACLE instance shut down.
SQL> ORACLE instance started.

Total System Global Area  481259520 bytes
Fixed Size                  1337324 bytes
Variable Size              394266644 bytes
Database Buffers           79691776 bytes
Redo Buffers                5963776 bytes
Database mounted.
SQL>
Database altered.

SQL>
Database altered.

SQL> Database log mode          Archive Mode
Automatic archival             Enabled
Archive destination            USE_DB_RECOVERY_FILE_DEST
Oldest online log sequence     15
Next log sequence to archive   17
Current log sequence           17
SQL>
$

```

- 4) Set up dbtest as the net service name for your planned dbtest database.
 - a) In a graphical terminal window as the oracle user, set up your environment to point to your orcl instance and invoke the netca utility.

```

$ . oraenv
ORACLE_SID = [orcl] ? orcl
$ netca


```

The Oracle Net Configuration Assistant (NETCA) opens a window.

- b) On the Welcome page, select “Local Net Service Name configuration,” and click Next.
- c) On the Net Service Name Configuration page, select Add and click Next.

Practice 20-1: Duplicating a Database (continued)

- d) In the Service Name field, enter `dbtest` and click Next.
- e) On the Net Service Name Configuration, Select Protocols page, select TCP and click Next.




- f) On the Net Service Name Configuration, TCP/IP Protocol page, enter **your** host name, for example, `edrsr37p1.us.oracle.com`, select “Use the standard port number of 1521,” and then click Next.
 - g) On the Net Service Name Configuration, Test page, select “No, do not test” (because your `dbtest` database does not yet exist) and click Next.
 - h) On the Net Service Name Configuration, Net Service Name page, enter `dbtest` as Net Service Name, and then click Next.
 - i) Click No in answer to the question “Would you like to configure another net service name?” and then click Next.
 - j) When you see the completion message, click Next again.
 - k) Finally, click Finish.
- 5) Use Oracle Net Manager to configure the LISTENER with the `dbtest` and `orcl` database services.
- a) In a graphical terminal window as the `oracle` user, set up your environment to point to your +ASM instance and invoke the `netmgr` utility.

```
$ . oraenv
ORACLE_SID = [orcl] ? +ASM
```

Practice 20-1: Duplicating a Database (continued)


```
The Oracle base for  
ORACLE_HOME=/u01/app/oracle/product/11.2.0/grid is  
/u01/app/oracle  
$ netmgr
```

- b) The Oracle Net Manager opens a window. Click the “+” icon, right before the word “Local,” then click the “+” icon, right before the word “Listeners” to expand the nodes in the navigation tree until you see the listener, called “LISTENER.”




- c) First select LISTENER in the left part of the window then, select Database Services from the drop-down in the right part of the window.
- d) Click the Add Database button.

Practice 20-1: Duplicating a Database (continued)




- e) Enter or confirm the following values:
Global Database Name: dbtest
Oracle Home Directory: /u01/app/oracle/product/11.2.0/grid/
SID: dbtest
- f) Click the Add Database button again.
- g) Enter the following values:
Global Database Name: orcl
Oracle Home Directory: /u01/app/oracle/product/11.2.0/grid/
SID: orcl

Practice 20-1: Duplicating a Database (continued)



- h) From the Oracle Net Manager menu bar, select File > Save Network Configuration, then File > Exit.
- 6) Clone a database by using RMAN. Start the duplication process in Enterprise Manager.
- Log in to Enterprise Manager as the SYS user with the oracle_4U password and connect as SYSDBA.
 - Navigate to Data Movement > Clone Database (in the Move Database Files section).



- c) On the Clone Database: Source Type page, select “A running database” and “Use Recovery Manager (RMAN) to copy database files” and then click Continue.

Practice 20-1: Duplicating a Database (continued)

Source Options Select Destination Destination Options Database Configuration Schedule Review

Clone Database: Source Options

Source Database **orcl.example.com** Cancel Step 1 of 6 Next

Source Host **edrsr37p1.us.oracle.com**

The source database will be duplicated directly to the specified destination Oracle Home. No staging areas are required.

Concurrent File Copy Processes The number of concurrent processes (up to 50) used by Recovery Manager (RMAN) to copy the database files. Increased concurrency may speed the process if sufficient network bandwidth is available.

Source Host Credentials

Enter the credentials of the user who owns the source database Oracle server installation.

Username

Password

☒ Save as Preferred Credential

- d) On the Clone Database: Source Options page, enter or confirm `oracle` as the username and password, click “Save as Preferred Credential,” and then click Next.

Source Options **Select Destination** Destination Options Database Configuration Schedule Review

Clone Database: Select Destination

Source Database **orcl.example.com** Cancel Back Step 2 of 6 Next

Source Host **edrsr37p1.us.oracle.com**

Destination Oracle Home

Specify the host and Oracle Home where the cloned database will be created. The host should be a discovered Enterprise Manager target and match the operating system of the source database. The Oracle Home should exist on the specified host and match the version of the source database.

Host

Oracle Home

Destination Host Credentials

Enter the credentials of the user who owns the Oracle Home selected above.

Username

Password

☐ Save as Preferred Credential

Destination Database

Global Database Name Typical format : name.domain

Instance Name

Database Storage

- e) On the Clone Database: Select Destination page, enter `dbtest` both as Global Database Name and as Instance Name, and select Automatic Storage Management (ASM) from the Database Storage drop down list. Then click Next.
- f) If the Clone Database: ASM Instance Login page appears, enter `oracle_4U` as SYS password, and click Login.

Practice 20-1: Duplicating a Database (continued)

Source Options Select Destination **Destination Options** Database Configuration Schedule Review

Clone Database: Destination Options

Source Database: orcl.example.com ASM Instance: +ASM_edrsr37p1.us.oracle.com Cancel Back Step 3 of 6 **Next**

Source Host: edrsr37p1.us.oracle.com Destination Host: edrsr37p1.us.oracle.com

Database File Locations

Database Area
Specify the location where datafiles, tempfiles, redo log files, and control files will be created.
Total Disk Space Required: **1740 MB**
Database Area: DATA

Tablespace Storage Locations: **Default** Customize

Redo Log and Control File Locations: **Default** Multiplex

If multiplex locations are not specified, these files will be created in both the database and flash recovery areas.

Flash Recovery Area
☒ Use flash recovery area
To enhance data protection and performance, Oracle recommends that a flash recovery area be used.
Specify the location where recovery-related files (archived redo log files, RMAN backups, etc.) will be created.
Flash Recovery Area: FRA

Flash Recovery Area Size (MB): 2000

Limit on the total space used by files created in the flash recovery area. The default value is the same as the source database setting.

- g) On the Clone Database: Destination Options page, enter or confirm DATA as Database Area, FRA as the Flash Recovery Area, and enter 2000 as the Flash Recovery Area Size. Then click Next.
- h) You receive a warning that the FRA is smaller than twice the database size. Because you plan to rarely use the FRA of this test database, click Yes to continue.

Practice 20-1: Duplicating a Database (continued)

Source Options Select Destination Destination Options **Database Configuration** Schedule Review

Clone Database: Database Configuration

Source Database: orcl.example.com ASM Instance: +ASM_edrsr37p1.us.oracle.com Cancel Back Step 4 of 6 Next

Source Host: edrsr37p1.us.oracle.com Destination Host: edrsr37p1.us.oracle.com

Network Configuration File Location

Specify the network configuration file location. The configuration files include listener.ora, tnsnames.ora, and sqlnet.ora. Clone Database will read these files and, if necessary, add configuration information about the destination database to listener.ora and tnsnames.ora.

* Configuration File Location: /u01/app/oracle/product/11.2.0/dbhome_1/network/admin

Listener Oracle Home

Specify the Oracle Home from which the listener for the cloned database will be started.

* Listener Oracle Home: /u01/app/oracle/product/11.2.0/dbhome_1

Database Control Configuration

☒ Configure Enterprise Manager Database Control for this database

SYS Password: Confirm SYS Password:

DBSNMP Password: Confirm DBSNMP Password:

SYSMAN Password: Confirm SYSMAN Password:

HTTP Port: 5505

Post Cloning Script

☐ Run Post Cloning Scripts

- i) On the Clone Database: Database Configuration page:
- Select “Configure Enterprise Manager Database Control for this database”,
 - Confirm
/u01/app/oracle/product/11.2.0/dbhome_1/network/admin as
the Configuration File Location.
 - Enter or confirm /u01/app/oracle/product/11.2.0/dbhome_1 in the
Listener Oracle Home field.
 - Enter oracle_4U six times in all password fields, and enter 5505 as HTTP
port.
 - Click Next.
- j) If you receive a warning, that the sqlnet.ora file or the listener.ora file
do not exist, accept the warning by clicking Yes.

Practice 20-1: Duplicating a Database (continued)

Source Options Select Destination Destination Options Database Configuration **Schedule** Review

Clone Database: Schedule

Source Database: **orcl.example.com** ASM Instance: **+ASM_edrsr37p1.us.oracle.com** Cancel Back Step 5 of 6 **Next**

Source Host: **edrsr37p1.us.oracle.com** Destination Host: **edrsr37p1.us.oracle.com**

Specify a name and description for the clone job. Specify a date to start the job.

Job Name and Description

* Job Name: **DBClone_orcl.example.com_5**

Description:

Start

☒ Immediately

- k) On the Clone Database: Schedule page, ensure that the job starts immediately and click Next.

Previous Schedule **Review**

Clone Database: Review

The database **ORCL** on host **edrsr37p1.us.oracle.com** will be cloned to database **dbtest** on host **edrsr37p1.us.oracle.com** in Oracle Home **/u01/app/oracle/product/11.2.0/dbhome_1**. Cancel Back Step 6 of 6 **Submit Job**

Job Name: **DBClone_orcl.example.com_5**
 Scheduled: **Immediately**
 Source Type: **A running database**

Details

Source Database		Destination Database	
Global Database Name	ORCL	Global Database Name	dbtest
Instance Name	orcl	Instance Name	dbtest
Database Version	11.2.0.1.0	Oracle Server Version	11.2.0.1.0
Oracle Home	/u01/app/oracle/product/11.2.0/dbhome_1	Oracle Base	/u01/app/oracle
Host	edrsr37p1.us.oracle.com	Oracle Home	/u01/app/oracle/product/11.2.0/dbhome_1
Operating System	Enterprise Linux Enterprise Linux Server release 5.2 (Carthage) 2.6.18	Host	edrsr37p1.us.oracle.com
Host Username	oracle	Operating System	Enterprise Linux Enterprise Linux Server release 5.2 (Carthage) 2.6.18
Database Username	SYS	Host Username	oracle
Staging Area Location	/u01/app/oracle/product/11.2.0/dbhome_1/dbs	Database Username	SYS
Target Database Name	orcl.example.com	Staging Area Location	/u01/app/oracle/product/11.2.0/dbhome_1/dbs
Archiving Mode	ARCHIVELOG	File Transfer Method	RMAN duplicate
		Configuration File Location	/u01/app/oracle/product/11.2.0/dbhome_1/network/admin
		Database Storage	Automatic Storage Management
		Masking Definition	Not specified
		ASM Instance	+ASM_edrsr37p1.us.oracle.com

Practice 20-1: Duplicating a Database (continued)

Database Storage

Database files (datafiles, control files, log files, tempfiles) will be created using **Automatic Storage Management**. The names of all database files will be generated by Oracle using ASM naming conventions. If any location(s) were specified via Multiplex Redo Log Files and Control Files, log files and control files will be created in those locations. Otherwise, they will be created in both the database area and flash recovery area. [View Source Log Files and Control Files](#)

Database Area **DATA**
Flash Recovery Area **FRA**
Flash Recovery Area Size (MB) **2000**
Multiplex Redo Log Files and Control Files **No**

Tablespaces

Source Name	Size (MB)	Status	Type	To Location
EXAMPLE	101	ONLINE	PERMANENT	DATA
SYS_AUX	601	ONLINE	PERMANENT	DATA
SYSTEM	681	ONLINE	PERMANENT	DATA
TEMP	29	ONLINE	TEMPORARY	DATA
UNDOTBS1	146	ONLINE	UNDO	DATA
USERS	8	ONLINE	PERMANENT	DATA

Directory Objects

Directory Name	Source Directory Path	Destination Directory Path
SUBDIR	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/order_entry/2002/Sep	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/order_entry/2002/Sep
SS_OE_XMLDIR	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/order_entry/	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/order_entry/
LOG_FILE_DIR	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/log/	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/log/
DATA_FILE_DIR	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/sales_history/	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/sales_history/
XMLDIR	/ade/b/598210036/oracle/rdbms/xml	/ade/b/598210036/oracle/rdbms/xml
MEDIA_DIR	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/product_media/	/u01/app/oracle/product/11.2.0/dbhome_1/demo/schema/product_media/
DATA_PUMP_DIR	/u01/app/oracle/admin/orcl/dpump/	/u01/app/oracle/admin/orcl/dpump/

External Files

Name	Source Directory Name	Size (KB)	Destination Directory Name
sale1v3.dat	DATA_FILE_DIR	1	DATA_FILE_DIR

[Cancel](#) [Back](#) [Step 6 of 6](#) [Submit Job](#)

- l) On the Clone Database: Review page, review the Details, including the Database Storage and click Submit Job.
- m) Wait on the “Clone Database job is being submitted” page.

Clone Database: Confirmation

[View Status](#) [OK](#)

Submit Successful

Your clone request has been submitted successfully. Click 'View Status' to view the status of your clone job. Click 'OK' to end this session.

- n) The Clone Database: Confirmation page should display a success message. Click the View Status to transfer to the Job Activity page.
- o) This takes you to the Execution page. Occasionally, click your browser's reload button, to display the job progress until you receive a success message. (The execution time for your job depends on your hardware and available system resources.)

Practice 20-1: Duplicating a Database (continued)

Summary	
Status	Succeeded
Scheduled	Aug 2, 2009 6:53:22 PM (UTC+07:00)
Started	Aug 2, 2009 6:53:22 PM (UTC+07:00)
Ended	Aug 2, 2009 7:52:29 PM (UTC+07:00)
Elapsed Time	3546 seconds
Notification	No

p) Scroll to the bottom of the page to see the executed steps. Some of the executed steps have output logs, for example:

- Source Preparation shows the initialization parameters of the source database.
- Destination Preparation shows dbtest listener and service information.
- Duplicate database contains RMAN operations.
- Recover Database shows restarting of the dbtest database.
- Add Temporary Files also shows output from Enterprise Manager configuration.
- Check Database and Mask data each log into the new duplicated database.

Name	Targets	Status	Started	Ended	Elapsed Time (seconds)
Execution: edrsr37p1.us.oracle.com	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:53:22 PM (UTC+07:00)	Aug 2, 2009 7:52:29 PM (UTC+07:00)	3546
Previous					
Step: Source Preparation	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:53:35 PM (UTC+07:00)	Aug 2, 2009 6:53:38 PM (UTC+07:00)	3
Step: Create Control File	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:53:45 PM (UTC+07:00)	Aug 2, 2009 6:53:46 PM (UTC+07:00)	1
Step: Destination Directories Creation	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:53:56 PM (UTC+07:00)	Aug 2, 2009 6:53:56 PM (UTC+07:00)	0
Step: Copy Initialization and Password Files	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:54:06 PM (UTC+07:00)	Aug 2, 2009 6:54:07 PM (UTC+07:00)	1
Step: Skip Copy or Transfer Controlfile	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:54:16 PM (UTC+07:00)	Aug 2, 2009 6:54:17 PM (UTC+07:00)	1
Step: Destination Preparation	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:54:26 PM (UTC+07:00)	Aug 2, 2009 6:54:34 PM (UTC+07:00)	8
Step: Duplicate Database	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 6:54:36 PM (UTC+07:00)	Aug 2, 2009 7:15:47 PM (UTC+07:00)	1270
Step: Skip Creating Standby Control File	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:15:56 PM (UTC+07:00)	Aug 2, 2009 7:15:58 PM (UTC+07:00)	2
Step: Skip Switching Clone Type	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:16:07 PM (UTC+07:00)	Aug 2, 2009 7:16:09 PM (UTC+07:00)	2
Step: Recover Database	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:16:17 PM (UTC+07:00)	Aug 2, 2009 7:16:45 PM (UTC+07:00)	28
Step: Add Temporary Files	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:16:48 PM (UTC+07:00)	Aug 2, 2009 7:51:31 PM (UTC+07:00)	2083
Step: Check Database and Run Post Cloning Scripts	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:51:43 PM (UTC+07:00)	Aug 2, 2009 7:51:58 PM (UTC+07:00)	14
Step: Mask data	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:52:07 PM (UTC+07:00)	Aug 2, 2009 7:52:09 PM (UTC+07:00)	2
Step: Add EM Target	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:52:17 PM (UTC+07:00)	Aug 2, 2009 7:52:19 PM (UTC+07:00)	2
Step: Cleanup Source Temporary Directory	edrsr37p1.us.oracle.com	Succeeded	Aug 2, 2009 7:52:27 PM (UTC+07:00)	Aug 2, 2009 7:52:29 PM (UTC+07:00)	2

7) Test the access to your cloned databases in SQL*Plus.

Practice 20-1: Duplicating a Database (continued)

- a) Connected as the `oracle` user in a graphical terminal session, ensure that you are pointing to the `orcl` database.

```
$ . oraenv
ORACLE_SID = [+ASM] ? orcl
$
```

- b) Connect as the `SYS` user to your `orcl` database and execute the following query:

```
select dbid, name, created, open_mode
from v$database;
```

```
$ sqlplus / as sysdba

SQL> select dbid, name, created, open_mode from v$database;

          DBID NAME                CREATED                OPEN_MODE
-----
1221383234 ORCL                2009-07-30:19:21:38 READ WRITE
SQL>
```

- c) Now connect as the `SYSTEM` user with the `oracle_4U` password to your `dbtest` database and execute the preceding query. Exit from `SQL*Plus`.

```
SQL> connect system@dbtest
Enter password: oracle_4U <<< not displayed
Connected.
SQL> select dbid, name, created, open_mode from v$database;

          DBID NAME                CREATED                OPEN_MODE
-----
1086723993 DBTEST                2009-08-02:19:12:25 READ WRITE
SQL> exit
$
```


- 8) With the `dbca` utility, delete the `DBTEST` database because it is no longer needed

- a. In a terminal window, start `dbca`.

```
$ dbca
```

- b. Click Next on the Welcome page.

- c. Choose Delete a Database on the Operations page.



- d. Select `dbtest` from the list of databases to delete. Then click Finish.

Practice 20-1: Duplicating a Database (continued)

- e. Confirm the delete operation by clicking Yes.
- f. After the delete operation is finished, click No when asked if you want to perform another dbca operation.

Usman Qamar (usman.qamar@live.com) has a non-transferable
license to use this Student Guide.