

Use for GMM

The following import statement is required to avoid a warning when we use the GMM. There is a memory leak when we use GMM. Do not use it for other entropy approximations because it slows down the campaign in general.

Note: it causes a problem with the plots. They are created twice.

```
In [1]: #import os
#os.environ["OMP_NUM_THREADS"] = '1'
```

```
In [2]: import MyPlotting as MyPlots
import matplotlib.pyplot as plt
from datastruct import Settings, Experiment, ExperimentStep, DataPoint
from entropy import calc_entropy, default_entropy_options
import numpy as np

from functions_gain_factor import recalculating_entropy
```

9 Reloading Experiments

```
In [3]: # #Reloading Data
exp_control = Experiment.load('4/test1_control_id4c.gz', recalc_yprofs=True)
exp_entropy1 = Experiment.load('4/test1_entropy_id4e1.gz', recalc_yprofs=True)
exp_entropy2 = Experiment.load('4/test1_entropy_id4e2.gz', recalc_yprofs=True)
exp_on_the_fly1 = Experiment.load('4/test1_on_the_fly1_id4o1.gz', recalc_yprofs=True)
exp_on_the_fly2 = Experiment.load('4/test1_on_the_fly2_id4o2.gz', recalc_yprofs=True)

#####Use only when you have a GMM version of
####GMM case
# exp_control_gmm = Experiment.Load('1/test1_control_id1c_gmm.gz', recalc_yprofs=True)
# exp_entropy1_gmm = Experiment.Load('1/test1_entropy_id1e1_gmm.gz', recalc_yprofs=True)
# exp_entropy2_gmm = Experiment.Load('1/test1_entropy_id1e2_gmm.gz', recalc_yprofs=True)
# exp_on_the_fly1_gmm = Experiment.Load('1/test1_on_the_fly1_id1o1_gmm.gz', recalc_yprofs=True)
# exp_on_the_fly2_gmm = Experiment.Load('1/test1_on_the_fly2_id1o2_gmm.gz', recalc_yprofs=True)

#reloaded_exp.creation_time.isoformat()
```

```
In [ ]:
```

```
In [4]: #Notice now all the outcomes have the same size except for the datax, datay and datady
#Last unfitted point
len(exp_entropy1.entropy()) #34
len(exp_entropy1.load_yprofs()) #34
len(exp_entropy1.load_pts()) #34
len(exp_entropy1.getdata()[0]) #35
len(exp_entropy1.meastimes()) #34
```

```
Out[4]: 34
```

Warning

Remember that the maximum time spend in the control data is way greater than for the autonomous cases. Thus, when we are plotting the y-profiles and the histogram for the parameters we should may be truncated the values of control until a time that is closer to max amount of time spend in the autonomous cases.

10 Compare to Benchmark

```
In [5]: # from matplotlib.colors import LogNorm
# from numpy.matlib import repmat

print(exp_entropy1.settings.ground_truth_pars) #{'I0': 30.0, 'A': 15.0, 'phi0': 155.0,
print(exp_on_the_fly1.settings.ground_truth_pars)

{'I0': 30.0, 'A': 1.5, 'phi0': 155.0, 'T': 401.0, 'sigma': 797.0}
{'I0': 30.0, 'A': 1.5, 'phi0': 155.0, 'T': 401.0, 'sigma': 797.0}
```

10.1 Y-Profiles Histograms

```
In [6]: ##Plotting the Last set of Y-profiles for the different approaches
##If you do not want to plot the figure of merits do not provide them. It still works

#Entropy 1
MyPlots.plot_y_profiles(exp_entropy1.load_yprofs()[-1],exp_entropy1.settings.x,
                      FOM = exp_entropy1.load_FOM()[-1],
                      this_title = "Histogram of Y profiles Entropy 1 (Selected) Approach")

#Entropy 2
MyPlots.plot_y_profiles(exp_entropy2.load_yprofs()[-1],exp_entropy2.settings.x,
                      FOM = exp_entropy2.load_FOM()[-1],
                      this_title = "Histogram of Y profiles Entropy 2 (All) Approach")

#On-the Fly 1
MyPlots.plot_y_profiles(exp_on_the_fly1.load_yprofs()[-1],exp_on_the_fly1.settings.x,
                      FOM = exp_on_the_fly1.load_FOM()[-1],
                      this_title = "Histogram of Y profiles On-The_Fly 1 Approach" )

#On-the Fly 2
MyPlots.plot_y_profiles(exp_on_the_fly2.load_yprofs()[-1],exp_on_the_fly2.settings.x,
                      FOM = exp_on_the_fly2.load_FOM()[-1],
                      this_title = "Histogram of Y profiles On-The_Fly 2 Approach" )

#Control Data
MyPlots.plot_y_profiles(exp_control.load_yprofs()[-1],exp_control.settings.x,
                      this_title = "Histogram of Y profiles My Control Evenly Approach")
```





Figure of Merits for each x



Histogram of Y profiles Entropy 2 (All) Approach





Figure of Merits for each x







Figure of Merits for each x








Figure of Merits for each x



Histogram of Y profiles My Control Evenly Approach



In [7]: ##### GMM TO COMPARE Commnet out everything below unless you have a reason

```
# #Entropy 1
# MyPlots.plot_y_profiles(exp_entropy1_gmm.Load_yprofs()[-1],exp_entropy1_gmm.settings,
# FOM = exp_entropy1_gmm.Load_FOM()[-1],
# this_title = "Histogram of Y profiles Entropy 1 (Selected) GMM Approach")

# #Entropy 2
# MyPlots.plot_y_profiles(exp_entropy2_gmm.Load_yprofs()[-1],exp_entropy2_gmm.settings,
# FOM = exp_entropy2_gmm.Load_FOM()[-1],
# this_title = "Histogram of Y profiles Entropy 2 (ALL) GMM Approach")

# #On-the Fly 1
# MyPlots.plot_y_profiles(exp_on_the_fly1_gmm.Load_yprofs()[-1],exp_on_the_fly1_gmm.settings,
# FOM = exp_on_the_fly1_gmm.Load_FOM()[-1],
# this_title = "Histogram of Y profiles On-The_Fly 1 GMM Approach")

# #On-the Fly 1
# MyPlots.plot_y_profiles(exp_on_the_fly2_gmm.Load_yprofs()[-1],exp_on_the_fly2_gmm.settings,
# FOM = exp_on_the_fly2_gmm.Load_FOM()[-1],
# this_title = "Histogram of Y profiles On-The_Fly 2 GMM Approach")
```

```
# #Control Data
# MyPlots.plot_y_profiles(exp_control_gmm.Load_yprofs()[-1],exp_control_gmm.settings.x
# this_title = "Histogram of Y profiles My Control EvenLy GMM
```

10.2 Histogram for the Parameters Samples

Getting the Lists for the Parameters The containers total_pts (and similars) stores 2-D arrays on them; each 2-d array represents an iteration. The 2-d array contain the samples for all the parameters n_samplesn_parameters (*where the number of samples can change per iteration, but the number of columns is constant*). First,based on the columns of each array (each column represents a parameter) we will create lists that represent each parameter where each sub-list inside the list for a given paremeter represents the samples at an iterations, n_iterationsn_samples

Note: 1) Any of the 2-d arays in this_total_pts and this_total_pts2 have as columns representing each parameter. The columns represent respectvily A, I0, T, and phi0. They are in the same order than in the console output from the loop.

2) We Cannot create 2D arrays for each parameter because the number of samples per iteration can change. Thus, we create lists for each parameter.

plottinh_hist() Here we create an auxiliary funtion to plot each of the sublists (that represent the samples at all the iterations for a given parameter) of the output of using the function above.

WARNING: Remember that the number of samples per iteration can change. Thus, a histogram may not be the best way to visualize converge. we have two options.

1. Normalize the number of samples for al iterations.
2. commnet out the line of code mark_outliers() in the main loop. So, we do not rule outliers and then we will have the same number of samples for all iterations.

plottinh_hist()

In [8]: *#getting the lists for both approaches. The lists contains lists where each sublists i #sublists that represent a parameter there are sublists that represent the samples for #at an iteration.*

```
#Entropy Method
list_par_separated_e1 = MyPlots.getting_list_each_par(exp_entropy1.load_pts()) #This l
list_par_separated_e2 = MyPlots.getting_list_each_par(exp_entropy2.load_pts())
#On-the-fly 1 Method
list_par_separated_o1 = MyPlots.getting_list_each_par(exp_on_the_fly1.load_pts())
#On-the-fly 2 Method
list_par_separated_o2 = MyPlots.getting_list_each_par(exp_on_the_fly2.load_pts())
#Control method
list_par_separated_c = MyPlots.getting_list_each_par(exp_control.load_pts())

#####GMM VERSION

# #Entropy Method
# list_par_separated_e1_gmm = MyPlots.getting_list_each_par(exp_entropy1_gmm.Load_pts()
```

```
# list_par_separated_e2_gmm = MyPlots.getting_list_each_par(exp_entropy2_gmm.Load_pts()
# #On-the-fly 1 Method
# list_par_separated_o1_gmm = MyPlots.getting_list_each_par(exp_on_the_fly1_gmm.Load_pt
# #On-the-fly 2 Method
# list_par_separated_o2_gmm = MyPlots.getting_list_each_par(exp_on_the_fly2_gmm.Load_p
# #Control method
# list_par_separated_c_gmm = MyPlots.getting_list_each_par(exp_control_gmm.Load_pts())
```

```
In [9]: aux_list = [list_par_separated_e1[0], list_par_separated_e2[0], list_par_separated_o1[0],
               list_par_separated_o2[0], list_par_separated_c[0]]

list_times = [exp_entropy1.totaltimes(), exp_entropy2.totaltimes(), exp_on_the_fly1.tot
              exp_on_the_fly2.totaltimes(), exp_control.totaltimes()]

names_for_approaches = ["Entropy 1 (Selected) MVN", "Entropy 2 (All) MVN", "On-the fly
                           "Control-45 even MVN"]
par_name = "A"

# specify y-edges for all three histograms
y_min, y_max = MyPlots.finding_max_min(aux_list)

for i in range(len(aux_list)):
    MyPlots.plotting_hist_logtime(aux_list[i], names_for_approaches[i], par_name, y_mi

#####
#####GMM VERSION COMMENT OUT IF YOU DO NOT HAVE A GMM VERSION


# aux_list = [list_par_separated_e1_gmm[0], list_par_separated_e2_gmm[0], list_par_sepa
#               list_par_separated_o2_gmm[0], list_par_separated_c_gmm[0]]

# names_for_approaches = ["Entropy 1 (Selected) GMM", "Entropy 2 (ALL) GMM", "On-the fl
#                           "Control-45 even GMM"]
# par_name = "A"

# # specify y-edges for all three histograms
# y_min, y_max = MyPlots.finding_max_min(aux_list)


# for i in range(len(aux_list)):
#     MyPlots.plotting_hist(aux_list[i], names_for_approaches[i], par_name, y_min, y_max)

my x edges
[0.44639502 0.95154499 1.31774187 1.50557368 1.63498984 1.71795907
 1.78486836 1.85717012 1.91976715 1.97586794 2.0451627 2.12013424
 2.18994048 2.2492402 2.29414646 2.3421648 2.40906087 2.47615681
 2.52438774 2.58500109 2.64092705 2.68546711 2.73761444 2.79487593
 2.84902418 2.89694222 2.94830773 2.99906035 3.03813744 3.08632006
 3.15194876 3.2115815 3.27638365 3.35067769 3.4246986 ]
```




my_x_edges

```
[0.44639502 0.95154499 1.31774187 1.50557368 1.63606243 1.73391121
 1.82251617 1.91257659 1.98960538 2.06175655 2.12546355 2.18077189
 2.25197971 2.31256712 2.35381257 2.40881159 2.47099297 2.5209696
 2.56429131 2.62088542 2.68566276 2.73918314 2.79101143 2.85499732
 2.91543725 2.96379939 3.00235691 3.05023604 3.104729 3.15233484
 3.20371134 3.26087401 3.3248971 3.39095641]
```




my_x_edges


```
[0.44639502 0.95154499 1.26735426 1.4206245 1.54658413 1.63740902
 1.73800638 1.81003835 1.87103353 1.93748985 1.99739601 2.05500862
 2.11816231 2.18429427 2.24375376 2.2997706 2.35851198 2.41789218
 2.47571243 2.53402971 2.59109599 2.64816962 2.70529786 2.76190836
 2.81942135 2.86970205 2.9220648 2.9831701 3.04434838 3.10045872
 3.15287884 3.20707604 3.26084244 3.31794559 3.37577641 3.42899673]
```



my_x_edges

```
[0.44639502 0.95154499 1.26955629 1.42428365 1.54881476 1.63878346
 1.73776091 1.83396724 1.9359325 2.03386926 2.10821452 2.16651449
 2.23932464 2.32083876 2.39013092 2.44558157 2.50328623 2.56044612
 2.61624826 2.67388883 2.72590699 2.77579446 2.82725318 2.87954614
 2.93324385 2.98501806 3.03468462 3.09422217 3.16071356 3.22057245
 3.27310182 3.32678422 3.38520711]
```





```
In [10]: aux_list = [list_par_separated_e1[1], list_par_separated_e2[1], list_par_separated_o1[1],
               list_par_separated_o2[1], list_par_separated_c[1]]

list_times = [exp_entropy1.totaltimes(), exp_entropy2.totaltimes(), exp_on_the_fly1.totaltimes(),
              exp_on_the_fly2.totaltimes(), exp_control.totaltimes()]

names_for_approaches = ["Entropy 1 (Selected)", "Entropy 2 (All)", "On-the fly 1", "On-the fly 2",
                        "Control-45 even"]
par_name = "I0"

# specify y-edges for all three histograms

#WARNING: If you are plotting the GMM versions, you will need to include the values used
#values below
y_min, y_max = MyPlots.finding_max_min(aux_list)
```

```
for i in range(len(aux_list)):
    MyPlots.plotting_hist_logtime(aux_list[i], names_for_approaches[i], par_name, y_mi

#####
# GMM VERSION COMMENT OUT IF YOU DO NOT HAVE A GMM VERSION


# aux_list = [list_par_separated_e1_gmm[1], list_par_separated_e2_gmm[1], list_par_sep
#             list_par_separated_o2_gmm[1], list_par_separated_c_gmm[1]]

# names_for_approaches = ["Entropy 1 (Selected) GMM", "Entropy 2 (ALL) GMM", "On-the fl
#                         "Control-45 even GMM"]
# par_name = "I0"

#
# # specify y-edges for all three histograms
# y_min, y_max = MyPlots.finding_max_min(aux_list)


# for i in range(len(aux_list)):
#     MyPlots.plotting_hist(aux_list[i], names_for_approaches[i], par_name, y_min, y_max)

my x edges
[0.44639502 0.95154499 1.31774187 1.50557368 1.63498984 1.71795907
 1.78486836 1.85717012 1.91976715 1.97586794 2.0451627 2.12013424
 2.18994048 2.2492402 2.29414646 2.3421648 2.40906087 2.47615681
 2.52438774 2.58500109 2.64092705 2.68546711 2.73761444 2.79487593
 2.84902418 2.89694222 2.94830773 2.99906035 3.03813744 3.08632006
 3.15194876 3.2115815 3.27638365 3.35067769 3.4246986 ]
```



my x edges


```
[0.44639502 0.95154499 1.31774187 1.50557368 1.63606243 1.73391121
 1.82251617 1.91257659 1.98960538 2.06175655 2.12546355 2.18077189
 2.25197971 2.31256712 2.35381257 2.40881159 2.47099297 2.5209696
 2.56429131 2.62088542 2.68566276 2.73918314 2.79101143 2.85499732
 2.91543725 2.96379939 3.00235691 3.05023604 3.104729 3.15233484
 3.20371134 3.26087401 3.3248971 3.39095641]
```



my x edges

```
[0.44639502 0.95154499 1.26735426 1.4206245 1.54658413 1.63740902
 1.73800638 1.81003835 1.87103353 1.93748985 1.99739601 2.05500862
 2.11816231 2.18429427 2.24375376 2.2997706 2.35851198 2.41789218
 2.47571243 2.53402971 2.59109599 2.64816962 2.70529786 2.76190836
 2.81942135 2.86970205 2.9220648 2.9831701 3.04434838 3.10045872
 3.15287884 3.20707604 3.26084244 3.31794559 3.37577641 3.42899673]
```


Histogram of Parameter: I0 -On-the fly 1 approach



```
my x edges
```


```
[0.44639502 0.95154499 1.26955629 1.42428365 1.54881476 1.63878346
 1.73776091 1.83396724 1.9359325 2.03386926 2.10821452 2.16651449
 2.23932464 2.32083876 2.39013092 2.44558157 2.50328623 2.56044612
 2.61624826 2.67388883 2.72590699 2.77579446 2.82725318 2.87954614
 2.93324385 2.98501806 3.03468462 3.09422217 3.16071356 3.22057245
 3.27310182 3.32678422 3.38520711]
```

Histogram of Parameter: I0 -On-the fly 2 approach



my x edges

```
[2.12400496 2.14307285 2.16713147 2.203179 2.25542118 2.32797081  
2.42377446 2.54362306 2.68585652 2.84696932 3.02270427 3.209021  
3.40261866 3.60105122 3.80139375]
```



```
In [11]: #Plotting histograms for T
aux_list = [list_par_separated_e1[2], list_par_separated_e2[2], list_par_separated_o1[2],
            list_par_separated_o2[2], list_par_separated_c[2]]

list_times = [exp_entropy1.totaltimes(), exp_entropy2.totaltimes(), exp_on_the_fly1.totaltimes(),
              exp_on_the_fly2.totaltimes(), exp_control.totaltimes()]


names_for_approaches = ["Entropy 1 (Selected)", "Entropy 2 (All)", "On-the fly 1", "On-the fly 2",
                        "Control-45 even"]
par_name = "T"

# specify y-edges for all three histograms
y_min, y_max = MyPlots.finding_max_min(aux_list)

for i in range(len(aux_list)):
    MyPlots.plotting_hist_logtime(aux_list[i], names_for_approaches[i], par_name, y_min, y_max)
```


```
#####
#GMM VERSION COMMNENT OUT IF YOU DO NOT HAVE A GMM VERSION

# aux_list = [list_par_separated_e1_gmm[2],list_par_separated_e2_gmm[2], list_par_sep#
#               list_par_separated_o2_gmm[2], list_par_separated_c_gmm[2]]#
#
# names_for_approaches = ["Entropy 1 (Selected) GMM", "Entropy 2 (ALL) GMM", "On-the fl#
#                           "Control-45 even GMM"]#
# par_name = "T"#
#
#
# # specify y-edges for all three histograms#
# y_min, y_max = MyPlots.finding_max_min(aux_list)#
#
# for i in range(len(aux_list)):##
#     MyPlots.plotting_hist(aux_list[i], names_for_approaches[i], par_name, y_min, y_max)#
#
my x edges#
[0.44639502 0.95154499 1.31774187 1.50557368 1.63498984 1.71795907#
 1.78486836 1.85717012 1.91976715 1.97586794 2.0451627 2.12013424#
 2.18994048 2.2492402 2.29414646 2.3421648 2.40906087 2.47615681#
 2.52438774 2.58500109 2.64092705 2.68546711 2.73761444 2.79487593#
 2.84902418 2.89694222 2.94830773 2.99906035 3.03813744 3.08632006#
 3.15194876 3.2115815 3.27638365 3.35067769 3.4246986 ]
```




my_x edges

```
[0.44639502 0.95154499 1.31774187 1.50557368 1.63606243 1.73391121
 1.82251617 1.91257659 1.98960538 2.06175655 2.12546355 2.18077189
 2.25197971 2.31256712 2.35381257 2.40881159 2.47099297 2.5209696
 2.56429131 2.62088542 2.68566276 2.73918314 2.79101143 2.85499732
 2.91543725 2.96379939 3.00235691 3.05023604 3.104729   3.15233484
 3.20371134 3.26087401 3.3248971  3.39095641]
```




my_x_edges

```
[0.44639502 0.95154499 1.26735426 1.4206245 1.54658413 1.63740902
 1.73800638 1.81003835 1.87103353 1.93748985 1.99739601 2.05500862
 2.11816231 2.18429427 2.24375376 2.2997706 2.35851198 2.41789218
 2.47571243 2.53402971 2.59109599 2.64816962 2.70529786 2.76190836
 2.81942135 2.86970205 2.9220648 2.9831701 3.04434838 3.10045872
 3.15287884 3.20707604 3.26084244 3.31794559 3.37577641 3.42899673]
```




my x edges

```
[0.44639502 0.95154499 1.26955629 1.42428365 1.54881476 1.63878346
 1.73776091 1.83396724 1.9359325 2.03386926 2.10821452 2.16651449
 2.23932464 2.32083876 2.39013092 2.44558157 2.50328623 2.56044612
 2.61624826 2.67388883 2.72590699 2.77579446 2.82725318 2.87954614
 2.93324385 2.98501806 3.03468462 3.09422217 3.16071356 3.22057245
 3.27310182 3.32678422 3.38520711]
```



my_x_edges

```
[2.12400496 2.14307285 2.16713147 2.203179 2.25542118 2.32797081  
2.42377446 2.54362306 2.68585652 2.84696932 3.02270427 3.209021  
3.40261866 3.60105122 3.80139375]
```



In []:

```
#Plotting histograms for Phi0
aux_list = [list_par_separated_e1[3],list_par_separated_e2[3], list_par_separated_o1[3],
            list_par_separated_o2[3], list_par_separated_c[3]]

list_times = [exp_entropy1.totaltimes(), exp_entropy2.totaltimes(), exp_on_the_fly1.totaltimes(),
              exp_on_the_fly2.totaltimes(), exp_control.totaltimes()]

names_for_approaches = ["Entropy 1 (Selected)", "Entropy 2 (All)", "On-the fly 1", "On-the fly 2", "Control-45 even"]
par_name = "Phi0"

# specify y-edges for all three histograms
y_min, y_max = MyPlots.finding_max_min(aux_list)
```

```

for i in range(len(aux_list)):
    MyPlots.plotting_hist_logtime(aux_list[i], names_for_approaches[i], par_name, y_mi

#####
#####GMM VERSION COMMENT OUT IF YOU DO NOT HAVE A GMM VERSION

# aux_list = [list_par_separated_e1_gmm[3], list_par_separated_e2_gmm[3], list_par_sep
#             list_par_separated_o2_gmm[3], list_par_separated_c_gmm[3]]


# names_for_approaches = ["Entropy 1 (Selected) GMM", "Entropy 2 (ALL) GMM", "On-the fl
#                         "Control-45 even GMM"]
# par_name = "Phi0"

#
# # specify y-edges for all three histograms
# y_min, y_max = MyPlots.finding_max_min(aux_list)

# for i in range(len(aux_list)):
#     MyPlots.plotting_hist(aux_list[i], names_for_approaches[i], par_name, y_min, y_n


my x edges
[0.44639502 0.95154499 1.31774187 1.50557368 1.63498984 1.71795907
 1.78486836 1.85717012 1.91976715 1.97586794 2.0451627 2.12013424
 2.18994048 2.2492402 2.29414646 2.3421648 2.40906087 2.47615681
 2.52438774 2.58500109 2.64092705 2.68546711 2.73761444 2.79487593
 2.84902418 2.89694222 2.94830773 2.99906035 3.03813744 3.08632006
 3.15194876 3.2115815 3.27638365 3.35067769 3.4246986 ]

```




my_x_edges

```
[0.44639502 0.95154499 1.31774187 1.50557368 1.63606243 1.73391121
 1.82251617 1.91257659 1.98960538 2.06175655 2.12546355 2.18077189
 2.25197971 2.31256712 2.35381257 2.40881159 2.47099297 2.5209696
 2.56429131 2.62088542 2.68566276 2.73918314 2.79101143 2.85499732
 2.91543725 2.96379939 3.00235691 3.05023604 3.104729 3.15233484
 3.20371134 3.26087401 3.3248971 3.39095641]
```




my x edges

```
[0.44639502 0.95154499 1.26735426 1.4206245 1.54658413 1.63740902
 1.73800638 1.81003835 1.87103353 1.93748985 1.99739601 2.05500862
 2.11816231 2.18429427 2.24375376 2.2997706 2.35851198 2.41789218
 2.47571243 2.53402971 2.59109599 2.64816962 2.70529786 2.76190836
 2.81942135 2.86970205 2.9220648 2.9831701 3.04434838 3.10045872
 3.15287884 3.20707604 3.26084244 3.31794559 3.37577641 3.42899673]
```




my_x_edges

```
[0.44639502 0.95154499 1.26955629 1.42428365 1.54881476 1.63878346
 1.73776091 1.83396724 1.9359325 2.03386926 2.10821452 2.16651449
 2.23932464 2.32083876 2.39013092 2.44558157 2.50328623 2.56044612
 2.61624826 2.67388883 2.72590699 2.77579446 2.82725318 2.87954614
 2.93324385 2.98501806 3.03468462 3.09422217 3.16071356 3.22057245
 3.27310182 3.32678422 3.38520711]
```



my x edges

```
[2.12400496 2.14307285 2.16713147 2.203179 2.25542118 2.32797081  
2.42377446 2.54362306 2.68585652 2.84696932 3.02270427 3.209021  
3.40261866 3.60105122 3.80139375]
```



10.3 Entropy V.S Time

```
In [13]: #Notice we could also print the total entropy, instead, of the marginalized entropy.
#On-the-fly always deals with the total entropy. You cannot choose a parameter of interest
times = [exp_entropy1.totaltimes(), exp_on_the_fly1.totaltimes(),
         exp_on_the_fly2.totaltimes(), exp_control.totaltimes(), exp_entropy2.totaltime]

entropies = [exp_entropy1.entropy(), exp_on_the_fly1.entropy(),
            exp_on_the_fly2.entropy(), exp_control.entropy(), exp_entropy2.entropy()]


list_names = ["Entropy 1 ", "On-the-fly 1", "On-the-fly 2", "Control", "Entropy 2"]

MyPlots.plot_entropy_times(times, entropies, list_names, "Total Entropy")

#C1 blue entrop
#C2 yellow on the
#C3 green on the 2
```

```
#C4 red control
#C5 Purple entropy2
```

```
#Total Entropy
```



```
In [14]: #DELETE LATER THIS WORK ONLY IF YOU HAVE A GMM
```

```
#Entropy 1 Comparisson
#Blue fast mvn
#Orange gmm
```

```
# MyPlots.plot_entropy_times([exp_entropy1.totaltimes(), exp_entropy1_gmm.totaltimes()]
#                               [exp_entropy1.entropy(), exp_entropy1_gmm.entropy()])
# plt.savefig("entropy1 total entropy mvn_blue gmm_orange.png")
```

```
In [15]: #DELETE LATER THIS WORK ONLY IF YOU HAVE A GMM
```

```
#Entropy 2 Comparisson
#Blue fast mvn
#Orange gmm
```

```
#COMMENT OUT IF YOU DO NOT HAVE A GMM VERSION
```

```
# MyPlots.plot_entropy_times([exp_entropy2.totaltimes(), exp_entropy2_gmm.totaltimes()]
#                               [exp_entropy2.entropy(), exp_entropy2_gmm.entropy()])
```

```
In [16]: #On the fly Comparisson
#Blue fast mvn
#Orange gmm
```

```
# MyPlots.plot_entropy_times([exp_on_the_fly1.totaltimes(), exp_on_the_fly1_gmm.totaltimes()]
#                                         [exp_on_the_fly1.entropy(), exp_on_the_fly1_gmm.entropy()])
```

In [17]: #On the fly 2- Total Entropy Comparisson
#Blue fast mvn
#Orange gmm

```
# MyPlots.plot_entropy_times([exp_on_the_fly2.totaltimes(), exp_on_the_fly2_gmm.totaltimes()]
#                                         [exp_on_the_fly2.entropy(), exp_on_the_fly2_gmm.entropy()])
```

In []:


In [18]: #Ask REMEMBER THE RETURN OF ENOTROPY_MARG() BC entropy2 does not have a marginal
times = [exp_entropy1.totaltimes(), exp_on_the_fly1.totaltimes(),
 exp_on_the_fly2.totaltimes(), exp_control.totaltimes(), exp_entropy2.totaltimes()]

list_names = ["Entropy 1 ", "On-the-fly 1", "On-the-fly 2", "Control", "Entropy 2"]

#Rememeber that the marginal entropy for entropy2 apporach is the same as total entropy
#is not selecting any parameters. Thus, we calculate here using the select of any of the
#approaches that it must be same.
entro = [calc_entropy(this_pts, select_pars=exp_on_the_fly2.settings.sel,
 options=exp_entropy2.settings.entropy_options)[0] for this_pts in exp_
 _pts]

entropies = [exp_entropy1.entropy_marg(), exp_on_the_fly1.entropy_marg(),
 exp_on_the_fly2.entropy_marg(), exp_control.entropy_marg(), entro]
MyPlots.plot_entropy_times(times, entropies, list_names, "Marginal Entropy(A)")

Marginal Entropy(A)



In [19]: *#DELETE LATER THIS WORK ONLY IF YOU HAVE A GMM*

```
#Entropy 1 Marginal Comparisson
#Blue fast mvn
#Orange gmm
```

```
# MyPlots.plot_entropy_times([exp_entropy1.totaltimes(), exp_entropy1_gmm.totaltimes()]
#                           [exp_entropy1.entropy_marg(), exp_entropy1_gmm.entropy_marg])
```

In [20]: *#Entropy 2- Marginal Comparisson*

```
# #####Comment out unless you have a GMM version
# gmm_setting= {'method': 'gmm', 'n_components': None}
# entro1 = recalculating_entropy(exp_entropy2, exp_on_the_fly2.settings.sel,gmm_setting)
# entro2 = recalculating_entropy(exp_entropy2_gmm, exp_on_the_fly2.settings.sel,gmm_setting)
# #Blue fast mvn
# #Orange gmm
# MyPlots.plot_entropy_times([exp_entropy2.totaltimes(), exp_entropy2_gmm.totaltimes()]
#                           [entro1, entro2])
```

In [21]: *#DELETE LATER THIS WORK ONLY IF YOU HAVE A GMM*

```
#On the fly 1 Marginal Comparisson
#Blue fast mvn
#Orange gmm

#Comment out if you do not have GMM version
```

```
# MyPlots.plot_entropy_times([exp_on_the_fly1.totaltimes(), exp_on_the_fly1_gmm.totalt
#                                         [exp_on_the_fly1.entropy_marg(), exp_on_the_fly1_gmm.entr
```

In [22]: *#DELETE LATER THIS WORK ONLY IF YOU HAVE A GMM*

```
#On the fly 1 Marginal Comparisson
#Blue fast mvn
#Orange gmm
```

```
# MyPlots.plot_entropy_times([exp_on_the_fly2.totaltimes(), exp_on_the_fly2_gmm.totalt
#                                         [exp_on_the_fly2.entropy_marg(), exp_on_the_fly2_gmm.entr
```

Helper Functions for Estimator of PDF and Log-likelihoods

These function will be used in the remaining sections

.....

estimator_avg_at

Note: In my opinion, the estimator_avg_at causes an error in some cases bc at some points of the iteration the values are concentrate around the ground truth. Thus, there are no many points to take on the left or right of the interval. So the checking below alert us!

```
if (left_value_index < 0) or (right_value_index > (NUMBER_SAMPLES - 1)): Alert!
```

"" Note: Notice compute_likelihoods assumes independence of the parameters (columns). It is using David's estimator for pdf. Ask But can we assume that?

""" Notes likelihood_helper_kde:

1. Using KDE to estimate the pdf. Notice that KDE is a non-parametric estimator. However, it assumes independent samples; this could be a problem. Remember each sample is measurement point in the main loop is chosen based in the previous results.
2. Ask about the bandwidth for this function. In the next functions, we use a kde in a single feature (a parameter or a y at a given measurement place); so we can use the std as the bandwidth. We use the std bc all the other methods s.a. silverman or scott gave us terrible estimators. Thus, it may be the case that they are terrible estimators since we are using silverman. In this case, I am using "silverman". Since it is a multidimensional pdf I cannot use just the std. Should I tried to use something similar to the std?
""" #likelihood_helper_kde

10.4 Estimator of Log Likelihoods for the Y's

We will use David's estimator and a multidimensional Kde

Using David's Estimator

In [23]:

```
#all_total_Likelihoods
#At each iteration, we have a y-profiles. We compute the likelihood at each x and add
Sum_likelihoods_at_each_iter_entropy1_for_ys = MyPlots.compute_likelihoods(exp_entropy1,
                                                                           exp_entropy2)
Sum_likelihoods_at_each_iter_entropy2_for_ys = MyPlots.compute_likelihoods(exp_entropy1,
                                                                           exp_entropy2)
Sum_likelihoods_at_each_iter_on_the_fly1_for_ys = MyPlots.compute_likelihoods(exp_on_the_fly1,
                                                                           exp_on_the_fly2)
Sum_likelihoods_at_each_iter_on_the_fly2_for_ys = MyPlots.compute_likelihoods(exp_on_the_fly1,
                                                                           exp_on_the_fly2)


Sum_likelihoods_at_each_iter_control_for_ys = MyPlots.compute_likelihoods(exp_control1,
                                                                           exp_control2)
#Sum_Likelihoods_at_each_iter_control_for_ys = compute_likelihoods(total_yprofs_control)
```

In [24]:


```
MyPlots.plot_likelihood_iterations(5,1, [Sum_likelihoods_at_each_iter_entropy1_for_ys,
                                          Sum_likelihoods_at_each_iter_on_the_fly1_for_ys,
                                          Sum_likelihoods_at_each_iter_on_the_fly2_for_ys,
                                          Sum_likelihoods_at_each_iter_control_for_ys,
                                          Sum_likelihoods_at_each_iter_entropy2_for_ys
                                         ,["Entropy 1 Approach(Selected) Y's-David's Estimator",
                                           "On-the-fly 1 Approach Y's-David's Estimator",
                                           "On-the-fly 2 Approach Y's-David's Estimator",
                                           "Control Approach Y's-David's Estimator",
                                           "Entropy 2 Approach(All) Y's-David's Estimator"]])
```

#REMEMBER: CONTROL TAKES A DIFFERENT NUMBER OF POINTS THAN THE OTHER APPROACHES.

Run Plots



```
In [25]: #Add Later the other apporaches to this plot
#[exp_entropy.totaltimes()[1:], exp_on_the_fly.totaltimes()[1:], exp_control.totaltime
MyPlots.plot_likelihood_time(5,1, [Sum_likelihoods_at_each_iter_entropy1_for_ys,
                                  Sum_likelihoods_at_each_iter_on_the_fly1_for_
                                  Sum_likelihoods_at_each_iter_on_the_fly2_for_
                                  Sum_likelihoods_at_each_iter_control_for_ys,
                                  Sum_likelihoods_at_each_iter_entropy2_for_ys]
                               ,[exp_entropy1.totaltimes(), exp_on_the_fly1.totaltimes(),
                                exp_on_the_fly2.totaltimes(), exp_control.totaltimes(),
                                exp_entropy2.totaltimes()],
                               ["Entropy 1 Approach(Selected) Y's-David's Estimator",
                                "On-the-fly 1 Approach Y's-David'Estimator",
                                "On-the-fly 2 Approach Y's-David'Estimator",
                                "Control Approach Y's-David'Estimator",
                                "Entropy 2 Approach(All) Y's-David's Estimator"])
```



Using Multi-Dimensional KDE

```
In [26]: #all_total_likelihoods
Sum_likelihoods_at_each_iter_entropy1_for_ys_kde = MyPlots.likelihood_helper_kde(exp_en
exp_er)

Sum_likelihoods_at_each_iter_entropy2_for_ys_kde = MyPlots.likelihood_helper_kde(exp_en
exp_er)

Sum_likelihoods_at_each_iter_on_the_fly1_for_ys_kde = MyPlots.likelihood_helper_kde(exp_en
exp_er)


Sum_likelihoods_at_each_iter_on_the_fly2_for_ys_kde = MyPlots.likelihood_helper_kde(exp_en
exp_er)

Sum_likelihoods_at_each_iter_control_for_ys_kde = MyPlots.likelihood_helper_kde(exp_co
exp_cr)


#Sum_likelihoods_at_each_iter_control_for_ys_kde = likelihood_helper_kde(total_yprofs)
```

```
In [27]: #Add later the other approaches to this plot
MyPlots.plot_likelihood_iterations(5,1
    , [Sum_likelihoods_at_each_iter_entropy1_for_ys_kde,
      Sum_likelihoods_at_each_iter_on_the_fly1_for_ys_kde,
      Sum_likelihoods_at_each_iter_on_the_fly2_for_ys_kde,
      Sum_likelihoods_at_each_iter_control_for_ys_kde,
      Sum_likelihoods_at_each_iter_entropy2_for_ys_kde]
    , ["Entropy 1 Approach(Selected) Y's- Joint KDE",
      "On-the-fly 1 Approach Y's-Joint KDE",
      "On-the-fly 2 Approach Y's-Joint KDE",
      "Control Approach Y's-Joint-KDE",
      "Entropy 2 Approach(All) Y's-Joint KDE"])
```

Run Plots



```
In [28]: MyPlots.plot_likelihood_time(5,1)
          ,[Sum_likelihoods_at_each_iter_entropy1_for_ys_kde,
           Sum_likelihoods_at_each_iter_on_the_fly1_for_ys_kde,
           Sum_likelihoods_at_each_iter_on_the_fly2_for_ys_kde,
           Sum_likelihoods_at_each_iter_control_for_ys_kde,
           Sum_likelihoods_at_each_iter_entropy2_for_ys_kde
          ],
          [ exp_entropy1.totaltimes(),
            exp_on_the_fly1.totaltimes(),
            exp_on_the_fly2.totaltimes(),
            exp_control.totaltimes(),
            exp_entropy2.totaltimes()
          ],
          ["Entropy 1 Approach(Selected) Y's-Joint KDE",
           "On-the-fly 1 Approach Y's-Joint KDE",
           "On-the-fly 2 Approach Y's-Joint KDE",
           "Control Approach Y's-Joint KDE",
           "Entropy 2 Approach(All) Y's-Joint KDE"])
```



8.5 Estimator of log-likelihood for the Parameters

The log likelihoods estimator will be computed with two fitting: The log likelihoods are computed for the ground truth values.

We compute the log likelihoods in two ways:

-David's estimator for pdf: by default this estimator calculates the pdf for each parameter separately. It is equivalent to the second fitting in Kde

-Kde estimator for pdf: For the kde we use two approaches. The first fitting will use all the samples for all the parameters at a given iteration

The second fitting will use only the data for one parameter to estimate a pdf of each parameter at a given iteration

David's Estimator for Parameters

In [29]:

```
#all_total_Likelihoods
Sum_likelihoods_at_each_iter_entropy1_for_pars = MyPlots.compute_likelihoods(exp_entropy1_for_pars, exp_entropy1_for_pars, 3)
Sum_likelihoods_at_each_iter_entropy2_for_pars = MyPlots.compute_likelihoods(exp_entropy2_for_pars, exp_entropy2_for_pars, 3)

Sum_likelihoods_at_each_iter_on_the_fly1_for_pars = MyPlots.compute_likelihoods(exp_on_the_fly1_for_pars, exp_on_the_fly1_for_pars, 3)
Sum_likelihoods_at_each_iter_on_the_fly2_for_pars = MyPlots.compute_likelihoods(exp_on_the_fly2_for_pars, exp_on_the_fly2_for_pars, 3)
```


```
Sum_likelihoods_at_each_iter_control_for_pars = MyPlots.compute_likelihoods(exp_contr
                                         exp_cor
                                         3)
#Sum_Likelihoods_at_each_iter_control_for_pars = compute_likelihoods(total_pts_control

ERROR: the ground truth to estimate is too close to one extreme. So, we do not have e
nought samples eitheron the left or right of the ground truth
This is the left index
-2
this is righth index
3
ERROR: the ground truth to estimate is too close to one extreme. So, we do not have e
nought samples eitheron the left or right of the ground truth
This is the left index
-1
this is righth index
4
ERROR: the ground truth to estimate is too close to one extreme. So, we do not have e
nought samples eitheron the left or right of the ground truth
This is the left index
835
this is righth index
840
C:\Users\rober\anaconda3\lib\site-packages\numpy\core\fromnumeric.py:3432: RuntimeWar
ning: Mean of empty slice.
    return _methods._mean(a, axis=axis, dtype=dtype,
C:\Users\rober\anaconda3\lib\site-packages\numpy\core\_methods.py:190: RuntimeWarnin
g: invalid value encountered in double_scalars
    ret = ret.dtype.type(ret / rcount)
```


In [30]:

```
MyPlots.plot_likelihood_iterations(5,1,
                                    [Sum_likelihoods_at_each_iter_entropy1_for_pars,
                                     Sum_likelihoods_at_each_iter_on_the_fly1_for_pars,
                                     Sum_likelihoods_at_each_iter_on_the_fly2_for_pars,
                                     Sum_likelihoods_at_each_iter_control_for_pars,
                                     Sum_likelihoods_at_each_iter_entropy2_for_pars,
                                    ],
                                    ["Entropy 1 Approach All Pars- David's Estimator",
                                     "On-the-fly 1 Approach All Pars- David's Estimator",
                                     "On-the-fly 2 Approach All Pars- David's Estimator",
                                     "Control Approach All Pars- David's Estimator",
                                     "Entropy 2 Approach All Pars- David's Estimator"
                                    ])
#help(plot_Likelihood_iterations)
```

Run Plots



```
In [31]: MyPlots.plot_likelihood_time(5,1,
    [Sum_likelihoods_at_each_iter_entropy1_for_pars,
     Sum_likelihoods_at_each_iter_on_the_fly1_for_pars,
     Sum_likelihoods_at_each_iter_on_the_fly2_for_pars,
     Sum_likelihoods_at_each_iter_control_for_pars,
     Sum_likelihoods_at_each_iter_entropy2_for_pars
    ],
    [exp_entropy1.totaltimes(),
     exp_on_the_fly1.totaltimes(),
     exp_on_the_fly2.totaltimes(),
     exp_control.totaltimes(),
     exp_entropy2.totaltimes()
    ],
    ["Entropy 1 Approach All Pars- David's Estimator",
     "On-the-fly 1 Approach All Pars- David's Estimator",
     "On-the-fly 2 Approach All Pars- David's Estimator",
     "Control Approach All Pars- David's Estimator",
     "Entropy 2 Approach All Pars- David's Estimator"
    ])
```




Multidimensional KDE Estimator for Parameters

Combined Parameters


```
In [32]: #all_total_Likelihoods
Sum_likelihoods_at_each_iter_entropy1_for_pars_kde = MyPlots.likelihood_helper_kde(exp_entropy1.get_t
Sum_likelihoods_at_each_iter_entropy2_for_pars_kde = MyPlots.likelihood_helper_kde(exp_
Sum_likelihoods_at_each_iter_on_the_fly1_for_pars_kde = MyPlots.likelihood_helper_kde(exp_on_the_
Sum_likelihoods_at_each_iter_on_the_fly2_for_pars_kde = MyPlots.likelihood_helper_kde(exp_on_the_
Sum_likelihoods_at_each_iter_control_for_pars_kde = MyPlots.likelihood_helper_kde(exp_on_the_
```

```
In [33]: MyPlots.plot_likelihood_iterations(5,1,
[Sum_likelihoods_at_each_iter_entropy1_for_pars_kde,
Sum_likelihoods_at_each_iter_on_the_fly1_for_pars_kde,
Sum_likelihoods_at_each_iter_on_the_fly2_for_pars_kde,
Sum_likelihoods_at_each_iter_control_for_pars_kde,
Sum_likelihoods_at_each_iter_entropy2_for_pars_kde
]
,[ "Entropy 1(Selected) Approach All Pars- Multi KDE",
"On-the-fly 1 Approach All Pars- Multi KDE",
"On-the-fly 2 Approach All Pars- Multi KDE",
"Control Approach All Pars- Multi KDE",
"Entropy 2(All) Approach All Pars- Multi KDE"
])
```

Run Plots



```
In [34]: MyPlots.plot_likelihood_time(5,1,
    [Sum_likelihoods_at_each_iter_entropy1_for_pars_kde,
     Sum_likelihoods_at_each_iter_on_the_fly1_for_pars_kde,
     Sum_likelihoods_at_each_iter_on_the_fly2_for_pars_kde,
     Sum_likelihoods_at_each_iter_control_for_pars_kde,
     Sum_likelihoods_at_each_iter_entropy2_for_pars_kde
    ],
    [exp_entropy1.totaltimes(),
     exp_on_the_fly1.totaltimes(),
     exp_on_the_fly2.totaltimes(),
     exp_control.totaltimes(),
     exp_entropy2.totaltimes()
    ],
    ["Entropy 1 Approach All Pars- Multi KDE",
     "On-the-fly 1 Approach All Pars- Multi KDE",
     "On-the-fly 2 Approach All Pars- Multi KDE",
     "Control Approach All Pars- Multi KDE",
     "Entropy 2 Approach All Pars- Multi KDE"
    ])
)
```



Separated for each parameter. We will use the kde in the data for each parameter to build independent pdf's for each parameter

```
In [35]: #Example with entropy approach
kdes_entropy1, log_pars_entropy1 = MyPlots.kdes_and_loglikelihoods_for_pars(exp_entropy1.get_true())
exp_entropy1.get_true()

kdes_entropy2, log_pars_entropy2 = MyPlots.kdes_and_loglikelihoods_for_pars(exp_entropy2.get_true())
exp_entropy2.get_true()

#Example with on-the-fly approach
kdes_on_the_fly1, log_pars_on_the_fly1 = MyPlots.kdes_and_loglikelihoods_for_pars(exp_on_the_fly1)
exp_on_the_fly1

kdes_on_the_fly2, log_pars_on_the_fly2 = MyPlots.kdes_and_loglikelihoods_for_pars(exp_on_the_fly2)
exp_on_the_fly2

kdes_control, log_pars_control = MyPlots.kdes_and_loglikelihoods_for_pars(exp_control)
exp_control.get_true()

#####
#Comment out the section below. It makes sense only if you have a GMM version
#####

## #Example with entropy approach
# kdes_entropy1_gmm, log_pars_entropy1_gmm = MyPlots.kdes_and_LogLikelihoods_for_pars(exp_entropy1_gmm.get_true())
# exp_entropy1_gmm.get_true()

# kdes_entropy2_gmm, log_pars_entropy2_gmm = MyPlots.kdes_and_LogLikelihoods_for_pars(exp_entropy2_gmm.get_true())
# exp_entropy2_gmm.get_true()


## #Example with on-the-fly approach
# kdes_on_the_fly1_gmm, log_pars_on_the_fly1_gmm = MyPlots.kdes_and_LogLikelihoods_for_pars(exp_on_the_fly1_gmm.get_true())
# exp_on_the_fly1_gmm.get_true()

# kdes_on_the_fly2_gmm, log_pars_on_the_fly2_gmm = MyPlots.kdes_and_LogLikelihoods_for_pars(exp_on_the_fly2_gmm.get_true())
# exp_on_the_fly2_gmm.get_true()

## kdes_control_gmm, log_pars_control_gmm = MyPlots.kdes_and_LogLikelihoods_for_pars(exp_control_gmm.get_true())
# exp_control_gmm.get_true()
```


```
In [36]: #Adding the loglikelihhods of the parameters at a given iteration
log_sums_kde_separated_iters_entropy1 = np.sum(log_pars_entropy1, axis= 1)
log_sums_kde_separated_iters_entropy2 = np.sum(log_pars_entropy2, axis= 1)
log_sums_kde_sepataed_iters_on_the_fly1 = np.sum(log_pars_on_the_fly1, axis= 1)
log_sums_kde_sepataed_iters_on_the_fly2 = np.sum(log_pars_on_the_fly2, axis= 1)
log_sums_kde_separated_iters_control = np.sum(log_pars_control, axis= 1)
```

```
In [37]: MyPlots.plot_likelihood_iterations(5,1,
                                         [log_sums_kde_separated_iters_entropy1,
                                          log_sums_kde_sepataed_iters_on_the_fly1,
                                          log_sums_kde_sepataed_iters_on_the_fly2 ,
                                          log_sums_kde_separated_iters_control,
                                          log_sums_kde_separated_iters_entropy2],
                                         ["Entropy 1(Selected) Approach All Pars(separated)- KDE",
                                          "On-the-fly 1 Approach All Pars(separated)- KDE",
                                          "On-the-fly 2 Approach All Pars(separated)- KDE",
                                          "Control Approach All Pars(separated)- KDE",
                                          "Entropy 2(All) Approach All Pars(separated)- KDE"])
```



```
In [38]: MyPlots.plot_likelihood_time(4,1,
                                    [log_sums_kde_separated_iters_entropy1,
                                     log_sums_kde_sepataed_iters_on_the_fly1,
                                     log_sums_kde_sepataed_iters_on_the_fly2,
                                     log_sums_kde_separated_iters_control,
                                     log_sums_kde_separated_iters_entropy2],
                                    [exp_entropy1.totaltimes(),
                                     exp_on_the_fly1.totaltimes(),
                                     exp_on_the_fly2.totaltimes(),
                                     exp_control.totaltimes(),
                                     exp_entropy2.totaltimes()],
                                    ["Entropy 1(Selected) Approach All Pars(separated)- KDE",
                                     "On-the-fly 1 Approach All Pars(separated)- KDE",
```

```
"On-the-fly 2 Approach All Pars(separated)- KDE",
"Control Approach All Pars(separated)- KDE",
"Entropy 2(All) Approach All Pars(separated)- KDE"
])
```



Histogram for Parameter Samples

A

1. First we look at the last sample for all the autonomous approaches. 2. Second, we look at the result using GMM



```
In [39]: MyPlots.plot_hist_1d_kde(list_par_separated_e1[0][-1], kdes_entropy1[-1,0],"Entropy 1
plt.show()

MyPlots.plot_hist_1d_kde(list_par_separated_e2[0][-1], kdes_entropy2[-1,0],"Entropy 2
len(exp_entropy2.totaltimes()))
plt.show()


MyPlots.plot_hist_1d_kde(list_par_separated_o1[0][-1], kdes_on_the_fly1[-1,0],"On-the-
len(exp_on_the_fly1.totaltimes()))
plt.show()

MyPlots.plot_hist_1d_kde(list_par_separated_o2[0][-1], kdes_on_the_fly2[-1,0],"On-the-
len(exp_on_the_fly2.totaltimes()))
plt.show()


MyPlots.plot_hist_1d_kde(list_par_separated_c[0][-1], kdes_control[-1,0],"Control MVN"
len(exp_control.totaltimes()))
plt.show()
```




On-the-fly 1 MVN Method, 1-D KDE for A
(iteration 35), Sample Mean: 1.3403, Sample Std: 0.2192



On-the-fly 2 MVN Method, 1-D KDE for A
(iteration 32), Sample Mean: 1.2729, Sample Std: 0.2433



**Control MVN Method, 1-D KDE for A
(iteration 14), Sample Mean: 1.4804, Sample Std: 0.1286**



In [40]: *#DELETE THIS LATER THIS MAKES SENSE ONLY IF YOU HAVE ALSO A GMM VERSION #####*

```

# MyPlots.plot_hist_1d_kde(list_par_separated_e1_gmm[0][-1],
#                           kdes_entropy1_gmm[-1,0], "Entropy 1 GMM", "A",
#                           len(exp_entropy1_gmm.totaltimes()))
# plt.show()

# MyPlots.plot_hist_1d_kde(list_par_separated_e2_gmm[0][-1], kdes_entropy2_gmm[-1,0],
#                           len(exp_entropy2_gmm.totaltimes()))
# plt.show()

# MyPlots.plot_hist_1d_kde(list_par_separated_o1_gmm[0][-1], kdes_on_the_fly1_gmm[-1,0],
#                           len(exp_on_the_fly1_gmm.totaltimes()))
# plt.show()

# MyPlots.plot_hist_1d_kde(list_par_separated_o2_gmm[0][-1], kdes_on_the_fly2_gmm[-1,0],
#                           len(exp_on_the_fly2_gmm.totaltimes()))
# plt.show()

# MyPlots.plot_hist_1d_kde(list_par_separated_c_gmm[0][-1], kdes_control_gmm[-1,0], "Control GMM", "A",
#                           len(exp_control_gmm.totaltimes()))
# plt.show()

```

```
#####
#####
```

Recalculating Entropies for the cases using the GMM

```
In [41]: # entropy1_H_total_gmm = recalculating_entropy(exp_entropy1, None, gmm_setting)
# entropy1_H_marg_gmm = recalculating_entropy(exp_entropy1, exp_entropy1.settings.sel,
#                                              gmm_setting)

# entropy2_H_total_gmm = recalculating_entropy(exp_entropy2, None, gmm_setting)
# entropy2_H_marg_gmm = recalculating_entropy(exp_entropy2, exp_on_the_fly1.settings.sel,
#                                              gmm_setting)

# on_the_fly1_H_total_gmm = recalculating_entropy(exp_on_the_fly1, None, gmm_setting)
# on_the_fly1_H_marg_gmm = recalculating_entropy(exp_on_the_fly1, exp_on_the_fly1.settings.sel,
#                                              gmm_setting)

# on_the_fly2_H_total_gmm = recalculating_entropy(exp_on_the_fly2, None, gmm_setting)
# on_the_fly2_H_marg_gmm = recalculating_entropy(exp_on_the_fly2, exp_on_the_fly2.settings.sel,
#                                              gmm_setting)

# control_H_total_gmm = recalculating_entropy(exp_control, None, gmm_setting)
# control_H_marg_gmm = recalculating_entropy(exp_control, exp_control.settings.sel, gmm_setting)
```

```
In [42]: #Notice we could also print the total entropy, instead, of the marginalized entropy.
#On-thefly always deals with the total entropy. You cannot choose a parameter of interest.

#Using the recalculated entropies using GMM

# times = [exp_entropy1.totaltimes(), exp_on_the_fly1.totaltimes(),
#           exp_on_the_fly2.totaltimes(), exp_control.totaltimes(), exp_entropy2.totaltimes()]
# entropies = [entropy1_H_total_gmm, on_the_fly1_H_total_gmm,
#              on_the_fly2_H_total_gmm, control_H_total_gmm, entropy2_H_total_gmm]
# MyPlots.plot_entropy_times(times, entropies)

#C1 blue entropy
#C2 yellow on the fly
#C3 green on the fly
#C4 red control
#C5 Purple entropy2

#Total Entropy
```

```
In [43]: #####This works only if you have a GMM version

# MyPlots.plot_entropy_times([exp_entropy1.totaltimes(),exp_entropy1.totaltimes()],
#                            [exp_entropy1.entropy(), entropy1_H_total_gmm])

#Blue MVN
#Orange GMM
```

```
In [44]: # MyPlots.plot_entropy_times([exp_entropy2.totaltimes(),exp_entropy2.totaltimes()],
#                            [exp_entropy2.entropy(), entropy2_H_total_gmm])
```

```
#Again undistinguishable
```

```
In [45]: # MyPlots.plot_entropy_times([exp_on_the_fly1.totaltimes(),exp_on_the_fly1.totaltimes()
#                                         [exp_on_the_fly1.entropy(), on_the_fly1_H_total_gmm])
```

```
#Again undistinguishable
```

```
In [46]: # MyPlots.plot_entropy_times([exp_on_the_fly2.totaltimes(),exp_on_the_fly2.totaltimes()
#                                         [exp_on_the_fly2.entropy(), on_the_fly2_H_total_gmm])
```

```
#Again undistinguishable
```

```
In [47]: #Notice we could also print the total entropy, instead, of the marginalized entropy.
#On-thefly always deals with the total entropy. You cannot choose a parameter of inter
```

```
# times = [exp_entropy1.totaltimes(), exp_on_the_fly1.totaltimes(),
#           exp_on_the_fly2.totaltimes(),exp_control.totaltimes(), exp_entropy2.totaltime
# entropies = [entropy1_H_marg_gmm, on_the_fly1_H_marg_gmm,
#              on_the_fly2_H_marg_gmm, control_H_marg_gmm, entropy2_H_marg_gmm]
# MyPlots.plot_entropy_times(times, entropies)
```

```
In [48]: # MyPlots.plot_entropy_times([exp_entropy1.totaltimes(),exp_entropy1.totaltimes()],
#                               [exp_entropy1.entropy_marg(),entropy1_H_marg_gmm ])
```

```
In [49]: # MyPlots.plot_entropy_times([exp_entropy2.totaltimes(),exp_entropy2.totaltimes()],
#                               [exp_entropy2.entropy_marg(),entropy2_H_marg_gmm ])
```

```
In [50]: # MyPlots.plot_entropy_times([exp_on_the_fly1.totaltimes(),exp_on_the_fly1.totaltimes(),
#                               [exp_on_the_fly1.entropy_marg(),on_the_fly1_H_marg_gmm])
```


```
In [51]: # MyPlots.plot_entropy_times([exp_on_the_fly2.totaltimes(),exp_on_the_fly2.totaltimes(),
#                               [exp_on_the_fly2.entropy_marg(),on_the_fly2_H_marg_gmm])
```

End of the Recalculation section


```
In [52]: #Printing the evolution of parameter I for Entropy
#Later do the same for parameter A since that was the parameter selected by entropy
```

```
for i in range(len(exp_entropy1.totaltimes())):
    MyPlots.plot_hist_1d_kde(list_par_separated_e1[0][i], kdes_entropy1[i,0],"Entropy
```


Entropy 1 Method, 1-D KDE for A
(iteration 0), Sample Mean: 27.6859, Sample Std: 16.7827




Entropy 1 Method, 1-D KDE for A
(iteration 1), Sample Mean: 19.9699, Sample Std: 15.7035





Entropy 1 Method, 1-D KDE for A
(iteration 2), Sample Mean: 6.9675, Sample Std: 4.9537




Entropy 1 Method, 1-D KDE for A
(iteration 3), Sample Mean: 7.0346, Sample Std: 3.5849








Entropy 1 Method, 1-D KDE for A
(iteration 6), Sample Mean: 5.8822, Sample Std: 1.7477




Entropy 1 Method, 1-D KDE for A
(iteration 7), Sample Mean: 5.4770, Sample Std: 1.5513







Entropy 1 Method, 1-D KDE for A
(iteration 10), Sample Mean: 3.4915, Sample Std: 1.3632




Entropy 1 Method, 1-D KDE for A
(iteration 11), Sample Mean: 3.5992, Sample Std: 1.1130




Entropy 1 Method, 1-D KDE for A
(iteration 12), Sample Mean: 2.9620, Sample Std: 0.9685




Entropy 1 Method, 1-D KDE for A
(iteration 13), Sample Mean: 3.1899, Sample Std: 0.9814





Entropy 1 Method, 1-D KDE for A
(iteration 14), Sample Mean: 2.9964, Sample Std: 0.9006




Entropy 1 Method, 1-D KDE for A
(iteration 15), Sample Mean: 2.7846, Sample Std: 0.8219







Entropy 1 Method, 1-D KDE for A
(iteration 18), Sample Mean: 2.2326, Sample Std: 0.6187




Entropy 1 Method, 1-D KDE for A
(iteration 19), Sample Mean: 2.3222, Sample Std: 0.5693





Entropy 1 Method, 1-D KDE for A
(iteration 20), Sample Mean: 2.1311, Sample Std: 0.5009




Entropy 1 Method, 1-D KDE for A
(iteration 21), Sample Mean: 2.0255, Sample Std: 0.5083







Entropy 1 Method, 1-D KDE for A
(iteration 24), Sample Mean: 1.8322, Sample Std: 0.3941




Entropy 1 Method, 1-D KDE for A
(iteration 25), Sample Mean: 1.8469, Sample Std: 0.3630




Entropy 1 Method, 1-D KDE for A
(iteration 26), Sample Mean: 1.8031, Sample Std: 0.3488




Entropy 1 Method, 1-D KDE for A
(iteration 27), Sample Mean: 1.7602, Sample Std: 0.3398




Entropy 1 Method, 1-D KDE for A
(iteration 28), Sample Mean: 1.7802, Sample Std: 0.2943




Entropy 1 Method, 1-D KDE for A
(iteration 29), Sample Mean: 1.7389, Sample Std: 0.2551




Entropy 1 Method, 1-D KDE for A
(iteration 30), Sample Mean: 1.7262, Sample Std: 0.2347




Entropy 1 Method, 1-D KDE for A
(iteration 31), Sample Mean: 1.8088, Sample Std: 0.2162



Entropy 1 Method, 1-D KDE for A
(iteration 32), Sample Mean: 1.8469, Sample Std: 0.1836




Entropy 1 Method, 1-D KDE for A
(iteration 33), Sample Mean: 1.7159, Sample Std: 0.1670




In []:


```
In [53]: for i in range(len(exp_entropy2.totaltimes())):
    MyPlots.plot_hist_1d_kde(list_par_separated_e2[0][i], kdes_entropy2[i,0], "Entropy")
```




Entropy 2 Method, 1-D KDE for A
(iteration 1), Sample Mean: 15.6039, Sample Std: 16.2061




Entropy 2 Method, 1-D KDE for A
(iteration 2), Sample Mean: 5.1067, Sample Std: 6.7592




Entropy 2 Method, 1-D KDE for A
(iteration 3), Sample Mean: 2.3321, Sample Std: 1.9475




Entropy 2 Method, 1-D KDE for A
(iteration 4), Sample Mean: 1.9544, Sample Std: 1.5256





Entropy 2 Method, 1-D KDE for A
(iteration 5), Sample Mean: 1.7852, Sample Std: 1.5801




Entropy 2 Method, 1-D KDE for A
(iteration 6), Sample Mean: 1.5617, Sample Std: 1.1251







Entropy 2 Method, 1-D KDE for A
(iteration 9), Sample Mean: 2.4549, Sample Std: 1.0424




Entropy 2 Method, 1-D KDE for A
(iteration 10), Sample Mean: 2.3290, Sample Std: 0.9541




Entropy 2 Method, 1-D KDE for A
(iteration 11), Sample Mean: 2.0440, Sample Std: 0.9582




Entropy 2 Method, 1-D KDE for A
(iteration 12), Sample Mean: 2.5214, Sample Std: 0.8078




Entropy 2 Method, 1-D KDE for A
(iteration 13), Sample Mean: 2.4212, Sample Std: 0.8274




Entropy 2 Method, 1-D KDE for A
(iteration 14), Sample Mean: 2.3609, Sample Std: 0.8076




Entropy 2 Method, 1-D KDE for A
(iteration 15), Sample Mean: 2.0116, Sample Std: 0.7011




Entropy 2 Method, 1-D KDE for A
(iteration 16), Sample Mean: 2.0010, Sample Std: 0.6590




Entropy 2 Method, 1-D KDE for A
(iteration 17), Sample Mean: 1.9661, Sample Std: 0.6143




Entropy 2 Method, 1-D KDE for A
(iteration 18), Sample Mean: 1.9040, Sample Std: 0.5521




Entropy 2 Method, 1-D KDE for A
(iteration 19), Sample Mean: 1.8715, Sample Std: 0.4967




Entropy 2 Method, 1-D KDE for A
(iteration 20), Sample Mean: 1.7877, Sample Std: 0.4650





Entropy 2 Method, 1-D KDE for A
(iteration 21), Sample Mean: 1.7222, Sample Std: 0.4342




Entropy 2 Method, 1-D KDE for A
(iteration 22), Sample Mean: 1.7323, Sample Std: 0.3879







Entropy 2 Method, 1-D KDE for A
(iteration 25), Sample Mean: 1.7930, Sample Std: 0.3716




Entropy 2 Method, 1-D KDE for A
(iteration 26), Sample Mean: 1.7455, Sample Std: 0.3280




Entropy 2 Method, 1-D KDE for A
(iteration 27), Sample Mean: 1.7311, Sample Std: 0.3198




Entropy 2 Method, 1-D KDE for A
(iteration 28), Sample Mean: 1.6214, Sample Std: 0.2723




Entropy 2 Method, 1-D KDE for A
(iteration 29), Sample Mean: 1.6625, Sample Std: 0.2847




Entropy 2 Method, 1-D KDE for A
(iteration 30), Sample Mean: 1.5699, Sample Std: 0.2456



Entropy 2 Method, 1-D KDE for A
(iteration 31), Sample Mean: 1.5498, Sample Std: 0.1844





Entropy 2 Method, 1-D KDE for A
(iteration 32), Sample Mean: 1.6407, Sample Std: 0.1860




```
In [54]: #Printing the evolution of parameter A for On-the-fly 1
for i in range(len(exp_on_the_fly1.totaltimes())):
```


```
MyPlots.plot_hist_1d_kde(list_par_separated_o1[0][i], kdes_on_the_fly1[i,0],"On-the-fly 1 Method, 1-D KDE for A (iteration 0), Sample Mean: 27.5543, Sample Std: 16.4689")
```




On-the-fly 1 Method, 1-D KDE for A
(iteration 2), Sample Mean: 11.9205, Sample Std: 13.7741




On-the-fly 1 Method, 1-D KDE for A
(iteration 3), Sample Mean: 4.6794, Sample Std: 5.1673




On-the-fly 1 Method, 1-D KDE for A
(iteration 4), Sample Mean: 6.3041, Sample Std: 8.3262




On-the-fly 1 Method, 1-D KDE for A
(iteration 5), Sample Mean: 2.2977, Sample Std: 1.7241




On-the-fly 1 Method, 1-D KDE for A
(iteration 6), Sample Mean: 3.3174, Sample Std: 1.9590




On-the-fly 1 Method, 1-D KDE for A
(iteration 7), Sample Mean: 3.7653, Sample Std: 1.8664




On-the-fly 1 Method, 1-D KDE for A
(iteration 8), Sample Mean: 3.1633, Sample Std: 1.4232




On-the-fly 1 Method, 1-D KDE for A
(iteration 9), Sample Mean: 3.4233, Sample Std: 1.4809




On-the-fly 1 Method, 1-D KDE for A
(iteration 10), Sample Mean: 2.8496, Sample Std: 1.3505




On-the-fly 1 Method, 1-D KDE for A
(iteration 11), Sample Mean: 2.7074, Sample Std: 1.2504




On-the-fly 1 Method, 1-D KDE for A
(iteration 12), Sample Mean: 2.4124, Sample Std: 1.0948




On-the-fly 1 Method, 1-D KDE for A
(iteration 13), Sample Mean: 2.8640, Sample Std: 1.1032




On-the-fly 1 Method, 1-D KDE for A
(iteration 14), Sample Mean: 2.5292, Sample Std: 0.9094




On-the-fly 1 Method, 1-D KDE for A
(iteration 15), Sample Mean: 2.4623, Sample Std: 0.8592




On-the-fly 1 Method, 1-D KDE for A
(iteration 16), Sample Mean: 2.4583, Sample Std: 0.8295




On-the-fly 1 Method, 1-D KDE for A
(iteration 17), Sample Mean: 2.4638, Sample Std: 0.7889







On-the-fly 1 Method, 1-D KDE for A
(iteration 18), Sample Mean: 2.1037, Sample Std: 0.7685




On-the-fly 1 Method, 1-D KDE for A
(iteration 19), Sample Mean: 2.1439, Sample Std: 0.7024









On-the-fly 1 Method, 1-D KDE for A
(iteration 24), Sample Mean: 1.7062, Sample Std: 0.4324




On-the-fly 1 Method, 1-D KDE for A
(iteration 25), Sample Mean: 1.6132, Sample Std: 0.4370




On-the-fly 1 Method, 1-D KDE for A
(iteration 26), Sample Mean: 1.5646, Sample Std: 0.3627




On-the-fly 1 Method, 1-D KDE for A
(iteration 27), Sample Mean: 1.5535, Sample Std: 0.3733




On-the-fly 1 Method, 1-D KDE for A
(iteration 28), Sample Mean: 1.4045, Sample Std: 0.3369




On-the-fly 1 Method, 1-D KDE for A
(iteration 29), Sample Mean: 1.4687, Sample Std: 0.2716




On-the-fly 1 Method, 1-D KDE for A
(iteration 30), Sample Mean: 1.4375, Sample Std: 0.2669




On-the-fly 1 Method, 1-D KDE for A
(iteration 31), Sample Mean: 1.3952, Sample Std: 0.2693




On-the-fly 1 Method, 1-D KDE for A
(iteration 32), Sample Mean: 1.4079, Sample Std: 0.2195



On-the-fly 1 Method, 1-D KDE for A
(iteration 33), Sample Mean: 1.3799, Sample Std: 0.2193




On-the-fly 1 Method, 1-D KDE for A
(iteration 34), Sample Mean: 1.3403, Sample Std: 0.2192




```
In [55]: #Printing the evolution of parameter A for On-the-fly 2
for i in range(len(exp_on_the_fly2.totaltimes())):
    MyPlots.plot_hist_1d_kde(list_par_separated_o2[0][i], kdes_on_the_fly2[i,0],"On-the-fly 2")
```


On-the-fly 2 Method, 1-D KDE for A
(iteration 0), Sample Mean: 26.0726, Sample Std: 16.6293




On-the-fly 2 Method, 1-D KDE for A
(iteration 1), Sample Mean: 13.1252, Sample Std: 14.3359





On-the-fly 2 Method, 1-D KDE for A
(iteration 2), Sample Mean: 11.7174, Sample Std: 13.7701




On-the-fly 2 Method, 1-D KDE for A
(iteration 3), Sample Mean: 3.6541, Sample Std: 3.1669







On-the-fly 2 Method, 1-D KDE for A
(iteration 6), Sample Mean: 2.2131, Sample Std: 1.6009




On-the-fly 2 Method, 1-D KDE for A
(iteration 7), Sample Mean: 1.7166, Sample Std: 1.2595




On-the-fly 2 Method, 1-D KDE for A
(iteration 8), Sample Mean: 1.4528, Sample Std: 1.0216




On-the-fly 2 Method, 1-D KDE for A
(iteration 9), Sample Mean: 1.9009, Sample Std: 1.2746




On-the-fly 2 Method, 1-D KDE for A
(iteration 10), Sample Mean: 1.4081, Sample Std: 0.9754




On-the-fly 2 Method, 1-D KDE for A
(iteration 11), Sample Mean: 1.2576, Sample Std: 0.8609




On-the-fly 2 Method, 1-D KDE for A
(iteration 12), Sample Mean: 1.1753, Sample Std: 0.8198




On-the-fly 2 Method, 1-D KDE for A
(iteration 13), Sample Mean: 2.0123, Sample Std: 0.8422




On-the-fly 2 Method, 1-D KDE for A
(iteration 14), Sample Mean: 1.7205, Sample Std: 0.8669




On-the-fly 2 Method, 1-D KDE for A
(iteration 15), Sample Mean: 1.7101, Sample Std: 0.6921




On-the-fly 2 Method, 1-D KDE for A
(iteration 16), Sample Mean: 1.4342, Sample Std: 0.6723




On-the-fly 2 Method, 1-D KDE for A
(iteration 17), Sample Mean: 1.4420, Sample Std: 0.6834




On-the-fly 2 Method, 1-D KDE for A
(iteration 18), Sample Mean: 1.8345, Sample Std: 0.5975




On-the-fly 2 Method, 1-D KDE for A
(iteration 19), Sample Mean: 1.7776, Sample Std: 0.5827




On-the-fly 2 Method, 1-D KDE for A
(iteration 20), Sample Mean: 1.6894, Sample Std: 0.5708




On-the-fly 2 Method, 1-D KDE for A
(iteration 21), Sample Mean: 1.7541, Sample Std: 0.6161




On-the-fly 2 Method, 1-D KDE for A
(iteration 22), Sample Mean: 1.4999, Sample Std: 0.4776




On-the-fly 2 Method, 1-D KDE for A
(iteration 23), Sample Mean: 1.5216, Sample Std: 0.3997




On-the-fly 2 Method, 1-D KDE for A
(iteration 24), Sample Mean: 1.4926, Sample Std: 0.3960




On-the-fly 2 Method, 1-D KDE for A
(iteration 25), Sample Mean: 1.5227, Sample Std: 0.3869




On-the-fly 2 Method, 1-D KDE for A
(iteration 26), Sample Mean: 1.4478, Sample Std: 0.3658




On-the-fly 2 Method, 1-D KDE for A
(iteration 27), Sample Mean: 1.4413, Sample Std: 0.3562




On-the-fly 2 Method, 1-D KDE for A
(iteration 28), Sample Mean: 1.3977, Sample Std: 0.2966




On-the-fly 2 Method, 1-D KDE for A
(iteration 29), Sample Mean: 1.4161, Sample Std: 0.2937



On-the-fly 2 Method, 1-D KDE for A
(iteration 30), Sample Mean: 1.2563, Sample Std: 0.2398



On-the-fly 2 Method, 1-D KDE for A
(iteration 31), Sample Mean: 1.2729, Sample Std: 0.2433



Playground

In []:

In []:

In []:

In []: