NISTIR XXXX Draft

Ongoing Face Recognition Vendor Test (FRVT)

Part 1: Verification

Patrick Grother
Mei Ngan
Kayee Hanaoka
Information Access Division
Information Technology Laboratory

This publication is available free of charge from:
https://www.nist.gov/programs-projects/face-recognition-vendor-test-frvt-ongoing

2020/02/27

National Institute of Standards and Technology
U.S. Department of Commerce

ACKNOWLEDGMENTS

The authors are grateful to staff in the NIST Biometrics Research Laboratory for infrastructure supporting rapid evaluation of algorithms.

DISCLAIMER

Specific hardware and software products identified in this report were used in order to perform the evaluations described in this document. In no case does identification of any commercial product, trade name, or vendor, imply recommendation or endorsement by the National Institute of Standards and Technology, nor does it imply that the products and equipment identified are necessarily the best available for the purpose.

INSTITUTIONAL REVIEW BOARD

The National Institute of Standards and Technology's Research Protections Office reviewed the protocol for this project and determined it is not human subjects research as defined in Department of Commerce Regulations, 15 CFR 27, also known as the Common Rule for the Protection of Human Subjects (45 CFR 46, Subpart A).

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FRVT STATUS

This report is a draft NIST Interagency Report, and is open for comment. It is the sixteenth edition of the report since the first was published in June 2017. Prior editions of this report are maintained on the FRVT website, and may contain useful information about older algorithms and datasets no longer used in FRVT.

FRVT remains open: All four tracks of the FRVT remain open to new algorithm submissions indefinitely. This report will be updated as new algorithms are evaluated, as new datasets are added, and as new analyses are included. Comments and suggestions should be directed to frvt@nist.gov.

Changes since January 20, 2020:

- ▷ The report adds results for five new developers: Ability Enterprise (Andro Video), Chosun University, Fujitsu Research and Development Center, University of Coimbra, and Xforward AI Technology.
- ▷ The report adds results for algorithms from six returning developers: AlphaSSTG, Incode Technologies, Kneron. Shanghai Jiao Tong University, Vocord, and X-Laboratory.
- ▷ We have corrected template comparison timing numbers for algorithms submitted September 2019 to January 2020. The values reported previously were slower due to a software bug.
- ▷ We have dropped results for algorithms from Vocord and Incode per policy to only list results for two algorithms per developer.
- ▷ The FRVT 1:1 homepage has been updated with latest accuracy results.
- ▷ The FRVT 1:N homepage now includes an update to the September 2019 NIST Interagency Report 8271. The new report adds results for one-to-many search algorithms submitted to NIST from June 2019 to January 2020.

Changes since January 6, 2020:

- ▷ Section 2 has been updated to better describe the Visa and Border images. The caption for Table 10 has been updated to better relate the accuracy values to particular image comparisons.
- ▷ The report adds results for five new developers: Acer, Advance.AI, Expasoft, Netbridge Technology, and Videmo Intelligente Videoanalyse.
- ▷ The report adds results for algorithms from 7 returning developers: China Electronics Import-Export Corp, Intel Research Group, ITMO University, Neurotechnology, N-Tech Lab, Rokid, and VisionLabs.
- ▷ We have dropped results from this edition of the report per policy to only list results for two algorithms per developer: N-Tech Lab, Neurotechnology, ITMO, Visionlabs, and CEIEC.
- ▷ The FRVT homepage has been updated with latest accuracy results.

Changes since November 11, 2019:

- ▷ Table 5 has been updated to include runtime memory usage. This is the first time such a quantity has been reported. The value is the peak size of the resident set size logged during enrollment of single images.
- ▷ We have migrated summary results table to a new platform that supports sortable tables: https://pages.nist.gov/frvt/html/frvt11.html
- ▷ The report adds results for four new developers: Antheus Technologia, BioID Technologies SA, Canon Information Tech. (Beijing), Samsung S1 (listed in the tables as S1), and Taiwan AI Labs.

- ▷ The report adds results for algorithms from 13 returning developers: Anke Investments, Chunghwa Telecom, Deepglint, Institute of Information Technologies, iQIYI, Kneron, Ping An Technology, Paravision, KanKan Ai, Rokid Corporation, Shanghai Universiy - Shanghai Film Academy, Veridas Digital Authentication Solutions, and Videonetics Technology.
- ▷ We have dropped results from this edition of the report per policy to only list results for two algorithms per developer: remarkai-000, veridas-001, sensetime-001, iit-000, anke-003, and everai-002. Results for these are available in prior editions of this report linked from the FRVT page.
- ▷ We issued NIST Interagency Report 8280: FRVT Part 3: Demographics on 2019-12-19. It includes results for many of the algorithms covered by this report.

Changes since October 16, 2019:

- ▷ The report adds results for ten new developers: Ai-Union Technology, ASUSTek Computer, DiDi ChuXing Technology, Innovative Technology, Luxand, MVision, Pyramid Cyber Security + Forensic, Scanovate, Shenzhen AiMall Tech, and TUPU Technology.
- ▷ The report adds results for 12 returning developers: CTBC Bank Glory Gorilla Technology Guangzhou Pixel Solutions Imagus Technology Incode Technologies Lomonosov Moscow State University Rank One Computing Samtech InfoNet Shanghai Ulucu Electronics Technology Synesis, and Winsense.
- ▷ We have dropped results from this edition of the report per policy to only list results for two algorithms per developer: glory-000, gorilla-002, incode-003, rankone-006, and synesis-004.
- ▷ Results for five recently submitted algorithms will appear in the next report.

Changes since September 11, 2019:

- ▷ The report adds results for five new participants: Awidit Systems (Awiros), Momemtum Digital (Sertis), Trueface AI, Shanghai Jiao Tong University, and X-Laboratory.
- ▷ The reports adds results for five new algorithms from returning developers: Cyberlink, Hengrui AI Technology, Idemia, Panasonic R+D Singapore, and Tevian. This causes three algorithm, to be de-listed from the report per policy to list results for two algorithms per developer.

Changes since July 31 2019:

- ▷ The HTML table on the FRVT 1:1 homepage has been updated to include a column for cross-domain Visa-Border verification. Results for this new dataset appeared in the July 29 report under the name "CrossEV" - these are now renamed "Visa-Border".
- ▷ The FRVT 1:1 homepage lists algorithms according to lowest mean rank accuracy:
  Rank($\text{FNMR}_{\text{VISA}}$ at FMR = 0.000001) +
  Rank($\text{FNMR}_{\text{VISA-BORDER}}$ at FMR = 0.000001) +
  Rank($\text{FNMR}_{\text{MUGSHOT}}$ at FMR = 0.00001 after 14 years) +
  Rank($\text{FNMR}_{\text{WILD}}$ at FMR = 0.00001)
  This ordering rewards high accuracy across all datasets.
- ▷ The main results in Table 10 is now in landscape format to accomodate extra columns for the Visa-Border set, and mugshot comparisons after at least 12 years.
- ▷ The report adds results for nine new participants: Alpha SSTG, Intel Research, ULSee, Chungwa Telecon, iSAP Solution, Rokid, Shenzhen EI Networks, CSA Intellicloud, Shenzhen Intellifusion Technologies.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

- ▷ The reports adds results for six new algorithms from returning developers: Innovatrics, Dahua Technology, Tech5 SA, Intellivision, Nodeflux and Imperial College, London. One algorithm, from Imperial has been retired, per policy to list results for two algorithms per developer.
- ▷ The cross-country false match rate heatmaps starting from Figure 375 have been replotted to reveal more structure by listing countries by region instead of alphabetically.
- ▷ The next version of this report will be posted around October 18, 2019.

Changes since July 3 2019:

- ▷ The HTML table on the FRVT 1:1 homepage has been updated to list the 20 most accurate developers rather than algorithms, choosing the most accurate algorithm from each developer based on visa and mugshot results. Also, the algorithms are ordered in terms of lowest mean rank across mugshot, visa and wild datasets, rewarding broad accuracy over a good result on one particular dataset.
- ▷ This report includes results for a new dataset - see the column labelled "visa-border" in Table 5. It compares a new set of high quality visa-like portraits with a set webcam border-crossing photos that exhibit moderately poor pose variations and background illumination. The two new sets are described in sections 2.3 and 2.4. The comparisons are "cross-domain" in that the algorithm must compare "visa" and "wild" images. Results for other algorithms will be added in future reports as they become available.
- ▷ This report adds results for algorithms from 9 developers submitted in early July 2019. These are from 3DiVi, Camvi, EverAI-Paravision, Facesoft, Farbar (F8), Institute of Information Technologies, Shanghai U. Film Academy, Via Technologies, and Ulucu Electronics Tech. Six of these are new participants.
- ▷ Several other algorithms have been submitted and are being evaluated. Results will be released in the next report, scheduled for September 5. That report will include results for new datasets.
- ▷ Older algorithms from Everai, Camvi and 3DiVi, have been retired, per the policy to list only two algorithms per developer.

Changes since June 20 2019:

- ▷ This report adds results for algorithms from 18 developers submitted in early June 2019. These are from CTBC Bank, Deep Glint, Thales Cogent, Ever AI Paravision, Gorilla Technology, Imagus, Incode, Kneron, N-Tech Lab, Neurotechnology, Notiontag Technologies, Star Hybrid, Videonetics, Vigilant Solutions, Winsense, Anke Investments, CEIEC, and DSK. Nine of these are new participants.
- ▷ Several other algorithms have been submitted and are being evaluated. Results will be released in the next report, scheduled for August 1.
- ▷ Older algorithms from Everai, Thales Cogent, Gorilla Technology, Incode, Neurotechnology, N-Tech Lab and Vigilant Solutions have been retired, per the policy to list only two algorithms per developer.

Changes since April 2019:

- ▷ This report adds results for nine algorithms from nine developers submitted in early June 2019. These are from Tencent Deepsea, Hengrui, Kedacom, Moontime, Guangzhou Pixel, Rank One Computing, Synesis, Sensetime and Vocord.
- ▷ Another 23 algorithms have been submitted and are being evaluated. Results will be released in the next report, scheduled for July 3.
- ▷ Older algorithms for Rank One, Synesis, and Vocord have been retired, per the policy to list only two algorithms per developer.

Changes since February 2019:

- ▷ This report adds results for 49 algorithms from 42 developers submitted in early March 2019.

- ▷ This report omits results for algorithms that we retired. We retired for three reasons: 1. The developer submitted a new algorithm, and we only list two. 2. The algorithm needs a GPU, and we no longer allow GPU-based algorithms. 3. Inoperable algorithms.
- ▷ Previous results for retired algorithms are available in older editions of this report linked here.
- ▷ The mugshot database used from February 2017 to January 2019 has been replaced with an extract of the mugshot database documented in NIST Interagency Report 8238, November 2018. The new mugshot set is described in section 2.5 and is adopted because:
  - ▷▷ It has much better identity label integrity, so that false non-match rates are substantially lower than those reported in FRVT 1:1 reports to date - see Figure 42.
  - ▷▷ It includes images collected over a 17 year period such that ageing can be much better characterized - - see Figure 157.
- ▷ Using the new mugshot database, Figure 157 shows accuracy for four demographic groups identified in the biographic metadata that accompanies the data: black females, black males, white females and white males.
- ▷ The report adds Figure 12 with results for the twenty human-difficult pairs used in the May 2018 paper *Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms* by Phillips et al. [1].
- ▷ The report uses an update to the wild image database that corrects some ground truth labels.
- ▷ Some results for the child exploitation database are not complete. They are typically updated less frequently than for other image sets.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Contents

ACKNOWLEDGMENTS 1

DISCLAIMER 1

INSTITUTIONAL REVIEW BOARD 1

1 METRICS 33
1.1 CORE ACCURACY . . . 33

2 DATASETS 34
2.1 CHILD EXPLOITATION IMAGES . . . 34
2.2 VISA IMAGES . . . 34
2.3 APPLICATION IMAGES . . . 34
2.4 BORDER CROSSING IMAGES . . . 35
2.5 MUGSHOT IMAGES . . . 35
2.6 WILD IMAGES . . . 36

3 RESULTS 36
3.1 TEST GOALS . . . 36
3.2 TEST DESIGN . . . 36
3.3 FAILURE TO ENROLL . . . 39
3.4 RECOGNITION ACCURACY . . . 44
3.5 GENUINE DISTRIBUTION STABILITY . . . 170
3.5.1 EFFECT OF BIRTH PLACE ON THE GENUINE DISTRIBUTION . . . 170
3.5.2 EFFECT OF AGEING . . . 188
3.5.3 EFFECT OF AGE ON GENUINE SUBJECTS . . . 201
3.6 IMPOSTOR DISTRIBUTION STABILITY . . . 220
3.6.1 EFFECT OF BIRTH PLACE ON THE IMPOSTOR DISTRIBUTION . . . 220
3.6.2 EFFECT OF AGE ON IMPOSTORS . . . 615

List of Tables

1 ALGORITHM SUMMARY . . . 21
2 ALGORITHM SUMMARY . . . 22
3 ALGORITHM SUMMARY . . . 23
4 ALGORITHM SUMMARY . . . 24
5 ALGORITHM SUMMARY . . . 25
6 FALSE NON-MATCH RATE . . . 26
7 FALSE NON-MATCH RATE . . . 27
8 FALSE NON-MATCH RATE . . . 28
9 FALSE NON-MATCH RATE . . . 29
10 FALSE NON-MATCH RATE . . . 30
11 FAILURE TO ENROL RATES . . . 40
12 FAILURE TO ENROL RATES . . . 41
13 FAILURE TO ENROL RATES . . . 42
14 FAILURE TO ENROL RATES . . . 43

List of Figures

1 PERFORMANCE SUMMARY: FNMR VS. TEMPLATE SIZE TRADEOFF . . . 31
2 PERFORMANCE SUMMARY: FNMR VS. TEMPLATE TIME TRADEOFF . . . 32

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3 EXAMPLE IMAGES . . . 36
(A) VISA . . . 36
(B) MUGSHOT . . . 36
(C) WILD . . . 36
(D) BORDER (FROM VISABORDER) . . . 36
4 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 45
5 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 46
6 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 47
7 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 48
8 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 49
9 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 50
10 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 51
11 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 52
12 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 53
13 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 54
14 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 55
15 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 56
16 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 57
17 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 58
18 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 59
19 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 60
20 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 61
21 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 62
22 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 63
23 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 64
24 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 65
25 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 66
26 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 67
27 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 68
28 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 69
29 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 70
30 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 71
31 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 72
32 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 73
33 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 74
34 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 75
35 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 76
36 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 77
37 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 78
38 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 79
39 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 80
40 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 81
41 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 82
42 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 83
43 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 84
44 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 85
45 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 86
46 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 87
47 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 88
48 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 89
49 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 90
50 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 91
51 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 92
52 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 93
53 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 94
54 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 95

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

55 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 96
56 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 97
57 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 98
58 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 99
59 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 100
60 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 101
61 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 102
62 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 103
63 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 104
64 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 105
65 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 106
66 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 107
67 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 108
68 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 109
69 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 110
70 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 111
71 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 112
72 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 113
73 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 114
74 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 115
75 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 116
76 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 117
77 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 118
78 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 119
79 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 120
80 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 121
81 SEX EFFECTS: VISA IMAGES . . . 122
82 SEX EFFECTS: VISA IMAGES . . . 123
83 SEX EFFECTS: VISA IMAGES . . . 124
84 SEX EFFECTS: VISA IMAGES . . . 125
85 SEX EFFECTS: VISA IMAGES . . . 126
86 SEX EFFECTS: VISA IMAGES . . . 127
87 SEX EFFECTS: VISA IMAGES . . . 128
88 SEX EFFECTS: VISA IMAGES . . . 129
89 SEX EFFECTS: VISA IMAGES . . . 130
90 SEX EFFECTS: VISA IMAGES . . . 131
91 SEX EFFECTS: VISA IMAGES . . . 132
92 SEX EFFECTS: VISA IMAGES . . . 133
93 SEX EFFECTS: VISA IMAGES . . . 134
94 SEX EFFECTS: VISA IMAGES . . . 135
95 SEX EFFECTS: VISA IMAGES . . . 136
96 SEX EFFECTS: VISA IMAGES . . . 137
97 SEX EFFECTS: VISA IMAGES . . . 138
98 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 139
99 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 140
100 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 141
101 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 142
102 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 143
103 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 144
104 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 145
105 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 146
106 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 147
107 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 148
108 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 149
109 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 150
110 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 151

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

111 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 152
112 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 153
113 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 154
114 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 155
115 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 156
116 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 157
117 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 158
118 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 159
119 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 160
120 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 161
121 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 162
122 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 163
123 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 164
124 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 165
125 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 166
126 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 167
127 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 168
128 FALSE MATCH RATE CONCENTRATION: VISA IMAGES . . . 169
129 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 171
130 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 172
131 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 173
132 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 174
133 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 175
134 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 176
135 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 177
136 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 178
137 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 179
138 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 180
139 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 181
140 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 182
141 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 183
142 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 184
143 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 185
144 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 186
145 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 187
146 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 189
147 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 190
148 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 191
149 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 192
150 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 193
151 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 194
152 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 195
153 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 196
154 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 197
155 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 198
156 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 199
157 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 200
158 EFFECT OF SUBJECT AGE ON FNMR . . . 202
159 EFFECT OF SUBJECT AGE ON FNMR . . . 203
160 EFFECT OF SUBJECT AGE ON FNMR . . . 204
161 EFFECT OF SUBJECT AGE ON FNMR . . . 205
162 EFFECT OF SUBJECT AGE ON FNMR . . . 206
163 EFFECT OF SUBJECT AGE ON FNMR . . . 207
164 EFFECT OF SUBJECT AGE ON FNMR . . . 208
165 EFFECT OF SUBJECT AGE ON FNMR . . . 209
166 EFFECT OF SUBJECT AGE ON FNMR . . . 210

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

167 EFFECT OF SUBJECT AGE ON FNMR . . . 211
168 EFFECT OF SUBJECT AGE ON FNMR . . . 212
169 EFFECT OF SUBJECT AGE ON FNMR . . . 213
170 EFFECT OF SUBJECT AGE ON FNMR . . . 214
171 EFFECT OF SUBJECT AGE ON FNMR . . . 215
172 EFFECT OF SUBJECT AGE ON FNMR . . . 216
173 EFFECT OF SUBJECT AGE ON FNMR . . . 217
174 EFFECT OF SUBJECT AGE ON FNMR . . . 218
175 WORST CASE REGIONAL EFFECT FNMR . . . 221
176 IMPOSTOR DISTRIBUTION SHIFTS FOR SELECT COUNTRY PAIRS . . . 223
177 ALGORITHM 3DIVI-003 CROSS REGION FMR . . . 224
178 ALGORITHM 3DIVI-004 CROSS REGION FMR . . . 225
179 ALGORITHM ACER-000 CROSS REGION FMR . . . 226
180 ALGORITHM ADERA-001 CROSS REGION FMR . . . 227
181 ALGORITHM ADVANCE-002 CROSS REGION FMR . . . 228
182 ALGORITHM AIFIRST-001 CROSS REGION FMR . . . 229
183 ALGORITHM AILABS-001 CROSS REGION FMR . . . 230
184 ALGORITHM AIMALL-001 CROSS REGION FMR . . . 231
185 ALGORITHM AIUNIONFACE-000 CROSS REGION FMR . . . 232
186 ALGORITHM ALCHERA-000 CROSS REGION FMR . . . 233
187 ALGORITHM ALCHERA-001 CROSS REGION FMR . . . 234
188 ALGORITHM ALLGOVISION-000 CROSS REGION FMR . . . 235
189 ALGORITHM ALPHAFACE-001 CROSS REGION FMR . . . 236
190 ALGORITHM ALPHAFACE-002 CROSS REGION FMR . . . 237
191 ALGORITHM AMPLIFIEDGROUP-001 CROSS REGION FMR . . . 238
192 ALGORITHM ANDROVIDEO-000 CROSS REGION FMR . . . 239
193 ALGORITHM ANKE-004 CROSS REGION FMR . . . 240
194 ALGORITHM ANKE-005 CROSS REGION FMR . . . 241
195 ALGORITHM ANTHEUS-000 CROSS REGION FMR . . . 242
196 ALGORITHM ANYVISION-002 CROSS REGION FMR . . . 243
197 ALGORITHM ANYVISION-004 CROSS REGION FMR . . . 244
198 ALGORITHM ASUSAICS-000 CROSS REGION FMR . . . 245
199 ALGORITHM AWARE-003 CROSS REGION FMR . . . 246
200 ALGORITHM AWARE-004 CROSS REGION FMR . . . 247
201 ALGORITHM AWIROS-001 CROSS REGION FMR . . . 248
202 ALGORITHM AYONIX-000 CROSS REGION FMR . . . 249
203 ALGORITHM BIOIDTECHSWISS-000 CROSS REGION FMR . . . 250
204 ALGORITHM BM-001 CROSS REGION FMR . . . 251
205 ALGORITHM CAMVI-002 CROSS REGION FMR . . . 252
206 ALGORITHM CAMVI-004 CROSS REGION FMR . . . 253
207 ALGORITHM CEIEC-002 CROSS REGION FMR . . . 254
208 ALGORITHM CEIEC-003 CROSS REGION FMR . . . 255
209 ALGORITHM CHOSUN-000 CROSS REGION FMR . . . 256
210 ALGORITHM CHTFACE-001 CROSS REGION FMR . . . 257
211 ALGORITHM CHTFACE-002 CROSS REGION FMR . . . 258
212 ALGORITHM CIB-000 CROSS REGION FMR . . . 259
213 ALGORITHM COGENT-003 CROSS REGION FMR . . . 260
214 ALGORITHM COGENT-004 CROSS REGION FMR . . . 261
215 ALGORITHM COGNITEC-000 CROSS REGION FMR . . . 262
216 ALGORITHM COGNITEC-001 CROSS REGION FMR . . . 263
217 ALGORITHM CTBCBANK-000 CROSS REGION FMR . . . 264
218 ALGORITHM CTBCBANK-001 CROSS REGION FMR . . . 265
219 ALGORITHM CYBEREXTRUDER-001 CROSS REGION FMR . . . 266
220 ALGORITHM CYBEREXTRUDER-002 CROSS REGION FMR . . . 267
221 ALGORITHM CYBERLINK-002 CROSS REGION FMR . . . 268
222 ALGORITHM CYBERLINK-003 CROSS REGION FMR . . . 269

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

223 ALGORITHM DAHUA-003 CROSS REGION FMR . . . 270
224 ALGORITHM DAHUA-004 CROSS REGION FMR . . . 271
225 ALGORITHM DEEPGLINT-001 CROSS REGION FMR . . . 272
226 ALGORITHM DEEPGLINT-002 CROSS REGION FMR . . . 273
227 ALGORITHM DEEPSEA-001 CROSS REGION FMR . . . 274
228 ALGORITHM DERMALOG-005 CROSS REGION FMR . . . 275
229 ALGORITHM DERMALOG-006 CROSS REGION FMR . . . 276
230 ALGORITHM DIDIGLOBALFACE-001 CROSS REGION FMR . . . 277
231 ALGORITHM DIGITALBARRIERS-002 CROSS REGION FMR . . . 278
232 ALGORITHM DSK-000 CROSS REGION FMR . . . 279
233 ALGORITHM EINETWORKS-000 CROSS REGION FMR . . . 280
234 ALGORITHM EXPASOFT-000 CROSS REGION FMR . . . 281
235 ALGORITHM F8-001 CROSS REGION FMR . . . 282
236 ALGORITHM FACESOFT-000 CROSS REGION FMR . . . 283
237 ALGORITHM FUJITSULAB-000 CROSS REGION FMR . . . 284
238 ALGORITHM GLORY-001 CROSS REGION FMR . . . 285
239 ALGORITHM GLORY-002 CROSS REGION FMR . . . 286
240 ALGORITHM GORILLA-003 CROSS REGION FMR . . . 287
241 ALGORITHM GORILLA-004 CROSS REGION FMR . . . 288
242 ALGORITHM HIK-001 CROSS REGION FMR . . . 289
243 ALGORITHM HR-001 CROSS REGION FMR . . . 290
244 ALGORITHM HR-002 CROSS REGION FMR . . . 291
245 ALGORITHM ID3-003 CROSS REGION FMR . . . 292
246 ALGORITHM ID3-004 CROSS REGION FMR . . . 293
247 ALGORITHM IDEMIA-004 CROSS REGION FMR . . . 294
248 ALGORITHM IDEMIA-005 CROSS REGION FMR . . . 295
249 ALGORITHM IIT-001 CROSS REGION FMR . . . 296
250 ALGORITHM IIT-002 CROSS REGION FMR . . . 297
251 ALGORITHM IMAGUS-000 CROSS REGION FMR . . . 298
252 ALGORITHM IMAGUS-001 CROSS REGION FMR . . . 299
253 ALGORITHM IMPERIAL-000 CROSS REGION FMR . . . 300
254 ALGORITHM IMPERIAL-002 CROSS REGION FMR . . . 301
255 ALGORITHM INCODE-005 CROSS REGION FMR . . . 302
256 ALGORITHM INCODE-006 CROSS REGION FMR . . . 303
257 ALGORITHM INNOVATIVETECHNOLOGYLTD-001 CROSS REGION FMR . . . 304
258 ALGORITHM INNOVATRICS-004 CROSS REGION FMR . . . 305
259 ALGORITHM INNOVATRICS-006 CROSS REGION FMR . . . 306
260 ALGORITHM INTELLICLOUDAI-001 CROSS REGION FMR . . . 307
261 ALGORITHM INTELLIFUSION-001 CROSS REGION FMR . . . 308
262 ALGORITHM INTELLIVISION-001 CROSS REGION FMR . . . 309
263 ALGORITHM INTELLIVISION-002 CROSS REGION FMR . . . 310
264 ALGORITHM INTELRESEARCH-000 CROSS REGION FMR . . . 311
265 ALGORITHM INTELRESEARCH-001 CROSS REGION FMR . . . 312
266 ALGORITHM INTSYSMSU-000 CROSS REGION FMR . . . 313
267 ALGORITHM INTSYSMSU-001 CROSS REGION FMR . . . 314
268 ALGORITHM IQFACE-000 CROSS REGION FMR . . . 315
269 ALGORITHM IQFACE-001 CROSS REGION FMR . . . 316
270 ALGORITHM ISAP-001 CROSS REGION FMR . . . 317
271 ALGORITHM ISITYOU-000 CROSS REGION FMR . . . 318
272 ALGORITHM ISYSTEMS-001 CROSS REGION FMR . . . 319
273 ALGORITHM ISYSTEMS-002 CROSS REGION FMR . . . 320
274 ALGORITHM ITMO-006 CROSS REGION FMR . . . 321
275 ALGORITHM ITMO-007 CROSS REGION FMR . . . 322
276 ALGORITHM KAKAO-001 CROSS REGION FMR . . . 323
277 ALGORITHM KAKAO-002 CROSS REGION FMR . . . 324
278 ALGORITHM KEDACOM-000 CROSS REGION FMR . . . 325

279 ALGORITHM KNERON-003 CROSS REGION FMR . . . 326
280 ALGORITHM KNERON-005 CROSS REGION FMR . . . 327
281 ALGORITHM LOOKMAN-002 CROSS REGION FMR . . . 328
282 ALGORITHM LOOKMAN-004 CROSS REGION FMR . . . 329
283 ALGORITHM LUXAND-000 CROSS REGION FMR . . . 330
284 ALGORITHM MEGVII-001 CROSS REGION FMR . . . 331
285 ALGORITHM MEGVII-002 CROSS REGION FMR . . . 332
286 ALGORITHM MEIYA-001 CROSS REGION FMR . . . 333
287 ALGORITHM MICROFOCUS-001 CROSS REGION FMR . . . 334
288 ALGORITHM MICROFOCUS-002 CROSS REGION FMR . . . 335
289 ALGORITHM MT-000 CROSS REGION FMR . . . 336
290 ALGORITHM MVISION-001 CROSS REGION FMR . . . 337
291 ALGORITHM NETBRIDGETECH-001 CROSS REGION FMR . . . 338
292 ALGORITHM NEUROTECHNOLOGY-006 CROSS REGION FMR . . . 339
293 ALGORITHM NEUROTECHNOLOGY-008 CROSS REGION FMR . . . 340
294 ALGORITHM NODEFLUX-001 CROSS REGION FMR . . . 341
295 ALGORITHM NODEFLUX-002 CROSS REGION FMR . . . 342
296 ALGORITHM NOTIONTAG-000 CROSS REGION FMR . . . 343
297 ALGORITHM NTECHLAB-007 CROSS REGION FMR . . . 344
298 ALGORITHM NTECHLAB-008 CROSS REGION FMR . . . 345
299 ALGORITHM PARAVISION-004 CROSS REGION FMR . . . 346
300 ALGORITHM PIXELALL-002 CROSS REGION FMR . . . 347
301 ALGORITHM PIXELALL-003 CROSS REGION FMR . . . 348
302 ALGORITHM PSL-002 CROSS REGION FMR . . . 349
303 ALGORITHM PSL-003 CROSS REGION FMR . . . 350
304 ALGORITHM PYRAMID-000 CROSS REGION FMR . . . 351
305 ALGORITHM RANKONE-007 CROSS REGION FMR . . . 352
306 ALGORITHM RANKONE-008 CROSS REGION FMR . . . 353
307 ALGORITHM REALNETWORKS-002 CROSS REGION FMR . . . 354
308 ALGORITHM REALNETWORKS-003 CROSS REGION FMR . . . 355
309 ALGORITHM REMARKAI-001 CROSS REGION FMR . . . 356
310 ALGORITHM REMARKAI-002 CROSS REGION FMR . . . 357
311 ALGORITHM ROKID-000 CROSS REGION FMR . . . 358
312 ALGORITHM ROKID-001 CROSS REGION FMR . . . 359
313 ALGORITHM S1-001 CROSS REGION FMR . . . 360
314 ALGORITHM SAFFE-001 CROSS REGION FMR . . . 361
315 ALGORITHM SAFFE-002 CROSS REGION FMR . . . 362
316 ALGORITHM SAMTECH-001 CROSS REGION FMR . . . 363
317 ALGORITHM SCANOVATE-001 CROSS REGION FMR . . . 364
318 ALGORITHM SENSETIME-002 CROSS REGION FMR . . . 365
319 ALGORITHM SENSETIME-003 CROSS REGION FMR . . . 366
320 ALGORITHM SERTIS-000 CROSS REGION FMR . . . 367
321 ALGORITHM SHAMAN-000 CROSS REGION FMR . . . 368
322 ALGORITHM SHAMAN-001 CROSS REGION FMR . . . 369
323 ALGORITHM SHU-001 CROSS REGION FMR . . . 370
324 ALGORITHM SHU-002 CROSS REGION FMR . . . 371
325 ALGORITHM SIAT-002 CROSS REGION FMR . . . 372
326 ALGORITHM SIAT-004 CROSS REGION FMR . . . 373
327 ALGORITHM SJTU-001 CROSS REGION FMR . . . 374
328 ALGORITHM SJTU-002 CROSS REGION FMR . . . 375
329 ALGORITHM SMILART-002 CROSS REGION FMR . . . 376
330 ALGORITHM SMILART-003 CROSS REGION FMR . . . 377
331 ALGORITHM STARHYBRID-001 CROSS REGION FMR . . . 378
332 ALGORITHM SYNESIS-005 CROSS REGION FMR . . . 379
333 ALGORITHM SYNESIS-006 CROSS REGION FMR . . . 380
334 ALGORITHM SYNOLOGY-000 CROSS REGION FMR . . . 381

335 ALGORITHM TECH5-002 CROSS REGION FMR . . . 382
336 ALGORITHM TECH5-003 CROSS REGION FMR . . . 383
337 ALGORITHM TEVIAN-004 CROSS REGION FMR . . . 384
338 ALGORITHM TEVIAN-005 CROSS REGION FMR . . . 385
339 ALGORITHM TIGER-002 CROSS REGION FMR . . . 386
340 ALGORITHM TIGER-003 CROSS REGION FMR . . . 387
341 ALGORITHM TONGYI-005 CROSS REGION FMR . . . 388
342 ALGORITHM TOSHIBA-002 CROSS REGION FMR . . . 389
343 ALGORITHM TOSHIBA-003 CROSS REGION FMR . . . 390
344 ALGORITHM TRUEFACE-000 CROSS REGION FMR . . . 391
345 ALGORITHM TUPUTECH-000 CROSS REGION FMR . . . 392
346 ALGORITHM ULSEE-001 CROSS REGION FMR . . . 393
347 ALGORITHM ULUFACE-002 CROSS REGION FMR . . . 394
348 ALGORITHM ULUFACE-003 CROSS REGION FMR . . . 395
349 ALGORITHM UPC-001 CROSS REGION FMR . . . 396
350 ALGORITHM VCOG-002 CROSS REGION FMR . . . 397
351 ALGORITHM VD-001 CROSS REGION FMR . . . 398
352 ALGORITHM VERIDAS-002 CROSS REGION FMR . . . 399
353 ALGORITHM VERIDAS-003 CROSS REGION FMR . . . 400
354 ALGORITHM VIA-000 CROSS REGION FMR . . . 401
355 ALGORITHM VIDEMO-000 CROSS REGION FMR . . . 402
356 ALGORITHM VIDEONETICS-001 CROSS REGION FMR . . . 403
357 ALGORITHM VIDEONETICS-002 CROSS REGION FMR . . . 404
358 ALGORITHM VIGILANTSOLUTIONS-006 CROSS REGION FMR . . . 405
359 ALGORITHM VIGILANTSOLUTIONS-007 CROSS REGION FMR . . . 406
360 ALGORITHM VION-000 CROSS REGION FMR . . . 407
361 ALGORITHM VISIONBOX-000 CROSS REGION FMR . . . 408
362 ALGORITHM VISIONBOX-001 CROSS REGION FMR . . . 409
363 ALGORITHM VISIONLABS-007 CROSS REGION FMR . . . 410
364 ALGORITHM VISIONLABS-008 CROSS REGION FMR . . . 411
365 ALGORITHM VISTEAM-000 CROSS REGION FMR . . . 412
366 ALGORITHM VOCORD-007 CROSS REGION FMR . . . 413
367 ALGORITHM VOCORD-008 CROSS REGION FMR . . . 414
368 ALGORITHM WINSENSE-000 CROSS REGION FMR . . . 415
369 ALGORITHM WINSENSE-001 CROSS REGION FMR . . . 416
370 ALGORITHM X-LABORATORY-000 CROSS REGION FMR . . . 417
371 ALGORITHM X-LABORATORY-001 CROSS REGION FMR . . . 418
372 ALGORITHM XFORWARDAI-000 CROSS REGION FMR . . . 419
373 ALGORITHM YISHENG-004 CROSS REGION FMR . . . 420
374 ALGORITHM YITU-003 CROSS REGION FMR . . . 421
375 ALGORITHM 3DIVI-003 CROSS COUNTRY FMR . . . 422
376 ALGORITHM 3DIVI-004 CROSS COUNTRY FMR . . . 423
377 ALGORITHM ACER-000 CROSS COUNTRY FMR . . . 424
378 ALGORITHM ADERA-001 CROSS COUNTRY FMR . . . 425
379 ALGORITHM ADVANCE-002 CROSS COUNTRY FMR . . . 426
380 ALGORITHM AIFIRST-001 CROSS COUNTRY FMR . . . 427
381 ALGORITHM AILABS-001 CROSS COUNTRY FMR . . . 428
382 ALGORITHM AIMALL-001 CROSS COUNTRY FMR . . . 429
383 ALGORITHM AIUNIONFACE-000 CROSS COUNTRY FMR . . . 430
384 ALGORITHM ALCHERA-000 CROSS COUNTRY FMR . . . 431
385 ALGORITHM ALCHERA-001 CROSS COUNTRY FMR . . . 432
386 ALGORITHM ALLGOVISION-000 CROSS COUNTRY FMR . . . 433
387 ALGORITHM ALPHAFACE-001 CROSS COUNTRY FMR . . . 434
388 ALGORITHM ALPHAFACE-002 CROSS COUNTRY FMR . . . 435
389 ALGORITHM AMPLIFIEDGROUP-001 CROSS COUNTRY FMR . . . 436
390 ALGORITHM ANDROVIDEO-000 CROSS COUNTRY FMR . . . 437
391 ALGORITHM ANKE-004 CROSS COUNTRY FMR . . . 438

392 ALGORITHM ANKE-005 CROSS COUNTRY FMR . . . 439
393 ALGORITHM ANTHEUS-000 CROSS COUNTRY FMR . . . 440
394 ALGORITHM ANYVISION-002 CROSS COUNTRY FMR . . . 441
395 ALGORITHM ANYVISION-004 CROSS COUNTRY FMR . . . 442
396 ALGORITHM ASUSAICS-000 CROSS COUNTRY FMR . . . 443
397 ALGORITHM AWARE-003 CROSS COUNTRY FMR . . . 444
398 ALGORITHM AWARE-004 CROSS COUNTRY FMR . . . 445
399 ALGORITHM AWIROS-001 CROSS COUNTRY FMR . . . 446
400 ALGORITHM AYONIX-000 CROSS COUNTRY FMR . . . 447
401 ALGORITHM BIOIDTECHSWISS-000 CROSS COUNTRY FMR . . . 448
402 ALGORITHM BM-001 CROSS COUNTRY FMR . . . 449
403 ALGORITHM CAMVI-002 CROSS COUNTRY FMR . . . 450
404 ALGORITHM CAMVI-004 CROSS COUNTRY FMR . . . 451
405 ALGORITHM CEIEC-002 CROSS COUNTRY FMR . . . 452
406 ALGORITHM CEIEC-003 CROSS COUNTRY FMR . . . 453
407 ALGORITHM CHOSUN-000 CROSS COUNTRY FMR . . . 454
408 ALGORITHM CHTFACE-001 CROSS COUNTRY FMR . . . 455
409 ALGORITHM CHTFACE-002 CROSS COUNTRY FMR . . . 456
410 ALGORITHM CIB-000 CROSS COUNTRY FMR . . . 457
411 ALGORITHM COGENT-003 CROSS COUNTRY FMR . . . 458
412 ALGORITHM COGENT-004 CROSS COUNTRY FMR . . . 459
413 ALGORITHM COGNITEC-000 CROSS COUNTRY FMR . . . 460
414 ALGORITHM COGNITEC-001 CROSS COUNTRY FMR . . . 461
415 ALGORITHM CTBCBANK-000 CROSS COUNTRY FMR . . . 462
416 ALGORITHM CTBCBANK-001 CROSS COUNTRY FMR . . . 463
417 ALGORITHM CYBEREXTRUDER-001 CROSS COUNTRY FMR . . . 464
418 ALGORITHM CYBEREXTRUDER-002 CROSS COUNTRY FMR . . . 465
419 ALGORITHM CYBERLINK-002 CROSS COUNTRY FMR . . . 466
420 ALGORITHM CYBERLINK-003 CROSS COUNTRY FMR . . . 467
421 ALGORITHM DAHUA-003 CROSS COUNTRY FMR . . . 468
422 ALGORITHM DAHUA-004 CROSS COUNTRY FMR . . . 469
423 ALGORITHM DEEPGLINT-001 CROSS COUNTRY FMR . . . 470
424 ALGORITHM DEEPGLINT-002 CROSS COUNTRY FMR . . . 471
425 ALGORITHM DEEPSEA-001 CROSS COUNTRY FMR . . . 472
426 ALGORITHM DERMALOG-005 CROSS COUNTRY FMR . . . 473
427 ALGORITHM DERMALOG-006 CROSS COUNTRY FMR . . . 474
428 ALGORITHM DIDIGLOBALFACE-001 CROSS COUNTRY FMR . . . 475
429 ALGORITHM DIGITALBARRIERS-002 CROSS COUNTRY FMR . . . 476
430 ALGORITHM DSK-000 CROSS COUNTRY FMR . . . 477
431 ALGORITHM EINETWORKS-000 CROSS COUNTRY FMR . . . 478
432 ALGORITHM EXPASOFT-000 CROSS COUNTRY FMR . . . 479
433 ALGORITHM F8-001 CROSS COUNTRY FMR . . . 480
434 ALGORITHM FACESOFT-000 CROSS COUNTRY FMR . . . 481
435 ALGORITHM FUJITSULAB-000 CROSS COUNTRY FMR . . . 482
436 ALGORITHM GLORY-001 CROSS COUNTRY FMR . . . 483
437 ALGORITHM GLORY-002 CROSS COUNTRY FMR . . . 484
438 ALGORITHM GORILLA-003 CROSS COUNTRY FMR . . . 485
439 ALGORITHM GORILLA-004 CROSS COUNTRY FMR . . . 486
440 ALGORITHM HIK-001 CROSS COUNTRY FMR . . . 487
441 ALGORITHM HR-001 CROSS COUNTRY FMR . . . 488
442 ALGORITHM HR-002 CROSS COUNTRY FMR . . . 489
443 ALGORITHM ID3-003 CROSS COUNTRY FMR . . . 490
444 ALGORITHM ID3-004 CROSS COUNTRY FMR . . . 491
445 ALGORITHM IDEMIA-004 CROSS COUNTRY FMR . . . 492
446 ALGORITHM IDEMIA-005 CROSS COUNTRY FMR . . . 493
447 ALGORITHM IIT-001 CROSS COUNTRY FMR . . . 494

448 ALGORITHM IIT-002 CROSS COUNTRY FMR . . . 495
449 ALGORITHM IMAGUS-000 CROSS COUNTRY FMR . . . 496
450 ALGORITHM IMAGUS-001 CROSS COUNTRY FMR . . . 497
451 ALGORITHM IMPERIAL-000 CROSS COUNTRY FMR . . . 498
452 ALGORITHM IMPERIAL-002 CROSS COUNTRY FMR . . . 499
453 ALGORITHM INCODE-005 CROSS COUNTRY FMR . . . 500
454 ALGORITHM INCODE-006 CROSS COUNTRY FMR . . . 501
455 ALGORITHM INNOVATIVETECHNOLOGYLTD-001 CROSS COUNTRY FMR . . . 502
456 ALGORITHM INNOVATRICS-004 CROSS COUNTRY FMR . . . 503
457 ALGORITHM INNOVATRICS-006 CROSS COUNTRY FMR . . . 504
458 ALGORITHM INTELLICLOUDAI-001 CROSS COUNTRY FMR . . . 505
459 ALGORITHM INTELLIFUSION-001 CROSS COUNTRY FMR . . . 506
460 ALGORITHM INTELLIVISION-001 CROSS COUNTRY FMR . . . 507
461 ALGORITHM INTELLIVISION-002 CROSS COUNTRY FMR . . . 508
462 ALGORITHM INTELRESEARCH-000 CROSS COUNTRY FMR . . . 509
463 ALGORITHM INTSYSMSU-000 CROSS COUNTRY FMR . . . 510
464 ALGORITHM INTSYSMSU-001 CROSS COUNTRY FMR . . . 511
465 ALGORITHM IQFACE-000 CROSS COUNTRY FMR . . . 512
466 ALGORITHM IQFACE-001 CROSS COUNTRY FMR . . . 513
467 ALGORITHM ISAP-001 CROSS COUNTRY FMR . . . 514
468 ALGORITHM ISITYOU-000 CROSS COUNTRY FMR . . . 515
469 ALGORITHM ISYSTEMS-001 CROSS COUNTRY FMR . . . 516
470 ALGORITHM ISYSTEMS-002 CROSS COUNTRY FMR . . . 517
471 ALGORITHM ITMO-006 CROSS COUNTRY FMR . . . 518
472 ALGORITHM ITMO-007 CROSS COUNTRY FMR . . . 519
473 ALGORITHM KAKAO-001 CROSS COUNTRY FMR . . . 520
474 ALGORITHM KAKAO-002 CROSS COUNTRY FMR . . . 521
475 ALGORITHM KEDACOM-000 CROSS COUNTRY FMR . . . 522
476 ALGORITHM KNERON-003 CROSS COUNTRY FMR . . . 523
477 ALGORITHM LOOKMAN-002 CROSS COUNTRY FMR . . . 524
478 ALGORITHM LOOKMAN-004 CROSS COUNTRY FMR . . . 525
479 ALGORITHM LUXAND-000 CROSS COUNTRY FMR . . . 526
480 ALGORITHM MEGVII-001 CROSS COUNTRY FMR . . . 527
481 ALGORITHM MEGVII-002 CROSS COUNTRY FMR . . . 528
482 ALGORITHM MEIYA-001 CROSS COUNTRY FMR . . . 529
483 ALGORITHM MICROFOCUS-001 CROSS COUNTRY FMR . . . 530
484 ALGORITHM MICROFOCUS-002 CROSS COUNTRY FMR . . . 531
485 ALGORITHM MT-000 CROSS COUNTRY FMR . . . 532
486 ALGORITHM MVISION-001 CROSS COUNTRY FMR . . . 533
487 ALGORITHM NETBRIDGETECH-001 CROSS COUNTRY FMR . . . 534
488 ALGORITHM NEUROTECHNOLOGY-006 CROSS COUNTRY FMR . . . 535
489 ALGORITHM NEUROTECHNOLOGY-008 CROSS COUNTRY FMR . . . 536
490 ALGORITHM NODEFLUX-001 CROSS COUNTRY FMR . . . 537
491 ALGORITHM NODEFLUX-002 CROSS COUNTRY FMR . . . 538
492 ALGORITHM NOTIONTAG-000 CROSS COUNTRY FMR . . . 539
493 ALGORITHM NTECHLAB-007 CROSS COUNTRY FMR . . . 540
494 ALGORITHM PARAVISION-004 CROSS COUNTRY FMR . . . 541
495 ALGORITHM PIXELALL-002 CROSS COUNTRY FMR . . . 542
496 ALGORITHM PIXELALL-003 CROSS COUNTRY FMR . . . 543
497 ALGORITHM PSL-002 CROSS COUNTRY FMR . . . 544
498 ALGORITHM PSL-003 CROSS COUNTRY FMR . . . 545
499 ALGORITHM PYRAMID-000 CROSS COUNTRY FMR . . . 546
500 ALGORITHM RANKONE-007 CROSS COUNTRY FMR . . . 547
501 ALGORITHM RANKONE-008 CROSS COUNTRY FMR . . . 548
502 ALGORITHM REALNETWORKS-002 CROSS COUNTRY FMR . . . 549
503 ALGORITHM REALNETWORKS-003 CROSS COUNTRY FMR . . . 550

504 ALGORITHM REMARKAI-001 CROSS COUNTRY FMR . . . 551
505 ALGORITHM REMARKAI-002 CROSS COUNTRY FMR . . . 552
506 ALGORITHM ROKID-000 CROSS COUNTRY FMR . . . 553
507 ALGORITHM ROKID-001 CROSS COUNTRY FMR . . . 554
508 ALGORITHM S1-001 CROSS COUNTRY FMR . . . 555
509 ALGORITHM SAFFE-001 CROSS COUNTRY FMR . . . 556
510 ALGORITHM SAFFE-002 CROSS COUNTRY FMR . . . 557
511 ALGORITHM SAMTECH-001 CROSS COUNTRY FMR . . . 558
512 ALGORITHM SCANOVATE-001 CROSS COUNTRY FMR . . . 559
513 ALGORITHM SENSETIME-002 CROSS COUNTRY FMR . . . 560
514 ALGORITHM SENSETIME-003 CROSS COUNTRY FMR . . . 561
515 ALGORITHM SERTIS-000 CROSS COUNTRY FMR . . . 562
516 ALGORITHM SHAMAN-000 CROSS COUNTRY FMR . . . 563
517 ALGORITHM SHAMAN-001 CROSS COUNTRY FMR . . . 564
518 ALGORITHM SHU-001 CROSS COUNTRY FMR . . . 565
519 ALGORITHM SHU-002 CROSS COUNTRY FMR . . . 566
520 ALGORITHM SIAT-002 CROSS COUNTRY FMR . . . 567
521 ALGORITHM SIAT-004 CROSS COUNTRY FMR . . . 568
522 ALGORITHM SJTU-001 CROSS COUNTRY FMR . . . 569
523 ALGORITHM SMILART-002 CROSS COUNTRY FMR . . . 570
524 ALGORITHM SMILART-003 CROSS COUNTRY FMR . . . 571
525 ALGORITHM STARHYBRID-001 CROSS COUNTRY FMR . . . 572
526 ALGORITHM SYNESIS-005 CROSS COUNTRY FMR . . . 573
527 ALGORITHM SYNESIS-006 CROSS COUNTRY FMR . . . 574
528 ALGORITHM SYNOLOGY-000 CROSS COUNTRY FMR . . . 575
529 ALGORITHM TECH5-002 CROSS COUNTRY FMR . . . 576
530 ALGORITHM TECH5-003 CROSS COUNTRY FMR . . . 577
531 ALGORITHM TEVIAN-004 CROSS COUNTRY FMR . . . 578
532 ALGORITHM TEVIAN-005 CROSS COUNTRY FMR . . . 579
533 ALGORITHM TIGER-002 CROSS COUNTRY FMR . . . 580
534 ALGORITHM TIGER-003 CROSS COUNTRY FMR . . . 581
535 ALGORITHM TONGYI-005 CROSS COUNTRY FMR . . . 582
536 ALGORITHM TOSHIBA-002 CROSS COUNTRY FMR . . . 583
537 ALGORITHM TOSHIBA-003 CROSS COUNTRY FMR . . . 584
538 ALGORITHM TRUEFACE-000 CROSS COUNTRY FMR . . . 585
539 ALGORITHM TUPUTECH-000 CROSS COUNTRY FMR . . . 586
540 ALGORITHM ULSEE-001 CROSS COUNTRY FMR . . . 587
541 ALGORITHM ULUFACE-002 CROSS COUNTRY FMR . . . 588
542 ALGORITHM ULUFACE-003 CROSS COUNTRY FMR . . . 589
543 ALGORITHM UPC-001 CROSS COUNTRY FMR . . . 590
544 ALGORITHM VCOG-002 CROSS COUNTRY FMR . . . 591
545 ALGORITHM VD-001 CROSS COUNTRY FMR . . . 592
546 ALGORITHM VERIDAS-002 CROSS COUNTRY FMR . . . 593
547 ALGORITHM VERIDAS-003 CROSS COUNTRY FMR . . . 594
548 ALGORITHM VIA-000 CROSS COUNTRY FMR . . . 595
549 ALGORITHM VIDEONETICS-001 CROSS COUNTRY FMR . . . 596
550 ALGORITHM VIDEONETICS-002 CROSS COUNTRY FMR . . . 597
551 ALGORITHM VIGILANTSOLUTIONS-006 CROSS COUNTRY FMR . . . 598
552 ALGORITHM VIGILANTSOLUTIONS-007 CROSS COUNTRY FMR . . . 599
553 ALGORITHM VION-000 CROSS COUNTRY FMR . . . 600
554 ALGORITHM VISIONBOX-000 CROSS COUNTRY FMR . . . 601
555 ALGORITHM VISIONBOX-001 CROSS COUNTRY FMR . . . 602
556 ALGORITHM VISIONLABS-007 CROSS COUNTRY FMR . . . 603
557 ALGORITHM VISTEAM-000 CROSS COUNTRY FMR . . . 604
558 ALGORITHM VOCORD-007 CROSS COUNTRY FMR . . . 605
559 ALGORITHM VOCORD-008 CROSS COUNTRY FMR . . . 606
560 ALGORITHM WINSENSE-000 CROSS COUNTRY FMR . . . 607

561 ALGORITHM WINSENSE-001 CROSS COUNTRY FMR . . . 608
562 ALGORITHM X-LABORATORY-000 CROSS COUNTRY FMR . . . 609
563 ALGORITHM X-LABORATORY-001 CROSS COUNTRY FMR . . . 610
564 ALGORITHM XFORWARDAI-000 CROSS COUNTRY FMR . . . 611
565 ALGORITHM YISHENG-004 CROSS COUNTRY FMR . . . 612
566 ALGORITHM YITU-003 CROSS COUNTRY FMR . . . 613
567 IMPOSTOR COUNTS FOR CROSS COUNTRY FMR CALCULATIONS . . . 614
568 ALGORITHM 3DIVI-003 CROSS AGE FMR . . . 616
569 ALGORITHM 3DIVI-004 CROSS AGE FMR . . . 617
570 ALGORITHM ACER-000 CROSS AGE FMR . . . 618
571 ALGORITHM ADERA-001 CROSS AGE FMR . . . 619
572 ALGORITHM ADVANCE-002 CROSS AGE FMR . . . 620
573 ALGORITHM AIFIRST-001 CROSS AGE FMR . . . 621
574 ALGORITHM AILABS-001 CROSS AGE FMR . . . 622
575 ALGORITHM AIMALL-001 CROSS AGE FMR . . . 623
576 ALGORITHM AIUNIONFACE-000 CROSS AGE FMR . . . 624
577 ALGORITHM ALCHERA-000 CROSS AGE FMR . . . 625
578 ALGORITHM ALCHERA-001 CROSS AGE FMR . . . 626
579 ALGORITHM ALLGOVISION-000 CROSS AGE FMR . . . 627
580 ALGORITHM ALPHAFACE-001 CROSS AGE FMR . . . 628
581 ALGORITHM ALPHAFACE-002 CROSS AGE FMR . . . 629
582 ALGORITHM AMPLIFIEDGROUP-001 CROSS AGE FMR . . . 630
583 ALGORITHM ANDROVIDEO-000 CROSS AGE FMR . . . 631
584 ALGORITHM ANKE-004 CROSS AGE FMR . . . 632
585 ALGORITHM ANKE-005 CROSS AGE FMR . . . 633
586 ALGORITHM ANTHEUS-000 CROSS AGE FMR . . . 634
587 ALGORITHM ANYVISION-002 CROSS AGE FMR . . . 635
588 ALGORITHM ANYVISION-004 CROSS AGE FMR . . . 636
589 ALGORITHM ASUSAICS-000 CROSS AGE FMR . . . 637
590 ALGORITHM AWARE-003 CROSS AGE FMR . . . 638
591 ALGORITHM AWARE-004 CROSS AGE FMR . . . 639
592 ALGORITHM AWIROS-001 CROSS AGE FMR . . . 640
593 ALGORITHM AYONIX-000 CROSS AGE FMR . . . 641
594 ALGORITHM BIOIDTECHSWISS-000 CROSS AGE FMR . . . 642
595 ALGORITHM BM-001 CROSS AGE FMR . . . 643
596 ALGORITHM CAMVI-002 CROSS AGE FMR . . . 644
597 ALGORITHM CAMVI-004 CROSS AGE FMR . . . 645
598 ALGORITHM CEIEC-002 CROSS AGE FMR . . . 646
599 ALGORITHM CEIEC-003 CROSS AGE FMR . . . 647
600 ALGORITHM CHOSUN-000 CROSS AGE FMR . . . 648
601 ALGORITHM CHTFACE-001 CROSS AGE FMR . . . 649
602 ALGORITHM CHTFACE-002 CROSS AGE FMR . . . 650
603 ALGORITHM CIB-000 CROSS AGE FMR . . . 651
604 ALGORITHM COGENT-003 CROSS AGE FMR . . . 652
605 ALGORITHM COGENT-004 CROSS AGE FMR . . . 653
606 ALGORITHM COGNITEC-000 CROSS AGE FMR . . . 654
607 ALGORITHM COGNITEC-001 CROSS AGE FMR . . . 655
608 ALGORITHM CTBCBANK-000 CROSS AGE FMR . . . 656
609 ALGORITHM CTBCBANK-001 CROSS AGE FMR . . . 657
610 ALGORITHM CYBEREXTRUDER-001 CROSS AGE FMR . . . 658
611 ALGORITHM CYBEREXTRUDER-002 CROSS AGE FMR . . . 659
612 ALGORITHM CYBERLINK-002 CROSS AGE FMR . . . 660
613 ALGORITHM CYBERLINK-003 CROSS AGE FMR . . . 661
614 ALGORITHM DAHUA-003 CROSS AGE FMR . . . 662
615 ALGORITHM DAHUA-004 CROSS AGE FMR . . . 663
616 ALGORITHM DEEPGLINT-001 CROSS AGE FMR . . . 664
617 ALGORITHM DEEPGLINT-002 CROSS AGE FMR . . . 665

618 ALGORITHM DEEPSEA-001 CROSS AGE FMR . . . 666
619 ALGORITHM DERMALOG-005 CROSS AGE FMR . . . 667
620 ALGORITHM DERMALOG-006 CROSS AGE FMR . . . 668
621 ALGORITHM DIDIGLOBALFACE-001 CROSS AGE FMR . . . 669
622 ALGORITHM DIGITALBARRIERS-002 CROSS AGE FMR . . . 670
623 ALGORITHM DSK-000 CROSS AGE FMR . . . 671
624 ALGORITHM EINETWORKS-000 CROSS AGE FMR . . . 672
625 ALGORITHM EXPASOFT-000 CROSS AGE FMR . . . 673
626 ALGORITHM F8-001 CROSS AGE FMR . . . 674
627 ALGORITHM FACESOFT-000 CROSS AGE FMR . . . 675
628 ALGORITHM FUJITSULAB-000 CROSS AGE FMR . . . 676
629 ALGORITHM GLORY-001 CROSS AGE FMR . . . 677
630 ALGORITHM GLORY-002 CROSS AGE FMR . . . 678
631 ALGORITHM GORILLA-003 CROSS AGE FMR . . . 679
632 ALGORITHM GORILLA-004 CROSS AGE FMR . . . 680
633 ALGORITHM HIK-001 CROSS AGE FMR . . . 681
634 ALGORITHM HR-001 CROSS AGE FMR . . . 682
635 ALGORITHM HR-002 CROSS AGE FMR . . . 683
636 ALGORITHM ID3-003 CROSS AGE FMR . . . 684
637 ALGORITHM ID3-004 CROSS AGE FMR . . . 685
638 ALGORITHM IDEMIA-004 CROSS AGE FMR . . . 686
639 ALGORITHM IDEMIA-005 CROSS AGE FMR . . . 687
640 ALGORITHM IIT-001 CROSS AGE FMR . . . 688
641 ALGORITHM IIT-002 CROSS AGE FMR . . . 689
642 ALGORITHM IMAGUS-000 CROSS AGE FMR . . . 690
643 ALGORITHM IMAGUS-001 CROSS AGE FMR . . . 691
644 ALGORITHM IMPERIAL-000 CROSS AGE FMR . . . 692
645 ALGORITHM IMPERIAL-002 CROSS AGE FMR . . . 693
646 ALGORITHM INCODE-005 CROSS AGE FMR . . . 694
647 ALGORITHM INCODE-006 CROSS AGE FMR . . . 695
648 ALGORITHM INNOVATIVETECHNOLOGYLTD-001 CROSS AGE FMR . . . 696
649 ALGORITHM INNOVATRICS-004 CROSS AGE FMR . . . 697
650 ALGORITHM INNOVATRICS-006 CROSS AGE FMR . . . 698
651 ALGORITHM INTELLICLOUDAI-001 CROSS AGE FMR . . . 699
652 ALGORITHM INTELLIFUSION-001 CROSS AGE FMR . . . 700
653 ALGORITHM INTELLIVISION-001 CROSS AGE FMR . . . 701
654 ALGORITHM INTELLIVISION-002 CROSS AGE FMR . . . 702
655 ALGORITHM INTELRESEARCH-000 CROSS AGE FMR . . . 703
656 ALGORITHM INTELRESEARCH-001 CROSS AGE FMR . . . 704
657 ALGORITHM INTSYSMSU-000 CROSS AGE FMR . . . 705
658 ALGORITHM INTSYSMSU-001 CROSS AGE FMR . . . 706
659 ALGORITHM IQFACE-000 CROSS AGE FMR . . . 707
660 ALGORITHM IQFACE-001 CROSS AGE FMR . . . 708
661 ALGORITHM ISAP-001 CROSS AGE FMR . . . 709
662 ALGORITHM ISITYOU-000 CROSS AGE FMR . . . 710
663 ALGORITHM ISYSTEMS-001 CROSS AGE FMR . . . 711
664 ALGORITHM ISYSTEMS-002 CROSS AGE FMR . . . 712
665 ALGORITHM ITMO-006 CROSS AGE FMR . . . 713
666 ALGORITHM ITMO-007 CROSS AGE FMR . . . 714
667 ALGORITHM KAKAO-001 CROSS AGE FMR . . . 715
668 ALGORITHM KAKAO-002 CROSS AGE FMR . . . 716
669 ALGORITHM KEDACOM-000 CROSS AGE FMR . . . 717
670 ALGORITHM KNERON-003 CROSS AGE FMR . . . 718
671 ALGORITHM KNERON-005 CROSS AGE FMR . . . 719
672 ALGORITHM LOOKMAN-002 CROSS AGE FMR . . . 720
673 ALGORITHM LOOKMAN-004 CROSS AGE FMR . . . 721

674 ALGORITHM LUXAND-000 CROSS AGE FMR . . . 722
675 ALGORITHM MEGVII-001 CROSS AGE FMR . . . 723
676 ALGORITHM MEGVII-002 CROSS AGE FMR . . . 724
677 ALGORITHM MEIYA-001 CROSS AGE FMR . . . 725
678 ALGORITHM MICROFOCUS-001 CROSS AGE FMR . . . 726
679 ALGORITHM MICROFOCUS-002 CROSS AGE FMR . . . 727
680 ALGORITHM MT-000 CROSS AGE FMR . . . 728
681 ALGORITHM MVISION-001 CROSS AGE FMR . . . 729
682 ALGORITHM NETBRIDGETECH-001 CROSS AGE FMR . . . 730
683 ALGORITHM NEUROTECHNOLOGY-006 CROSS AGE FMR . . . 731
684 ALGORITHM NEUROTECHNOLOGY-008 CROSS AGE FMR . . . 732
685 ALGORITHM NODEFLUX-001 CROSS AGE FMR . . . 733
686 ALGORITHM NODEFLUX-002 CROSS AGE FMR . . . 734
687 ALGORITHM NOTIONTAG-000 CROSS AGE FMR . . . 735
688 ALGORITHM NTECHLAB-007 CROSS AGE FMR . . . 736
689 ALGORITHM NTECHLAB-008 CROSS AGE FMR . . . 737
690 ALGORITHM PARAVISION-004 CROSS AGE FMR . . . 738
691 ALGORITHM PIXELALL-002 CROSS AGE FMR . . . 739
692 ALGORITHM PIXELALL-003 CROSS AGE FMR . . . 740
693 ALGORITHM PSL-002 CROSS AGE FMR . . . 741
694 ALGORITHM PSL-003 CROSS AGE FMR . . . 742
695 ALGORITHM PYRAMID-000 CROSS AGE FMR . . . 743
696 ALGORITHM RANKONE-007 CROSS AGE FMR . . . 744
697 ALGORITHM RANKONE-008 CROSS AGE FMR . . . 745
698 ALGORITHM REALNETWORKS-002 CROSS AGE FMR . . . 746
699 ALGORITHM REALNETWORKS-003 CROSS AGE FMR . . . 747
700 ALGORITHM REMARKAI-001 CROSS AGE FMR . . . 748
701 ALGORITHM REMARKAI-002 CROSS AGE FMR . . . 749
702 ALGORITHM ROKID-000 CROSS AGE FMR . . . 750
703 ALGORITHM ROKID-001 CROSS AGE FMR . . . 751
704 ALGORITHM S1-001 CROSS AGE FMR . . . 752
705 ALGORITHM SAFFE-001 CROSS AGE FMR . . . 753
706 ALGORITHM SAFFE-002 CROSS AGE FMR . . . 754
707 ALGORITHM SAMTECH-001 CROSS AGE FMR . . . 755
708 ALGORITHM SCANOVATE-001 CROSS AGE FMR . . . 756
709 ALGORITHM SENSETIME-002 CROSS AGE FMR . . . 757
710 ALGORITHM SENSETIME-003 CROSS AGE FMR . . . 758
711 ALGORITHM SERTIS-000 CROSS AGE FMR . . . 759
712 ALGORITHM SHAMAN-000 CROSS AGE FMR . . . 760
713 ALGORITHM SHAMAN-001 CROSS AGE FMR . . . 761
714 ALGORITHM SHU-001 CROSS AGE FMR . . . 762
715 ALGORITHM SHU-002 CROSS AGE FMR . . . 763
716 ALGORITHM SIAT-002 CROSS AGE FMR . . . 764
717 ALGORITHM SIAT-004 CROSS AGE FMR . . . 765
718 ALGORITHM SJTU-001 CROSS AGE FMR . . . 766
719 ALGORITHM SJTU-002 CROSS AGE FMR . . . 767
720 ALGORITHM SMILART-002 CROSS AGE FMR . . . 768
721 ALGORITHM SMILART-003 CROSS AGE FMR . . . 769
722 ALGORITHM STARHYBRID-001 CROSS AGE FMR . . . 770
723 ALGORITHM SYNESIS-005 CROSS AGE FMR . . . 771
724 ALGORITHM SYNESIS-006 CROSS AGE FMR . . . 772
725 ALGORITHM SYNOLOGY-000 CROSS AGE FMR . . . 773
726 ALGORITHM TECH5-002 CROSS AGE FMR . . . 774
727 ALGORITHM TECH5-003 CROSS AGE FMR . . . 775
728 ALGORITHM TEVIAN-004 CROSS AGE FMR . . . 776
729 ALGORITHM TEVIAN-005 CROSS AGE FMR . . . 777

730 ALGORITHM TIGER-002 CROSS AGE FMR . . . 778
731 ALGORITHM TIGER-003 CROSS AGE FMR . . . 779
732 ALGORITHM TONGYI-005 CROSS AGE FMR . . . 780
733 ALGORITHM TOSHIBA-002 CROSS AGE FMR . . . 781
734 ALGORITHM TOSHIBA-003 CROSS AGE FMR . . . 782
735 ALGORITHM TRUEFACE-000 CROSS AGE FMR . . . 783
736 ALGORITHM TUPUTECH-000 CROSS AGE FMR . . . 784
737 ALGORITHM ULSEE-001 CROSS AGE FMR . . . 785
738 ALGORITHM ULUFACE-002 CROSS AGE FMR . . . 786
739 ALGORITHM ULUFACE-003 CROSS AGE FMR . . . 787
740 ALGORITHM UPC-001 CROSS AGE FMR . . . 788
741 ALGORITHM VCOG-002 CROSS AGE FMR . . . 789
742 ALGORITHM VD-001 CROSS AGE FMR . . . 790
743 ALGORITHM VERIDAS-002 CROSS AGE FMR . . . 791
744 ALGORITHM VERIDAS-003 CROSS AGE FMR . . . 792
745 ALGORITHM VIA-000 CROSS AGE FMR . . . 793
746 ALGORITHM VIDEMO-000 CROSS AGE FMR . . . 794
747 ALGORITHM VIDEONETICS-001 CROSS AGE FMR . . . 795
748 ALGORITHM VIDEONETICS-002 CROSS AGE FMR . . . 796
749 ALGORITHM VIGILANTSOLUTIONS-006 CROSS AGE FMR . . . 797
750 ALGORITHM VIGILANTSOLUTIONS-007 CROSS AGE FMR . . . 798
751 ALGORITHM VION-000 CROSS AGE FMR . . . 799
752 ALGORITHM VISIONBOX-000 CROSS AGE FMR . . . 800
753 ALGORITHM VISIONBOX-001 CROSS AGE FMR . . . 801
754 ALGORITHM VISIONLABS-007 CROSS AGE FMR . . . 802
755 ALGORITHM VISIONLABS-008 CROSS AGE FMR . . . 803
756 ALGORITHM VISTEAM-000 CROSS AGE FMR . . . 804
757 ALGORITHM VOCORD-007 CROSS AGE FMR . . . 805
758 ALGORITHM VOCORD-008 CROSS AGE FMR . . . 806
759 ALGORITHM WINSENSE-000 CROSS AGE FMR . . . 807
760 ALGORITHM WINSENSE-001 CROSS AGE FMR . . . 808
761 ALGORITHM X-LABORATORY-000 CROSS AGE FMR . . . 809
762 ALGORITHM X-LABORATORY-001 CROSS AGE FMR . . . 810
763 ALGORITHM XFORWARDAI-000 CROSS AGE FMR . . . 811
764 ALGORITHM YISHENG-004 CROSS AGE FMR . . . 812
765 ALGORITHM YITU-003 CROSS AGE FMR . . . 813

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
1	3Divi	3divi	003	2018-10-09	191636	^{40}358	^{191}4096 ± 0	^{127}650 ± 90	^{15}627 ± 11	^{19}623 ± 32
2	3Divi	3divi	004	2019-07-22	263670	^{51}430	^{101}2048 ± 0	^{198}984 ± 131	^{26}794 ± 35	^{28}801 ± 40
3	ADVANCE.AI	advance	002	2019-12-19	257173	^{32}295	^{65}2048 ± 0	^{167}811 ± 2	^{103}3292 ± 26	^{103}3306 ± 57
4	ASUSTek Computer Inc	asusaics	000	2019-10-24	257418	^{88}605	^{89}2048 ± 0	^{77}488 ± 18	^{160}8118 ± 128	^{159}8053 ± 456
5	Ability Enterprise Co. Ltd - Andro Video	andro	000	2020-02-03	128502	^{42}360	^{83}2048 ± 0	^{46}308 ± 1	^{114}3580 ± 32	^{110}3609 ± 60
6	Acer Incorporated	acer	000	2020-01-08	109735	^{63}478	^{98}2048 ± 0	^{24}222 ± 0	^{109}3479 ± 71	^{113}3636 ± 232
7	Adera Global PTE Ltd	adera	001	2019-06-17	0	^{24}190	^{175}2560 ± 0	^{7}97 ± 0	^{64}1604 ± 71	^{65}1649 ± 56
8	Ai First	aifirst	001	2019-11-21	224157	^{64}485	^{64}2048 ± 0	^{109}589 ± 4	^{107}3442 ± 40	^{106}3450 ± 123
9	AiUnion Technology Co Ltd	aiunionface	000	2019-10-22	241642	^{46}402	^{103}2048 ± 0	^{130}653 ± 32	^{106}3439 ± 47	^{115}3657 ± 167
10	Alchera Inc	alchera	000	2019-03-01	258450	^{90}614	^{86}2048 ± 0	^{107}587 ± 13	^{101}3189 ± 32	^{94}3031 ± 142
11	Alchera Inc	alchera	000	2019-03-01	174013	^{62}473	^{81}2048 ± 0	^{119}627 ± 11	^{104}3342 ± 81	^{99}3243 ± 47
12	Alivia / Innovation Sys	isystems	001	2018-06-12	274621	^{139}1091	^{63}2048 ± 0	^{39}291 ± 9	^{9}557 ± 16	^{11}564 ± 22
13	Alivia / Innovation Sys	isystems	002	2018-10-18	358984	^{170}1595	^{112}2048 ± 0	^{172}822 ± 8	^{24}749 ± 31	^{21}632 ± 28
14	AllGoVision	allgovision	000	2019-03-01	172509	^{81}561	^{120}2048 ± 0	^{60}384 ± 8	^{185}29903 ± 406	^{186}29735 ± 194
15	AlphaSSTG	alphaface	001	2019-09-03	259849	^{78}527	^{92}2048 ± 0	^{115}613 ± 3	^{110}3482 ± 41	^{101}3279 ± 91
16	AlphaSSTG	alphaface	002	2020-02-20	768995	^{161}1434	^{109}2048 ± 0	^{120}628 ± 2	^{33}945 ± 25	^{33}935 ± 17
17	Amplified Group	amplifiedgroup	001	2019-03-01	0	^{8}81	^{31}866 ± 2	^{5}93 ± 0	^{190}57803 ± 4210	^{190}56365 ± 1196
18	Anke Investments	anke	004	2019-06-27	349388	^{97}706	^{153}2056 ± 0	^{118}625 ± 1	^{16}633 ± 22	^{20}632 ± 34
19	Anke Investments	anke	005	2019-11-21	328553	^{143}1134	^{155}2056 ± 0	^{108}589 ± 2	^{98}3121 ± 44	^{102}3296 ± 71
20	Antheus Technologia Ltda	antheus	000	2019-12-05	119453	^{15}116	^{25}520 ± 0	^{9}109 ± 1	^{154}7085 ± 31	^{153}7082 ± 37
21	AnyVision	anyvision	002	2018-01-31	662659	^{60}468	^{39}1024 ± 0	^{28}248 ± 0	^{191}74069 ± 188	^{191}74019 ± 198
22	AnyVision	anyvision	004	2018-06-15	401001	^{141}1102	^{36}1024 ± 0	^{54}355 ± 1	^{75}1891 ± 51	^{72}1829 ± 85
23	Aware	aware	003	2018-10-19	377729	^{154}1348	^{180}3108 ± 0	^{164}783 ± 10	^{57}1392 ± 42	^{58}1334 ± 80
24	Aware	aware	004	2019-03-01	427829	^{175}1820	^{168}2084 ± 0	^{186}900 ± 10	^{53}1279 ± 50	^{57}1287 ± 100
25	Awidit Systems	awiros	001	2019-09-23	15499	^{11}88	^{16}512 ± 0	^{8}99 ± 8	^{73}1868 ± 100	^{86}2467 ± 78
26	Ayonix	ayonix	000	2017-06-22	58505	^{5}69	^{40}1036 ± 0	^{1}18 ± 2	^{14}621 ± 23	^{18}620 ± 26
27	Beijing Vion Technology Inc	vion	000	2018-10-19	228219	^{67}498	^{144}2052 ± 0	^{50}333 ± 1	^{187}39839 ± 3561	^{181}26830 ± 2241
28	BioID Technologies SA	bioidtechswiss	000	2019-11-15	758466	^{130}1039	^{10}256 ± 0	^{122}631 ± 2	^{186}34933 ± 139	^{187}34866 ± 121
29	Bitmain	bitmain	001	2018-10-17	287734	^{17}148	^{1}64 ± 0	^{72}444 ± 88	^{74}1887 ± 31	^{73}1877 ± 26
30	CSA IntelliCloud Technology	intellicloudai	001	2019-08-13	220831	^{93}655	^{133}2048 ± 0	^{76}479 ± 18	^{38}1010 ± 16	^{39}1024 ± 31
31	CTBC Bank Co Ltd	ctbcbank	000	2019-06-28	257208	^{82}570	^{87}2048 ± 0	^{100}568 ± 43	^{113}3551 ± 87	^{134}4805 ± 209
32	CTBC Bank Co Ltd	ctbcbank	001	2019-10-28	275511	^{85}603	^{125}2048 ± 0	^{132}654 ± 33	^{152}6321 ± 283	^{148}6218 ± 286
33	Camvi Technologies	camvitech	002	2018-10-19	236278	^{102}737	^{38}1024 ± 0	^{143}677 ± 7	^{13}612 ± 26	^{14}603 ± 20
34	Camvi Technologies	camvitech	004	2019-07-12	280733	^{124}919	^{113}2048 ± 0	^{159}759 ± 10	^{34}948 ± 40	^{35}963 ± 31
35	Canon Information Technology (Beijing) Co Ltd	cib	000	2019-12-11	340288	^{80}557	^{108}2048 ± 0	^{199}988 ± 40	^{183}26805 ± 83	^{182}26857 ± 177
36	China Electronics Import-Export Corp	ceiec	002	2019-06-12	269063	^{48}426	^{80}2048 ± 0	^{114}612 ± 17	^{81}2188 ± 57	^{82}2301 ± 56
37	China Electronics Import-Export Corp	ceiec	003	2020-01-06	260371	^{50}430	^{82}2048 ± 0	^{170}819 ± 3	^{132}4594 ± 109	^{135}4864 ± 62
38	China University of Petroleum	upc	001	2019-06-05	0	^{135}1077	^{42}1052 ± 0	^{97}551 ± 15	^{97}3114 ± 44	^{98}3165 ± 97
39	Chosun University	chosun	000	2020-02-12	167093	^{16}136	^{75}2048 ± 0	^{71}441 ± 1	^{37}983 ± 20	^{37}983 ± 29
40	Chunghwa Telecom Co. Ltd	chtface	001	2019-08-06	94088	^{37}355	^{115}2048 ± 0	^{23}218 ± 12	^{78}2089 ± 45	^{78}2087 ± 23
41	Chunghwa Telecom Co. Ltd	chtface	002	2019-12-07	363153	^{140}1100	^{97}2048 ± 0	^{105}585 ± 14	^{131}4551 ± 41	^{130}4550 ± 80
42	Cognitec Systems GmbH	cognitec	000	2018-10-19	474759	^{66}495	^{140}2052 ± 0	^{25}224 ± 1	^{122}3835 ± 108	^{119}3782 ± 83
43	Cognitec Systems GmbH	cognitec	001	2019-03-01	476809	^{68}498	^{147}2052 ± 0	^{42}297 ± 17	^{128}4253 ± 59	^{124}4102 ± 167
44	Cyberextruder	cyberex	001	2017-08-02	121211	^{21}178	^{9}256 ± 0	^{185}893 ± 25	^{41}1083 ± 16	^{44}1079 ± 19

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 1: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]		
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor	
45	Cyberextruder	cyberex	002	2018-01-30	168909	^{26}194	^{66}2048 ± 0	^{86}532 ± 6	^{72}1803 ± 14	^{68}1779 ± 22	
46	Cyberlink Corp	cyberlink	002	2019-06-12	222311	^{103}760	^{142}2052 ± 0	^{134}656 ± 22	^{84}2264 ± 71	^{89}2649 ± 195	
47	Cyberlink Corp	cyberlink	003	2019-10-07	470949	^{113}824	^{139}2052 ± 0	^{67}424 ± 1	^{137}4857 ± 53	^{138}5168 ± 69	
48	DSK	dsk	000	2019-06-28	11967	^{28}252	^{18}512 ± 0	^{44}304 ± 47	^{156}7152 ± 115	^{154}7134 ± 111	
49	Dahua Technology Co Ltd	dahua	003	2019-08-14	605337	^{189}3739	^{114}2048 ± 0	^{88}537 ± 4	^{18}653 ± 28	^{15}606 ± 38	
50	Dahua Technology Co Ltd	dahua	004	2019-12-18	832455	^{192}4885	^{93}2048 ± 0	^{153}740 ± 11	^{95}3105 ± 56	^{96}3142 ± 115	
51	Deepglint	deepglint	001	2019-06-21	569802	^{123}917	^{189}4096 ± 0	^{151}721 ± 4	^{118}3680 ± 35	^{107}3517 ± 182	
52	Deepglint	deepglint	002	2019-11-15	459642	^{171}1614	^{186}4096 ± 0	^{137}667 ± 1	^{175}18395 ± 217	^{173}17399 ± 429	
53	Dermalog	dermalog	005	2018-02-02	0	^{39}357	^{2}128 ± 0	^{12}130 ± 11	^{6}499 ± 22	^{8}500 ± 22	
54	Dermalog	dermalog	006	2018-10-18	0	^{128}970	^{3}128 ± 0	^{85}532 ± 12	^{7}506 ± 23	^{6}459 ± 23	
55	DiDi ChuXing Technology Co	didiglobalface	001	2019-10-23	259849	^{77}527	^{91}2048 ± 0	^{126}650 ± 13	^{115}3592 ± 32	^{109}3588 ± 83	
56	Digital Barriers	barriers	002	2019-03-01	83002	^{179}1930	^{157}2056 ± 0	^{21}209 ± 11	^{168}13409 ± 228	^{167}13267 ± 206	
57	Expasoft LLC	expasoft	000	2020-01-06	15341	^{12}100	^{130}2048 ± 0	^{3}69 ± 0	^{129}4429 ± 54	^{125}4158 ± 108	
58	FaceSoft Ltd	facesoft	000	2019-07-10	370120	^{109}796	^{135}2048 ± 0	^{142}675 ± 18	^{82}2239 ± 28	^{81}2277 ± 96	
59	FarBar Inc	f8	001	2019-07-11	272977	^{149}1276	^{78}2048 ± 0	^{173}822 ± 39	^{171}15262 ± 139	^{170}15277 ± 212	
60	Fujitsu Research	Development Center Co Ltd	fujitsulab	000	2020-02-04	0	^{56}453	^{20}512 ± 0	^{66}419 ± 1	^{116}3613 ± 37	^{111}3621 ± 29
61	Gemalto Cogent	cogent	003	2019-03-01	698290	^{162}1445	^{32}973 ± 0	^{194}952 ± 0	^{166}12496 ± 75	^{165}11822 ± 163	
62	Gemalto Cogent	cogent	004	2019-06-14	722919	^{132}1059	^{61}1983 ± 0	^{192}941 ± 28	^{170}14448 ± 56	^{171}15882 ± 81	
63	Glory Ltd	glory	001	2018-06-08	0	^{152}1331	^{58}1726 ± 0	^{62}393 ± 2	^{164}9607 ± 128	^{163}9539 ± 182	
64	Glory Ltd	glory	002	2019-11-12	0	^{129}982	^{171}2106 ± 0	^{110}594 ± 5	^{163}8815 ± 105	^{161}8782 ± 78	
65	Gorilla Technology	gorilla	003	2019-06-19	94409	^{94}668	^{44}1132 ± 0	^{51}334 ± 25	^{91}2840 ± 42	^{91}2865 ± 87	
66	Gorilla Technology	gorilla	004	2019-11-04	186952	^{117}853	^{174}2192 ± 0	^{64}397 ± 3	^{143}5269 ± 84	^{141}5259 ± 105	
67	Guangzhou Pixel Solutions Co Ltd	pixelall	002	2019-06-06	0	^{34}342	^{176}2560 ± 0	^{20}191 ± 1	^{49}1223 ± 56	^{53}1230 ± 47	
68	Guangzhou Pixel Solutions Co Ltd	pixelall	003	2019-10-15	0	^{119}865	^{177}2560 ± 0	^{149}708 ± 21	^{127}4216 ± 257	^{129}4488 ± 56	
69	Hengrui AI Technology Ltd	hr	001	2019-06-04	346156	^{172}1682	^{164}2057 ± 0	^{136}665 ± 3	^{173}17816 ± 260	^{174}17878 ± 464	
70	Hengrui AI Technology Ltd	hr	001	2019-10-08	390059	^{153}1337	^{165}2057 ± 0	^{188}904 ± 4	^{180}24112 ± 766	^{179}23859 ± 739	
71	Hikvision Research Institute	hik	001	2019-03-01	667866	^{194}6597	^{50}1408 ± 0	^{128}651 ± 0	^{5}488 ± 19	^{7}477 ± 22	
72	ID3 Technology	id3	003	2018-10-05	265951	^{36}354	^{12}264 ± 0	^{47}316 ± 19	^{56}1330 ± 25	^{59}1354 ± 28	
73	ID3 Technology	id3	004	2019-03-01	171526	^{89}613	^{11}264 ± 0	^{92}541 ± 11	^{42}1135 ± 23	^{49}1156 ± 32	
74	ITMO University	itmo	006	2019-03-01	599187	^{165}1489	^{173}2121 ± 0	^{168}814 ± 1	^{181}26154 ± 148	^{180}26217 ± 260	
75	ITMO University	itmo	007	2020-01-06	415979	^{182}2199	^{118}2048 ± 0	^{154}742 ± 3	^{135}4825 ± 69	^{136}5016 ± 281	
76	Idemia	Idemia	004	2019-03-01	406924	^{69}501	^{14}352 ± 0	^{45}306 ± 5	^{144}5592 ± 518	^{143}5533 ± 426	
77	Idemia	Idemia	005	2019-10-11	509824	^{91}618	^{30}588 ± 0	^{84}524 ± 20	^{157}7543 ± 370	^{164}10415 ± 174	
78	Imagus Technology Pty Ltd	imagus	000	2019-06-19	183453	^{59}466	^{127}2048 ± 0	^{69}425 ± 24	^{43}1145 ± 25	^{67}1718 ± 63	
79	Imagus Technology Pty Ltd	imagus	001	2019-10-22	282680	^{114}826	^{102}2048 ± 0	^{171}820 ± 45	^{119}3700 ± 34	^{108}3585 ± 238	
80	Imperial College London	imperial	000	2019-03-01	370120	^{110}796	^{100}2048 ± 0	^{139}669 ± 1	^{79}2130 ± 32	^{77}2052 ± 100	
81	Imperial College London	imperial	002	2019-08-28	472327	^{176}1826	^{68}2048 ± 0	^{101}570 ± 2	^{136}4827 ± 69	^{131}4557 ± 160	
82	Incode Technologies Inc	incode	005	2019-10-17	256242	^{138}1089	^{96}2048 ± 0	^{99}567 ± 4	^{130}4443 ± 91	^{133}4685 ± 72	
83	Incode Technologies Inc	incode	006	2020-02-20	266095	^{112}814	^{71}2048 ± 0	^{75}472 ± 1	^{70}1788 ± 41	^{71}1798 ± 59	
84	Innovative Technology Ltd	innovativetechnologyltd	001	2019-10-22	177232	^{33}341	^{106}2048 ± 0	^{70}432 ± 7	^{133}4676 ± 34	^{128}4468 ± 169	
85	Innovatrics	innovatrics	004	2018-10-19	0	^{157}1367	^{43}1076 ± 0	^{61}391 ± 0	^{162}8573 ± 274	^{158}7929 ± 244	
86	Innovatrics	innovatrics	006	2019-08-13	0	^{142}1107	^{26}538 ± 0	^{174}824 ± 10	^{147}5763 ± 217	^{146}5631 ± 824	
87	Institute of Information Technologies	iitvision	001	2019-07-05	269176	^{107}788	^{105}2048 ± 0	^{147}699 ± 4	^{39}1060 ± 48	^{42}1074 ± 54	
88	Institute of Information Technologies	iitvision	002	2019-12-04	259579	^{101}731	^{123}2048 ± 0	^{82}516 ± 1	^{108}3447 ± 59	^{114}3649 ± 83	

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 2: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
89	Intel Research Group	intelresearch	000	2019-07-08	388229	^{183}2406	^{69}2048 ± 0	^{187}902 ± 6	^{134}4800 ± 152	^{132}4561 ± 97
90	Intel Research Group	intelresearch	001	2020-01-14	353997	^{160}1433	^{111}2048 ± 0	^{145}680 ± 3	^{148}5854 ± 128	^{150}6291 ± 151
91	Intellivision	intellivision	001	2017-10-10	43692	^{7}74	^{160}2056 ± 0	^{2}62 ± 2	^{86}2573 ± 91	^{88}2544 ± 38
92	Intellivision	intellivision	002	2019-08-23	43692	^{9}81	^{154}2056 ± 0	^{53}342 ± 30	^{172}16049 ± 195	^{169}15136 ± 389
93	Is It You	isityou	000	2017-06-26	48010	^{13}110	^{198}19200 ± 0	^{10}113 ± 5	^{193}237517 ± 1318	^{193}237374 ± 1279
94	Kakao Corp	kakao	001	2019-03-01	107616	^{27}225	^{35}1024 ± 0	^{59}379 ± 1	^{30}930 ± 22	^{34}948 ± 38
95	Kakao Corp	kakao	002	2019-06-19	479406	^{86}603	^{136}2048 ± 0	^{155}747 ± 6	^{67}1720 ± 62	^{66}1715 ± 83
96	Kedacom International Pte	kedacom	000	2019-06-03	245292	^{197}23574	^{13}292 ± 0	^{80}506 ± 3	^{19}684 ± 14	^{22}682 ± 16
97	Kneron Inc	kenron	003	2019-07-01	58366	^{22}188	^{94}2048 ± 0	^{36}281 ± 3	^{142}5237 ± 63	^{142}5274 ± 99
98	Kneron Inc	kenron	005	2020-02-21	375374	^{57}457	^{72}2048 ± 0	^{83}518 ± 2	^{76}1922 ± 11	^{74}1926 ± 20
99	Lomonosov Moscow State University	intsysmsu	000	2019-06-18	650193	^{133}1066	^{73}2048 ± 0	^{87}535 ± 20	^{11}610 ± 22	^{17}613 ± 31
100	Lomonosov Moscow State University	intsysmsu	001	2019-10-22	384409	^{108}789	^{95}2048 ± 0	^{116}617 ± 5	^{99}3135 ± 26	^{105}3440 ± 235
101	Lookman Electroplast Industries	lookman	002	2018-06-13	138200	^{195}16518	^{28}548 ± 0	^{16}173 ± 1	^{12}610 ± 19	^{16}612 ± 22
102	Lookman Electroplast Industries	lookman	004	2019-06-03	244775	^{196}23548	^{27}548 ± 0	^{81}507 ± 5	^{29}871 ± 29	^{32}878 ± 29
103	Luxand Inc	luxand	000	2019-11-07	0	^{156}1366	^{41}1040 ± 0	^{65}406 ± 22	^{83}2240 ± 32	^{80}2234 ± 25
104	MVision	mvision	001	2019-11-12	227502	^{99}723	^{22}512 ± 0	^{146}690 ± 21	^{71}1797 ± 38	^{70}1788 ± 32
105	Megvii/Face++	megvii	001	2018-06-15	1361523	^{159}1426	^{132}2048 ± 0	^{93}543 ± 0	^{141}5228 ± 32	^{139}5252 ± 60
106	Megvii/Face++	megvii	002	2018-10-19	1809564	^{178}1879	^{194}4100 ± 0	^{124}644 ± 0	^{189}50630 ± 183	^{189}47591 ± 716
107	MicroFocus	microfocus	001	2018-06-13	104524	^{23}190	^{7}256 ± 0	^{32}264 ± 18	^{1}215 ± 8	^{1}217 ± 10
108	MicroFocus	microfocus	002	2018-10-17	96288	^{19}176	^{6}256 ± 0	^{30}259 ± 18	^{2}337 ± 34	^{2}230 ± 25
109	Momentum Digital Co Ltd	sertis	000	2019-10-07	265572	^{49}427	^{70}2048 ± 0	^{156}755 ± 0	^{123}3883 ± 44	^{121}3884 ± 66
110	Moontime Smart Technology	mt	000	2019-06-03	372169	^{131}1056	^{137}2049 ± 0	^{152}724 ± 12	^{66}1678 ± 47	^{64}1614 ± 85
111	N-Tech Lab	ntech	007	2019-06-25	2509686	^{193}5070	^{181}3348 ± 0	^{165}792 ± 3	^{48}1209 ± 59	^{55}1267 ± 65
112	N-Tech Lab	ntech	008	2020-01-06	1138002	^{186}2707	^{49}1300 ± 0	^{98}552 ± 1	^{89}2665 ± 31	^{90}2832 ± 50
113	Netbridge Technology Incoporation	netbridgetech	001	2020-01-08	133108	^{73}508	^{187}4096 ± 0	^{4}85 ± 2	^{167}13233 ± 108	^{168}14368 ± 213
114	Neurotechnology	neurotech	006	2019-06-26	525541	^{167}1538	^{19}512 ± 0	^{144}678 ± 56	^{8}513 ± 14	^{10}535 ± 26
115	Neurotechnology	neurotech	008	2020-01-08	119718	^{95}694	^{8}256 ± 0	^{52}339 ± 0	^{45}1158 ± 26	^{51}1158 ± 28
116	Nodeflux	nodeflux	001	2019-03-01	262553	^{43}363	^{110}2048 ± 0	^{27}247 ± 1	^{102}3242 ± 81	^{100}3255 ± 93
117	Nodeflux	nodeflux	002	2019-08-13	774668	^{58}466	^{134}2048 ± 0	^{150}717 ± 16	^{149}5922 ± 170	^{157}7911 ± 367
118	NotionTag Technologies Private Limited	notiontag	000	2019-06-12	92753	^{76}525	^{29}584 ± 0	^{96}548 ± 64	^{188}44672 ± 269	^{188}44593 ± 358
119	Panasonic R+D Center Singapore	psl	002	2019-02-28	804934	^{174}1814	^{143}2052 ± 0	^{183}888 ± 9	^{63}1590 ± 48	^{45}1133 ± 78
120	Panasonic R+D Center Singapore	psl	003	2019-10-01	1159643	^{191}3960	^{172}2120 ± 0	^{180}867 ± 7	^{124}3915 ± 50	^{122}3899 ± 226
121	Paravision (EverAI)	everai paravision	003	2019-07-01	539802	^{146}1225	^{188}4096 ± 0	^{141}674 ± 4	^{22}699 ± 20	^{24}713 ± 47
122	Paravision (EverAI)	everai paravision	004	2019-12-11	556670	^{169}1572	^{185}4096 ± 0	^{182}879 ± 34	^{150}5997 ± 29	^{147}5682 ± 185
123	Pyramid Cyber Security + Forensic (P) Ltd	pyramid	000	2019-11-04	372608	^{111}804	^{151}2056 ± 0	^{104}583 ± 2	^{155}7147 ± 59	^{155}7586 ± 425
124	Rank One Computing	rankone	007	2019-06-03	0	^{4}67	^{5}165 ± 0	^{26}245 ± 5	^{20}688 ± 20	^{13}601 ± 16
125	Rank One Computing	rankone	008	2019-11-12	0	^{6}70	^{4}165 ± 0	^{34}272 ± 4	^{32}944 ± 29	^{30}864 ± 26
126	Realnetworks Inc	realnetworks	002	2019-02-28	95328	^{44}370	^{60}1848 ± 0	^{29}250 ± 2	^{54}1285 ± 17	^{54}1247 ± 42
127	Realnetworks Inc	realnetworks	003	2019-06-12	95334	^{35}345	^{59}1848 ± 0	^{18}177 ± 10	^{61}1516 ± 29	^{62}1522 ± 60
128	Remark Holdings	remarkai	001	2019-03-01	241857	^{100}730	^{146}2052 ± 0	^{175}831 ± 6	^{50}1229 ± 20	^{29}805 ± 56
129	Remark Holdings	remarkai	001	2019-11-21	224157	^{53}443	^{85}2048 ± 0	^{193}952 ± 4	^{117}3614 ± 40	^{112}3632 ± 32
130	Rokid Corporation Ltd	rokid	000	2019-08-01	258612	^{145}1218	^{161}2056 ± 0	^{94}547 ± 2	^{120}3711 ± 88	^{118}3746 ± 209
131	Rokid Corporation Ltd	rokid	001	2019-12-13	641223	^{134}1071	^{166}2060 ± 0	^{190}912 ± 3	^{146}5696 ± 111	^{145}5610 ± 59
132	Saffe Ltd	saffe	001	2018-10-19	85973	^{18}168	^{47}1280 ± 0	^{35}281 ± 1	^{52}1274 ± 19	^{56}1277 ± 26

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 3: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
133	Saffe Ltd	saffe	002	2019-03-01	260622	^{118}855	^{122}2048 ± 0	^{169}817 ± 11	^{23}717 ± 7	^{25}714 ± 29
134	Samsung S1 Corp	s1	001	2019-12-06	435491	^{105}772	^{170}2092 ± 0	^{111}602 ± 21	^{126}4151 ± 44	^{127}4428 ± 246
135	Samtech InfoNet Limited	samtech	001	2019-10-15	288082	^{87}605	^{156}2056 ± 0	^{40}294 ± 3	^{158}7694 ± 59	^{156}7678 ± 91
136	Scanovate Ltd	scanovate	001	2019-11-12	257083	^{84}601	^{76}2048 ± 0	^{103}579 ± 24	^{169}14306 ± 352	^{172}16031 ± 538
137	Sensetime Group Ltd	sensetime	002	2018-10-19	531783	^{180}2094	^{149}2052 ± 0	^{166}797 ± 3	^{90}2713 ± 90	^{83}2301 ± 25
138	Sensetime Group Ltd	sensetime	003	2019-06-04	787853	^{185}2519	^{148}2052 ± 0	^{189}910 ± 4	^{139}5017 ± 137	^{140}5258 ± 51
139	Shaman Software	shaman	000	2017-12-05	0	^{71}507	^{190}4096 ± 0	^{131}653 ± 16	^{3}380 ± 25	^{4}379 ± 31
140	Shaman Software	shaman	001	2018-01-13	0	^{74}511	^{184}4096 ± 0	^{41}294 ± 2	^{17}635 ± 19	^{5}441 ± 25
141	Shanghai Jiao Tong University	sjtu	001	2019-09-27	347115	^{52}438	^{67}2048 ± 0	^{129}651 ± 4	^{198}2674654 ± 64798	^{198}2376946 ± 202419
142	Shanghai Jiao Tong University	sjtu	002	2020-02-12	446215	^{79}538	^{124}2048 ± 0	^{177}835 ± 2	^{197}2211198 ± 26052	^{197}2210428 ± 21877
143	Shanghai Ulucu Electronics Technology Co. Ltd	uluface	002	2019-07-10	0	^{137}1088	^{104}2048 ± 0	^{181}873 ± 42	^{178}19207 ± 1114	^{176}18501 ± 274
144	Shanghai Ulucu Electronics Technology Co. Ltd	uluface	003	2019-11-12	97357	^{148}1264	^{179}3072 ± 0	^{196}970 ± 15	^{184}27666 ± 198	^{185}29560 ± 244
145	Shanghai Universiy - Shanghai Film Academy	shu	001	2019-06-17	329513	^{47}402	^{129}2048 ± 0	^{113}612 ± 5	^{88}2619 ± 19	^{92}2987 ± 143
146	Shanghai Universiy - Shanghai Film Academy	shu	002	2019-12-10	731250	^{121}890	^{183}4096 ± 0	^{158}759 ± 5	^{199}2926869 ± 49960	^{199}2926507 ± 48716
147	Shanghai Yitu Technology	yitu	003	2019-03-01	1525719	^{188}3737	^{167}2082 ± 0	^{179}860 ± 0	^{174}18305 ± 71	^{175}18286 ± 62
148	Shenzhen AiMall Tech Ltd	aimall	001	2019-11-12	128820	^{20}178	^{37}1024 ± 0	^{49}328 ± 0	^{140}5038 ± 40	^{152}6849 ± 401
149	Shenzhen EI Networks Limited	einetworks	000	2019-08-13	372608	^{120}880	^{162}2056 ± 0	^{125}645 ± 3	^{138}4876 ± 66	^{137}5156 ± 77
150	Shenzhen Inst Adv Integrated Tech CAS	SIAT	002	2018-06-13	486842	^{184}2434	^{150}2052 ± 0	^{102}579 ± 0	^{25}769 ± 13	^{26}750 ± 13
151	Shenzhen Inst Adv Integrated Tech CAS	SIAT	004	2019-03-01	940063	^{190}3860	^{193}4100 ± 0	^{140}670 ± 0	^{125}4013 ± 45	^{120}3782 ± 173
152	Shenzhen Intellifusion Technologies Co Ltd	intellifusion	001	2019-08-22	271872	^{104}762	^{74}2048 ± 0	^{161}778 ± 61	^{121}3756 ± 59	^{123}3953 ± 126
153	Smilart	smilart	002	2018-02-06	111826	^{29}263	^{34}1024 ± 0	^{17}176 ± 16	^{176}18784 ± 136	^{177}18795 ± 151
154	Smilart	smilart	003	2018-06-18	67339	^{25}192	^{17}512 ± 0	^{19}180 ± 12	^{58}1395 ± 74	^{40}1027 ± 66
155	Star Hybrid Limited	starhybrid	001	2019-06-19	100509	^{116}845	^{88}2048 ± 0	^{56}358 ± 82	^{40}1075 ± 51	^{43}1078 ± 53
156	Synesis	synesis	005	2019-06-06	146509	^{92}638	^{107}2048 ± 0	^{22}211 ± 9	^{10}599 ± 23	^{12}581 ± 32
157	Synesis	synesis	006	2019-10-10	731941	^{164}1472	^{195}4104 ± 0	^{95}547 ± 1	^{145}5658 ± 17	^{144}5603 ± 148
158	Synology Inc	synology	000	2019-10-23	221021	^{55}453	^{77}2048 ± 0	^{68}425 ± 25	^{179}23628 ± 206	^{184}29262 ± 4987
159	TUPU Technology Co Ltd	tuputech	000	2019-10-11	11476	^{2}33	^{84}2048 ± 0	^{11}124 ± 7	^{182}26308 ± 269	^{183}28022 ± 2594
160	Taiwan AI Labs	ailabs	001	2019-12-18	1054663	^{147}1252	^{79}2048 ± 0	^{135}664 ± 4	^{192}100635 ± 999	^{192}100995 ± 1587
161	Tech5 SA	tech5	002	2019-03-01	1150887	^{163}1461	^{48}1280 ± 0	^{162}780 ± 10	^{60}1406 ± 120	^{41}1048 ± 57
162	Tech5 SA	tech5	003	2019-08-19	1427464	^{173}1745	^{51}1536 ± 0	^{191}937 ± 39	^{55}1313 ± 35	^{60}1360 ± 41
163	Tencent Deepsea Lab	deepsea	001	2019-06-03	147497	^{41}358	^{33}1024 ± 0	^{121}630 ± 7	^{59}1401 ± 37	^{61}1467 ± 50
164	Tevian	tevian	004	2019-03-01	863474	^{106}774	^{90}2048 ± 0	^{79}506 ± 30	^{4}474 ± 31	^{3}326 ± 20
165	Tevian	tevian	005	2019-09-21	921043	^{136}1083	^{119}2048 ± 0	^{123}642 ± 32	^{94}3097 ± 31	^{116}3700 ± 278
166	TigerIT Americas LLC	tiger	002	2018-06-13	341638	^{75}522	^{158}2056 ± 0	^{63}393 ± 20	^{80}2135 ± 29	^{79}2137 ± 38
167	TigerIT Americas LLC	tiger	003	2018-10-16	426164	^{98}708	^{152}2056 ± 0	^{73}458 ± 21	^{77}2031 ± 35	^{76}2029 ± 38
168	TongYi Transportation Technology	tongyi	005	2019-06-12	1140701	^{181}2121	^{169}2089 ± 0	^{14}165 ± 1	^{177}18924 ± 65	^{178}20158 ± 103
169	Toshiba	toshiba	002	2018-10-19	813606	-	^{55}1560 ± 0	^{91}541 ± 0	^{111}3521 ± 369	^{85}2449 ± 124
170	Toshiba	toshiba	003	2019-03-01	984125	^{144}1197	^{56}1560 ± 0	^{90}540 ± 0	^{85}2390 ± 41	^{84}2407 ± 81
171	Trueface.ai	trueface	000	2019-10-08	255123	^{65}493	^{126}2048 ± 0	^{57}368 ± 11	^{93}3040 ± 26	^{97}3144 ± 51
172	ULSee Inc	ulsee	001	2019-07-31	370519	-	^{121}2048 ± 0	^{133}654 ± 2	^{151}6065 ± 94	^{149}6228 ± 77
173	Universidade de Coimbra	visteam	000	2020-01-14	32729	^{10}83	^{52}1536 ± 0	^{6}96 ± 7	^{153}6361 ± 87	^{151}6668 ± 277
174	VCognition	vcog	002	2017-06-12	3229434	^{187}3666	^{199}61504 ± 5	^{55}357 ± 25	^{194}296154 ± 3077	^{194}296436 ± 4183
175	Veridas Digital Authentication Solutions S.L.	veridas	002	2019-03-01	193466	^{70}505	^{24}512 ± 0	^{138}669 ± 20	^{68}1733 ± 81	^{75}1934 ± 44
176	Veridas Digital Authentication Solutions S.L.	veridas	003	2019-11-27	293109	^{61}469	^{99}2048 ± 0	^{184}892 ± 33	^{159}7974 ± 51	^{162}9463 ± 206

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 4: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
177	Via Technologies Inc.	via	000	2019-07-08	124422	^{127}964	^{116}2048 ± 0	^{148}707 ± 8	^{36}966 ± 28	^{38}1021 ± 44
178	Videmo Intelligente Videoanalyse	videmo	000	2019-12-19	139643	^{45}390	^{131}2048 ± 0	^{13}141 ± 5	^{96}3106 ± 145	^{95}3127 ± 57
179	Videonetics Technology Pvt Ltd	videonetics	001	2019-06-19	30875	^{3}61	^{15}512 ± 0	^{31}262 ± 3	^{44}1153 ± 38	^{46}1142 ± 65
180	Videonetics Technology Pvt Ltd	videonetics	002	2019-11-21	121981	^{14}115	^{145}2052 ± 0	^{37}281 ± 5	^{112}3533 ± 57	^{117}3742 ± 65
181	Vigilant Solutions	vigilant	006	2019-03-01	343048	^{151}1316	^{54}1548 ± 0	^{178}841 ± 8	^{31}939 ± 32	^{23}711 ± 37
182	Vigilant Solutions	vigilant	007	2019-06-27	255600	^{122}912	^{53}1548 ± 0	^{78}493 ± 6	^{27}803 ± 35	^{27}800 ± 40
183	Visidon	visidon	001	2019-02-26	170262	^{31}281	^{141}2052 ± 0	^{48}316 ± 6	^{51}1258 ± 38	^{47}1148 ± 109
184	Vision-Box	visionbox	000	2019-02-26	176501	^{38}355	^{128}2048 ± 0	^{43}304 ± 7	^{65}1648 ± 57	^{52}1192 ± 42
185	Vision-Box	visionbox	001	2019-03-01	256869	^{83}579	^{117}2048 ± 0	^{197}983 ± 7	^{46}1161 ± 22	^{48}1154 ± 20
186	VisionLabs	visionlabs	007	2019-06-12	357204	^{30}266	^{21}512 ± 0	^{33}272 ± 0	^{35}965 ± 41	^{36}972 ± 31
187	VisionLabs	visionlabs	008	2020-01-06	706099	^{54}446	^{23}512 ± 0	^{74}467 ± 1	^{69}1759 ± 37	^{69}1786 ± 35
188	Vocord	vocord	007	2019-06-06	587489	^{155}1352	^{57}1664 ± 0	^{163}780 ± 2	^{87}2593 ± 83	^{87}2526 ± 59
189	Vocord	vocord	008	2020-01-031	603867	^{168}1559	^{178}2688 ± 0	^{195}962 ± 2	^{92}3015 ± 50	^{93}2988 ± 62
190	Winsense Co Ltd	winsense	000	2019-06-17	270819	^{115}833	^{45}1280 ± 0	^{38}283 ± 1	^{62}1551 ± 31	^{63}1532 ± 42
191	Winsense Co Ltd	winsense	001	2019-10-16	264428	^{125}922	^{46}1280 ± 0	^{160}768 ± 9	^{100}3143 ± 32	^{126}4230 ± 226
192	X-Laboratory	x-laboratory	000	2019-09-03	520020	^{166}1524	^{163}2056 ± 0	^{176}832 ± 38	^{105}3380 ± 91	^{104}3314 ± 253
193	X-Laboratory	x-laboratory	001	2020-01-21	625140	^{177}1844	^{159}2056 ± 0	^{106}586 ± 2	^{28}813 ± 28	^{31}872 ± 32
194	Xforward AI Technology Co LTD	xforwardai	000	2020-02-06	242457	^{158}1392	^{62}2048 ± 0	^{157}757 ± 6	^{47}1185 ± 44	^{50}1157 ± 44
195	Xiamen Meiya Pico Information Co. Ltd	meiya	001	2019-03-01	280055	^{72}507	^{138}2049 ± 0	^{117}622 ± 12	^{161}8356 ± 615	^{160}8134 ± 97
196	Zhuhai Yisheng Electronics Technology	yisheng	004	2018-06-12	486351	^{150}1279	^{182}3704 ± 0	^{58}378 ± 12	^{21}693 ± 137	^{9}526 ± 34
197	iQIYI Inc	iqface	000	2019-06-04	268819	^{96}704	^{196}4750 ± 32	^{89}538 ± 26	^{196}636433 ± 38446	^{195}632654 ± 85615
198	iQIYI Inc	iqface	001	2019-12-11	1145590	^{126}938	^{197}4752 ± 35	^{112}603 ± 1	^{195}634025 ± 5555	^{196}633845 ± 4950
199	iSAP Solution Corporation	isap	001	2019-08-07	99049	^{1}18	^{192}4096 ± 0	^{15}171 ± 12	^{165}12413 ± 154	^{166}12251 ± 382

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 5: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
1	3divi-003	0.0318	145	0.0588	143	0.0097	133	0.0389	148	0.0639	145	0.0619	139	0.0867	137	0.5365	34
2	3divi-004	0.0095	57	0.0153	60	0.0049	80	0.0097	61	0.0145	60	0.0175	67	0.0665	131	0.5025	27
3	acer-000	0.1393	165	0.9075	192	0.0650	168	0.9981	191	-		1.0000	186	0.9841	185	-	
4	adera-001	0.1021	162	0.1757	160	0.0368	162	0.1823	168	0.2967	166	0.1714	155	0.1965	157	0.7202	66
5	advance-002	0.0089	51	0.0137	52	0.0034	50	0.0073	33	0.0115	39	0.0400	122	0.0498	116	-	
6	aifirst-001	0.0119	77	0.0170	66	0.0067	108	0.0084	47	0.0127	46	0.0131	43	0.0432	101	0.4301	17
7	ailabs-001	0.0158	105	0.0276	113	0.0065	101	0.0192	122	0.0317	118	0.0352	117	0.0338	80	-	
8	aimall-001	0.0176	115	0.0324	121	0.0074	121	0.0225	129	0.0407	129	-		0.0344	82	0.6587	54
9	aiunionface-000	0.0104	64	0.0154	62	0.0051	84	0.0082	46	0.0122	44	0.0141	44	0.0306	56	-	
10	alchera-000	0.0165	110	0.0243	101	0.0086	126	0.0125	92	0.0186	85	0.0204	79	0.0370	89	-	
11	alchera-001	0.0183	116	0.0299	116	0.0078	122	0.0142	100	0.0234	102	0.0239	93	0.0372	90	-	
12	allgovision-000	0.0346	146	0.0527	139	0.0210	150	0.0232	131	0.0339	120	0.0372	120	0.0607	127	-	
13	alphaface-001	0.0065	31	0.0097	32	0.0025	36	0.0039	11	0.0063	15	0.0083	15	0.0280	12	-	
14	alphaface-002	0.0052	19	0.0075	20	0.0019	22	0.0030	2	0.0044	5	1.0000	189	0.0279	9	-	
15	amplifiedgroup-001	0.5034	185	0.5848	184	0.2999	188	0.6973	183	0.8316	181	0.7807	176	0.4250	176	-	
16	androvideo-000	0.0243	131	0.0438	136	0.0098	134	0.0239	134	0.0365	126	0.0483	131	0.1162	147	-	
17	anke-004	0.0080	45	0.0154	61	0.0031	44	0.0073	32	0.0112	37	0.0102	29	0.0288	30	0.3577	8
18	anke-005	0.0070	37	0.0109	41	0.0022	29	0.0059	25	0.0094	26	0.0105	30	0.0289	32	0.3337	6
19	antheus-000	0.2564	173	0.3776	174	0.1059	175	0.7240	184	0.8699	184	0.8899	180	0.7668	179	0.9233	90
20	anyvision-002	0.0660	156	0.0898	152	0.0387	163	0.0928	161	0.1512	158	0.0899	147	0.2227	161	0.6960	60
21	anyvision-004	0.0267	138	0.0385	133	0.0081	124	0.0258	138	0.0487	139	0.0234	90	0.0470	111	0.4633	21
22	asusaics-000	0.0125	83	0.0209	84	0.0043	63	0.0085	48	0.0134	52	0.0143	46	0.0295	40	-	
23	aware-003	0.0793	158	0.1161	158	0.0288	160	0.1028	162	0.1708	161	0.1698	154	0.3180	172	0.8512	80
24	aware-004	0.0690	157	0.0949	155	0.0257	155	0.0837	159	0.1436	157	0.1171	151	0.0516	118	-	
25	awiros-001	0.4044	178	0.4622	177	0.2880	187	0.5530	177	0.6518	175	0.2008	156	0.5584	178	-	
26	ayonix-000	0.4351	181	0.4872	178	0.2299	182	0.6150	180	0.7510	178	0.6557	172	0.3635	173	0.8434	78
27	bioidtechswiss-000	0.0066	33	0.0082	27	0.0015	14	0.0113	80	0.0225	97	0.0078	13	0.0278	7	-	
28	bm-001	0.7431	191	0.9494	194	0.6188	193	0.9586	188	0.9843	186	0.9049	181	0.9935	186	0.8845	85
29	camvi-002	0.0125	84	0.0221	90	0.0049	82	0.0089	53	0.0145	62	0.0142	45	0.0288	28	0.5760	42
30	camvi-004	0.0171	113	0.0316	120	0.0049	79	0.0042	12	0.0049	9	0.0097	27	0.0284	19	0.5788	44
31	ceiec-002	0.0161	108	0.0193	78	0.0124	142	0.0122	89	0.0164	73	0.0270	99	0.0465	110	0.5156	31
32	ceiec-003	0.0071	40	0.0107	39	0.0024	35	0.0061	27	0.0079	21	0.0160	53	0.0308	60	-	
33	chosun-000	0.8481	193	1.0000	198	0.7301	194	1.0000	197	-		1.0000	196	1.0000	195	-	
34	chtface-001	0.9993	197	0.9994	197	0.9993	198	0.9999	193	-		1.0000	185	0.9980	187	-	
35	chtface-002	0.0150	98	0.0268	109	0.0054	88	0.0096	60	0.0140	56	0.0186	70	0.0306	57	-	
36	cib-000	0.0084	48	0.0156	63	0.0053	85	0.0049	15	0.0051	10	0.0275	102	0.0294	39	-	
37	cogent-003	0.0091	52	0.0188	75	0.0032	45	0.0098	63	0.0132	50	0.0187	71	0.0406	96	-	
38	cogent-004	0.0064	30	0.0116	44	0.0024	34	0.0096	59	0.0134	53	0.0157	50	0.0379	91	0.7177	65
39	cognitec-000	0.0116	73	0.0177	67	0.0036	52	0.0118	85	0.0167	75	0.0285	105	0.0953	141	0.8365	77
40	cognitec-001	0.0126	85	0.0185	74	0.0047	75	0.0120	87	0.0168	76	0.0270	98	0.0598	126	-	
41	ctbcbank-000	0.0168	111	0.0250	106	0.0064	99	0.0146	103	0.0224	96	0.0211	82	1.0000	194	0.8803	83
42	ctbcbank-001	0.0155	101	0.0235	98	0.0060	96	0.0148	107	0.0243	105	0.0207	80	1.0000	197	-	
43	cyberextruder-001	0.1972	169	0.2547	167	0.0755	170	0.4686	176	0.6387	174	0.3807	167	0.1747	154	0.7804	75
44	cyberextruder-002	0.0811	159	0.1336	159	0.0265	157	0.1465	166	0.2266	165	0.2086	159	0.1000	144	0.6105	48

Table 6: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA columns compare images described in section 2.2. The MUGSHOT columns compare images described in section 2.5. The VISA-BORDER column compare images described in section 2.3 with those described in section 2.4. The WILD columns compare images described in section 2.6. The CHILD-EXPLOITATION columns compare images described in section 2.1.

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
45	cyberlink-002	0.0114	72	0.0195	79	0.0044	64	0.0101	67	0.0163	71	0.0160	54	0.0298	44	0.5003	26
46	cyberlink-003	0.0118	75	0.0192	77	0.0042	59	0.0098	64	0.0161	68	0.0153	49	0.0303	51	-	
47	dahua-003	0.0052	20	0.0068	16	0.0023	33	0.0056	21	0.0062	14	0.0113	35	0.0285	22	0.6253	50
48	dahua-004	0.0045	15	0.0058	10	0.0019	24	0.0036	7	0.0048	8	0.0051	5	0.0281	14	-	
49	deepglint-001	0.0040	10	0.0062	14	0.0014	13	0.0047	14	0.0067	16	0.0069	9	0.0278	6	0.4006	12
50	deepglint-002	0.0016	2	0.0027	3	0.0004	2	0.0032	6	0.0033	2	0.0043	2	0.0280	11	0.3422	7
51	deepsea-001	0.0136	90	0.0215	87	0.0071	117	0.0142	101	0.0214	92	0.0163	58	0.0347	83	0.5606	39
52	dermalog-005	0.1526	167	0.1823	163	0.0658	169	0.2580	170	0.4018	168	-		0.0855	135	0.6842	57
53	dermalog-006	0.0253	136	0.0369	131	0.0172	147	0.0171	116	0.0283	112	0.0217	85	0.0623	129	0.5852	45
54	didiglobalface-001	0.0055	24	0.0092	29	0.0016	15	0.0030	3	0.0045	6	0.0088	19	0.0282	17	0.4270	15
55	digitalbarriers-002	0.3360	176	0.3690	172	0.0968	174	0.0877	160	0.1557	159	0.0971	150	0.0436	103	-	
56	dsk-000	0.1526	166	0.2169	164	0.0765	171	0.3787	173	0.5426	172	0.3115	162	0.2201	159	0.7313	68
57	einetworks-000	0.0099	60	0.0180	70	0.0047	74	0.0088	51	0.0140	58	0.0130	41	0.0293	36	-	
58	everai-paravision-003	0.0034	7	0.0050	8	0.0011	8	0.0036	10	0.0052	12	0.0092	22	0.0278	8	0.2669	2
59	expasoft-000	0.0427	149	0.0655	148	0.0233	154	0.0239	133	0.0393	127	0.0673	141	0.0565	124	-	
60	f8-001	0.0249	135	0.0336	123	0.0182	148	0.0178	119	0.0232	101	0.0303	112	0.0475	113	0.5272	32
61	facesoft-000	0.0085	49	0.0112	43	0.0032	47	0.0064	29	0.0107	32	0.0091	20	0.0275	3	0.4992	25
62	fujitsulab-000	0.0123	79	0.0212	85	0.0057	92	0.0091	54	0.0133	51	0.0251	96	0.0445	105	-	
63	glory-001	0.0902	160	0.1082	157	0.0410	164	0.1642	167	0.2065	164	0.2186	160	0.4261	177	0.8831	84
64	glory-002	0.0241	128	0.0311	119	0.0188	149	0.0116	82	0.0151	64	0.0157	52	0.1265	149	-	
65	gorilla-003	0.0165	109	0.0291	114	0.0053	86	0.0205	126	0.0437	132	0.0297	110	0.0359	87	0.9756	93
66	gorilla-004	0.0138	91	0.0239	100	0.0049	81	0.0243	135	0.0444	133	0.0275	101	0.0287	27	-	
67	hik-001	0.0096	58	0.0125	48	0.0036	54	0.0093	57	0.0164	72	0.0108	32	0.0271	1	-	
68	hr-001	0.0044	14	0.0072	19	0.0019	21	0.0073	35	0.0108	35	0.0125	38	0.0303	50	0.5499	36
69	hr-002	0.0043	12	0.0059	11	0.0017	16	0.0054	16	0.0076	18	0.0076	12	0.0338	79	-	
70	id3-003	0.0361	147	0.0757	149	0.0104	140	0.0292	142	0.0476	136	0.0447	130	0.0848	134	0.5865	46
71	id3-004	0.0198	123	0.0344	126	0.0084	125	0.0238	132	0.0423	131	0.0289	107	-		-	
72	idemia-004	0.0160	107	0.0244	103	0.0065	102	0.0199	124	0.0354	122	0.0268	97	0.0309	61	-	
73	idemia-005	0.0132	86	0.0216	88	0.0057	93	0.0121	88	0.0218	95	0.0215	84	0.0294	38	0.4343	18
74	iit-001	0.0104	65	0.0179	69	0.0048	78	0.0099	66	0.0142	59	0.1222	152	0.3092	171	0.4836	23
75	iit-002	0.0111	70	0.0177	68	0.0054	87	0.0085	49	0.0140	57	0.0193	75	0.1373	150	-	
76	imagus-000	0.0642	154	0.0882	150	0.0330	161	0.0497	151	0.0905	149	0.0848	145	0.1158	146	0.6936	59
77	imagus-001	0.0245	132	0.0407	134	0.0091	129	0.0257	137	0.0497	141	0.0514	133	0.0971	142	-	
78	imperial-000	0.0067	35	0.0108	40	0.0022	30	0.0080	43	0.0134	54	0.0087	18	0.0281	15	-	
79	imperial-002	0.0058	26	0.0081	25	0.0027	37	0.0055	19	0.0085	23	0.0083	16	0.0273	2	0.5151	28
80	incode-005	0.0111	71	0.0189	76	0.0042	60	0.0156	113	0.0304	116	0.0195	76	0.0562	123	-	
81	incode-006	0.0156	102	0.0273	111	0.0051	83	0.0117	83	0.0238	103	0.0202	78	0.0325	70	-	
82	innovativetechnologyltd-001	0.0578	152	0.0938	154	0.0258	156	0.0501	152	0.0981	150	-		0.0449	106	-	
83	innovatrics-004	0.0194	120	0.0292	115	0.0068	110	0.0344	145	0.0617	144	0.0562	136	0.0454	109	0.4650	22
84	innovatrics-006	0.0058	27	0.0089	28	0.0021	26	0.0061	28	0.0096	29	0.0096	26	0.0281	13	0.3056	4
85	intellicloudai-001	0.0142	93	0.0234	97	0.0064	100	0.0092	56	0.0145	61	0.0162	56	0.0409	97	-	
86	intellifusion-001	0.0072	41	0.0094	30	0.0028	42	0.0056	22	0.0085	24	0.0111	34	0.0289	31	0.5454	35
87	intellivision-001	0.1335	164	0.2205	165	0.0417	165	0.1090	164	0.1670	160	0.1385	153	0.2445	163	0.7766	74
88	intellivision-002	0.1000	161	0.1775	161	0.0265	158	0.0610	155	0.1009	151	0.0805	144	0.0768	133	-	

Table 7: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA *columns compare images described in section 2.2. The* MUGSHOT *columns compare images described in section 2.5. The* VISA-BORDER *column compare images described in section 2.3 with those described in section 2.4. The* WILD *columns compare images described in section 2.6. The* CHILD-EXPLOITATION *columns compare images described in section 2.1.*

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
89	intelresearch-000	0.0307	142	0.0578	142	0.0093	130	0.0385	147	0.0751	148	0.0409	124	0.0324	67	-	
90	intelresearch-001	0.0242	129	0.0595	145	0.0097	132	0.0129	96	0.0292	114	0.0351	116	0.0919	140	-	
91	intsysmsu-000	0.0135	88	0.0204	81	0.0069	112	0.0112	77	0.0161	67	0.0148	47	0.2330	162	-	
92	intsysmsu-001	0.9543	196	0.9888	196	0.9165	197	0.9923	189	-		0.9977	182	0.7871	180	-	
93	iqface-000	0.0091	54	0.0143	55	0.0043	62	0.0075	38	0.0110	36	0.0171	65	0.0381	92	0.6490	52
94	iqface-001	0.0088	50	0.0117	45	0.0047	73	0.0177	117	0.0230	100	0.0165	61	0.0597	125	-	
95	isap-001	0.5092	186	0.6588	186	0.2338	184	0.6899	182	0.7978	179	0.7200	173	0.1931	156	-	
96	isityou-000	0.5682	188	0.7033	188	0.4145	191	1.0000	194	-		1.0000	190	1.0000	190	1.0000	96
97	isystems-001	0.0149	97	0.0245	104	0.0067	107	0.0138	99	0.0210	90	0.0209	81	0.0524	121	0.5152	30
98	isystems-002	0.0118	74	0.0182	72	0.0066	103	0.0111	74	0.0162	69	0.0166	62	0.0516	119	0.4876	24
99	itmo-006	0.0125	82	0.0220	89	0.0046	69	0.0149	108	0.0266	111	0.0233	88	0.0329	73	-	
100	itmo-007	0.0080	46	0.0125	49	0.0033	48	0.0107	70	0.0185	83	0.0167	63	0.0300	47	-	
101	kakao-001	0.4553	183	0.5532	183	0.2034	180	0.6580	181	0.8150	180	0.4831	169	1.0000	199	-	
102	kakao-002	0.0625	153	0.1779	162	0.0168	146	0.0791	158	0.1381	156	0.0636	140	1.0000	192	1.0000	103
103	kedacom-000	0.0055	23	0.0081	26	0.0027	38	0.0111	76	0.0120	42	0.0415	125	0.2511	165	0.7650	72
104	kneron-003	0.0542	150	0.0902	153	0.0218	152	0.0346	146	0.0562	143	0.0919	148	0.3053	170	0.6962	61
105	kneron-005	0.0157	103	0.0259	108	0.0072	119	0.0126	94	0.0212	91	0.0406	123	0.0471	112	-	
106	lookman-002	0.0297	140	0.0547	141	0.0102	139	0.0339	144	0.0562	142	0.0614	138	0.2640	168	-	
107	lookman-004	0.0074	43	0.0099	34	0.0037	55	0.0124	91	0.0149	63	0.0430	128	0.2516	166	0.7664	73
108	luxand-000	0.2056	171	0.2814	168	0.0895	173	0.4053	174	0.5365	171	0.3497	164	0.2222	160	-	
109	megvii-001	0.0157	104	0.0244	102	0.0045	68	0.0392	149	0.0671	146	0.0168	64	0.0916	139	0.4418	19
110	megvii-002	0.0104	66	0.0145	57	0.0036	53	0.0225	128	0.0345	121	0.0099	28	0.0692	132	0.3013	3
111	meiya-001	0.0171	112	0.0275	112	0.0066	105	0.0159	114	0.0261	110	0.0311	113	0.0363	88	-	
112	microfocus-001	0.4482	182	0.5524	182	0.2309	183	0.7256	185	0.8416	182	0.7301	174	0.2567	167	0.6890	58
113	microfocus-002	0.3605	177	0.5057	179	0.1566	178	0.5783	178	0.7223	176	0.5909	171	0.1582	153	0.6517	53
114	mt-000	0.0100	61	0.0170	65	0.0047	72	0.0074	37	0.0118	41	0.0127	39	0.0326	71	0.3773	11
115	mvision-001	0.0191	118	0.0233	95	0.0131	143	0.0204	125	0.0356	123	0.0198	77	0.0431	100	-	
116	netbridgetech-001	0.4749	184	0.6599	187	0.1800	179	0.4438	175	0.5676	173	0.4491	168	0.1098	145	-	
117	neurotechnology-006	0.0098	59	0.0136	51	0.0040	58	0.0105	69	0.0182	81	0.0164	59	0.0303	52	0.5911	47
118	neurotechnology-008	0.0091	53	0.0184	73	0.0023	31	0.0076	40	0.0116	40	0.0157	51	0.0301	49	-	
119	nodeflux-001	1.0000	199	1.0000	199	1.0000	199	1.0000	199	-		0.5169	170	1.0000	198	-	
120	nodeflux-002	0.0186	117	0.0340	124	0.0070	114	0.0261	139	0.0451	135	0.0548	135	0.0299	46	-	
121	notiontag-000	0.6669	189	0.7885	189	0.3222	190	0.3715	172	0.4978	170	0.8571	178	0.1807	155	0.6479	51
122	ntechlab-007	0.0056	25	0.0076	21	0.0018	18	0.0073	36	0.0128	48	0.0079	14	0.0276	5	0.3316	5
123	ntechlab-008	0.0041	11	0.0061	12	0.0011	7	0.0056	20	0.0108	33	0.0042	1	0.0289	34	-	
124	paravision-004	0.0030	6	0.0046	6	0.0012	9	0.0030	4	0.0036	3	0.0091	21	0.0288	29	0.2467	1
125	pixelall-002	0.0193	119	0.0340	125	0.0066	104	0.0127	95	0.0209	88	0.0234	91	0.0342	81	0.8963	87
126	pixelall-003	0.0074	44	0.0118	46	0.0032	46	0.0057	23	0.0079	20	0.0121	37	0.0285	24	-	
127	psl-002	0.0107	68	0.0180	71	0.0048	77	0.0089	52	0.0120	43	0.0790	143	0.0295	41	-	
128	psl-003	0.0065	32	0.0099	35	0.0028	40	0.0055	18	0.0075	17	1.0000	188	0.0296	43	-	
129	pyramid-000	0.0136	89	0.0233	96	0.0056	90	0.0117	84	0.0192	87	0.0185	69	0.0304	53	-	
130	rankone-007	0.0197	122	0.0366	130	0.0057	94	0.0113	79	0.0177	79	0.0286	106	0.0450	107	0.6686	55
131	rankone-008	0.0124	80	0.0232	94	0.0045	67	0.0082	45	0.0107	31	0.0188	73	0.0420	98	-	
132	realnetworks-002	0.0248	133	0.0358	127	0.0099	136	0.0513	153	0.1127	152	0.0371	119	0.0334	75	-	

Table 8: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA columns compare images described in section 2.2. The MUGSHOT columns compare images described in section 2.5. The VISA-BORDER column compare images described in section 2.3 with those described in section 2.4. The WILD columns compare images described in section 2.6. The CHILD-EXPLOITATION columns compare images described in section 2.1.

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
133	realnetworks-003	0.0259	137	0.0372	132	0.0100	137	0.0541	154	0.1208	154	0.0378	121	0.0335	77	0.5152	29
134	remarkai-001	0.0144	94	0.0256	107	0.0061	97	0.0102	68	0.0159	66	0.0162	57	0.0308	59	-	
135	remarkai-002	0.0151	100	0.0197	80	0.0102	138	0.0075	39	0.0108	34	0.0119	36	0.0426	99	-	
136	rokid-000	0.0093	56	0.0145	56	0.0038	56	0.0073	34	0.0102	30	0.0164	60	0.0857	136	-	
137	rokid-001	0.0105	67	0.0162	64	0.0042	61	0.0094	58	0.0163	70	0.0181	68	0.0325	68	-	
138	s1-001	0.0314	144	0.0651	147	0.0099	135	0.0252	136	0.0357	124	0.0444	129	0.8493	181	-	
139	saffe-001	0.4339	180	0.5261	180	0.2340	185	0.7539	187	0.8736	185	0.7977	177	0.3887	174	0.8973	88
140	saffe-002	0.0119	78	0.0206	82	0.0054	89	0.0107	72	0.0177	78	0.0244	94	0.0308	58	-	
141	samtech-001	0.0197	121	0.0365	128	0.0066	106	0.0146	105	0.0241	104	0.0238	92	0.0337	78	-	
142	scanovate-001	0.0175	114	0.0331	122	0.0061	98	0.0163	115	0.0248	106	0.2476	161	0.4060	175	-	
143	sensetime-002	0.0068	36	0.0098	33	0.0035	51	0.0143	102	-		0.0278	104	0.9999	188	0.5309	33
144	sensetime-003	0.0021	3	0.0027	2	0.0005	3	0.0027	1	0.0027	1	0.0051	6	0.0329	72	0.3683	9
145	sertis-000	0.0118	76	0.0208	83	0.0047	70	0.0080	42	0.0127	45	0.0110	33	0.0285	23	-	
146	shaman-000	0.9297	195	0.9774	195	0.9128	196	0.9990	192	-		0.9999	184	0.9575	184	0.9618	91
147	shaman-001	0.3346	175	0.4616	176	0.1360	177	0.2368	169	0.3723	167	0.3574	165	0.1498	152	0.8990	89
148	shu-001	0.0103	63	0.0140	54	0.0044	65	0.0293	143	0.0688	147	0.0172	66	0.0986	143	0.4590	20
149	shu-002	-		0.0079	23	0.0017	17	0.0146	104	0.0308	117	1.0000	187	0.0284	20	-	
150	siat-002	0.0091	55	0.0126	50	0.0039	57	0.0109	73	0.0190	86	0.0276	103	0.0520	120	0.4277	16
151	siat-004	0.0067	34	0.0099	36	0.0028	41	0.0152	110	-		0.0275	100	1.0000	189	-	
152	sjtu-001	0.0051	18	0.0080	24	0.0019	20	0.0211	127	0.0446	134	0.0131	42	0.0289	33	-	
153	sjtu-002	0.0053	22	0.0078	22	0.0027	39	0.0138	98	0.0296	115	0.0084	17	0.0284	21	-	
154	smilart-002	0.2440	172	0.3532	171	0.0821	172	-		-		0.3785	166	-		0.6999	62
155	smilart-003	0.6944	190	0.8836	190	0.1088	176	0.0695	156	0.1193	153	0.0894	146	0.1190	148	-	
156	starhybrid-001	0.0108	69	0.0138	53	0.0058	95	0.0081	44	0.0113	38	0.0152	48	0.0350	85	0.5584	37
157	synesis-005	0.0147	95	0.0226	92	0.0073	120	0.0153	111	0.0226	98	0.0213	83	0.0334	76	0.5601	38
158	synesis-006	0.0070	38	0.0096	31	0.0023	32	0.0107	71	0.0166	74	-		0.0292	35	-	
159	synology-000	0.0149	96	0.0238	99	0.0067	109	0.0148	106	0.0261	109	0.0221	86	0.0330	74	-	
160	tech5-002	0.0046	16	0.0063	15	0.0009	6	0.0113	81	0.0216	94	0.0233	89	0.0310	62	-	
161	tech5-003	0.0053	21	0.0070	17	0.0014	12	0.0099	65	0.0185	82	0.0095	25	0.0306	54	0.8963	86
162	tevian-004	0.0228	126	0.0304	117	0.0069	111	0.0226	130	0.0478	137	0.0128	40	0.0394	94	-	
163	tevian-005	0.0043	13	0.0062	13	0.0020	25	0.0057	24	0.0085	25	0.0070	10	0.0300	48	0.5625	41
164	tiger-002	0.0658	155	0.0889	151	0.0227	153	0.1083	163	0.1766	162	0.0952	149	0.0512	117	0.7862	76
165	tiger-003	0.0313	143	0.0602	146	0.0087	127	0.0188	121	0.0359	125	0.0344	114	0.0482	115	0.5610	40
166	tongyi-005	0.0073	42	0.0146	58	0.0019	23	0.0187	120	0.0421	130	0.0161	55	0.0399	95	0.6195	49
167	toshiba-002	0.0134	87	0.0222	91	0.0048	76	0.0097	62	0.0154	65	-		0.0434	102	0.7103	63
168	toshiba-003	0.0125	81	0.0214	86	0.0047	71	0.0085	50	0.0131	49	-		0.0282	16	-	
169	trueface-000	0.0249	134	0.4321	175	0.0069	113	0.0119	86	0.0180	80	0.0297	111	0.0614	128	-	
170	tuputech-000	0.3218	174	0.3696	173	0.2779	186	-		-		0.3237	163	0.9415	183	-	
171	ulsee-001	0.0151	99	0.0246	105	0.0080	123	0.0113	78	0.0185	84	0.0187	72	0.0316	64	-	
172	uluface-002	0.0081	47	0.0123	47	0.0033	49	0.0071	31	0.0095	28	0.0107	31	0.0444	104	0.6729	56
173	uluface-003	0.0100	62	0.0150	59	0.0044	66	0.0079	41	0.0128	47	-		0.0635	130	-	
174	upc-001	0.0234	127	0.0519	138	0.0071	116	0.0291	141	0.0490	140	0.0294	108	0.0314	63	0.4224	14
175	vcog-002	0.7522	192	0.9033	191	0.5040	192	-		-		-		-		0.7523	70
176	vd-001	0.0243	130	0.0452	137	0.0093	131	0.0271	140	0.0402	128	0.0424	127	0.1389	151	-	

Table 9: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA columns compare images described in section 2.2. The MUGSHOT columns compare images described in section 2.5. The VISA-BORDER column compare images described in section 2.3 with those described in section 2.4. The WILD columns compare images described in section 2.6. The CHILD-EXPLOITATION columns compare images described in section 2.1.

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
177	veridas-002	0.1733	168	0.2257	166	0.0528	167	0.2617	171	0.4147	169	0.2073	158	0.0450	108	-	
178	veridas-003	0.0557	151	0.0983	156	0.0154	145	0.0734	157	0.1267	155	0.0694	142	0.0299	45	0.5785	43
179	via-000	0.0216	125	0.0365	129	0.0088	128	0.0177	118	0.0287	113	0.0296	109	0.0349	84	0.7638	71
180	videmo-000	0.0298	141	0.0423	135	0.0211	151	0.0155	112	0.0260	108	0.0246	95	0.0541	122	-	
181	videonetics-001	0.5483	187	0.6446	185	0.3063	189	0.7517	186	0.8607	183	0.8664	179	0.2986	169	0.7297	67
182	videonetics-002	0.4274	179	0.5329	181	0.2168	181	0.6081	179	0.7438	177	0.7775	175	0.1976	158	0.7435	69
183	vigilantsolutions-006	0.1264	163	0.3221	169	0.0136	144	0.0150	109	0.0254	107	0.0493	132	0.0321	66	-	
184	vigilantsolutions-007	0.0202	124	0.0307	118	0.0070	115	0.0136	97	0.0227	99	0.0356	118	0.0306	55	1.0000	184
185	vion-000	0.0419	148	0.0590	144	0.0288	159	0.0422	150	0.0478	138	0.0581	137	0.2479	164	0.8765	82
186	visionbox-000	0.0293	139	0.0541	140	0.0110	141	0.0197	123	0.0339	119	0.0349	115	0.0476	114	-	
187	visionbox-001	0.0159	106	0.0270	110	0.0072	118	0.0111	75	0.0173	77	0.0190	74	0.0389	93	-	
188	visionlabs-007	0.0038	8	0.0048	7	0.0012	11	0.0036	8	0.0048	7	0.0057	7	0.0286	26	0.3708	10
189	visionlabs-008	0.0026	4	0.0036	4	0.0007	4	0.0031	5	0.0040	4	0.0045	3	0.0282	18	-	
190	visteam-000	0.9200	194	0.9489	193	0.8616	195	0.9959	190	-		0.9994	183	0.8783	182	-	
191	vocord-007	0.0039	9	0.0053	9	0.0012	10	0.0061	26	0.0094	27	0.0520	134	0.0280	10	0.8468	79
192	vocord-008	0.0029	5	0.0038	5	0.0008	5	0.0042	13	0.0055	13	0.0045	4	0.0286	25	-	
193	winsense-000	0.0140	92	0.0228	93	0.0056	91	0.0125	93	0.0215	93	0.0226	87	0.0352	86	0.8600	81
194	winsense-001	0.0062	29	0.0099	37	0.0022	28	0.0092	55	0.0210	89	0.0093	23	0.0320	65	0.4155	13
195	x-laboratory-000	0.0071	39	0.0106	38	0.0030	43	0.0123	90	0.0138	55	0.0419	126	0.0295	42	0.9686	92
196	x-laboratory-001	0.0059	28	0.0110	42	0.0022	27	0.0054	17	0.0078	19	0.0094	24	0.0294	37	-	
197	xforwardai-000	0.0050	17	0.0072	18	0.0018	19	0.0036	9	0.0051	11	0.0074	11	0.0276	4	-	
198	yisheng-004	0.1988	170	0.3329	170	0.0475	166	0.1147	165	0.1849	163	0.2044	157	0.0908	138	0.7152	64
199	yitu-003	0.0015	1	0.0026	1	0.0003	1	0.0066	30	0.0085	22	0.0064	8	0.0325	69	-	

Table 10: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA columns compare images described in section 2.2. The MUGSHOT columns compare images described in section 2.5. The VISA-BORDER column compare images described in section 2.3 with those described in section 2.4. The WILD columns compare images described in section 2.6. The CHILD-EXPLOITATION columns compare images described in section 2.1.

Figure 1: The points show false non-match rates (FNMR) versus the size of the encoded template. FNMR is the geometric mean of FNMR values for visa and mugshot images (from Figs. 32 and 42) at a false match rate (FMR) of 0.0001. The color of the points encodes template generation time - which spans at least one order of magnitude. Durations are measured on a single core of a c. 2016 Intel Xeon CPU E5-2630 v4 running at 2.20GHz. Algorithms with poor FNMR are omitted.

Figure 2: The points show false non-match rates (FNMR) versus the duration of the template generation operation. FNMR is the geometric mean of FNMR values for visa and mugshot images (from Figs. 32 and 42) at a false match rate (FMR) of 0.0001. Template generation time is a median estimated over 640 x 480 pixel portraits. It is measured on a single core of a c. 2016 Intel Xeon CPU E5-2630 v4 running at 2.20GHz. The color of the points encodes template size - which span two orders of magnitude. Algorithms with poor FNMR are omitted.

1 Metrics

1.1 Core accuracy

Given a vector of N genuine scores, u, the false non-match rate (FNMR) is computed as the proportion below some threshold, T:

$$\text{FNMR}(T) = 1 - \frac{1}{N}\sum_{i=1}^{N} H(u_i - T) \tag{1}$$

where $H(x)$ is the unit step function, and $H(0)$ taken to be 1.

Similarly, given a vector of N impostor scores, v, the false match rate (FMR) is computed as the proportion above T:

$$\text{FMR}(T) = \frac{1}{N}\sum_{i=1}^{N} H(v_i - T) \tag{2}$$

The threshold, T, can take on any value. We typically generate a set of thresholds from quantiles of the observed impostor scores, v, as follows. Given some interesting false match rate range, $[\text{FMR}_L, \text{FMR}_U]$, we form a vector of K thresholds corresponding to FMR measurements evenly spaced on a logarithmic scale

$$T_k = Q_v(1 - \text{FMR}_k) \tag{3}$$

where Q is the quantile function, and FMR_k comes from

$$\log_{10}\text{FMR}_k = \log_{10}\text{FMR}_L + \frac{k}{K}\,[\log_{10}\text{FMR}_U - \log_{10}\text{FMR}_L] \tag{4}$$

Error tradeoff characteristics are plots of FNMR(T) vs. FMR(T). These are plotted with $\text{FMR}_U \to 1$ and FMR_L as low as is sustained by the number of impostor comparisons, N. This is somewhat higher than the "rule of three" limit $3/N$ because samples are not independent, due to re-use of images.

2 Datasets

2.1 Child exploitation images

- ▷ The number of images is on the order of 10^4.
- ▷ The number of subjects is on the order of 10^3.
- ▷ The number of subjects with two images on the order of 10^3.
- ▷ The images are operational. They are taken from ongoing investigations of child exploitation crimes. The images are arbitrarily unconstrained. Pose varies considerably around all three axes, including subject lying down. Resolution varies very widely. Faces can be occluded by other objects, including hair and hands. Lighting varies, although the images are intended for human viewing. Mis-focus is rare. Images are given to the algorithm without any cropping; faces may occupy widely varying areas.
- ▷ The images are usually large from contemporary cameras. The mean interocular distance (IOD) is 70 pixels.
- ▷ The images are of subjects from several countries, due to the global production of this imagery.
- ▷ The images are of children, from infancy to late adolescence.
- ▷ All of the images are live capture, none are scanned. Many have been cropped.
- ▷ When these images are input to the algorithm, they are labelled as being of type ”EXPLOITATION” - see Table 4 of the FRVT API.

2.2 Visa images

- ▷ The number of images is on the order of 10^5.
- ▷ The number of subjects is on the order of 10^5.
- ▷ The number of subjects with two images is on the order of 10^4.
- ▷ The images have geometry in reasonable conformance with the ISO/IEC 19794-5 Full Frontal image type. Pose is generally excellent.
- ▷ The images are of size 252x300 pixels. The mean interocular distance (IOD) is 69 pixels.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to visa issuance patterns.
- ▷ The images are of subjects of all ages, including children, again with imbalance due to visa issuance demand.
- ▷ Many of the images are live capture. A substantial number of the images are photographs of paper photographs.
- ▷ When these images are input to the algorithm, they are labelled as being of type ”ISO” - see Table 4 of the FRVT API.

2.3 Application images

- ▷ The number of images is on the order of 10^6.
- ▷ The number of subjects is on the order of 10^6.
- ▷ The number of subjects with two images is on the order of 10^6.

- ▷ The images have geometry in good conformance with the ISO/IEC 19794-5 Full Frontal image type. Pose is generally excellent.
- ▷ The images are of size 300x300 pixels. The mean interocular distance (IOD) is 61 pixels.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to population and immigration patterns.
- ▷ The images are of subjects of adults with imbalance due due to population and immigration patterns and demand.
- ▷ All of the images are live capture.
- ▷ When these images are input to the algorithm, they are labelled as being of type "ISO" - see Table 4 of the FRVT API.

2.4 Border crossing images

- ▷ The number of images is on the order of 10^6.
- ▷ The number of subjects is on the order of 10^6.
- ▷ The number of subjects with two images is on the order of 10^6.
- ▷ The images are taken with at camera oriented by an attendant toward a cooperating subject. This is done under time constraints so there are role, pitch and yaw angle variations. Also background illumination is sometimes strong, so the face is under-exposed. There is some perspective distortion due to close range images. Some faces are partially cropped.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to population and immigration patterns.
- ▷ The images are of subjects of adults with imbalance due due to population and immigration patterns and demand.
- ▷ The images have mean IOD of 38 pixels.
- ▷ The images are all live capture.
- ▷ When these images are input to the algorithm, they are labelled as being of type "WILD" - see Table 4 of the FRVT API.

2.5 Mugshot images

- ▷ The number of images is on the order of 10^6.
- ▷ The number of subjects is on the order of 10^6.
- ▷ The number of subjects with two images is on the order of 10^6.
- ▷ The images have geometry in reasonable conformance with the ISO/IEC 19794-5 Full Frontal image type.
- ▷ The images are of variable sizes. The median IOD is 105 pixels. The mean IOD is 113 pixels. The 1-st, 5-th, 10-th, 25-th, 75-th, 90-th and 99-th percentiles are 34, 58, 70, 87, 121, 161 and 297 pixels.
- ▷ The images are of subjects from the United States.
- ▷ The images are of adults.
- ▷ The images are all live capture.
- ▷ When these images are input to the algorithm, they are labelled as being of type "mugshot" - see Table 4 of the FRVT API.

(a) Visa (b) Mugshot (c) Wild (d) Border (from VisaBorder)

Figure 3: The figure gives simulated samples of image types used in this report.

2.6 Wild images

- ▷ The number of images is on the order of 10^5.
- ▷ The number of subjects is on the order of 10^3.
- ▷ The number of subjects with two images on the order of 10^3.
- ▷ The images include many photojournalism-style images. Images are given to the algorithm using a variable but generally tight crop of the head. Resolution varies very widely. The images are very unconstrained, with wide yaw and pitch pose variation. Faces can be occluded, including hair and hands.
- ▷ The images are of adults.
- ▷ All of the images are live capture, none are scanned.
- ▷ When these images are input to the algorithm, they are labelled as being of type "WILD" - see Table 4 of the FRVT API.

3 Results

3.1 Test goals

- ▷ To state overall accuracy.
- ▷ To compare algorithms.

3.2 Test design

Method: For visa images:

- ▷ The comparisons are of visa photos against visa photos.
- ▷ The number of genuine comparisons is on the order of 10^4.
- ▷ The number of impostor comparisons is on the order of 10^{10}.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates. However, later analysis is conducted on subsets.
- ▷ The number of persons is on the order of 10^5.
- ▷ The number of images used to make 1 template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

For mugshot images:

- ▷ The comparisons are of mugshot photos against mugshot photos.
- ▷ The number of genuine comparisons is on the order of 10^6.
- ▷ The number of impostor comparisons is on the order of 10^8.
- ▷ The impostors are paired by sex, but not by age or other covariates.
- ▷ The number of persons is on the order of 10^6.
- ▷ The number of images used to make 1 template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

Method: For wild images:

- ▷ The comparisons are of wild photos against wild photos.
- ▷ The number of genuine comparisons is on the order of 10^6.
- ▷ The number of impostor comparisons is on the order of 10^7.
- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates.
- ▷ The number of persons is on the order of 10^4.
- ▷ The number of images used to make 1 template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

For child exploitation images:

- ▷ The comparisons are of unconstrained child exploitation photos against others of the same type.
- ▷ The number of genuine comparisons is on the order of 10^4.
- ▷ The number of impostor comparisons is on the order of 10^7.
- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates.
- ▷ The number of persons is on the order of 10^3.
- ▷ The number of images used to make 1 template is 1.

- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.
- ▷ We produce two performance statements. First, is a DET as used for visa and mugshot images. The second is a cumulative match characteristic (CMC) summarizing a simulated one-to-many search process. This is done as follows.
  - We regard M enrollment templates as items in a gallery.
  - These M templates come from $M > N$ individuals, because multiple images of a subject are present in the gallery under separate identifiers.
  - We regard the verification templates as search templates.
  - For each search we compute the rank of the highest scoring mate.
  - This process should properly be conducted with a 1:N algorithm, such as those tested in NIST IR 8009. We use the 1:1 algorithms in a simulated 1:N mode here to a) better reflect what a child exploitation analyst does, and b) to show algorithm efficacy is better than that revealed in the verification DETs.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3.3 Failure to enroll

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
1	3divi-003	0.1806	70	0.0007	153	0.0006	145	0.0294	168
2	3divi-004	0.2302	80	0.0008	157	0.0006	147	0.0222	165
3	acer-000	-	199	0.0002	105	0.0004	120	0.0008	102
4	adera-001	0.1928	74	0.0003	119	0.0005	139	0.0505	181
5	advance-002	-	199	0.0000	64	0.0004	103	0.0009	110
6	aifirst-001	0.0000	4	0.0000	3	0.0000	3	0.0000	43
7	ailabs-001	-	199	0.0007	156	0.0005	128	0.0016	120
8	aimall-001	0.0000	20	0.0000	21	0.0000	22	0.0001	51
9	aiunionface-000	-	199	0.0000	28	0.0000	30	0.0000	46
10	alchera-000	-	199	0.0004	134	0.0014	179	0.0038	131
11	alchera-001	-	199	0.0004	133	0.0014	178	0.0038	130
12	allgovision-000	-	199	0.0026	186	0.0052	195	0.0131	153
13	alphaface-001	-	199	0.0000	67	0.0004	110	0.0004	71
14	alphaface-002	-	199	0.0000	68	0.0004	111	0.0004	73
15	amplifiedgroup-001	-	199	0.0189	198	0.0279	201	0.1390	195
16	androvideo-000	-	199	0.0000	17	0.0000	17	0.0002	54
17	anke-004	0.0944	55	0.0001	85	0.0004	112	0.0006	92
18	anke-005	0.1228	62	0.0001	96	0.0004	119	0.0007	95
19	antheus-000	0.0000	18	0.0000	45	0.0000	49	0.0242	166
20	anyvision-002	0.4866	98	0.0070	195	0.0090	198	0.1146	191
21	anyvision-004	0.1660	67	0.0001	95	0.0004	101	0.0080	141
22	asusaics-000	-	199	0.0000	23	0.0000	24	0.0000	17
23	aware-003	0.3314	90	0.0016	180	0.0013	175	0.0745	188
24	aware-004	-	199	0.0002	103	0.0005	126	0.0014	118
25	awiros-001	-	199	0.0386	199	0.0872	202	0.3415	199
26	ayonix-000	0.0000	3	0.0113	196	0.0137	200	0.1194	192
27	bioidtechswiss-000	-	199	0.0003	118	0.0004	122	0.0006	88
28	bm-001	0.0000	22	0.0000	52	0.0000	25	0.0000	18
29	camvi-002	0.0000	5	0.0000	34	0.0000	36	0.0000	27
30	camvi-004	0.0000	10	0.0000	38	0.0000	41	0.0000	32
31	ceiec-002	0.2482	84	0.0036	190	0.0031	191	0.0081	142
32	ceiec-003	-	199	0.0001	73	0.0004	108	0.0004	68
33	chosun-000	-	199	0.0000	11	0.0000	11	0.0000	9
34	chtface-001	-	199	0.0000	41	0.0000	44	0.0000	35
35	chtface-002	-	199	0.0002	115	0.0007	150	0.0014	117
36	cib-000	-	199	0.0001	98	0.0000	38	0.0000	29
37	cogent-003	-	199	0.0001	80	0.0004	98	0.0009	112
38	cogent-004	0.0000	7	0.0000	5	0.0000	5	0.0000	3
39	cognitec-000	0.6342	102	0.0007	154	0.0007	154	0.0388	176
40	cognitec-001	-	199	0.0008	161	0.0010	157	0.0185	161
41	ctbcbank-000	0.3285	89	0.0011	169	0.0019	183	0.0868	190
42	ctbcbank-001	-	199	0.0005	146	0.0010	158	0.0844	189
43	cyberextruder-001	0.5338	100	0.0024	184	0.0029	189	0.0597	185
44	cyberextruder-002	0.2672	87	0.0027	187	0.0028	188	0.0335	173
45	cyberlink-002	0.1463	66	0.0004	127	0.0004	125	0.0007	99
46	cyberlink-003	-	199	0.0001	71	0.0004	85	0.0008	104
47	dahua-003	0.2222	79	0.0002	110	0.0003	65	0.0002	56
48	dahua-004	-	199	0.0001	94	0.0003	61	0.0002	57
49	deepglint-001	0.0000	23	0.0000	24	0.0000	26	0.0000	19
50	deepglint-002	0.0669	49	0.0002	111	0.0004	87	0.0003	62
51	deepsea-001	0.0000	11	0.0000	9	0.0000	9	0.0000	7
52	dermalog-005	0.1796	68	0.0013	175	0.0041	192	0.0163	159
53	dermalog-006	0.1797	69	0.0013	174	0.0041	193	0.0163	160
54	didiglobalface-001	0.2175	77	0.0000	66	0.0004	109	0.0004	70
55	digitalbarriers-002	-	199	0.0028	188	0.0027	187	0.0071	140
56	dsk-000	0.0000	17	0.0000	16	0.0000	16	0.0000	13
57	einetworks-000	-	199	0.0002	108	0.0005	137	0.0008	105
58	everai-paravision-003	0.0705	51	0.0002	102	0.0004	86	0.0004	80
59	expasoft-000	-	199	0.0000	48	0.0000	52	0.0000	40
60	f8-001	0.2026	76	0.0035	189	0.0030	190	0.0087	145

Table 11: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
61	facesoft-000	0.0000	29	0.0000	50	0.0000	54	0.0000	41
62	fujitsulab-000	-	199	0.0005	142	0.0002	57	0.0099	147
63	glory-001	0.0000	14	0.0051	193	0.0010	160	0.1651	196
64	glory-002	-	199	0.0015	177	0.0011	171	0.0557	183
65	gorilla-003	0.1347	63	0.0003	126	0.0004	124	0.0043	134
66	gorilla-004	-	199	0.0000	55	0.0003	69	0.0004	77
67	hik-001	-	199	0.0000	40	0.0000	43	0.0000	34
68	hr-001	0.1198	61	0.0001	70	0.0004	90	0.0003	65
69	hr-002	-	199	0.0002	107	0.0004	113	0.0004	69
70	id3-003	0.3032	88	0.0016	181	0.0011	170	0.0317	171
71	id3-004	-	199	0.0015	179	0.0011	169	-	199
72	idemia-004	-	199	0.0000	57	0.0004	82	0.0003	66
73	idemia-005	0.0239	34	0.0000	54	0.0003	70	0.0003	61
74	iit-001	0.0843	54	0.0001	100	0.0004	105	0.0104	148
75	iit-002	-	199	0.0009	164	0.0005	142	0.0443	179
76	imagus-000	0.1107	59	0.0010	168	0.0012	173	0.0347	174
77	imagus-001	-	199	0.0001	86	0.0004	106	0.0396	177
78	imperial-000	-	199	0.0000	27	0.0000	29	0.0000	22
79	imperial-002	0.0000	9	0.0000	8	0.0000	8	0.0000	6
80	incode-005	-	199	0.0001	81	0.0004	104	0.0007	100
81	incode-006	-	199	0.0001	97	0.0004	75	0.0004	75
82	innovativetechnologyltd-001	-	199	0.0024	185	0.0025	186	0.0055	138
83	innovatrics-004	0.1170	60	0.0000	65	0.0004	107	0.0041	133
84	innovatrics-006	0.0350	37	0.0000	59	0.0004	79	0.0003	67
85	intellicloudai-001	-	199	0.0000	49	0.0000	53	0.0001	52
86	intellifusion-001	0.0949	56	0.0001	77	0.0003	73	0.0005	87
87	intellivision-001	0.5495	101	0.0048	192	0.0042	194	0.1358	193
88	intellivision-002	-	199	0.0012	171	0.0005	143	0.0146	154
89	intelresearch-000	-	199	0.0000	61	0.0003	72	0.0001	53
90	intelresearch-001	-	199	0.0005	145	0.0010	159	0.0407	178
91	intsysmsu-000	-	199	0.0004	132	0.0012	172	0.0031	129
92	intsysmsu-001	-	199	0.0001	84	0.0004	102	0.0004	78
93	iqface-000	0.0000	12	0.0000	39	0.0000	42	0.0000	33
94	iqface-001	-	199	0.0000	51	0.0000	18	0.0000	14
95	isap-001	-	199	0.0000	37	0.0000	40	0.0000	31
96	isityou-000	0.4714	96	0.0023	182	0.0010	162	0.0663	187
97	isystems-001	0.1421	64	0.0010	166	0.0007	151	0.0128	151
98	isystems-002	0.1421	65	0.0010	167	0.0007	152	0.0128	152
99	itmo-006	-	199	0.0004	137	0.0004	100	0.0006	91
100	itmo-007	-	199	0.0003	125	0.0000	46	0.0004	76
101	kakao-001	-	199	0.0002	112	0.0005	130	0.0310	169
102	kakao-002	0.2494	85	0.0002	113	0.0005	133	0.0310	170
103	kedacom-000	0.0000	21	0.0000	22	0.0000	23	0.0000	16
104	kneron-003	0.4883	99	0.0044	191	0.0016	182	0.1823	197
105	kneron-005	-	199	0.0006	150	0.0005	134	0.0097	146
106	lookman-002	-	199	0.0000	36	0.0000	39	0.0000	30
107	lookman-004	0.0000	1	0.0000	32	0.0000	34	0.0000	25
108	luxand-000	-	199	0.0000	10	0.0000	10	0.0000	8
109	megvii-001	0.0274	36	0.0007	155	0.0004	84	0.0152	157
110	megvii-002	0.0274	35	0.0054	194	0.0004	83	0.0126	150
111	meiya-001	-	199	0.0004	138	0.0010	163	0.0025	125
112	microfocus-001	0.0791	53	0.0008	160	0.0016	181	0.0220	164
113	microfocus-002	0.0791	52	0.0008	159	0.0016	180	0.0220	163
114	mt-000	0.1043	57	0.0002	109	0.0004	114	0.0004	72
115	mvision-001	-	199	0.0000	33	0.0000	35	0.0000	26
116	netbridgetech-001	-	199	0.0000	7	0.0000	7	0.0000	5
117	neurotechnology-006	0.1068	58	0.0004	131	0.0004	92	0.0018	121
118	neurotechnology-008	-	199	0.0004	130	0.0004	89	0.0018	122
119	nodeflux-001	-	199	0.0001	87	0.0002	60	0.0003	60
120	nodeflux-002	-	199	0.0008	158	0.0005	136	0.0008	108

Table 12: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
121	notiontag-000	0.0000	27	0.0000	29	0.0000	31	0.0000	23
122	ntechlab-007	0.0682	50	0.0001	72	0.0004	80	0.0005	86
123	ntechlab-008	-	199	0.0001	74	0.0004	77	0.0005	83
124	paravision-004	0.0570	44	0.0002	106	0.0004	95	0.0008	103
125	pixelall-002	0.0001	30	0.0000	15	0.0000	15	0.0001	48
126	pixelall-003	-	199	0.0000	43	0.0000	47	0.0000	36
127	psl-002	-	199	0.0000	20	0.0000	21	0.0000	15
128	psl-003	-	199	0.0000	62	0.0004	99	0.0003	64
129	pyramid-000	-	199	0.0005	143	0.0007	153	0.0015	119
130	rankone-007	0.3518	92	0.0003	120	0.0004	116	0.0043	135
131	rankone-008	-	199	0.0003	116	0.0004	74	0.0040	132
132	realnetworks-002	-	199	0.0004	129	0.0003	67	0.0004	79
133	realnetworks-003	0.0076	32	0.0004	128	0.0003	66	0.0004	81
134	remarkai-001	-	199	0.0000	31	0.0000	33	0.0000	47
135	remarkai-002	-	199	0.0000	19	0.0000	20	0.0000	44
136	rokid-000	-	199	0.0001	83	0.0005	135	0.0354	175
137	rokid-001	-	199	0.0000	18	0.0000	19	0.0007	101
138	s1-001	-	199	0.0013	172	0.0007	149	0.0600	186
139	saffe-001	0.0000	26	0.0000	26	0.0000	28	0.0000	21
140	saffe-002	-	199	0.0000	46	0.0000	50	0.0000	37
141	samtech-001	-	199	0.0004	136	0.0008	155	0.0013	116
142	scanovate-001	-	199	0.0024	183	0.0014	177	0.2751	198
143	sensetime-002	0.3345	91	0.0011	170	0.0005	141	0.0218	162
144	sensetime-003	0.0554	42	0.0000	53	0.0004	96	0.0004	82
145	sertis-000	-	199	0.0000	69	0.0004	88	0.0004	74
146	shaman-000	0.0000	6	0.0000	35	0.0000	37	0.0000	28
147	shaman-001	0.0000	2	0.0000	2	0.0000	2	0.0000	42
148	shu-001	0.1822	71	0.0010	165	0.0006	144	0.0499	180
149	shu-002	-	199	0.0005	139	0.0004	115	0.0007	96
150	siat-002	0.0616	46	0.0000	60	0.0004	97	0.0048	137
151	siat-004	-	199	0.0000	58	0.0004	94	0.0003	63
152	sjtu-001	-	199	0.0005	141	0.0004	121	0.0008	106
153	sjtu-002	-	199	0.0005	140	0.0004	118	0.0007	98
154	smilart-002	0.2422	82	0.0003	124	0.0011	166	0.0575	184
155	smilart-003	-	199	0.0014	176	0.0013	176	0.0555	182
156	starhybrid-001	0.2340	81	0.0009	163	0.0023	185	0.0044	136
157	synesis-005	0.1862	72	0.0001	82	0.0005	127	0.0021	123
158	synesis-006	-	199	0.0000	63	0.0003	63	0.0002	59
159	synology-000	-	199	0.0000	13	0.0000	13	0.0000	11
160	tech5-002	-	199	0.0001	79	0.0003	62	0.0000	45
161	tech5-003	0.0016	31	0.0001	78	0.0003	64	0.0002	55
162	tevian-004	-	199	0.0002	104	0.0005	138	0.0057	139
163	tevian-005	0.3606	93	0.0006	151	0.0006	148	0.0012	114
164	tiger-002	0.0619	47	0.0001	90	0.0004	93	0.0082	144
165	tiger-003	0.0619	48	0.0001	88	0.0004	91	0.0082	143
166	tongyi-005	0.0000	8	0.0000	6	0.0000	6	0.0000	4
167	toshiba-002	0.0000	16	0.0000	14	0.0000	14	0.0000	12
168	toshiba-003	-	199	0.0001	91	0.0001	56	0.0002	58
169	trueface-000	-	199	0.0000	47	0.0000	51	0.0000	38
170	tuputech-000	-	199	0.0632	200	0.0081	197	0.6383	200
171	ulsee-001	-	199	0.0000	44	0.0000	48	0.0001	49
172	uluface-002	0.0000	28	0.0000	30	0.0000	32	0.0000	24
173	uluface-003	-	199	0.0002	101	0.0002	58	0.0244	167
174	upc-001	0.0450	39	0.0003	117	0.0003	71	0.0011	113
175	vd-001	-	199	0.0004	135	0.0009	156	0.0024	124
176	veridas-002	-	199	0.0001	92	0.0005	132	0.0006	90
177	veridas-003	0.1893	73	0.0001	89	0.0005	131	0.0006	89
178	via-000	0.0000	13	0.0000	42	0.0000	45	0.0001	50
179	videmo-000	-	199	0.0003	121	0.0012	174	0.0158	158
180	videonetics-001	0.4799	97	0.0015	178	0.0010	161	0.0112	149

Table 13: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
181	videonetics-002	0.4598	95	0.0006	152	0.0005	140	0.0013	115
182	vigilantsolutions-006	-	199	0.0001	76	0.0004	81	0.0005	85
183	vigilantsolutions-007	0.2538	86	0.0001	75	0.0004	78	0.0005	84
184	vion-000	0.6388	103	0.0130	197	0.0078	196	0.1389	194
185	visionbox-000	-	199	0.0005	149	0.0011	168	0.0028	128
186	visionbox-001	-	199	0.0005	148	0.0011	167	0.0028	127
187	visionlabs-007	0.1939	75	0.0003	122	0.0005	129	0.0008	107
188	visionlabs-008	-	199	0.0002	114	0.0004	123	0.0009	109
189	visteam-000	-	199	0.0005	144	0.0011	164	0.0026	126
190	vocord-007	0.0000	19	0.0001	99	0.0004	76	0.0009	111
191	vocord-008	-	199	0.0003	123	0.0001	55	0.0007	97
192	winsense-000	0.0000	15	0.0000	12	0.0000	12	0.0000	10
193	winsense-001	0.0000	24	0.0000	25	0.0000	27	0.0000	20
194	x-laboratory-000	0.0000	25	0.0005	147	0.0002	59	0.0000	39
195	x-laboratory-001	-	199	0.0001	93	0.0004	117	0.0007	93
196	xforwardai-000	-	199	0.0000	1	0.0000	1	0.0000	1
197	yisheng-004	0.4279	94	0.0013	173	0.0006	146	0.0321	172
198	yitu-003	-	199	0.0009	162	0.0000	4	0.0000	2

Table 14: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.

3.4 Recognition accuracy

Core algorithm accuracy is stated via:

- ▷ **Cooperative subjects**
  - The summary table of Figure 10;
  - The visa image DETs of Figure 32;
  - The mugshot DETs of Figure 42;
  - The mugshot ageing profiles of Figure 157;
  - The human-difficult pairs of Figure 12
- ▷ **Non-cooperative subjects**
  - The photojournalism DET of Figure 51
  - The child-exploitation DET of Figure 55;
  - The child-exploitation CMC of Figure 59.

Figure 127 shows dependence of false match rate on algorithm score threshold. This allows a deployer to set a threshold to target a particular false match rate appropriate to the security objectives of the application.

Figure 107 likewise shows FMR(T) but for mugshots, and specially four subsets of the population.

Note that in both the mugshot and visa sets false match rates vary with the ethnicity, age, and sex, of the enrollee and impostor - see section 3.6. For example figure 70 summarizes FMR for impostors paired from four groups black females, black males, white females, white males.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 4: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 5: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 6: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 7: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 8: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 9: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 10: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 11: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 12: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 13: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 14: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 15: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 16: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 17: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 18: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 19: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 20: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 21: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 22: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 23: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 24: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 25: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 26: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 27: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 28: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 29: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 30: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 31: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 32: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 33: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 34: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 35: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 36: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 37: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 38: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 39: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 40: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 41: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 42: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 43: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 44: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 45: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 46: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 47: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 48: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 49: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 50: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 51: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 52: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 53: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 54: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 55: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 56: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 55 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 57: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 55 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 58: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 55 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 59: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 55 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 60: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank for two cases: 1. Whole image provided to the algorithm; 2. Human annotated rectangular region, cropped and provided to the algorithm. The difference between the traces is associated with detection of difficult faces, and fine localization.

Figure 61: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 62: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 63: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 64: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 65: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 66: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 67: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 68: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 69: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 70: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 71: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 72: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 73: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 74: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 75: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 76: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 77: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 78: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 79: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 80: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 107. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 81: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 82: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 83: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 84: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 85: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 86: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 87: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 88: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 89: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 90: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 91: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 92: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 93: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 94: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 95: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 96: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between $(FMR,FNMR)_{MALE}$ and $(FMR,FNMR)_{FEMALE}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 97: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 98: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 99: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 100: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 101: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 102: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 103: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 104: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 105: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 106: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 107: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 108: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 109: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 110: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 111: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 112: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 113: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 114: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 115: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 116: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 117: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 118: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 119: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 120: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 121: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 122: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 123: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 124: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 125: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 126: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 127: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 128: For the visa images, the curves show how false matches are concentrated in certain images. Specifically each line plots FMR(k) with k the number of images rejected in decreasing order of how many false matches that image was involved in. FMR(0) $= 10^{-4}$. In terms of the biometric zoo, the most "wolf-ish" images are rejected first i.e. those enrollment or verification images most often involved in false matches. A flatter response is considered superior. A steeply descending response indicates that certain kinds of images false match against others, e.g. if hypothetically images of men with particular mustaches would falsely match others.

3.5 Genuine distribution stability

3.5.1 Effect of birth place on the genuine distribution

Background: Both skin tone and bone structure vary geographically. Prior studies have reported variations in FNMR and FMR.

Goal: To measure false non-match rate (FNMR) variation with country of birth.

Methods: Thresholds are determined that give FMR = $\{0.001, 0.0001\}$ over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores. Only those countries with at least 140 individuals are included in the analysis.

Results: Figure 145 shows FNMR by country of birth for the two thresholds.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 129: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 130: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 131: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 132: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 133: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 134: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 135: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 136: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 137: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 138: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 139: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 140: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 141: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 142: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 143: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 144: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 145: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Caveats: The results may not relate to subject-specific properties. Instead they could reflect image-specific quality differences, which could occur due to collection protocol or software processing variations.

3.5.2 Effect of ageing

Background: Faces change appearance throughout life. This change gradually reduces similarity of a new image to an earlier image. Face recognition algorithms give reduced similarity scores and more frequent false rejections.

Goal: To quantify false non-match rates (FNMR) as a function of elapsed time in an adult population.

Methods: Using the mugshot images, a threshold is set to give FMR = 0.00001 over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores.

Results: For the visa images, Figure 157 shows how false non-match rates for genuine users, as a function of age group.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 146: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\widetilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 147: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\widetilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 148: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 149: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 150: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 151: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 152: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all (10^8) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 153: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all (10^8) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 154: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 155: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 156: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\widetilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 157: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{1}0^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

3.5.3 Effect of age on genuine subjects

Background: Faces change appearance throughout life. Face recognition algorithms have previously beeen reported to give better accuracy on older individuals (See NIST IR 8009).

Goal: To quantify false non-match rates (FNMR) as a function of age, without an ageing component.

Methods: Using the visa images, which span fewer than five years, thresholds are determined that give FMR = 0.001 and 0.0001 over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores.

Results: For the visa images, Figure 174 shows how false non-match rates for genuine users, as a function of age group.

The notable aspects are:

- ▷ Younger subjects give considerably higher FNMR. This is likely due to rapid growth and change in facial appearance.
- ▷ FNMR trends down throughout life. The last bin, AGE $>$ 72, contains fewer than 140 mated pairs, and may be affected by small sample size.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 158: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 159: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 160: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 161: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 162: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 163: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 164: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 165: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 166: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 167: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 168: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 169: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 170: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 171: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 172: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 173: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 174: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Caveats: None.

3.6 Impostor distribution stability

3.6.1 Effect of birth place on the impostor distribution

Background: Facial appearance varies geographically, both in terms of skin tone, cranio-facial structure and size. This section addresses whether false match rates vary intra- and inter-regionally.

Goals:

- ▷ To show the effect of birth region of the impostor and enrollee on false match rates.
- ▷ To determine whether some algorithms give better impostor distribution stability.

Methods:

- ▷ For the visa images, NIST defined 10 regions: Sub-Saharan Africa, South Asia, Polynesia, North Africa, Middle East, Europe, East Asia, Central and South America, Central Asia, and the Caribbean.
- ▷ For the visa images, NIST mapped each country of birth to a region. There is some arbitrariness to this. For example, Egypt could reasonably be assigned to the Middle East instead of North Africa. An alternative methodology could, for example, assign the Philippines to *both* Polynesia and East Asia.
- ▷ FMR is computed for cases where all face images of impostors born in region r_2 are compared with enrolled face images of persons born in region r_1.

$$\text{FMR}(r_1, r_2, T) = \frac{\sum_{i=1}^{N_{r_1,r_2}} H(s_i - T)}{N_{r_1,r_2}} \tag{5}$$

  where the same threshold, T, is used in all cells, and H is the unit step function. The threshold is set to give FMR(T) = 0.001 over the entire set of visa image impostor comparisons.
- ▷ This analysis is then repeated by country-pair, but only for those country pairs where both have at least 1000 images available. The countries[1] appear in the axes of graphs that follow.
- ▷ The mean number of impostor scores in any cross-region bin is 33 million. The smallest number of impostor scores in any bin is 135000, for Central Asia - North Africa. While these counts are large enough to support reasonable significance, the number of individual faces is much smaller, on the order of $N^{0.5}$.
- ▷ The numbers of impostor scores in any cross-country bin is shown in Figure 567.

Results: Subsequent figures show heatmaps that use color to represent the base-10 logarithm of the false match rate. Red colors indicate high (bad) false match rates. Dark colors indicate benign false match rates. There are two series of graphs corresponding to aggregated geographical regions, and to countries. The notable observations are:

- ▷ The on-diagonal elements correspond to within-region impostors. FMR is generally above the nominal value of FMR = 0.001. Particularly there is usually higher FMR in, Sub-Saharan Africa, South Asia, and the Caribbean. Europe and Central Asia, on the other hand, usually give FMR closer to the nominal value.
- ▷ The off-diagonal elements correspond to across-region impostors. The highest FMR is produced between the Caribbean and Sub-Saharan Africa.
- ▷ Algorithms vary.

[1] These are Argentina, Australia, Brazil, Chile, China, Costa Rica, Cuba, Czech Republic, Dominican Republic, Ecuador, Egypt, El Salvador, Germany, Ghana, Great Britain, Greece, Guatamala, Haiti, Hong Kong, Honduras, Indonesia, India, Israel, Jamaica, Japan, Kenya, Korea, Lebanon, Mexico, Malaysia, Nepal, Nigeria, Peru, Philippines, Pakistan, Poland, Romania, Russia, South Africa, Saudi Arabia, Thailand, Trinidad, Turkey, Taiwan, Ukraine, Venezuela, and Vietnam.

Figure 175: For the visa images, the dots show FMR for impostor comparisons of individuals of the same sex and same age group for the region of the world that gives the worst (highest) FMR when the threshold is set to give FMR = 0.001 (red vertical line) over all on the order of 10^{10} impostor scores i.e. zero-effort. The shift of the dots to right shows massive increases in FMR when impostors have the same sex, age, and region of birth. The color code indicates which region gives the worst case FMR. If the observed variation is due to the prevalence of one kind of images in the training imagery, then algorithms developed on one kind of data might be expected to give higher FMR on other kinds.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

- ▷ We computed the same quantities for a global FMR = 0.0001. The effects are similar.

Caveats:

- ▷ The effects of variable impostor rates on one-to-many identification systems may well differ from what's implied by these one-to-one verification results. Two reasons for this are a) the enrollment galleries are usually imbalanced across countries of birth, age and sex; b) one-to-many identification algorithms often implement techniques aimed at stabilizing the impostor distribution. Further research is necessary.
- ▷ In principle, the effects seen in this subsection could be due to differences in the image capture process. We consider this unlikely since the effects are maintained across geography - e.g. Caribbean vs. Africa, or Japan vs. China.

Figure 176: For visa images, the heatmap shows how the mean of the impostor distribution for the country pair (a,b) is shifted relative to the mean of the global impostor distribution, expressed as a number of standard deviations of the global impostor distribution. This statistic is designed to show shifts in the entire impostor distribution, not just tail effects that manifest as the anomalously high (or low) false match rates that appear in the subsequent figures. The countries are chosen to show that skin tone alone does not explain impostor distribution shifts. The reduced shift in Asian populations with the Yitu and TongYiTrans algorithms, is accompanied by positive shifts in the European populations. This reversal relative to most other algorithms, may derive from use of nationally weighted training sets. The figure is computed from same-sex and same-age impostor pairs.

Figure 177: For algorithm 3divi-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 178: For algorithm 3divi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 179: For algorithm acer-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 180: For algorithm adera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 181: For algorithm advance-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 182: For algorithm aifirst-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 183: For algorithm ailabs-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 184: For algorithm aimall-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 185: For algorithm aiunionface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 186: For algorithm alchera-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 187: For algorithm alchera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 188: For algorithm allgovision-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 189: For algorithm alphaface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 190: For algorithm alphaface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 191: For algorithm amplifiedgroup-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 192: For algorithm androvideo-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 193: For algorithm anke-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 194: For algorithm anke-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 195: For algorithm antheus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 196: For algorithm anyvision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 197: For algorithm anyvision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 198: For algorithm asusaics-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 199: For algorithm aware-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 200: For algorithm aware-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 201: For algorithm awiros-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 202: For algorithm ayonix-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 203: For algorithm bioidtechswiss-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 204: For algorithm bm-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 205: For algorithm camvi-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 206: For algorithm camvi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 207: For algorithm ceiec-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 208: For algorithm ceiec-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 209: For algorithm chosun-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 210: For algorithm chtface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 211: For algorithm chtface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 212: For algorithm cib-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 213: For algorithm cogent-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 214: For algorithm cogent-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 215: For algorithm cognitec-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 216: For algorithm cognitec-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 217: For algorithm ctbcbank-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 218: For algorithm ctbcbank-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 219: For algorithm cyberextruder-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 220: For algorithm cyberextruder-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 221: For algorithm cyberlink-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 222: For algorithm cyberlink-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 223: For algorithm dahua-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 224: For algorithm dahua-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 225: For algorithm deepglint-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 226: For algorithm deepglint-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 227: For algorithm deepsea-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 228: For algorithm dermalog-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 229: For algorithm dermalog-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 230: For algorithm didiglobalface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 231: For algorithm digitalbarriers-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 232: For algorithm dsk-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 233: For algorithm einetworks-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 234: For algorithm expasoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 235: For algorithm f8-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 236: For algorithm facesoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 237: For algorithm fujitsulab-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 238: For algorithm glory-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 239: For algorithm glory-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 240: For algorithm gorilla-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 241: For algorithm gorilla-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 242: For algorithm hik-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 243: For algorithm hr-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 244: For algorithm hr-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 245: For algorithm id3-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 246: For algorithm id3-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 247: For algorithm idemia-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 248: For algorithm idemia-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 249: For algorithm iit-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 250: For algorithm iit-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 251: For algorithm imagus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 252: For algorithm imagus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 253: For algorithm imperial-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 254: For algorithm imperial-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 255: For algorithm incode-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 256: For algorithm incode-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 257: For algorithm innovativetechnologyltd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 258: For algorithm innovatrics-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 259: For algorithm innovatrics-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 260: For algorithm intellicloudai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 261: For algorithm intellifusion-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 262: For algorithm intellivision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 263: For algorithm intellivision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 264: For algorithm intelresearch-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 265: For algorithm intelresearch-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 266: For algorithm intsysmsu-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 267: For algorithm intsysmsu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 268: For algorithm iqface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 269: For algorithm iqface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 270: For algorithm isap-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 271: For algorithm isityou-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 272: For algorithm isystems-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 273: For algorithm isystems-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 274: For algorithm itmo-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 275: For algorithm itmo-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 276: For algorithm kakao-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 277: For algorithm kakao-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 278: For algorithm kedacom-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 279: For algorithm kneron-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 280: For algorithm kneron-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 281: For algorithm lookman-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 282: For algorithm lookman-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 283: For algorithm luxand-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 284: For algorithm megvii-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 285: For algorithm megvii-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 286: For algorithm meiya-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 287: For algorithm microfocus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 288: For algorithm microfocus-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 289: For algorithm mt-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 290: For algorithm mvision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 291: For algorithm netbridgetech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 292: For algorithm neurotechnology-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 293: For algorithm neurotechnology-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 294: For algorithm nodeflux-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 295: For algorithm nodeflux-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 296: For algorithm notiontag-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 297: For algorithm ntechlab-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 298: For algorithm ntechlab-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 299: For algorithm paravision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 300: For algorithm pixelall-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 301: For algorithm pixelall-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 302: For algorithm psl-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 303: For algorithm psl-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 304: For algorithm pyramid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 305: For algorithm rankone-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 306: For algorithm rankone-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 307: For algorithm realnetworks-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 308: For algorithm realnetworks-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 309: For algorithm remarkai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 310: For algorithm remarkai-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 311: For algorithm rokid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 312: For algorithm rokid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 313: For algorithm s1-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 314: For algorithm saffe-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 315: For algorithm saffe-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 316: For algorithm samtech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 317: For algorithm scanovate-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 318: For algorithm sensetime-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 319: For algorithm sensetime-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 320: For algorithm sertis-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 321: For algorithm shaman-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 322: For algorithm shaman-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 323: For algorithm shu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 324: For algorithm shu-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 325: For algorithm siat-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 326: For algorithm siat-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 327: For algorithm sjtu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 328: For algorithm sjtu-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 329: For algorithm smilart-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 330: For algorithm smilart-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 331: For algorithm starhybrid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 332: For algorithm synesis-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 333: For algorithm synesis-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 334: For algorithm synology-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 335: For algorithm tech5-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 336: For algorithm tech5-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 337: For algorithm tevian-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 338: For algorithm tevian-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 339: For algorithm tiger-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 340: For algorithm tiger-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 341: For algorithm tongyi-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 342: For algorithm toshiba-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 343: For algorithm toshiba-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 344: For algorithm trueface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 345: For algorithm tuputech-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 346: For algorithm ulsee-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 347: For algorithm uluface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 348: For algorithm uluface-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 349: For algorithm upc-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 350: For algorithm vcog-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 351: For algorithm vd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 352: For algorithm veridas-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 353: For algorithm veridas-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 354: For algorithm via-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 355: For algorithm videmo-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 356: For algorithm videonetics-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 357: For algorithm videonetics-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 358: For algorithm vigilantsolutions-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 359: For algorithm vigilantsolutions-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 360: For algorithm vion-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 361: For algorithm visionbox-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 362: For algorithm visionbox-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 363: For algorithm visionlabs-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 364: For algorithm visionlabs-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 365: For algorithm visteam-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 366: For algorithm vocord-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 367: For algorithm vocord-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 368: For algorithm winsense-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 369: For algorithm winsense-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 370: For algorithm x-laboratory-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 371: For algorithm x-laboratory-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 372: For algorithm xforwardai-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 373: For algorithm yisheng-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 374: For algorithm yitu-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 375: For algorithm 3divi-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 376: For algorithm 3divi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 377: For algorithm acer-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 378: For algorithm adera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 379: For algorithm advance-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 380: For algorithm aifirst-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 381: For algorithm ailabs-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 382: For algorithm aimall-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 383: For algorithm aiunionface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 384: For algorithm alchera-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 385: For algorithm alchera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 386: For algorithm allgovision-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 387: For algorithm alphaface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 388: For algorithm alphaface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 389: For algorithm amplifiedgroup-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 390: For algorithm androvideo-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 391: For algorithm anke-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 392: For algorithm anke-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 393: For algorithm antheus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 394: For algorithm anyvision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 395: For algorithm anyvision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 396: For algorithm asusaics-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 397: For algorithm aware-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 398: For algorithm aware-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 399: For algorithm awiros-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 400: For algorithm ayonix-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 401: For algorithm bioidtechswiss-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 402: For algorithm bm-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 403: For algorithm camvi-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 404: For algorithm camvi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 405: For algorithm ceiec-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 406: For algorithm ceiec-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 407: For algorithm chosun-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 408: For algorithm chtface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 409: For algorithm chtface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 410: For algorithm cib-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 411: For algorithm cogent-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 412: For algorithm cogent-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 413: For algorithm cognitec-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 414: For algorithm cognitec-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 415: For algorithm ctbcbank-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 416: For algorithm ctbcbank-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 417: For algorithm cyberextruder-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 418: For algorithm cyberextruder-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 419: For algorithm cyberlink-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 420: For algorithm cyberlink-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 421: For algorithm dahua-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 422: For algorithm dahua-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 423: For algorithm deepglint-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 424: For algorithm deepglint-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 425: For algorithm deepsea-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 426: For algorithm dermalog-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 427: For algorithm dermalog-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 428: For algorithm didiglobalface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 429: For algorithm digitalbarriers-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 430: For algorithm dsk-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 431: For algorithm einetworks-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 432: For algorithm expasoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 433: For algorithm f8-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 434: For algorithm facesoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 435: For algorithm fujitsulab-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 436: For algorithm glory-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 437: For algorithm glory-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 438: For algorithm gorilla-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 439: For algorithm gorilla-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 440: For algorithm hik-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 441: For algorithm hr-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 442: For algorithm hr-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 443: For algorithm id3-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 444: For algorithm id3-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 445: For algorithm idemia-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 446: For algorithm idemia-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 447: For algorithm iit-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 448: For algorithm iit-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 449: For algorithm imagus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 450: For algorithm imagus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 451: For algorithm imperial-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 452: For algorithm imperial-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 453: For algorithm incode-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 454: For algorithm incode-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 455: For algorithm innovativetechnologyltd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 456: For algorithm innovatrics-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 457: For algorithm innovatrics-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 458: For algorithm intellicloudai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 459: For algorithm intellifusion-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 460: For algorithm intellivision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 461: For algorithm intellivision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 462: For algorithm intelresearch-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 463: For algorithm intsysmsu-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 464: For algorithm intsysmsu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 465: For algorithm iqface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 466: For algorithm iqface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 467: For algorithm isap-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 468: For algorithm isityou-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 469: For algorithm isystems-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 470: For algorithm isystems-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 471: For algorithm itmo-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 472: For algorithm itmo-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 473: For algorithm kakao-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 474: For algorithm kakao-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 475: For algorithm kedacom-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 476: For algorithm kneron-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 477: For algorithm lookman-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 478: For algorithm lookman-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 479: For algorithm luxand-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 480: For algorithm megvii-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 481: For algorithm megvii-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 482: For algorithm meiya-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 483: For algorithm microfocus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 484: For algorithm microfocus-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 485: For algorithm mt-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 486: For algorithm mvision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 487: For algorithm netbridgetech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 488: For algorithm neurotechnology-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 489: For algorithm neurotechnology-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 490: For algorithm nodeflux-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 491: For algorithm nodeflux-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 492: For algorithm notiontag-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 493: For algorithm ntechlab-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 494: For algorithm paravision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 495: For algorithm pixelall-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 496: For algorithm pixelall-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 497: For algorithm psl-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 498: For algorithm psl-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 499: For algorithm pyramid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 500: For algorithm rankone-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 501: For algorithm rankone-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 502: For algorithm realnetworks-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 503: For algorithm realnetworks-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 504: For algorithm remarkai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 505: For algorithm remarkai-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 506: For algorithm rokid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 507: For algorithm rokid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 508: For algorithm s1-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 509: For algorithm saffe-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 510: For algorithm saffe-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 511: For algorithm samtech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 512: For algorithm scanovate-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 513: For algorithm sensetime-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 514: For algorithm sensetime-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 515: For algorithm sertis-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 516: For algorithm shaman-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 517: For algorithm shaman-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 518: For algorithm shu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 519: For algorithm shu-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 520: For algorithm siat-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 521: For algorithm siat-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 522: For algorithm sjtu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 523: For algorithm smilart-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 524: For algorithm smilart-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 525: For algorithm starhybrid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 526: For algorithm synesis-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 527: For algorithm synesis-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 528: For algorithm synology-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 529: For algorithm tech5-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 530: For algorithm tech5-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 531: For algorithm tevian-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 532: For algorithm tevian-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 533: For algorithm tiger-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 534: For algorithm tiger-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 535: For algorithm tongyi-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 536: For algorithm toshiba-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 537: For algorithm toshiba-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 538: For algorithm trueface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 539: For algorithm tuputech-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 540: For algorithm ulsee-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 541: For algorithm uluface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 542: For algorithm uluface-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 543: For algorithm upc-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 544: For algorithm vcog-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 545: For algorithm vd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 546: For algorithm veridas-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 547: For algorithm veridas-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 548: For algorithm via-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 549: For algorithm videonetics-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 550: For algorithm videonetics-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 551: For algorithm vigilantsolutions-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 552: For algorithm vigilantsolutions-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 553: For algorithm vion-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 554: For algorithm visionbox-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 555: For algorithm visionbox-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 556: For algorithm visionlabs-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 557: For algorithm visteam-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 558: For algorithm vocord-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 559: For algorithm vocord-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 560: For algorithm winsense-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 561: For algorithm winsense-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 562: For algorithm x-laboratory-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 563: For algorithm x-laboratory-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 564: For algorithm xforwardai-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 565: For algorithm yisheng-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 566: For algorithm yitu-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 567: For visa images, the heatmap shows the count of impostor comparisons of faces from different individuals who were born in the given country pair.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3.6.2 Effect of age on impostors

Background: This section shows the effect of age on the impostor distribution. The ideal behaviour is that the age of the enrollee and the impostor would not affect impostor scores. This would support FMR stability over sub-populations.

Goals:

- ▷ To show the effect of relative ages of the impostor and enrollee on false match rates.
- ▷ To determine whether some algorithms have better impostor distribution stability.

Methods:

- ▷ Define 14 age group bins, spanning 0 to over 100 years old.
- ▷ Compute FMR over all impostor comparisons for which the subjects in the enrollee and impostor images have ages in two bins.
- ▷ Compute FMR over all impostor comparisons for which the subjects are additionally of the same sex, and born in the same geographic region.

Results:

The notable aspects are:

- ▷ Diagonal dominance: Impostors are more likely to be matched against their same age group.
- ▷ Same sex and same region impostors are more successful. On the diagonal, an impostor is more likely to succeed by posing as someone of the same sex. If $\Delta \log_{10} \text{FMR} = 0.2$, then same-sex same-region FMR exceeds the all-pairs FMR by factor of $10^{0.2} = 1.6$.
- ▷ Young children impostors give elevated FMR against young children. Older adult impostor give elevated FMR against older adults. These effects are quite large, for example if $\Delta \log_{10} \text{FMR} = 1.0$ larger than a 32 year old, then these groups have higher FMR by a factor of $10^1 = 10$. This would imply an FMR above 0.01 for a nominal (global) FMR = 0.001.
- ▷ Algorithms vary.
- ▷ We computed the same quantities for a global FMR = 0.0001. The effects are similar.

Note the calculations in this section include impostors paired across all countries of birth.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 568: For algorithm 3divi-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 569: For algorithm 3divi-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 570: For algorithm acer-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 571: For algorithm adera-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 572: For algorithm advance-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 573: For algorithm aifirst-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 574: For algorithm ailabs-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 575: For algorithm aimall-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 576: For algorithm aiunionface-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 577: For algorithm alchera-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 578: For algorithm alchera-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 579: For algorithm allgovision-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 580: For algorithm alphaface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 581: For algorithm alphaface-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 582: For algorithm amplifiedgroup-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 583: For algorithm androvideo-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 584: For algorithm anke-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 585: For algorithm anke-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 586: For algorithm antheus-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 587: For algorithm anyvision-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 588: For algorithm anyvision-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 589: For algorithm asusaics-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 590: For algorithm aware-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 591: For algorithm aware-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 592: For algorithm awiros-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 593: For algorithm ayonix-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 594: For algorithm bioidtechswiss-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 595: For algorithm bm-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 596: For algorithm camvi-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 597: For algorithm camvi-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 598: For algorithm ceiec-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 599: For algorithm ceiec-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 600: For algorithm chosun-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 601: For algorithm chtface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 602: For algorithm chtface-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 603: For algorithm cib-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 604: For algorithm cogent-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 605: For algorithm cogent-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 606: For algorithm cognitec-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 607: For algorithm cognitec-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 608: For algorithm ctbcbank-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 609: For algorithm ctbcbank-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 610: For algorithm cyberextruder-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 611: For algorithm cyberextruder-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 612: For algorithm cyberlink-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 613: For algorithm cyberlink-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 614: For algorithm dahua-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 615: For algorithm dahua-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 616: For algorithm deepglint-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 617: For algorithm deepglint-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 618: For algorithm deepsea-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 619: For algorithm dermalog-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 620: For algorithm dermalog-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 621: For algorithm didiglobalface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 622: For algorithm digitalbarriers-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 623: For algorithm dsk-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 624: For algorithm einetworks-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 625: For algorithm expasoft-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 626: For algorithm f8-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 627: For algorithm facesoft-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 628: For algorithm fujitsulab-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 629: For algorithm glory-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 630: For algorithm glory-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 631: For algorithm gorilla-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 632: For algorithm gorilla-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 633: For algorithm hik-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 634: For algorithm hr-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 635: For algorithm hr-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 636: For algorithm id3-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 637: For algorithm id3-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 638: For algorithm idemia-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 639: For algorithm idemia-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 640: For algorithm iit-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 641: For algorithm iit-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 642: For algorithm imagus-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 643: For algorithm imagus-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 644: For algorithm imperial-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 645: For algorithm imperial-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 646: For algorithm incode-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 647: For algorithm incode-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 648: For algorithm innovativetechnologyltd-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 649: For algorithm innovatrics-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 650: For algorithm innovatrics-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 651: For algorithm intellicloudai-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 652: For algorithm intellifusion-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 653: For algorithm intellivision-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 654: For algorithm intellivision-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 655: For algorithm intelresearch-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 656: For algorithm intelresearch-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 657: For algorithm intsysmsu-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 658: For algorithm intsysmsu-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 659: For algorithm iqface-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 660: For algorithm iqface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 661: For algorithm isap-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 662: For algorithm isityou-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 663: For algorithm isystems-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 664: For algorithm isystems-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 665: For algorithm itmo-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 666: For algorithm itmo-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 667: For algorithm kakao-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 668: For algorithm kakao-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 669: For algorithm kedacom-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 670: For algorithm kneron-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 671: For algorithm kneron-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 672: For algorithm lookman-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 673: For algorithm lookman-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 674: For algorithm luxand-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 675: For algorithm megvii-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 676: For algorithm megvii-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 677: For algorithm meiya-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 678: For algorithm microfocus-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 679: For algorithm microfocus-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 680: For algorithm mt-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 681: For algorithm mvision-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 682: For algorithm netbridgetech-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 683: For algorithm neurotechnology-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 684: For algorithm neurotechnology-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 685: For algorithm nodeflux-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 686: For algorithm nodeflux-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 687: For algorithm notiontag-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 688: For algorithm ntechlab-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 689: For algorithm ntechlab-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 690: For algorithm paravision-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 691: For algorithm pixelall-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 692: For algorithm pixelall-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 693: For algorithm psl-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 694: For algorithm psl-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 695: For algorithm pyramid-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 696: For algorithm rankone-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 697: For algorithm rankone-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 698: For algorithm realnetworks-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 699: For algorithm realnetworks-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 700: For algorithm remarkai-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 701: For algorithm remarkai-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 702: For algorithm rokid-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 703: For algorithm rokid-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 704: For algorithm s1-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 705: For algorithm saffe-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 706: For algorithm saffe-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 707: For algorithm samtech-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 708: For algorithm scanovate-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 709: For algorithm sensetime-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 710: For algorithm sensetime-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 711: For algorithm sertis-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 712: For algorithm shaman-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 713: For algorithm shaman-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 714: For algorithm shu-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 715: For algorithm shu-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 716: For algorithm siat-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 717: For algorithm siat-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 718: For algorithm sjtu-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 719: For algorithm sjtu-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 720: For algorithm smilart-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 721: For algorithm smilart-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 722: For algorithm starhybrid-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 723: For algorithm synesis-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 724: For algorithm synesis-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 725: For algorithm synology-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 726: For algorithm tech5-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 727: For algorithm tech5-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 728: For algorithm tevian-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 729: For algorithm tevian-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 730: For algorithm tiger-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 731: For algorithm tiger-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 732: For algorithm tongyi-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 733: For algorithm toshiba-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 734: For algorithm toshiba-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 735: For algorithm trueface-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 736: For algorithm tuputech-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 737: For algorithm ulsee-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 738: For algorithm uluface-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 739: For algorithm uluface-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 740: For algorithm upc-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 741: For algorithm vcog-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 742: For algorithm vd-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 743: For algorithm veridas-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 744: For algorithm veridas-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 745: For algorithm via-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 746: For algorithm videmo-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 747: For algorithm videonetics-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 748: For algorithm videonetics-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 749: For algorithm vigilantsolutions-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 750: For algorithm vigilantsolutions-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 751: For algorithm vion-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 752: For algorithm visionbox-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 753: For algorithm visionbox-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 754: For algorithm visionlabs-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 755: For algorithm visionlabs-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 756: For algorithm visteam-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 757: For algorithm vocord-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 758: For algorithm vocord-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 759: For algorithm winsense-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 760: For algorithm winsense-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 761: For algorithm x-laboratory-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 762: For algorithm x-laboratory-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 763: For algorithm xforwardai-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 764: For algorithm yisheng-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 765: For algorithm yitu-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Accuracy Terms + Definitions

In biometrics, Type II errors occur when two samples of one person do not match – this is called a **false negative**. Correspondingly, Type I errors occur when samples from two persons do match – this is called a **false positive**. Matches are declared by a biometric system when the native comparison score from the recognition algorithm meets some **threshold**. Comparison scores can be either **similarity scores**, in which case higher values indicate that the samples are more likely to come from the same person, or **dissimilarity scores**, in which case higher values indicate different people. Similarity scores are traditionally computed by **fingerprint** and **face** recognition algorithms, while dissimilarities are used in **iris recognition**. In some cases, the dissimilarity score is a distance; this applies only when **metric** properties are obeyed. In any case, scores can be either **mate** scores, coming from a comparison of one person's samples, or **nonmate** scores, coming from comparison of different persons' samples. The words **genuine** or **authentic** are synonyms for mate, and the word **impostor** is used a synonym for nonmate. The words mate and nonmate are traditionally used in identification applications (such as law enforcement search, or background checks) while genuine and impostor are used in verification applications (such as access control).

A **error tradeoff** characteristic represents the tradeoff between Type II and Type I classification errors. For verification this plots false non-match rate (FNMR) vs. false match rate (FMR) parametrically with T.

The error tradeoff plots are often called **detection error tradeoff (DET)** characteristics or **receiver operating characteristic** (ROC). These serve the same function but differ, for example, in plotting the complement of an error rate (e.g. TMR = 1 – FNMR) and in transforming the axes most commonly using logarithms, to show multiple decades of FMR. More rarely, the function might be the inverse Gaussian function.

More detail and generality is provided in formal biometrics testing standards, see the various parts of ISO/IEC 19795 Biometrics Testing and Reporting. More terms, including and beyond those to do with accuracy, see ISO/IEC 2382-37 Information technology -- Vocabulary -- Part 37: Harmonized biometric vocabulary

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

References

[1] P. Jonathon Phillips, Amy N. Yates, Ying Hu, Carina A. Hahn, Eilidh Noyes, Kelsey Jackson, Jacqueline G. Cavazos, Géraldine Jeckeln, Rajeev Ranjan, Swami Sankaranarayanan, Jun-Cheng Chen, Carlos D. Castillo, Rama Chellappa, David White, and Alice J. O'Toole. Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms. *Proceedings of the National Academy of Sciences*, 115(24):6171–6176, 2018.