NISTIR XXXX Draft

Ongoing Face Recognition Vendor Test (FRVT)

Part 1: Verification

Patrick Grother
Mei Ngan
Kayee Hanaoka
Information Access Division
Information Technology Laboratory

This publication is available free of charge from:
https://www.nist.gov/programs-projects/face-recognition-vendor-test-frvt-ongoing

2020/01/22

National Institute of Standards and Technology
U.S. Department of Commerce

ACKNOWLEDGMENTS

The authors are grateful to staff in the NIST Biometrics Research Laboratory for infrastructure supporting rapid evaluation of algorithms.

DISCLAIMER

Specific hardware and software products identified in this report were used in order to perform the evaluations described in this document. In no case does identification of any commercial product, trade name, or vendor, imply recommendation or endorsement by the National Institute of Standards and Technology, nor does it imply that the products and equipment identified are necessarily the best available for the purpose.

INSTITUTIONAL REVIEW BOARD

The National Institute of Standards and Technology's Research Protections Office reviewed the protocol for this project and determined it is not human subjects research as defined in Department of Commerce Regulations, 15 CFR 27, also known as the Common Rule for the Protection of Human Subjects (45 CFR 46, Subpart A).

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FRVT STATUS

This report is a draft NIST Interagency Report, and is open for comment. It is the sixteenth edition of the report since the first was published in June 2017. Prior editions of this report are maintained on the FRVT website, and may contain useful information about older algorithms and datasets no longer used in FRVT.

FRVT remains open: All four tracks of the FRVT remain open to new algorithm submissions indefinitely. This report will be updated as new algorithms are evaluated, as new datasets are added, and as new analyses are included. Comments and suggestions should be directed to frvt@nist.gov.

Changes since January 6, 2020:

- ▹ Section 2 has been updated to better describe the Visa and Border images. The caption for Table 10 has been updated to better relate the accuracy values to particular image comparisons.
- ▹ The report adds results for five new developers: Acer, Advance.AI, Expasoft, Netbridge Technology, and Videmo Intelligente Videoanalyse.
- ▹ The report adds results for algorithms from 7 returning developers: China Electronics Import-Export Corp, Intel Research Group, ITMO University, Neurotechnology, N-Tech Lab, Rokid, and VisionLabs.
- ▹ We have dropped results from this edition of the report per policy to only list results for two algorithms per developer: N-Tech Lab, Neurotechnology, ITMO, Visionlabs, and CEIEC.
- ▹ The FRVT homepage has been updated with latest accuracy results.

Changes since November 11, 2019:

- ▹ Table 5 has been updated to include runtime memory usage. This is the first time such a quantity has been reported. The value is the peak size of the resident set size logged during enrollment of single images.
- ▹ We have migrated summary results table to a new platform that supports sortable tables: https://pages.nist.gov/frvt/html/frvt11.html
- ▹ The report adds results for four new developers: Antheus Technologia, BioID Technologies SA, Canon Information Tech. (Beijing), and Samsung S1 (listed in the tables as S1).
- ▹ The report adds results for algorithms from 13 returning developers: Anke Investments, Chunghwa Telecom, Deepglint, Institute of Information Technologies, iQIYI, Kneron, Ping An Technology, Paravision, KanKan Ai, Rokid Corporation, Shanghai Universiy - Shanghai Film Academy, Veridas Digital Authentication Solutions, and Videonetics Technology.
- ▹ We have dropped results from this edition of the report per policy to only list results for two algorithms per developer: remarkai-000, veridas-001, sensetime-001, iit-000, anke-003, and everai-002. Results for these are available in prior editions of this report linked from the FRVT page.
- ▹ We issued NIST Interagency Report 8280: FRVT Part 3: Demographics on 2019-12-19. It includes results for many of the algorithms covered by this report.

Changes since October 16, 2019:

- ▹ The report adds results for ten new developers: Ai-Union Technology, ASUSTek Computer, DiDi ChuXing Technology, Innovative Technology, Luxand, MVision, Pyramid Cyber Security + Forensic, Scanovate, Shenzhen AiMall Tech, and TUPU Technology.

- ▷ The report adds results for 12 returning developers: CTBC Bank Glory Gorilla Technology Guangzhou Pixel Solutions Imagus Technology Incode Technologies Lomonosov Moscow State University Rank One Computing Samtech InfoNet Shanghai Ulucu Electronics Technology Synesis, and Winsense.
- ▷ We have dropped results from this edition of the report per policy to only list results for two algorithms per developer: glory-000, gorilla-002, incode-003, rankone-006, and synesis-004.
- ▷ Results for five recently submitted algorithms will appear in the next report.

Changes since September 11, 2019:

- ▷ The report adds results for five new participants: Awidit Systems (Awiros), Momemtum Digital (Sertis), Trueface AI, Shanghai Jiao Tong University, and X-Laboratory.
- ▷ The reports adds results for five new algorithms from returning developers: Cyberlink, Hengrui AI Technology, Idemia, Panasonic R+D Singapore, and Tevian. This causes three algorithm, to be de-listed from the report per policy to list results for two algorithms per developer.

Changes since July 31 2019:

- ▷ The HTML table on the FRVT 1:1 homepage has been updated to include a column for cross-domain Visa-Border verification. Results for this new dataset appeared in the July 29 report under the name "CrossEV" - these are now renamed "Visa-Border".
- ▷ The FRVT 1:1 homepage lists algorithms according to lowest mean rank accuracy:
  Rank($\text{FNMR}_{\text{VISA}}$ at FMR = 0.000001) +
  Rank($\text{FNMR}_{\text{VISA-BORDER}}$ at FMR = 0.000001) +
  Rank($\text{FNMR}_{\text{MUGSHOT}}$ at FMR = 0.00001 after 14 years) +
  Rank($\text{FNMR}_{\text{WILD}}$ at FMR = 0.00001)
  This ordering rewards high accuracy across all datasets.
- ▷ The main results in Table 10 is now in landscape format to accomodate extra columns for the Visa-Border set, and mugshot comparisons after at least 12 years.
- ▷ The report adds results for nine new participants: Alpha SSTG, Intel Research, ULSee, Chungwa Telecon, iSAP Solution, Rokid, Shenzhen EI Networks, CSA Intellicloud, Shenzhen Intellifusion Technologies.
- ▷ The reports adds results for six new algorithms from returning developers: Innovatrics, Dahua Technology, Tech5 SA, Intellivision, Nodeflux and Imperial College, London. One algorithm, from Imperial has been retired, per policy to list results for two algorithms per developer.
- ▷ The cross-country false match rate heatmaps starting from Figure 364 have been replotted to reveal more structure by listing countries by region instead of alphabetically.
- ▷ The next version of this report will be posted around October 18, 2019.

Changes since July 3 2019:

- ▷ The HTML table on the FRVT 1:1 homepage has been updated to list the 20 most accurate developers rather than algorithms, choosing the most accurate algorithm from each developer based on visa and mugshot results. Also, the algorithms are ordered in terms of lowest mean rank across mugshot, visa and wild datasets, rewarding broad accuracy over a good result on one particular dataset.
- ▷ This report includes results for a new dataset - see the column labelled "visa-border" in Table 5. It compares a new set of high quality visa-like portraits with a set webcam border-crossing photos that exhibit moderately poor pose variations and background illumination. The two new sets are described in sections 2.3 and 2.4. The comparisons are "cross-domain" in that the algorithm must compare "visa" and "wild" images. Results for other algorithms will be added in future reports as they become available.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

- ▷ This report adds results for algorithms from 9 developers submitted in early July 2019. These are from 3DiVi, Camvi, EverAI-Paravision, Facesoft, Farbar (F8), Institute of Information Technologies, Shanghai U. Film Academy, Via Technologies, and Ulucu Electronics Tech. Six of these are new participants.
- ▷ Several other algorithms have been submitted and are being evaluated. Results will be released in the next report, scheduled for September 5. That report will include results for new datasets.
- ▷ Older algorithms from Everai, Camvi and 3DiVi, have been retired, per the policy to list only two algorithms per developer.

Changes since June 20 2019:

- ▷ This report adds results for algorithms from 18 developers submitted in early June 2019. These are from CTBC Bank, Deep Glint, Thales Cogent, Ever AI Paravision, Gorilla Technology, Imagus, Incode, Kneron, N-Tech Lab, Neurotechnology, Notiontag Technologies, Star Hybrid, Videonetics, Vigilant Solutions, Winsense, Anke Investments, CEIEC, and DSK. Nine of these are new participants.
- ▷ Several other algorithms have been submitted and are being evaluated. Results will be released in the next report, scheduled for August 1.
- ▷ Older algorithms from Everai, Thales Cogent, Gorilla Technology, Incode, Neurotechnology, N-Tech Lab and Vigilant Solutions have been retired, per the policy to list only two algorithms per developer.

Changes since April 2019:

- ▷ This report adds results for nine algorithms from nine developers submitted in early June 2019. These are from Tencent Deepsea, Hengrui, Kedacom, Moontime, Guangzhou Pixel, Rank One Computing, Synesis, Sensetime and Vocord.
- ▷ Another 23 algorithms have been submitted and are being evaluated. Results will be released in the next report, scheduled for July 3.
- ▷ Older algorithms for Rank One, Synesis, and Vocord have been retired, per the policy to list only two algorithms per developer.

Changes since February 2019:

- ▷ This report adds results for 49 algorithms from 42 developers submitted in early March 2019.
- ▷ This report omits results for algorithms that we retired. We retired for three reasons: 1. The developer submitted a new algorithm, and we only list two. 2. The algorithm needs a GPU, and we no longer allow GPU-based algorithms. 3. Inoperable algorithms.
- ▷ Previous results for retired algorithms are available in older editions of this report linked here.
- ▷ The mugshot database used from February 2017 to January 2019 has been replaced with an extract of the mugshot database documented in NIST Interagency Report 8238, November 2018. The new mugshot set is described in section 2.5 and is adopted because:
  - ▷▷ It has much better identity label integrity, so that false non-match rates are substantially lower than those reported in FRVT 1:1 reports to date - see Figure 41.
  - ▷▷ It includes images collected over a 17 year period such that ageing can be much better characterized - - see Figure 154.
- ▷ Using the new mugshot database, Figure 154 shows accuracy for four demographic groups identified in the biographic metadata that accompanies the data: black females, black males, white females and white males.
- ▷ The report adds Figure 11 with results for the twenty human-difficult pairs used in the May 2018 paper *Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms* by Phillips et al. [1].

- ▷ The report uses an update to the wild image database that corrects some ground truth labels.
- ▷ Some results for the child exploitation database are not complete. They are typically updated less frequently than for other image sets.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Contents

ACKNOWLEDGMENTS 1

DISCLAIMER 1

INSTITUTIONAL REVIEW BOARD 1

1 METRICS 32
1.1 CORE ACCURACY . . . 32

2 DATASETS 33
2.1 CHILD EXPLOITATION IMAGES . . . 33
2.2 VISA IMAGES . . . 33
2.3 APPLICATION IMAGES . . . 33
2.4 BORDER CROSSING IMAGES . . . 34
2.5 MUGSHOT IMAGES . . . 34
2.6 WILD IMAGES . . . 35

3 RESULTS 35
3.1 TEST GOALS . . . 35
3.2 TEST DESIGN . . . 35
3.3 FAILURE TO ENROLL . . . 38
3.4 RECOGNITION ACCURACY . . . 43
3.5 GENUINE DISTRIBUTION STABILITY . . . 167
3.5.1 EFFECT OF BIRTH PLACE ON THE GENUINE DISTRIBUTION . . . 167
3.5.2 EFFECT OF AGEING . . . 184
3.5.3 EFFECT OF AGE ON GENUINE SUBJECTS . . . 197
3.6 IMPOSTOR DISTRIBUTION STABILITY . . . 215
3.6.1 EFFECT OF BIRTH PLACE ON THE IMPOSTOR DISTRIBUTION . . . 215
3.6.2 EFFECT OF AGE ON IMPOSTORS . . . 598

List of Tables

1 ALGORITHM SUMMARY . . . 20
2 ALGORITHM SUMMARY . . . 21
3 ALGORITHM SUMMARY . . . 22
4 ALGORITHM SUMMARY . . . 23
5 ALGORITHM SUMMARY . . . 24
6 FALSE NON-MATCH RATE . . . 25
7 FALSE NON-MATCH RATE . . . 26
8 FALSE NON-MATCH RATE . . . 27
9 FALSE NON-MATCH RATE . . . 28
10 FALSE NON-MATCH RATE . . . 29
11 FAILURE TO ENROL RATES . . . 39
12 FAILURE TO ENROL RATES . . . 40
13 FAILURE TO ENROL RATES . . . 41
14 FAILURE TO ENROL RATES . . . 42

List of Figures

1 PERFORMANCE SUMMARY: FNMR VS. TEMPLATE SIZE TRADEOFF . . . 30
2 PERFORMANCE SUMMARY: FNMR VS. TEMPLATE TIME TRADEOFF . . . 31

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3 EXAMPLE IMAGES . . . 35
(A) VISA . . . 35
(B) MUGSHOT . . . 35
(C) WILD . . . 35
(D) BORDER (FROM VISABORDER) . . . 35
4 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 44
5 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 45
6 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 46
7 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 47
8 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 48
9 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 49
10 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 50
11 PERFORMANCE ON 20 HUMAN-DIFFICULT PAIRS . . . 51
12 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 52
13 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 53
14 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 54
15 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 55
16 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 56
17 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 57
18 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 58
19 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 59
20 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 60
21 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 61
22 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 62
23 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 63
24 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 64
25 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 65
26 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 66
27 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 67
28 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 68
29 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 69
30 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 70
31 ERROR TRADEOFF CHARACTERISTIC: VISA IMAGES . . . 71
32 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 72
33 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 73
34 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 74
35 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 75
36 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 76
37 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 77
38 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 78
39 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 79
40 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 80
41 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 81
42 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 82
43 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 83
44 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 84
45 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 85
46 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 86
47 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 87
48 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 88
49 ERROR TRADEOFF CHARACTERISTIC: WILD IMAGES . . . 89
50 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 90
51 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 91
52 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 92
53 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 93
54 ERROR TRADEOFF CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 94

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

55 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 95
56 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 96
57 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 97
58 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 98
59 CMC CHARACTERISTICS: CHILD EXPLOITATION IMAGES . . . 99
60 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 100
61 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 101
62 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 102
63 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 103
64 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 104
65 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 105
66 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 106
67 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 107
68 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 108
69 FALSE MATCH RATES WITHIN AND ACROSS DEMOGRAPHIC GROUPS . . . 109
70 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 110
71 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 111
72 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 112
73 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 113
74 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 114
75 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 115
76 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 116
77 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 117
78 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 118
79 SEX AND RACE EFFECTS: MUGSHOT IMAGES . . . 119
80 SEX EFFECTS: VISA IMAGES . . . 120
81 SEX EFFECTS: VISA IMAGES . . . 121
82 SEX EFFECTS: VISA IMAGES . . . 122
83 SEX EFFECTS: VISA IMAGES . . . 123
84 SEX EFFECTS: VISA IMAGES . . . 124
85 SEX EFFECTS: VISA IMAGES . . . 125
86 SEX EFFECTS: VISA IMAGES . . . 126
87 SEX EFFECTS: VISA IMAGES . . . 127
88 SEX EFFECTS: VISA IMAGES . . . 128
89 SEX EFFECTS: VISA IMAGES . . . 129
90 SEX EFFECTS: VISA IMAGES . . . 130
91 SEX EFFECTS: VISA IMAGES . . . 131
92 SEX EFFECTS: VISA IMAGES . . . 132
93 SEX EFFECTS: VISA IMAGES . . . 133
94 SEX EFFECTS: VISA IMAGES . . . 134
95 SEX EFFECTS: VISA IMAGES . . . 135
96 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 136
97 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 137
98 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 138
99 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 139
100 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 140
101 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 141
102 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 142
103 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 143
104 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 144
105 FALSE MATCH RATE CALIBRATION: MUGSHOT IMAGES . . . 145
106 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 146
107 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 147
108 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 148
109 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 149
110 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 150
111 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 151

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

112 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 152
113 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 153
114 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 154
115 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 155
116 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 156
117 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 157
118 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 158
119 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 159
120 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 160
121 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 161
122 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 162
123 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 163
124 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 164
125 FALSE MATCH RATE CALIBRATION: VISA IMAGES . . . 165
126 FALSE MATCH RATE CONCENTRATION: VISA IMAGES . . . 166
127 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 168
128 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 169
129 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 170
130 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 171
131 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 172
132 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 173
133 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 174
134 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 175
135 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 176
136 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 177
137 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 178
138 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 179
139 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 180
140 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 181
141 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 182
142 EFFECT OF COUNTRY OF BIRTH ON FNMR . . . 183
143 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 185
144 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 186
145 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 187
146 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 188
147 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 189
148 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 190
149 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 191
150 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 192
151 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 193
152 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 194
153 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 195
154 ERROR TRADEOFF CHARACTERISTIC: MUGSHOT IMAGES . . . 196
155 EFFECT OF SUBJECT AGE ON FNMR . . . 198
156 EFFECT OF SUBJECT AGE ON FNMR . . . 199
157 EFFECT OF SUBJECT AGE ON FNMR . . . 200
158 EFFECT OF SUBJECT AGE ON FNMR . . . 201
159 EFFECT OF SUBJECT AGE ON FNMR . . . 202
160 EFFECT OF SUBJECT AGE ON FNMR . . . 203
161 EFFECT OF SUBJECT AGE ON FNMR . . . 204
162 EFFECT OF SUBJECT AGE ON FNMR . . . 205
163 EFFECT OF SUBJECT AGE ON FNMR . . . 206
164 EFFECT OF SUBJECT AGE ON FNMR . . . 207
165 EFFECT OF SUBJECT AGE ON FNMR . . . 208
166 EFFECT OF SUBJECT AGE ON FNMR . . . 209

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

167 EFFECT OF SUBJECT AGE ON FNMR . . . 210
168 EFFECT OF SUBJECT AGE ON FNMR . . . 211
169 EFFECT OF SUBJECT AGE ON FNMR . . . 212
170 EFFECT OF SUBJECT AGE ON FNMR . . . 213
171 WORST CASE REGIONAL EFFECT FNMR . . . 216
172 IMPOSTOR DISTRIBUTION SHIFTS FOR SELECT COUNTRY PAIRS . . . 218
173 ALGORITHM 3DIVI-003 CROSS REGION FMR . . . 219
174 ALGORITHM 3DIVI-004 CROSS REGION FMR . . . 220
175 ALGORITHM ACER-000 CROSS REGION FMR . . . 221
176 ALGORITHM ADERA-001 CROSS REGION FMR . . . 222
177 ALGORITHM ADVANCE-002 CROSS REGION FMR . . . 223
178 ALGORITHM AIFIRST-001 CROSS REGION FMR . . . 224
179 ALGORITHM AILABS-001 CROSS REGION FMR . . . 225
180 ALGORITHM AIMALL-001 CROSS REGION FMR . . . 226
181 ALGORITHM AIUNIONFACE-000 CROSS REGION FMR . . . 227
182 ALGORITHM ALCHERA-000 CROSS REGION FMR . . . 228
183 ALGORITHM ALCHERA-001 CROSS REGION FMR . . . 229
184 ALGORITHM ALLGOVISION-000 CROSS REGION FMR . . . 230
185 ALGORITHM ALPHAFACE-001 CROSS REGION FMR . . . 231
186 ALGORITHM AMPLIFIEDGROUP-001 CROSS REGION FMR . . . 232
187 ALGORITHM ANKE-004 CROSS REGION FMR . . . 233
188 ALGORITHM ANKE-005 CROSS REGION FMR . . . 234
189 ALGORITHM ANTHEUS-000 CROSS REGION FMR . . . 235
190 ALGORITHM ANYVISION-002 CROSS REGION FMR . . . 236
191 ALGORITHM ANYVISION-004 CROSS REGION FMR . . . 237
192 ALGORITHM ASUSAICS-000 CROSS REGION FMR . . . 238
193 ALGORITHM AWARE-003 CROSS REGION FMR . . . 239
194 ALGORITHM AWARE-004 CROSS REGION FMR . . . 240
195 ALGORITHM AWIROS-001 CROSS REGION FMR . . . 241
196 ALGORITHM AYONIX-000 CROSS REGION FMR . . . 242
197 ALGORITHM BIOIDTECHSWISS-000 CROSS REGION FMR . . . 243
198 ALGORITHM BM-001 CROSS REGION FMR . . . 244
199 ALGORITHM CAMVI-002 CROSS REGION FMR . . . 245
200 ALGORITHM CAMVI-004 CROSS REGION FMR . . . 246
201 ALGORITHM CEIEC-002 CROSS REGION FMR . . . 247
202 ALGORITHM CEIEC-003 CROSS REGION FMR . . . 248
203 ALGORITHM CHTFACE-001 CROSS REGION FMR . . . 249
204 ALGORITHM CHTFACE-002 CROSS REGION FMR . . . 250
205 ALGORITHM CIB-000 CROSS REGION FMR . . . 251
206 ALGORITHM COGENT-003 CROSS REGION FMR . . . 252
207 ALGORITHM COGENT-004 CROSS REGION FMR . . . 253
208 ALGORITHM COGNITEC-000 CROSS REGION FMR . . . 254
209 ALGORITHM COGNITEC-001 CROSS REGION FMR . . . 255
210 ALGORITHM CTBCBANK-000 CROSS REGION FMR . . . 256
211 ALGORITHM CTBCBANK-001 CROSS REGION FMR . . . 257
212 ALGORITHM CYBEREXTRUDER-001 CROSS REGION FMR . . . 258
213 ALGORITHM CYBEREXTRUDER-002 CROSS REGION FMR . . . 259
214 ALGORITHM CYBERLINK-002 CROSS REGION FMR . . . 260
215 ALGORITHM CYBERLINK-003 CROSS REGION FMR . . . 261
216 ALGORITHM DAHUA-003 CROSS REGION FMR . . . 262
217 ALGORITHM DAHUA-004 CROSS REGION FMR . . . 263
218 ALGORITHM DEEPGLINT-001 CROSS REGION FMR . . . 264
219 ALGORITHM DEEPGLINT-002 CROSS REGION FMR . . . 265
220 ALGORITHM DEEPSEA-001 CROSS REGION FMR . . . 266
221 ALGORITHM DERMALOG-005 CROSS REGION FMR . . . 267
222 ALGORITHM DERMALOG-006 CROSS REGION FMR . . . 268

223 ALGORITHM DIDIGLOBALFACE-001 CROSS REGION FMR . . . 269
224 ALGORITHM DIGITALBARRIERS-002 CROSS REGION FMR . . . 270
225 ALGORITHM DSK-000 CROSS REGION FMR . . . 271
226 ALGORITHM EINETWORKS-000 CROSS REGION FMR . . . 272
227 ALGORITHM EXPASOFT-000 CROSS REGION FMR . . . 273
228 ALGORITHM F8-001 CROSS REGION FMR . . . 274
229 ALGORITHM FACESOFT-000 CROSS REGION FMR . . . 275
230 ALGORITHM GLORY-001 CROSS REGION FMR . . . 276
231 ALGORITHM GLORY-002 CROSS REGION FMR . . . 277
232 ALGORITHM GORILLA-003 CROSS REGION FMR . . . 278
233 ALGORITHM GORILLA-004 CROSS REGION FMR . . . 279
234 ALGORITHM HIK-001 CROSS REGION FMR . . . 280
235 ALGORITHM HR-001 CROSS REGION FMR . . . 281
236 ALGORITHM HR-002 CROSS REGION FMR . . . 282
237 ALGORITHM ID3-003 CROSS REGION FMR . . . 283
238 ALGORITHM ID3-004 CROSS REGION FMR . . . 284
239 ALGORITHM IDEMIA-004 CROSS REGION FMR . . . 285
240 ALGORITHM IDEMIA-005 CROSS REGION FMR . . . 286
241 ALGORITHM IIT-001 CROSS REGION FMR . . . 287
242 ALGORITHM IIT-002 CROSS REGION FMR . . . 288
243 ALGORITHM IMAGUS-000 CROSS REGION FMR . . . 289
244 ALGORITHM IMAGUS-001 CROSS REGION FMR . . . 290
245 ALGORITHM IMPERIAL-000 CROSS REGION FMR . . . 291
246 ALGORITHM IMPERIAL-002 CROSS REGION FMR . . . 292
247 ALGORITHM INCODE-004 CROSS REGION FMR . . . 293
248 ALGORITHM INCODE-005 CROSS REGION FMR . . . 294
249 ALGORITHM INNOVATIVETECHNOLOGYLTD-001 CROSS REGION FMR . . . 295
250 ALGORITHM INNOVATRICS-004 CROSS REGION FMR . . . 296
251 ALGORITHM INNOVATRICS-006 CROSS REGION FMR . . . 297
252 ALGORITHM INTELLICLOUDAI-001 CROSS REGION FMR . . . 298
253 ALGORITHM INTELLIFUSION-001 CROSS REGION FMR . . . 299
254 ALGORITHM INTELLIVISION-001 CROSS REGION FMR . . . 300
255 ALGORITHM INTELLIVISION-002 CROSS REGION FMR . . . 301
256 ALGORITHM INTELRESEARCH-000 CROSS REGION FMR . . . 302
257 ALGORITHM INTELRESEARCH-001 CROSS REGION FMR . . . 303
258 ALGORITHM INTSYSMSU-000 CROSS REGION FMR . . . 304
259 ALGORITHM INTSYSMSU-001 CROSS REGION FMR . . . 305
260 ALGORITHM IQFACE-000 CROSS REGION FMR . . . 306
261 ALGORITHM IQFACE-001 CROSS REGION FMR . . . 307
262 ALGORITHM ISAP-001 CROSS REGION FMR . . . 308
263 ALGORITHM ISITYOU-000 CROSS REGION FMR . . . 309
264 ALGORITHM ISYSTEMS-001 CROSS REGION FMR . . . 310
265 ALGORITHM ISYSTEMS-002 CROSS REGION FMR . . . 311
266 ALGORITHM ITMO-006 CROSS REGION FMR . . . 312
267 ALGORITHM ITMO-007 CROSS REGION FMR . . . 313
268 ALGORITHM KAKAO-001 CROSS REGION FMR . . . 314
269 ALGORITHM KAKAO-002 CROSS REGION FMR . . . 315
270 ALGORITHM KEDACOM-000 CROSS REGION FMR . . . 316
271 ALGORITHM KNERON-003 CROSS REGION FMR . . . 317
272 ALGORITHM KNERON-004 CROSS REGION FMR . . . 318
273 ALGORITHM LOOKMAN-002 CROSS REGION FMR . . . 319
274 ALGORITHM LOOKMAN-004 CROSS REGION FMR . . . 320
275 ALGORITHM LUXAND-000 CROSS REGION FMR . . . 321
276 ALGORITHM MEGVII-001 CROSS REGION FMR . . . 322
277 ALGORITHM MEGVII-002 CROSS REGION FMR . . . 323
278 ALGORITHM MEIYA-001 CROSS REGION FMR . . . 324
279 ALGORITHM MICROFOCUS-001 CROSS REGION FMR . . . 325

280 ALGORITHM MICROFOCUS-002 CROSS REGION FMR . . . 326
281 ALGORITHM MT-000 CROSS REGION FMR . . . 327
282 ALGORITHM MVISION-001 CROSS REGION FMR . . . 328
283 ALGORITHM NETBRIDGETECH-001 CROSS REGION FMR . . . 329
284 ALGORITHM NEUROTECHNOLOGY-006 CROSS REGION FMR . . . 330
285 ALGORITHM NEUROTECHNOLOGY-008 CROSS REGION FMR . . . 331
286 ALGORITHM NODEFLUX-001 CROSS REGION FMR . . . 332
287 ALGORITHM NODEFLUX-002 CROSS REGION FMR . . . 333
288 ALGORITHM NOTIONTAG-000 CROSS REGION FMR . . . 334
289 ALGORITHM NTECHLAB-007 CROSS REGION FMR . . . 335
290 ALGORITHM NTECHLAB-008 CROSS REGION FMR . . . 336
291 ALGORITHM PA-004 CROSS REGION FMR . . . 337
292 ALGORITHM PARAVISION-004 CROSS REGION FMR . . . 338
293 ALGORITHM PIXELALL-002 CROSS REGION FMR . . . 339
294 ALGORITHM PIXELALL-003 CROSS REGION FMR . . . 340
295 ALGORITHM PSL-002 CROSS REGION FMR . . . 341
296 ALGORITHM PSL-003 CROSS REGION FMR . . . 342
297 ALGORITHM PYRAMID-000 CROSS REGION FMR . . . 343
298 ALGORITHM RANKONE-007 CROSS REGION FMR . . . 344
299 ALGORITHM RANKONE-008 CROSS REGION FMR . . . 345
300 ALGORITHM REALNETWORKS-002 CROSS REGION FMR . . . 346
301 ALGORITHM REALNETWORKS-003 CROSS REGION FMR . . . 347
302 ALGORITHM REMARKAI-001 CROSS REGION FMR . . . 348
303 ALGORITHM REMARKAI-002 CROSS REGION FMR . . . 349
304 ALGORITHM ROKID-000 CROSS REGION FMR . . . 350
305 ALGORITHM ROKID-001 CROSS REGION FMR . . . 351
306 ALGORITHM S1-001 CROSS REGION FMR . . . 352
307 ALGORITHM SAFFE-001 CROSS REGION FMR . . . 353
308 ALGORITHM SAFFE-002 CROSS REGION FMR . . . 354
309 ALGORITHM SAMTECH-001 CROSS REGION FMR . . . 355
310 ALGORITHM SCANOVATE-001 CROSS REGION FMR . . . 356
311 ALGORITHM SENSETIME-002 CROSS REGION FMR . . . 357
312 ALGORITHM SENSETIME-003 CROSS REGION FMR . . . 358
313 ALGORITHM SERTIS-000 CROSS REGION FMR . . . 359
314 ALGORITHM SHAMAN-000 CROSS REGION FMR . . . 360
315 ALGORITHM SHAMAN-001 CROSS REGION FMR . . . 361
316 ALGORITHM SHU-001 CROSS REGION FMR . . . 362
317 ALGORITHM SHU-002 CROSS REGION FMR . . . 363
318 ALGORITHM SIAT-002 CROSS REGION FMR . . . 364
319 ALGORITHM SIAT-004 CROSS REGION FMR . . . 365
320 ALGORITHM SJTU-001 CROSS REGION FMR . . . 366
321 ALGORITHM SMILART-002 CROSS REGION FMR . . . 367
322 ALGORITHM SMILART-003 CROSS REGION FMR . . . 368
323 ALGORITHM STARHYBRID-001 CROSS REGION FMR . . . 369
324 ALGORITHM SYNESIS-005 CROSS REGION FMR . . . 370
325 ALGORITHM SYNESIS-006 CROSS REGION FMR . . . 371
326 ALGORITHM SYNOLOGY-000 CROSS REGION FMR . . . 372
327 ALGORITHM TECH5-002 CROSS REGION FMR . . . 373
328 ALGORITHM TECH5-003 CROSS REGION FMR . . . 374
329 ALGORITHM TEVIAN-004 CROSS REGION FMR . . . 375
330 ALGORITHM TEVIAN-005 CROSS REGION FMR . . . 376
331 ALGORITHM TIGER-002 CROSS REGION FMR . . . 377
332 ALGORITHM TIGER-003 CROSS REGION FMR . . . 378
333 ALGORITHM TONGYI-005 CROSS REGION FMR . . . 379
334 ALGORITHM TOSHIBA-002 CROSS REGION FMR . . . 380
335 ALGORITHM TOSHIBA-003 CROSS REGION FMR . . . 381
336 ALGORITHM TRUEFACE-000 CROSS REGION FMR . . . 382

337 ALGORITHM TUPUTECH-000 CROSS REGION FMR . . . 383
338 ALGORITHM ULSEE-001 CROSS REGION FMR . . . 384
339 ALGORITHM ULUFACE-002 CROSS REGION FMR . . . 385
340 ALGORITHM ULUFACE-003 CROSS REGION FMR . . . 386
341 ALGORITHM UPC-001 CROSS REGION FMR . . . 387
342 ALGORITHM VCOG-002 CROSS REGION FMR . . . 388
343 ALGORITHM VD-001 CROSS REGION FMR . . . 389
344 ALGORITHM VERIDAS-002 CROSS REGION FMR . . . 390
345 ALGORITHM VERIDAS-003 CROSS REGION FMR . . . 391
346 ALGORITHM VIA-000 CROSS REGION FMR . . . 392
347 ALGORITHM VIDEMO-000 CROSS REGION FMR . . . 393
348 ALGORITHM VIDEONETICS-001 CROSS REGION FMR . . . 394
349 ALGORITHM VIDEONETICS-002 CROSS REGION FMR . . . 395
350 ALGORITHM VIGILANTSOLUTIONS-006 CROSS REGION FMR . . . 396
351 ALGORITHM VIGILANTSOLUTIONS-007 CROSS REGION FMR . . . 397
352 ALGORITHM VION-000 CROSS REGION FMR . . . 398
353 ALGORITHM VISIONBOX-000 CROSS REGION FMR . . . 399
354 ALGORITHM VISIONBOX-001 CROSS REGION FMR . . . 400
355 ALGORITHM VISIONLABS-007 CROSS REGION FMR . . . 401
356 ALGORITHM VISIONLABS-008 CROSS REGION FMR . . . 402
357 ALGORITHM VOCORD-006 CROSS REGION FMR . . . 403
358 ALGORITHM VOCORD-007 CROSS REGION FMR . . . 404
359 ALGORITHM WINSENSE-000 CROSS REGION FMR . . . 405
360 ALGORITHM WINSENSE-001 CROSS REGION FMR . . . 406
361 ALGORITHM X-LABORATORY-000 CROSS REGION FMR . . . 407
362 ALGORITHM YISHENG-004 CROSS REGION FMR . . . 408
363 ALGORITHM YITU-003 CROSS REGION FMR . . . 409
364 ALGORITHM 3DIVI-003 CROSS COUNTRY FMR . . . 410
365 ALGORITHM 3DIVI-004 CROSS COUNTRY FMR . . . 411
366 ALGORITHM ACER-000 CROSS COUNTRY FMR . . . 412
367 ALGORITHM ADERA-001 CROSS COUNTRY FMR . . . 413
368 ALGORITHM ADVANCE-002 CROSS COUNTRY FMR . . . 414
369 ALGORITHM AIFIRST-001 CROSS COUNTRY FMR . . . 415
370 ALGORITHM AILABS-001 CROSS COUNTRY FMR . . . 416
371 ALGORITHM AIMALL-001 CROSS COUNTRY FMR . . . 417
372 ALGORITHM AIUNIONFACE-000 CROSS COUNTRY FMR . . . 418
373 ALGORITHM ALCHERA-000 CROSS COUNTRY FMR . . . 419
374 ALGORITHM ALCHERA-001 CROSS COUNTRY FMR . . . 420
375 ALGORITHM ALLGOVISION-000 CROSS COUNTRY FMR . . . 421
376 ALGORITHM ALPHAFACE-001 CROSS COUNTRY FMR . . . 422
377 ALGORITHM AMPLIFIEDGROUP-001 CROSS COUNTRY FMR . . . 423
378 ALGORITHM ANKE-004 CROSS COUNTRY FMR . . . 424
379 ALGORITHM ANKE-005 CROSS COUNTRY FMR . . . 425
380 ALGORITHM ANTHEUS-000 CROSS COUNTRY FMR . . . 426
381 ALGORITHM ANYVISION-002 CROSS COUNTRY FMR . . . 427
382 ALGORITHM ANYVISION-004 CROSS COUNTRY FMR . . . 428
383 ALGORITHM ASUSAICS-000 CROSS COUNTRY FMR . . . 429
384 ALGORITHM AWARE-003 CROSS COUNTRY FMR . . . 430
385 ALGORITHM AWARE-004 CROSS COUNTRY FMR . . . 431
386 ALGORITHM AWIROS-001 CROSS COUNTRY FMR . . . 432
387 ALGORITHM AYONIX-000 CROSS COUNTRY FMR . . . 433
388 ALGORITHM BIOIDTECHSWISS-000 CROSS COUNTRY FMR . . . 434
389 ALGORITHM BM-001 CROSS COUNTRY FMR . . . 435
390 ALGORITHM CAMVI-002 CROSS COUNTRY FMR . . . 436
391 ALGORITHM CAMVI-004 CROSS COUNTRY FMR . . . 437
392 ALGORITHM CEIEC-002 CROSS COUNTRY FMR . . . 438
393 ALGORITHM CEIEC-003 CROSS COUNTRY FMR . . . 439

394 ALGORITHM CHTFACE-001 CROSS COUNTRY FMR . . . 440
395 ALGORITHM CHTFACE-002 CROSS COUNTRY FMR . . . 441
396 ALGORITHM CIB-000 CROSS COUNTRY FMR . . . 442
397 ALGORITHM COGENT-003 CROSS COUNTRY FMR . . . 443
398 ALGORITHM COGENT-004 CROSS COUNTRY FMR . . . 444
399 ALGORITHM COGNITEC-000 CROSS COUNTRY FMR . . . 445
400 ALGORITHM COGNITEC-001 CROSS COUNTRY FMR . . . 446
401 ALGORITHM CTBCBANK-000 CROSS COUNTRY FMR . . . 447
402 ALGORITHM CTBCBANK-001 CROSS COUNTRY FMR . . . 448
403 ALGORITHM CYBEREXTRUDER-001 CROSS COUNTRY FMR . . . 449
404 ALGORITHM CYBEREXTRUDER-002 CROSS COUNTRY FMR . . . 450
405 ALGORITHM CYBERLINK-002 CROSS COUNTRY FMR . . . 451
406 ALGORITHM CYBERLINK-003 CROSS COUNTRY FMR . . . 452
407 ALGORITHM DAHUA-003 CROSS COUNTRY FMR . . . 453
408 ALGORITHM DAHUA-004 CROSS COUNTRY FMR . . . 454
409 ALGORITHM DEEPGLINT-001 CROSS COUNTRY FMR . . . 455
410 ALGORITHM DEEPGLINT-002 CROSS COUNTRY FMR . . . 456
411 ALGORITHM DEEPSEA-001 CROSS COUNTRY FMR . . . 457
412 ALGORITHM DERMALOG-005 CROSS COUNTRY FMR . . . 458
413 ALGORITHM DERMALOG-006 CROSS COUNTRY FMR . . . 459
414 ALGORITHM DIDIGLOBALFACE-001 CROSS COUNTRY FMR . . . 460
415 ALGORITHM DIGITALBARRIERS-002 CROSS COUNTRY FMR . . . 461
416 ALGORITHM DSK-000 CROSS COUNTRY FMR . . . 462
417 ALGORITHM EINETWORKS-000 CROSS COUNTRY FMR . . . 463
418 ALGORITHM EXPASOFT-000 CROSS COUNTRY FMR . . . 464
419 ALGORITHM F8-001 CROSS COUNTRY FMR . . . 465
420 ALGORITHM FACESOFT-000 CROSS COUNTRY FMR . . . 466
421 ALGORITHM GLORY-001 CROSS COUNTRY FMR . . . 467
422 ALGORITHM GLORY-002 CROSS COUNTRY FMR . . . 468
423 ALGORITHM GORILLA-003 CROSS COUNTRY FMR . . . 469
424 ALGORITHM GORILLA-004 CROSS COUNTRY FMR . . . 470
425 ALGORITHM HIK-001 CROSS COUNTRY FMR . . . 471
426 ALGORITHM HR-001 CROSS COUNTRY FMR . . . 472
427 ALGORITHM HR-002 CROSS COUNTRY FMR . . . 473
428 ALGORITHM ID3-003 CROSS COUNTRY FMR . . . 474
429 ALGORITHM ID3-004 CROSS COUNTRY FMR . . . 475
430 ALGORITHM IDEMIA-004 CROSS COUNTRY FMR . . . 476
431 ALGORITHM IDEMIA-005 CROSS COUNTRY FMR . . . 477
432 ALGORITHM IIT-001 CROSS COUNTRY FMR . . . 478
433 ALGORITHM IIT-002 CROSS COUNTRY FMR . . . 479
434 ALGORITHM IMAGUS-000 CROSS COUNTRY FMR . . . 480
435 ALGORITHM IMAGUS-001 CROSS COUNTRY FMR . . . 481
436 ALGORITHM IMPERIAL-000 CROSS COUNTRY FMR . . . 482
437 ALGORITHM IMPERIAL-002 CROSS COUNTRY FMR . . . 483
438 ALGORITHM INCODE-004 CROSS COUNTRY FMR . . . 484
439 ALGORITHM INCODE-005 CROSS COUNTRY FMR . . . 485
440 ALGORITHM INNOVATIVETECHNOLOGYLTD-001 CROSS COUNTRY FMR . . . 486
441 ALGORITHM INNOVATRICS-004 CROSS COUNTRY FMR . . . 487
442 ALGORITHM INNOVATRICS-006 CROSS COUNTRY FMR . . . 488
443 ALGORITHM INTELLICLOUDAI-001 CROSS COUNTRY FMR . . . 489
444 ALGORITHM INTELLIFUSION-001 CROSS COUNTRY FMR . . . 490
445 ALGORITHM INTELLIVISION-001 CROSS COUNTRY FMR . . . 491
446 ALGORITHM INTELLIVISION-002 CROSS COUNTRY FMR . . . 492
447 ALGORITHM INTELRESEARCH-000 CROSS COUNTRY FMR . . . 493
448 ALGORITHM INTSYSMSU-000 CROSS COUNTRY FMR . . . 494
449 ALGORITHM INTSYSMSU-001 CROSS COUNTRY FMR . . . 495

450 ALGORITHM IQFACE-000 CROSS COUNTRY FMR . . . 496
451 ALGORITHM IQFACE-001 CROSS COUNTRY FMR . . . 497
452 ALGORITHM ISAP-001 CROSS COUNTRY FMR . . . 498
453 ALGORITHM ISITYOU-000 CROSS COUNTRY FMR . . . 499
454 ALGORITHM ISYSTEMS-001 CROSS COUNTRY FMR . . . 500
455 ALGORITHM ISYSTEMS-002 CROSS COUNTRY FMR . . . 501
456 ALGORITHM ITMO-006 CROSS COUNTRY FMR . . . 502
457 ALGORITHM ITMO-007 CROSS COUNTRY FMR . . . 503
458 ALGORITHM KAKAO-001 CROSS COUNTRY FMR . . . 504
459 ALGORITHM KAKAO-002 CROSS COUNTRY FMR . . . 505
460 ALGORITHM KEDACOM-000 CROSS COUNTRY FMR . . . 506
461 ALGORITHM KNERON-003 CROSS COUNTRY FMR . . . 507
462 ALGORITHM KNERON-004 CROSS COUNTRY FMR . . . 508
463 ALGORITHM LOOKMAN-002 CROSS COUNTRY FMR . . . 509
464 ALGORITHM LOOKMAN-004 CROSS COUNTRY FMR . . . 510
465 ALGORITHM LUXAND-000 CROSS COUNTRY FMR . . . 511
466 ALGORITHM MEGVII-001 CROSS COUNTRY FMR . . . 512
467 ALGORITHM MEGVII-002 CROSS COUNTRY FMR . . . 513
468 ALGORITHM MEIYA-001 CROSS COUNTRY FMR . . . 514
469 ALGORITHM MICROFOCUS-001 CROSS COUNTRY FMR . . . 515
470 ALGORITHM MICROFOCUS-002 CROSS COUNTRY FMR . . . 516
471 ALGORITHM MT-000 CROSS COUNTRY FMR . . . 517
472 ALGORITHM MVISION-001 CROSS COUNTRY FMR . . . 518
473 ALGORITHM NETBRIDGETECH-001 CROSS COUNTRY FMR . . . 519
474 ALGORITHM NEUROTECHNOLOGY-006 CROSS COUNTRY FMR . . . 520
475 ALGORITHM NEUROTECHNOLOGY-008 CROSS COUNTRY FMR . . . 521
476 ALGORITHM NODEFLUX-001 CROSS COUNTRY FMR . . . 522
477 ALGORITHM NODEFLUX-002 CROSS COUNTRY FMR . . . 523
478 ALGORITHM NOTIONTAG-000 CROSS COUNTRY FMR . . . 524
479 ALGORITHM NTECHLAB-007 CROSS COUNTRY FMR . . . 525
480 ALGORITHM PA-004 CROSS COUNTRY FMR . . . 526
481 ALGORITHM PARAVISION-004 CROSS COUNTRY FMR . . . 527
482 ALGORITHM PIXELALL-002 CROSS COUNTRY FMR . . . 528
483 ALGORITHM PIXELALL-003 CROSS COUNTRY FMR . . . 529
484 ALGORITHM PSL-002 CROSS COUNTRY FMR . . . 530
485 ALGORITHM PSL-003 CROSS COUNTRY FMR . . . 531
486 ALGORITHM PYRAMID-000 CROSS COUNTRY FMR . . . 532
487 ALGORITHM RANKONE-007 CROSS COUNTRY FMR . . . 533
488 ALGORITHM RANKONE-008 CROSS COUNTRY FMR . . . 534
489 ALGORITHM REALNETWORKS-002 CROSS COUNTRY FMR . . . 535
490 ALGORITHM REALNETWORKS-003 CROSS COUNTRY FMR . . . 536
491 ALGORITHM REMARKAI-001 CROSS COUNTRY FMR . . . 537
492 ALGORITHM REMARKAI-002 CROSS COUNTRY FMR . . . 538
493 ALGORITHM ROKID-000 CROSS COUNTRY FMR . . . 539
494 ALGORITHM ROKID-001 CROSS COUNTRY FMR . . . 540
495 ALGORITHM S1-001 CROSS COUNTRY FMR . . . 541
496 ALGORITHM SAFFE-001 CROSS COUNTRY FMR . . . 542
497 ALGORITHM SAFFE-002 CROSS COUNTRY FMR . . . 543
498 ALGORITHM SAMTECH-001 CROSS COUNTRY FMR . . . 544
499 ALGORITHM SCANOVATE-001 CROSS COUNTRY FMR . . . 545
500 ALGORITHM SENSETIME-002 CROSS COUNTRY FMR . . . 546
501 ALGORITHM SENSETIME-003 CROSS COUNTRY FMR . . . 547
502 ALGORITHM SERTIS-000 CROSS COUNTRY FMR . . . 548
503 ALGORITHM SHAMAN-000 CROSS COUNTRY FMR . . . 549
504 ALGORITHM SHAMAN-001 CROSS COUNTRY FMR . . . 550
505 ALGORITHM SHU-001 CROSS COUNTRY FMR . . . 551

506 ALGORITHM SHU-002 CROSS COUNTRY FMR . . . 552
507 ALGORITHM SIAT-002 CROSS COUNTRY FMR . . . 553
508 ALGORITHM SIAT-004 CROSS COUNTRY FMR . . . 554
509 ALGORITHM SJTU-001 CROSS COUNTRY FMR . . . 555
510 ALGORITHM SMILART-002 CROSS COUNTRY FMR . . . 556
511 ALGORITHM SMILART-003 CROSS COUNTRY FMR . . . 557
512 ALGORITHM STARHYBRID-001 CROSS COUNTRY FMR . . . 558
513 ALGORITHM SYNESIS-005 CROSS COUNTRY FMR . . . 559
514 ALGORITHM SYNESIS-006 CROSS COUNTRY FMR . . . 560
515 ALGORITHM SYNOLOGY-000 CROSS COUNTRY FMR . . . 561
516 ALGORITHM TECH5-002 CROSS COUNTRY FMR . . . 562
517 ALGORITHM TECH5-003 CROSS COUNTRY FMR . . . 563
518 ALGORITHM TEVIAN-004 CROSS COUNTRY FMR . . . 564
519 ALGORITHM TEVIAN-005 CROSS COUNTRY FMR . . . 565
520 ALGORITHM TIGER-002 CROSS COUNTRY FMR . . . 566
521 ALGORITHM TIGER-003 CROSS COUNTRY FMR . . . 567
522 ALGORITHM TONGYI-005 CROSS COUNTRY FMR . . . 568
523 ALGORITHM TOSHIBA-002 CROSS COUNTRY FMR . . . 569
524 ALGORITHM TOSHIBA-003 CROSS COUNTRY FMR . . . 570
525 ALGORITHM TRUEFACE-000 CROSS COUNTRY FMR . . . 571
526 ALGORITHM TUPUTECH-000 CROSS COUNTRY FMR . . . 572
527 ALGORITHM ULSEE-001 CROSS COUNTRY FMR . . . 573
528 ALGORITHM ULUFACE-002 CROSS COUNTRY FMR . . . 574
529 ALGORITHM ULUFACE-003 CROSS COUNTRY FMR . . . 575
530 ALGORITHM UPC-001 CROSS COUNTRY FMR . . . 576
531 ALGORITHM VCOG-002 CROSS COUNTRY FMR . . . 577
532 ALGORITHM VD-001 CROSS COUNTRY FMR . . . 578
533 ALGORITHM VERIDAS-002 CROSS COUNTRY FMR . . . 579
534 ALGORITHM VERIDAS-003 CROSS COUNTRY FMR . . . 580
535 ALGORITHM VIA-000 CROSS COUNTRY FMR . . . 581
536 ALGORITHM VIDEONETICS-001 CROSS COUNTRY FMR . . . 582
537 ALGORITHM VIDEONETICS-002 CROSS COUNTRY FMR . . . 583
538 ALGORITHM VIGILANTSOLUTIONS-006 CROSS COUNTRY FMR . . . 584
539 ALGORITHM VIGILANTSOLUTIONS-007 CROSS COUNTRY FMR . . . 585
540 ALGORITHM VION-000 CROSS COUNTRY FMR . . . 586
541 ALGORITHM VISIONBOX-000 CROSS COUNTRY FMR . . . 587
542 ALGORITHM VISIONBOX-001 CROSS COUNTRY FMR . . . 588
543 ALGORITHM VISIONLABS-007 CROSS COUNTRY FMR . . . 589
544 ALGORITHM VOCORD-006 CROSS COUNTRY FMR . . . 590
545 ALGORITHM VOCORD-007 CROSS COUNTRY FMR . . . 591
546 ALGORITHM WINSENSE-000 CROSS COUNTRY FMR . . . 592
547 ALGORITHM WINSENSE-001 CROSS COUNTRY FMR . . . 593
548 ALGORITHM X-LABORATORY-000 CROSS COUNTRY FMR . . . 594
549 ALGORITHM YISHENG-004 CROSS COUNTRY FMR . . . 595
550 ALGORITHM YITU-003 CROSS COUNTRY FMR . . . 596
551 IMPOSTOR COUNTS FOR CROSS COUNTRY FMR CALCULATIONS . . . 597
552 ALGORITHM 3DIVI-003 CROSS AGE FMR . . . 599
553 ALGORITHM 3DIVI-004 CROSS AGE FMR . . . 600
554 ALGORITHM ACER-000 CROSS AGE FMR . . . 601
555 ALGORITHM ADERA-001 CROSS AGE FMR . . . 602
556 ALGORITHM ADVANCE-002 CROSS AGE FMR . . . 603
557 ALGORITHM AIFIRST-001 CROSS AGE FMR . . . 604
558 ALGORITHM AILABS-001 CROSS AGE FMR . . . 605
559 ALGORITHM AIMALL-001 CROSS AGE FMR . . . 606
560 ALGORITHM AIUNIONFACE-000 CROSS AGE FMR . . . 607
561 ALGORITHM ALCHERA-000 CROSS AGE FMR . . . 608
562 ALGORITHM ALCHERA-001 CROSS AGE FMR . . . 609

563 ALGORITHM ALLGOVISION-000 CROSS AGE FMR . . . 610
564 ALGORITHM ALPHAFACE-001 CROSS AGE FMR . . . 611
565 ALGORITHM AMPLIFIEDGROUP-001 CROSS AGE FMR . . . 612
566 ALGORITHM ANKE-004 CROSS AGE FMR . . . 613
567 ALGORITHM ANKE-005 CROSS AGE FMR . . . 614
568 ALGORITHM ANTHEUS-000 CROSS AGE FMR . . . 615
569 ALGORITHM ANYVISION-002 CROSS AGE FMR . . . 616
570 ALGORITHM ANYVISION-004 CROSS AGE FMR . . . 617
571 ALGORITHM ASUSAICS-000 CROSS AGE FMR . . . 618
572 ALGORITHM AWARE-003 CROSS AGE FMR . . . 619
573 ALGORITHM AWARE-004 CROSS AGE FMR . . . 620
574 ALGORITHM AWIROS-001 CROSS AGE FMR . . . 621
575 ALGORITHM AYONIX-000 CROSS AGE FMR . . . 622
576 ALGORITHM BIOIDTECHSWISS-000 CROSS AGE FMR . . . 623
577 ALGORITHM BM-001 CROSS AGE FMR . . . 624
578 ALGORITHM CAMVI-002 CROSS AGE FMR . . . 625
579 ALGORITHM CAMVI-004 CROSS AGE FMR . . . 626
580 ALGORITHM CEIEC-002 CROSS AGE FMR . . . 627
581 ALGORITHM CEIEC-003 CROSS AGE FMR . . . 628
582 ALGORITHM CHTFACE-001 CROSS AGE FMR . . . 629
583 ALGORITHM CHTFACE-002 CROSS AGE FMR . . . 630
584 ALGORITHM CIB-000 CROSS AGE FMR . . . 631
585 ALGORITHM COGENT-003 CROSS AGE FMR . . . 632
586 ALGORITHM COGENT-004 CROSS AGE FMR . . . 633
587 ALGORITHM COGNITEC-000 CROSS AGE FMR . . . 634
588 ALGORITHM COGNITEC-001 CROSS AGE FMR . . . 635
589 ALGORITHM CTBCBANK-000 CROSS AGE FMR . . . 636
590 ALGORITHM CTBCBANK-001 CROSS AGE FMR . . . 637
591 ALGORITHM CYBEREXTRUDER-001 CROSS AGE FMR . . . 638
592 ALGORITHM CYBEREXTRUDER-002 CROSS AGE FMR . . . 639
593 ALGORITHM CYBERLINK-002 CROSS AGE FMR . . . 640
594 ALGORITHM CYBERLINK-003 CROSS AGE FMR . . . 641
595 ALGORITHM DAHUA-003 CROSS AGE FMR . . . 642
596 ALGORITHM DAHUA-004 CROSS AGE FMR . . . 643
597 ALGORITHM DEEPGLINT-001 CROSS AGE FMR . . . 644
598 ALGORITHM DEEPGLINT-002 CROSS AGE FMR . . . 645
599 ALGORITHM DEEPSEA-001 CROSS AGE FMR . . . 646
600 ALGORITHM DERMALOG-005 CROSS AGE FMR . . . 647
601 ALGORITHM DERMALOG-006 CROSS AGE FMR . . . 648
602 ALGORITHM DIDIGLOBALFACE-001 CROSS AGE FMR . . . 649
603 ALGORITHM DIGITALBARRIERS-002 CROSS AGE FMR . . . 650
604 ALGORITHM DSK-000 CROSS AGE FMR . . . 651
605 ALGORITHM EINETWORKS-000 CROSS AGE FMR . . . 652
606 ALGORITHM EXPASOFT-000 CROSS AGE FMR . . . 653
607 ALGORITHM F8-001 CROSS AGE FMR . . . 654
608 ALGORITHM FACESOFT-000 CROSS AGE FMR . . . 655
609 ALGORITHM GLORY-001 CROSS AGE FMR . . . 656
610 ALGORITHM GLORY-002 CROSS AGE FMR . . . 657
611 ALGORITHM GORILLA-003 CROSS AGE FMR . . . 658
612 ALGORITHM GORILLA-004 CROSS AGE FMR . . . 659
613 ALGORITHM HIK-001 CROSS AGE FMR . . . 660
614 ALGORITHM HR-001 CROSS AGE FMR . . . 661
615 ALGORITHM HR-002 CROSS AGE FMR . . . 662
616 ALGORITHM ID3-003 CROSS AGE FMR . . . 663
617 ALGORITHM ID3-004 CROSS AGE FMR . . . 664
618 ALGORITHM IDEMIA-004 CROSS AGE FMR . . . 665
619 ALGORITHM IDEMIA-005 CROSS AGE FMR . . . 666

620 ALGORITHM IIT-001 CROSS AGE FMR . . . 667
621 ALGORITHM IIT-002 CROSS AGE FMR . . . 668
622 ALGORITHM IMAGUS-000 CROSS AGE FMR . . . 669
623 ALGORITHM IMAGUS-001 CROSS AGE FMR . . . 670
624 ALGORITHM IMPERIAL-000 CROSS AGE FMR . . . 671
625 ALGORITHM IMPERIAL-002 CROSS AGE FMR . . . 672
626 ALGORITHM INCODE-004 CROSS AGE FMR . . . 673
627 ALGORITHM INCODE-005 CROSS AGE FMR . . . 674
628 ALGORITHM INNOVATIVETECHNOLOGYLTD-001 CROSS AGE FMR . . . 675
629 ALGORITHM INNOVATRICS-004 CROSS AGE FMR . . . 676
630 ALGORITHM INNOVATRICS-006 CROSS AGE FMR . . . 677
631 ALGORITHM INTELLICLOUDAI-001 CROSS AGE FMR . . . 678
632 ALGORITHM INTELLIFUSION-001 CROSS AGE FMR . . . 679
633 ALGORITHM INTELLIVISION-001 CROSS AGE FMR . . . 680
634 ALGORITHM INTELLIVISION-002 CROSS AGE FMR . . . 681
635 ALGORITHM INTELRESEARCH-000 CROSS AGE FMR . . . 682
636 ALGORITHM INTELRESEARCH-001 CROSS AGE FMR . . . 683
637 ALGORITHM INTSYSMSU-000 CROSS AGE FMR . . . 684
638 ALGORITHM INTSYSMSU-001 CROSS AGE FMR . . . 685
639 ALGORITHM IQFACE-000 CROSS AGE FMR . . . 686
640 ALGORITHM IQFACE-001 CROSS AGE FMR . . . 687
641 ALGORITHM ISAP-001 CROSS AGE FMR . . . 688
642 ALGORITHM ISITYOU-000 CROSS AGE FMR . . . 689
643 ALGORITHM ISYSTEMS-001 CROSS AGE FMR . . . 690
644 ALGORITHM ISYSTEMS-002 CROSS AGE FMR . . . 691
645 ALGORITHM ITMO-006 CROSS AGE FMR . . . 692
646 ALGORITHM ITMO-007 CROSS AGE FMR . . . 693
647 ALGORITHM KAKAO-001 CROSS AGE FMR . . . 694
648 ALGORITHM KAKAO-002 CROSS AGE FMR . . . 695
649 ALGORITHM KEDACOM-000 CROSS AGE FMR . . . 696
650 ALGORITHM KNERON-003 CROSS AGE FMR . . . 697
651 ALGORITHM KNERON-004 CROSS AGE FMR . . . 698
652 ALGORITHM LOOKMAN-002 CROSS AGE FMR . . . 699
653 ALGORITHM LOOKMAN-004 CROSS AGE FMR . . . 700
654 ALGORITHM LUXAND-000 CROSS AGE FMR . . . 701
655 ALGORITHM MEGVII-001 CROSS AGE FMR . . . 702
656 ALGORITHM MEGVII-002 CROSS AGE FMR . . . 703
657 ALGORITHM MEIYA-001 CROSS AGE FMR . . . 704
658 ALGORITHM MICROFOCUS-001 CROSS AGE FMR . . . 705
659 ALGORITHM MICROFOCUS-002 CROSS AGE FMR . . . 706
660 ALGORITHM MT-000 CROSS AGE FMR . . . 707
661 ALGORITHM MVISION-001 CROSS AGE FMR . . . 708
662 ALGORITHM NETBRIDGETECH-001 CROSS AGE FMR . . . 709
663 ALGORITHM NEUROTECHNOLOGY-006 CROSS AGE FMR . . . 710
664 ALGORITHM NEUROTECHNOLOGY-008 CROSS AGE FMR . . . 711
665 ALGORITHM NODEFLUX-001 CROSS AGE FMR . . . 712
666 ALGORITHM NODEFLUX-002 CROSS AGE FMR . . . 713
667 ALGORITHM NOTIONTAG-000 CROSS AGE FMR . . . 714
668 ALGORITHM NTECHLAB-007 CROSS AGE FMR . . . 715
669 ALGORITHM NTECHLAB-008 CROSS AGE FMR . . . 716
670 ALGORITHM PA-004 CROSS AGE FMR . . . 717
671 ALGORITHM PARAVISION-004 CROSS AGE FMR . . . 718
672 ALGORITHM PIXELALL-002 CROSS AGE FMR . . . 719
673 ALGORITHM PIXELALL-003 CROSS AGE FMR . . . 720
674 ALGORITHM PSL-002 CROSS AGE FMR . . . 721
675 ALGORITHM PSL-003 CROSS AGE FMR . . . 722
676 ALGORITHM PYRAMID-000 CROSS AGE FMR . . . 723

677 ALGORITHM RANKONE-007 CROSS AGE FMR . . . 724
678 ALGORITHM RANKONE-008 CROSS AGE FMR . . . 725
679 ALGORITHM REALNETWORKS-002 CROSS AGE FMR . . . 726
680 ALGORITHM REALNETWORKS-003 CROSS AGE FMR . . . 727
681 ALGORITHM REMARKAI-001 CROSS AGE FMR . . . 728
682 ALGORITHM REMARKAI-002 CROSS AGE FMR . . . 729
683 ALGORITHM ROKID-000 CROSS AGE FMR . . . 730
684 ALGORITHM SAFFE-001 CROSS AGE FMR . . . 731
685 ALGORITHM SAFFE-002 CROSS AGE FMR . . . 732
686 ALGORITHM SAMTECH-001 CROSS AGE FMR . . . 733
687 ALGORITHM SENSETIME-002 CROSS AGE FMR . . . 734
688 ALGORITHM SENSETIME-003 CROSS AGE FMR . . . 735
689 ALGORITHM SERTIS-000 CROSS AGE FMR . . . 736
690 ALGORITHM SHAMAN-000 CROSS AGE FMR . . . 737
691 ALGORITHM SHAMAN-001 CROSS AGE FMR . . . 738
692 ALGORITHM SHU-001 CROSS AGE FMR . . . 739
693 ALGORITHM SIAT-002 CROSS AGE FMR . . . 740
694 ALGORITHM SIAT-004 CROSS AGE FMR . . . 741
695 ALGORITHM SJTU-001 CROSS AGE FMR . . . 742
696 ALGORITHM SMILART-002 CROSS AGE FMR . . . 743
697 ALGORITHM SMILART-003 CROSS AGE FMR . . . 744
698 ALGORITHM STARHYBRID-001 CROSS AGE FMR . . . 745
699 ALGORITHM SYNESIS-005 CROSS AGE FMR . . . 746
700 ALGORITHM SYNESIS-006 CROSS AGE FMR . . . 747
701 ALGORITHM SYNOLOGY-000 CROSS AGE FMR . . . 748
702 ALGORITHM TECH5-002 CROSS AGE FMR . . . 749
703 ALGORITHM TECH5-003 CROSS AGE FMR . . . 750
704 ALGORITHM TEVIAN-004 CROSS AGE FMR . . . 751
705 ALGORITHM TEVIAN-005 CROSS AGE FMR . . . 752
706 ALGORITHM TIGER-002 CROSS AGE FMR . . . 753
707 ALGORITHM TIGER-003 CROSS AGE FMR . . . 754
708 ALGORITHM TONGYI-005 CROSS AGE FMR . . . 755
709 ALGORITHM TOSHIBA-002 CROSS AGE FMR . . . 756
710 ALGORITHM TOSHIBA-003 CROSS AGE FMR . . . 757
711 ALGORITHM TRUEFACE-000 CROSS AGE FMR . . . 758
712 ALGORITHM TUPUTECH-000 CROSS AGE FMR . . . 759
713 ALGORITHM ULSEE-001 CROSS AGE FMR . . . 760
714 ALGORITHM ULUFACE-002 CROSS AGE FMR . . . 761
715 ALGORITHM UPC-001 CROSS AGE FMR . . . 762
716 ALGORITHM VCOG-002 CROSS AGE FMR . . . 763
717 ALGORITHM VD-001 CROSS AGE FMR . . . 764
718 ALGORITHM VERIDAS-002 CROSS AGE FMR . . . 765
719 ALGORITHM VIA-000 CROSS AGE FMR . . . 766
720 ALGORITHM VIDEONETICS-001 CROSS AGE FMR . . . 767
721 ALGORITHM VIGILANTSOLUTIONS-006 CROSS AGE FMR . . . 768
722 ALGORITHM VIGILANTSOLUTIONS-007 CROSS AGE FMR . . . 769
723 ALGORITHM VION-000 CROSS AGE FMR . . . 770
724 ALGORITHM VISIONBOX-000 CROSS AGE FMR . . . 771
725 ALGORITHM VISIONBOX-001 CROSS AGE FMR . . . 772
726 ALGORITHM VISIONLABS-007 CROSS AGE FMR . . . 773
727 ALGORITHM VOCORD-006 CROSS AGE FMR . . . 774
728 ALGORITHM VOCORD-007 CROSS AGE FMR . . . 775
729 ALGORITHM WINSENSE-000 CROSS AGE FMR . . . 776
730 ALGORITHM WINSENSE-001 CROSS AGE FMR . . . 777
731 ALGORITHM X-LABORATORY-000 CROSS AGE FMR . . . 778
732 ALGORITHM YISHENG-004 CROSS AGE FMR . . . 779
733 ALGORITHM YITU-003 CROSS AGE FMR . . . 780

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
1	3Divi	3divi	003	2018-10-09	191636	^{37}358	^{184}4096 ± 0	^{120}650 ± 90	^{15}627 ± 11	^{19}623 ± 32
2	3Divi	3divi	004	2019-07-22	263670	^{49}430	^{97}2048 ± 0	^{189}984 ± 131	^{26}794 ± 35	^{28}801 ± 40
3	ADVANCE.AI	advance	002	2019-12-19	257173	^{29}295	^{63}2048 ± 0	^{159}811 ± 2	^{98}3292 ± 26	^{98}3306 ± 57
4	ASUSTek Computer Inc	asusaics	000	2019-10-24	257418	^{80}603	^{85}2048 ± 0	^{73}488 ± 18	^{154}8118 ± 128	^{153}8053 ± 456
5	Acer Incorporated	acer	000	2020-01-08	109735	^{60}476	^{94}2048 ± 0	^{23}222 ± 0	^{104}3479 ± 71	^{106}3636 ± 232
6	Adera Global PTE Ltd	adera	001	2019-06-17	0	^{21}190	^{169}2560 ± 0	^{6}97 ± 0	^{60}1604 ± 71	^{61}1649 ± 56
7	Ai First	aifirst	001	2019-11-21	224157	^{61}482	^{62}2048 ± 0	^{103}589 ± 4	^{102}3442 ± 40	^{101}3450 ± 123
8	AiUnion Technology Co Ltd	aiunionface	000	2019-10-22	241642	^{43}406	^{99}2048 ± 0	^{123}653 ± 32	^{101}3439 ± 47	^{108}3657 ± 167
9	Alchera Inc	alchera	000	2019-03-01	258450	^{84}614	^{82}2048 ± 0	^{101}587 ± 13	^{96}3189 ± 32	^{89}3031 ± 142
10	Alchera Inc	alchera	000	2019-03-01	174013	^{59}473	^{78}2048 ± 0	^{113}627 ± 11	^{99}3342 ± 81	^{94}3243 ± 47
11	Alivia / Innovation Sys	isystems	001	2018-06-12	274621	^{136}1091	^{61}2048 ± 0	^{38}291 ± 9	^{9}557 ± 16	^{11}564 ± 22
12	Alivia / Innovation Sys	isystems	002	2018-10-18	358984	^{165}1595	^{108}2048 ± 0	^{164}822 ± 8	^{24}749 ± 31	^{21}632 ± 28
13	AllGoVision	allgovision	000	2019-03-01	172509	^{76}561	^{116}2048 ± 0	^{58}384 ± 8	^{179}29903 ± 406	^{180}29735 ± 194
14	AlphaSSTG	alphaface	001	2019-09-03	259849	^{73}531	^{88}2048 ± 0	^{109}613 ± 3	^{105}3482 ± 41	^{96}3279 ± 91
15	Amplified Group	amplifiedgroup	001	2019-03-01	0	^{8}81	^{31}866 ± 2	^{5}93 ± 0	^{184}57803 ± 4210	^{184}56365 ± 1196
16	Anke Investments	anke	004	2019-06-27	349388	^{92}706	^{148}2056 ± 0	^{112}625 ± 1	^{16}633 ± 22	^{20}632 ± 34
17	Anke Investments	anke	005	2019-11-21	328553	^{140}1130	^{150}2056 ± 0	^{102}589 ± 2	^{93}3121 ± 44	^{97}3296 ± 71
18	Antheus Technologia Ltda	antheus	000	2019-12-05	119453	^{13}116	^{24}520 ± 0	^{8}109 ± 1	^{148}7085 ± 31	^{147}7082 ± 37
19	AnyVision	anyvision	002	2018-01-31	662659	^{55}468	^{39}1024 ± 0	^{27}248 ± 0	^{185}74069 ± 188	^{185}74019 ± 198
20	AnyVision	anyvision	004	2018-06-15	401001	^{138}1102	^{36}1024 ± 0	^{52}355 ± 1	^{70}1891 ± 51	^{67}1829 ± 85
21	Aware	aware	003	2018-10-19	377729	^{152}1348	^{173}3108 ± 0	^{156}783 ± 10	^{53}1392 ± 42	^{54}1334 ± 80
22	Aware	aware	004	2019-03-01	427829	^{170}1820	^{162}2084 ± 0	^{178}900 ± 10	^{49}1279 ± 50	^{53}1287 ± 100
23	Awidit Systems	awiros	001	2019-09-23	15499	^{9}88	^{16}512 ± 0	^{7}99 ± 8	^{68}1868 ± 100	^{82}2467 ± 78
24	Ayonix	ayonix	000	2017-06-22	58505	^{4}69	^{40}1036 ± 0	^{1}18 ± 2	^{14}621 ± 23	^{18}620 ± 26
25	Beijing Vion Technology Inc	vion	000	2018-10-19	228219	^{64}498	^{139}2052 ± 0	^{48}333 ± 1	^{181}39839 ± 3561	^{175}26830 ± 2241
26	BioID Technologies SA	bioidtechswiss	000	2019-11-15	758466	^{127}1041	^{10}256 ± 0	^{115}631 ± 2	^{180}34933 ± 139	^{181}34866 ± 121
27	Bitmain	bitmain	001	2018-10-17	287734	^{14}148	^{1}64 ± 0	^{68}444 ± 88	^{69}1887 ± 31	^{68}1877 ± 26
28	CSA IntelliCloud Technology	intellicloudai	001	2019-08-13	220831	^{88}655	^{128}2048 ± 0	^{72}479 ± 18	^{35}1010 ± 16	^{36}1024 ± 31
29	CTBC Bank Co Ltd	ctbcbank	000	2019-06-28	257208	^{77}570	^{83}2048 ± 0	^{95}568 ± 43	^{108}3551 ± 87	^{129}4805 ± 209
30	CTBC Bank Co Ltd	ctbcbank	001	2019-10-28	275511	^{86}624	^{120}2048 ± 0	^{125}654 ± 33	^{147}6321 ± 283	^{143}6218 ± 286
31	Camvi Technologies	camvitech	002	2018-10-19	236278	^{98}737	^{38}1024 ± 0	^{136}677 ± 7	^{13}612 ± 26	^{14}603 ± 20
32	Camvi Technologies	camvitech	004	2019-07-12	280733	^{121}919	^{109}2048 ± 0	^{151}759 ± 10	^{32}948 ± 40	^{33}963 ± 31
33	Canon Information Technology (Beijing) Co Ltd	cib	000	2019-12-11	340288	^{75}558	^{105}2048 ± 0	^{190}988 ± 40	^{177}26805 ± 83	^{176}26857 ± 177
34	China Electronics Import-Export Corp	ceiec	002	2019-06-12	269063	^{47}426	^{77}2048 ± 0	^{108}612 ± 17	^{77}2188 ± 57	^{77}2301 ± 56
35	China Electronics Import-Export Corp	ceiec	003	2020-01-06	260371	^{46}425	^{79}2048 ± 0	^{162}819 ± 3	^{127}4594 ± 109	^{130}4864 ± 62
36	China University of Petroleum	upc	001	2019-06-05	0	^{132}1077	^{42}1052 ± 0	^{92}551 ± 15	^{92}3114 ± 44	^{93}3165 ± 97
37	Chunghwa Telecom Co. Ltd	chtface	001	2019-08-06	94088	^{33}352	^{111}2048 ± 0	^{22}218 ± 12	^{74}2089 ± 45	^{73}2087 ± 23
38	Chunghwa Telecom Co. Ltd	chtface	002	2019-12-07	363153	^{137}1100	^{93}2048 ± 0	^{100}585 ± 14	^{126}4551 ± 41	^{125}4550 ± 80
39	Cognitec Systems GmbH	cognitec	000	2018-10-19	474759	^{63}495	^{135}2052 ± 0	^{24}224 ± 1	^{116}3835 ± 108	^{112}3782 ± 83
40	Cognitec Systems GmbH	cognitec	001	2019-03-01	476809	^{65}498	^{142}2052 ± 0	^{41}297 ± 17	^{122}4253 ± 59	^{118}4102 ± 167
41	Cyberextruder	cyberex	001	2017-08-02	121211	^{18}178	^{9}256 ± 0	^{177}893 ± 25	^{38}1083 ± 16	^{41}1079 ± 19
42	Cyberextruder	cyberex	002	2018-01-30	168909	^{23}194	^{64}2048 ± 0	^{81}532 ± 6	^{67}1803 ± 14	^{64}1779 ± 22
43	Cyberlink Corp	cyberlink	002	2019-06-12	222311	^{99}760	^{137}2052 ± 0	^{127}656 ± 22	^{80}2264 ± 71	^{85}2649 ± 195
44	Cyberlink Corp	cyberlink	003	2019-10-07	470949	^{110}822	^{134}2052 ± 0	^{64}424 ± 1	^{132}4857 ± 53	^{133}5168 ± 69

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 1: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
45	DSK	dsk	000	2019-06-28	11967	^{25}252	^{18}512 ± 0	^{43}304 ± 47	^{150}7152 ± 115	^{148}7134 ± 111
46	Dahua Technology Co Ltd	dahua	003	2019-08-14	605337	^{183}3754	^{110}2048 ± 0	^{83}537 ± 4	^{18}653 ± 28	^{15}606 ± 38
47	Dahua Technology Co Ltd	dahua	004	2019-12-18	832455	^{186}4881	^{89}2048 ± 0	^{146}740 ± 11	^{90}3105 ± 56	^{91}3142 ± 115
48	Deepglint	deepglint	001	2019-06-21	569802	^{120}917	^{182}4096 ± 0	^{144}721 ± 4	^{111}3680 ± 35	^{102}3517 ± 182
49	Deepglint	deepglint	002	2019-11-15	459642	^{167}1693	^{179}4096 ± 0	^{130}667 ± 1	^{169}18395 ± 217	^{167}17399 ± 429
50	Dermalog	dermalog	005	2018-02-02	0	^{36}357	^{2}128 ± 0	^{11}130 ± 11	^{6}499 ± 22	^{8}500 ± 22
51	Dermalog	dermalog	006	2018-10-18	0	^{126}970	^{3}128 ± 0	^{80}532 ± 12	^{7}506 ± 23	^{6}459 ± 23
52	DiDi ChuXing Technology Co	didiglobalface	001	2019-10-23	259849	^{74}533	^{87}2048 ± 0	^{119}650 ± 13	^{109}3592 ± 32	^{104}3588 ± 83
53	Digital Barriers	barriers	002	2019-03-01	83002	^{173}1930	^{152}2056 ± 0	^{20}209 ± 11	^{162}13409 ± 228	^{161}13267 ± 206
54	Expasoft LLC	expasoft	000	2020-01-06	15341	^{10}98	^{125}2048 ± 0	^{3}69 ± 0	^{124}4429 ± 54	^{119}4158 ± 108
55	FaceSoft Ltd	facesoft	000	2019-07-10	370120	^{106}796	^{130}2048 ± 0	^{135}675 ± 18	^{78}2239 ± 28	^{76}2277 ± 96
56	FarBar Inc	f8	001	2019-07-11	272977	^{147}1276	^{74}2048 ± 0	^{165}822 ± 39	^{165}15262 ± 139	^{164}15277 ± 212
57	Gemalto Cogent	cogent	003	2019-03-01	698290	^{158}1445	^{32}973 ± 0	^{186}952 ± 0	^{160}12496 ± 75	^{159}11822 ± 163
58	Gemalto Cogent	cogent	004	2019-06-14	722919	^{129}1059	^{60}1983 ± 0	^{184}941 ± 28	^{164}14448 ± 56	^{165}15882 ± 81
59	Glory Ltd	glory	001	2018-06-08	0	^{151}1331	^{57}1726 ± 0	^{60}393 ± 2	^{158}9607 ± 128	^{157}9539 ± 182
60	Glory Ltd	glory	002	2019-11-12	0	^{123}935	^{165}2106 ± 0	^{104}594 ± 5	^{157}8815 ± 105	^{155}8782 ± 78
61	Gorilla Technology	gorilla	003	2019-06-19	94409	^{89}668	^{44}1132 ± 0	^{49}334 ± 25	^{87}2840 ± 42	^{87}2865 ± 87
62	Gorilla Technology	gorilla	004	2019-11-04	186952	^{114}853	^{168}2192 ± 0	^{62}397 ± 3	^{138}5269 ± 84	^{136}5259 ± 105
63	Guangzhou Pixel Solutions Co Ltd	pixelall	002	2019-06-06	0	^{30}342	^{170}2560 ± 0	^{19}191 ± 1	^{45}1223 ± 56	^{49}1230 ± 47
64	Guangzhou Pixel Solutions Co Ltd	pixelall	003	2019-10-15	0	^{116}866	^{171}2560 ± 0	^{142}708 ± 21	^{121}4216 ± 257	^{124}4488 ± 56
65	Hengrui AI Technology Ltd	hr	001	2019-06-04	346156	^{166}1682	^{158}2057 ± 0	^{129}665 ± 3	^{167}17816 ± 260	^{168}17878 ± 464
66	Hengrui AI Technology Ltd	hr	001	2019-10-08	390059	^{150}1329	^{159}2057 ± 0	^{180}904 ± 4	^{174}24112 ± 766	^{173}23859 ± 739
67	Hikvision Research Institute	hik	001	2019-03-01	667866	^{188}6597	^{50}1408 ± 0	^{121}651 ± 0	^{5}488 ± 19	^{7}477 ± 22
68	ID3 Technology	id3	003	2018-10-05	265951	^{34}354	^{12}264 ± 0	^{45}316 ± 19	^{52}1330 ± 25	^{55}1354 ± 28
69	ID3 Technology	id3	004	2019-03-01	171526	^{83}613	^{11}264 ± 0	^{87}541 ± 11	^{39}1135 ± 23	^{46}1156 ± 32
70	ITMO University	itmo	006	2019-03-01	599187	^{161}1489	^{167}2121 ± 0	^{160}814 ± 1	^{175}26154 ± 148	^{174}26217 ± 260
71	ITMO University	itmo	007	2020-01-06	415979	^{176}2190	^{114}2048 ± 0	^{147}742 ± 3	^{130}4825 ± 69	^{131}5016 ± 281
72	Idemia	Idemia	004	2019-03-01	406924	^{66}501	^{14}352 ± 0	^{44}306 ± 5	^{139}5592 ± 518	^{138}5533 ± 426
73	Idemia	Idemia	005	2019-10-11	509824	^{85}623	^{29}588 ± 0	^{79}524 ± 20	^{151}7543 ± 370	^{158}10415 ± 174
74	Imagus Technology Pty Ltd	imagus	000	2019-06-19	183453	^{54}466	^{122}2048 ± 0	^{66}425 ± 24	^{40}1145 ± 25	^{63}1718 ± 63
75	Imagus Technology Pty Ltd	imagus	001	2019-10-22	282680	^{108}802	^{98}2048 ± 0	^{163}820 ± 45	^{112}3700 ± 34	^{103}3585 ± 238
76	Imperial College London	imperial	000	2019-03-01	370120	^{107}796	^{96}2048 ± 0	^{132}669 ± 1	^{75}2130 ± 32	^{72}2052 ± 100
77	Imperial College London	imperial	002	2019-08-28	472327	^{171}1824	^{66}2048 ± 0	^{96}570 ± 2	^{131}4827 ± 69	^{126}4557 ± 160
78	Incode Technologies Inc	incode	004	2019-06-12	260224	^{97}733	^{71}2048 ± 0	^{71}479 ± 23	^{71}1913 ± 60	^{80}2443 ± 114
79	Incode Technologies Inc	incode	004	2019-10-17	256242	^{135}1090	^{92}2048 ± 0	^{94}567 ± 4	^{125}4443 ± 91	^{128}4685 ± 72
80	Innovative Technology Ltd	innovativetechnologyltd	001	2019-10-22	177232	^{31}343	^{102}2048 ± 0	^{67}432 ± 7	^{128}4676 ± 34	^{123}4468 ± 169
81	Innovatrics	innovatrics	004	2018-10-19	0	^{154}1367	^{43}1076 ± 0	^{59}391 ± 0	^{156}8573 ± 274	^{152}7929 ± 244
82	Innovatrics	innovatrics	006	2019-08-13	0	^{139}1109	^{25}538 ± 0	^{166}824 ± 10	^{142}5763 ± 217	^{141}5631 ± 824
83	Institute of Information Technologies	iitvision	001	2019-07-05	269176	^{103}788	^{101}2048 ± 0	^{140}699 ± 4	^{36}1060 ± 48	^{39}1074 ± 54
84	Institute of Information Technologies	iitvision	002	2019-12-04	259579	^{96}731	^{119}2048 ± 0	^{78}516 ± 1	^{103}3447 ± 59	^{107}3649 ± 83
85	Intel Research Group	intelresearch	000	2019-07-08	388229	^{177}2406	^{67}2048 ± 0	^{179}902 ± 6	^{129}4800 ± 152	^{127}4561 ± 97
86	Intel Research Group	intelresearch	001	2020-01-14	353997	^{157}1432	^{107}2048 ± 0	^{138}680 ± 3	^{143}5854 ± 128	^{145}6291 ± 151
87	Intellivision	intellivision	001	2017-10-10	43692	^{6}74	^{154}2056 ± 0	^{2}62 ± 2	^{82}2573 ± 91	^{84}2544 ± 38
88	Intellivision	intellivision	002	2019-08-23	43692	^{7}80	^{149}2056 ± 0	^{51}342 ± 30	^{166}16049 ± 195	^{163}15136 ± 389

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 2: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
89	Is It You	isityou	000	2017-06-26	48010	^{11}110	^{191}19200 ± 0	^{9}113 ± 5	^{187}237517 ± 1318	^{187}237374 ± 1279
90	Kakao Corp	kakao	001	2019-03-01	107616	^{24}225	^{35}1024 ± 0	^{57}379 ± 1	^{29}930 ± 22	^{32}948 ± 38
91	Kakao Corp	kakao	002	2019-06-19	479406	^{81}603	^{131}2048 ± 0	^{148}747 ± 6	^{63}1720 ± 62	^{62}1715 ± 83
92	Kedacom International Pte	kedacom	000	2019-06-03	245292	^{191}23574	^{13}292 ± 0	^{76}506 ± 3	^{19}684 ± 14	^{22}682 ± 16
93	Kneron Inc	kenron	003	2019-07-01	58366	^{19}188	^{90}2048 ± 0	^{35}281 ± 3	^{137}5237 ± 63	^{137}5274 ± 99
94	Kneron Inc	kenron	004	2019-12-03	272218	^{111}828	^{103}2048 ± 0	^{192}1455 ± 5	^{123}4345 ± 59	^{121}4373 ± 105
95	Lomonosov Moscow State University	intsysmsu	000	2019-06-18	650193	^{130}1066	^{69}2048 ± 0	^{82}535 ± 20	^{11}610 ± 22	^{17}613 ± 31
96	Lomonosov Moscow State University	intsysmsu	001	2019-10-22	384409	^{104}789	^{91}2048 ± 0	^{110}617 ± 5	^{94}3135 ± 26	^{100}3440 ± 235
97	Lookman Electroplast Industries	lookman	002	2018-06-13	138200	^{189}16518	^{27}548 ± 0	^{15}173 ± 1	^{12}610 ± 19	^{16}612 ± 22
98	Lookman Electroplast Industries	lookman	004	2019-06-03	244775	^{190}23548	^{26}548 ± 0	^{77}507 ± 5	^{28}871 ± 29	^{31}878 ± 29
99	Luxand Inc	luxand	000	2019-11-07	0	^{155}1369	^{41}1040 ± 0	^{63}406 ± 22	^{79}2240 ± 32	^{75}2234 ± 25
100	MVision	mvision	001	2019-11-12	227502	^{94}712	^{21}512 ± 0	^{139}690 ± 21	^{66}1797 ± 38	^{66}1788 ± 32
101	Megvii/Face++	megvii	001	2018-06-15	1361523	^{156}1426	^{127}2048 ± 0	^{88}543 ± 0	^{136}5228 ± 32	^{134}5252 ± 60
102	Megvii/Face++	megvii	002	2018-10-19	1809564	^{172}1879	^{187}4100 ± 0	^{117}644 ± 0	^{183}50630 ± 183	^{183}47591 ± 716
103	MicroFocus	microfocus	001	2018-06-13	104524	^{20}190	^{7}256 ± 0	^{31}264 ± 18	^{1}215 ± 8	^{1}217 ± 10
104	MicroFocus	microfocus	002	2018-10-17	96288	^{16}176	^{6}256 ± 0	^{29}259 ± 18	^{2}337 ± 34	^{2}230 ± 25
105	Momentum Digital Co Ltd	sertis	000	2019-10-07	265572	^{48}427	^{68}2048 ± 0	^{149}755 ± 0	^{117}3883 ± 44	^{114}3884 ± 66
106	Moontime Smart Technology	mt	000	2019-06-03	372169	^{128}1056	^{132}2049 ± 0	^{145}724 ± 12	^{62}1678 ± 47	^{60}1614 ± 85
107	N-Tech Lab	ntech	007	2019-06-25	2509686	^{187}5070	^{174}3348 ± 0	^{157}792 ± 3	^{44}1209 ± 59	^{51}1267 ± 65
108	N-Tech Lab	ntech	008	2020-01-06	1138002	^{180}2705	^{49}1300 ± 0	^{93}552 ± 1	^{85}2665 ± 31	^{86}2832 ± 50
109	Netbridge Technology Incoporation	netbridgetech	001	2020-01-08	133108	^{56}468	^{180}4096 ± 0	^{4}85 ± 2	^{161}13233 ± 108	^{162}14368 ± 213
110	Neurotechnology	neurotech	006	2019-06-26	525541	^{163}1538	^{19}512 ± 0	^{137}678 ± 56	^{8}513 ± 14	^{10}535 ± 26
111	Neurotechnology	neurotech	008	2020-01-08	119718	^{90}702	^{8}256 ± 0	^{50}339 ± 0	^{42}1158 ± 26	^{47}1158 ± 28
112	Nodeflux	nodeflux	001	2019-03-01	262553	^{39}363	^{106}2048 ± 0	^{26}247 ± 1	^{97}3242 ± 81	^{95}3255 ± 93
113	Nodeflux	nodeflux	002	2019-08-13	774668	^{58}471	^{129}2048 ± 0	^{143}717 ± 16	^{144}5922 ± 170	^{151}7911 ± 367
114	NotionTag Technologies Private Limited	notiontag	000	2019-06-12	92753	^{72}525	^{28}584 ± 0	^{91}548 ± 64	^{182}44672 ± 269	^{182}44593 ± 358
115	Panasonic R+D Center Singapore	psl	002	2019-02-28	804934	^{169}1814	^{138}2052 ± 0	^{175}888 ± 9	^{59}1590 ± 48	^{42}1133 ± 78
116	Panasonic R+D Center Singapore	psl	003	2019-10-01	1159643	^{185}3961	^{166}2120 ± 0	^{171}867 ± 7	^{118}3915 ± 50	^{115}3899 ± 226
117	Paravision (EverAI)	everai paravision	003	2019-07-01	539802	^{144}1225	^{181}4096 ± 0	^{134}674 ± 4	^{22}699 ± 20	^{24}713 ± 47
118	Paravision (EverAI)	everai paravision	004	2019-12-11	556670	^{164}1570	^{178}4096 ± 0	^{173}879 ± 34	^{145}5997 ± 29	^{142}5682 ± 185
119	Ping An Technology	Pingan	004	2019-11-20	257981	^{105}795	^{75}2048 ± 0	^{191}1011 ± 2	^{115}3806 ± 335	^{117}4086 ± 60
120	Pyramid Cyber Security + Forensic (P) Ltd	pyramid	000	2019-11-04	372608	^{109}804	^{146}2056 ± 0	^{99}583 ± 2	^{149}7147 ± 59	^{149}7586 ± 425
121	Rank One Computing	rankone	007	2019-06-03	0	^{3}67	^{5}165 ± 0	^{25}245 ± 5	^{20}688 ± 20	^{13}601 ± 16
122	Rank One Computing	rankone	008	2019-11-12	0	^{5}70	^{4}165 ± 0	^{33}272 ± 4	^{31}944 ± 29	^{30}864 ± 26
123	Realnetworks Inc	realnetworks	002	2019-02-28	95328	^{40}370	^{59}1848 ± 0	^{28}250 ± 2	^{50}1285 ± 17	^{50}1247 ± 42
124	Realnetworks Inc	realnetworks	003	2019-06-12	95334	^{32}345	^{58}1848 ± 0	^{17}177 ± 10	^{57}1516 ± 29	^{58}1522 ± 60
125	Remark Holdings	remarkai	001	2019-03-01	241857	^{95}730	^{141}2052 ± 0	^{167}831 ± 6	^{46}1229 ± 20	^{29}805 ± 56
126	Remark Holdings	remarkai	001	2019-11-21	224157	^{52}446	^{81}2048 ± 0	^{185}952 ± 4	^{110}3614 ± 40	^{105}3632 ± 32
127	Rokid Corporation Ltd	rokid	000	2019-08-01	258612	^{142}1197	^{155}2056 ± 0	^{89}547 ± 2	^{113}3711 ± 88	^{111}3746 ± 209
128	Rokid Corporation Ltd	rokid	001	2019-12-13	641223	^{131}1068	^{160}2060 ± 0	^{182}912 ± 3	^{141}5696 ± 111	^{140}5610 ± 59
129	Saffe Ltd	saffe	001	2018-10-19	85973	^{15}168	^{47}1280 ± 0	^{34}281 ± 1	^{48}1274 ± 19	^{52}1277 ± 26
130	Saffe Ltd	saffe	002	2019-03-01	260622	^{115}855	^{118}2048 ± 0	^{161}817 ± 11	^{23}717 ± 7	^{25}714 ± 29
131	Samsung S1 Corp	s1	001	2019-12-06	435491	^{101}773	^{164}2092 ± 0	^{105}602 ± 21	^{120}4151 ± 44	^{122}4428 ± 246
132	Samtech InfoNet Limited	samtech	001	2019-10-15	288082	^{82}605	^{151}2056 ± 0	^{39}294 ± 3	^{152}7694 ± 59	^{150}7678 ± 91

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 3: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
133	Scanovate Ltd	scanovate	001	2019-11-12	257083	^{79}595	^{72}2048 ± 0	^{98}579 ± 24	^{163}14306 ± 352	^{166}16031 ± 538
134	Sensetime Group Ltd	sensetime	002	2018-10-19	531783	^{174}2094	^{144}2052 ± 0	^{158}797 ± 3	^{86}2713 ± 90	^{78}2301 ± 25
135	Sensetime Group Ltd	sensetime	003	2019-06-04	787853	^{179}2539	^{143}2052 ± 0	^{181}910 ± 4	^{134}5017 ± 137	^{135}5258 ± 51
136	Shaman Software	shaman	000	2017-12-05	0	^{68}507	^{183}4096 ± 0	^{124}653 ± 16	^{3}380 ± 25	^{4}379 ± 31
137	Shaman Software	shaman	001	2018-01-13	0	^{70}511	^{177}4096 ± 0	^{40}294 ± 2	^{17}635 ± 19	^{5}441 ± 25
138	Shanghai Jiao Tong University	sjtu	001	2019-09-27	347115	^{50}437	^{65}2048 ± 0	^{122}651 ± 4	^{191}2674654 ± 64798	^{191}2376946 ± 202419
139	Shanghai Ulucu Electronics Technology Co. Ltd	uluface	002	2019-07-10	0	^{134}1088	^{100}2048 ± 0	^{172}873 ± 42	^{172}19207 ± 1114	^{170}18501 ± 274
140	Shanghai Ulucu Electronics Technology Co. Ltd	uluface	003	2019-11-12	97357	^{146}1259	^{172}3072 ± 0	^{187}970 ± 15	^{178}27666 ± 198	^{179}29560 ± 244
141	Shanghai Universiy - Shanghai Film Academy	shu	001	2019-06-17	329513	^{42}402	^{124}2048 ± 0	^{107}612 ± 5	^{84}2619 ± 19	^{88}2987 ± 143
142	Shanghai Universiy - Shanghai Film Academy	shu	002	2019-12-10	731250	^{118}890	^{176}4096 ± 0	^{150}759 ± 5	^{192}2926869 ± 49960	^{192}2926507 ± 48716
143	Shanghai Yitu Technology	yitu	003	2019-03-01	1525719	^{182}3737	^{161}2082 ± 0	^{170}860 ± 0	^{168}18305 ± 71	^{169}18286 ± 62
144	Shenzhen AiMall Tech Ltd	aimall	001	2019-11-12	128820	^{17}178	^{37}1024 ± 0	^{47}328 ± 0	^{135}5038 ± 40	^{146}6849 ± 401
145	Shenzhen EI Networks Limited	einetworks	000	2019-08-13	372608	^{117}880	^{156}2056 ± 0	^{118}645 ± 3	^{133}4876 ± 66	^{132}5156 ± 77
146	Shenzhen Inst Adv Integrated Tech CAS	SIAT	002	2018-06-13	486842	^{178}2434	^{145}2052 ± 0	^{97}579 ± 0	^{25}769 ± 13	^{26}750 ± 13
147	Shenzhen Inst Adv Integrated Tech CAS	SIAT	004	2019-03-01	940063	^{184}3860	^{186}4100 ± 0	^{133}670 ± 0	^{119}4013 ± 45	^{113}3782 ± 173
148	Shenzhen Intellifusion Technologies Co Ltd	intellifusion	001	2019-08-22	271872	^{100}762	^{70}2048 ± 0	^{153}778 ± 61	^{114}3756 ± 59	^{116}3953 ± 126
149	Smilart	smilart	002	2018-02-06	111826	^{26}263	^{34}1024 ± 0	^{16}176 ± 16	^{170}18784 ± 136	^{171}18795 ± 151
150	Smilart	smilart	003	2018-06-18	67339	^{22}192	^{17}512 ± 0	^{18}180 ± 12	^{54}1395 ± 74	^{37}1027 ± 66
151	Star Hybrid Limited	starhybrid	001	2019-06-19	100509	^{113}845	^{84}2048 ± 0	^{54}358 ± 82	^{37}1075 ± 51	^{40}1078 ± 53
152	Synesis	synesis	005	2019-06-06	146509	^{87}638	^{104}2048 ± 0	^{21}211 ± 9	^{10}599 ± 23	^{12}581 ± 32
153	Synesis	synesis	006	2019-10-10	731941	^{160}1468	^{188}4104 ± 0	^{90}547 ± 1	^{140}5658 ± 17	^{139}5603 ± 148
154	Synology Inc	synology	000	2019-10-23	221021	^{53}453	^{73}2048 ± 0	^{65}425 ± 25	^{173}23628 ± 206	^{178}29262 ± 4987
155	TUPU Technology Co Ltd	tuputech	000	2019-10-11	11476	^{1}33	^{80}2048 ± 0	^{10}124 ± 7	^{176}26308 ± 269	^{177}28022 ± 2594
156	Taiwan AI Labs	ailabs	001	2019-12-18	1054663	^{145}1256	^{76}2048 ± 0	^{128}664 ± 4	^{186}100635 ± 999	^{186}100995 ± 1587
157	Tech5 SA	tech5	002	2019-03-01	1150887	^{159}1461	^{48}1280 ± 0	^{154}780 ± 10	^{56}1406 ± 120	^{38}1048 ± 57
158	Tech5 SA	tech5	003	2019-08-19	1427464	^{168}1735	^{51}1536 ± 0	^{183}937 ± 39	^{51}1313 ± 35	^{56}1360 ± 41
159	Tencent Deepsea Lab	deepsea	001	2019-06-03	147497	^{38}358	^{33}1024 ± 0	^{114}630 ± 7	^{55}1401 ± 37	^{57}1467 ± 50
160	Tevian	tevian	004	2019-03-01	863474	^{102}774	^{86}2048 ± 0	^{75}506 ± 30	^{4}474 ± 31	^{3}326 ± 20
161	Tevian	tevian	005	2019-09-21	921043	^{133}1082	^{115}2048 ± 0	^{116}642 ± 32	^{89}3097 ± 31	^{109}3700 ± 278
162	TigerIT Americas LLC	tiger	002	2018-06-13	341638	^{71}522	^{153}2056 ± 0	^{61}393 ± 20	^{76}2135 ± 29	^{74}2137 ± 38
163	TigerIT Americas LLC	tiger	003	2018-10-16	426164	^{93}708	^{147}2056 ± 0	^{69}458 ± 21	^{73}2031 ± 35	^{71}2029 ± 38
164	TongYi Transportation Technology	tongyi	005	2019-06-12	1140701	^{175}2121	^{163}2089 ± 0	^{13}165 ± 1	^{171}18924 ± 65	^{172}20158 ± 103
165	Toshiba	toshiba	002	2018-10-19	813606	-	^{54}1560 ± 0	^{86}541 ± 0	^{106}3521 ± 369	^{81}2449 ± 124
166	Toshiba	toshiba	003	2019-03-01	984125	^{141}1197	^{55}1560 ± 0	^{85}540 ± 0	^{81}2390 ± 41	^{79}2407 ± 81
167	Trueface.ai	trueface	000	2019-10-08	255123	^{62}493	^{121}2048 ± 0	^{55}368 ± 11	^{88}3040 ± 26	^{92}3144 ± 51
168	ULSee Inc	ulsee	001	2019-07-31	370519	^{44}416	^{117}2048 ± 0	^{126}654 ± 2	^{146}6065 ± 94	^{144}6228 ± 77
169	VCognition	vcog	002	2017-06-12	3229434	^{181}3666	^{192}61504 ± 5	^{53}357 ± 25	^{188}296154 ± 3077	^{188}296436 ± 4183
170	Veridas Digital Authentication Solutions S.L.	veridas	002	2019-03-01	193466	^{67}505	^{23}512 ± 0	^{131}669 ± 20	^{64}1733 ± 81	^{69}1934 ± 44
171	Veridas Digital Authentication Solutions S.L.	veridas	003	2019-11-27	293109	^{57}468	^{95}2048 ± 0	^{176}892 ± 33	^{153}7974 ± 51	^{156}9463 ± 206
172	Via Technologies Inc.	via	000	2019-07-08	124422	^{125}964	^{112}2048 ± 0	^{141}707 ± 8	^{34}966 ± 28	^{35}1021 ± 44
173	Videmo Intelligente Videoanalyse	videmo	000	2019-12-19	139643	^{41}391	^{126}2048 ± 0	^{12}141 ± 5	^{91}3106 ± 145	^{90}3127 ± 57
174	Videonetics Technology Pvt Ltd	videonetics	001	2019-06-19	30875	^{2}61	^{15}512 ± 0	^{30}262 ± 3	^{41}1153 ± 38	^{43}1142 ± 65
175	Videonetics Technology Pvt Ltd	videonetics	002	2019-11-21	121981	^{12}115	^{140}2052 ± 0	^{36}281 ± 5	^{107}3533 ± 57	^{110}3742 ± 65
176	Vigilant Solutions	vigilant	006	2019-03-01	343048	^{149}1316	^{53}1548 ± 0	^{169}841 ± 8	^{30}939 ± 32	^{23}711 ± 37

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 4: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

	Developer	Short	Seq.	Validation	Config[1]	Template			Comparison Time (ns)[4]	
	Name	Name	Num.	Date	Data (KB)	Memory (MB)[2]	Size (B)	Time (ms)[3]	Genuine	Impostor
177	Vigilant Solutions	vigilant	007	2019-06-27	255600	^{119}912	^{52}1548 ± 0	^{74}493 ± 6	^{27}803 ± 35	^{27}800 ± 40
178	Visidon	visidon	001	2019-02-26	170262	^{28}281	^{136}2052 ± 0	^{46}316 ± 6	^{47}1258 ± 38	^{44}1148 ± 109
179	Vision-Box	visionbox	000	2019-02-26	176501	^{35}355	^{123}2048 ± 0	^{42}304 ± 7	^{61}1648 ± 57	^{48}1192 ± 42
180	Vision-Box	visionbox	001	2019-03-01	256869	^{78}579	^{113}2048 ± 0	^{188}983 ± 7	^{43}1161 ± 22	^{45}1154 ± 20
181	VisionLabs	visionlabs	007	2019-06-12	357204	^{27}266	^{20}512 ± 0	^{32}272 ± 0	^{33}965 ± 41	^{34}972 ± 31
182	VisionLabs	visionlabs	008	2020-01-06	706099	^{51}446	^{22}512 ± 0	^{70}467 ± 1	^{65}1759 ± 37	^{65}1786 ± 35
183	Vocord	vocord	006	2019-03-01	559457	^{143}1216	^{30}768 ± 0	^{174}886 ± 1	^{72}2020 ± 72	^{70}1969 ± 62
184	Vocord	vocord	007	2019-06-06	587489	^{153}1352	^{56}1664 ± 0	^{155}780 ± 2	^{83}2593 ± 83	^{83}2526 ± 59
185	Winsense Co Ltd	winsense	000	2019-06-17	270819	^{112}833	^{45}1280 ± 0	^{37}283 ± 1	^{58}1551 ± 31	^{59}1532 ± 42
186	Winsense Co Ltd	winsense	001	2019-10-16	264428	^{122}922	^{46}1280 ± 0	^{152}768 ± 9	^{95}3143 ± 32	^{120}4230 ± 226
187	X-Laboratory	x-laboratory	000	2019-09-03	520020	^{162}1524	^{157}2056 ± 0	^{168}832 ± 38	^{100}3380 ± 91	^{99}3314 ± 253
188	Xiamen Meiya Pico Information Co. Ltd	meiya	001	2019-03-01	280055	^{69}507	^{133}2049 ± 0	^{111}622 ± 12	^{155}8356 ± 615	^{154}8134 ± 97
189	Zhuhai Yisheng Electronics Technology	yisheng	004	2018-06-12	486351	^{148}1279	^{175}3704 ± 0	^{56}378 ± 12	^{21}693 ± 137	^{9}526 ± 34
190	iQIYI Inc	iqface	000	2019-06-04	268819	^{91}704	^{189}4750 ± 32	^{84}538 ± 26	^{190}636433 ± 38446	^{189}632654 ± 85615
191	iQIYI Inc	iqface	001	2019-12-11	1145590	^{124}939	^{190}4752 ± 35	^{106}603 ± 1	^{189}634025 ± 5555	^{190}633845 ± 4950
192	iSAP Solution Corporation	isap	001	2019-08-07	99049	^{45}420	^{185}4096 ± 0	^{14}171 ± 12	^{159}12413 ± 154	^{160}12251 ± 382

Notes	
1	The configuration size does not capture static data included in libraries. We do not count these because some algorithms include common ancilliary libraries for image processing (e.g. openCV) or numerical computation (e.g. blas).
2	The memory usage is the peak resident set size reported by the ps system call during template generation.
3	The median template creation times are measured on Intel®Xeon®CPU E5-2630 v4 @ 2.20GHz processors or, for GPU-enabled implementations, NVidia Tesla K40.
4	The comparison durations, in nanoseconds, are estimated using std::chrono::high_resolution_clock which on the machine in (2) counts 1ns clock ticks. Precision is somewhat worse than that however. The ± value is the median absolute deviation times 1.48 for Normal consistency.

Table 5: Summary of algorithms and properties included in this report. The red superscripts give ranking for the quantity in that column.

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
1	3divi-003	0.0318	139	0.0588	138	0.0097	127	0.0389	142	0.0639	139	0.0619	135	0.0867	133	0.5365	35
2	3divi-004	0.0095	54	0.0153	57	0.0049	77	0.0097	58	0.0145	55	0.0175	64	0.0665	126	0.5025	27
3	acer-000	0.1393	160	0.9075	187	0.0650	163	0.9981	185	-		1.0000	181	0.9841	179	-	
4	adera-001	0.1021	157	0.1757	155	0.0368	157	0.1823	163	0.2967	161	0.1714	151	0.1965	152	0.7202	67
5	advance-002	0.0089	48	0.0137	49	0.0034	46	0.0073	29	0.0115	35	0.0400	117	0.0498	111	-	
6	aifirst-001	0.0119	74	0.0170	63	0.0067	103	0.0084	44	0.0127	42	0.0131	39	0.0432	98	0.4301	17
7	ailabs-001	0.0158	99	0.0276	107	0.0065	96	0.0192	117	0.0317	113	0.0352	112	0.0338	76	-	
8	aimall-001	0.0176	109	0.0324	116	0.0074	115	0.0225	124	0.0407	123	-		0.0344	79	0.6587	55
9	aiunionface-000	0.0104	61	0.0154	59	0.0051	80	0.0082	43	0.0122	40	0.0141	40	0.0306	52	-	
10	alchera-000	0.0165	104	0.0243	97	0.0086	120	0.0125	88	0.0186	82	0.0204	75	0.0370	86	-	
11	alchera-001	0.0183	110	0.0299	111	0.0078	116	0.0142	95	0.0234	99	0.0239	89	0.0372	87	-	
12	allgovision-000	0.0346	140	0.0527	134	0.0210	145	0.0232	126	0.0339	115	0.0372	115	0.0607	122	-	
13	alphaface-001	0.0065	27	0.0097	28	0.0025	33	0.0039	9	0.0063	12	0.0083	13	0.0280	10	-	
14	amplifiedgroup-001	0.5034	180	0.5848	179	0.2999	183	0.6973	178	0.8316	176	0.7807	172	0.4250	171	-	
15	anke-004	0.0080	42	0.0154	58	0.0031	40	0.0073	28	0.0112	33	0.0102	25	0.0288	27	0.3577	8
16	anke-005	0.0070	33	0.0109	38	0.0022	26	0.0059	21	0.0094	22	0.0105	26	0.0289	29	0.3337	6
17	antheus-000	0.2564	168	0.3776	169	0.1059	170	0.7240	179	0.8699	179	0.8899	176	0.7668	174	0.9233	91
18	anyvision-002	0.0660	151	0.0898	147	0.0387	158	0.0928	156	0.1512	153	0.0899	143	0.2227	156	0.6960	61
19	anyvision-004	0.0267	132	0.0385	128	0.0081	118	0.0258	132	0.0487	133	0.0234	86	0.0470	107	0.4633	21
20	asusaics-000	0.0125	79	0.0209	81	0.0043	60	0.0085	45	0.0134	47	0.0143	42	0.0295	36	-	
21	aware-003	0.0793	153	0.1161	153	0.0288	155	0.1028	157	0.1708	156	0.1698	150	0.3180	167	0.8512	81
22	aware-004	0.0690	152	0.0949	150	0.0257	150	0.0837	154	0.1436	152	0.1171	147	0.0516	113	-	
23	awiros-001	0.4044	173	0.4622	172	0.2880	182	0.5530	172	0.6518	170	0.2008	152	0.5584	173	-	
24	ayonix-000	0.4351	176	0.4872	173	0.2299	177	0.6150	175	0.7510	173	0.6557	168	0.3635	168	0.8434	79
25	bioidtechswiss-000	0.0066	29	0.0082	23	0.0015	13	0.0113	77	0.0225	94	0.0078	11	0.0278	6	-	
26	bm-001	0.7431	186	0.9494	188	0.6188	188	0.9586	183	0.9843	181	0.9049	177	0.9935	180	0.8845	86
27	camvi-002	0.0125	80	0.0221	86	0.0049	79	0.0089	50	0.0145	57	0.0142	41	0.0288	25	0.5760	43
28	camvi-004	0.0171	107	0.0316	115	0.0049	76	0.0042	10	0.0049	8	0.0097	23	0.0284	18	0.5788	45
29	ceiec-002	0.0161	102	0.0193	75	0.0124	136	0.0122	85	0.0164	70	0.0270	94	0.0465	106	0.5156	32
30	ceiec-003	0.0071	36	0.0107	36	0.0024	32	0.0061	23	0.0079	17	0.0160	49	0.0308	56	-	
31	chtface-001	0.9993	190	0.9994	191	0.9993	191	0.9999	187	-		1.0000	180	0.9980	181	-	
32	chtface-002	0.0150	94	0.0268	104	0.0054	84	0.0096	57	0.0140	51	0.0186	67	0.0306	53	-	
33	cib-000	0.0084	45	0.0156	60	0.0053	81	0.0049	12	0.0051	9	0.0275	97	0.0294	35	-	
34	cogent-003	0.0091	49	0.0188	72	0.0032	41	0.0098	60	0.0132	46	0.0187	68	0.0406	93	-	
35	cogent-004	0.0064	26	0.0116	40	0.0024	31	0.0096	55	0.0134	48	0.0157	46	0.0379	88	0.7177	66
36	cognitec-000	0.0116	70	0.0177	64	0.0036	49	0.0118	81	0.0167	72	0.0285	100	0.0953	137	0.8365	78
37	cognitec-001	0.0126	81	0.0185	71	0.0047	72	0.0120	83	0.0168	73	0.0270	93	0.0598	121	-	
38	ctbcbank-000	0.0168	105	0.0250	102	0.0064	94	0.0146	98	0.0224	93	0.0211	78	1.0000	188	0.8803	84
39	ctbcbank-001	0.0155	97	0.0235	94	0.0060	91	0.0148	102	0.0243	101	0.0207	76	1.0000	190	-	
40	cyberextruder-001	0.1972	164	0.2547	162	0.0755	165	0.4686	171	0.6387	169	0.3807	163	0.1747	149	0.7804	76
41	cyberextruder-002	0.0811	154	0.1336	154	0.0265	152	0.1465	161	0.2266	160	0.2086	155	0.1000	140	0.6105	49
42	cyberlink-002	0.0114	69	0.0195	76	0.0044	61	0.0101	64	0.0163	68	0.0160	50	0.0298	40	0.5003	26
43	cyberlink-003	0.0118	72	0.0192	74	0.0042	56	0.0098	61	0.0161	65	0.0153	45	0.0303	47	-	
44	dahua-003	0.0052	17	0.0068	15	0.0023	30	0.0056	17	0.0062	11	0.0113	31	0.0285	20	0.6253	51

Table 6: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA columns compare images described in section 2.2. The MUGSHOT columns compare images described in section 2.5. The VISA-BORDER column compare images described in section 2.3 with those described in section 2.4. The WILD columns compare images described in section 2.6. The CHILD-EXPLOITATION columns compare images described in section 2.1.

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
45	dahua-004	0.0045	14	0.0058	9	0.0019	22	0.0036	6	0.0048	7	0.0051	4	0.0281	12	-	
46	deepglint-001	0.0040	9	0.0062	13	0.0014	12	0.0047	11	0.0067	13	0.0069	8	0.0278	5	0.4006	12
47	deepglint-002	0.0016	2	0.0027	3	0.0004	2	0.0032	5	0.0033	2	0.0043	2	0.0280	9	0.3422	7
48	deepsea-001	0.0136	86	0.0215	83	0.0071	112	0.0142	96	0.0214	89	0.0163	54	0.0347	80	0.5606	40
49	dermalog-005	0.1526	162	0.1823	158	0.0658	164	0.2580	165	0.4018	163	-		0.0855	131	0.6842	58
50	dermalog-006	0.0253	130	0.0369	126	0.0172	142	0.0171	111	0.0283	108	0.0217	81	0.0623	124	0.5852	46
51	didiglobalface-001	0.0055	20	0.0092	25	0.0016	14	0.0030	2	0.0045	5	0.0088	16	0.0282	16	0.4270	15
52	digitalbarriers-002	0.3360	171	0.3690	167	0.0968	169	0.0877	155	0.1557	154	0.0971	146	0.0436	100	-	
53	dsk-000	0.1526	161	0.2169	159	0.0765	166	0.3787	168	0.5426	167	0.3115	158	0.2201	154	0.7313	69
54	einetworks-000	0.0099	57	0.0180	67	0.0047	71	0.0088	48	0.0140	53	0.0130	37	0.0293	33	-	
55	everai-paravision-003	0.0034	6	0.0050	7	0.0011	7	0.0036	8	0.0052	10	0.0092	19	0.0278	7	0.2669	2
56	expasoft-000	0.0427	144	0.0655	143	0.0233	149	0.0239	128	0.0393	121	0.0673	137	0.0565	119	-	
57	f8-001	0.0249	129	0.0336	118	0.0182	143	0.0178	114	0.0232	98	0.0303	107	0.0475	108	0.5272	33
58	facesoft-000	0.0085	46	0.0112	39	0.0032	43	0.0064	25	0.0107	28	0.0091	17	0.0275	3	0.4992	25
59	glory-001	0.0902	155	0.1082	152	0.0410	159	0.1642	162	0.2065	159	0.2186	156	0.4261	172	0.8831	85
60	glory-002	0.0241	123	0.0311	114	0.0188	144	0.0116	79	0.0151	60	0.0157	48	0.1265	144	-	
61	gorilla-003	0.0165	103	0.0291	109	0.0053	82	0.0205	121	0.0437	126	0.0297	105	0.0359	84	0.9756	94
62	gorilla-004	0.0138	87	0.0239	96	0.0049	78	0.0243	129	0.0444	127	0.0275	96	0.0287	24	-	
63	hik-001	0.0096	55	0.0125	44	0.0036	51	0.0093	53	0.0164	69	0.0108	28	0.0271	1	-	
64	hr-001	0.0044	13	0.0072	17	0.0019	20	0.0073	31	0.0108	31	0.0125	34	0.0303	46	0.5499	37
65	hr-002	0.0043	11	0.0059	10	0.0017	16	0.0054	13	0.0076	15	0.0076	10	0.0338	75	-	
66	id3-003	0.0361	141	0.0757	144	0.0104	134	0.0292	136	0.0476	130	0.0447	124	0.0848	130	0.5865	47
67	id3-004	0.0198	118	0.0344	121	0.0084	119	0.0238	127	0.0423	125	0.0289	102	-		-	
68	idemia-004	0.0160	101	0.0244	99	0.0065	97	0.0199	119	0.0354	117	0.0268	92	0.0309	57	-	
69	idemia-005	0.0132	82	0.0216	84	0.0057	88	0.0121	84	0.0218	92	0.0215	80	0.0294	34	0.4343	18
70	iit-001	0.0104	62	0.0179	66	0.0048	75	0.0099	63	0.0142	54	0.1222	148	0.3092	166	0.4836	23
71	iit-002	0.0111	67	0.0177	65	0.0054	83	0.0085	46	0.0140	52	0.0193	72	0.1373	145	-	
72	imagus-000	0.0642	149	0.0882	145	0.0330	156	0.0497	145	0.0905	143	0.0848	141	0.1158	142	0.6936	60
73	imagus-001	0.0245	126	0.0407	129	0.0091	123	0.0257	131	0.0497	135	0.0514	128	0.0971	138	-	
74	imperial-000	0.0067	31	0.0108	37	0.0022	27	0.0080	39	0.0134	49	0.0087	15	0.0281	13	-	
75	imperial-002	0.0058	22	0.0081	21	0.0027	34	0.0055	15	0.0085	19	0.0083	14	0.0273	2	0.5151	29
76	incode-004	0.0077	41	0.0132	47	0.0034	47	0.0096	56	0.0160	63	0.0171	61	0.0313	59	0.5102	28
77	incode-005	0.0111	68	0.0189	73	0.0042	57	0.0156	108	0.0304	111	0.0195	73	0.0562	118	-	
78	innovativetechnologyltd-001	0.0578	147	0.0938	149	0.0258	151	0.0501	147	0.0981	145	-		0.0449	102	-	
79	innovatrics-004	0.0194	114	0.0292	110	0.0068	105	0.0344	139	0.0617	138	0.0562	132	0.0454	105	0.4650	22
80	innovatrics-006	0.0058	23	0.0089	24	0.0021	24	0.0061	24	0.0096	25	0.0096	22	0.0281	11	0.3056	4
81	intellicloudai-001	0.0142	89	0.0234	93	0.0064	95	0.0092	52	0.0145	56	0.0162	52	0.0409	94	-	
82	intellifusion-001	0.0072	37	0.0094	26	0.0028	38	0.0056	18	0.0085	20	0.0111	30	0.0289	28	0.5454	36
83	intellivision-001	0.1335	159	0.2205	160	0.0417	160	0.1090	159	0.1670	155	0.1385	149	0.2445	158	0.7766	75
84	intellivision-002	0.1000	156	0.1775	156	0.0265	153	0.0610	150	0.1009	146	0.0805	140	0.0768	129	-	
85	intelresearch-000	0.0307	136	0.0578	137	0.0093	124	0.0385	141	0.0751	142	0.0409	118	0.0324	64	-	
86	intelresearch-001	0.0242	124	0.0595	140	0.0097	126	0.0129	92	0.0292	110	0.0351	111	0.0919	136	-	
87	intsysmsu-000	0.0135	84	0.0204	78	0.0069	107	0.0112	74	0.0161	64	0.0148	43	0.2330	157	-	
88	intsysmsu-001	0.9543	189	0.9888	190	0.9165	190	0.9923	184	-		0.9977	178	0.7871	175	-	

Table 7: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA *columns compare images described in section 2.2. The* MUGSHOT *columns compare images described in section 2.5. The* VISA-BORDER *column compare images described in section 2.3 with those described in section 2.4. The* WILD *columns compare images described in section 2.6. The* CHILD-EXPLOITATION *columns compare images described in section 2.1.*

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
89	iqface-000	0.0091	51	0.0143	52	0.0043	59	0.0075	34	0.0110	32	0.0171	62	0.0381	89	0.6490	53
90	iqface-001	0.0088	47	0.0117	41	0.0047	70	0.0177	112	0.0230	97	0.0165	57	0.0597	120	-	
91	isap-001	0.5092	181	0.6588	181	0.2338	179	0.6899	177	0.7978	174	0.7200	169	0.1931	151	-	
92	isityou-000	0.5682	183	0.7033	183	0.4145	186	1.0000	188	-		1.0000	184	1.0000	184	1.0000	97
93	isystems-001	0.0149	93	0.0245	100	0.0067	102	0.0138	94	0.0210	88	0.0209	77	0.0524	116	0.5152	31
94	isystems-002	0.0118	71	0.0182	69	0.0066	98	0.0111	71	0.0162	66	0.0166	58	0.0516	114	0.4876	24
95	itmo-006	0.0125	78	0.0220	85	0.0046	66	0.0149	103	0.0266	107	0.0233	84	0.0329	69	-	
96	itmo-007	0.0080	43	0.0125	45	0.0033	44	0.0107	67	0.0185	80	0.0167	59	0.0300	43	-	
97	kakao-001	0.4553	178	0.5532	178	0.2034	175	0.6580	176	0.8150	175	0.4831	165	1.0000	192	-	
98	kakao-002	0.0625	148	0.1779	157	0.0168	141	0.0791	153	0.1381	151	0.0636	136	1.0000	186	1.0000	104
99	kedacom-000	0.0055	19	0.0081	22	0.0027	35	0.0111	73	0.0120	38	0.0415	119	0.2511	160	0.7650	73
100	kneron-003	0.0542	145	0.0902	148	0.0218	147	0.0346	140	0.0562	137	0.0919	144	0.3053	165	0.6962	62
101	kneron-004	0.0197	115	0.0283	108	0.0101	131	0.0129	91	0.0201	85	0.0452	125	0.0670	127	-	
102	lookman-002	0.0297	134	0.0547	136	0.0102	133	0.0339	138	0.0562	136	0.0614	134	0.2640	163	-	
103	lookman-004	0.0074	39	0.0099	30	0.0037	52	0.0124	87	0.0149	58	0.0430	122	0.2516	161	0.7664	74
104	luxand-000	0.2056	166	0.2814	163	0.0895	168	0.4053	169	0.5365	166	0.3497	160	0.2222	155	-	
105	megvii-001	0.0157	98	0.0244	98	0.0045	65	0.0392	143	0.0671	140	0.0168	60	0.0916	135	0.4418	19
106	megvii-002	0.0104	63	0.0145	54	0.0036	50	0.0225	123	0.0345	116	0.0099	24	0.0692	128	0.3013	3
107	meiya-001	0.0171	106	0.0275	106	0.0066	100	0.0159	109	0.0261	106	0.0311	108	0.0363	85	-	
108	microfocus-001	0.4482	177	0.5524	177	0.2309	178	0.7256	180	0.8416	177	0.7301	170	0.2567	162	0.6890	59
109	microfocus-002	0.3605	172	0.5057	174	0.1566	173	0.5783	173	0.7223	171	0.5909	167	0.1582	148	0.6517	54
110	mt-000	0.0100	58	0.0170	62	0.0047	69	0.0074	33	0.0118	37	0.0127	35	0.0326	67	0.3773	11
111	mvision-001	0.0191	112	0.0233	91	0.0131	137	0.0204	120	0.0356	118	0.0198	74	0.0431	97	-	
112	netbridgetech-001	0.4749	179	0.6599	182	0.1800	174	0.4438	170	0.5676	168	0.4491	164	0.1098	141	-	
113	neurotechnology-006	0.0098	56	0.0136	48	0.0040	55	0.0105	66	0.0182	78	0.0164	55	0.0303	48	0.5911	48
114	neurotechnology-008	0.0091	50	0.0184	70	0.0023	28	0.0076	36	0.0116	36	0.0157	47	0.0301	45	-	
115	nodeflux-001	1.0000	192	1.0000	192	1.0000	192	1.0000	192	-		0.5169	166	1.0000	191	-	
116	nodeflux-002	0.0186	111	0.0340	119	0.0070	109	0.0261	133	0.0451	129	0.0548	131	0.0299	42	-	
117	notiontag-000	0.6669	184	0.7885	184	0.3222	185	0.3715	167	0.4978	165	0.8571	174	0.1807	150	0.6479	52
118	ntechlab-007	0.0056	21	0.0076	18	0.0018	18	0.0073	32	0.0128	44	0.0079	12	0.0276	4	0.3316	5
119	ntechlab-008	0.0041	10	0.0061	11	0.0011	6	0.0056	16	0.0108	29	0.0042	1	0.0289	31	-	
120	pa-004	0.0375	142	0.0514	132	0.0156	140	0.0501	146	0.0918	144	0.0526	130	0.0343	78	-	
121	paravision-004	0.0030	5	0.0046	5	0.0012	8	0.0030	3	0.0036	3	0.0091	18	0.0288	26	0.2467	1
122	pixelall-002	0.0193	113	0.0340	120	0.0066	99	0.0127	90	0.0209	86	0.0234	87	0.0342	77	0.8963	88
123	pixelall-003	0.0074	40	0.0118	42	0.0032	42	0.0057	19	0.0079	16	0.0121	33	0.0285	22	-	
124	psl-002	0.0107	65	0.0180	68	0.0048	74	0.0089	49	0.0120	39	0.0790	139	0.0295	37	-	
125	psl-003	0.0065	28	0.0099	31	0.0028	36	0.0055	14	0.0075	14	1.0000	183	0.0296	39	-	
126	pyramid-000	0.0136	85	0.0233	92	0.0056	86	0.0117	80	0.0192	84	0.0185	66	0.0304	49	-	
127	rankone-007	0.0197	117	0.0366	125	0.0057	89	0.0113	76	0.0177	76	0.0286	101	0.0450	103	0.6686	56
128	rankone-008	0.0124	76	0.0232	90	0.0045	64	0.0082	42	0.0107	27	0.0188	70	0.0420	95	-	
129	realnetworks-002	0.0248	127	0.0358	122	0.0099	129	0.0513	148	0.1127	147	0.0371	114	0.0334	71	-	
130	realnetworks-003	0.0259	131	0.0372	127	0.0100	130	0.0541	149	0.1208	149	0.0378	116	0.0335	73	0.5152	30
131	remarkai-001	0.0144	90	0.0256	103	0.0061	92	0.0102	65	0.0159	62	0.0162	53	0.0308	55	-	
132	remarkai-002	0.0151	96	0.0197	77	0.0102	132	0.0075	35	0.0108	30	0.0119	32	0.0426	96	-	

Table 8: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA *columns compare images described in section 2.2. The* MUGSHOT *columns compare images described in section 2.5. The* VISA-BORDER *column compare images described in section 2.3 with those described in section 2.4. The* WILD *columns compare images described in section 2.6. The* CHILD-EXPLOITATION *columns compare images described in section 2.1.*

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
133	rokid-000	0.0093	53	0.0145	53	0.0038	53	0.0073	30	0.0102	26	0.0164	56	0.0857	132	-	
134	rokid-001	0.0105	64	0.0162	61	0.0042	58	0.0094	54	0.0163	67	0.0181	65	0.0325	65	-	
135	s1-001	0.0314	138	0.0651	142	0.0099	128	0.0252	130	0.0357	119	0.0444	123	0.8493	176	-	
136	saffe-001	0.4339	175	0.5261	175	0.2340	180	0.7539	182	0.8736	180	0.7977	173	0.3887	169	0.8973	89
137	saffe-002	0.0119	75	0.0206	79	0.0054	85	0.0107	69	0.0177	75	0.0244	90	0.0308	54	-	
138	samtech-001	0.0197	116	0.0365	123	0.0066	101	0.0146	100	0.0241	100	0.0238	88	0.0337	74	-	
139	scanovate-001	0.0175	108	0.0331	117	0.0061	93	0.0163	110	0.0248	102	0.2476	157	0.4060	170	-	
140	sensetime-002	0.0068	32	0.0098	29	0.0035	48	0.0143	97	-		0.0278	99	0.9999	182	0.5309	34
141	sensetime-003	0.0021	3	0.0027	2	0.0005	3	0.0027	1	0.0027	1	0.0051	5	0.0329	68	0.3683	9
142	sertis-000	0.0118	73	0.0208	80	0.0047	67	0.0080	38	0.0127	41	0.0110	29	0.0285	21	-	
143	shaman-000	0.9297	188	0.9774	189	0.9128	189	0.9990	186	-		0.9999	179	0.9575	178	0.9618	92
144	shaman-001	0.3346	170	0.4616	171	0.1360	172	0.2368	164	0.3723	162	0.3574	161	0.1498	147	0.8990	90
145	shu-001	0.0103	60	0.0140	51	0.0044	62	0.0293	137	0.0688	141	0.0172	63	0.0986	139	0.4590	20
146	shu-002	-		0.0079	19	0.0017	17	0.0146	99	0.0308	112	1.0000	182	0.0284	19	-	
147	siat-002	0.0091	52	0.0126	46	0.0039	54	0.0109	70	0.0190	83	0.0276	98	0.0520	115	0.4277	16
148	siat-004	0.0067	30	0.0099	32	0.0028	37	0.0152	105	-		0.0275	95	1.0000	183	-	
149	sjtu-001	0.0051	16	0.0080	20	0.0019	19	0.0211	122	0.0446	128	0.0131	38	0.0289	30	-	
150	smilart-002	0.2440	167	0.3532	166	0.0821	167	-		-		0.3785	162	-		0.6999	63
151	smilart-003	0.6944	185	0.8836	185	0.1088	171	0.0695	151	0.1193	148	0.0894	142	0.1190	143	-	
152	starhybrid-001	0.0108	66	0.0138	50	0.0058	90	0.0081	40	0.0113	34	0.0152	44	0.0350	82	0.5584	38
153	synesis-005	0.0147	91	0.0226	88	0.0073	114	0.0153	106	0.0226	95	0.0213	79	0.0334	72	0.5601	39
154	synesis-006	0.0070	34	0.0096	27	0.0023	29	0.0107	68	0.0166	71	-		0.0292	32	-	
155	synology-000	0.0149	92	0.0238	95	0.0067	104	0.0148	101	0.0261	105	0.0221	82	0.0330	70	-	
156	tech5-002	0.0046	15	0.0063	14	0.0009	5	0.0113	78	0.0216	91	0.0233	85	0.0310	58	-	
157	tech5-003	0.0053	18	0.0070	16	0.0014	11	0.0099	62	0.0185	79	0.0095	21	0.0306	50	0.8963	87
158	tevian-004	0.0228	121	0.0304	112	0.0069	106	0.0226	125	0.0478	131	0.0128	36	0.0394	91	-	
159	tevian-005	0.0043	12	0.0062	12	0.0020	23	0.0057	20	0.0085	21	0.0070	9	0.0300	44	0.5625	42
160	tiger-002	0.0658	150	0.0889	146	0.0227	148	0.1083	158	0.1766	157	0.0952	145	0.0512	112	0.7862	77
161	tiger-003	0.0313	137	0.0602	141	0.0087	121	0.0188	116	0.0359	120	0.0344	109	0.0482	110	0.5610	41
162	tongyi-005	0.0073	38	0.0146	55	0.0019	21	0.0187	115	0.0421	124	0.0161	51	0.0399	92	0.6195	50
163	toshiba-002	0.0134	83	0.0222	87	0.0048	73	0.0097	59	0.0154	61	-		0.0434	99	0.7103	64
164	toshiba-003	0.0125	77	0.0214	82	0.0047	68	0.0085	47	0.0131	45	-		0.0282	14	-	
165	trueface-000	0.0249	128	0.4321	170	0.0069	108	0.0119	82	0.0180	77	0.0297	106	0.0614	123	-	
166	tuputech-000	0.3218	169	0.3696	168	0.2779	181	-		-		0.3237	159	0.9415	177	-	
167	ulsee-001	0.0151	95	0.0246	101	0.0080	117	0.0113	75	0.0185	81	0.0187	69	0.0316	61	-	
168	uluface-002	0.0081	44	0.0123	43	0.0033	45	0.0071	27	0.0095	24	0.0107	27	0.0444	101	0.6729	57
169	uluface-003	0.0100	59	0.0150	56	0.0044	63	0.0079	37	0.0128	43	-		0.0635	125	-	
170	upc-001	0.0234	122	0.0519	133	0.0071	111	0.0291	135	0.0490	134	0.0294	103	0.0314	60	0.4224	14
171	vcog-002	0.7522	187	0.9033	186	0.5040	187	-		-		-		-		0.7523	71
172	vd-001	0.0243	125	0.0452	131	0.0093	125	0.0271	134	0.0402	122	0.0424	121	0.1389	146	-	
173	veridas-002	0.1733	163	0.2257	161	0.0528	162	0.2617	166	0.4147	164	0.2073	154	0.0450	104	-	
174	veridas-003	0.0557	146	0.0983	151	0.0154	139	0.0734	152	0.1267	150	0.0694	138	0.0299	41	0.5785	44
175	via-000	0.0216	120	0.0365	124	0.0088	122	0.0177	113	0.0287	109	0.0296	104	0.0349	81	0.7638	72
176	videmo-000	0.0298	135	0.0423	130	0.0211	146	0.0155	107	0.0260	104	0.0246	91	0.0541	117	-	

Table 9: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA *columns compare images described in section 2.2. The* MUGSHOT *columns compare images described in section 2.5. The* VISA-BORDER *column compare images described in section 2.3 with those described in section 2.4. The* WILD *columns compare images described in section 2.6. The* CHILD-EXPLOITATION *columns compare images described in section 2.1.*

		FALSE NON-MATCH RATE (FNMR)															
	Algorithm	CONSTRAINED, COOPERATIVE												LESS CONSTRAINED, NON-COOP.			
	Name	VISAMC		VISA		VISA		MUGSHOT		MUGSHOT12+YRS		VISABORDER		WILD		CHILDEXP	
	FMR	0.0001		1E-06		0.0001		1E-05		1E-05		1E-06		0.0001		0.01	
177	videonetics-001	0.5483	182	0.6446	180	0.3063	184	0.7517	181	0.8607	178	0.8664	175	0.2986	164	0.7297	68
178	videonetics-002	0.4274	174	0.5329	176	0.2168	176	0.6081	174	0.7438	172	0.7775	171	0.1976	153	0.7435	70
179	vigilantsolutions-006	0.1264	158	0.3221	164	0.0136	138	0.0150	104	0.0254	103	0.0493	127	0.0321	63	-	
180	vigilantsolutions-007	0.0202	119	0.0307	113	0.0070	110	0.0136	93	0.0227	96	0.0356	113	0.0306	51	1.0000	178
181	vion-000	0.0419	143	0.0590	139	0.0288	154	0.0422	144	0.0478	132	0.0581	133	0.2479	159	0.8765	83
182	visionbox-000	0.0293	133	0.0541	135	0.0110	135	0.0197	118	0.0339	114	0.0349	110	0.0476	109	-	
183	visionbox-001	0.0159	100	0.0270	105	0.0072	113	0.0111	72	0.0173	74	0.0190	71	0.0389	90	-	
184	visionlabs-007	0.0038	7	0.0048	6	0.0012	10	0.0036	7	0.0048	6	0.0057	6	0.0286	23	0.3708	10
185	visionlabs-008	0.0026	4	0.0036	4	0.0007	4	0.0031	4	0.0040	4	0.0045	3	0.0282	17	-	
186	vocord-006	0.0062	24	0.0102	34	0.0016	15	0.0082	41	0.0151	59	0.0475	126	0.0282	15	-	
187	vocord-007	0.0039	8	0.0053	8	0.0012	9	0.0061	22	0.0094	23	0.0520	129	0.0280	8	0.8468	80
188	winsense-000	0.0140	88	0.0228	89	0.0056	87	0.0125	89	0.0215	90	0.0226	83	0.0352	83	0.8600	82
189	winsense-001	0.0062	25	0.0099	33	0.0022	25	0.0092	51	0.0210	87	0.0093	20	0.0320	62	0.4155	13
190	x-laboratory-000	0.0071	35	0.0106	35	0.0030	39	0.0123	86	0.0138	50	0.0419	120	0.0295	38	0.9686	93
191	yisheng-004	0.1988	165	0.3329	165	0.0475	161	0.1147	160	0.1849	158	0.2044	153	0.0908	134	0.7152	65
192	yitu-003	0.0015	1	0.0026	1	0.0003	1	0.0066	26	0.0085	18	0.0064	7	0.0325	66	-	

Table 10: FNMR is the proportion of mated comparisons below a threshold set to achieve the FMR given in the header on the fourth row. FMR is the proportion of impostor comparisons at or above that threshold. The light grey values give rank over all algorithms in that column. The pink columns use only same-sex impostors; others are selected regardless of demographics. The exception, in the green column, uses "matched-covariates" i.e. impostors of the same sex, age group, and country of birth. The second pink column includes effects of extended ageing. Missing entries for border, visa, mugshot and wild images generally mean the algorithm did not run to completion. For child exploitation, missing entries arise because NIST executes those runs only infrequently. The VISA columns compare images described in section 2.2. The MUGSHOT columns compare images described in section 2.5. The VISA-BORDER column compare images described in section 2.3 with those described in section 2.4. The WILD columns compare images described in section 2.6. The CHILD-EXPLOITATION columns compare images described in section 2.1.

Figure 1: The points show false non-match rates (FNMR) versus the size of the encoded template. FNMR is the geometric mean of FNMR values for visa and mugshot images (from Figs. 31 and 41) at a false match rate (FMR) of 0.0001. The color of the points encodes template generation time - which spans at least one order of magnitude. Durations are measured on a single core of a c. 2016 Intel Xeon CPU E5-2630 v4 running at 2.20GHz. Algorithms with poor FNMR are omitted.

Figure 2: The points show false non-match rates (FNMR) versus the duration of the template generation operation. FNMR is the geometric mean of FNMR values for visa and mugshot images (from Figs. 31 and 41) at a false match rate (FMR) of 0.0001. Template generation time is a median estimated over 640 x 480 pixel portraits. It is measured on a single core of a c. 2016 Intel Xeon CPU E5-2630 v4 running at 2.20GHz. The color of the points encodes template size - which span two orders of magnitude. Algorithms with poor FNMR are omitted.

1 Metrics

1.1 Core accuracy

Given a vector of N genuine scores, u, the false non-match rate (FNMR) is computed as the proportion below some threshold, T:

$$\text{FNMR}(T) = 1 - \frac{1}{N}\sum_{i=1}^{N} H(u_i - T) \tag{1}$$

where $H(x)$ is the unit step function, and $H(0)$ taken to be 1.

Similarly, given a vector of N impostor scores, v, the false match rate (FMR) is computed as the proportion above T:

$$\text{FMR}(T) = \frac{1}{N}\sum_{i=1}^{N} H(v_i - T) \tag{2}$$

The threshold, T, can take on any value. We typically generate a set of thresholds from quantiles of the observed impostor scores, v, as follows. Given some interesting false match rate range, $[\text{FMR}_L, \text{FMR}_U]$, we form a vector of K thresholds corresponding to FMR measurements evenly spaced on a logarithmic scale

$$T_k = Q_v(1 - \text{FMR}_k) \tag{3}$$

where Q is the quantile function, and FMR_k comes from

$$\log_{10}\text{FMR}_k = \log_{10}\text{FMR}_L + \frac{k}{K}\,[\log_{10}\text{FMR}_U - \log_{10}\text{FMR}_L] \tag{4}$$

Error tradeoff characteristics are plots of FNMR(T) vs. FMR(T). These are plotted with $\text{FMR}_U \to 1$ and FMR_L as low as is sustained by the number of impostor comparisons, N. This is somewhat higher than the "rule of three" limit $3/N$ because samples are not independent, due to re-use of images.

2 Datasets

2.1 Child exploitation images

- ▷ The number of images is on the order of 10^4.
- ▷ The number of subjects is on the order of 10^3.
- ▷ The number of subjects with two images on the order of 10^3.
- ▷ The images are operational. They are taken from ongoing investigations of child exploitation crimes. The images are arbitrarily unconstrained. Pose varies considerably around all three axes, including subject lying down. Resolution varies very widely. Faces can be occluded by other objects, including hair and hands. Lighting varies, although the images are intended for human viewing. Mis-focus is rare. Images are given to the algorithm without any cropping; faces may occupy widely varying areas.
- ▷ The images are usually large from contemporary cameras. The mean interocular distance (IOD) is 70 pixels.
- ▷ The images are of subjects from several countries, due to the global production of this imagery.
- ▷ The images are of children, from infancy to late adolescence.
- ▷ All of the images are live capture, none are scanned. Many have been cropped.
- ▷ When these images are input to the algorithm, they are labelled as being of type ”EXPLOITATION” - see Table 4 of the FRVT API.

2.2 Visa images

- ▷ The number of images is on the order of 10^5.
- ▷ The number of subjects is on the order of 10^5.
- ▷ The number of subjects with two images is on the order of 10^4.
- ▷ The images have geometry in reasonable conformance with the ISO/IEC 19794-5 Full Frontal image type. Pose is generally excellent.
- ▷ The images are of size 252x300 pixels. The mean interocular distance (IOD) is 69 pixels.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to visa issuance patterns.
- ▷ The images are of subjects of all ages, including children, again with imbalance due to visa issuance demand.
- ▷ Many of the images are live capture. A substantial number of the images are photographs of paper photographs.
- ▷ When these images are input to the algorithm, they are labelled as being of type ”ISO” - see Table 4 of the FRVT API.

2.3 Application images

- ▷ The number of images is on the order of 10^6.
- ▷ The number of subjects is on the order of 10^6.
- ▷ The number of subjects with two images is on the order of 10^6.

- ▷ The images have geometry in good conformance with the ISO/IEC 19794-5 Full Frontal image type. Pose is generally excellent.
- ▷ The images are of size 300x300 pixels. The mean interocular distance (IOD) is 61 pixels.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to population and immigration patterns.
- ▷ The images are of subjects of adults with imbalance due due to population and immigration patterns and demand.
- ▷ All of the images are live capture.
- ▷ When these images are input to the algorithm, they are labelled as being of type "ISO" - see Table 4 of the FRVT API.

2.4 Border crossing images

- ▷ The number of images is on the order of 10^6.
- ▷ The number of subjects is on the order of 10^6.
- ▷ The number of subjects with two images is on the order of 10^6.
- ▷ The images are taken with at camera oriented by an attendant toward a cooperating subject. This is done under time constraints so there are role, pitch and yaw angle variations. Also background illumination is sometimes strong, so the face is under-exposed. There is some perspective distortion due to close range images. Some faces are partially cropped.
- ▷ The images are of subjects from greater than 100 countries, with significant imbalance due to population and immigration patterns.
- ▷ The images are of subjects of adults with imbalance due due to population and immigration patterns and demand.
- ▷ The images have mean IOD of 38 pixels.
- ▷ The images are all live capture.
- ▷ When these images are input to the algorithm, they are labelled as being of type "WILD" - see Table 4 of the FRVT API.

2.5 Mugshot images

- ▷ The number of images is on the order of 10^6.
- ▷ The number of subjects is on the order of 10^6.
- ▷ The number of subjects with two images is on the order of 10^6.
- ▷ The images have geometry in reasonable conformance with the ISO/IEC 19794-5 Full Frontal image type.
- ▷ The images are of variable sizes. The median IOD is 105 pixels. The mean IOD is 113 pixels. The 1-st, 5-th, 10-th, 25-th, 75-th, 90-th and 99-th percentiles are 34, 58, 70, 87, 121, 161 and 297 pixels.
- ▷ The images are of subjects from the United States.
- ▷ The images are of adults.
- ▷ The images are all live capture.
- ▷ When these images are input to the algorithm, they are labelled as being of type "mugshot" - see Table 4 of the FRVT API.

(a) Visa (b) Mugshot (c) Wild (d) Border (from VisaBorder)

Figure 3: The figure gives simulated samples of image types used in this report.

2.6 Wild images

- ▷ The number of images is on the order of 10^5.
- ▷ The number of subjects is on the order of 10^3.
- ▷ The number of subjects with two images on the order of 10^3.
- ▷ The images include many photojournalism-style images. Images are given to the algorithm using a variable but generally tight crop of the head. Resolution varies very widely. The images are very unconstrained, with wide yaw and pitch pose variation. Faces can be occluded, including hair and hands.
- ▷ The images are of adults.
- ▷ All of the images are live capture, none are scanned.
- ▷ When these images are input to the algorithm, they are labelled as being of type "WILD" - see Table 4 of the FRVT API.

3 Results

3.1 Test goals

- ▷ To state overall accuracy.
- ▷ To compare algorithms.

3.2 Test design

Method: For visa images:

- ▷ The comparisons are of visa photos against visa photos.
- ▷ The number of genuine comparisons is on the order of 10^4.
- ▷ The number of impostor comparisons is on the order of 10^{10}.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates. However, later analysis is conducted on subsets.
- ▷ The number of persons is on the order of 10^5.
- ▷ The number of images used to make 1 template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

For mugshot images:

- ▷ The comparisons are of mugshot photos against mugshot photos.
- ▷ The number of genuine comparisons is on the order of 10^6.
- ▷ The number of impostor comparisons is on the order of 10^8.
- ▷ The impostors are paired by sex, but not by age or other covariates.
- ▷ The number of persons is on the order of 10^6.
- ▷ The number of images used to make 1 template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

Method: For wild images:

- ▷ The comparisons are of wild photos against wild photos.
- ▷ The number of genuine comparisons is on the order of 10^6.
- ▷ The number of impostor comparisons is on the order of 10^7.
- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates.
- ▷ The number of persons is on the order of 10^4.
- ▷ The number of images used to make 1 template is 1.
- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.

For child exploitation images:

- ▷ The comparisons are of unconstrained child exploitation photos against others of the same type.
- ▷ The number of genuine comparisons is on the order of 10^4.
- ▷ The number of impostor comparisons is on the order of 10^7.
- ▷ The comparisons are fully zero-effort, meaning impostors are paired without attention to sex, age or other covariates.
- ▷ The number of persons is on the order of 10^3.
- ▷ The number of images used to make 1 template is 1.

- ▷ The number of templates used to make each comparison score is two corresponding to simple one-to-one verification.
- ▷ We produce two performance statements. First, is a DET as used for visa and mugshot images. The second is a cumulative match characteristic (CMC) summarizing a simulated one-to-many search process. This is done as follows.
  - We regard M enrollment templates as items in a gallery.
  - These M templates come from $M > N$ individuals, because multiple images of a subject are present in the gallery under separate identifiers.
  - We regard the verification templates as search templates.
  - For each search we compute the rank of the highest scoring mate.
  - This process should properly be conducted with a 1:N algorithm, such as those tested in NIST IR 8009. We use the 1:1 algorithms in a simulated 1:N mode here to a) better reflect what a child exploitation analyst does, and b) to show algorithm efficacy is better than that revealed in the verification DETs.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3.3 Failure to enroll

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
1	3divi-003	0.1806	70	0.0007	145	0.0006	137	0.0294	160
2	3divi-004	0.2302	81	0.0008	149	0.0006	139	0.0222	157
3	acer-000	-	192	0.0002	100	0.0004	113	0.0008	95
4	adera-001	0.1928	74	0.0003	114	0.0005	131	0.0505	173
5	advance-002	-	192	0.0000	61	0.0004	98	0.0009	104
6	aifirst-001	0.0000	4	0.0000	2	0.0000	2	0.0000	41
7	ailabs-001	-	192	0.0007	148	0.0005	121	0.0016	115
8	aimall-001	0.0000	20	0.0000	18	0.0000	19	0.0001	49
9	aiunionface-000	-	192	0.0000	25	0.0000	27	0.0000	44
10	alchera-000	-	192	0.0004	129	0.0014	172	0.0038	125
11	alchera-001	-	192	0.0004	128	0.0014	171	0.0038	124
12	allgovision-000	-	192	0.0026	179	0.0052	188	0.0131	145
13	alphaface-001	-	192	0.0000	64	0.0004	106	0.0004	68
14	amplifiedgroup-001	-	192	0.0189	191	0.0279	194	0.1390	187
15	anke-004	0.0944	55	0.0001	82	0.0004	107	0.0006	88
16	anke-005	0.1228	62	0.0001	92	0.0004	112	0.0007	90
17	antheus-000	0.0000	18	0.0000	42	0.0000	46	0.0242	158
18	anyvision-002	0.4866	99	0.0070	188	0.0090	191	0.1146	183
19	anyvision-004	0.1660	67	0.0001	91	0.0004	96	0.0080	135
20	asusaics-000	-	192	0.0000	20	0.0000	21	0.0000	15
21	aware-003	0.3314	91	0.0016	173	0.0013	168	0.0745	180
22	aware-004	-	192	0.0002	98	0.0005	119	0.0014	113
23	awiros-001	-	192	0.0386	192	0.0872	195	0.3415	191
24	ayonix-000	0.0000	3	0.0113	189	0.0137	193	0.1194	184
25	bioidtechswiss-000	-	192	0.0003	113	0.0004	115	0.0006	84
26	bm-001	0.0000	22	0.0000	49	0.0000	22	0.0000	16
27	camvi-002	0.0000	5	0.0000	31	0.0000	33	0.0000	25
28	camvi-004	0.0000	10	0.0000	35	0.0000	38	0.0000	30
29	ceiec-002	0.2482	85	0.0036	183	0.0031	184	0.0081	136
30	ceiec-003	-	192	0.0001	70	0.0004	103	0.0004	65
31	chtface-001	-	192	0.0000	38	0.0000	41	0.0000	33
32	chtface-002	-	192	0.0002	110	0.0007	143	0.0014	111
33	cib-000	-	192	0.0001	93	0.0000	35	0.0000	27
34	cogent-003	-	192	0.0001	77	0.0004	93	0.0009	106
35	cogent-004	0.0000	7	0.0000	4	0.0000	4	0.0000	2
36	cognitec-000	0.6342	103	0.0007	146	0.0007	147	0.0388	168
37	cognitec-001	-	192	0.0008	153	0.0010	151	0.0185	152
38	ctbcbank-000	0.3285	90	0.0011	161	0.0019	176	0.0868	182
39	ctbcbank-001	-	192	0.0005	139	0.0010	152	0.0844	181
40	cyberextruder-001	0.5338	101	0.0024	177	0.0029	182	0.0597	177
41	cyberextruder-002	0.2672	88	0.0027	180	0.0028	181	0.0335	165
42	cyberlink-002	0.1463	66	0.0004	122	0.0004	118	0.0007	92
43	cyberlink-003	-	192	0.0001	67	0.0004	80	0.0008	97
44	dahua-003	0.2222	80	0.0002	105	0.0003	60	0.0002	53
45	dahua-004	-	192	0.0001	90	0.0003	56	0.0002	54
46	deepglint-001	0.0000	23	0.0000	21	0.0000	23	0.0000	17
47	deepglint-002	0.0669	49	0.0002	106	0.0004	82	0.0003	59
48	deepsea-001	0.0000	11	0.0000	8	0.0000	8	0.0000	6
49	dermalog-005	0.1796	68	0.0013	167	0.0041	185	0.0163	150
50	dermalog-006	0.1797	69	0.0013	166	0.0041	186	0.0163	151
51	didiglobalface-001	0.2175	77	0.0000	63	0.0004	105	0.0004	67
52	digitalbarriers-002	-	192	0.0028	181	0.0027	180	0.0071	134
53	dsk-000	0.0000	17	0.0000	14	0.0000	14	0.0000	11
54	einetworks-000	-	192	0.0002	103	0.0005	129	0.0008	98
55	everai-paravision-003	0.0705	51	0.0002	97	0.0004	81	0.0004	75
56	expasoft-000	-	192	0.0000	45	0.0000	49	0.0000	38
57	f8-001	0.2026	76	0.0035	182	0.0030	183	0.0087	139
58	facesoft-000	0.0000	29	0.0000	47	0.0000	51	0.0000	39
59	glory-001	0.0000	14	0.0051	186	0.0010	154	0.1651	188
60	glory-002	-	192	0.0015	169	0.0011	164	0.0557	175

Table 11: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
61	gorilla-003	0.1347	63	0.0003	121	0.0004	117	0.0043	128
62	gorilla-004	-	192	0.0000	52	0.0003	64	0.0004	72
63	hik-001	-	192	0.0000	37	0.0000	40	0.0000	32
64	hr-001	0.1198	61	0.0001	66	0.0004	85	0.0003	62
65	hr-002	-	192	0.0002	102	0.0004	108	0.0004	66
66	id3-003	0.3032	89	0.0016	174	0.0011	163	0.0317	163
67	id3-004	-	192	0.0015	172	0.0011	162	-	192
68	idemia-004	-	192	0.0000	54	0.0004	77	0.0003	63
69	idemia-005	0.0239	34	0.0000	51	0.0003	66	0.0003	58
70	iit-001	0.0843	54	0.0001	95	0.0004	100	0.0104	140
71	iit-002	-	192	0.0009	156	0.0005	134	0.0443	171
72	imagus-000	0.1107	59	0.0010	160	0.0012	166	0.0347	166
73	imagus-001	-	192	0.0001	83	0.0004	101	0.0396	169
74	imperial-000	-	192	0.0000	24	0.0000	26	0.0000	20
75	imperial-002	0.0000	9	0.0000	7	0.0000	7	0.0000	5
76	incode-004	0.2202	78	0.0004	133	0.0007	141	0.0014	112
77	incode-005	-	192	0.0001	78	0.0004	99	0.0007	93
78	innovativetechnologyltd-001	-	192	0.0024	178	0.0025	179	0.0055	132
79	innovatrics-004	0.1170	60	0.0000	62	0.0004	102	0.0041	127
80	innovatrics-006	0.0350	37	0.0000	56	0.0004	74	0.0003	64
81	intellicloudai-001	-	192	0.0000	46	0.0000	50	0.0001	50
82	intellifusion-001	0.0949	56	0.0001	74	0.0003	69	0.0005	82
83	intellivision-001	0.5495	102	0.0048	185	0.0042	187	0.1358	185
84	intellivision-002	-	192	0.0012	163	0.0005	135	0.0146	146
85	intelresearch-000	-	192	0.0000	58	0.0003	68	0.0001	51
86	intelresearch-001	-	192	0.0005	138	0.0010	153	0.0407	170
87	intsysmsu-000	-	192	0.0004	127	0.0012	165	0.0031	123
88	intsysmsu-001	-	192	0.0001	81	0.0004	97	0.0004	73
89	iqface-000	0.0000	12	0.0000	36	0.0000	39	0.0000	31
90	iqface-001	-	192	0.0000	48	0.0000	15	0.0000	12
91	isap-001	-	192	0.0000	34	0.0000	37	0.0000	29
92	isityou-000	0.4714	97	0.0023	175	0.0010	156	0.0663	179
93	isystems-001	0.1421	64	0.0010	158	0.0007	144	0.0128	143
94	isystems-002	0.1421	65	0.0010	159	0.0007	145	0.0128	144
95	itmo-006	-	192	0.0004	132	0.0004	95	0.0006	87
96	itmo-007	-	192	0.0003	120	0.0000	43	0.0004	71
97	kakao-001	-	192	0.0002	107	0.0005	123	0.0310	161
98	kakao-002	0.2494	86	0.0002	108	0.0005	126	0.0310	162
99	kedacom-000	0.0000	21	0.0000	19	0.0000	20	0.0000	14
100	kneron-003	0.4883	100	0.0044	184	0.0016	175	0.1823	189
101	kneron-004	-	192	0.0015	171	0.0007	148	0.0201	153
102	lookman-002	-	192	0.0000	33	0.0000	36	0.0000	28
103	lookman-004	0.0000	1	0.0000	29	0.0000	31	0.0000	23
104	luxand-000	-	192	0.0000	9	0.0000	9	0.0000	7
105	megvii-001	0.0274	36	0.0007	147	0.0004	79	0.0152	148
106	megvii-002	0.0274	35	0.0054	187	0.0004	78	0.0126	142
107	meiya-001	-	192	0.0004	134	0.0010	157	0.0025	120
108	microfocus-001	0.0791	53	0.0008	152	0.0016	174	0.0220	156
109	microfocus-002	0.0791	52	0.0008	151	0.0016	173	0.0220	155
110	mt-000	0.1043	57	0.0002	104	0.0004	109	0.0004	69
111	mvision-001	-	192	0.0000	30	0.0000	32	0.0000	24
112	netbridgetech-001	-	192	0.0000	6	0.0000	6	0.0000	4
113	neurotechnology-006	0.1068	58	0.0004	126	0.0004	87	0.0018	116
114	neurotechnology-008	-	192	0.0004	125	0.0004	84	0.0018	117
115	nodeflux-001	-	192	0.0001	84	0.0002	55	0.0003	57
116	nodeflux-002	-	192	0.0008	150	0.0005	128	0.0008	102
117	notiontag-000	0.0000	27	0.0000	26	0.0000	28	0.0000	21
118	ntechlab-007	0.0682	50	0.0001	69	0.0004	75	0.0005	81
119	ntechlab-008	-	192	0.0001	71	0.0004	72	0.0005	78
120	pa-004	-	192	0.0001	68	0.0004	104	0.0006	83

Table 12: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
121	paravision-004	0.0570	44	0.0002	101	0.0004	90	0.0008	96
122	pixelall-002	0.0001	30	0.0000	13	0.0000	13	0.0001	46
123	pixelall-003	-	192	0.0000	40	0.0000	44	0.0000	34
124	psl-002	-	192	0.0000	17	0.0000	18	0.0000	13
125	psl-003	-	192	0.0000	59	0.0004	94	0.0003	61
126	pyramid-000	-	192	0.0005	137	0.0007	146	0.0015	114
127	rankone-007	0.3518	93	0.0003	116	0.0004	111	0.0043	129
128	rankone-008	-	192	0.0003	111	0.0004	70	0.0040	126
129	realnetworks-002	-	192	0.0004	124	0.0003	62	0.0004	74
130	realnetworks-003	0.0076	32	0.0004	123	0.0003	61	0.0004	76
131	remarkai-001	-	192	0.0000	28	0.0000	30	0.0000	45
132	remarkai-002	-	192	0.0000	16	0.0000	17	0.0000	42
133	rokid-000	-	192	0.0001	80	0.0005	127	0.0354	167
134	rokid-001	-	192	0.0000	15	0.0000	16	0.0007	94
135	s1-001	-	192	0.0013	164	0.0007	142	0.0600	178
136	saffe-001	0.0000	26	0.0000	23	0.0000	25	0.0000	19
137	saffe-002	-	192	0.0000	43	0.0000	47	0.0000	35
138	samtech-001	-	192	0.0004	131	0.0008	149	0.0013	110
139	scanovate-001	-	192	0.0024	176	0.0014	170	0.2751	190
140	sensetime-002	0.3345	92	0.0011	162	0.0005	133	0.0218	154
141	sensetime-003	0.0554	42	0.0000	50	0.0004	91	0.0004	77
142	sertis-000	-	192	0.0000	65	0.0004	83	0.0004	70
143	shaman-000	0.0000	6	0.0000	32	0.0000	34	0.0000	26
144	shaman-001	0.0000	2	0.0000	1	0.0000	1	0.0000	40
145	shu-001	0.1822	71	0.0010	157	0.0006	136	0.0499	172
146	shu-002	-	192	0.0005	135	0.0004	110	0.0007	91
147	siat-002	0.0616	46	0.0000	57	0.0004	92	0.0048	131
148	siat-004	-	192	0.0000	55	0.0004	89	0.0003	60
149	sjtu-001	-	192	0.0005	136	0.0004	114	0.0008	100
150	smilart-002	0.2422	83	0.0003	119	0.0011	159	0.0575	176
151	smilart-003	-	192	0.0014	168	0.0013	169	0.0555	174
152	starhybrid-001	0.2340	82	0.0009	155	0.0023	178	0.0044	130
153	synesis-005	0.1862	72	0.0001	79	0.0005	120	0.0021	118
154	synesis-006	-	192	0.0000	60	0.0003	58	0.0002	56
155	synology-000	-	192	0.0000	11	0.0000	11	0.0000	9
156	tech5-002	-	192	0.0001	76	0.0003	57	0.0000	43
157	tech5-003	0.0016	31	0.0001	75	0.0003	59	0.0002	52
158	tevian-004	-	192	0.0002	99	0.0005	130	0.0057	133
159	tevian-005	0.3606	94	0.0006	143	0.0006	140	0.0012	108
160	tiger-002	0.0619	47	0.0001	87	0.0004	88	0.0082	138
161	tiger-003	0.0619	48	0.0001	85	0.0004	86	0.0082	137
162	tongyi-005	0.0000	8	0.0000	5	0.0000	5	0.0000	3
163	toshiba-002	0.0000	16	0.0000	12	0.0000	12	0.0000	10
164	toshiba-003	-	192	0.0001	88	0.0001	52	0.0002	55
165	trueface-000	-	192	0.0000	44	0.0000	48	0.0000	36
166	tuputech-000	-	192	0.0632	193	0.0081	190	0.6383	192
167	ulsee-001	-	192	0.0000	41	0.0000	45	0.0001	47
168	uluface-002	0.0000	28	0.0000	27	0.0000	29	0.0000	22
169	uluface-003	-	192	0.0002	96	0.0002	53	0.0244	159
170	upc-001	0.0450	39	0.0003	112	0.0003	67	0.0011	107
171	vd-001	-	192	0.0004	130	0.0009	150	0.0024	119
172	veridas-002	-	192	0.0001	89	0.0005	125	0.0006	86
173	veridas-003	0.1893	73	0.0001	86	0.0005	124	0.0006	85
174	via-000	0.0000	13	0.0000	39	0.0000	42	0.0001	48
175	videmo-000	-	192	0.0003	117	0.0012	167	0.0158	149
176	videonetics-001	0.4799	98	0.0015	170	0.0010	155	0.0112	141
177	videonetics-002	0.4598	96	0.0006	144	0.0005	132	0.0013	109
178	vigilantsolutions-006	-	192	0.0001	73	0.0004	76	0.0005	80
179	vigilantsolutions-007	0.2538	87	0.0001	72	0.0004	73	0.0005	79
180	vion-000	0.6388	104	0.0130	190	0.0078	189	0.1389	186

Table 13: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] *The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.*

	Algorithm	Failure to Enrol Rate[1]							
	Name	CHILD-EXPLOIT		MUGSHOT		VISA		WILD	
181	visionbox-000	-	192	0.0005	142	0.0011	161	0.0028	122
182	visionbox-001	-	192	0.0005	141	0.0011	160	0.0028	121
183	visionlabs-007	0.1939	75	0.0003	118	0.0005	122	0.0008	101
184	visionlabs-008	-	192	0.0002	109	0.0004	116	0.0009	103
185	vocord-006	-	192	0.0003	115	0.0003	65	0.0008	99
186	vocord-007	0.0000	19	0.0001	94	0.0004	71	0.0009	105
187	winsense-000	0.0000	15	0.0000	10	0.0000	10	0.0000	8
188	winsense-001	0.0000	24	0.0000	22	0.0000	24	0.0000	18
189	x-laboratory-000	0.0000	25	0.0005	140	0.0002	54	0.0000	37
190	yisheng-004	0.4279	95	0.0013	165	0.0006	138	0.0321	164
191	yitu-003	-	192	0.0009	154	0.0000	3	0.0000	1

Table 14: FTE is the proportion of failed template generation attempts. Failures can occur because the software throws an exception, or because the software electively refuses to process the input image. This would typically occur if a face is not detected. FTE is measured as the number of function calls that give EITHER a non-zero error code OR that give a "small" template. This is defined as one whose size is less than 0.3 times the median template size for that algorithm. This second rule is needed because some algorithms incorrectly fail to return a non-zero error code when template generation fails.

[1] *The effects of FTE are included in the accuracy results of this report by regarding any template comparison involving a failed template to produce a low similarity score. Thus higher FTE results in higher FNMR and lower FMR.*

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3.4 Recognition accuracy

Core algorithm accuracy is stated via:

- ▷ **Cooperative subjects**
  - The summary table of Figure 10;
  - The visa image DETs of Figure 31;
  - The mugshot DETs of Figure 41;
  - The mugshot ageing profiles of Figure 154;
  - The human-difficult pairs of Figure 11
- ▷ **Non-cooperative subjects**
  - The photojournalism DET of Figure 49
  - The child-exploitation DET of Figure 54;
  - The child-exploitation CMC of Figure 58.

Figure 125 shows dependence of false match rate on algorithm score threshold. This allows a deployer to set a threshold to target a particular false match rate appropriate to the security objectives of the application.

Figure 105 likewise shows FMR(T) but for mugshots, and specially four subsets of the population.

Note that in both the mugshot and visa sets false match rates vary with the ethnicity, age, and sex, of the enrollee and impostor - see section 3.6. For example figure 69 summarizes FMR for impostors paired from four groups black females, black males, white females, white males.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 4: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 5: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 6: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 7: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 8: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 9: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 10: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 11: The Figure shows, in blue, algorithms that correctly separate the 12 genuine and 8 impostor pairs used in the May 2018 paper Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms *(Phillips et al. [1]). In red are algorithms that are imperfect. Some algorithms fail only because they failed to make a template e.g. due to face detection failure (shown as a triangle). Others fail because the pairs were selected for that study because they had been difficult for three leading algorithms used in FRVT 2006. Caution: Given the small sample size (n=20) the figure may change substantially if larger or different sets were used. The images can be downloaded from the* Supplemental Information *page provided with that publication.*

Figure 12: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 13: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 14: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 15: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 16: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 17: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 18: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 19: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 20: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 21: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 22: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 23: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 24: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 25: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 26: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 27: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 28: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 29: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 30: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 31: For the visa images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR.

Figure 32: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 33: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 34: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 35: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 36: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 37: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 38: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 39: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 40: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 41: For the mugshot images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show decades of FMR.

Figure 42: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 43: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 44: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 45: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 46: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 47: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 48: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 49: For the 2018 wild image comparisons, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show several decades of FMR.

Figure 50: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 51: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 52: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 53: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 54: For child exploitation images, detection error tradeoff (DET) characteristics showing false non-match rate vs. false match rate plotted parametrically on threshold, T. The scales are logarithmic in order to show many decades of FMR. Accuracy is poor because many images have adverse quality characteristics, and because detection and enrollment fails.

Figure 55: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 54 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 56: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 54 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 57: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 54 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 58: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank. This is simulation of a one-to-many search experiment - see discussion in section 3.2. The scales are logarithmic in order to show the effect of long candidate lists. Accuracy is poor but much improved relative to the 1:1 DETs of Fig. 54 because a search can succeed if any of a subject's several enrolled images matches the search image with a high score.

Figure 59: For child exploitation images, cumulative match characteristics (CMC) showing true positive identification rate vs. rank for two cases: 1. Whole image provided to the algorithm; 2. Human annotated rectangular region, cropped and provided to the algorithm. The difference between the traces is associated with detection of difficult faces, and fine localization.

Figure 60: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 61: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 62: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 63: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 64: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 65: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 66: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 67: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 68: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 69: For the mugshot images, FMR *for same-sex impostor pairs of images annotated with codes for black female, black male, white female, white male. The threshold is set for each algorithm to give* FMR *= 0.001 for white males which is the demographc that usually gives the lowest* FMR*. This means the top right box is the same color in all panels. The panels are sorted over multiple pages in order of* FMR *on black females, which is the demographc that usually gives the highest* FMR*.*

Figure 70: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 71: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 72: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 73: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 74: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 75: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 76: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 77: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 78: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 79: For the mugshot images, error tradeoff characteristics for white females, black females, black males and white males. The Z-shaped grey lines correspond to fixed thresholds, showing both *FNMR and FMR vary at one T value. Note: Many of the plots will naively be read as saying women gives worse error rates than men because the solid traces lie above the dotted ones. However, this is misleading and incomplete: The grey lines show the traces reveal horizontal shifts. Thus for the cogent-003 algorithm FNMR for men is* higher *than for women* at a fixed threshold *but, at the same time, FMR is higher for women - see Figure 105. As access control systems almost always operate at a fixed threshold, the naive interpretation is incorrect.*

Figure 80: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 81: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 82: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 83: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 84: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 85: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 86: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 87: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 88: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 89: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 90: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 91: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 92: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 93: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 94: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 95: For the visa images, FNMR and FMR at six operating points along the DET characteristic. At each point a line is drawn between (FMR,FNMR)$_{\text{MALE}}$ and (FMR,FNMR)$_{\text{FEMALE}}$ showing how which sex has lower FMR and/or FNMR. The "M" label denotes male, the other end of the line corresponds to female. The six operating thresholds are selected to give the nominal false match rates given in the legend, and are computed over all impostor pairs regardless of age, sex, and place of birth. The plotted FMR values are broadly an order of magnitude larger than the nominal rates because FMR is computed over demographically-matched impostor pairs i.e individuals of the same sex, from the same geographic region (see section 3.6.1), and the same age group (see section 3.6.2).

Figure 96: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 97: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 98: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 99: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 100: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 101: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 102: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 103: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 104: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

Figure 105: For the mugshot images, the false match calibration curves show false match rate vs. threshold. Separate curves appear for white females, black females, black males and white males.

2020/01/22 09:17:44
FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 106: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 107: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 108: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 109: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 110: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 111: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 112: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 113: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 114: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 115: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 116: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 117: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 118: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 119: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 120: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 121: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 122: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 123: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 124: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 125: For the visa images, the false match calibration curves show FMR vs. threshold, T. The blue (lower) curves are for zero-effort impostors (i.e. comparing all images against all). The red (upper) curves are for persons of the same-sex, same-age, and same national-origin. This shows that FMR is underestimated (by a factor of 10 or more) by using a zero-effort impostor calculation to calibrate T. As shown later (sec. 3.6), FMR is higher for demographic-matched impostors.

Figure 126: For the visa images, the curves show how false matches are concentrated in certain images. Specifically each line plots FMR(k) with k the number of images rejected in decreasing order of how many false matches that image was involved in. FMR(0) $= 10^{-4}$. In terms of the biometric zoo, the most "wolf-ish" images are rejected first i.e. those enrollment or verification images most often involved in false matches. A flatter response is considered superior. A steeply descending response indicates that certain kinds of images false match against others, e.g. if hypothetically images of men with particular mustaches would falsely match others.

3.5 Genuine distribution stability

3.5.1 Effect of birth place on the genuine distribution

Background: Both skin tone and bone structure vary geographically. Prior studies have reported variations in FNMR and FMR.

Goal: To measure false non-match rate (FNMR) variation with country of birth.

Methods: Thresholds are determined that give FMR = $\{0.001, 0.0001\}$ over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores. Only those countries with at least 140 individuals are included in the analysis.

Results: Figure 142 shows FNMR by country of birth for the two thresholds.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 127: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 128: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 129: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 130: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 131: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 132: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 133: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 134: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 135: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 136: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 137: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 138: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 139: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 140: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 141: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 142: For the visa images, the dots show FNMR by country of birth for two globally set operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.1. The figures shows an order of magnitude variation in FNMR across country of birth; these effects are likely due quality variations, then demographics like age and race. The error rates in some cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Caveats: The results may not relate to subject-specific properties. Instead they could reflect image-specific quality differences, which could occur due to collection protocol or software processing variations.

3.5.2 Effect of ageing

Background: Faces change appearance throughout life. This change gradually reduces similarity of a new image to an earlier image. Face recognition algorithms give reduced similarity scores and more frequent false rejections.

Goal: To quantify false non-match rates (FNMR) as a function of elapsed time in an adult population.

Methods: Using the mugshot images, a threshold is set to give FMR = 0.00001 over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores.

Results: For the visa images, Figure 154 shows how false non-match rates for genuine users, as a function of age group.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 143: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\widetilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 144: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\widetilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 145: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 146: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\widetilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 147: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 148: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all (10^8) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 149: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 150: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 151: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 152: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 153: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all ($\tilde{10}^8$) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

Figure 154: For the mugshot images, FNMR *as a function of elapsed time between initial enrollment and second verification images. The panels appear most accurate first, and vertical scale changes on each page. The four traces correspond to images annotated with codes for black female, black male, white female, white male. The threshold is fixed for each algorithm to give FMR = 0.00001 over all (10^8) impostor comparisons. For short time-lapses, the most accurate algorithms give very few errors (FNMR < 0.001) so that the uncertainty estimates are high.*

3.5.3 Effect of age on genuine subjects

Background: Faces change appearance throughout life. Face recognition algorithms have previously beeen reported to give better accuracy on older individuals (See NIST IR 8009).

Goal: To quantify false non-match rates (FNMR) as a function of age, without an ageing component.

Methods: Using the visa images, which span fewer than five years, thresholds are determined that give FMR = 0.001 and 0.0001 over the entire impostor set. Then FNMR is measured over 1000 bootstrap replications of the genuine scores.

Results: For the visa images, Figure 170 shows how false non-match rates for genuine users, as a function of age group.

The notable aspects are:

- ▷ Younger subjects give considerably higher FNMR. This is likely due to rapid growth and change in facial appearance.
- ▷ FNMR trends down throughout life. The last bin, AGE $>$ 72, contains fewer than 140 mated pairs, and may be affected by small sample size.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 155: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 156: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 157: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 158: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 159: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 160: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 161: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 162: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 163: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 164: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 165: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 166: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 167: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 168: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 169: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Figure 170: For the visa images, the dots show FNMR by age group for two operating thresholds corresponding to FMR = $\{0.001, 0.0001\}$ computed over all on the order of 10^{10} impostor scores. The FMR in each bin will vary also - see subsequent impostor heatmaps in sec. 3.6.2. Given a pair of face images taken at different times, we assign the comparison to the bin that is the arithmetic average of the subject's ages. This plot shows only the effect of age, not ageing. The number of comparisons in each bin is generally in the thousands, however the first and last bins are computed over 149 and 124 respectively. The error rates in some (adult) cases are zero, and in others the DET is flat so the error rates at the two thresholds are identical. The lines span 1% and 99% of boostrap replicated FNMR estimates.

Caveats: None.

3.6 Impostor distribution stability

3.6.1 Effect of birth place on the impostor distribution

Background: Facial appearance varies geographically, both in terms of skin tone, cranio-facial structure and size. This section addresses whether false match rates vary intra- and inter-regionally.

Goals:

- ▷ To show the effect of birth region of the impostor and enrollee on false match rates.
- ▷ To determine whether some algorithms give better impostor distribution stability.

Methods:

- ▷ For the visa images, NIST defined 10 regions: Sub-Saharan Africa, South Asia, Polynesia, North Africa, Middle East, Europe, East Asia, Central and South America, Central Asia, and the Caribbean.
- ▷ For the visa images, NIST mapped each country of birth to a region. There is some arbitrariness to this. For example, Egypt could reasonably be assigned to the Middle East instead of North Africa. An alternative methodology could, for example, assign the Philippines to *both* Polynesia and East Asia.
- ▷ FMR is computed for cases where all face images of impostors born in region r_2 are compared with enrolled face images of persons born in region r_1.

$$\text{FMR}(r_1, r_2, T) = \frac{\sum_{i=1}^{N_{r_1,r_2}} H(s_i - T)}{N_{r_1,r_2}} \tag{5}$$

  where the same threshold, T, is used in all cells, and H is the unit step function. The threshold is set to give FMR(T) = 0.001 over the entire set of visa image impostor comparisons.
- ▷ This analysis is then repeated by country-pair, but only for those country pairs where both have at least 1000 images available. The countries[1] appear in the axes of graphs that follow.
- ▷ The mean number of impostor scores in any cross-region bin is 33 million. The smallest number of impostor scores in any bin is 135000, for Central Asia - North Africa. While these counts are large enough to support reasonable significance, the number of individual faces is much smaller, on the order of $N^{0.5}$.
- ▷ The numbers of impostor scores in any cross-country bin is shown in Figure 551.

Results: Subsequent figures show heatmaps that use color to represent the base-10 logarithm of the false match rate. Red colors indicate high (bad) false match rates. Dark colors indicate benign false match rates. There are two series of graphs corresponding to aggregated geographical regions, and to countries. The notable observations are:

- ▷ The on-diagonal elements correspond to within-region impostors. FMR is generally above the nominal value of FMR = 0.001. Particularly there is usually higher FMR in, Sub-Saharan Africa, South Asia, and the Caribbean. Europe and Central Asia, on the other hand, usually give FMR closer to the nominal value.
- ▷ The off-diagonal elements correspond to across-region impostors. The highest FMR is produced between the Caribbean and Sub-Saharan Africa.
- ▷ Algorithms vary.

[1] These are Argentina, Australia, Brazil, Chile, China, Costa Rica, Cuba, Czech Republic, Dominican Republic, Ecuador, Egypt, El Salvador, Germany, Ghana, Great Britain, Greece, Guatamala, Haiti, Hong Kong, Honduras, Indonesia, India, Israel, Jamaica, Japan, Kenya, Korea, Lebanon, Mexico, Malaysia, Nepal, Nigeria, Peru, Philippines, Pakistan, Poland, Romania, Russia, South Africa, Saudi Arabia, Thailand, Trinidad, Turkey, Taiwan, Ukraine, Venezuela, and Vietnam.

Figure 171: For the visa images, the dots show FMR for impostor comparisons of individuals of the same sex and same age group for the region of the world that gives the worst (highest) FMR when the threshold is set to give FMR = 0.001 (red vertical line) over all on the order of 10^{10} impostor scores i.e. zero-effort. The shift of the dots to right shows massive increases in FMR when impostors have the same sex, age, and region of birth. The color code indicates which region gives the worst case FMR. If the observed variation is due to the prevalence of one kind of images in the training imagery, then algorithms developed on one kind of data might be expected to give higher FMR on other kinds.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

- ▷ We computed the same quantities for a global FMR = 0.0001. The effects are similar.

Caveats:

- ▷ The effects of variable impostor rates on one-to-many identification systems may well differ from what's implied by these one-to-one verification results. Two reasons for this are a) the enrollment galleries are usually imbalanced across countries of birth, age and sex; b) one-to-many identification algorithms often implement techniques aimed at stabilizing the impostor distribution. Further research is necessary.
- ▷ In principle, the effects seen in this subsection could be due to differences in the image capture process. We consider this unlikely since the effects are maintained across geography - e.g. Caribbean vs. Africa, or Japan vs. China.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 172: For visa images, the heatmap shows how the mean of the impostor distribution for the country pair (a,b) is shifted relative to the mean of the global impostor distribution, expressed as a number of standard deviations of the global impostor distribution. This statistic is designed to show shifts in the entire impostor distribution, not just tail effects that manifest as the anomalously high (or low) false match rates that appear in the subsequent figures. The countries are chosen to show that skin tone alone does not explain impostor distribution shifts. The reduced shift in Asian populations with the Yitu and TongYiTrans algorithms, is accompanied by positive shifts in the European populations. This reversal relative to most other algorithms, may derive from use of nationally weighted training sets. The figure is computed from same-sex and same-age impostor pairs.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 173: For algorithm 3divi-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 174: For algorithm 3divi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 175: For algorithm acer-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 176: For algorithm adera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 177: For algorithm advance-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 178: For algorithm aifirst-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 179: For algorithm ailabs-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 180: For algorithm aimall-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 181: For algorithm aiunionface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 182: For algorithm alchera-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 183: For algorithm alchera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 184: For algorithm allgovision-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 185: For algorithm alphaface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 186: For algorithm amplifiedgroup-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 187: For algorithm anke-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 188: For algorithm anke-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 189: For algorithm antheus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 190: For algorithm anyvision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 191: For algorithm anyvision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 192: For algorithm asusaics-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 193: For algorithm aware-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 194: For algorithm aware-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 195: For algorithm awiros-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 196: For algorithm ayonix-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 197: For algorithm bioidtechswiss-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 198: For algorithm bm-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 199: For algorithm camvi-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 200: For algorithm camvi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 201: For algorithm ceiec-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 202: For algorithm ceiec-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 203: For algorithm chtface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 204: For algorithm chtface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 205: For algorithm cib-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 206: For algorithm cogent-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 207: For algorithm cogent-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 208: For algorithm cognitec-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 209: For algorithm cognitec-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 210: For algorithm ctbcbank-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 211: For algorithm ctbcbank-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 212: For algorithm cyberextruder-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 213: For algorithm cyberextruder-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 214: For algorithm cyberlink-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 215: For algorithm cyberlink-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 216: For algorithm dahua-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 217: For algorithm dahua-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 218: For algorithm deepglint-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 219: For algorithm deepglint-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 220: For algorithm deepsea-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 221: For algorithm dermalog-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 222: For algorithm dermalog-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 223: For algorithm didiglobalface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 224: For algorithm digitalbarriers-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 225: For algorithm dsk-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 226: For algorithm einetworks-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 227: For algorithm expasoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 228: For algorithm f8-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 229: For algorithm facesoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 230: For algorithm glory-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 231: For algorithm glory-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 232. For algorithm gorilla-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 233: For algorithm gorilla-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 234: For algorithm hik-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 235: For algorithm hr-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 236: For algorithm hr-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 237: For algorithm id3-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 238: For algorithm id3-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 239: For algorithm idemia-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 240: For algorithm idemia-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 241: For algorithm iit-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 242: For algorithm iit-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 243: For algorithm imagus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 244: For algorithm imagus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 245: For algorithm imperial-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 246: For algorithm imperial-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 247: For algorithm incode-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 248: For algorithm incode-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 249: For algorithm innovativetechnologyltd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 250: For algorithm innovatrics-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 251: For algorithm innovatrics-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 252: For algorithm intellicloudai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 253: For algorithm intellifusion-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 254: For algorithm intellivision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 255: For algorithm intellivision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 256: For algorithm intelresearch-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 257: For algorithm intelresearch-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 258: For algorithm intsysmsu-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 259: For algorithm intsysmsu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 260: For algorithm iqface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 261: For algorithm iqface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 262: For algorithm isap-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 263: For algorithm isityou-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 264: For algorithm isystems-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 265: For algorithm isystems-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 266: For algorithm itmo-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 267: For algorithm itmo-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 268: For algorithm kakao-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 269: For algorithm kakao-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 270: For algorithm kedacom-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 271: For algorithm kneron-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 272: For algorithm kneron-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 273: For algorithm lookman-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 274: For algorithm lookman-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 275: For algorithm luxand-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 276: For algorithm megvii-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 277: For algorithm megvii-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 278: For algorithm meiya-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 279: For algorithm microfocus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 280: For algorithm microfocus-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 281: For algorithm mt-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 282: For algorithm mvision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 283: For algorithm netbridgetech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 284: For algorithm neurotechnology-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 285: For algorithm neurotechnology-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 286: For algorithm nodeflux-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 287: For algorithm nodeflux-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 288: For algorithm notiontag-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 289: For algorithm ntechlab-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 290: For algorithm ntechlab-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 291: For algorithm pa-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 292: For algorithm paravision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 293: For algorithm pixelall-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 294: For algorithm pixelall-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 295: For algorithm psl-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 296: For algorithm psl-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 297: For algorithm pyramid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 298: For algorithm rankone-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 299: For algorithm rankone-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 300: For algorithm realnetworks-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 301: For algorithm realnetworks-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 302: For algorithm remarkai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 303: For algorithm remarkai-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 304: For algorithm rokid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 305: For algorithm rokid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 306: For algorithm s1-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 307: For algorithm saffe-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 308: For algorithm saffe-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 309: For algorithm samtech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 310: For algorithm scanovate-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 311: For algorithm sensetime-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 312: For algorithm sensetime-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 313: For algorithm sertis-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 314: For algorithm shaman-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 315: For algorithm shaman-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 316: For algorithm shu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 317: For algorithm shu-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 318: For algorithm siat-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 319: For algorithm siat-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 320: For algorithm sjtu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 321: For algorithm smilart-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 322: For algorithm smilart-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 323: For algorithm starhybrid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 324: For algorithm synesis-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 325: For algorithm synesis-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 326: For algorithm synology-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 327: For algorithm tech5-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 328: For algorithm tech5-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 329: For algorithm tevian-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 330: For algorithm tevian-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 331: For algorithm tiger-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 332: For algorithm tiger-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 333: For algorithm tongyi-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 334: For algorithm toshiba-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 335: For algorithm toshiba-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 336: For algorithm trueface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 337: For algorithm tuputech-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 338: For algorithm ulsee-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 339: For algorithm uluface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 340: For algorithm uluface-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 341: For algorithm upc-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 342: For algorithm vcog-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 343: For algorithm vd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 344: For algorithm veridas-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 345: For algorithm veridas-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 346: For algorithm via-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 347: For algorithm videmo-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 348: For algorithm videonetics-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 349: For algorithm videonetics-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 350: For algorithm vigilantsolutions-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 351: For algorithm vigilantsolutions-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 352: For algorithm vion-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 353: For algorithm visionbox-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 354: For algorithm visionbox-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 355: For algorithm visionlabs-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 356: For algorithm visionlabs-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 357: For algorithm vocord-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 358: For algorithm vocord-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 359: For algorithm winsense-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 360: For algorithm winsense-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 361: For algorithm x-laboratory-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 362: For algorithm yisheng-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 363: For algorithm yitu-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given region pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 364: For algorithm 3divi-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 365: For algorithm 3divi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 366: For algorithm acer-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 367: For algorithm adera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 368: For algorithm advance-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 369: For algorithm aifirst-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 370: For algorithm ailabs-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 371: For algorithm aimall-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 372: For algorithm aiunionface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 373: For algorithm alchera-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 374: For algorithm alchera-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 375: For algorithm allgovision-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 376: For algorithm alphaface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 377: For algorithm amplifiedgroup-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 378: For algorithm anke-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 379: For algorithm anke-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 380: For algorithm antheus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 381: For algorithm anyvision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 382: For algorithm anyvision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 383: For algorithm asusaics-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 384: For algorithm aware-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 385: For algorithm aware-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 386: For algorithm awiros-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 387: For algorithm ayonix-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 388: For algorithm bioidtechswiss-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 389: For algorithm bm-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 390: For algorithm camvi-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 391: For algorithm camvi-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 392: For algorithm ceiec-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 393: For algorithm ceiec-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 394: For algorithm chtface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 395: For algorithm chtface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 396: For algorithm cib-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 397: For algorithm cogent-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 398: For algorithm cogent-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 399: For algorithm cognitec-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 400: For algorithm cognitec-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 401: For algorithm ctbcbank-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 402: For algorithm ctbcbank-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 403: For algorithm cyberextruder-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 404: For algorithm cyberextruder-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 405: For algorithm cyberlink-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 406: For algorithm cyberlink-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 407: For algorithm dahua-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 408: For algorithm dahua-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 409: For algorithm deepglint-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 410: For algorithm deepglint-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 411: For algorithm deepsea-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 412: For algorithm dermalog-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 413: For algorithm dermalog-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 414: For algorithm didiglobalface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 415: For algorithm digitalbarriers-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 416: For algorithm dsk-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 417: For algorithm einetworks-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 418: For algorithm expasoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 419: For algorithm f8-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 420: For algorithm facesoft-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 421: For algorithm glory-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 422: For algorithm glory-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 423: For algorithm gorilla-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 424: For algorithm gorilla-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 425: For algorithm hik-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 426: For algorithm hr-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 427: For algorithm hr-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 428: For algorithm id3-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 429: For algorithm id3-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 430: For algorithm idemia-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 431: For algorithm idemia-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 432: For algorithm iit-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 433: For algorithm iit-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 434: For algorithm imagus-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 435: For algorithm imagus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 436: For algorithm imperial-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 437: For algorithm imperial-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 438: For algorithm incode-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 439: For algorithm incode-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 440: For algorithm innovativetechnologyltd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 441: For algorithm innovatrics-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 442: For algorithm innovatrics-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 443: For algorithm intellicloudai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 444: For algorithm intellifusion-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 445: For algorithm intellivision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 446: For algorithm intellivision-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 447: For algorithm intelresearch-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 448: For algorithm intsysmsu-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 449: For algorithm intsysmsu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 450: For algorithm iqface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 451: For algorithm iqface-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 452: For algorithm isap-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 453: For algorithm isityou-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 454: For algorithm isystems-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 455: For algorithm isystems-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 456: For algorithm itmo-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 457: For algorithm itmo-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 458: For algorithm kakao-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 459: For algorithm kakao-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 460: For algorithm kedacom-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 461: For algorithm kneron-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 462: For algorithm kneron-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 463: For algorithm lookman-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 464: For algorithm lookman-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 465: For algorithm luxand-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 466: For algorithm megvii-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 467: For algorithm megvii-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 468: For algorithm meiya-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 469: For algorithm microfocus-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 470: For algorithm microfocus-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 471: For algorithm mt-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 472: For algorithm mvision-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 473: For algorithm netbridgetech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 474: For algorithm neurotechnology-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 475: For algorithm neurotechnology-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 476: For algorithm nodeflux-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 477: For algorithm nodeflux-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 478: For algorithm notiontag-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 479: For algorithm ntechlab-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 480: For algorithm pa-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 481: For algorithm paravision-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 482: For algorithm pixelall-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 483: For algorithm pixelall-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 484: For algorithm psl-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 485: For algorithm psl-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 486: For algorithm pyramid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 487: For algorithm rankone-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 488: For algorithm rankone-008 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 489: For algorithm realnetworks-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 490: For algorithm realnetworks-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 491: For algorithm remarkai-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 492: For algorithm remarkai-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 493: For algorithm rokid-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 494: For algorithm rokid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 495: For algorithm s1-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 496: For algorithm saffe-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 497: For algorithm saffe-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 498: For algorithm samtech-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 499: For algorithm scanovate-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 500: For algorithm sensetime-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 501: For algorithm sensetime-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 502: For algorithm sertis-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 503: For algorithm shaman-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 504: For algorithm shaman-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 505: For algorithm shu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 506: For algorithm shu-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 507: For algorithm siat-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 508: For algorithm siat-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 509: For algorithm sjtu-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 510: For algorithm smilart-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 511: For algorithm smilart-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 512: For algorithm starhybrid-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 513: For algorithm synesis-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 514: For algorithm synesis-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 515: For algorithm synology-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 516: For algorithm tech5-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 517: For algorithm tech5-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 518: For algorithm tevian-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 519: For algorithm tevian-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 520: For algorithm tiger-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 521: For algorithm tiger-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 522: For algorithm tongyi-005 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 523: For algorithm toshiba-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 524: For algorithm toshiba-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 525: For algorithm trueface-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 526: For algorithm tuputech-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

Figure 527: For algorithm ulsee-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 528: For algorithm uluface-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 529: For algorithm uluface-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 530: For algorithm upc-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 531: For algorithm vcog-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 532: For algorithm vd-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 533: For algorithm veridas-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 534: For algorithm veridas-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 535: For algorithm via-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 536: For algorithm videonetics-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 537: For algorithm videonetics-002 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 538: For algorithm vigilantsolutions-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 539: For algorithm vigilantsolutions-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 540: For algorithm vion-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 541: For algorithm visionbox-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 542: For algorithm visionbox-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 543: For algorithm visionlabs-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 544: For algorithm vocord-006 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 545: For algorithm vocord-007 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 546: For algorithm winsense-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 547: For algorithm winsense-001 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 548: For algorithm x-laboratory-000 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 549: For algorithm yisheng-004 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 550: For algorithm yitu-003 operating on visa images, the heatmap shows false match rates observed over impostor comparisons of faces from different individuals who were born in the given country pair. False matches are counted against a recognition threshold fixed globally to give the target FMR in the plot title, computed over all on the order of 10^{10} impostor comparisons. If text appears in each box it gives the same quantity as that coded by the color. Grey indicates FMR is at the intended FMR target level. Light red colors present a security vulnerability to, for example, a passport gate. Each +1 increase in log10 FMR corresponds to a factor of 10 increase in FMR. The matrix is not quite symmetric because images in the enrollment and verification sets are different.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 551: For visa images, the heatmap shows the count of impostor comparisons of faces from different individuals who were born in the given country pair.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

3.6.2 Effect of age on impostors

Background: This section shows the effect of age on the impostor distribution. The ideal behaviour is that the age of the enrollee and the impostor would not affect impostor scores. This would support FMR stability over sub-populations.

Goals:

- ▷ To show the effect of relative ages of the impostor and enrollee on false match rates.
- ▷ To determine whether some algorithms have better impostor distribution stability.

Methods:

- ▷ Define 14 age group bins, spanning 0 to over 100 years old.
- ▷ Compute FMR over all impostor comparisons for which the subjects in the enrollee and impostor images have ages in two bins.
- ▷ Compute FMR over all impostor comparisons for which the subjects are additionally of the same sex, and born in the same geographic region.

Results:

The notable aspects are:

- ▷ Diagonal dominance: Impostors are more likely to be matched against their same age group.
- ▷ Same sex and same region impostors are more successful. On the diagonal, an impostor is more likely to succeed by posing as someone of the same sex. If $\Delta \log_{10} \text{FMR} = 0.2$, then same-sex same-region FMR exceeds the all-pairs FMR by factor of $10^{0.2} = 1.6$.
- ▷ Young children impostors give elevated FMR against young children. Older adult impostor give elevated FMR against older adults. These effects are quite large, for example if $\Delta \log_{10} \text{FMR} = 1.0$ larger than a 32 year old, then these groups have higher FMR by a factor of $10^1 = 10$. This would imply an FMR above 0.01 for a nominal (global) FMR = 0.001.
- ▷ Algorithms vary.
- ▷ We computed the same quantities for a global FMR = 0.0001. The effects are similar.

Note the calculations in this section include impostors paired across all countries of birth.

Figure 552: For algorithm 3divi-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 553: For algorithm 3divi-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 554: For algorithm acer-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 555: For algorithm adera-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 556: For algorithm advance-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 557: For algorithm aifirst-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 558: For algorithm ailabs-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 559: For algorithm aimall-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 560: For algorithm aiunionface-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 561: For algorithm alchera-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 562: For algorithm alchera-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 563: For algorithm allgovision-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 564: For algorithm alphaface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 565: For algorithm amplifiedgroup-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 566: For algorithm anke-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 567: For algorithm anke-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 568: For algorithm antheus-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 569: For algorithm anyvision-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 570: For algorithm anyvision-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 571: For algorithm asusaics-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 572: For algorithm aware-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 573: For algorithm aware-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 574: For algorithm awiros-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 575: For algorithm ayonix-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 576: For algorithm bioidtechswiss-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 577: For algorithm bm-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 578: For algorithm camvi-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 579: For algorithm camvi-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 580: For algorithm ceiec-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 581: For algorithm ceiec-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 582: For algorithm chtface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 583: For algorithm chtface-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 584: For algorithm cib-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 585: For algorithm cogent-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 586: For algorithm cogent-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 587: For algorithm cognitec-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 588: For algorithm cognitec-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 589: For algorithm ctbcbank-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 590: For algorithm ctbcbank-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 591: For algorithm cyberextruder-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 592: For algorithm cyberextruder-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 593: For algorithm cyberlink-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 594: For algorithm cyberlink-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 595: For algorithm dahua-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 596: For algorithm dahua-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 597: For algorithm deepglint-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 598: For algorithm deepglint-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 599: For algorithm deepsea-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 600: For algorithm dermalog-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 601: For algorithm dermalog-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 602: For algorithm didiglobalface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 603: For algorithm digitalbarriers-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 604: For algorithm dsk-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 605: For algorithm einetworks-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 606: For algorithm expasoft-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 607: For algorithm f8-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 608: For algorithm facesoft-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 609: For algorithm glory-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 610: For algorithm glory-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 611: For algorithm gorilla-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 612: For algorithm gorilla-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 613: For algorithm hik-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 614: For algorithm hr-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 615: For algorithm hr-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 616: For algorithm id3-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 617: For algorithm id3-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 618: For algorithm idemia-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 619: For algorithm idemia-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 620: For algorithm iit-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 621: For algorithm iit-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 622: For algorithm imagus-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 623: For algorithm imagus-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 624: For algorithm imperial-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 625: For algorithm imperial-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 626: For algorithm incode-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 627: For algorithm incode-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 628: For algorithm innovativetechnologyltd-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 629: For algorithm innovatrics-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 630: For algorithm innovatrics-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 631: For algorithm intellicloudai-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 632: For algorithm intellifusion-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 633: For algorithm intellivision-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 634: For algorithm intellivision-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 635: For algorithm intelresearch-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 636: For algorithm intelresearch-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 637: For algorithm intsysmsu-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 638: For algorithm intsysmsu-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 639: For algorithm iqface-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 640: For algorithm iqface-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 641: For algorithm isap-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 642: For algorithm isityou-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 643: For algorithm isystems-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 644: For algorithm isystems-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 645: For algorithm itmo-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 646: For algorithm itmo-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 647: For algorithm kakao-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 648: For algorithm kakao-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 649: For algorithm kedacom-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 650: For algorithm kneron-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 651: For algorithm kneron-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 652: For algorithm lookman-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 653: For algorithm lookman-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 654: For algorithm luxand-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 655: For algorithm megvii-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 656: For algorithm megvii-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 657: For algorithm meiya-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 658: For algorithm microfocus-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 659: For algorithm microfocus-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 660: For algorithm mt-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 661: For algorithm mvision-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 662: For algorithm netbridgetech-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 663: For algorithm neurotechnology-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 664: For algorithm neurotechnology-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 665: For algorithm nodeflux-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 666: For algorithm nodeflux-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 667: For algorithm notiontag-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 668: For algorithm ntechlab-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 669: For algorithm ntechlab-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 670: For algorithm pa-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 671: For algorithm paravision-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 672: For algorithm pixelall-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 673: For algorithm pixelall-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 674: For algorithm psl-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 675: For algorithm psl-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 676: For algorithm pyramid-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 677: For algorithm rankone-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 678: For algorithm rankone-008 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 679: For algorithm realnetworks-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 680: For algorithm realnetworks-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 681: For algorithm remarkai-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 682: For algorithm remarkai-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 683: For algorithm rokid-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 684: For algorithm saffe-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 685: For algorithm saffe-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 686: For algorithm samtech-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 687: For algorithm sensetime-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 688: For algorithm sensetime-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 689: For algorithm sertis-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 690: For algorithm shaman-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 691: For algorithm shaman-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 692: For algorithm shu-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 693: For algorithm siat-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 694: For algorithm siat-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 695: For algorithm sjtu-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 696: For algorithm smilart-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 697: For algorithm smilart-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 698: For algorithm starhybrid-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 699: For algorithm synesis-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 700: For algorithm synesis-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 701: For algorithm synology-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 702: For algorithm tech5-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 703: For algorithm tech5-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 704: For algorithm tevian-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 705: For algorithm tevian-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 706: For algorithm tiger-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 707: For algorithm tiger-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 708: For algorithm tongyi-005 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 709: For algorithm toshiba-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 710: For algorithm toshiba-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 711: For algorithm trueface-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 712: For algorithm tuputech-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 713: For algorithm ulsee-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 714: For algorithm uluface-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 715: For algorithm upc-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 716: For algorithm vcog-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 717: For algorithm vd-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 718: For algorithm veridas-002 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 719: For algorithm via-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Figure 720: For algorithm videonetics-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 721: For algorithm vigilantsolutions-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 722: For algorithm vigilantsolutions-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 723: For algorithm vion-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 724: For algorithm visionbox-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 725: For algorithm visionbox-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 726: For algorithm visionlabs-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 727: For algorithm vocord-006 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 728: For algorithm vocord-007 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 729: For algorithm winsense-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 730: For algorithm winsense-001 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 731: For algorithm x-laboratory-000 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 732: For algorithm yisheng-004 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

Figure 733: For algorithm yitu-003 operating on visa images, the heatmap shows false match observed over impostor comparisons of faces from different individuals who have the given age pair. False matches are counted against a recognition threshold fixed globally to give FMR = 0.0001 over all on the order of 10^{10} impostor comparisons. The text in each box gives the same quantity as that coded by the color. Light colors present a security vulnerability to, for example, a passport gate.

Accuracy Terms + Definitions

In biometrics, Type II errors occur when two samples of one person do not match – this is called a **false negative**. Correspondingly, Type I errors occur when samples from two persons do match – this is called a **false positive**. Matches are declared by a biometric system when the native comparison score from the recognition algorithm meets some **threshold**. Comparison scores can be either **similarity scores**, in which case higher values indicate that the samples are more likely to come from the same person, or **dissimilarity scores**, in which case higher values indicate different people. Similarity scores are traditionally computed by **fingerprint** and **face** recognition algorithms, while dissimilarities are used in **iris recognition**. In some cases, the dissimilarity score is a distance; this applies only when **metric** properties are obeyed. In any case, scores can be either **mate** scores, coming from a comparison of one person's samples, or **nonmate** scores, coming from comparison of different persons' samples. The words **genuine** or **authentic** are synonyms for mate, and the word **impostor** is used a synonym for nonmate. The words mate and nonmate are traditionally used in identification applications (such as law enforcement search, or background checks) while genuine and impostor are used in verification applications (such as access control).

A **error tradeoff** characteristic represents the tradeoff between Type II and Type I classification errors. For verification this plots false non-match rate (FNMR) vs. false match rate (FMR) parametrically with T.

The error tradeoff plots are often called **detection error tradeoff (DET)** characteristics or **receiver operating characteristic** (ROC). These serve the same function but differ, for example, in plotting the complement of an error rate (e.g. TMR = 1 – FNMR) and in transforming the axes most commonly using logarithms, to show multiple decades of FMR. More rarely, the function might be the inverse Gaussian function.

More detail and generality is provided in formal biometrics testing standards, see the various parts of ISO/IEC 19795 Biometrics Testing and Reporting. More terms, including and beyond those to do with accuracy, see ISO/IEC 2382-37 Information technology -- Vocabulary -- Part 37: Harmonized biometric vocabulary

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

FNMR(T) "False non-match rate"
FMR(T) "False match rate"

References

[1] P. Jonathon Phillips, Amy N. Yates, Ying Hu, Carina A. Hahn, Eilidh Noyes, Kelsey Jackson, Jacqueline G. Cavazos, Géraldine Jeckeln, Rajeev Ranjan, Swami Sankaranarayanan, Jun-Cheng Chen, Carlos D. Castillo, Rama Chellappa, David White, and Alice J. O'Toole. Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms. *Proceedings of the National Academy of Sciences*, 115(24):6171–6176, 2018.