

A: Datasheet

Algorithm: neurotechnology_014

Developer: Neurotechnology

Submission Date: 2023_12_27

Template size: 256 bytes

Template time (2.5 percentile): 470 msec

Template time (median): 472 msec

Template time (97.5 percentile): 525 msec

Investigation:

Frontal mugshot ranking 13 (out of 472) -- FNIR(1600000, 0, 1) = 0.0009 vs. lowest 0.0008 from intema_001

Mugshot webcam ranking 16 (out of 434) -- FNIR(1600000, 0, 1) = 0.0063 vs. lowest 0.0054 from sensetime_009

Mugshot profile ranking 26 (out of 403) -- FNIR(1600000, 0, 1) = 0.0592 vs. lowest 0.0510 from nec_009

Immigration visa-border ranking 26 (out of 361) -- FNIR(1600000, 0, 1) = 0.0009 vs. lowest 0.0006 from cloudwalk_mt_002

Immigration visa-kiosk ranking 38 (out of 305) -- FNIR(1600000, 0, 1) = 0.0503 vs. lowest 0.0387 from cloudwalk_mt_002

Identification:

Frontal mugshot ranking 52 (out of 472) -- FNIR(1600000, T, L+1) = 0.0033, FPIR=0.001000 vs. lowest 0.0011 from idemia_010


Mugshot webcam ranking 54 (out of 432) -- FNIR(1600000, T, L+1) = 0.0219, FPIR=0.001000 vs. lowest 0.0071 from nec_009

Mugshot profile ranking 34 (out of 402) -- FNIR(1600000, T, L+1) = 0.2237, FPIR=0.001000 vs. lowest 0.0634 from cloudwalk_mt_002


Immigration visa-border ranking 45 (out of 360) -- FNIR(1600000, T, L+1) = 0.0060, FPIR=0.001000 vs. lowest 0.0010 from cloudwalk_mt_002

Immigration visa-kiosk ranking 42 (out of 305) -- FNIR(1600000, T, L+1) = 0.0886, FPIR=0.001000 vs. lowest 0.0485 from nec_009


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (vtcc_001)




C: Evolution of accuracy for NEUROTECHNOLOGY algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_009)



L: Investigational mode: FNIR(1600000, R, 0) by probe type





M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.


Algorithm: neurotechnology_014, Dataset: Border-Crossing Ageing N = 1600000
Text encodes FNIR, Color encodes log(FNIR)



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.



Algorithm: neurotechnology_014, Dataset: Border-Crossing Ageing
Threshold: 2149.000000 set to achive FPIR(30-45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

