

# JavaScript

## Lecture 3b (Some language features)

Waterford Institute of Technology

June 9, 2016

John Fitzgerald

# JavaScript

## Functions

### function

- Block of code defined once
- Invokable many times
- May include parameters
- Observe differences Java
- Functions attached to objects referred to as *methods*
- Functions are objects
  - Assignable to variable
  - Allowable as parameter

```
function square(x) {  
    return x * x;  
}  
  
console.log(square(10)); // => 100
```

```
function add() {  
    let counter = 0;  
    function plus() {counter += 1;}  
  
    plus();  
    return counter;  
}  
  
console.log(add()); // => 1
```

# JavaScript

## Function has four parts

- (1) Reserved word **function**
  - (2) Name **square** (optional)
  - (3) Zero or more parameters (**x**)
  - (4) Statement(s) within curly braces
- Reserved **return** (optional)

```
function square(x) {  
    return x * x;  
}  
  
let square = function(x) {  
    return x * x;  
}  
  
square(3); // => 9
```

# Function

## Hidden parameters

Every function has 2 hidden parameters

- **this**
  - Reference determined by which of four available function invocation patterns used.
- **arguments**
  - Array type object containing all parameters.
  - Treat as obsolete, instead use rest arguments.
  - Rest arguments a real Array, not Array-like arguments

```
let anObject = {  
  value: 0,  
  increment: function () {  
    this.value += 1;  
  },  
};
```

```
// Output: 1  
anObject.increment();
```

```
function aFunction(...args) {  
  return args.length;  
}
```

```
// Output: 2  
console.log(aFunction(3, 4));
```

# Functions

## Invocation Patterns

Four function invocation patterns:

- 1. Method invocation
  - **this** bound to containing object
  - function is method - a property of containing object
- 2. Function invocation
  - **this** bound to global object
  - function property of global object
- 3. Constructor invocation
  - **this** bound to containing object
  - **new** not used: this bound to global
- 4. Apply invocation
  - Outside course scope

```
let anObject = {  
  value: 0,  
  increment: function () {  
    this.value += 1;  
  },  
};
```

```
// method invocation  
anObject.increment();
```

```
value = 0;  
function increment() {  
  this.value += 1;  
};
```

```
// function invocation  
increment();
```

# JavaScript

## this binding

Note: behaviour different in strict mode

```
// Function invocation: this bound to global object
function set(x) {
  this.x = x;
  console.log(x); // => 100
};
set(100); // sets global variable x to 100
```

```
// Here, because of strict mode, this is undefined
'use strict';
function set(x) {
  this.x = x; // => TypeError
  console.log(x);
};
set(100); // fails due to TypeError
```

# JavaScript

## this binding

```
// Method invocation: this bound to containing object
const myObj = {
  x: 100,
  set: function (x) {
    this.x = x;
    return this;
  },
};
myObj.set(100); // sets myObj.x to 100
console.log(myObj); // Object {x: 100}
console.log(myObj.set(100)); // Object {x: 100}
```

# JavaScript

## this binding

**strict mode** causes different behaviour:

- 'use strict';
- Prevents access to global variable
- **this** undefined
- TypeError generated when code below run in strict mode

```
// Method invocation: this now bound to global object
myObj = {
  x: 0,
  set: function (x) {
    modify(x);
    function modify(val) { // nested function
      this.x = x; // this bound to global obj: undefined in strict mode
    };
  },
};
```



# JavaScript

## this binding

### Arrow function - introduction

```
// What we're familiar with:  
function add(x, y) {  
    return x + y;  
}  
  
console.log(add(10, 20)); // 30
```

```
/**  
 * Alternative approach: arrow function.  
 * @see page 46 ES6 and Beyond (referenced)  
 * @see MDN (referenced)  
 */  
const add2 = (x, y) => x + y;  
console.log(add2(10, 20)); // 30
```

# JavaScript

## this binding

### Pre-ES6 workaround hack

```
'use strict';
let myObj = {
  x: 0,
  set: function (x) {
    let that = this;
    modify(x);
    function modify(val) { // nested function
      that.x = x; // workaround hack
    };
  },
};

myObj.set(100); // myObj.x set to 100
```

# JavaScript

## this binding

Use arrow function to bind inner **this** to containing object

```
//this now bound to containing object myObj
let myObj = {
  x: 0,
  set: function (x) {
    let modify = (val) => { // nested function
      this.x = val; // this now bound to myObj
      console.log(this); // Object{x: 0}
    };

    modify(x);
  },
};

console.log(myObj); // Object{x: 0}

myObj.set(100); // myObj.x set to 100
```

# JavaScript

## this binding

### Another JavaScript booby trap

```
// Okay: Method invocation: this bound to containing object
myObj = {
  x: 0,
  set: function (x) {
    this.x = x;
    return this;
  },
};

console.log(myObj); // Object {x: 0}
console.log(myObj.set(0)); // Object {x: 0}
```

# JavaScript

## this binding

### Another JavaScript booby trap

```
/**
 * Not okay: Alternative approach: arrow function.
 * Method invocation: this now bound to global object
 * @see page 50 ES6 and Beyond (referenced)
 */
myObj = {
  x: 0,
  set: x => {
    this.x = x;
    return this;
  },
};

console.log(myObj); // Object {x: 0}
console.log(myObj.set(0)); // Window {...}
```

# JavaScript

## this binding

### Constructor invocation: not recommended

```
'use strict';  
function Person(name) {  
  this.name = name; // this bound to Person object  
}
```

```
let x = new Person('Jane');  
console.log(x); // Object { name: "Jane" }
```

```
// Omitting 'use strict'  
// If strict mode & new omitted then this undefined  
function Person(name) {  
  this.name = name; // this bound to global object  
}
```

```
let x = Person('Jane'); // Oops! Forgot new keyword  
console.log(x); // undefined
```

# JavaScript

## Passing function as function argument

```
// Passing a named function as an argument
function myFn(fn) {
  const result = fn();
  console.log(result);
};

function myOtherFn() {
  return 'hello world';
};

// logs 'hello world'
myFn(myOtherFn);
```

# Functions

Which to use? Function expression or function statement


```
// Function statements: Airbnb recommendation (ES6)
function outer1() {
  hoisted(); // => foo
  function hoisted() {
    console.log('foo');
  }
}
```

```
// Function expressions: Crockford recommendation (ES5)
let outer2 = function outer2() {
  notHoisted(); // => TypeError: notHoisted is not a function
  let notHoisted = function() {
    console.log('bar');
  };
};
```



# Summary

- Functions
  - First class objects
  - May be assigned to variable
  - Passed as parameters
  - Values in objects
  - Contain other functions
  - The arrow function (ES6)



Except where otherwise noted, this content is licensed under a Creative Commons Attribution-NonCommercial 3.0 License.

For more information, please see <http://creativecommons.org/licenses/by-nc/3.0/>



Waterford Institute of Technology  
INSTITIÚD TEICNEOLAÍOCHTA PHORT LÁIRGE

