


Week-5 Gate-5 Report

Objective :

The objective of this assessment is to stabilize the Playwright automation suite by identifying failures, diagnosing their root causes, validating fixes, and providing supporting evidence. The assessment focuses on writing reliable tests and demonstrating debugging maturity.

Frameworks :



The Above was the Framework which I have used in the following Project.

This assessment covers the following topics:

- Flakiness Analysis
- Diagnostic Logging

- Artifact Management
- Offline & Resilient UI
- Returns & Refund Testing The overall approach followed throughout the assessment is: Diagnose → Fix → Evidence → Explain

diagnostic.fixture.ts

Implemented diagnostic fixtures providing:

- Correlation ID generation
- Structured logging
- Automatic HTTP header injection
- Failure log attachment
- Child logger creation
- Diagnostic log capture

app.fixture.ts

Extended the diagnostic fixture with:

- Evidence collection
- Automatic JSON/text attachment
- Reusable custom fixture

Logging Framework

Implemented a reusable Winston logger featuring:

- Structured logs
- Sensitive data redaction
- Console logging
- Metadata support
- Correlation IDs
- NDJSON log attachment for failed tests

Sensitive information automatically redacted:

- Authorization

- Password
- Token
- CVV
- Card Number

API Helper Layer

Created reusable API helper methods.

Functions include:

- Seed Order
- Refund Order
- Refund Eligibility Check
- Get Refund Ledger
- Open Returns Page
- Generate Idempotency Key

Tools Used :

- Playwright
- TypeScript
- Node.js
- Visual Studio Code
- Git & GitHub

Now I will Provide the tests done in the following project with full evidence in the following document

The first test case I did on refund

I the refund test case we used idempotency Key .

If we haven't used this key the test will fail because if the customer click refund for the two times there may be chance of giving over refund so if use that key it will check the key so it will get to know that it is duplicate refund so it wont do that if we use idempotency Key .

The following was the pic without idempotency Key.

```
Error Context: test-results\refund-refund-security-Ref-58da7--Refuse-the-two-money-leaks-chromium\erro
r-context.md

[chromium] > tests\refund\full-refund.spec.ts:12:7 > Full Refund > Full Refund
[INFO] 2026-07-04T10:10:44.130Z - test finished {"status":"passed"}
[chromium] > tests\refund\partial-refund.spec.ts:12:7 > Partial Refund > Refund Lab
[INFO] 2026-07-04T10:10:44.231Z - Submitting partial refund
[INFO] 2026-07-04T10:10:44.252Z - Ledger verified {"status":"PARTIALLY_REFUNDED","refundCount":1}
[INFO] 2026-07-04T10:10:44.350Z - test finished {"status":"passed"}
  1 failed
  [chromium] > tests\refund\refund-security.spec.ts:11:7 > Refund Security > Refuse the two money leaks
  4 passed (4.7s)

  Serving HTML report at http://localhost:9323. Press Ctrl+C to quit.
  [
```

Q

Search tests

All5

✓ Passed4

✗ Failed1

Flaky0

Skipped0

Project: chromium4/7/2026, 3:40:40 pm Total time: 4.7s

▼ refund/refund-security.spec.ts

✗ Refund Security › Refuse the two money leakschromium494ms
refund/refund-security.spec.ts:11

▼ refund/full-refund.spec.ts

✓ Full Refund › Full Refundchromium1.8s
refund/full-refund.spec.ts:12

▼ refund/partial-refund.spec.ts

✓ Partial Refund › Refund Labchromium2.3s
refund/partial-refund.spec.ts:12

▼ refund/refund-check.spec.ts

✓ Refund Eligibility › Valid refundchromium748ms
refund/refund-check.spec.ts:26

✓ Refund Eligibility › Over refundchromium896ms
refund/refund-check.spec.ts:26

Now the below are the screenshots with idempotency key

The site should be open before it goes to offline.

The below screenshot shows that the test failed if we open website after offline.

```
✓ test.describe("Making Network Offline and Online", () => {
✓   test("Prove the offline banner", async ({ page, context, log, evidence }) => {
✓     // log.info("Opening POS page");
     // await page.goto("/pos");
     // Simulate losing connectivity
     log.info("Switching network to offline");
     await context.setOffline(true);
     log.info("Opening POS page");
     await page.goto("/pos");
  });
});
```

In the following test we are opening the test after going to offline mode so the test will get Failed.

```
Error Context: test-results\pos-network-Making-Network-be84c-ne-Prove-the-offline-banner-chromium\erro
r-context.md

1 failed
[chromium] > tests\pos\network.spec.ts:5:7 > Making Network Offline and Online > Prove the offline ban
ner
2 passed (4.5s)

Serving HTML report at http://localhost:9323. Press Ctrl+C to quit.
```

pos/network.spec.ts		
✗	Making Network Offline and Online > Prove the offline banner chromium	2.4s
	pos/network.spec.ts:5	
✓	Making Network Offline and Online > Rollback a failed optimistic write chromium	1.9s
	pos/network.spec.ts:45	
✓	Making Network Offline and Online > Sync once, even through a flaky reconnect chromium	2.5s
	pos/network.spec.ts:71	

So to make it correct first we need to go to the following webpage then we should go to the offline mode.

```

test.describe("Making Network Offline and Online", () => {
  test("Prove the offline banner", async ({ page, context, log, evidence }) => {
    log.info("Opening POS page");
    await page.goto("/pos");
    // Simulate losing connectivity
    log.info("Switching network to offline");
    await context.setOffline(true);
    await expect(page.getByTestId("network-banner")).toContainText("Offline");
    log.info("Verified offline banner");
  });
});

```

```

[INFO] 2026-07-04T10:27:47.413Z - Verified outbox flushed
[INFO] 2026-07-04T10:27:47.417Z - test finished {"status":"passed"}
[chromium] > tests\pos\network.spec.ts:5:7 > Making Network Offline and Online > Prove the offline banner
[INFO] 2026-07-04T10:27:48.304Z - Queued sale 3
[INFO] 2026-07-04T10:27:48.308Z - Verified outbox contains 3 queued sales
[INFO] 2026-07-04T10:27:48.308Z - Reconnecting network
[INFO] 2026-07-04T10:27:48.358Z - Verified queued sales synced successfully
[INFO] 2026-07-04T10:27:48.363Z - test finished {"status":"passed"}
  3 passed (5.4s)

```

To open last HTML report run:

```
npx playwright show-report
```

C:\Users\299167\Desktop\week-5-gate-5\SDET\week-4-gate4>

Q Search tests

All3

✓ Passed3

Failed0

Flaky0

Skipped0

Project: chromium

4/7/2026, 3:57:43 pm Total time: 5.4s

▼ pos/network.spec.ts

✓ Making Network Offline and Online › Prove the offline bannerchromium3.5s

pos/network.spec.ts:5

✓ Making Network Offline and Online › Rollback a failed optimistic writechromium1.9s

pos/network.spec.ts:43

✓ Making Network Offline and Online › Sync once, even through a flaky reconnectchromium2.6s

pos/network.spec.ts:69

The third test I have done on flaky test.

```
import {test, expect} from "../../fixtures/dignostic.fixture";

// Verify checkout flow remains stable when navigating to the confirmation page
test("flaky", async ({page, log}) => {
  log.info("Flakiness check")
  await page.goto("/catalog")
  await page.getByRole('link', { name: 'View Running Shoes' }).click();
  await page.getByRole('button', { name: 'Add to cart' }).click();
  await page.getByRole('button', { name: 'Proceed to checkout' }).click();
  await page.locator('#coupon-code').fill("UST10");
  await expect(page.locator('.order-summary')).toContainText('-Rs. 450');
  // Allow a little extra time for order submission
  await page.getByRole('button', { name: 'Place order' }).click({timeout:100});
  await expect(page.locator("#confirmation-title")).toHaveText("Thank you for your order")
})
```

I Run the following test for 1 time.

```
C:\Users\299167\Desktop\week-5-gate-5\SDET\week-4-gate4>npx playwright test flaky

Running 1 test using 1 worker
[chromium] > tests\flaky\flaky.spec.ts:5:5 > flaky
[INFO] 2026-07-04T10:44:41.063Z - test started
[INFO] 2026-07-04T10:44:41.065Z - Flakiness check
[INFO] 2026-07-04T10:44:42.190Z - test finished {"status":"passed"}
  1 passed (3.3s)

To open last HTML report run:

  npx playwright show-report
```

Now if I run the following same code to repeat-each = 50 then some times the test got failed.

The Command I used to run the following test for the 50 times is
npx playwright test flaky.spec.ts --repeat-each=50

Q

Search tests

All

50

✓ Passed

10

✗ Failed

40

Flaky

0

Skipped

0

🔄

⚙️

Project: chromium

4/7/2026, 4:15:32 pm Total time: 1.5m

▼ flaky/flaky.spec.ts		
✗ flaky	chromium	2.8s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.3s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.1s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.0s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.0s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.0s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.3s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	2.6s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.1s
flaky/flaky.spec.ts:5		

✗ flaky	chromium	3.9s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.4s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.5s
flaky/flaky.spec.ts:5		
✗ flaky	chromium	3.6s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	2.6s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	2.7s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	3.5s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	3.3s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	4.3s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	3.4s
flaky/flaky.spec.ts:5		
✓ flaky	chromium	3.8s
flaky/flaky.spec.ts:5		

It only got passed for the 10 times remaining all the times it got failed.

The next test case I have done on artifact

artifact means it will store screen shots and video on the failure.

On successfully passing the test we don't get anything

Filter steps

> Before Hooks

1.3s

> Navigate to "/debug-lab" — artifact-management.spec.ts:16

620ms

> Expect "toBeVisible" getByRole("heading", { name: 'Debug Lab' }) — artifact-management.spec.ts:18

88ms

> POST "/api/cart/items" — artifact-management.spec.ts:20

88ms

> GET "/api/cart" — artifact-management.spec.ts:34

3ms

> Expect "toBe" — artifact-management.spec.ts:41

0ms

> Expect "toBe" — artifact-management.spec.ts:42

0ms

> Expect "toMatchObject" — artifact-management.spec.ts:44

1ms

> After Hooks

587ms

> Attachments

> cartResponse.json

> Executed in Worker #2

But if we failed the test we will get Screenshot and videos on the result page

Search tests

All 3 Passed 1 Failed 2 Flaky 0 Skipped 0

Project: chromium4/7/2026, 4:38:34 pmTotal time: 15.7s

> artifact-management.spec.ts

Week 5 Day 3 - Artifact Management > captures cart evidence without attaching it on a passing test

7.7s

artifact-management.spec.ts:13 View Trace

Week 5 Day 3 - Artifact Management > captures cart evidence without attaching it on a passing test

7.5s

artifact-management.spec.ts:13 View Trace

> Navigate to "/debug-lab" — artifact-management.spec.ts:16

668ms

> Expect "toBeVisible" getByRole("heading", { name: 'Debug Lab' }) — artifact-management.spec.ts:18

95ms

> POST "/api/cart/items" — artifact-management.spec.ts:20

69ms

> GET "/api/cart" — artifact-management.spec.ts:34

3ms

> Expect "toBe" — artifact-management.spec.ts:41

3ms


> After Hooks

638ms


> Worker Cleanup

485ms

> Screenshots



You will also get Trace in artifact management



The Following was the Screenshot for the all test cases which I have done

Q Search tests		All 10	✓ Passed 10	Failed 0	Flaky 0	Skipped 0		
Project: chromium			4/7/2026, 4:50:01 pm Total time: 10.9s					
▼ debug/artifact-management.spec.ts								
✓	Artifact Management › captures cart evidence without attaching it on a passing test				chromium	4.4s		
debug/artifact-management.spec.ts:12								
▼ flaky/flaky.spec.ts								
✓	flaky				chromium	5.0s		
flaky/flaky.spec.ts:5								
▼ pos/network.spec.ts								
✓	Making Network Offline and Online › Prove the offline banner				chromium	4.8s		
pos/network.spec.ts:5								
✓	Making Network Offline and Online › Rollback a failed optimistic write				chromium	4.7s		
pos/network.spec.ts:43								
✓	Making Network Offline and Online › Sync once, even through a flaky reconnect				chromium	3.0s		
pos/network.spec.ts:69								
▼ refund/full-refund.spec.ts								
✓	Full Refund › Full Refund				chromium	2.3s		
refund/full-refund.spec.ts:12								
▼ refund/partial-refund.spec.ts								
✓	Partial Refund › Refund Lab				chromium	2.5s		
refund/partial-refund.spec.ts:12								
▼ refund/refund-check.spec.ts								
✓	Refund Eligibility › Valid refund				chromium	1.7s		
refund/refund-check.spec.ts:26								
✓	Refund Eligibility › Over refund				chromium	1.2s		
refund/refund-check.spec.ts:26								
▼ refund/refund-security.spec.ts								
✓	Refund Security › Refuse the two money leaks				chromium	1.2s		
refund/refund-security.spec.ts:11								

Challenges Faced:

- Diagnosing flaky tests
- Handling offline scenarios
- Validating idempotent requests
- Preventing duplicate refunds
- Testing financial calculations
- Capturing useful debugging evidence

Conclusion :

This project demonstrates the development of a robust and maintainable automation testing framework using Playwright and TypeScript. The framework combines UI testing, API testing, and hybrid test scenarios to validate critical retail application workflows, including refund processing, offline synchronization, diagnostics, artifact management, and application stability.

To improve maintainability and scalability, the project uses custom Playwright fixtures, reusable API helper methods, structured logging with Winston, and automatic evidence collection. These components simplify test development, reduce code duplication, and provide detailed diagnostic information for troubleshooting test failures.