

Subjective Questions and Answers

Q1. Why are Playwright test less flaky compared to selenium?

Ans. *Flaky means whenever the test runs sometimes it passes sometimes it fails. Playwright is less weight compared to selenium, it can run with parallel runners and has built in auto waits and it is easy to find the element using locators such as `getByRole()`, `getByLabel()`, `getByText()`. But when it comes to the selenium it is a heavy framework and also here the priority order changes like `By.id()`, `By.className()`, `By.cssSelector()`. So, there might be chance of flaky for finding the locators correctly.*

Q2. Describe the different types of locators available in playwright. Which one do you prefer and why?

Ans. *Playwright has different types of locator, bases on it priority order has shown below:*

`getByRole()` -> This locator is used to find with the roles which are assigned in the html page.

Example: `await expect(page.getByRole("heading", {name: `/title/i` })).toBeVisible();`

`getByLabel()` -> This locator is used to find the element with the label which can also be called as user facing locator.

Example: `await page.getByLabel("email").fill(example@gmail.com);`

`getByText()` -> This locator is used to find the text in the webpage.

Example: `expect(getByText("example")).toBeVisible();`

`getByTestId()` -> This locator is used to find the element by testId.

Example: `await expect(page.getByTestId("xxxx"))).toBeVisible();`

`locator()` -> This is used to find elements using class or by id or by frame locator

`xPath()` -> This is used to find elements using xpath.

Q3. How to handle alerts, dialogues and popups in playwright?

Ans. *Those can be handled using a promise or by creating a constant like:*

```
page.on('dialog', async dialog =>(  
  console.log(dialog.message());  
  await dialog.accept();  
)
```

Q4. How do you debug failing test in playwright test?

Ans. We can debug failing test using traceback or by verify the screenshots on failing.

Or we can run the test by using `-debug` command or by running it in headed mode or by pausing the page in the middle of the code.

Q5. What is the role of `test.describe()`, `test.beforeEach()`, `test.AfterEach()`?

Ans. `Test.describe()` is used to describe the test which we write to know the context of the test.

`Test.beforeEach()` is used to run the method which run before every test.

`Test.AfterEach()` is used to run the method after each test.