

In []:

Dataset Overview

HAM10000 ("Human Against Machine with 10000 training images") dataset - a large collection of multi-source dermatoscopic images of pigmented lesions

The dermatoscopic images are collected from different populations, acquired and stored by different modalities. The final dataset consists of 10015 dermatoscopic images.

It has 7 different classes of skin cancer which are listed below :

- Melanocytic nevi
- Melanoma
- Benign keratosis-like lesions
- Basal cell carcinoma
- Actinic keratoses
- Vascular lesions
- Dermatofibroma

Importing libraries

In []:

```
import seaborn as sns
import pandas as pd
import matplotlib.pyplot as plt
from imblearn.over_sampling import RandomOverSampler
import numpy as np
from sklearn.model_selection import train_test_split
import os, cv2
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Conv2D, Flatten, Dense, MaxPool2D, Activation
from sklearn.metrics import classification_report, accuracy_score
```

Reading the Data

In []:

```
data = pd.read_csv('/kaggle/input/skin-cancer-mnist-ham10000/hmnist_28_28_RGB.csv')
data.head()
```

Data Preprocessing

Data Cleaning

In []:

```
data['label'].unique()
```

In []:

```
y = data['label']
x = data.drop(columns = ['label'])
```

```
In [ ]:
```

```
data.isnull().sum().sum() #no null values present
```

```
In [ ]:
```

```
meta_data = pd.read_csv('/kaggle/input/skin-cancer-mnist-ham10000/HAM10000_metadata.csv')
meta_data.head()
```

```
In [ ]:
```

```
meta_data['dx'].unique()
```

```
In [ ]:
```

```
y = data['label']
x = data.drop(columns = ['label'])
```

```
In [ ]:
```

```
data.isnull().sum().sum() #no null values present
```

```
In [ ]:
```

```
meta_data = pd.read_csv('/kaggle/input/skin-cancer-mnist-ham10000/HAM10000_metadata.csv')
meta_data.head()
```

```
In [ ]:
```

```
meta_data['dx'].unique()
```

Exploratory Data Analysis

```
In [ ]:
```

```
sns.countplot(x = 'dx', data = meta_data)
plt.xlabel('Disease(Classes)', size=12)
plt.ylabel('Frequency', size=12)
plt.title('Frequency Distribution of Classes')
```

```
In [ ]:
```

```
sns.set_style('whitegrid')
colors = ['#87ace8', '#e3784d', 'green']
fig, axes = plt.subplots(figsize=(8,8))

ax = sns.countplot(x='sex', data=meta_data, palette = 'Paired')
for container in ax.containers:
    ax.bar_label(container)
plt.title('Gender-wise Distribution')
plt.xticks(rotation=45)
plt.show()
```

```
In [ ]:
```

```
sns.set_style('whitegrid')
fig, axes = plt.subplots(figsize=(12,8))
ax = sns.countplot(x='dx', data=meta_data, order = meta_data['dx'].value_counts().index,
palette = 'Paired')
for container in ax.containers:
    ax.bar_label(container)
plt.title('Cell Types Skin Cancer Affected patients')
plt.xticks(rotation=45)
plt.show()
```

```
In [ ]:
```

In []:

```
classes = {2:'bkl', 4:'nv', 3:'df', 6:'mel', 5:'vasc', 1:'bcc', 0:'akiec'}

classes_labels=[]
for key in classes.keys():
    classes_labels.append(key)
print(classes_labels)
```

In []:

```
sns.set_style('whitegrid')
fig,axes = plt.subplots(figsize=(12,8))
ax = sns.countplot(x='dx',hue='sex', data=meta_data, order = meta_data['dx'].value_counts().index, palette = 'Paired')
for container in ax.containers:
    ax.bar_label(container)
plt.title('Cell Types Frequencies')
plt.xticks(rotation=45)
plt.show()
```

In []:

```
sns.set_style('whitegrid')
fig,axes = plt.subplots(figsize=(12,8))
ax = sns.countplot(x='localization',data=meta_data, order = meta_data['localization'].value_counts().index, palette = 'crest')
for container in ax.containers:
    ax.bar_label(container)
plt.title('Localization Area Frequencies')
plt.xticks(rotation=45)
plt.show()
```

In []:

```
sns.set_style('whitegrid')
fig,axes = plt.subplots(figsize=(12,8))
ax = sns.histplot(data=meta_data, x='age')
plt.title('Age Histogram')
plt.show()
```

In []:

```
sns.set_style('whitegrid')
fig,axes = plt.subplots(figsize=(12,8))
ax = sns.histplot(data=meta_data, x='age',hue='sex',multiple='stack')
plt.title('Age Histogram Gender Wise')
plt.show()
```

In []:

```
print(x.shape,y.shape)
# To overcome class imbalance
oversample = RandomOverSampler()
x,y = oversample.fit_resample(x,y)
print(x.shape,y.shape)
```

In []:

```
# reshaping the data so that it can be taken by convolution neural network(without disturbing the no. of samples)
x = np.array(x).reshape(-1,28,28,3)
print('Shape of X :',x.shape)
print('Shape of y :',y.shape)
```

In []:

```
# Splitting Data
```

```
X_train, X_test, Y_train, Y_test = train_test_split(x,y, test_size=0.2, random_state=1)
print(X_train.shape,Y_train.shape)
print(X_test.shape , Y_test.shape)
```

In []:

```
model_CNN = Sequential()
model_CNN.add(Conv2D(16, kernel_size = (3,3), input_shape = (28, 28, 3), activation = 'relu', padding = 'same'))
model_CNN.add(MaxPool2D(pool_size = (2,2)))

model_CNN.add(Conv2D(32, kernel_size = (3,3), activation = 'relu', padding = 'same'))
model_CNN.add(MaxPool2D(pool_size = (2,2), padding = 'same'))

model_CNN.add(Conv2D(64, kernel_size = (3,3), activation = 'relu', padding = 'same'))
model_CNN.add(MaxPool2D(pool_size = (2,2), padding = 'same'))
model_CNN.add(Conv2D(128, kernel_size = (3,3), activation = 'relu', padding = 'same'))
model_CNN.add(MaxPool2D(pool_size = (2,2), padding = 'same'))

model_CNN.add(Flatten())
model_CNN.add(Dense(64, activation = 'relu'))
model_CNN.add(Dense(32))
model_CNN.add(Activation(activation='relu'))
model_CNN.add(Dense(7))
model_CNN.add(Activation(activation='softmax'))

optimizer = tf.keras.optimizers.Adam(learning_rate = 0.001)

model_CNN.compile(loss = 'sparse_categorical_crossentropy',
                  optimizer = optimizer,
                  metrics = ['accuracy'])
print(model_CNN.summary())
```

In []:

```
from tensorflow.keras.callbacks import ReduceLRonPlateau, EarlyStopping
early_stop = EarlyStopping(monitor='val_loss', patience=10, verbose=1, mode='auto')
reduce_lr = ReduceLRonPlateau(monitor='val_loss', factor=0.1, patience=3, verbose=1, mode='auto')
history = model_CNN.fit(X_train,
                        Y_train,
                        validation_split=0.2,
                        batch_size = 64,
                        epochs = 50,
                        callbacks = [reduce_lr, early_stop])
```

In []:

```
results = model_CNN.evaluate(X_test , Y_test, verbose=0)

print("CNN Model Test Results")
print("      Test Loss: {:.5f}".format(results[0]))
print("      Test Accuracy: {:.2f}%".format(results[1] * 100))
```

In []:

```
plt.plot(history.history['accuracy'])
plt.plot(history.history['val_accuracy'])
plt.title('model accuracy')
plt.ylabel('accuracy')
plt.xlabel('epoch')
plt.legend(['train', 'val'], loc='upper left')
plt.show()
```

In []:

```
plt.plot(history.history['loss'])
plt.plot(history.history['val_loss'])
plt.title('model loss')
plt.ylabel('loss')
plt.xlabel('epoch')
```

```
plt.legend(['train', 'val'], loc='upper right')
plt.show()
```

In []:

```
from sklearn.metrics import confusion_matrix , classification_report

y_true_CNN = list(Y_test)
y_pred_CNN = model_CNN.predict(X_test)
y_pred_CNN = list(map(lambda x: np.argmax(x), y_pred_CNN))
print("Predicting First Ten Rows:")
print('Y Actual Values :' , y_true_CNN[0:10])
print('Y Predicted Values :' , y_pred_CNN[0:10])
```

In []:

```
cm_CNN = confusion_matrix(y_true_CNN,y_pred_CNN,labels=classes_labels)
print(confusion_matrix(y_true_CNN,y_pred_CNN,labels=classes_labels))
sns.heatmap(cm_CNN, annot = True, fmt='')
```

In []:

```
#training acc vs testing acc graph
plt.plot(history.history["accuracy"] , 'ro-' , label = "Training Accuracy")
plt.plot(history.history["val_accuracy"] , 'go-' , label = "Testing Accuracy")
plt.legend()
plt.show()
```

In []:

```
#predicting
y_pred_CNN = model_CNN.predict(X_test)
target_names = [f"{classes[i]}" for i in range(7)]
y_pred_CNN = list(map(lambda x: np.argmax(x), y_pred_CNN))
print("CNN Model Prediction Results")
print(classification_report(Y_test , y_pred_CNN,target_names=target_names))
```

In []:

```
# Layers definitions
from keras import backend as K
for l in range(len(model_CNN.layers)):
    print(l, model_CNN.layers[l])
```

In []:

```
model_CNN.layers[-2]
```

In []:

```
import os
os.environ["KERAS_BACKEND"] = "tensorflow"
kerasBKED = os.environ["KERAS_BACKEND"]
print(kerasBKED)
```

Separating Features Layers from the CNN Model

In []:

```
import tensorflow as tf
# feature_extractor = tf.keras.Model(inputs=model_CNN.input,
#                                     outputs=model_CNN.get_layer(-2).output)
# output_layers_model =tf.keras.Model(inputs=model_CNN.input, outputs=model_CNN.output)
# cnn_layer_output = model_CNN.layers[-2].output
# cnn_model_features = tf.keras.Model(inputs=model_CNN.input, outputs=cnn_layer_output)
cnn_model_features = tf.keras.Model(inputs=model_CNN.input, outputs=model_CNN.layers[-3]
                                     .output)
```

Extracting Features from CNN Model

In []:

```
# Extract features from input data using the CNN model
X_train_cnn = cnn_model_features.predict(X_train)
X_test_cnn = cnn_model_features.predict(X_test)
```

Integrating CNN with SVM Classifier using Grid Search for Best Parameters

In []:

```
import numpy as np
from sklearn.svm import SVC
from sklearn.model_selection import GridSearchCV

parameters = {'kernel':['rbf'],
              'C':[1, 10, 100, 1000],
              'gamma':[1e-3, 1e-4]}
clf = GridSearchCV(SVC(), parameters)
clf.fit(X_train_cnn, Y_train)
# Evaluate the combined CNN-SVM model on a test dataset
svm_accuracy = clf.score(X_test_cnn, Y_test)
print('SVM Accuracy:', svm_accuracy*100)
y_testSVM = clf.predict(X_test_cnn)
```

In []:

```
svm_accuracy = clf.score(X_test_cnn, Y_test)
print('SVM Accuracy:', svm_accuracy*100)
svmclf = clf.best_estimator_
print(svmclf)
svmclf.fit(X_train_cnn, Y_train)
print("Accuracy: {0}".format(accuracy_score(Y_test, y_testSVM)*100))
```

In []:

```
y_testSVM = svmclf.predict(X_test_cnn)
from sklearn.metrics import confusion_matrix, classification_report, accuracy_score

print(classification_report(Y_test, y_testSVM, target_names=target_names))
print("Accuracy: {0}".format(accuracy_score(Y_test, y_testSVM)*100))
```

In []:

Integrating CNN with Random Forest Classifier using Grid Search for Best Parameters

In []:

```
from sklearn.ensemble import RandomForestClassifier
from sklearn.model_selection import GridSearchCV

parameters = {"max_depth": [3, None],
              "max_features": [1, 3, 10],
              "min_samples_split": [1.0, 3, 10],
              "min_samples_leaf": [1, 3, 10],
              "bootstrap": [True, False],
              "criterion": ["gini", "entropy"],
              "n_estimators": [10, 20, 50]}

rclf = RandomForestClassifier()
rgclf = GridSearchCV(rclf, param_grid=parameters)
rgclf.fit(X_train_cnn, Y_train)
```

```
RFC_accuracy = rgclf.score(X_test_cnn, Y_test)
print('Random Forest Classifier Accuracy:', RFC_accuracy*100)
y_test_RF = rgclf.predict(X_test_cnn)
print("Accuracy: {0}".format(accuracy_score(Y_test, y_test_RF)*100))
```

In []:

```
y_test_RF = rgclf.predict(X_test_cnn)
print("Accuracy: {0}".format(accuracy_score(Y_test, y_test_RF)*100))
RFclf = rgclf.best_estimator_
RFclf.fit(X_test_cnn, Y_test)
print(RFclf)
y_testRFC = RFclf.predict(X_test_cnn)
from sklearn.metrics import confusion_matrix, classification_report, accuracy_score

print(classification_report(Y_test, y_testRFC, target_names=target_names))
print("Accuracy: {0}".format(accuracy_score(Y_test, y_testRFC)*100))
```

Integrating CNN with KNN Classifier using Grid Search for Best Parameters

In []:

```
from sklearn.neighbors import KNeighborsClassifier
from sklearn.model_selection import GridSearchCV

parameters = {"n_neighbors": [1, 5, 10, 30],
              "weights": ['uniform', 'distance'],
              "metric": ['minkowski', 'euclidean', 'manhattan'],
              "algorithm": ['auto', 'ball_tree', 'kd_tree', 'brute']}

kclf = KNeighborsClassifier()
kgclf = GridSearchCV(kclf, param_grid=parameters)
kgclf.fit(X_train_cnn, Y_train)
KNN_accuracy = kgclf.score(X_test_cnn, Y_test)
print('KNN Classifier Accuracy:', KNN_accuracy*100)
```

In []:

```
y_testKNN = kgclf.predict(X_test_cnn)
KNNclf = kgclf.best_estimator_
print(KNNclf)
from sklearn.metrics import confusion_matrix, classification_report, accuracy_score

print(classification_report(Y_test, y_testKNN, target_names=target_names))
print("Accuracy Score: {0}".format(accuracy_score(Y_test, y_testKNN)*100))
```

Integrating CNN with Logistic Regression Classifier using Grid Search for Best Parameters

In []:

```
from sklearn.linear_model import LogisticRegression
from sklearn.model_selection import GridSearchCV
from sklearn.metrics import accuracy_score
from sklearn.metrics import confusion_matrix, classification_report, accuracy_score

# Create a logistic regression object
lr = LogisticRegression()

# Define the hyperparameter grid to search over
param_grid = {'C': [0.001, 0.01, 0.1, 1, 10, 100],
              'penalty': ['l1', 'l2']}

# Perform grid search with 5-fold cross-validation
grid_search_LR = GridSearchCV(lr, param_grid, cv=5)
```

```
grid_search_LR.fit(X_train_cnn, Y_train)

# Print the best hyperparameters and the corresponding accuracy score
print("Best hyperparameters: ", grid_search_LR.best_params_)
y_test_LR = grid_search_LR.predict(X_test_cnn)

print(classification_report(Y_test, y_test_LR, target_names=target_names))
print("Accuracy: {0}".format(accuracy_score(Y_test, y_test_LR)*100))
```

In []:

In []:

In []:

In []: