

An Experience with Text Classification in *Datadays 2019*

Majid Hajiheidari Amirmohammad Asadi

April, 2019

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Divar Posts Dataset

- ▶ Released for DataDays 2019
- ▶ One million posts

بارگشت همه آگهی ها / املاک / اجاره مسکونی (آپارتمان، خانه، زمین) / آپارتمان



190متر/4خواب/فول محدوده کاج
دقایقی پیش

نشان کردن

شروع چت

دریافت اطلاعات تماس

آپارتمان	دسته بندی
تهران سعادت آباد	محل
ارائه	نوع آگهی
شخصی	آگهی دهنده
چهار	تعداد اتاق
۱۹۰	متراژ

بارگشت همه آگهی ها / سرگرمی و فراغت / دوچرخه/اسکیت/اسکوتر

بارگشت همه آگهی ها / سرگرمی و فراغت / دوچرخه/اسکیت/اسکوتر



دوچرخه مریدا 7-300 سال ۲۰۱۷
۲ ساعت پیش

نشان کردن

شروع چت

دریافت اطلاعات تماس

دوچرخه/اسکیت/اسکوتر	دسته بندی
تهران میدان آزادی	محل
فروشی	نوع آگهی
۵/۸۰۰/۰۰۰ تومان	قیمت

با سلام یک دستگاه دوچرخه مریدا 7-300 سال ۲۰۱۷ در حد آک ایک سایز 27/5 تنه 18/5 با کمک باد ست اورژم دنده=طوق و

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Columns

- ▶ id
- ▶ archive_by_user
- ▶ published_at
- ▶ **cat1**
- ▶ **cat2**
- ▶ **cat3**
- ▶ city
- ▶ **title**
- ▶ **desc**
- ▶ price
- ▶ image_count
- ▶ platform
- ▶ mileage
- ▶ brand
- ▶ year
- ▶ type

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

The Problem: Categorization

- ▶ We need to categorize posts based on other posts features;
- ▶ We only use text features(title & description)!

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
TF-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Features

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

No. of Classes

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Feature Extraction

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Feature extraction is a dimensionality reduction process, where an initial set of raw variables is reduced to more manageable groups (features) for processing, while still accurately and completely describing the original data set.

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Vectorizing the Text: Count Vectorizer

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

An example: We want to vectorize these 4 sentences¹:

1. Hello, how are you!
2. Win money, win from home.
3. Call me now
4. Hello, Call you tomorrow?

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

¹Example from Rahul Vasaikar

Vectorizing the Text: Count Vectorizer

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

1. We first build a vocabulary:

vocabulary =

{are, call, from, hello, home, how, me, money, now, tomorrow, win, you}

2. Then, we vectorize each sentence based on the occurness of each word:

	are	call	from	hello	home	how	me	money	now	tom...	win	you
1	1	0	0	1	0	1	0	0	0	0	0	1
2	0	0	1	0	1	0	0	1	0	0	2	0
3	0	1	0	0	0	0	1	0	1	0	0	0
4	0	1	0	1	0	0	0	0	0	1	0	1

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
TF-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Vectorizing the Text: Count Vectorizer

N pair of samples

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
TF-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Tf-idf Vectoizer

- ▶ Tf-idf stands for term frequency-inverse document frequency
- ▶ a statistical measure used to evaluate how important a word is to a document in a collection or corpus
- ▶ the tf-idf weight is composed by two terms:

TF Term Frequency, which measures how frequently a term occurs in a document.

$$TF(t) = \frac{\text{Number of times term } t \text{ appears in a document}}{\text{Total number of terms in the document}}$$

IDF Inverse Document Frequency, which measures how important a term is

$$IDF(t) = \ln \frac{\text{Total number of documents}}{\text{Number of documents with term } t \text{ in it}}$$

Tf-idf Vectorizer: An Example

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Consider a document containing 100 words wherein the word *cat* appears 3 times. The term frequency (i.e., *tf*) for *cat* is then $tf(cat) = \frac{3}{100} = 0.03$. Now, assume we have 10 million documents and the word *cat* appears in one thousand of these. Then, the inverse document frequency (i.e., *idf*) is calculated as $idf(cat) = \ln \frac{10,000,000}{1,000} = 4$. Thus, the Tf-idf weight is the product of these quantities: $tf - idf(cat) = 0.03 * 4 = 0.12$.

Temp Frame

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer

Tf-idf Vectorizer

Embedding

Classification
Algorithms

Naive Bayes

CNN

Linear SVM

Passive Aggressive

A Comparison
among Models

The End

Classification Algorithms

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

We used different classifiers and applied different models on the data. The classifiers we tested are:

- ▶ Naive Bayes
- ▶ Linear Support Vector Machine(SVM)
- ▶ Passive Aggressive
- ▶ Convolutional Neural Network(CNN)

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Naive Bayes Classifier



$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

Photo by Matt Buck



An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Bayes Classifier: Naive One!

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

It is possible to show that accuracy is minimized, on average, by a very simple classifier that assigns each observation to the most likely class, given its predictor values. In other words, we should simply assign a test observation with predictor vector \mathbf{x}_0 to the class j for which

$$P(Y = j \mid \mathbf{X} = \mathbf{x})$$

is largest.

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Bayes Classifier: Naive One!

We make two assumptions:

1. X_1, X_2, \dots , and X_m are independent from each other;
2. $X_1, X_2, \dots, X_m \mid Y \sim MN(\cdot, p_1, p_2, \dots, p_m)$

$$\begin{aligned} P(Y = j \mid \mathbf{X} = (x_1, x_2, \dots, x_m)) &= \frac{P(\mathbf{X} = (x_1, x_2, \dots, x_m) \mid Y = j) \cdot P(Y = j)}{P(\mathbf{X} = \mathbf{x})} \\ &= \frac{P(X_1 = x_1 \mid Y = j) \cdot \dots \cdot P(X_m = x_m \mid Y = j) \cdot P(Y = j)}{P(\mathbf{X} = \mathbf{x})}. \end{aligned}$$

$$\begin{aligned} \hat{y} &= \arg \max_{j \in \text{classes}} \frac{P(X_1 = x_1 \mid Y = j) \cdot \dots \cdot P(X_m = x_m \mid Y = j) \cdot P(Y = j)}{P(\mathbf{X} = \mathbf{x})} \\ &= \arg \max_{j \in \text{classes}} P(X_1 = x_1 \mid Y = j) \cdot \dots \cdot P(X_m = x_m \mid Y = j) \cdot P(Y = j). \end{aligned}$$

Bayes Classifier: Naive One!

Let's dive into code!

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Hyperparameters

Two important hyperparameters:

1. Size of the vocabulary;
2. Laplace/ Lidstone smoothing parameter(α).

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
TF-idf Vectorizer
Embedding


Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Size of Vocabulary



It is convex! (to be completed)

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes

CNN


Linear SVM

Passive Aggressive

A Comparison
among Models

The End

Laplace/ Lidstone Smoothing Parameter(α)



It is convex! (to be completed)

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes

CNN

Linear SVM

Passive Aggressive

A Comparison
among Models

The End

Grid Search

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes

CNN

Linear SVM

Passive Aggressive

A Comparison
among Models

The End

Temp Frame

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Temp Frame

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Temp Frame

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Temp Frame

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Linear SVM

- ▶ A non-probabilistic classifier
- ▶ A discriminative classifier formally defined by a separating hyperplane
- ▶ The algorithm outputs an optimal hyperplane which categorizes new examples
- ▶ A good separation is achieved by the hyperplane that has the largest distance to the nearest training-data point of any class

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN

Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Linear SVM: Behind the Scene

Given training vectors $x_i \in \mathbb{R}^p$, $i=1, \dots, n$, in two classes, and a vector $y \in \{1, -1\}^n$, SVM classifier solves the following primal problem:

$$\begin{aligned} \min_{w, b, \zeta} \quad & \frac{1}{2} w^T w + C \sum_{i=1}^n \zeta_i \\ \text{subject to} \quad & y_i (w^T \phi(x_i) + b) \geq 1 - \zeta_i, \\ & \zeta_i \geq 0, i = 1, \dots, n \end{aligned}$$

Its dual is:

$$\begin{aligned} \min_{\alpha} \quad & \frac{1}{2} \alpha^T Q \alpha - e^T \alpha \\ \text{subject to} \quad & y^T \alpha = 0 \\ & 0 \leq \alpha_i \leq C, i = 1, \dots, n \end{aligned}$$

Linear SVM: Behind the Scene(cont'd)

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

where e is the vector of all ones, $C > 0$ is the upper bound, Q is an n by n positive semidefinite matrix, $Q_{ij} \equiv y_i y_j K(x_i, x_j)$, where $K(x_i, x_j) = \phi(x_i)^T \phi(x_j)$ is the kernel. Here, training vectors are implicitly mapped into a higher (maybe infinite) dimensional space by the function ϕ . The decision function is:

$$\text{sgn}\left(\sum_{i=1}^n y_i \alpha_i K(x_i, x) + \rho\right)$$

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN

Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Temp Frame

This slide is temp.

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End

Thanks for your attention!

Codes in slides (in my GitHub):(github link)

Divar posts dataset:(divar link)

Any questions?

An Experience
with Text
Classification in
Datadays 2019

Majid Hajiheidari,
Amirmohammad
Asadi

Introduction:
Divar Dataset

The Problem:
Categorization

Feature Extraction

Count Vectorizer
Tf-idf Vectorizer
Embedding

Classification
Algorithms

Naive Bayes
CNN
Linear SVM
Passive Aggressive

A Comparison
among Models

The End