

SQL queries for the queries in Q. 8.16

- a.
SELECT FNAME, LNAME
FROM EMPLOYEE, WORKS-ON, PROJECT
WHERE SSN = ESSN AND PNO = PNUMBER AND
PNO = 5 AND PNAME = 'PRODUCTX' AND HOURS > 10;
- b.
SELECT FNAME, LNAME
FROM EMPLOYEE, DEPENDENT
WHERE SSN = ESSN AND FNAME = DEPENDENT-NAME;
- c.
SELECT E.FNAME, E.LNAME
FROM EMPLOYEE E, S
WHERE E.SUPERSSN = S.SSN AND
S.FNAME = 'FRANKLIN' AND S.LNAME = 'DONG';
- d.
SELECT PNAME, SUM(HOURS)
FROM PROJECT, WORKS-ON
WHERE PNUMBER = PNO
GROUP BY PNAME;
- e.
SELECT E.FNAME, E.LNAME
FROM EMPLOYEE E
WHERE NOT EXISTS
(SELECT *
FROM PROJECT
WHERE PNUMBER NOT IN (SELECT PNO
FROM WORKS-ON
WHERE ESSN = E.SSN));



g.

h.

j.

```
SELECT  LNAME
FROM    EMPLOYEE, DEPARTMENT
WHERE   SSN = MGRSSN
        AND SSN NOT IN (SELECT ESSN
                        FROM DEPENDENT);
```

k.

```
SELECT  E.FNAME, E.LNAME, E.ADDRESS
FROM    EMPLOYEE E
WHERE   EXISTS (SELECT *
                FROM WORKS_ON, PROJECT
                WHERE PNO = PNUMBER AND
                       E.SSN = ESSN AND
                       PLOCATION NOT IN
                           (SELECT DLOCATION
                            FROM DEPT_LOCATIONS
                            WHERE E.DNO = DNUMBER));
```

- k. Generalize Query i above to list the names and addresses of employees who work on a project in one city but whose department has no location in that city.