

DEVELOPMENT OF AUTOMATED MOBILE ROBOTIC ARM VEHICLE FOR COLD STORAGE OPERATIONS

**Mr. Girish A. Patil^{*1}, Mr. Subodh S. Bhosale^{*2}, Mr. Omkar A. Pore^{*3},
Mr. Utkarsh S. Jadhav^{*4}, Mr. Sunil S. Dhargude^{*5}, Mr. Suraj. H. Kumbhar^{*6}**

^{*1,2,3,4,5,6}Department Of Mechanical Engineering, Vidya Pratishthan's Kamalnayan Bajaj Institute Of Engineering And Technology, Baramati, (Savitribai Phule Pune University), Maharashtra, India.

DOI: <https://www.doi.org/10.56726/IRJMETS75091>

ABSTRACT

The development of an innovative autonomous mobile robotic arm designed specifically for cold storage environments, aiming to enhance operational efficiency, precision, and safety. The system integrates advanced servo control, environmental sensing, and autonomous navigation to perform critical tasks such as picking, sorting, and storing temperature-sensitive items in sub-zero conditions. Adaptable to various storage configurations, the robotic arm ensures the safe handling of delicate goods through dynamic path planning and real-time feedback mechanisms. It addresses key challenges faced by industries like food logistics and pharmaceuticals, where maintaining product integrity and compliance is essential. By reducing the need for human intervention in extreme environments, the system improves worker safety, increases task reliability, and contributes to long-term cost savings. This technological advancement marks a significant step toward smarter more resilient, and sustainable warehouse automation in cold chain logistics.

I. INTRODUCTION

This study introduces an autonomous mobile robotic arm specifically engineered for cold storage applications, aiming to improve handling efficiency and operational safety in low-temperature environments. Designed to autonomously traverse cold storage facilities, the system performs tasks such as object identification, sorting, and placement with minimal human intervention. Its adaptive design accommodates different warehouse layouts and ensures the safe manipulation of fragile, temperature-sensitive items. This technology is particularly significant for industries like pharmaceuticals and food processing, where preserving product quality is paramount. By reducing human exposure to freezing conditions and enhancing process accuracy, the robotic arm boosts productivity and lowers operational costs.

II. LITERATURE REVIEW

2.1 Environmental and Operational Barriers in Cold Storage Automation

Cold storage environments introduce challenges beyond low temperatures. Singh et al. (2020) highlight that condensation and ice formation can cause slippage, wear, and sensor errors. Reduced visibility due to fogging or frost further disrupts vision-based systems (Patel & Huang, 2021). Automation in such conditions demands sealed hardware, thermal regulation, and redundant sensors to ensure reliable operation. Additionally, prolonged exposure to cold can degrade adhesive properties, cable flexibility, and actuator responsiveness, impacting overall system performance. Therefore, cold storage automation must account for both environmental and material degradation factors.

2.2 Technological Gaps in Existing Robotic Solutions

Most robotic systems are not engineered for sub-zero conditions, lacking insulation and hardened components for cold storage use (Nguyen et al., 2022). Moreover, wireless communication can degrade due to insulation and metallic structures (Choudhary & Iqbal, 2020), hindering coordination. Battery efficiency also drops significantly in low temperatures, reducing operating time and requiring frequent maintenance or energy management strategies. To meet the unique demands of cold chain logistics, next-generation robotic systems must incorporate both environmental hardening and intelligent energy optimization.

2.3 Mobile Robotic Arms in Logistics and Cold Storage

Mobile robotic arms combine the advantages of mobility and precise manipulation, making them suitable for warehouse automation. Wurman et al. (2017) explored their integration in large-scale logistics for improved

order fulfillment and inventory handling. Despite their success in general applications, these robots are rarely used in sub-zero environments. Gupta et al. (2023) demonstrated that AI-enabled mobile manipulators improve automation but acknowledged that thermal durability and component insulation are still areas requiring further innovation.

2.4 Vision and Object Recognition under Cold Conditions

Effective object recognition is critical for robotic systems, particularly in cluttered or variable warehouse environments. Convolutional Neural Networks (CNNs) have been widely implemented for image classification and object localization. However, cold storage environments pose challenges such as fogged lenses, low lighting, and frost accumulation. Research by Chen et al. (2021) emphasizes the need for specialized vision systems in such settings. To overcome these issues, Huang et al. (2022) recommend sensor fusion techniques that combine infrared cameras, thermal sensors, and traditional RGB imaging to maintain performance in visually impaired conditions.

2.5 Navigation and Mapping in Cold Storage

Accurate and reliable navigation is crucial for mobile systems in environments with narrow aisles and reflective surfaces. LiDAR combined with SLAM (Simultaneous Localization and Mapping) has proven effective in creating real-time spatial maps. However, cold storage settings introduce unique problems, such as signal distortion due to reflective surfaces or obstruction from ice and frost. Research by Thrun et al. (2020) supports the use of multisensor systems that integrate LiDAR, thermal, and ultrasonic sensors to improve navigation accuracy under challenging conditions. Park et al. (2023) further suggest the implementation of adaptive filtering algorithms for error correction in icy and low-light scenarios.

2.6 Real-Time Environmental Adaptation in Robotics

Environmental variability is a key issue in cold storage automation. Adaptive robotics equipped with AI can respond dynamically to these changes. Khatib (2022) explored adaptive control strategies in robotic manipulators, enabling them to modify their behavior based on external inputs like temperature or mechanical stress. Similarly, Liu et al. (2023) applied reinforcement learning techniques to robotic systems, allowing them to self-adjust their movements and control parameters through experience, thereby increasing reliability and reducing the need for human intervention.

The development of an Automated Mobile Robotic Arm for Cold Storage Operations follows a structured and systematic approach to ensure efficient material handling, precise object recognition, and real-time adaptation to harsh environmental conditions. The process involves a series of research, design, prototyping, testing, and optimization phases to create a reliable and cost-effective robotic solution tailored for cold storage warehouse automation.

Literature Review & Problem Identification:

Problem Identification:

To ensure efficiency and safety in cold storage operations, robotic systems must overcome environmental and technological challenges. Below are the key issues currently limiting automation in sub-zero logistics environments:

1. Environmental Challenges in Cold Storage

Temperature Extremes: Components face thermal stress; plastics may fracture, lubricants become ineffective, and energy sources like Li-ion batteries show poor performance.

Condensation and Frost Accumulation: Moisture due to temperature fluctuations can lead to corrosion and short circuits in unprotected electronics.

Visibility and Illumination Issues: Dim lighting and frequent fogging significantly hinder optical sensors, LiDAR units, and cameras, impacting navigation and perception.

2. Limitations of Existing Robotics Solutions

Stationary AS/RS Systems: Conventional systems are fixed and unsuitable for environments requiring adaptive and flexible logistics handling.

Autonomous Mobile Robot Constraints: AMRs require significant retrofitting to handle sub-zero conditions, including specialized casings and weatherproof sensor arrays.

Lack of Integrated Mobility and Manipulation: Current robotic arms in warehousing lack autonomous navigation and cold-environment readiness, limiting their effectiveness in integrated pick-and-place operations.

Key Development Phases:**1. Research & Requirements Analysis**

An in-depth investigation of the thermal, mechanical, and operational challenges specific to cold storage environments. This phase focused on identifying viable materials, robust sensor suites, and AI-based solutions (e.g., object recognition and LiDAR-based mapping). Emphasis was placed on reinforcement learning for dynamic adaptability.

2. Design & System Architecture

Creation of a comprehensive system design integrating a mobile base and robotic arm, optimized for maneuverability and thermal insulation. AI-driven object detection algorithms and onboard processing modules were embedded for autonomous operations. Protective housings and internal heating mechanisms were proposed to maintain operational integrity.

3. Prototyping & Hardware Integration

Fabrication of the robotic platform using industrial-grade components suitable for extreme temperatures. Integration of multi-sensor systems—LiDAR, depth cameras, and AI vision modules—alongside a reinforced mechanical frame and adaptive end-effector mechanisms.

4. Testing & Performance Evaluation

Laboratory and cold-room testing were conducted to simulate real warehouse environments. Evaluations were carried out for gripping accuracy, navigation robustness, power consumption, and thermal resistance. Special attention was given to joint torque and energy management to maintain uptime during prolonged operations.

5. Optimization & Deployment

Improvements to AI object detection and motion planning algorithms were made based on performance feedback. System integration with warehouse management systems (WMS) was completed to enable seamless logistics automation. Final tuning focused on ensuring reliable autonomous behavior with minimal human supervision.

III. MODELING AND WORKING**Design Explanation: 1. Structural Design**

Material Selection: The robotic arm is primarily constructed using 3D-printed thermoplastics such as PLA or ABS. These materials are chosen due to their favorable strength-to-weight ratio, ease of fabrication, and moderate thermal insulation—beneficial for cold storage applications.

Articulated Framework: The arm is composed of modular and articulated segments, inspired by industrial robotic manipulators. This modularity enhances range of motion and simplifies maintenance or upgrades.

Compact Configuration: The components are arranged to minimize space while maintaining full functional capability, critical in cluttered or narrow cold storage layouts.

2. Actuation and Motion

Servo-Based Actuation: Multiple servo motors are strategically placed to actuate each joint independently, providing multi-degree-of-freedom (DOF) movement across the arm. These are enclosed in protective housings to shield from cold-induced brittleness and condensation.

Gear Transmission System: A precisely meshed gear train embedded in the base supports rotational movements of the entire arm structure, offering smooth transitions and precise angular positioning, even under load.

3. Mechanical Linkages

Parallel Linkage Mechanism: The arm employs a parallel linkage setup, ensuring consistent angular motion at the end-effector and maintaining horizontal alignment—a necessity for accurate grasping and placement.

Reinforced Joints: High-stress pivot points are bolstered using metallic bolts and threaded fasteners to mitigate mechanical wear and enhance operational durability, especially during repetitive cycles.

4. End-Effector (Gripper)

Adaptive Gripper System: The end effector consists of a claw-type gripper actuated by a micro-servo. The gripper is designed to adapt to objects of varying sizes and shapes, including cold or slippery surfaces. Optional configurations such as vacuum suction or electromagnetic gripping are supported for application-specific needs.

5. Base and Mounting

Robust Ground Interface: The base unit is fabricated with a low center of gravity to enhance stability during operations. It includes a wide stance with optional suction or bolted mounting holes to secure the platform against dynamic forces.

Mecanum Wheel Integration: The base is equipped with omnidirectional Mecanum wheels, enabling it to move laterally and rotate in place—a major advantage in restricted warehouse lanes.

Conceptual Design & Prototyping :

The conceptual design and layout were developed using SolidWorks, resulting in a comprehensive 3D model that integrated key components like sensors, extinguishing mechanisms, and housing structures. This phase focused on optimizing spatial arrangements for a compact, efficient layout, ensuring alignment with the electric vehicle's structural framework. SolidWorks enabled thorough analysis of spatial constraints, enhancing the functionality and safety of the fire suppression system. After prototyping and improvements, the design was finalized, addressing potential challenges and ensuring practical feasibility. This phase laid the groundwork for the next development stages, providing a clear, effective layout for electric vehicle applications.

Layout & Its Key Features: Layout:

The following design is made, and the image gives an idea about the layout of all the components.



Figure 1: Components Layout

Key features:

- 1. Mobile Base & Robotic Arm Integration:** Combines an intelligent, AI-powered robotic arm with a mobile base, enabling real-time task execution and movement within structured environments.
- 2. Mecanum Wheel Drive System:** Offers superior maneuverability in 360 degrees, allowing the system to perform side-shifting, rotation, and diagonal travel, crucial in constrained storage layouts.
- 3. Modular and Scalable Design:** The system architecture supports modular upgrades, such as sensor attachments or gripper modifications, promoting flexibility and long-term use.
- 4. Servo-Controlled Arm with Multiple DOF:** Equipped with five or more degrees of freedom, the arm can perform complex pick-and-place sequences with millimeter precision.
- 5. AI and Sensor-Based Navigation:** Integrates LiDAR, infrared, and visual sensors with neural networks for obstacle avoidance, SLAM-based path planning, and object identification even in low-visibility cold environments.

6. Cold-Resistant Engineering: All vital electronics are insulated and sealed to resist frost, while actuators are lubricated with low-temperature-rated grease to prevent mechanical freezing.

7. Multi-Functional End-Effector: The gripper can be interchanged based on task requirements, enabling it to handle cartons, metal tools, or sealed containers with minimal slippage or damage.

8. Autonomous and Manual Modes: Operable via remote controller (Bluetooth, RF, or Wi-Fi) or in fully autonomous mode using pre-programmed routes and AI-driven decision-making.

Working:

The mobile robotic arm integrates a responsive control system that supports both remote manual operation and fully autonomous functionality, optimized for cold storage environments. Communication with the robot is established through wireless protocols such as Wi-Fi, Bluetooth, or RF modules, enabling real-time feedback and control.

Operators can interact with the system using a dedicated joystick or a custom-built mobile application, allowing them to steer the robot, manipulate the robotic arm, and activate gripping mechanisms. In autonomous mode, the robot leverages artificial intelligence for navigation and object recognition, executing predefined tasks without human input.

LiDAR sensors, in combination with advanced sensor fusion techniques, enable the system to detect and adapt to environmental obstacles, ensuring smooth and safe operation. This dual-mode functionality—manual and autonomous—enhances operational flexibility, making the robot a practical solution for automating logistics and handling processes in cold storage facilities where traditional systems may fail.

Pick and Place Process:

The pick and place operation of the mobile robotic arm follows a structured sequence, integrating AI-driven perception, precise actuation, and autonomous navigation for efficient object handling.

1. Object Detection & Localization – Using AI-based vision and LiDAR sensors, the system identifies and locates objects within its workspace.
2. Navigation & Positioning – The Mecanum wheel base moves the robot to the optimal position, ensuring precise alignment with the target object.
3. Arm Actuation & Gripping – The multi-DOF robotic arm extends toward the object, and the adaptive gripper (vacuum, soft, or electromagnetic) securely grasps it.
4. Transport & Repositioning – The robotic system moves to the designated drop-off location, optimizing its path through autonomous route planning.
5. Object Placement & Release – The arm accurately positions and releases the object at the specified location before returning to its idle state or next task.




Figure 2: Components

Analysis & Calculations :

Payload Capacity and Overload protection :

This is the maximum weight that robotic arm is designed to lift (assumption) and safety margin has to 1.3 more than load.

$P_{safe} = P_{exact\ load} \times \text{safety factor}$

$P_{safe} = 200\ mg \times 1.3 = 130\ mg = 260\ mg$ **Torque Calculation**

for Arm Joints :

$T = F \times r$ ($F = m \times g = 0.200 \times 9.81 = 1.962\ N$)

$T = 1.962 \times 50 = 98.1\ N.cm$ ($r = 50\ cm$ overall height)

$T = 10.00\ kg.cm$

Motor Power :

$P = T \times \omega / 1000$

$P = 0.981 \times (2\pi/t) / 1000$ ($t = 3\ sec$)

$P = 0.00205\ Kw$ ($P = 2.05\ W$)



Figure 3 : Mobile Robotic Arm

IV. RESULTS

For the development of an automated mobile robotic arm in cold storage operations:

- The payload capacity should be designed for at least 0.26 kg with an overload protection factor.
- The joint torque requirement is 10.00 kg.cm (98.1 N.cm) for smooth operation.
- The motor power requirement is 2.05 W, ensuring energy-efficient operation.

These calculations provide a fundamental basis for selecting appropriate actuators, ensuring reliability in cold storage environments. Further refinements should consider frictional losses, joint dynamics, and environmental adaptations.

V. CONCLUSION

Combining an automated robotic arm like the EEZYBotArm MK2 with an omnidirectional mobile base offers an efficient solution for cold storage and other industrial settings. This setup provides accurate handling and smooth movement in tight spaces. Its modular, flexible design suits a range of applications, from logistics to precision tasks. Future upgrades may include smarter AI, improved sensors, and IoT integration to enhance automation and real-time monitoring, driving productivity and safety in smart robotics.

VI. REFERENCES

- [1] Chen, L., Zhang, Y., & Wang, X. (2021). Vision-based object detection under low-temperature conditions for robotic applications. International Journal of Advanced Robotic Systems, 18(3), 1-12.

-
- [2] Kim, H., & Lee, S. (2020). Material degradation and sensor performance in cold storage robotics. *Journal of Robotics and Automation*, 35(4), 355-372.
 - [3] Park, M., Choi, H., & Kim, S. (2023). LiDAR performance in reflective and narrow-aisle environments: A case study in cold storage logistics. *Robotics and Computer-Integrated Manufacturing*, 78, 102432.
 - [4] Liu, B., Chen, D., & Zhou, H. (2023). Deep reinforcement learning for real-time robot path planning in dynamic warehouse settings. *IEEE Access*, 11, 56789–56799.
 - [5] Singh, R., & Patel, N. (2020). Review of mobile robotic arms in industrial automation and logistics. *Journal of Intelligent & Robotic Systems*, 98(1), 55–70.