Roles & Permissions — API Changes

Collectrix · Tenant › roles · 8 October 2026

Roles now store a list of permission keys (strings like `customers.notes.delete`) instead of numeric `allowedConfiguration` ids. Everything else in the roles folder stays as it is: same URLs, same `Authorization` header, same `{ meta, data }` response.

#	Endpoint	Status	Change
1	`getAllRole`	Changed	Each role returns `roleDescription` and `permissions`
2	`createRole`	Changed	`allowedConfiguration` → `permissions`
3	`updateRole`	Changed	`allowedConfiguration` → `permissions`
4	`deleteRole`	**New**	Delete a role by `roleId`
5	`getConfiguredRoles`	Removed	No longer called by the app

1. getAllRole — Changed

POST `{{baseUrl}}/v1/tenant/getAllRole`
Headers: `Authorization: {{tenant_auth}}`

Body

```
{}
```

Response

```
{
    "meta": {
        "status": true,
        "message": "Success",
        "code": 200
    },
    "data": {
        "permissionSchema": 2,
        "roles": [
            {
                "roleId": 1,
                "roleName": "Testing Role By Rakesh",
                "roleDescription": "This is a testing role created during development.",
                "userCount": 3,
                "permissions": [
                    "customers.view",
                    "customers.changeStatus",
                    "inbox.view"
                ]
            }
        ]
    }
}
```

Changes

- Add `roleDescription` to each role.
- Replace `allowedConfiguration` with `permissions` (array of strings).
- Add `permissionSchema: 2` (always 2). The app unlocks role editing when it sees it.
- Remove `totalConfiguration`.

2. createRole — Changed

POST `{{baseUrl}}/v1/tenant/createRole`
Headers: `Authorization: {{tenant_auth}}`

Body

```
{
    "roleName": "Testing Role By Rakesh",
    "roleDescription": "This is a testing role created during development.",
    "permissions": [
        "customers.view",
        "customers.changeStatus",
        "inbox.view"
    ]
}
```

Response

```
{
    "meta": {
        "status": true,
        "message": "Success",
        "code": 200
    },
    "data": {}
}
```

Changes

- Replace `allowedConfiguration: [1,2,3]` with `permissions: ["customers.view", ...]`.
- Reject any key not in the Permission keys list at the end of this document.

3. updateRole — Changed

POST `{{baseUrl}}/v1/tenant/updateRole`
Headers: `Authorization: {{tenant_auth}}`

Body

```
{
    "roleId": 1,
    "roleName": "Testing Role By Rakesh",
    "roleDescription": "This is a testing role created during development.",
    "permissions": [
        "customers.view",
        "customers.changeStatus",
        "inbox.view",
        "inbox.assign"
    ]
}
```

Response

```
{
    "meta": {
        "status": true,
        "message": "Success",
        "code": 200
    },
    "data": {}
}
```

Changes

- Same as createRole. `permissions` is the full list, not only the added keys: replace what is stored.

4. deleteRole — New

POST `{{baseUrl}}/v1/tenant/deleteRole`
Headers: `Authorization: {{tenant_auth}}`

Body

```
{
    "roleId": 1
}
```

Response

```
{
    "meta": {
        "status": true,
        "message": "Success",
        "code": 200
    },
    "data": {}
}
```

Rules

- Refuse while users are on the role (see Error messages).

5. getConfiguredRoles — Removed

The app no longer calls it. The permission list now lives in the app; the valid keys are listed below.

Error messages

Same pattern as the other APIs: HTTP 200 with `meta.status: false`. The app shows `meta.message` to the user as is.

```
{
    "meta": {
        "status": false,
        "message": "Role name already exists.",
        "code": 400
    },
    "data": {}
}
```

Endpoint	When	message
createRole, updateRole	`roleName` is empty	Role name is required.

Endpoint	When	message
createRole, updateRole	`roleName` already used in the tenant (ignore case)	Role name already exists.
createRole, updateRole	A key is not in the list below	Unknown permission: <key>
deleteRole	Users are still on the role	This role is assigned to N users. Move them to another role first.

`permissions: []` is allowed.

Permission keys

The 76 valid values for `permissions`.

Page	Keys
Customers	`customers.view`, `customers.edit`, `customers.changeStatus`, `customers.manageFlags`, `customers.moveTeam`, `customers.archive`, `customers.stopEngagement`, `customers.resumeEngagement`, `customers.export`
Notes	`customers.notes.view`, `customers.notes.create`, `customers.notes.edit`, `customers.notes.delete`
SMS & email	`customers.messages.view`, `customers.messages.sendSms`, `customers.messages.sendEmail`
Calls	`customers.calls.view`, `customers.calls.place`
Documents	`customers.documents.view`, `customers.documents.generate`, `customers.documents.delete`
Team Deck	`teamDeck.view`, `teamDeck.assign`
Moved Files	`movedFiles.view`, `movedFiles.takeOn`
Archive	`archive.view`, `archive.restore`, `archive.export`
Inbound Inbox	`inbox.view`, `inbox.assign`
Phone numbers	`phoneNumbers.view`, `phoneNumbers.buy`, `phoneNumbers.edit`, `phoneNumbers.release`
Template library	`templates.view`, `templates.create`, `templates.edit`, `templates.delete`
Client list	`clients.view`, `clients.create`, `clients.edit`, `clients.delete`
Upload customer data	`imports.view`, `imports.upload`, `imports.edit`, `imports.assignTeam`
Mass update	`massUpdate.view`, `massUpdate.apply`, `massUpdate.export`

Page	Keys
Activity & audit	`audit.view`, `audit.export`
Users	`users.view`, `users.create`, `users.edit`, `users.resetPassword`, `users.deactivate`
Teams	`teams.view`, `teams.create`, `teams.edit`, `teams.delete`
Roles	`roles.view`, `roles.create`, `roles.edit`, `roles.delete`
Tenant settings	`settings.view`, `settings.edit`
Data fields	`dataFields.view`, `dataFields.create`, `dataFields.edit`, `dataFields.delete`
Statuses	`statuses.view`, `statuses.create`, `statuses.edit`, `statuses.delete`
Status automation	`statusAutomation.view`, `statusAutomation.edit`