

BOUNDARYLENS

Technical Architecture, PPT Content & Comprehensive Defense Reference

A Rigorous, Evidence-Based Geospatial System for Proposed 3D Spatial and Vertical Property Delineation, Multi-Sensor Elevation Fusion, Floor Disambiguation, and Human-in-the-Loop Topology Verification.

Target Geography: Baramati ULB, Pune District, Maharashtra

Repository: [sujayghosh13/boundarylens-sih26011](#)

Test Suite Status: 124 / 124 Unit & Integration Tests Passed (100%)

Verified Buildings: 2,734 Processed 3D Footprints

Cadastral Parcels: 26 Digitized Revenue Parcels

Core AI Components: Random Forest (Floors) • Isolation Forest (Outliers)

Demo Health Check: Fully Verified • Port 8000 Ready

Legal Boundary: Proposed Spatial Linkage (Non-Statutory Decision Aid)

Document Purpose: Complete technical reference manual designed for presentation slides formulation, live demo narration, judge cross-examination defense, and architectural deep-dives. Adheres strictly to the master project constitution (AGENTS.md).

TABLE OF CONTENTS

1. Project Overview & Objectives	11. Human Verification & Reviewer Audit Engine
2. Problem Statement & Cadastral Challenges	12. Results & Verified Benchmark Table
3. Proposed Solution & System Philosophy	13. Standard Demo Exemplars & Edge Cases
4. End-to-End System Architecture	14. Verified Technology Stack
5. Exhaustive Dataset Inventory & Provenance	15. Project Directory Architecture
6. 3D Elevation & Surface Modeling (DEM/DSM)	16. Reproducibility & Execution Pipeline
7. Floor Estimation Engine & Machine Learning	17. Current Limitations & Explicit Boundaries
8. Anomaly Detection & Evidence Fusion	18. Future Technical Scope & Enhancements
9. Satellite Vegetation Signal (NDVI)	19. Comprehensive Judge Defense Q&A (25 Questions)
10. MapLibre 3D UI & Spatial Analytics Dashboard	20. Executive One-Page Reference Cheat Sheet

1. PROJECT OVERVIEW

Project Metadata

- Project Title:** BoundaryLens
- SIH Problem Statement ID:** SIH26011
- Domain:** Land Administration, GIS, 3D Cadastre, Remote Sensing, AI/ML
- Target Pilot Geography:** Baramati Municipal Council (ULB), Pune District, Maharashtra (Selected due to published NAKSHA pilot alignment and DILRMP cadastral progress)
- Repository:** [sujayghosh13/boundarylens-sih26011](https://github.com/sujayghosh13/boundarylens-sih26011)

One-Line Pitch & Core Objective

One-Line Description: BoundaryLens is an open-source, multi-modal geospatial system that binds 2D cadastral land parcels to vertical multi-level property volumes through multi-sensor elevation fusion, machine learning floor disambiguation, and human-in-the-loop topology verification.

Core Objective: Provide revenue officials and urban planners with a non-destructive, reproducible spatial workflow to propose vertical linkages between parent land records (ULPINs) and individual built units without making unverified legal assertions.

The Non-Negotiable Constitution Rule (AGENTS.md Rule 2): BoundaryLens generates a *"proposed 3D spatial linkage"*. It does NOT claim to issue an official government ULPIN, alter statutory land registries, or adjudicate ownership rights. Legal recognition belongs solely to competent land revenue authorities.

2. PROBLEM STATEMENT & CADASTRAL CHALLENGES

India's landmark **Unique Land Parcel Identification Number (ULPIN)** program (the 14-digit "Aadhaar for land") provides a foundational 2D spatial identity for ground parcels based on longitude and latitude coordinates of parcel vertices. However, modern urbanization has exposed fundamental limitations in strictly planar cadastral systems:

Challenge	The Real-World Issue	Why Traditional GIS Fails
Vertical Overlap & Stacking	A single 500 sq.m land parcel may host a 14-storey apartment building housing 56 distinct property owners.	2D GIS forces all units into the exact same polygon footprint. Individual flats, commercial shops, and basements share identical (X, Y) coordinates, causing spatial collision and ownership ambiguity.
Multi-Sensor Discrepancy	Satellite radar, optical imagery, municipal GIS, and revenue maps represent the same building with spatial offsets and projection shifts.	Traditional GIS pipelines fail or silently choose an arbitrary layer when datasets disagree, creating severe boundary distortion and false legal claims.


Challenge	The Real-World Issue	Why Traditional GIS Fails
Floor Ambiguity	Floor plans are rarely digitized; satellite sensors observe only roof elevation, not interior storeys.	Standard pipelines either assume a fixed floor height (e.g., 3m across all types) or hallucinate floor numbers, leading to gross taxation and property disputes.
Subterranean & Overhead Assets	Basement parking, underground metro lines, utilities, and cantilevered upper floors transcend surface bounds.	2D cadastral records possess no Z-axis dimension, rendering underground or overhanging property rights invisible and untraceable.

3. PROPOSED SOLUTION & SYSTEM PHILOSOPHY

BoundaryLens solves this multi-dimensional challenge through an **Evidence-Based Vertical Linkage Hierarchy**. Rather than forcing an opaque black-box deep neural network to fabricate 3D boundaries, BoundaryLens establishes a clear chain of custody:

1. Hierarchical Entity Modeling

Every spatial object is modeled as a nested four-tier graph entity:



2. Rigorous Evidence Hierarchy

Every single attribute (height, floor count, boundary) carries provenance:

- OBSERVED** Measured directly from authoritative tags or field surveys.
- ESTIMATED** Computed via mathematical fusion or calibrated ML models.
- PROPOSED** Geometric linkage awaiting statutory sign-off.
- CONFLICT** Conflicting evidence surfaced to a human officer.

4. END-TO-END SYSTEM ARCHITECTURE

The system operates through an eight-stage deterministic and AI-assisted pipeline, ensuring zero opaque hallucinations and full auditability:

```
[ Tier A / B Spatial Inputs ]
├─ OpenStreetMap (OSM) Vectors (Buildings, Highways, Levels)
├─ OpenCity Cadastral Shapefiles / KMZ (26 Digitized Revenue Parcels)
├─ Bare-Earth Digital Elevation Model (DEM - SRTM / AWS Terrain, 30m)
├─ Copernicus GLO-30 Digital Surface Model (DSM - Radar Surface, 30m)
├─ Sentinel-2 Optical L2A Multispectral Imagery (B4 Red & B8 NIR)
└─
    |
    ▼
[ Stage 1: Data Ingestion & CRS Normalization ]
├─ Schema sanitization & coordinate transformation to EPSG:4326 (WGS 84)
├─ Spatial indexing via R-tree / GeoPandas spatial indexes
└─
    |
    ▼
[ Stage 2: 2D Parcel-to-Building Spatial Containment ]
├─ Deterministic Shapely polygon intersection & centroids containment
├─ Linking each building to parent Cadastral Parcel ID (e.g., ULPIN-MH-PUN-BAR-001)
└─
    |
    ▼
[ Stage 3: Elevation & Height Disambiguation ]
├─ Ground elevation extraction from DEM at building centroid: Z_base
├─ Top-of-structure elevation extraction from DSM: Z_surface
├─ Mathematical Height Signal derivation: Height = max(0, Z_surface - Z_base)
└─
    |
    ▼
[ Stage 4: Floor Evidence & Storey Prediction ]
├─ Observed check: Extracts verified `building:levels` tag if available
├─ ML Fallback: Calibrated Random Forest Regressor predicts floors if missing
└─
    |
    ▼
[ Stage 5: Multispectral Vegetation Verification (NDVI) ]
├─ Samples Normalized Difference Vegetation Index (NDVI = (NIR - Red) / (NIR + Red))
├─ Flags potential false-positive building extractions caused by dense tree canopies
└─
    |
    ▼
[ Stage 6: AI Anomaly & Conflict Detection ]
├─ Isolation Forest analyzes multi-feature vectors (Height, Area, Aspect, NDVI)
├─ Outliers marked with flag `ISOLATION_FOREST_OUTLIER` -> HUMAN_VERIFICATION_REQUIRED
└─
    |
    ▼
[ Stage 7: Deterministic 3D Geometry Extrusion & Linkage Synthesis ]
├─ Vertical extrusion: Base Z to Base Z + Height
├─ Volumetric slicing into proposed floor-level units with unique Volume IDs
└─
    |
    ▼
[ Stage 8: Interactive MapLibre 3D UI & Human Reviewer Workflow ]
├─ GPU-accelerated client-side 3D rendering with dynamic pitch & rotation
├─ Reviewer Audit Console: Actions (APPROVE, CORRECT, REJECT, UNRESOLVED) + Event Log
```

5. EXHAUSTIVE DATASET INVENTORY & PROVENANCE

In adherence to AGENTS.md Rule 9 & 10, every dataset used in BoundaryLens is documented with exact spatial extents, licensing terms, and measurement certainty:

Dataset / Layer	Source / Provider	Type	Resolution	Role in Pipeline	Licence / Origin
Building Footprints	OpenStreetMap (OSM) Contributors	Vector Polygons	Sub-meter vertices	Primary building geometry, ground area, perimeter, and attribute tags (2,734 buildings in Baramati AOI).	Open Database Licence (ODbL)
Cadastral Parcels	OpenCity / DILRMP Pune digitised boundaries	Vector Polygons	Cadastral survey scale	Parent legal land parcel boundaries for Baramati pilot area (26 verified revenue parcels).	Open Municipal / Public Domain
Bare-Earth Terrain (DEM)	SRTM v3 / AWS Terrain Tiles	Raster GeoTIFF	30m spatial resolution	Provides ground terrain elevation (Z_base) above mean sea level across the municipality.	NASA / USGS / Public Domain
Surface Model (DSM)	Copernicus GLO-30 DSM	Raster GeoTIFF	30m spatial resolution	Measures top-of-canopy and top-of-structure elevation (Z_surface) across the landscape.	Copernicus Open Access Licence
Vegetation Index (NDVI)	Sentinel-2 L2A Multispectral Instrument	Raster GeoTIFF	10m spatial resolution	Computes pixel-level vegetation greenness to identify foliage overlap and false building masks.	ESA Copernicus Open Access
Observed Floor Counts	OpenStreetMap <code>building:levels</code>	Tabular / Attribute	Discrete integer	Ground-truth observed storeys (16 buildings in pilot AOI; 12,762 across Maharashtra training set).	ODbL Contributors

Explicit Clarification on External APIs: Google Open Buildings is *not* utilized in the current local baseline. The pipeline relies strictly on vetted OSM vector geometries and verified open satellite datasets to guarantee 100% offline reproducibility and open-source licensing compliance.

6. 3D ELEVATION & SURFACE MODELING (DEM/DSM)

Mathematical Height Derivation

Building height is calculated by subtracting ground terrain elevation from surface elevation at the footprint centroid (x_c, y_c) :

```
Z_base      = Bilinear_Sample(DEM, x_c, y_c)
Z_surface   = Bilinear_Sample(DSM, x_c, y_c)
Height_Signal = max(0.0, Z_surface - Z_base)
```

If height evaluates to less than 2.5 meters (due to raster smoothing over small sheds), a heuristic minimum baseline (e.g., 3.0m) or OSM tag inference is applied with an explicit `ESTIMATED` tag.

Elevation Principles (AGENTS.md Rule 4)

- **DEM = Terrain/Ground Elevation:** Represents bare-earth terrain stripped of vegetation and man-made structures.
- **DSM = Surface Elevation:** Captures the first reflective surface hit by radar pulses (roofs, tree tops, towers).
- **Height is an Evidence Signal:** At 30m resolution, satellite raster differences can smooth sharp edges. **DSM - DEM alone MUST NOT be described as an exact floor count source.**

7. FLOOR ESTIMATION ENGINE & MACHINE LEARNING

Floor count determination follows a dual-track strategy: authoritative observation where tagged, followed by an empirically trained and cross-validated Machine Learning regressor.

Track A: Observed Evidence

When an authoritative `building:levels` tag exists in the source dataset, it is preserved without modification:

- **Status:** `OBSERVED`
- **Confidence:** HIGH
- **Pilot AOI Count:** 16 buildings have verified ground-truth level tags in Baramati.

Track B: Machine Learning Fallback

When floor tags are missing, an engineered **Random Forest Regressor** estimates the floor count:

- **Status:** `ESTIMATED`
- **Confidence:** MEDIUM / LOW
- **Pilot AOI Count:** 2,453 buildings predicted; 265 marked `NOT_DETERMINABLE` due to missing height signals.

Model Specifications & Verified Evaluation Metrics

Model Architecture	Engineered Features	Training Data Volume	Cross-Validation Performance	Baramati Pilot Holdout Performance
Random Forest Regressor (<code>n_estimators=100</code> , <code>max_depth=12</code> , <code>random_state=42</code>)	• <code>height_m</code> (Derived Z signal) • <code>footprint_area_sqm</code> (Polygon area) • <code>perimeter_m</code> (Boundary length) • <code>aspect_ratio</code> (Bounding box ratio) • <code>compactness</code> ($4\pi \cdot \text{ext}\{\text{Area}\} / \text{ext}\{\text{Perimeter}\}^2$) • <code>convexity</code> ($\text{ext}\{\text{Area}\} / \text{ext}\{\text{ConvexHull Area}\}$)	12,762 real-world records across Pune and Maharashtra with verified OSM floor labels.	• MAE: 2.22 floors • RMSE: 3.01 floors • ±1 Floor Accuracy: 59.79% • R² Score: 0.41	• MAE: 1.21 floors • ±1 Floor Accuracy: 62.50% • <i>Tested on 16 unseen ground-truth buildings in Baramati AOI.</i>

8. ANOMALY DETECTION & EVIDENCE FUSION

To prevent erroneous automated decisions from polluting land records, BoundaryLens incorporates an unsupervised **Isolation Forest** algorithm (scikit-learn) paired with a deterministic **Evidence Fusion Rule Engine**:

Isolation Forest Outlier Detection

- **Contamination Factor:** 3.0% (\$0.03\$).
- **Input Vector:** Combines building area, derived height, height-to-area ratio, compactness, and centroid NDVI.
- **Action:** Isolates abnormal geometries (e.g., massive industrial sheds misidentified as multi-storey towers, or tiny footprint polygons with 40-meter height signals).
- **Current Verification:** Flagged **82 anomalous structures** in Baramati, immediately setting their status to `HUMAN_VERIFICATION_REQUIRED`.

Evidence Fusion Conflict Matrix

- **Conflict Rule 1:** If observed floor count contradicts height-derived floors by > 3 storeys $\rightarrow$ `CONFLICT`.
- **Conflict Rule 2:** If building polygon extends beyond parcel boundary by $> 15\%$ $\rightarrow$ `SPATIAL_ENCROACHMENT_WARNING`.
- **Conflict Rule 3:** If building centroid has $\text{NDVI} > 0.45 \rightarrow$ `VEGETATION_CANOPY_OVERLAP`.
- **Guiding Rule (AGENTS.md Rule 5):** AI assists; it never adjudicates disputes.

9. SATELLITE VEGETATION SIGNAL (NDVI)

NDVI Mathematical Formulation

Derived from Sentinel-2 Level-2A surface reflectance:

$$\text{NDVI} = (\text{Band 8 [NIR]} - \text{Band 4 [Red]}) / (\text{Band 8 [NIR]} + \text{Band 4 [Red]})$$

Ranges from $-\$1.0\$$ (water, clouds) to $+\$1.0\$$ (dense healthy photosynthetic biomass). Built structures typically range from $\$0.05\$$ to $\$0.22\$$.

Role in BoundaryLens

- **Not a Standalone Classifier:** NDVI does not replace building masks; it acts as a spectral sanity check.
- **Canopy Disambiguation:** Overhanging banyan or neem tree canopies over low-rise concrete roofs create large DSM elevation spikes. High NDVI (> 0.40) alerts the reviewer that the height signal is contaminated by tree foliage.

10. MAPLIBRE 3D UI & SPATIAL ANALYTICS DASHBOARD

The user interface is engineered with **MapLibre GL JS** (WebGL-accelerated vector mapping) delivering 60 FPS client-side rendering without external proprietary map licensing:

Dashboard Component	Technical Implementation	User Interaction & Capabilities
3D Extrusion Engine	Vector GeoJSON with MapLibre <code>fill-extrusion</code> layer	Renders all 2,734 buildings dynamically extruded to their derived heights (base Z + height) with 3D pitch/bearing rotation controls.
Cadastral Overlay	GeoJSON line & fill layers with distinct gold borders	Displays 26 Baramati revenue parcels. Clicking highlights the parent boundary and filters intersecting buildings.
Interactive Property Inspector	Dynamic DOM card bound to spatial feature properties	Displays building ID, parent parcel reference, ground elevation (DEM), height, floor count, provenance status, and confidence.
Vertical Unit / Floor Visualizer	Modular SVG / CSS 3D isometric stack	Breaks down selected building into discrete vertical levels (e.g., Ground, Floor 1, Floor 2), displaying unit volumes and IDs.
NDVI Multispectral Toggle	Client-side raster tile / GeoJSON color ramp overlay	Allows reviewers to toggle vegetation heatmaps to cross-reference canopy interference visually.

Dashboard Component	Technical Implementation	User Interaction & Capabilities
Reviewer Action Console	Interactive operational bar with status buttons	Enables authorized officials to execute review actions: APPROVE, CORRECT, REJECT, or MARK UNRESOLVED.

11. HUMAN VERIFICATION & REVIEWER AUDIT ENGINE

To adhere to public administration ethics and legal accountability, BoundaryLens implements a strict **Human-in-the-Loop** verification protocol (AGENTS.md Rule 8):

Reviewer Action State Machine

- **APPROVE:** Official accepts the proposed 3D linkage and floor count as verified provisional evidence.
- **CORRECT:** Official overrides estimated values with verified field data (e.g., changes predicted 4 floors to 3 observed floors).
- **REJECT:** Official discards the spatial linkage (e.g., demolished building or invalid boundary).
- **MARK UNRESOLVED:** Escalates conflicting evidence for physical ground cadastral re-survey.

Audit Trail Logging

Every decision triggers an immutable structured audit log:

```
{
  "event_id": "aud_20260919_0042",
  "building_id": "bld_baramati_1042",
  "timestamp": "2026-09-19T02:15:00Z",
  "action": "CORRECT",
  "previous_floors": 4,
  "corrected_floors": 3,
  "reviewer_id": "OFFICER_REVENUE_PUN_04",
  "reason": "Physical field register verification"
}
```

Demo Note: Maintained in session/in-memory queue; production architecture maps to persistent PostgreSQL audit tables.

12. RESULTS & VERIFIED BENCHMARK TABLE

The current repository implementation has undergone exhaustive automated testing and spatial validation. All metrics below represent **100% verified results** from the project test suite and demo health check:

System Component / Metric	Verified Result	Status	Verification Details
Automated Test Suite	124 / 124 Tests Passed (100%)	VERIFIED	Zero failures across ingestion, elevation, floor model, topology, AI, and reviewer modules.
Processed 3D Buildings	2,734 Buildings	VERIFIED	Fully normalized, extruded with DEM base elevation and DSM height signals.
Cadastral Parcels Linked	26 Revenue Parcels	VERIFIED	Clean spatial linkage with parent-child centroid and intersection mapping.
Observed Ground-Truth Floors	16 Buildings	OBSERVED	Authoritative OSM <code>building:levels</code> extracted and verified in Baramati AOI.
ML Predicted Floor Extrusions	2,453 Buildings	ESTIMATED	Predicted via Random Forest trained on 12,762 regional building records.
Non-Determinable Entities	265 Structures	NON_DETERM	Safely labeled <code>NOT_DETERMINABLE</code> rather than fabricating ungrounded height/floor data.
AI Anomalies Flagged	82 Outliers	FLAGGED	Flagged by Isolation Forest for human verification review.
Demo Health Check	PASS	VERIFIED	All JSON data files, frontend assets, and endpoints verified operational on Port 8000.

13. STANDARD DEMO EXEMPLARS & EDGE CASES

To demonstrate the system live to judges, use these three carefully selected and verified demo exemplars:

Exemplar Scenario	Building / Entity ID	Observed vs Estimated State	Key Presentation Talking Point
Case A: Standard Valid Building <i>(Normal Commercial/Residential)</i>	osm_bld_101 Matched to Parcel ULPIN-MH-PUN-BAR-001	- Base Elevation: 538.2 m (DEM) - Surface Elevation: 546.7 m (DSM) - Height: 8.5 m (Derived) - Floors: 3 (Predicted by RF) - Confidence: MEDIUM - Status: PROVISIONAL LINKAGE	Demonstrates end-to-end multi-sensor fusion: DEM provides ground level, DSM provides roof height, Random Forest estimates realistic storeys, and the 3D unit stack creates a proposed linkage to the parent cadastral parcel.
Case B: Anomaly / Conflict Exemplar <i>(Vegetation / Height Outlier)</i>	osm_bld_482 Spatial Conflict Flagged	- Derived Height: 18.2 m - Footprint Area: 42 sq.m - Mean NDVI: 0.48 (Dense Canopy) - AI Flag: ISOLATION_FOREST_OUTLIER - Status: HUMAN REVIEW REQ	Proves the system's ethical AI guardrails: The high height on a tiny footprint with high NDVI indicates an overhanging tree canopy rather than a 6-storey skyscraper. The system refuses to hallucinate and alerts a human reviewer.
Case C: Floor Comparison Exemplar <i>(Observed vs Predicted Validation)</i>	osm_bld_016 (Observed) vs osm_bld_204 (Predicted)	- bld_016 : building:levels=2 (OBSERVED) - bld_204 : Height 6.2m → 2 Floors (ESTIMATED) - Confidence: HIGH vs MEDIUM	Demonstrates strict scientific honesty: Shows judges that the system transparently distinguishes verified observed ground truth from estimated machine learning predictions, preserving legal integrity.

14. VERIFIED TECHNOLOGY STACK

Layer / Component	Technology	Specific Role in BoundaryLens
Language & Runtime	Python 3.11 / 3.12	Core processing language, scientific computation, and async pipeline orchestration.
Vector Geospatial	GeoPandas, Shapely, PyProj	Vector ingest, spatial indexing (R-tree), coordinate transformation (EPSG:4326), intersection checks.
Raster Geospatial	Rasterio, GDAL bindings, NumPy	Satellite DEM, DSM, and Sentinel-2 multispectral band extraction and bilinear spatial sampling.
Machine Learning	scikit-learn (Random Forest & Isolation Forest)	Floor level regression, feature scaling, isolation outlier detection, cross-validation metrics.
Web / 3D Visualization	MapLibre GL JS, HTML5, CSS3, JavaScript	Client-side GPU 3D polygon extrusion, dynamic camera pitching/rotation, responsive inspector cards.
Backend Serving	Python HTTP Server / FastAPI compatible	Lightweight local demo server hosting spatial GeoJSON endpoints and web assets on Port 8000.
Automated Testing	pytest, pytest-cov	Full test automation with 124 unit and regression test cases covering all edge scenarios.

15. PROJECT DIRECTORY ARCHITECTURE

```
BoundaryLens/
├── data/
│   ├── raw/                # Downloaded raw OSM, DEM/DSM GeoTIFFs, and OpenCity KMZ files
│   ├── processed/          # 2,734 extruded 3D building GeoJSONs, parcels, and floor tables
│   └── manifests/           # Data provenance records, licenses, acquisition dates (AGENTS.md Rule 9)
├── src/
│   ├── ingestion/          # Parsers for OSM XML/PBF, Cadastral shapefiles, raster reprojections
│   ├── alignment/          # Cadastral-to-building spatial containment & polygon overlap engine
│   ├── elevation/           # DEM ground terrain and DSM surface elevation sampler
│   ├── floor_model/         # Random Forest floor regression model training and inference
│   ├── ai/                  # Isolation Forest anomaly detection & evidence fusion matrix
│   ├── topology/           # Deterministic geometric validity & containment checks (Rule 6)
│   └── reviewer/           # Human-in-the-loop action handler & structured audit logging (Rule 8)
├── web/
│   ├── index.html           # Main 3D dashboard viewport, property card, and reviewer console
│   ├── app.js               # MapLibre GL controller, event handlers, and dynamic SVG visualizers
│   └── style.css             # High-contrast, responsive UI styling and spatial legend styling
├── tests/                   # 124 unit, integration, and end-to-end automated test suites
├── scripts/
│   └── demo_health_check.py  # Automated pre-flight validation script checking files and server readiness
├── run_demo.py              # Lightweight instant demo launcher (Port 8000, zero retraining)
├── run_pipeline.py          # Full end-to-end heavy batch pipeline (ETL, training, raster sampling)
├── requirements-demo.txt     # Minimal, stable dependencies required for presentation demo
├── AGENTS.md                # Master Project Constitution and legal boundary rules
└── README.md                # Complete technical documentation and setup guide
```

16. REPRODUCIBILITY & EXECUTION PIPELINE

Presentation Demo Execution (Recommended)

For live presentation and judge evaluation, use the lightweight demo launcher:

```
# 1. Activate Virtual Environment
. \env\Scripts\activate

# 2. Run Pre-flight Health Check
python scripts/demo_health_check.py

# 3. Launch Demo Server
python run_demo.py --port 8000
```

Why: Starts in < 2 seconds, serves existing pre-processed verified data, avoids slow external satellite downloads and non-deterministic retraining during the live pitch.

Full Pipeline Re-generation (Batch Mode)

To execute the entire multi-sensor ingestion and model retraining from scratch:

```
# Run Full Ingestion & Training Pipeline
python run_pipeline.py --aoi baramati
```

Operations Executed: Downloads OSM vectors, crops Copernicus GLO-30 DSM and SRTM DEM tiles, trains Random Forest model on 12,762 records, executes Isolation Forest, and exports GeoJSONs.

17. CURRENT LIMITATIONS & EXPLICIT BOUNDARIES

In accordance with scientific integrity and the project constitution, the following limitations are explicitly acknowledged:

- **Satellite Spatial Resolution:** 30m Copernicus DSM and SRTM DEM rasters smooth fine-scale structural details. Height signals represent neighborhood elevation trends rather than sub-centimeter architectural laser scans.

- **Interior Floor Layouts:** In the absence of architectural floor plans (CAD/BIM), floor plates are geometrically extruded as equal vertical slices rather than reflecting internal mezzanine variations.
- **Non-Statutory Status:** All generated 3D volumes and linkages are decision-support proposals. They do not constitute legally binding revenue titles without competent authority ratification.
- **Audit Trail Persistence:** The lightweight demo launcher maintains audit event logs in memory/session files; enterprise persistence requires the planned PostgreSQL/PostGIS backend.

18. FUTURE TECHNICAL SCOPE & ENHANCEMENTS

- **Drone LiDAR / Photogrammetry Ingestion:** Integrating LAS/LAZ point clouds via PDAL to achieve 5cm vertical accuracy for complex heritage structures.
- **Direct DILRMP Cadastral API Bridge:** Building secure authenticated connectors to state land record portals (e.g., Mahabhulekh) for real-time parcel validation.
- **BIM / IFC Architectural Model Ingestion:** Slicing interior unit boundaries directly from building permits and RERA registered architectural plans.
- **Sub-Surface Utility Cadastre:** Extending 3D coordinate bounding boxes below ground level ($Z < 0$) to map underground utilities, metro corridors, and basement parking volumes.

19. COMPREHENSIVE JUDGE DEFENSE Q&A (25 QUESTIONS)

Q1: Why did you build BoundaryLens instead of relying on standard 2D GIS?

Short Answer: 2D GIS collapses all storeys of a multi-level building into a single flat polygon. BoundaryLens introduces the Z-axis, binding individual vertical property units to their parent cadastral parcel to eliminate vertical property ownership ambiguity.

Technical Depth: As urban density rises, a 500 sq.m land parcel may contain 50 distinct apartments across 10 floors. In traditional 2D land records, all 50 owners share identical (X, Y) cadastral coordinates. BoundaryLens models properties as 3D spatial volumes with base elevation, height extrusion, and floor indices, establishing an unambiguous link from parent ULPIN down to individual units.

Q2: Are you officially generating or modifying legal ULPINs?

Short Answer: No. BoundaryLens produces a *"proposed 3D spatial linkage"* to assist revenue authorities. Official ULPIN issuance and statutory title modification remain strictly the prerogative of government land authorities.

Technical Depth: AGENTS.md Rule 2 strictly forbids claiming statutory authority. We treat the 14-digit ULPIN as the anchor reference for the ground parcel. Our system builds a topological parent-child graph (ULPIN → Building → Floor → Volume) providing a non-destructive, auditable candidate structure for government adoption.

Q3: What is the technical difference between DEM and DSM, and why do you need both?

Short Answer: DEM measures the bare-earth ground terrain elevation, while DSM measures the top surface of all features including roofs and trees. Building height is derived by subtracting DEM from DSM ($Z_{\text{surface}} - Z_{\text{base}}$).

Technical Depth: Without DEM, a building located on a 500-meter hill would appear 500 meters tall in DSM. By sampling SRTM bare-earth DEM and Copernicus GLO-30 DSM at the building centroid, we isolate the true above-ground structural height signal: $\text{Height} = \max(0, Z_{\text{DSM}} - Z_{\text{DEM}})$.

Q4: Can DSM - DEM alone directly guarantee the exact number of floors?

Short Answer: No. Height is only an evidence signal. Commercial buildings, warehouses, and residential flats have varying floor-to-ceiling clearances, which is why we combine height with spatial features and machine learning.

Technical Depth: A 9-meter building could be a 3-storey residential house (3m/floor) or a single-level industrial warehouse with high clearance. Raster smoothing at 30m resolution also introduces variance. Hence, AGENTS.md Rule 4 prohibits treating DEM/DSM as an exact floor source; it is fed into our Random Forest classifier alongside area, aspect ratio, and compactness.

Q5: How exactly does your Machine Learning model estimate floor counts?

Short Answer: We use a Random Forest Regressor trained on 12,762 real-world buildings with verified floor labels, evaluating height, footprint area, perimeter, compactness, and aspect ratio to predict storeys.

Technical Depth: The model evaluates six engineered morphological features: `height_m`, `footprint_area_sqm`, `perimeter_m`, `aspect_ratio`, `compactness` ($4\pi A / P^2$), and `convexity`. It achieved an MAE of 2.22 floors across regional testing and an MAE of 1.21 floors on the unseen Baramati pilot holdout with a $62.5\% \pm 1$ floor accuracy.

Q6: How do you differentiate between observed and estimated data in the system?

Short Answer: Every property record displays an explicit provenance tag: green **OBSERVED** for direct official tags and amber **ESTIMATED** for machine learning predictions.

Technical Depth: In our Baramati dataset, 16 buildings possess authoritative `building:levels` tags from ground surveys. These are tagged OBSERVED with HIGH confidence. The remaining 2,453 buildings are tagged ESTIMATED (ML_RANDOM_FOREST) with MEDIUM confidence, and 265 structures with insufficient signals are marked NOT_DETERMINABLE.

Q7: What is AI doing in your system? Is it making final legal decisions?

Short Answer: AI assists with floor estimation and outlier anomaly detection. AI never makes final legal or boundary decisions; it flags discrepancies for human reviewer adjudication.

Technical Depth: We follow AGENTS.md Rule 5 & 8. Deterministic questions (spatial containment, coordinate transformations, polygon overlaps) use exact geometry math (Shapely/PyProj). AI is restricted to pattern estimation (Random Forest) and anomaly detection (Isolation Forest). Outliers are routed to a human officer.

Q8: How does Isolation Forest work in BoundaryLens?

Short Answer: Isolation Forest isolates abnormal feature combinations (such as tiny footprints with excessive height signals or vegetation overlap), flagging 82 potential anomalies in Baramati for manual verification.

Technical Depth: Isolation Forest recursively partitions multi-dimensional feature space. Anomalous data points require fewer splits to isolate. Configured with a 3% contamination rate on normalized feature vectors (height, area, NDVI, aspect), it flagged 82 structural anomalies that violate standard urban morphology rules.

Q9: Why do you use Sentinel-2 NDVI in an urban building project?

Short Answer: NDVI measures vegetation greenness. We use it to detect when a dense tree canopy overhangs a building, preventing tree heights from being mistaken for building storeys.

Technical Depth: In tropical Indian towns like Baramati, large trees (e.g., Peepal, Banyan) often canopy over 1–2 storey buildings. Radar DSM pulses reflect off the tree canopy, generating a false 15m height signal. If centroid NDVI > 0.40, the system triggers a `VEGETATION_CANOPY_OVERLAP` alert, preventing false floor inflation.

Q10: Why is Human-in-the-Loop verification necessary?

Short Answer: Land administration has serious legal and financial consequences. No automated algorithm is 100% perfect, so statutory actions require a qualified human reviewer with complete audit logging.

Technical Depth: Under AGENTS.md Rule 8, reviewers can execute four explicit actions: APPROVE, CORRECT, REJECT, or MARK UNRESOLVED. Each action generates an immutable JSON audit log recording the official ID, timestamp, previous state, and justification, guaranteeing administrative transparency.

Q11: What happens when two data sources disagree?

Short Answer: We never silently pick a winner. The system flags the discrepancy as a `CONFLICT`, displays the conflicting values, and routes the building for human verification.

Technical Depth: AGENTS.md Rule 3 enforces an explicit evidence hierarchy. If OSM tags report 2 floors but the derived height signal indicates 20 meters, or if a building footprint extends across two cadastral parcels by > 15%, the system marks the feature as `CONFLICT` and prompts the reviewer for ground validation.

Q12: Why did you choose Baramati as your pilot location?

Short Answer: Baramati appears in published Survey of India NAKSHA pilot materials, and Pune district has documented progress in cadastral map digitization under DILRMP.

Technical Depth: Under AGENTS.md Rule 10, Baramati offers real-world open-data cadastral boundaries (OpenCity Pune wards) and high-quality open satellite coverage, allowing us to build an authentic, verifiable baseline without relying on fabricated mock data.

Q13: Can BoundaryLens scale to other Indian cities?

Short Answer: Yes. The ingestion pipeline accepts standard GeoJSON/Shapefile cadastre and global 30m DEM/DSM rasters, allowing it to execute across any Indian ULB with digitized parcels.

Technical Depth: All GIS operations use standard EPSG coordinate transformations and modular ETL classes. To scale to a new municipality, an administrator simply supplies the local cadastral shapefile and bounding box; the pipeline automatically streams OSM vectors and raster tiles.

Q14: How do you handle missing or corrupt data?

Short Answer: If data is missing or indeterminate, we explicitly mark it as `NOT_DETERMINABLE` rather than guessing or fabricating numbers.

Technical Depth: In our Baramati test set, 265 structures had missing height signals or invalid raster intersections. Rather than filling them with synthetic averages, our pipeline strictly assigns `NOT_DETERMINABLE` and surfaces them for ground review.

Q15: What happens if an OpenStreetMap building footprint is inaccurate or outdated?

Short Answer: The human reviewer can reject the footprint or update it with official cadastral survey vectors using the built-in reviewer controls.

Technical Depth: OSM serves as a Tier A publicly accessible baseline. Our pipeline supports plugging in Tier B authoritative municipal survey shapefiles seamlessly. When discrepancies exist, the reviewer marks the feature REJECT or CORRECT, recording the authoritative provenance.

Q16: What mapping technology is used in the frontend and why?

Short Answer: We use MapLibre GL JS for GPU-accelerated client-side 3D extrusion, rendering thousands of building polygons smoothly without expensive cloud tile licensing.

Technical Depth: MapLibre GL JS provides open-source, WebGL-native vector rendering. Using vector GeoJSON layers with dynamic `fill-extrusion-height` and `fill-extrusion-base` properties, we achieve 60 FPS performance, dynamic lighting, pitch, and bearing controls locally on Port 8000.

Q17: How does BoundaryLens maintain data provenance?

Short Answer: Every single building record stores its data source name, acquisition date, license, processing version, and verification status in its metadata.

Technical Depth: Conforming to AGENTS.md Rule 3 & 9, every exported GeoJSON feature embeds provenance attributes: `height_source`, `floor_source`, `model_version`, `provenance_status`, and `license_id`, ensuring complete transparency for government audits.

Q18: How do you prevent your system from making false claims?

Short Answer: Through strict constitutional coding rules: deterministic math for geometry, explicit qualitative confidence ratings, and mandatory human review for all anomalies.

Technical Depth: We enforce qualitative confidence levels (HIGH, MEDIUM, LOW, NOT_DETERMINABLE) derived from transparent validation criteria. Numerical accuracies are never quoted unless verified against ground-truth holdouts.

Q19: What is your testing and quality assurance status?

Short Answer: Our automated test suite achieved 124 out of 124 passed tests (100%), and our demo pre-flight health check verified all data files and frontend endpoints.

Technical Depth: Tested via `pytest` across 12 test modules covering ingestion, CRS projection, Shapely topology, raster sampling, Random Forest regression, Isolation Forest anomalies, and reviewer state transitions. All tests pass with zero regressions.

Q20: Why are you running a lightweight demo launcher tomorrow instead of the full pipeline?

Short Answer: The lightweight demo launcher starts instantly on Port 8000 and uses verified pre-processed data, avoiding slow external satellite downloads or network failures during the pitch.

Technical Depth: `run_pipeline.py` is a heavy batch process that crops large satellite rasters and trains ML models. `run_demo.py` provides a deterministic, zero-latency presentation server that runs 100% offline, guaranteeing a flawless live demonstration.

Q21: How does your 3D unit slicing work when floor plans are not available?

Short Answer: We generate synthetic vertical volume units by equally slicing the building's 3D height by its verified floor count, assigning unique hierarchical volume IDs.

Technical Depth: For a 9-meter building with 3 floors, each floor is allocated a 3.0m vertical Z-extent ([0,3), [3,6), [6,9]). While internal flat partitions require CAD/BIM floor plans, this provides the first necessary spatial anchor linking vertical storeys to parent land parcels.

Q22: What are the biggest limitations of the current implementation?

Short Answer: The 30m satellite elevation resolution limits fine architectural precision, and internal unit walls are not yet mapped due to the lack of digitized CAD floor plans.

Technical Depth: Global open rasters (Copernicus/SRTM) have a 30m spatial footprint, which smooths roof details. Furthermore, while the demo session logger is fully functional, an enterprise multi-user PostgreSQL/PostGIS database is required for production state deployment.

Q23: How can state land revenue departments actually deploy and use BoundaryLens?

Short Answer: As a secure decision-support portal integrated into state land record systems (e.g., Mahabhulekh), allowing survey officers to review and validate vertical property linkages before formal registration.

Technical Depth: BoundaryLens exports standard OGC-compliant GeoJSON and 3D Tiles. Revenue officers use the web console to audit building extrusions, resolve spatial anomalies, and export approved vertical linkage records directly to the cadastral database.

Q24: How does BoundaryLens align with the vision of DILRMP and NAKSHA?

Short Answer: It operationalizes the transition from 2D land digitisation to 3D vertical property mapping, directly addressing the urban multi-storey cadastre goals envisioned in NAKSHA.

Technical Depth: DILRMP has achieved near-complete 2D cadastral computerization across Maharashtra. NAKSHA pilots are testing drone and 3D property concepts. BoundaryLens bridges the gap by linking existing 2D cadastral records to emerging 3D spatial models without expensive proprietary software.

Q25: What are your immediate future technical plans?

Short Answer: Ingesting drone LiDAR point clouds (LAS) for 5cm vertical accuracy, integrating RERA architectural CAD floor plans, and transitioning to a persistent PostGIS backend.

Technical Depth: Immediate priorities include integrating PDAL for processing airborne LiDAR point clouds, writing an automated DXF/IFC parser for apartment layouts, and extending the data model underground for sub-surface metro and utility cadastre.

20. EXECUTIVE ONE-PAGE REFERENCE CHEAT SHEET

BOUNDARYLENS AT A GLANCE • SIH26011 FINAL DEFENSE CHEAT SHEET

The Problem & Solution

Problem: Traditional 2D cadastral ULPINs collapse multi-storey vertical apartments onto a single flat coordinate point, creating property ownership ambiguity.

Solution: BoundaryLens creates a *proposed 3D spatial linkage* connecting ground cadastral parcels to vertical multi-level volumes using multi-sensor elevation, machine learning floor disambiguation, and human verification.

Core Geospatial Math

Base Terrain: $Z_{\text{base}} = \text{DEM}(x, y)$ (Bare-earth terrain)

Surface Level: $Z_{\text{surface}} = \text{DSM}(x, y)$ (Top of structure)

Height Signal: $\text{Height} = \max(0, Z_{\text{surface}} - Z_{\text{base}})$

Vegetation Check: $\text{NDVI} = \frac{\text{NIR} - \text{Red}}{\text{NIR} + \text{Red}}$ (Detects tree canopies)

AI & Machine Learning Engine

- **Floor Model:** Random Forest Regressor (6 morphological features, 12,762 training records, MAE 1.21 on holdout).
- **Anomaly Detection:** Isolation Forest (3% contamination) flags structural and vegetation outliers.
- **Ethical Rule:** AI assists; human officers adjudicate.

Human Verification (Rule 8)

- **Actions:** APPROVE • CORRECT • REJECT • UNRESOLVED
- **Audit Trail:** Captures timestamp, reviewer ID, reason, and prior state.
- **Transparency:** Green **OBSERVED** vs Amber **ESTIMATED** labels.

The 5 Critical Numbers to Remember

124 / 124	2,734	26	12,762	82
Automated Unit & Integration Tests Passed (100%)	3D Buildings Processed in Baramati Pilot	Cadastral Parcels Linked to 3D Geometry	Regional Buildings Used to Train Floor Model	Anomalies Safely Flagged for Human Review

The 10 Golden Phrases for Tomorrow's Presentation

1. **"Proposed 3D spatial linkage"** (Never say we officially generate or alter government ULPINs).
2. **"Evidence-based hierarchy"** (We keep track of whether data is observed, estimated, or conflicting).
3. **"Multi-sensor fusion"** (We combine cadastral maps, OSM vectors, DEM ground terrain, DSM surface, and Sentinel-2 NDVI).
4. **"Height is an evidence signal"** (DEM/DSM indicates elevation difference, but does not directly guarantee exact floor counts).
5. **"Observed versus estimated"** (We never present machine learning predictions as surveyed facts).
6. **"Vegetation canopy disambiguation"** (NDVI prevents tall trees over roofs from being mistaken for skyscrapers).
7. **"Isolation Forest anomaly detection"** (Unsupervised AI flags abnormal geometries for manual inspection).
8. **"Human-in-the-loop verification"** (Statutory accountability remains with human revenue officers).
9. **"Non-destructive workflow"** (We add vertical intelligence without disrupting existing 2D land registry formats).
10. **"100% reproducible open-source stack"** (124/124 tests passed; operates fully offline on MapLibre and Python).

Presentation Readiness Verdict: System is 100% verified, stable, reproducible, and constitutionally compliant. Good luck for SIH 2026!