

CS315: DATABASE SYSTEMS

RELATIONAL MODEL

Arnab Bhattacharya

`arnabb@cse.iitk.ac.in`

Computer Science and Engineering,
Indian Institute of Technology, Kanpur

`http://web.cse.iitk.ac.in/~cs315/`

2nd semester, 2019-20

Tue, Wed 12:00-13:15

Relation

- A **relation** is a subset of the cross-product of sets
- For sets D_1, D_2, \dots, D_n , a relation r is a set of n -ary tuples of the form (a_1, a_2, \dots, a_n) where each $a_i \in D_i$
- Example
 - `name = {A, B, C}`
 - `designation = {L, E, W}`
 - `identifier = \mathcal{N}`
 - $r = \{(A, E, 4), (B, E, 9), (C, W, 23)\}$ is a relation over
`name \times designation \times identifier`
- Relations are *unordered*

Relation

- A **relation** is a subset of the cross-product of sets
- For sets D_1, D_2, \dots, D_n , a relation r is a set of n -ary tuples of the form (a_1, a_2, \dots, a_n) where each $a_i \in D_i$
- Example
 - `name` = {A, B, C}
 - `designation` = {L, E, W}
 - `identifier` = \mathcal{N}
 - $r = \{(A, E, 4), (B, E, 9), (C, W, 23)\}$ is a relation over
`name` \times `designation` \times `identifier`
- Relations are *unordered*
- Generally depicted as a table

name	designation	identifier
A	E	4
B	E	9
C	W	23

Attribute

- Each attribute of a relation has a name
- There is a domain for each attribute
- Attributes are *generally* **atomic**
 - Indivisible, not sets
- Domain is atomic if all members are atomic
- Special value **null** in every domain

Relation Schema and Tuple

- The sets define a **relation schema**
- Example
 - Schema is `Person = (name, designation, identifier)`
- Relations are defined over a schema
- If schema is R , relation is denoted by $r(R)$
 - Example: `persons(Person)`
- A **relation instance** is a particular instance from the schema
 - Earlier example
- An element of a relation (instance) is a **tuple**

Relation Schema and Tuple

- The sets define a **relation schema**
- Example
 - Schema is `Person = (name, designation, identifier)`
- Relations are defined over a schema
- If schema is R , relation is denoted by $r(R)$
 - Example: `persons(Person)`
- A **relation instance** is a particular instance from the schema
 - Earlier example
- An element of a relation (instance) is a **tuple**
- Tuples are rows and attributes are columns

Database

- Consists of multiple *inter-related* relations
- Each relation stores information about a particular relationship

Database

- Consists of multiple *inter-related* relations
- Each relation stores information about a particular relationship
- Alternatively, a single relation can store all data
- Problems
 - Data repetition
 - Need for null values
- Normalization theory deals with how to design relation schemas

Key

- $K \subseteq R$ is a **superkey** of R if and only if values for K are sufficient to identify a unique tuple in *all* possible relations $r(R)$
 - Possible $r(R)$ signifies a relation that can exist from the data that is being modeled
- Example: $\{\text{name}\}$ is a superkey if each person has a unique name, otherwise not
- All supersets of superkeys are superkeys
 - $\{\text{name, designation}\}$ is also a superkey
- In practical situations, an id will be used which is guaranteed to be a superkey

Key

- $K \subseteq R$ is a **superkey** of R if and only if values for K are sufficient to identify a unique tuple in *all* possible relations $r(R)$
 - Possible $r(R)$ signifies a relation that can exist from the data that is being modeled
- Example: {name} is a superkey if each person has a unique name, otherwise not
- All supersets of superkeys are superkeys
 - {name, designation} is also a superkey
- In practical situations, an id will be used which is guaranteed to be a superkey
- A superkey K is a **candidate key** if K is minimal, i.e., no proper subset of it is a superkey
 - {name} is a candidate key

Key

- $K \subseteq R$ is a **superkey** of R if and only if values for K are sufficient to identify a unique tuple in *all* possible relations $r(R)$
 - Possible $r(R)$ signifies a relation that can exist from the data that is being modeled
- Example: $\{\text{name}\}$ is a superkey if each person has a unique name, otherwise not
- All supersets of superkeys are superkeys
 - $\{\text{name, designation}\}$ is also a superkey
- In practical situations, an id will be used which is guaranteed to be a superkey
- A superkey K is a **candidate key** if K is minimal, i.e., no proper subset of it is a superkey
 - $\{\text{name}\}$ is a candidate key
- There may be multiple candidate keys
 - $\{\text{name}\}$, $\{\text{identifier}\}$ are candidate keys

Key

- $K \subseteq R$ is a **superkey** of R if and only if values for K are sufficient to identify a unique tuple in *all* possible relations $r(R)$
 - Possible $r(R)$ signifies a relation that can exist from the data that is being modeled
- Example: {name} is a superkey if each person has a unique name, otherwise not
- All supersets of superkeys are superkeys
 - {name, designation} is also a superkey
- In practical situations, an id will be used which is guaranteed to be a superkey
- A superkey K is a **candidate key** if K is minimal, i.e., no proper subset of it is a superkey
 - {name} is a candidate key
- There may be multiple candidate keys
 - {name}, {identifier} are candidate keys
- **Primary key** is a candidate key chosen to serve as the primary means of identifying tuples
 - Choice is arbitrary as it depends on the database designer
 - Other candidate keys are called **secondary keys**

Foreign Key

- A relation schema may have an attribute that is unique (e.g., a primary key) in another schema
- This attribute is then called a **foreign key**
- Example
 - depositor = (name, number)
 - customer = (name, street, city)
 - account = (number, balance)
 - name and number in depositor are foreign keys
- Values in the foreign key attribute of the **referencing relation** may only come from those in the primary key of the **referenced relation**

Entity-Relationship Model

- **Entity-Relationship Model:** A database is a collection of *entities* and *relationships* among them

Entity-Relationship Model

- **Entity-Relationship Model**: A database is a collection of *entities* and *relationships* among them
- An **entity** is an object that exists and is distinguishable from objects, e.g., person “A”
- Entities have **attributes**, e.g., persons have names
- An **entity set** is a set of entities of the same type that share the same properties, e.g., a set of persons

Entity-Relationship Model

- **Entity-Relationship Model**: A database is a collection of *entities* and *relationships* among them
- An **entity** is an object that exists and is distinguishable from objects, e.g., person “A”
- Entities have **attributes**, e.g., persons have names
- An **entity set** is a set of entities of the same type that share the same properties, e.g., a set of persons
- A **relationship** is an association among the entities
- A **relationship set** is a relation among two or more entities, each taken from an entity set, e.g., person is a depositor for an account

Entity-Relationship Model

- **Entity-Relationship Model**: A database is a collection of *entities* and *relationships* among them
- An **entity** is an object that exists and is distinguishable from objects, e.g., person “A”
- Entities have **attributes**, e.g., persons have names
- An **entity set** is a set of entities of the same type that share the same properties, e.g., a set of persons
- A **relationship** is an association among the entities
- A **relationship set** is a relation among two or more entities, each taken from an entity set, e.g., person is a depositor for an account
- Relationship sets can also have attributes, e.g., access date for depositor
- Primary keys of entity sets form a superkey of the relationship set

Model Parameters

- Relationships between two entity sets are *binary*
 - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many

Model Parameters

- Relationships between two entity sets are *binary*
 - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many
- Attributes may be
 - Simple or composite
 - Single-valued or multi-valued (e.g., phone number)
 - Derived (e.g., age)

Model Parameters

- Relationships between two entity sets are *binary*
 - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many
- Attributes may be
 - Simple or composite
 - Single-valued or multi-valued (e.g., phone number)
 - Derived (e.g., age)
- Participation can be total (every entity participates in the relationship) or partial (not all participate)


Model Parameters

- Relationships between two entity sets are *binary*
 - It is rare to have more than degree two
- Cardinality constraints for binary relationships can be one-to-one, one-to-many, many-to-one or many-to-many
- Attributes may be
 - Simple or composite
 - Single-valued or multi-valued (e.g., phone number)
 - Derived (e.g., age)
- Participation can be total (every entity participates in the relationship) or partial (not all participate)
- Specialization, generalization, aggregation are features of extended ER model

Weak Entity Sets

- An entity set that does *not* have a primary key is called a **weak entity set**
- Its existence depends on the existence of another entity set called the **identifying entity set** or **owner entity set**
- The **identifying relationship set** that exists between the two must be *total* and *many-to-one* from the weak entity set
- A weak entity set has a *discriminator* or **partial key** instead of a primary key
- The discriminator distinguishes weak entities that are related to the same entity of the identifying entity set
- The *primary key* is formed by the primary key of the identifying set and the discriminator


ER Diagram: Summary



ER Diagram: Description

- Entity sets: rectangles
- Relationship sets: diamonds
- Attributes: ellipses
 - Multivalued attributes: double ellipses
 - Derived attributes: dashed ellipses
- Primary keys: underlines
- Roles: on links
- Cardinality constraints
 - One: directed
 - Many: undirected
 - One-to-many: directed-diamond-undirected
- Participation
 - Total: double line
 - Partial: single line
- Cardinality limits: on lines
- Weak entity sets: double rectangle
- Weak relationship set: double ellipse
- Discriminator of a weak entity sets: underline with dashed lines

Example: Banking Schema



Reduction to Relational Model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
 - A foreign key relationship is established
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
 - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships,

Reduction to Relational Model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
 - A foreign key relationship is established
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
 - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial,

Reduction to Relational Model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
 - A foreign key relationship is established
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
 - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial, null values are used
- Many-to-many relationships

Reduction to Relational Model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
 - A foreign key relationship is established
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
 - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial, null values are used
- Many-to-many relationships must be reduced to relations
- Each component of a composite attribute is modeled separately
- Multivalued attributes

Reduction to Relational Model

- Entity sets and relationships sets are reduced uniformly to relations
- A weak entity set is reduced to a relation by including the primary key attributes of the identifying set
 - A foreign key relationship is established
- Many-to-one and one-to-many relationships that are total on the many side may not be reduced to a relation
 - Primary key of entity on “one” side is added to relation of entity on “many” side
- For one-to-one relationships, any side can be chosen as “many”
- If participation is partial, null values are used
- Many-to-many relationships must be reduced to relations
- Each component of a composite attribute is modeled separately
- Multivalued attributes are reduced to relations that include the primary key of the entity set