A COMPLETE MODEL COMPARISON

Tables A.1 and A.2 combine the results from the main paper with one new run of GPT-6 Luna and GPT-6.1 Sol on each of the 69 CSVStorm files. New model names are marked "(new)". Both models used the default medium reasoning effort and fresh API requests without local response-cache reuse. The Hybrid+DuckDB variant was evaluated only with the new models. Figure A.1 highlights exact reconstruction accuracy for three representative models evaluated with all three agentic architectures.

	System	SuT Success [%]	Pollock Score	Accuracy [%]
Hybrid	GPT-5.6 Sol	100.0	9.94	82.6
	GPT-5.6 Luna	100.0	9.71	73.9
	GPT-5.4 Mini	94.2	9.23	63.8
	Qwen3.5 0.8B	100.0	7.53	27.5
	GPT-6 Luna (new)	100.0	9.93	79.7
	GPT-6.1 Sol (new)	100.0	9.94	84.1
H+DB	GPT-6 Luna (new)	100.0	9.93	84.1
	GPT-6.1 Sol (new)	**100.0**	**9.94**	**85.5**
Full Agentic	GPT-5.6 Sol	98.6	9.57	73.9
	GPT-5.4 Mini	53.6	5.21	37.7
	GPT-6 Luna (new)	89.9	8.67	58.0
	GPT-6.1 Sol (new)	94.2	9.02	66.7
Custom Parser Code	GPT-5.6 Sol	68.1	6.71	44.9
	GPT-5.6 Luna	79.7	7.75	49.3
	GPT-5.4 Mini	95.7	8.46	34.8
	Qwen3.5 0.8B	0.0	0.00	0.0
	GPT-6 Luna (new)	95.7	9.37	63.8
	GPT-6.1 Sol (new)	97.1	9.56	62.3
Baselines	CleverCSV	100.0	8.67	55.1
	DuckDB Parse*	100.0	9.27	40.6
	DuckDB Auto	98.6	8.22	34.8
	PyCSV	94.2	8.73	10.1
	Pandas*	98.6	8.06	33.3

* denotes oracle-assisted parsing with access to file-format metadata such as the dialect.

Table A.1: CSVStorm results on 68 irregular and one control file, extending Table 1. SuT Success measures non-crashing runs. Accuracy measures exact reconstruction. H+DB adds DuckDB dialect sniffing to the hybrid parser. "(new)" identifies the new GPT-6 runs.




Figure A.1: Exact reconstruction accuracy for three agentic architectures and three representative models from Table A.1. The selected models were evaluated with each architecture; GPT-6.1 Sol is the new run.

Model	Acc.	Time		Cost	
	(%)↑	Median (s/file)↓	Total (s)↓	Median ($/file)↓	Total ($)↓
GPT-5.6 Sol	82.6	5.57	1092.54	0.0177	12.3958
GPT-5.6 Luna	73.9	4.64	563.20	0.0049	2.4736
GPT-5.4 Mini	63.8	**2.34**	**269.22**	0.0024	0.3375
Qwen3.5 0.8B	27.5	12.08	1402.32	Local	Local
GPT-6 Luna (new)	79.7	5.74	886.38	**0.00046**	**0.2518**
GPT-6.1 Sol (new)	**84.1**	3.74	618.28	0.00627	4.7109

Table A.2: Performance, runtime, and cost of the hybrid repair approach, extending Table 2. "(new)" identifies the new GPT-6 runs. Local models incur no API charge. New-run costs use recorded token usage and standard API rates and are not invoice totals.

The new timing measurements include network and provider latency and were made while other benchmark configurations were running. The custom parser code implementation does not save API token usage, so its cost cannot be reported from these runs.