

Scenario 1: Bad Container Image Deployment

Objective

Trace an incomplete Kubernetes rollout from a Datadog signal to the Deployment image and Amazon ECR, then recover safely.

Trigger the Incident

Run this from the repository root against your own lab environment:

```
./scripts/chaos/bad-deploy.sh banking banking-backend banking-backend
```

The script changes the live Deployment image to a nonexistent tag. Wait for Datadog and Kubernetes to observe the failed rollout before troubleshooting. Do not run another scenario until this one has been recovered.

Situation

The banking application still serves users, but a new release has not completed. Do not run the trigger yourself unless you are facilitating the lab.

Symptoms

- The rollout does not complete.
- New pods do not start while existing pods may remain healthy.

What You Know

- The issue began immediately after a banking backend release.
- Datadog shows the `banking-backend` Deployment with unavailable replicas and new pods that are not Ready.
- Existing pods may still serve traffic.

Start With Datadog

1. Go to **Infrastructure > Kubernetes > Explorer**, select **Pods** under **Select Resources**, and set the time range to **Past 30 Minutes**.

2. In **Filter by**, enter `kube_namespace:banking kube_deployment:banking-backend`. Open the newest pod whose status is `ErrImagePull` or `ImagePullBackOff`, then record its pod name and image.
3. Go to **Events > Explorer**, keep **Past 30 Minutes**, and search `kube_namespace:banking status:(warning OR error)`. Open an event containing `ErrImagePull`, `ImagePullBackOff`, `Failed to pull image`, or `does-not-exist`.

`kubernetes_state.deployment.replicas_unavailable` can remain `0` in this scenario because the two old pods continue serving while Kubernetes creates one bad surge pod. Use the desired-versus-updated gap plus the image-pull event as the primary evidence.

Record the first event timestamp, failed pod, and requested image before using `kubectl`.

Troubleshooting

1. Check the Deployment summary.

```
kubectl get deployment banking-backend -n banking
```

Expected output: `READY` remains `2/2`, `AVAILABLE` remains `2`, but `UP-TO-DATE` is only `1`. This means the old replicas are healthy while the new rollout is incomplete.

1. Find the failed new pod.

```
kubectl get pods -n banking -l app=banking-backend
```

Expected output: two older pods are `Running`, while the newest pod is `ErrImagePull` or `ImagePullBackOff` and shows `0/1 Ready`.

1. Inspect the failed pod and its recent events.

```
kubectl describe pod <pod-name> -n banking
```

Expected output: the **Events** section contains `Failed to pull image`, the requested tag ends in `does-not-exist`, and the registry reports that the image was not found.

1. Confirm the image configured on the Deployment.

```
kubectl get deployment banking-backend -n banking \
-o jsonpath='{.spec.template.spec.containers[0].image}'
```

Expected output: an ECR image URL ending in `:does-not-exist`.

1. Compare the requested tag with the images that actually exist in ECR.

```
aws ecr describe-images --repository-name sre-lab/banking-backend \
  --region us-east-1 --query 'imageDetails[].imageTags' --output table
```

Expected output: valid image tags are listed, but `does-not-exist` is absent. The missing ECR tag is the root cause.

Important Clues

Connect the Datadog replica mismatch with `ErrImagePull` or `ImagePullBackOff`, Kubernetes events, and the ECR image list.

Root Cause

Record your conclusion from Datadog, Kubernetes, and ECR evidence. Confirm it with the instructor after the exercise.

Fix

Roll back to the last working revision.

```
kubectl rollout history deployment/banking-backend -n banking
kubectl rollout undo deployment/banking-backend -n banking
```

Validation

```
kubectl rollout status deployment/banking-backend -n banking
kubectl get pods -n banking
```

Confirm the application still works, unavailable replicas return to zero, and the Datadog monitor recovers.

DevOps Lesson

Validate an ECR tag before changing a Kubernetes Deployment. A healthy old ReplicaSet does not mean a release succeeded.

STAR Method

Situation

Summarize the failed rollout without naming the cause first.

Task

Explain the safe recovery objective.

Action

Describe the evidence path from Datadog to Kubernetes and ECR.

Result

State how rollout and observability recovery were verified.

Natural Spoken Version

Use the matching example in [DevOps STAR Scenarios](#) after completing the lab.

Brief STAR Example

One of our EKS releases referenced image tag `v2.4.1`, but only `v2.4.0` existed in ECR. My task was to restore a safe rollout without interrupting the old healthy replicas. I used Datadog and Kubernetes events to confirm `ImagePullBackOff`, verified that the tag was missing in ECR, and rolled back the Deployment. The application remained available, the rollout recovered, and we added image-tag validation to the pipeline.