

## Week 04 - Part 01

Before we start, some announcements:

1 - We cannot change the tutorial times.

2 - WS solutions will be posted weekly (on the Wednesday of the tutorials). This gives you time to work on the WS on your own and test/improve your understanding

3 - A list of useful documents to review probability, linear algebra, and matrix calculus is posted on Course page.

4. You MUST write your own solution to each week's WS before checking the solutions and going to tutorials. This is the only way to learn. You do not need to submit your solutions.

## Week 04 - Part 01

Last week Recap: Logistic Regression & Gradient descent

- We saw the activation function and log-loss function.
- We saw the Maximum likelihood and Cross-Entropy Minimization interpretation of minimizing log-loss.
- We don't have a closed form solution for minimizing the log-loss function
- Hence, we used gradient descent to numerically find the minimizer

$$\underline{g}_t = -\nabla f(\underline{x}_t)$$

$$\underline{x}_{t+1} = \underline{x}_t + \epsilon_t \underline{g}_t$$

## A Quick Recall Before We Move On

Recall: Let  $f: \mathbb{R}^n \rightarrow \mathbb{R}$  and  $g: \mathbb{R} \rightarrow \mathbb{R}$ . Then

$$\nabla_{\underline{x}} g(f(\underline{x})) =$$

E.g.:  $\nabla_{\underline{x}} (1 + \log(\underline{a}^T \underline{x}))^2 =$

Homework: Prove the chain rule.

# Using Gradient Descent for Logistic Regression

■ Logistic Regression in-sample Error:

$$E_{in}(\underline{w}) = \frac{1}{N} \sum_{n=1}^N e_n(\underline{w}) = \frac{1}{N} \sum_{n=1}^N \log(1 + e^{-y_n \underline{w}^T \underline{x}_n})$$

$$\nabla_{\underline{w}_t} E_{in}(\underline{w}_t) = \frac{1}{N} \sum_{n=1}^N \nabla_{\underline{w}_t} e_n(\underline{w}_t) = \frac{1}{N} \sum_{n=1}^N \nabla_{\underline{w}_t} \log(1 + e^{-y_n \underline{w}_t^T \underline{x}_n})$$

■ Thus, Gradient Descent would update  $\underline{w}_t$  by

$$\underline{g}_t = -\nabla E_{in}(\underline{w}_t) = -\frac{1}{N} \sum_{n=1}^N \nabla e_n(\underline{w}_t)$$

$$\underline{w}_{t+1} = \underline{w}_t + \epsilon_t \underline{g}_t$$

■ Good News:

□ It can be shown that  $\frac{1}{N} \sum_{n=1}^N \log(1 + e^{-y_n \underline{w}^T \underline{x}_n})$  is convex.  
□

■ Bad News:

□ To run one iteration of Gradient Descent, we need to find  $\nabla_{\underline{w}_t} e_n(\underline{w}_t)$  for all  $n \in \{1, 2, \dots, N\}$  points.

□ This is costly, specially when  $N$  is large (big data).

■

# Stochastic Gradient Descent (SGD)

Gradient Descent (GD):  $\underline{w}_{t+1} = \underline{w}_t - \epsilon_t \nabla_{\underline{w}_t} E_{in}(\underline{w}_t)$  The average gradient of the points  $\frac{1}{N} \sum_{n=1}^N \nabla e_n(\underline{w}_t)$

Stochastic Gradient Descent (SGD): In each iteration,



■ But does it work?

☐ It has been proven that for convex functions and under mild conditions, SGD will find the solution.

☐ Don't worry about the proof. Don't worry about the conditions.

Note 1:  $\underline{g}_t$  of SGD is an unbiased estimate of  $\nabla E_{in}(\underline{w}_t)$

Let's study the expected update direction derived by SGD in each step.

$$\mathbb{E}[\underline{g}_t]$$



## Note 2: Full GD Complexity V.S. SGD Complexity

■ Full GD ("batch GD"): Per iteration complexity is



■ SGD: Per iteration complexity is

□ Complexity of [?] iteration of SGD = Complexity of 1 iteration of GD

Note 3: "mini-batch" GD is full-batch GD combined with SGD

■ mini-batch GD: In each iteration:

- Choose  $M$  sample  $r_1, r_2, \dots, r_M \in \{1, \dots, N\}$  uniformly at random

- $\underline{g}_t = \frac{1}{M} \sum_{i=1}^M \nabla e_{r_i}(\underline{w}_t)$

- $\underline{w}_{t+1} = \underline{w}_t + \epsilon_t \underline{g}_t$

■ Benefits:



# PLA is An Extremes Version of Logistic Regression with SGD

■ logistic regression with SGD updates:

$$\nabla e_n(\underline{w}_t) = \frac{-y_n \underline{x}_n}{1 + e^{y_n \underline{w}_t^T \underline{x}_n}}$$

$$\text{and } \underline{w}_{t+1} = \underline{w}_t + \epsilon_t \frac{y_n \underline{x}_n}{1 + e^{y_n \underline{w}_t^T \underline{x}_n}}$$

■ When we randomly pick some  $\underline{x}_n$  which is misclassified

$$\square y_n \underline{w}_t^T \underline{x}_n \leq 0 \implies 0 < e^{y_n \underline{w}_t^T \underline{x}_n} \leq 1$$

$$\square \text{ The SGD update would be } \underline{w}_{t+1} = \underline{w}_t + \frac{\epsilon_t}{1 + e^{y_n \underline{w}_t^T \underline{x}_n}} (y_n \underline{x}_n)$$

□ In extreme case,  $e^{y_n \underline{w}_t^T \underline{x}_n} \approx 0$  and the update rule would be

$$\underline{w}_{t+1} \approx \underline{w}_t + \epsilon_t (y_n \underline{x}_n) \quad (\text{Same as PLA if } \epsilon_t = 1.)$$

■ When we randomly pick some  $\underline{x}_n$  which is correctly classified.

$$\square y_n \underline{w}_t^T \underline{x}_n > 0 \implies 1 < e^{y_n \underline{w}_t^T \underline{x}_n}$$

$$\square \text{The SGD update would be } \underline{w}_{t+1} = \underline{w}_t + \frac{\epsilon_t}{1 + e^{y_n \underline{w}_t^T \underline{x}_n}} \cdot (y_n \underline{x}_n)$$

$\square$  In extreme case,  $\frac{1}{1 + e^{y_n \underline{w}_t^T \underline{x}_n}} \approx 0$  and the update rule would be

$$\underline{w}_{t+1} \approx \underline{w}_t$$

(Same as PLA as it does not  
update  $\underline{w}$  for correctly classified points)

