ANNUAL REPORT

ELMVALEWASTEWATER TREATMENT PLANT

FOR THE PERIOD: JANUARY 1, 2016 – DECEMBER 31, 2016

Prepared for the Corporation of the Township of Springwater by the Ontario Clean Water Agency





Ministry of the Environment & Climate Change Barrie District Office 54 Cedar Point Drive, Unit 1203 Barrie, ON L4N 5R7

ATTN: Water Compliance Supervisor

RE: 2016 Annual Performance Report for the Elmvale Wastewater Treatment

Plant

1128 Flos Road Ten, East, Springwater Township

The enclosed 2016 report for the above-referenced facility summarizes the performance and related activities in accordance with Certificate of Approval (CofA) #4989-66ZRKT; Condition 10 (6) as follows:

a) A summary and interpretation of all monitoring data and a comparison to the effluent limits outlined in Condition 7, including an overview of the success and adequacy of the Works;

Table 1 - Monitoring Plan

SOURCE	PARAMETER	FREQUENCY	METHOD		
	CBOD5				
RAW SEWAGE	Suspended Solids	Monthly			
(24-hour composite)	Total Kjeldahl Nitrogen				
	Total Phosphorus	Weekly			
	CBOD5	Monthly	External Analysis		
	Suspended Solids	WOTHIN	External Analysis		
FINAL EFFLUENT	Total Phosphorus	Weekly			
(24-hour composite,	Total Ammonia Nitrogen				
except <i>E.Coli</i> , pH &	Nitrate Nitrogen	Monthly Executed Weekly Solids Weekly Nitrogen			
Temperature are grab)	E.Coli				
	рН	Weekly	In-house		
	Temperature	VVCCKIY	In-house		

Table 2 - Effluent Limits & Comparison

SOURCE	PARAMETER	ANNUAL MAXIMUM	ANNUAL AVERAGE	COMPLIANCE LIMITS
EFFLUENT	CBOD5 (mg/L)	2.0	2.0	10.0 ANNUAL AVERAGE
	CBOD5 (kg/day)	2.6	2	18.0 ANNUAL AVERAGE
	TSS (mg/L)	7.0	2.6	5.0 ANNUAL AVERAGE
	TSS (kg/day)	6.1	2.4	9.0 ANNUAL AVERAGE
	Total Phosphorus (mg/L)	0.048	0.034	0.13 ANNUAL AVG (0.17 MONTHLY AVG)
	Total Phosphorus		0.03	0.30 MONTHLY AVG
	(kg/day)	0.05	0.31	82.8 CUMULATIVE ANNUAL
	рН	8.26	7.42	6.0 - 9.5 ALL TIMES

Table 3 - Total Phosphorus Loadings

	ELMV	ALE WWTP TOTAL PHOSPHO	RUS LOADINGS
2016	ADF	MONTHLY AVG. CONC. (mg/L)	MONTHLY AVG. LOADING (kg/day)
Jan	1047.42	0.045	0.047
Feb	1302.45	0.038	0.049
Mar	2091.26	0.048	0.100
Apr	1369.50	0.033	0.045
May	894.81	0.038	0.034
Jun	752.13	0.030	0.023
Jul	635.10	0.050	0.032
Aug	714.84	0.056	0.040
Sep	690.71	0.040	0.028
Oct	643.39	0.033	0.021
Nov	691.38	0.050	0.035
Dec	883.11	0.115	0.102
	Cum	ulative Yearly Loading (kg) =	14.16
		Avg. Monthly Loading (kg) =	0.046

The effluent parameters specified in the above table were analyzed by SGS Canada Inc., Lakefield, Ontario.

Table 4 - Daily Effluent Flow Data

MONTH	AVERAGE DAILY FLOW (m³)	PEAK FLOW (m³)	TOTAL FLOW (m³)
DESIGN	1800.0	6600.0	-
JANUARY	1047.42	1629.00	32470.00
FEBRUARY	1302.45	2319.00	37771.00
MARCH	2091.26	5434.00	64829.00
APRIL	1369.50	2284.00	41085.00
MAY	894.81	1210.00	27739.00
JUNE	752.13	955.00	22564.00
JULY	635.10	774.00	19688.00
AUGUST	714.84	1493.00	22160.00
SEPTEMBER	690.71	978.00	20721.30
OCTOBER	643.39	843.10	19945.20
NOVEMBER	691.38	1020.00	20049.90
DECEMBER	883.11	1311.00	27376.30
2016	AVERAGE: 976.34	MAXIMUM: 5434.00	TOTAL: 356398.70

The average daily flow for 2016 was 976.34m³, which is approximately 54% of the specified design flow of 1800 m³/day.

There were no instances when the daily peak of 6600m³ was exceeded. The peak flow of 5434m³/day occurred in March 2016. The peak flow rate of 5434m³/day is 82% of the approved Peak Flow Rating for the Works. Based on the above monitoring program, the sewage works provided adequate treatment within the required average daily flows for all parameters.

Refer to Appendix A for detailed performance assessment.

b) A description of any operating problems encountered and corrective actions taken;

There were no operating problems encountered in 2016.

c) A summary of maintenance carried out on major structure, equipment, apparatus, mechanism or thing forming part of the Works;

Plant maintenance, including scheduled and non-scheduled maintenance, is monitored using the Hansen Work Management System. Work orders are generated monthly and any actions over and above this work is documented on corrective work orders and entered into the system for future reference.

- Annual sewage pumping station cleanouts and flushing of collection system
- Aeration tanks #1 & #2 clean-out and diffuser membrane replacement
- Repair to variable frequency drive at Bishop Park SPS
- -Upgrade flow chart recorder to Red Lion human-machine interface screen (HMI)
- -Emergency sewer line flush on Peter Street
- -Replace cathodic anodes in west clarifier
- -Filter air lift repairs

d) A summary of any effluent quality assurance or control measures undertaken in the reporting period;

The effluent parameters specified in the above table are analyzed by SGS Lakefield Research Ltd., an accredited lab in Ontario.

In-house tests are conducted by licensed operators for monitoring purposes using Standard Methods and the data generated from these tests is used to determine the treatment efficiency while maintaining process control. All inhouse monitoring equipment is calibrated based on the manufacturer's recommendations.

e) A summary of the calibration and maintenance carried out on all effluent monitoring field equipment;

Flow meters are used to measure the raw sewage and final effluent flows, all were successfully calibrated in October 25, 2016 by Flowmetrix Technical Services Inc.

Refer to Appendix B for calibration reports.

f) A description of efforts made and results achieved in meeting the Effluent Objectives of Condition 6, if the concentration objectives are not met;

In 2016, the Elmvale WWTP provided effective wastewater treatment producing effluent with removal rates of CBOD5, TSS and Total Phosphorus (TP) all between 94% - 99%. Effluent objectives were regularly met throughout 2016.

Three objective exceedances occurred in 2016. TP loading was exceeded on March 29th. Concentrations of TP in the effluent were low; however flow was elevated and resulted in the exceedance. TP concentrations on December 28th were elevated and resulted in exceeding TP loading objectives.

Staff routinely monitor plant effluent quality and adjust process as required to maintain a high level of effluent quality from the Elmvale WWTP.

Effluent pH was maintained within the Objective Limits at all times during 2016.

Refer to Appendix A for detailed performance assessment.

g) A tabulation of the volume of sludge generated in the reporting period, an outline of anticipated volumes to be generated in the next reporting period and a summary of the locations to where the sludge was disposed;

Sludge is hauled by Region of Huronia Environmental Services of New Lowell and applied to certified organic soil conditioning sites based on the "Guidelines for the Utilization of Biosolids on Agricultural Lands" dated March 1996.

Refer to Appendix C for the annual sludge analysis summary.

The table below shows a breakdown of sludge haulage for 2016.

Table 5 - Sludge Haulage 2016

DATE	SITE#	AMOUNT HAULED (m³)				
01-Sep-16	NASM21400	242.0				
02-Sep-16	NASM21400	694.0				
06-Sep-15	NASM21400	568.0				
07-Sep-15	NASM21400	284.0				
	TOTAL:	1788				

A total volume of 1788m³ was removed from the Elmvale WWTP and utilized as a soil conditioner on agricultural land on the above-stated sites and fields.

A total volume of 381m³ was transferred from the Snow Valley Highlands WWTP to Elmvale WWTP throughout the year.

A total volume of 517m³ was transferred from the Royal Oaks WWTP to Elmvale WWTP throughout the year.

h) A summary of any complaints received during the reporting period and any steps taken to address the complaints;

There were no complaints regarding the Elmvale WWTP during the 2016 reporting period.

i) A summary of all By-pass, spill or abnormal discharge events;

There was one (1) by-pass event and one (1) spill occurrence from the Works in 2016.

Heavy precipitation and snow melt stressed the Bishop Park sewage pumping station (SPS) beyond its capacity and resulted in a bypass event on March 28, 2016.

Utility workers drilled into the redundant 6" forcemain from Bishop Park SPS to Elmvale WWTP on May 26, 2017. This line is not currently used; however, the valve at the splitter chamber was open which allowed sewage to escape from the damaged 6" forcemain. The damaged pipe was isolated and repaired.

Both of these occurrences were reported to the appropriate authorities. Detailed reports are in Appendix D.

j) Any other information the District Manager requires from time to time.

There is no additional information for the 2016 reporting period.

Regards,

Richard Eagle

Senior Operations Manager

) Ecgl.

Ontario Clean Water Agency, North Simcoe Hub

c.c. Mark Archer, Director of Public Works, Township of Springwater

APPENDIX A

PERFORMANCE ASSESSMENT REPORT

Ontario Clean Water Agency Performance Assessment Report Wastewater/Lagoon

From: 01/01/2016 to 31/12/2016

Report extracted 03/21/2017 10:44
Facility: [5634] ELMVALE WASTEWATER TREATMENT FACILITY

Works: [110000169]

	01/2016	02/2016	03/2016	04/2016	05/2016	06/2016	07/2016	08/2016	09/2016	10/2016	11/2016	12/2016	<total></total>	<avg></avg>	<max></max>	<criteria></criteria>
Flows:	01/2010	02/2010	03/2010	04/2010	03/2010	00/2010	07/2010	00/2010	03/2010	10/2010	11/2010	12/2010	C=10tal=>	<avg></avg>	C-WidA>	C-Criteria->
	34164.00	37961.00	61741.00	39388.00	26204.00	20971.00	19464.00	21904.00	20394.45	21239.90	20654.00	28809.10	352894.45			
Raw Flow: Avg - Raw (m³/d)	1102.06	1309.00	1991.65	1312.93	845.29	699.03	627.87	706.58	679.82	685.16	688.47	929.33		964.77		
	1744.00	2172.00	4329.00	2318.00	1122.00	918.00	779.00	1489.00	915.00	970.10	1056.00	1288.00			4329.00	
	32470.00	37771.00	64829.00	41085.00	27739.00	22564.00	19688.00	22160.00	20721.30	19945.20	20049.90	27376.30	356398.70			
	1047.42	1302.45	2091.26	1369.50	894.81	752.13	635.10	714.84	690.71	643.39	691.38	883.11		976.34		
	1629.00	2319.00	5434.00	2284.00	1210.00	955.00	774.00	1493.00	978.00	843.10	1020.00	1311.00			5434.00	
Carbonaceous Biochemical Oxygen Demand: CBOD:																
	54.000	48.000	129.000	77.000	121.000	109.000	271.000	44.000	155.000	366.000	197.000	197.000		147.333	366.000	
Raw: # of samples of cBOD5 - Raw (mg/L)	1	1	1	1	1	1	1	2.000	1	1	1	1	12			10.0
	2.000 <	2.000 <	2.000 <	4.000 <	2.000	< 2.000	2.000	2.000	2.000	2.000	< 2.000	< 2.000	12	2.167 <	4.000	10.0
Eff: # of samples of cBOD5 - Eff (mg/L)	2.095 <	2.605 <	4.183 <	5.478 <	1.790	< 1.504	1 1.270	1 1.430 <	1 1.381	1 1.287	< 1.383	1 < 1.766	12	2.181 <	5.478	18.0
	96.296	95.833	98.450	94.805	98.347	98.165	99.262	95.455	98.710	99.454	98.985	98.985	<	2.181 <	99.454	18.0
Biochemical Oxygen Demand: BOD5:	30.230	33.033	30.430	34.003	30.547	30.103	33.202	93.433	30.710	33.434	30.303	30.303			33.434	
Total Suspended Solids: TSS:																
	60.000	67.000	87.000	65.000	80.000	78.000	219.000	39.000	115.000	291.000	219.000	106.000		118.833	291.000	
Raw: # of samples of TSS - Raw (mg/L)	1	1	1	1	1	1	1	1	1	1	1	1	12			
	2.000	4.000	4.000	2.000	2.000	2.000	4.000	2.000	3.000	< 2.000	< 2.000	< 2.000	<	2.583	4.000	5.0
Eff: # of samples of TSS - Eff (mg/L)	1	1	1	1	1	1	1	1	1	1	1	1	12			
Loading: TSS - Eff (kg/d)	2.095	5.210	8.365	2.739	1.790	1.504	2.540	1.430	2.072	1.287	< 1.383	< 1.766	<	2.682	8.365	
Percent Removal: TSS - Raw (mg/L)	96.667	94.030	95.402	96.923	97.500	97.436	98.174	94.872	97.391	99.313	99.087	98.113			99.313	
Total Phosphorus: TP:																
	2.583	2.305	1.582	1.955	2.552	3.228	3.793	2.820	3.423	3.530	3.294	3.097		2.847	3.793	
Raw: # of samples of TP - Raw (mg/L)	4	4	5	4	5	4	4	5	4	4	5	4	52			
	0.045 <	0.038 <	0.048 <	0.033	0.038	< 0.030	< 0.050	0.056 <	0.040	< 0.033	< 0.050	0.115	<	0.048	0.115	0.17
Eff: # of samples of TP - Eff (mg/L)	4	4	5	4	5	4	4	5	4	4	5	4	52			
	0.047 <	0.049 <	0.100 <	0.045	0.034	< 0.023	0.032	0.040 <	0.028	0.021	< 0.035	0.102	<	0.046	0.102	
Percent Removal: TP - Raw (mg/L) Nitrogen Series:	98.258	98.373	96.966	98.338	98.511	99.070	98.682	98.014	98.831	99.079	98.482	96.287			99.079	
	15.400	10.300	17.200	15.400	21.900	28.400	35.000	25.800	30.200	33.000	38.900	23.600		24.592	38.900	
Raw: # of samples of TKN - Raw (mg/L)	15.400	10.300	17.200	15.400	21.900	28.400	35.000	25.800	30.200	33.000	38.900	23.600	12	24.592	38.900	
	0.100	0.300	0.900	0.300 <	0.100	< 0.100	< 0.100	0.100	0.100	< 0.100	< 0.100	< 0.100	12	0.200	0.900	
Eff: # of samples of TAN - Eff (mg/L)	1	1	1	1	1	1	1	1	1	1	1	1	12	0.200	0.300	
	0.105	0.391	1.882	0.411 <	0.089	< 0.075	5 0.064	0.071	0.069	< 0.064	< 0.069	< 0.088	<	0.282	1.882	
	15.400	23.900	11.200	10.400	21.600	27.500	27.700	32.700	28.000	33.800	28.700	23.500		23.700	33.800	
Eff: # of samples of NO3-N - Eff (mg/L)	1	1	1	1	1	1	1	1	1	1	1	1	12			
	0.030	0.330	1.710	1.110	0.060	< 0.030	< 0.030	0.030	0.030	< 0.030	< 0.030	0.040	<	0.288	1.710	
Eff: # of samples of NO2-N - Eff (mg/L)	1	1	1	1	1	1	1	1	1	1	1	1	12			
Disinfection:																
Eff: GMD E. Coli - Eff (cfu/100mL)	2.000	2.000	4.000	2.000	2.000	1.000	2.000	2.000	10.000	40.000	2.000	16.000		7.083	40.000	200.0
						\perp			\perp							
						+		1								
						1										
																,
						\perp			\perp							
						1			1							
							+	1		+	+		+			

Ontario Clean Water Agency Time Series Info Report

From: 01/01/2016 to 31/12/2016

Report extracted 03/29/2017 10:45

Facility Org Number: 5634

Facility Works Number: 110000169

Facility Name: ELMVALE WASTEWATER TREATMENT FACILITY

Facility Owner: Municipality: Township of Springwater

Facility Classification: Class 2 Wastewater Treatment

Receiver: Wye River
Service Population: 2651.0
Total Design Capacity: 6600.0 m3/day

	01/2016	02/2016	03/2016	04/2016	05/2016	06/2016	07/2016	08/2016	09/2016	10/2016	11/2016	12/2016	Total	Avg	Max	Min
Eff / pH																
Max IH	7.86	7.7	7.69	7.62	7.57	7.55	7.38	7.68	7.39	7.37	7.51	7.69			7.86	
Mean IH	7.577	7.506	7.516	7.366	7.393	7.395	7.274	7.251	7.274	7.227	7.264	7.454		7.377		
Min IH	7.39	7.22	7.35	7	7.3	7.32	7.1	6.96	7.16	6.97	7.09	7.15				6.96

ELMVALE WWTP 2016 DAILY TOTAL PHOSPHORUS OBJECTIVE LIMITS

TP Loading Objective Limit = 0.18 kg/day
TP Concentration Objective Limit = 0.1 mg/L

		TP	TP			TP	TP
Jan	Flow (m ³)	Conc	Loading	July	Flow (m ³)	Conc	Loading
5	1006	0.08	0.080	4	720	0.03	0.022
13	899	0.03	0.027	11	679	0.11	0.075
19	1213	0.03	0.036	20	523	0.03	0.016
25	1178	0.04	0.047	26	580	0.03	0.017
Feb				August			
2	2180	0.03	0.065	3	522	0.03	0.016
9	1207	0.03	0.036	8	581	0.08	0.046
17		0.06	0.048	15	604	0.06	0.036
23	1339	0.03	0.040	23	739	0.06	0.044
				29	686	0.05	0.034
March				Septembe			
1	1359	0.03	0.041	7		0.05	0.037
8	1890	0.03	0.057	12	725	0.03	0.022
14	1779	0.03	0.053	19	716	0.05	0.036
22	1241	0.09	0.112	26	579.1	0.03	0.017
29	3363	0.06	0.202				
April				October			
5	1297	0.03	0.039	4	784.1	0.03	0.024
11	1476	0.04	0.059	12	814.5	0.04	0.033
19	1047	0.03	0.031	18	676.6	0.03	0.020
26	1659	0.03	0.050	24	843.1	0.03	0.025
May				November			
1 VIA 3	736	0.04	0.029	November 1	720.2	0.04	0.029
9	811	0.04	0.029	8	364.2	0.04	0.029
17	887	0.03	0.024	14	741.8	0.03	0.011
25	826	0.04	0.033	21	511.4	0.05	0.007
31	689	0.04	0.033	29	880.5	0.04	0.025
31	003	0.04	0.020	23	000.5	0.04	0.000
June				December			
7	835	0.03	0.025	5	935	0.1	0.094
14	594	0.03	0.018	13	642	0.07	0.045
21	955	0.03	0.029	20	520.9	0.1	0.052
29	652	0.03	0.020	28	1311	0.19	0.249

APPENDIX B

CALIBRATION REPORTS



Western Office London, Ontario N5V 3P6

Eastern Office 2088 Jetstream Road 1602 Old Wooler Road Wooler, Ontario

AS FOUND CERTIFICATION

PASS

CLIENT DETAIL EQUIPMENT DETAIL [MUT] MANUFACTURER CUSTOMER OCWA - Georgian Bay Hub Milltronics CONTACT MODEL MultiRanger PLUS Richard Eagle Operations Manager **CONVERTER SERIAL NUMBER** C/28694/2/1

> PLANT ID Elmvale WWTP METER ID Influent Flow Parshall Flume FIT ID OCWA # 81217 **CLIENT TAG** OTHER ORG# 5634 **GPS COORDINATES** N/A 1128 Flos 10 Rd. E. **ADDRESS**

Quality Management Standards Information -Reference equipment and instrumentation used to conduct this verification test is found in our AC-QMS document at the time this test was

VER. BY - FM Paris Machuk

AS FOUND TEST RESULTS

VERIFICATION DATE October 25, 2016 CAL. FREQUENCY Annual CAL. DUE DATE October, 2017

PROGRAMMING PARAMETERS				TOTA	LIZER
THROAT DIMENSION (DN)	inches	6	AS FOUND	837708.23	МЗ
EMPTY DISTANCE	m	0.9719	AS LEFT	837767.34	МЗ
MAX. HEAD	m	0.4289	DIFFERENCE	59.11	МЗ
DEAD ZONE	m	0.543		TEST CRIT	TERIA
BLANKING DISTANCE	m	0.300	AS FOUND CERTIFICATION TEST		Yes
MAX. FLOW	LPS	100.1	ALLOWABLE [%] ERROR		5
F.S. RANGE - O/P	LPS	100.0			

COMPONENTS TESTED CONVERTER DISPLAY mA OUTPUT yes TOTALIZER yes ACCURACY BASED ON [% o.r.] no ERROR DOCUMENTED IN THIS REPORT; BASED ON % F.S.

13 268

-3.42

Ultrasonic sensor installed to ensure full scale flow condition

				3.4	10.0	30.0	56.8	89.6	% F.S. Range
				0.050	0.100	0.200	0.300	0.400	m
REF. FLOW RATE				3.35	10.03	29.98	56.89	89.62	LPS
MUT [Reading]				2.41	8.93	28.06	54.63	86.49	LPS
MUT [Difference]				-0.94	-1.10	-1.92	-2.26	-3.13	LPS
MUT [% Error]				-0.94	-1.10	-1.92	-2.25	-3.13	%
mA OUTPUT				4.536	5.603	8.793	13.096	18.330	mA
MUT [Reading]	min.	4.000	mA	4.392	5.441	8.489	12.726	17.813	mA
MUT [Difference]	max.	20.000	mA	-0.144	-0.162	-0.304	-0.370	-0.517	mA
MUT [% Error]				-0.72	-0.81	-1.52	-1.85	-2.59	%
TOTALIZER - REF. FL	OW RAT	ΓE						89.621	LPS
TOTALIZER [MUT]								12.83	M3
TEST TIME								148.05	SECONDS

COMMENTS QUALITY MANAGE	MENT STANDARD	S INFO.	RES	RESULTS		
[QMS] INFORMATIO	N IDENT.	ID#	TEST	AVG	PASS	
[REFERENCE] LEVI	L Sim. BOARD	n/a	1531	%FS	FAIL	
PROCESS METER	DMM	3	DISPLAY	-2.10	PASS	
STOP WATCH	SW	Yes	mA OUTPUT	-1.50	PASS	
			TOTALIZER	-3.42	PASS	

This report reflects the test results of the overall accuracy for the above flow converter using the specified manufacturers flow tube simulator to within the specified tolerance as identified within this report.

CALC. TOTALIZER

ERROR

МЗ



Western Office Eastern Office
2088 Jetstream Road London, Ontario Wooler, Ontario
N5V 3P6 KOK 3M0

AS FOUND CERTIFICATION

PASS

CLIENT DETAIL	_				EQUIPMENT D	ETAIL
CUSTOMER	OCWA - Georgian B	ay Hub		[MUT] MANUFACTURER	Mills	tronics
CONTACT	Richard Eagle			MODEL	MultiRanger	PLUS
	Operations Manager			CONVERTER SERIAL NUMBER	C/286	94/2/1
				PLANT ID	Elmvale V	VWTP
				METER ID F	inal Effluent Flow	Meter
				FIT ID		N/A
				CLIENT TAG	OCWA#	,
				OTHER		# 5634
VER. BY - FM	Paris Machuk			GPS COORDINATES		N/A
Quality Manag	gement Standards I	nformation			1128 Flos 10	Rd. E.
Reference equ	Jement Standards I	nentation used t	to	VERIFICATION DATE	October 25	. 2016
	uipment and instrun		.•	CAL. FREQUENCY	A	Annual
QMS documer	nt at the time this te	est was		CAL. DUE DATE	October	, 2017
PROGRAMMIN	G PARAMETERS				TOTA	LIZER
NOTCH ANGLE	Ξ (φ)	inches	90	AS FOUND	246634.77	МЗ
EMPTY DISTAN	ICE, TX to notch	m	0.965	AS LEFT	246659.08	МЗ
TRANSDUCER	(TX), to sump flc	m	n/a	DIFFERENCE	24.31	МЗ
SUMP LEVEL, z	zero flow	m	n/a		TEST CRI	TERIA
				AS FOUND CERTIFICATION TE	ST	Yes
MAX. HEAD		m	0.350	ALLOWABLE [%] ERROR		15
BLANKING DIST	TANCE	m	0.305			
DEAD ZONE		m	0.310	С	OMPONENTS TE	STED
MAX. FLOW		LPS	100.0	CONVERTER DISPLAY		Yes
F.S. RANGE - O)/P	LPS	100.0	mA OUTPUT		Yes
				TOTALIZER		Yes
				ACCURACY BASED ON [% o.r.]		No
Ultrasonic Senso	or is not installed high	enough, to ensu	re full scale flow conditions	ERROR DOCUMENTED IN THIS	REPORT; BASED ON	√ F.S.
	_	-				
AS FOUND TES	ST RESULTS					

			0.0	4.4	24.7	68.0	93.0	% F.S. Range
			0.000	0.100	0.200	0.300	0.340	m
REF. FLOW RATE			0.00	4.36	24.69	68.03	93.02	LPS
MUT [Reading]			0.00	4.43	24.59	66.64	92.04	LPS
MUT [Difference]			0.00	0.07	-0.10	-1.39	-0.98	LPS
MUT [% Error]			0.0	0.1	-0.1	-1.4	-1.0	%
mA OUTPUT			4.000	4.698	7.949	14.883	18.882	mA
MUT [Reading]	min. 4.000	mA	4.003	4.708	7.940	14.658	18.716	mA
MUT [Difference]	max. 20.000	mΑ	0.003	0.010	-0.009	-0.225	-0.166	mA
MUT [% Error]			0.02	0.05	-0.05	-1.13	-0.83	%
TOTALIZER - REF. FLC	W RATE						93.020	LPS
TOTALIZER [MUT]							10.28	M3
TEST TIME							111.44	SECONDS
CALC. TOTALIZER							10.366	M3
ERROR							-0.84	%

COMMENTS	QUALITY MANAGEME	NT STANDARD	S INFO.	RES	ULTS	
	[QMS] INFORMATION	[QMS] INFORMATION IDENT. ID#			AVG	PASS
	[REFERENCE] LEVEL	Sim. BOARD	n/a	TEST	%FS	FAIL
	PROCESS METER	PM	2	DISPLAY	-0.60	PASS
	STOP WATCH	SW	n/a	mA OUTPUT	-0.39	PASS
				TOTALIZER	-0.84	PASS

This report reflects the test results of the overall accuracy for the above flow converter using the specified manufacturers flow tube simulator to within the specified tolerance as identified within this report.

APPENDIX C

SLUDGE QUALITY ANALYSIS

ELMVALE WASTEWATER TREATMENT PLANT SLUDGE QUALITY DATA

2016		13-Jan	9-Feb	22-Mar	5-Apr	3-May	7-Jun	20-Jul	3-Aug	1-Sep	4-Oct	1-Nov	N/A	
		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	ОСТ	NOV	DEC	AVERAGE
<u>Nutrients</u>														
TS	(mg/L)	12500	24400	23100	21700	26100	26300	17800	25400	25400	15500	14900		21191
VS	(mg/L)	7710	15200	14000	13200	16100	15600	10000	14700	14000	8900	8500		12537
Ammonia	(mg/L)	1.0	12.0	2.1	6.4	5.1	9	26.4	6.1	8.3	1.3	2.6		7.3
Nitrate	(mg/L)	0.30	0.60	0.90	0.90	0.30	1.4	0.30	2.4	2.10	36.00	67.00		10.20
Ammonia + Nitrate	(mg/L)	1.3	12.6	3.0	7.3	5.4	10.4	26.7	8.5	10.4	37.3	69.6		17.5
TKN	(mg/L)	454	1060	1430	993	1170	1170	792	854	388	482	488		844
Phosphorus	(mg/L)	410	530	740	760	780	810	590	860	900	570	480		675
Metal Concentrations														
Arsenic	(mg/L)	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10		0.10
Cadmium	(mg/L)	0.01	0.01	0.010	0.005	0.015	0.009	0.01	0.02	0.01	0.01	0.01		0.01
Cobalt	(mg/L)	0.01	0.02	0.03	0.05	0.040	0.04	0.02	0.04	0.04	0.02	0.02		0.03
Chromium	(mg/L)	0.42	0.47	0.66	0.62	0.68	0.71	0.64	0.79	0.82	0.47	0.41		0.61
Copper	(mg/L)	3.20	4.40	6.20	6.20	6.60	7.30	5.00	7.60	7.70	4.80	3.80		5.71
Mercury	(mg/L)	0.370	0.160	0.220	0.013	0.0250	0.0200	0.019	0.019	0.1500	0.021	0.024		0.09
Potassium	(mg/L)	64	67.0	89.0	120.0	100.0	110.0	89.0	110.0	100.0	68.0	63.0		89.09
Molybdenum	(mg/L)	0.07	0.05	0.09	0.15	0.12	0.10	0.06	0.14	0.13	0.07	0.09		0.10
Nickel	(mg/L)	0.19	0.22	0.31	0.25	0.32	0.43	0.30	0.36	0.37	0.25	0.21		0.29
Lead	(mg/L)	0.10	0.10	0.20	0.20	0.20	0.20	0	0.20	0.20	0.10	0.10		0.16
Selenium	(mg/L)	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10		0.10
Zinc	(mg/L)	5.50	6.50	8.90	8.70	9.00	9.80	7.20	10.00	11.00	7.10	5.80		8.14
<u>Bacti</u>														
E. coli (cfu/1g dried wg	t)	25600	102459	42857	35443	37165	7605	6180	7874	6299	11613	19463		27505
E. coli (cfu/100mL)		32000	250000	99000	56000	97000	20000	11000	20000	16000	18000	29000		58909
Metal/Solids Concentr Arsenic [170]	<u>ation</u> (mg/kg)	8	4	4	5	4	4	6	4	4	6	7		5
Cadmium [34]	(mg/kg)	0	0	0	0	1	0	0	1	0	0	0		0
Cobalt [340]	(mg/kg)	1	1	1	2	2	2	1	2	2	1	1		1
Chromium [2800]	(mg/kg)	34	19	29	29	26	27	36	31	32	30	28		29
Copper [1700]	(mg/kg)	256	180	268	286	253	278	281	299	303	310	255		270
Mercury [11]	(mg/kg)	30	7	10	1	1	1	1	1	6	1	2		5
Molybdenum [94]	(mg/kg)	6	2	4	7	5	4	3	6	5	5	6		5
Nickel [420]	(mg/kg)	15	9	13	12	12	16	17	14	15	16	14		14
Lead [1100]	(mg/kg)	8	4	9	9	8	8	11	8	8	6	7		8
Selenium [34]	(mg/kg)	8	4	4	5	4	4	6	4	4	6	7		5
Zinc [4200]	(mg/kg)	440	266	385	401	345	373	404	394	433	458	389		390
• •	0,		_	- 1						_				

APPENDIX'

BYPASS & SPILL REPORTS

Ontario Clean Water Agency Environmental Incident Report

Facility ID:	5634	ert entRep
Facility Name:	Elmvale Wastewater Treatment Plant	
Address:	30 Woodland Dr.	_
City:	Wasaga Beach	_
Province:	Ontario	
Postal Code:	L9Z2V4	
Date of Occurrence:	03/28/2016	
Time of Occurrence:	06:50:06 AM	
Nature of the Incident		
• Level 1 Contingence	y O Level 2 Contingency O Level 3 Contingency Click here To Show	v the Definitions
Incident affected: A	ir Water Land Nothing	
☐ Chlorine ☐ Sodium Hypochlori ☐ Calcium Chloride ☐ Aluminum Compou ☐ Arsenic ☐ Fluoride	☐ Oil/Diesel/Gas Ite ☐ Untreated or partly treated sewage ☐ Odours Inds (Specify in Other) ☐ Water ☐ Iron Coagulants	
	Other:	
If this was a discharge, sp	ill or emission	
If a liquid, approximate	ely what quantity was released?: 392700 Litres	
If a gas, approximately	what quantity was released?:	
If a solid, approximate	ly what quantity was released?: Kg	
What was the source of	f release'?:	
Bishop Park Pum	np Station bypass due to extreme rain conditions	
Where did the release g	go?:	
Wye River		
If it entered a watercou	urse: • Yes O No	

If it went off site: ● Yes ○ No
Duration of the release?:3.1 hrs
Is the release now stopped?: ● Yes ○ No
Was there any damage? (i.e. property and/or environmental): ○ Yes ● No ○ N/A
If "Yes", describe below and fill out "Insurance Claim" report
Action(s) Taken
What actions were taken to control the incident?
Pump station bypass due to high flows caused by an extreme rain event (392.7m3). On arrival, the operator found the wet well level at approximately 2.90m; pumps #2 and #2 running. Operator immediately set up bypass hose and set valving for bypass as per SOP. Began bypassing with pump #2 at 650am to the Wye River. Wet well level at approximately 3.05m
What actions have been taken to remediate the incident?
Operator notified Hub Contact, Richard Eagle, of the by pass at 8:00am. Richard notified the Director of Public Works, Township of Springwater, at 822am. Operator notified SAC at 807 am; notified Public Health Inspector at 912 am; notified Regional Hub Manager, Karen Lorente, at 1030am. A chlorine drip was set up to provide some disinfection. The operator collected a set of upstream, downstream, and effluent point samples. Eisses Disposal was called in to trasnfer 2 loads from the Queen Street lift station to the Elmvale WWTP digester. Bypasses were intermittent throught the day and evening. Bypass ended at 1131pm. A total of 187 minutes of bypass time. Operator called SAC on Tuesday, March 29 to close the incident.
Was this a reportable spill or discharge?: ● Yes ○ No
If "Yes", at what time was it first reported to the MOE?
8:07am
Was it reported to the MOE district office?: ● Yes ○ No
If "Yes", which office/location and who was the contact?: Barrie District Office, Mark Bailey
Was it reported to MOE SAC?: ● Yes ○ No
If "Yes", at what time was it reported to MOE SAC?:
8:07am
Was it reported to Municipality?: ● Yes ○ No

If "Yes", at what time was it reported to Municipality?:

8:22am by Richard Eagle				
-------------------------	--	--	--	--

External Assistance/Involvement

Was corporate or area office assistance requested?: ○ Yes ● No					
If "Yes", was it received?: ○ Yes ○ No					
Was external emergency assistance requested?: ○ Yes ● No					
If "Yes", from who?: Fire Department Ambulance or Hospital MOE Coast Guard Police Municipality					
Other:					
Was there any media involvment?: ○ Yes ● No					
If "Yes", who?:					
Was the public affected?: ○ Yes ● No					
If "Yes", how?:					
Updated By: Mary-Jo Santi 04/01/2016 03:22:26 PM					

Comments:

***************** MULTI TX/RX REPORT **********************

TX/RX NO

4747

PGS.

TX/RX INCOMPLETE

TRANSACTION OK

[*013]7057396440 [*014]18002686061 [*015]7057211495 [*018]7057286957 [*066]14163148300

ERROR INFORMATION

MOE - Sewage

SAC - MOE MOH - Barrie Springwater Twp

Corporate



30 Woodland Drive Wasaga Beach, Ontario

L9Z 2V4

TEL: 705 429-2525

FAX: 705 429~7967

www.ocwa.com

Fax

To:

Mark Bailey - MOECC Barrie District Office Mark Archer - Township of Springwater Bev Mollard - OCWA VP Southern Ontario Liz Chopp - OCWA Operations Analyst Simcoe Muskoka District Health Unit Spills Action Centre - SAC

From:

Date:

Number of Pages (including this one):

Subject:

Mary-Jo Santi

Friday, April 01, 2016

Bishop Park Pump Station, Elmvale -

Notification of Bypass - Incident #128798

Please find the attached Environmental Incident Report for the Bishop Park Pump Station, Elmvale, Ontario submitted in accordance with terms and conditions of C of A 4989-66ZRKT and provisions of the Ontario Water Resources Act and Environmental Protection Act.

By-pass of the Bishop Park Pump Station, March 28, 2016 SAC Reference Number: 128798



SGS Canada Inc.

P.O. Box 4300 - 185 Concession St. Lakefield - Ontario - KOL 2HO

Phone: 705-652-2000 FAX: 705-652-6365

Works #: 110000169-NR **Project :** PO#017470

04-April-2016

Date Rec.: 29 March 2016 LR Report: CA12865-MAR16

Copy: #1

OCWA-Wasaga Beach (Elmvale WWTP)

Attn: Richard Eagle

30 Woodland Drive Wasaga Beach, ON L9Z 2V4,

Phone: 705 429-2525 Fax:pdf, ID Plant

CERTIFICATE OF ANALYSIS Final Report

Sample ID	Sample Date & Time	Temperature Upon Receipt °C	Carbonaceous Biochemical Oxygen Demand (CBOD5) mg/L	Total Suspended Solids mg/L	Phosphorus (total) mg/L	E. Coli cfu/100mL
1: Analysis Start Date			29-Mar-16	29-Mar-16	29-Mar-16	29-Mar-16
2: Analysis Start Time			16:20	14:24	21:57	16:40
3: Analysis Approval Date			04-Apr-16	31-Mar-16	30-Mar-16	31-Mar-16
4: Analysis Approval Time			14:07	15:16	12:20	10:29
6: PSBy PSBy-Bypass Effluent	28-Mar-16 07:40	9.0	32	71	0.96	440000
7: UP UP-Bishop Park (Upstream)	28-Mar-16 07:55	9.0	< 4	265	0.32	700
8: Down Down-Bishop Park (Downstream)	28-Mar-16 07:50	9.0	16	471	0.44	1260

Carrie Greenlaw
Project Specialist

Environmental Services, Analytical

Ontario Clean Water Agency Environmental Incident Report

Facility ID:	5634	EIncidentRep ort
Facility Name:	Elmvale Wastewater Treatment Plant	ort
Address:	1128 Flos Rd 10	_
City:	Elmvale	_
Province:	Ontario	
Postal Code:	L0L1P0	
Date of Occurrence:	05/26/2016	
Time of Occurrence:	11:34:00 AM	
Nature of the Incident		
• Level 1 Contingence	ey O Level 2 Contingency O Level 3 Contingency Click here To Show	the Definitions
Incident affected: A	ir 🗌 Water 🖾 Land 🔲 Nothing	
What was discharged of Chlorine Sodium Hypochlorical Calcium Chloride Aluminum Compouration Arsenic Fluoride	Oil/Diesel/Gas	
	Other:	
If this was a discharge, sp	ill or emission	
If a liquid, approximate	ely what quantity was released?:5000 Litres	
If a gas, approximately	what quantity was released?:	
	ly what quantity was released?: Kg	
, -FF	., 1	
What was the source o	f release?:	
6" sewage forcer	nain - not in service - was damaged by Hydro One excavator	
Where did the release	go?:	
Ground		
If it entered a watercou	ırse: ○ Yes ● No	

If it	went off site: ○ Yes ● No
Dur	ration of the release?:30mins
Is th	ne release now stopped?: Yes No
Was	s there any damage? (i.e. property and/or environmental): Yes No N/A
If "`	Yes", describe below and fill out "Insurance Claim" report
Action(s	s) Taken
Wh	at actions were taken to control the incident?
	Hydro One was working on Amelia Street this morning when they struck and damaged a main. A locate of our utilities was previously provided. A call came in to the Wasaga Beach Hub office at 11:34 am, indicating they had struck a watermain – it was in fact an out-of-service 6" forcemain (this line has been out of service since the mid 1990's - only used as back up if necessary). Samples were taken and sent for analysis to SGS Labs as per the C of A 4989-66ZRKT.
Wh	at actions have been taken to remediate the incident?
	Hapamp was called in to remediate and dispose of the material – which consisted of approximately 5m3 of stagnant water and old diluted sewage. This has been disposed of in the sanitary sewer via manhole on Hapamp property
Was	s this a reportable spill or discharge?: ● Yes ○ No
If "	Yes", at what time was it first reported to the MOE?
	SAC was called at 1:50pm
Was	s it reported to the MOE district office?: ● Yes ○ No
If "	Yes", which office/location and who was the contact?:
Was	s it reported to MOE SAC?: ● Yes ○ No
If "	Yes", at what time was it reported to MOE SAC?:
	Barrie District office MOECC - Mark Bailey. SAC - Blake Turner 1:50pm
Was	s it reported to Municipality?: Yes No
If "	Yes", at what time was it reported to Municipality?:

Township of Springwater - Director of Public Works, Mark Archer and Operations Coordinator,

External Assistance/Involvement

Was corporate or area office assistance requested?: ○ Yes ● No	
If "Yes", was it received?: \bigcirc Yes \bigcirc No	
Was external emergency assistance requested?: ● Yes ○ No	
If "Yes", from who?: Fire Department Ambulance or Hospital Police Municipality	☐ Canutec ☐ Coast Guard
Other: HAPAMP Vac Truck	
Was there any media involvment?: ○ Yes ● No	
If "Yes", who?:	
Was the public affected?: \bigcirc Yes $lacktriangle$ No	
If "Yes", how?:	
Updated By: Mary-Jo Santi 05/26/2016 05:06:23 PM	

Comments:



30 Woodland Drive Wasaga Beach, Ontario L9Z 2V4

FAX: 705 429-7967 www.ocwa.com

TEL: 705 429-2525

Fax

To:

Mark Bailey – MOECC Barrie District Office Mark Archer – Township of Springwater Liz Chopp – OCWA Operations Analyst Simcoe Muskoka District Health Unit Spills Action Centre – SAC

From:

Date:

Number of Pages (including this one):

Subject:

Mary-Jo Santi

Thursday, May 26, 2016

5

Forcemain Break, Amelia Street, Elmvale - -

Incident #3744-AABPCQ

Please find the attached **Environmental Incident Report** for a forcemain break/spill, **Amelia Street**, **Elmvale**, **Ontario** submitted in accordance with terms and conditions of C of A 4989-66ZRKT and provisions of the *Ontario Water Resources Act* and *Environmental Protection Act*.

Forcemain break due to Hydro One excavation – Amelia Street, Elmvale. SAC Reference Number: 3744-AABPCQ

I will follow up with Certificate of Analysis from sampling completed on May 26, 2016.

Please feel free to contact me should you require further information.

Thank you, Mary-Jo

Mary-Jo Santi, B.ES

Process Compliance Technician (A) | Ontario Clean Water Agency | Georgian Bay Hub | PH 705.429.2525 | Fax 705.429.7967 | msanti@ocwa.com



SGS Canada Inc.

P.O. Box 4300 - 185 Concession St. Lakefield - Ontario - KOL 2HO

Phone: 705-652-2000 FAX: 705-652-6365

Works #: 110000169
Project: PO#017470

07-June-2016

Date Rec.: 27 May 2016 **LR Report: CA12830-MAY16**

Copy: #2

OCWA-Wasaga Beach (Elmvale WWTP)

Attn: Richard Eagle

30 Woodland Drive Wasaga Beach, ON L9Z 2V4,

Phone: 705 429-2525 Fax:pdf, ID Plant

CERTIFICATE OF ANALYSIS Final Report

Analysis	1: Analysis Start Date	2: Analysis Start Time	3: Analysis Approval Date	4: Analysis Approval Time	6: Raw Raw-Amelia Street Spill
Sample Date & Time					26-May-16 13:55
Temperature Upon Receipt [°C]					20.0
Carbonaceous Biochemical Oxygen Demand [(CBOD5) mg/L]	27-May-16	16:24	02-Jun-16	09:29	< 326
Carbonaceous Biochemical Oxygen Demand [(CBOD5) mg/L]	01-Jun-16	18:32	07-Jun-16	15:17	44
Total Suspended Solids [mg/L]	31-May-16	09:34	03-Jun-16	15:45	597
Phosphorus (total) [mg/L]	27-May-16	22:25	01-Jun-16	13:16	0.52
E. Coli [cfu/100mL]	27-May-16	15:25	30-May-16	10:32	< 1000

Carrie Greenlaw Project Specialist

Environmental Services, Analytical