

# Lecture 1. FP? Haskell?

Functional Programming 2017/18

Alejandro Serrano



Universiteit Utrecht

[Faculty of **Science**  
Information and Computing **Sciences**]

# Goals

- ▶ What is Functional Programming?
- ▶ Why Haskell?
- ▶ How do I “run” Haskell?

Chapters 1 and 2 from Hutton’s book



# What is Functional Programming?

More a *style* than a *paradigm*

- ▶ You can write “functional code” in almost any language



# What is Functional Programming?

More a *style* than a *paradigm*

- ▶ You can write “functional code” in almost any language

Some distinguishing **features**:

1. Expressions instead of statements (more declarative)
2. Recursion instead of iteration
3. Functions as first-class citizens



# Expressions instead of statements

What code **does** versus what code **is**

- ▶ Statements manipulate the **state** of the program
- ▶ Statements have an inherent **order**
- ▶ *Variables* name and store pieces of state

```
int total = 0;  
for (int i = 1; i <= n; i++)  
    total += i;
```

- ▶ Value of a *whole expr.* depends only on its *subexpr.*
- ▶ Easier to compose and **reason** about

```
sum [1 .. n]    --> sum [1, 2, 3, .., n]  
                --> 1 + sum [2, 3, ..., n]
```



# Recursion instead of iteration

**Iteration** = repeating a process a number of times

```
int sum(int n) {  
    int total = 0;  
    for (int i = n; n > 0; i--)  
        total += i;  
    return total;  
}
```

**Recursion** = defining something in terms of itself

```
sum 0 = 0  
sum n = n + sum (n-1)
```



# Functions as first-class citizens

**Function** = mapping of arguments to a result

```
greet name = "Hello, " ++ name ++ "!"
```

- ▶ Functions can be parameters of another function
- ▶ Functions can be returned from functions

```
map greet ["Mary", "Joe"]  
--> ["Hello, Mary!", "Hello, Joe!"]
```

map applies the function `greet` to each element of the list



# Why Haskell?

Haskell can be defined with four adjectives

- ▶ Functional
- ▶ Statically typed
- ▶ Pure
- ▶ Lazy





# Haskell is statically typed

- ▶ Every expression and function has a *type*
- ▶ The compiler *prevents* wrong combinations

```
> :t (+)  -- Give me the type of +  
Int -> Int -> Int  
> 1 + 2  
3  
> 1 + True  
Couldn't match expected type 'Int'  
      with actual type 'Bool'
```

**Inference** = if no type is given for an expression, the compiler *guesses* one



# Haskell is pure

- ▶ You **cannot** use statement-based programming
  - ▶ Variables do not change, only give names
  - ▶ Program is easy to compose, understand and parallelize
- ▶ Functions which interact with the “outer world” are marked in their type with `IO`
  - ▶ This prevents unintended side-effects

```
readFile :: FilePath -> IO ()
```



# Haskell is lazy

We shall get to this one...



# Why Haskell?

- ▶ Haskell *forces* a functional style
  - ▶ In contrast with imperative and OO languages
  - ▶ We can do *equational reasoning*
- ▶ Haskell teaches the value of static types
  - ▶ Types are *always updated* documentation
  - ▶ Compiler finds bugs long before run time
- ▶ There are transferrable abilities
  - ▶ F# for .NET, Scala for JVM, Swift for iOS
  - ▶ Haskell has a growing user base and nice ecosystem
    - ▶ You can do webdev in Haskell!



# How do I “run” Haskell?



- ▶ We are going to use GHC in this course
  - ▶ The (Glorious) **G**lasgow **H**askell **C**ompiler
  - ▶ State-of-the-art and open source
- ▶ Windows and Mac
  - ▶ Go to <https://www.haskell.org/downloads>
  - ▶ Install *Haskell Platform Full*
- ▶ Linux
  - ▶ `sudo pkg-mgr install haskell-platform`
  - ▶ where `pkg-mgr` is your package manager: `apt-get`, `yum`, `emerge`, ...




# Compiler versus interpreter


- ▶ Compiler (`ghc`)
  - ▶ Takes one or more files as an input
  - ▶ Generates a library or complete executable
  - ▶ There is **no interaction**
  - ▶ How you do things in  
*Imperatief/Mobiel/Gameprogrammeren*
- ▶ Interpreter (`ghci`)
  - ▶ **Interactive**, expressions are evaluated on-the-go
  - ▶ Useful for **testing** and **exploration**
  - ▶ You can also *load* a file
    - ▶ Almost as if you have typed in the entire file



# GHC interpreter, ghci

1. Open a command line, terminal or console
2. Write `ghci` and press 

```
GHCi, version 8.0.1: http://www.haskell.org/ghc/  
Prelude>
```

3. Type an expression and press  to evaluate

```
Prelude> 2 + 3  
5  
Prelude>
```

4.  +  ( +  in Mac) or `:q`  to quit

```
Prelude> :q  
Leaving GHCi.
```





# First examples

```
> length [1, 2, 3]
3
> sum [1 .. 10]
55
> reverse [1 .. 10]
[10,9,8,7,6,5,4,3,2,1]
> replicate 10 3
[3,3,3,3,3,3,3,3,3,3]
> sum (replicate 10 3)
30
```

- ▶ Integer numbers appear as themselves
- ▶ `[1 .. 10]` creates a list from 1 to 10
- ▶ Functions are called (applied) **without** parentheses
  - ▶ In contrast to `replicate(10, 3)` in other languages



# More about parentheses

- ▶ Parentheses delimit subexpressions
  - ▶ `sum (replicate 10 3)`: `sum` takes 1 parameter
  - ▶ `sum replicate 10 3`: `sum` takes 3 parameters

```
> sum replicate 10 3
```

```
<interactive>: error:
```

- Couldn't match type '[t0]' with 't1 -> t'  
Expected type: `Int -> t0 -> t1 -> t`  
Actual type: `Int -> t0 -> [t0]`

```
> sum (replicate 10 3)
```

```
30
```



# First examples of types

```
> :t reverse
```

```
reverse :: [a] -> [a]
```

```
> :t replicate
```

```
replicate :: Int -> a -> [a]
```

- ▶ `->` separates each argument and the result
- ▶ `Int` is the type of (machine) integers
- ▶ `[Something]` declares a list of `Something`s
  - ▶ For example, `[Int]` is a list of integers
- ▶ `[a]` means list of *anything*
  - ▶ Note that `a` starts with a lowercase letter
  - ▶ `a` is called a *type variable*



# Operators

```
> [1, 2] ++ [3, 4]
[1, 2, 3, 4]
> (++) [1, 2] [3, 4]
> :t (++)
(++): :: [a] -> [a] -> [a]
```

- ▶ Some names are completely made out of symbols
  - ▶ Think of +, \*, &&, ||, ...
  - ▶ They are called **operators**
- ▶ Operators are used *between* the arguments
  - ▶ Anywhere else, you use parentheses



# Question

What happens if we do?

```
> [1, 2] ++ [True, False]
```



# Question

What happens if we do?

```
> [1, 2] ++ [True, False]
```

Type error!



# Define a function in the interpreter

```
> average ns = sum ns `div` length ns
> average [1,2,3]
2
> :t average
average :: Foldable t => t Int -> Int
```

- ▶ Functions are defined by one or more **equations**
- ▶ You turn a function into an operator with backticks
- ▶ Naming requirements
  - ▶ Function names must start with a lowercase
  - ▶ Arguments names too
- ▶ GHC has *inferred* a type for your function



# Define a function in a file

You can write this definition in a file

```
average :: [Int] -> Int
average ns = sum ns `div` length ns
```

and then load it in the interpreter

```
> :load average.hs
[1 of 1] Compiling Main ( average.hs, interpreted )
> average [1,2,3]
2
```

or even work on it and then reload

```
> :r
[1 of 1] Compiling Main ( average.hs, interpreted )
```





# Define a function by cases

```
fac :: Int -> Int
fac 0 = 1
fac n = n * fac (n-1)
```

- ▶ Each equation goes into its own line
- ▶ Equations are checked in order
  - ▶ If  $n$  is 0, then the function equals 1
  - ▶ If  $n$  is different from 0, then it goes to the second
- ▶ *Good style*: always write the type of your functions



# Question

What happens if we write?

```
fac :: Int -> Int
fac n = n * fac (n-1)
fac 0 = 1
```



# More basic types

- ▶ Bool: True or False (note the uppercase!)
  - ▶ Usual operations like && (and), || (or) and not
  - ▶ Result of comparisons with ==, !=, <, ...
  - ▶ **Warning!** = defines, == compares

```
> 1 == 2 || 3 == 4
```

```
False
```

```
> 1 < 2 && 3 < 4
```

```
True
```

```
> nand x y = not (x && y)
```

```
> nand True False
```

```
True
```



# More basic types

- ▶ **Char**: one single symbol
  - ▶ Written in *single* quotes: 'a', 'b', ...
- ▶ **String**: a sequence of characters
  - ▶ Written in *double* quotes: "hello"
  - ▶ They are simply [Char]
    - ▶ All list functions work for String

```
> ['a', 'b', 'c'] ++ ['d', 'e', 'f']  
"abcdef"  
> replicate 5 'a'  
"aaaaa"
```



# First example of higher-order function

```
> map fact [1 .. 5]
[1,2,6,24,120]
> map not [True, False, False]
[False,True,True]

> :t map
map :: (a -> b) -> [a] -> [b]
```

- ▶ `map` takes *two* arguments
  - ▶ The first argument is a function `a -> b`
  - ▶ The second argument is a list `[a]`
- ▶ `map` works for every pair of types `a` and `b` you choose
  - ▶ We say that `map` is *polymorphic*



# Homework

1. Install GHC in your machine
2. Try out the examples
3. Define some simple functions
  - ▶ Sum of the first  $n$  numbers
  - ▶ Build `greet` with two arguments

```
> greet "morning" "Paul"
"Good morning, Paul!"
```
  - ▶ Build `greeter` with two arguments

```
> greeter "morning" ["P", "Z"]
["Good morning, P!", "Good morning, Z!"]
```
4. Think about the types of those functions



# Two pieces of advice

## Get yourself a good editor

- ▶ At the very least, with syntax highlighting
- ▶ Visual Studio Code and Atom are quite nice
  - ▶ Available at `code.visualstudio.com` and `atom.io`
  - ▶ Install Haskell syntax highlighting afterwards
- ▶ vi or Emacs for the adventurous

## Get comfortable with the command line

- ▶ `https://tutorial.djangogirls.org/en/intro\_to\_command\_line/`



# A bit of history

Functional programming is quite **old**

- ▶ 1930s: Alonzo Church develops  $\lambda$ -calculus
  - ▶ Theoretical basis for functional languages
- ▶ 1950s: McCarthy develops Lisp, the first FP language
  - ▶ Lisp supports both statements and expressions
  - ▶ Still in use: Common Lisp, Scheme, Racket
- ▶ 1970s: ML introduces type systems with inference
- ▶ 1990s: development of the Haskell language
  - ▶ 1998: first stable version, Haskell'98
- ▶ 2010: current version of the Haskell language

