


Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



Range Searching


Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is

	1D	2D		dD	
		Today	Friday	Today	Friday
Space	$O(n)$				
Query	$O(\log n)$				




Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



	1D	2D		dD
		Today	Friday	
Space	$O(n)$	$O(n)$		$O(n)$
Query	$O(\log n)$	$O(\sqrt{n})$		$O(n^{1-\frac{1}{d}})$


Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



	1D	2D		dD
		Today	Friday	
Space	$O(n)$	$O(n)$	$O(n \log n)$	$O(n)$
Query	$O(\log n)$	$O(\sqrt{n})$	$O(\log^2 n)$	$O(n^{1-\frac{1}{d}})$


Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



	1D	2D		dD
		Today	Friday	
Space	$O(n)$	$O(n)$	$O(n \log n)$	$O(n)$
Query	$O(\log n)$	$O(\sqrt{n})$	$O(\log n)$	$O(n^{1-\frac{1}{d}})$


Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



	1D	2D		dD	
		Today	Friday	Today	Friday
Space	$O(n)$	$O(n)$	$O(n \log n)$	$O(n)$	$O(n \log^{d-1} n)$
Query	$O(\log n)$	$O(\sqrt{n})$	$O(\log n)$	$O(n^{1-\frac{1}{d}})$	$O(\log^{d-1} n)$


Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



	1D	2D		dD		
		Today	Friday	Today	Friday	
Space	$O(n)$	$O(n)$	$O(n \log n)$	$O(n)$	$O(n \log^{d-1} n)$	
Query	$O(\log n)$	$O(\sqrt{n})$	$O(\log n)$	$O(n^{1-\frac{1}{d}})$	$O(\log^{d-1} n)$	
Optimal						
Space	$\Theta(n \frac{\log n}{\log \log n})$		$O(\log n)$			


Range Searching

Problem:

Given n points in \mathbb{R}^d , store them s.t. we can report all k points in a axis parallel query box.

Results:

We report in $O(q(n) + k)$ time, where $q(n)$ is



	1D	2D		dD	
		Today	Friday	Today	Friday
Space	$O(n)$	$O(n)$	$O(n \log n)$	$O(n)$	$O(n \log^{d-1} n)$
Query	$O(\log n)$	$O(\sqrt{n})$	$O(\log n)$	$O(n^{1-\frac{1}{d}})$	$O(\log^{d-1} n)$
Optimal					
Space		$\Theta(n \frac{\log n}{\log \log n})$		$O(n(\frac{\log n}{\log \log n})^{d-1})$	$O(n \log^d n)$
Query		$O(\log n)$		$O(\log^{d-1} n)$	$O(\log^{d-2} n)$