

Coherent UI for Unity3D

1.6.0

Contents

1	Introduction	1
1.1	Brief overview of Coherent UI	1
1.2	Differences between Desktop and Mobile version	1
2	Installation	3
2.1	Prerequisites	3
2.2	Package contents and structure	3
2.3	Usage of the package	4
2.4	Switching between build targets	5
2.5	Trial version registration	6
3	Samples	7
3.1	Hello, Coherent UI	7
3.2	Facebook integration	9
3.3	Menu And HUD	10
3.4	Binding Demo	12
3.5	Archive resource	16
3.6	Mobile Demo	17
3.7	Oculus	19
4	Programmer's API	21
4.1	CoherentUISystem properties for Desktop	21
4.2	CoherentUISystem properties for Mobile	21
4.3	CoherentUIView properties for Desktop	22
4.4	CoherentUIView properties for Mobile	23
5	Important points	25
5.1	Binding	25
5.2	CoherentMethod attribute for .NET scripts	25
5.3	Namespaces	27
5.4	Subclassing CoherentUIView and UnityEventListener	27
5.5	Coherent UI system lifetime	28
5.6	Customizing initialization of the Coherent UI System	28

5.7	Update cycle	29
5.8	Input forwarding - Desktop	29
5.9	Input forwarding - Mobile	29
5.10	Custom file handler	30
5.11	UI Resources	31
5.12	Click-to-focus Views - Desktop only	31
5.13	Hit testing - Desktop only	32
5.14	Logging	32
6	Requirements	33
7	Namespace Documentation	35
7.1	Package Coherent	35
7.2	Package Coherent.UI	35
7.2.1	Enumeration Type Documentation	37
7.2.1.1	CertificateStatus	37
7.2.1.2	CursorTypes	37
7.2.1.3	Direct3DInterfaceType	37
7.2.1.4	DownloadErrorType	37
7.2.1.5	JavaScriptMessageType	37
7.2.1.6	MediaStreamType	37
7.2.1.7	RenderingDeviceType	38
7.2.1.8	ScriptCallErrorType	38
7.2.1.9	SystemErrorType	38
7.2.1.10	TextInputControlType	38
7.2.1.11	ViewErrorType	38
7.2.1.12	ViewType	38
7.3	Package Coherent.UI.Binding	39
7.3.1	Enumeration Type Documentation	39
7.3.1.1	PropertyBindingFlags	39
7.3.1.2	ValueType	39
8	Class Documentation	41
8.1	Coherent.UI.BoundEventHandle Struct Reference	41
8.1.1	Detailed Description	41
8.2	Coherent.UI.Binding.BoundObject Struct Reference	41
8.2.1	Detailed Description	41
8.2.2	Member Function Documentation	41
8.2.2.1	BindMethods	41
8.3	Coherent.UI.BrowserView Class Reference	42
8.3.1	Detailed Description	42

8.3.2	Member Function Documentation	42
8.3.2.1	GetHistory	42
8.3.2.2	GetViewType	42
8.3.2.3	GoBack	42
8.3.2.4	GoForward	42
8.4	Coherent.UI.BrowserViewListener Class Reference	43
8.4.1	Detailed Description	45
8.4.2	Member Function Documentation	45
8.4.2.1	CreateSurface	45
8.4.2.2	DestroySurface	46
8.4.2.3	OnBindingsReleased	47
8.4.2.4	OnCallback	47
8.4.2.5	OnCaretRectChanged	47
8.4.2.6	OnCertificateError	47
8.4.2.7	OnCursorChanged	48
8.4.2.8	OnDraw	48
8.4.2.9	OnError	48
8.4.2.10	OnFailLoad	48
8.4.2.11	OnFinishLoad	49
8.4.2.12	OnGetAuthCredentials	49
8.4.2.13	OnIMEShouldCancelComposition	49
8.4.2.14	OnJavaScriptMessage	49
8.4.2.15	OnNavigateTo	50
8.4.2.16	OnReadyForBindings	51
8.4.2.17	OnRequestMediaStream	51
8.4.2.18	OnScriptMessage	51
8.4.2.19	OnStartLoading	51
8.4.2.20	OnStopLoading	51
8.4.2.21	OnTextInputTypeChanged	52
8.4.2.22	OnURLRequest	53
8.4.2.23	OnViewCreated	53
8.4.2.24	Release	53
8.4.3	Event Documentation	53
8.4.3.1	BindingsReleased	53
8.4.3.2	Callback	53
8.4.3.3	CaretRectChanged	53
8.4.3.4	CertificateError	53
8.4.3.5	CursorChanged	54
8.4.3.6	Draw	54
8.4.3.7	Error	54

8.4.3.8	FailLoad	54
8.4.3.9	FinishLoad	54
8.4.3.10	GetAuthCredentials	54
8.4.3.11	IMEShouldCancelComposition	54
8.4.3.12	JavaScriptMessage	54
8.4.3.13	NavigateTo	54
8.4.3.14	ReadyForBindings	54
8.4.3.15	RequestMediaStream	54
8.4.3.16	ScriptMessage	54
8.4.3.17	StartLoading	55
8.4.3.18	StopLoading	55
8.4.3.19	TextInputTypeChanged	55
8.4.3.20	URLRequest	55
8.4.3.21	ViewCreated	55
8.5	Coherent.UI.BrowserViewListenerBase Class Reference	55
8.5.1	Detailed Description	55
8.6	Coherent.UI.Binding.CallbackArguments Class Reference	55
8.6.1	Detailed Description	56
8.6.2	Member Data Documentation	56
8.6.2.1	Arguments	56
8.7	Coherent.UI.Certificate Class Reference	56
8.7.1	Detailed Description	56
8.7.2	Property Documentation	56
8.7.2.1	Fingerprint	56
8.7.2.2	FingerprintCA	57
8.7.2.3	Issuer	57
8.7.2.4	SerialNumber	57
8.7.2.5	Subject	57
8.7.2.6	ValidEnd	57
8.7.2.7	ValidStart	57
8.8	Coherent.UI.CertificatePrincipal Class Reference	57
8.8.1	Detailed Description	58
8.8.2	Property Documentation	58
8.8.2.1	CommonName	58
8.8.2.2	CountryName	58
8.8.2.3	DomainComponents	58
8.8.2.4	LocalityName	58
8.8.2.5	OrganizationNames	58
8.8.2.6	OrganizationUnitNames	58
8.8.2.7	StateOrProvinceName	58

8.8.2.8	StreetAddresses	58
8.9	Coherent.UI.Binding.CoherentProperty Class Reference	58
8.9.1	Detailed Description	59
8.9.2	Constructor & Destructor Documentation	59
8.9.2.1	CoherentProperty	59
8.9.2.2	CoherentProperty	59
8.10	Coherent.UI.Binding.CoherentType Class Reference	59
8.10.1	Detailed Description	59
8.11	Coherent.UI.Download Class Reference	59
8.11.1	Detailed Description	60
8.11.2	Member Function Documentation	60
8.11.2.1	Cancel	60
8.11.2.2	Destroy	60
8.11.2.3	GetDownloadedBytesSoFar	60
8.11.2.4	GetFilename	60
8.11.2.5	GetId	61
8.11.2.6	GetReferrer	61
8.11.2.7	GetTotalBytes	61
8.11.2.8	GetURL	61
8.11.2.9	HasFailed	61
8.11.2.10	IsCancelled	61
8.11.2.11	IsComplete	61
8.12	Coherent.UI.EventListener Class Reference	62
8.12.1	Detailed Description	62
8.12.2	Member Function Documentation	62
8.12.2.1	OnDownloadComplete	62
8.12.2.2	OnDownloadFailed	62
8.12.2.3	OnDownloadStarted	62
8.12.2.4	OnError	62
8.12.2.5	SystemReady	62
8.13	Coherent.UI.EventModifiersState Class Reference	63
8.13.1	Detailed Description	63
8.14	Coherent.UI.EventMouseModifiersState Class Reference	63
8.14.1	Detailed Description	63
8.15	Coherent.UI.FileHandler Class Reference	63
8.15.1	Detailed Description	63
8.15.2	Member Function Documentation	63
8.15.2.1	ReadFile	63
8.15.2.2	WriteFile	64
8.16	Coherent.UI.HTTPHeader Class Reference	64

8.16.1 Detailed Description	64
8.16.2 Property Documentation	64
8.16.2.1 Content	64
8.16.2.2 Field	64
8.17 Coherent.UI.ILogHandler Class Reference	64
8.17.1 Detailed Description	65
8.17.2 Member Function Documentation	65
8.17.2.1 Assert	65
8.17.2.2 WriteLog	65
8.18 Coherent.UI.Binding.InvalidValueCastException Class Reference	65
8.18.1 Detailed Description	65
8.19 Coherent.UI.KeyEventData Class Reference	65
8.19.1 Detailed Description	66
8.19.2 Property Documentation	66
8.19.2.1 IsAutoRepeat	66
8.19.2.2 IsNumPad	66
8.19.2.3 KeyCode	66
8.19.2.4 Modifiers	66
8.19.2.5 Type	66
8.20 Coherent.UI.MediaStreamDevice Class Reference	66
8.20.1 Detailed Description	67
8.20.2 Property Documentation	67
8.20.2.1 DeviceId	67
8.20.2.2 Name	67
8.20.2.3 Type	67
8.21 Coherent.UI.MediaStreamRequest Class Reference	67
8.21.1 Detailed Description	67
8.21.2 Member Function Documentation	67
8.21.2.1 Respond	67
8.21.3 Property Documentation	68
8.21.3.1 Devices	68
8.22 Coherent.UI.MouseEventData Class Reference	68
8.22.1 Detailed Description	68
8.22.2 Property Documentation	68
8.22.2.1 Button	68
8.22.2.2 Modifiers	68
8.22.2.3 MouseModifiers	68
8.22.2.4 Type	69
8.22.2.5 WheelX	69
8.22.2.6 WheelY	69

8.22.2.7	X	69
8.22.2.8	Y	69
8.23	Coherent.UI.ResourceData Class Reference	69
8.23.1	Detailed Description	69
8.23.2	Member Function Documentation	69
8.23.2.1	GetBuffer	69
8.23.2.2	GetSize	70
8.23.2.3	SignalFailure	70
8.23.2.4	SignalSuccess	70
8.24	Coherent.UI.ResourceResponse Class Reference	70
8.24.1	Detailed Description	70
8.24.2	Member Function Documentation	70
8.24.2.1	GetBuffer	70
8.24.2.2	SignalFailure	71
8.24.2.3	SignalSuccess	71
8.25	Coherent.UI.SurfaceResponse Class Reference	71
8.25.1	Detailed Description	71
8.25.2	Member Function Documentation	71
8.25.2.1	Signal	71
8.26	Coherent.UI.SystemError Class Reference	71
8.26.1	Detailed Description	72
8.26.2	Property Documentation	72
8.26.2.1	Error	72
8.26.2.2	ErrorCode	72
8.27	Coherent.UI.SystemSettings Class Reference	72
8.27.1	Detailed Description	73
8.27.2	Property Documentation	73
8.27.2.1	CachePath	73
8.27.2.2	CookiesResource	73
8.27.2.3	D3DObject	73
8.27.2.4	FocusWindow	73
8.27.2.5	HostDirectory	73
8.27.2.6	HTML5LocalStoragePath	73
8.27.2.7	MinidumpFolder	73
8.28	Coherent.UI.SystemSettingsBase Class Reference	73
8.28.1	Detailed Description	74
8.28.2	Property Documentation	74
8.28.2.1	AllowCookies	74
8.28.2.2	D3DInterfaceType	74
8.28.2.3	DebuggerPort	74

8.28.2.4	DisableWebSecurity	74
8.28.2.5	EnableProxy	75
8.28.2.6	EnableSupportForProprietaryCodecs	75
8.28.2.7	ForceDisablePluginFullscreen	75
8.28.2.8	WriteMinidumps	75
8.29	Coherent.UI.TouchEventData Class Reference	75
8.29.1	Detailed Description	75
8.29.2	Property Documentation	75
8.29.2.1	HasRadiusInformation	75
8.29.2.2	Id	76
8.29.2.3	RadiusX	76
8.29.2.4	RadiusY	76
8.29.2.5	Type	76
8.29.2.6	X	76
8.29.2.7	Y	76
8.30	Coherent.UI.UISystem Class Reference	76
8.30.1	Detailed Description	76
8.30.2	Member Function Documentation	77
8.30.2.1	CreateView	77
8.30.2.2	CreateView	77
8.30.2.3	FetchSurfaces	77
8.30.2.4	Uninitialize	77
8.30.2.5	Update	77
8.31	Coherent.UI.Binding.UnsupportedPrimitiveTypeException Class Reference	77
8.31.1	Detailed Description	78
8.32	Coherent.UI.Binding.Value Class Reference	78
8.32.1	Detailed Description	79
8.32.2	Constructor & Destructor Documentation	79
8.32.2.1	Value	79
8.32.2.2	Value	79
8.32.2.3	Value	79
8.32.2.4	Value	79
8.32.2.5	Value	80
8.32.2.6	Value	80
8.32.2.7	Value	80
8.32.2.8	Value	80
8.32.2.9	Value	80
8.32.2.10	Value	80
8.32.2.11	Value	81
8.32.2.12	Value	82

8.32.3 Member Function Documentation	82
8.32.3.1 Equals	82
8.32.3.2 GetHashCode	82
8.32.3.3 operator bool	82
8.32.3.4 operator byte	82
8.32.3.5 operator Dictionary< string, Value >	83
8.32.3.6 operator double	83
8.32.3.7 operator float	83
8.32.3.8 operator int	83
8.32.3.9 operator sbyte	83
8.32.3.10 operator string	84
8.32.3.11 operator uint	84
8.32.3.12 operator Value[]	84
8.32.3.13 operator!=	84
8.32.3.14 operator==	85
8.32.4 Member Data Documentation	86
8.32.4.1 Type	86
8.33 Coherent.UI.Binding.ValueObject Class Reference	86
8.33.1 Detailed Description	86
8.34 Coherent.UI.View Class Reference	86
8.34.1 Detailed Description	89
8.34.2 Member Function Documentation	89
8.34.2.1 AuthCredentialsResponse	89
8.34.2.2 BindCall	89
8.34.2.3 Destroy	89
8.34.2.4 DownloadUrl	89
8.34.2.5 DrawSurface	89
8.34.2.6 ExecuteScript	89
8.34.2.7 FetchMouseOnUIQuery	90
8.34.2.8 FetchSurface	90
8.34.2.9 GetClickThroughAlphaThreshold	90
8.34.2.10 GetCurentViewPath	90
8.34.2.11 GetHeight	90
8.34.2.12 GetLastFailedPath	90
8.34.2.13 GetLastLoadedPath	90
8.34.2.14 GetLastRequestedPath	91
8.34.2.15 GetTargetFramerate	91
8.34.2.16 GetViewType	91
8.34.2.17 GetWidth	91
8.34.2.18 IMEActivate	91

8.34.2.19 IMECancelComposition	91
8.34.2.20 IMEConfirmComposition	91
8.34.2.21 IMEIsActive	92
8.34.2.22 IMESetComposition	92
8.34.2.23 InterceptURLRequests	92
8.34.2.24 IsMouseOnView	92
8.34.2.25 IsOnDemand	92
8.34.2.26 IssueMouseOnUIQuery	93
8.34.2.27 IsTransparent	93
8.34.2.28 KeyEvent	93
8.34.2.29 KillFocus	93
8.34.2.30 Load	93
8.34.2.31 MouseActivate	93
8.34.2.32 MouseEvent	93
8.34.2.33 PeekFrameReady	94
8.34.2.34 Redraw	94
8.34.2.35 RegisterForEvent	94
8.34.2.36 Reload	94
8.34.2.37 ReplyToJavaScriptMessage	94
8.34.2.38 RequestFrame	94
8.34.2.39 RequestFrame	95
8.34.2.40 Resize	95
8.34.2.41 SetClickThroughAlphaThreshold	95
8.34.2.42 SetFocus	95
8.34.2.43 SetScriptError	95
8.34.2.44 SetTargetFramerate	95
8.34.2.45 SupportsClickThrough	96
8.34.2.46 TouchEvent	96
8.34.2.47 TriggerEvent	96
8.34.2.48 UnbindCall	96
8.34.2.49 UnbindObject	96
8.34.2.50 UnregisterFromEvent	96
8.34.2.51 UsesSharedMemory	96
8.35 Coherent.UI.ViewError Class Reference	97
8.35.1 Detailed Description	97
8.35.2 Property Documentation	97
8.35.2.1 Error	97
8.35.2.2 ErrorCode	97
8.36 Coherent.UI.ViewInfo Class Reference	97
8.36.1 Detailed Description	98

8.36.2	Property Documentation	98
8.36.2.1	ClickThroughAlphaThreshold	98
8.36.2.2	ControlTimeOnDemand	98
8.36.2.3	ForceSoftwareRendering	98
8.36.2.4	Height	98
8.36.2.5	InProcessGPURendering	98
8.36.2.6	IsOnDemand	98
8.36.2.7	IsTransparent	99
8.36.2.8	SupportClickThrough	99
8.36.2.9	TargetFrameRate	99
8.36.2.10	UsesSharedMemory	99
8.36.2.11	Width	99
8.37	Coherent.UI.ViewListener Class Reference	99
8.37.1	Detailed Description	102
8.37.2	Member Function Documentation	102
8.37.2.1	CreateSurface	102
8.37.2.2	DestroySurface	102
8.37.2.3	OnBindingsReleased	102
8.37.2.4	OnCallback	103
8.37.2.5	OnCaretRectChanged	103
8.37.2.6	OnCertificateError	103
8.37.2.7	OnCursorChanged	103
8.37.2.8	OnDraw	104
8.37.2.9	OnError	105
8.37.2.10	OnFailLoad	105
8.37.2.11	OnFinishLoad	105
8.37.2.12	OnGetAuthCredentials	105
8.37.2.13	OnIMEShouldCancelComposition	106
8.37.2.14	OnJavaScriptMessage	106
8.37.2.15	OnNavigateTo	106
8.37.2.16	OnReadyForBindings	106
8.37.2.17	OnRequestMediaStream	106
8.37.2.18	OnScriptMessage	107
8.37.2.19	OnStartLoading	107
8.37.2.20	OnStopLoading	107
8.37.2.21	OnTextInputTypeChanged	107
8.37.2.22	OnURLRequest	107
8.37.2.23	OnViewCreated	108
8.37.2.24	Release	109
8.37.3	Event Documentation	109

8.37.3.1	BindingsReleased	109
8.37.3.2	Callback	109
8.37.3.3	CaretRectChanged	109
8.37.3.4	CertificateError	109
8.37.3.5	CursorChanged	109
8.37.3.6	Draw	109
8.37.3.7	Error	109
8.37.3.8	FailLoad	109
8.37.3.9	FinishLoad	109
8.37.3.10	GetAuthCredentials	110
8.37.3.11	IMEShouldCancelComposition	110
8.37.3.12	JavaScriptMessage	110
8.37.3.13	NavigateTo	110
8.37.3.14	ReadyForBindings	110
8.37.3.15	RequestMediaStream	110
8.37.3.16	ScriptMessage	110
8.37.3.17	StartLoading	110
8.37.3.18	StopLoading	110
8.37.3.19	TextInputTypeChanged	110
8.37.3.20	URLRequest	110
8.37.3.21	ViewCreated	110
8.38	Coherent.UI.ViewListenerBase Class Reference	111
8.38.1	Detailed Description	111
8.38.2	Member Enumeration Documentation	111
8.38.2.1	MessageLevel	111

Chapter 1

Introduction

This guide describes the features of the [Coherent UI](#) integration in Unity3D. A basic understanding of the Unity3D engine, as well as HTML/JavaScript is assumed. Having basic knowledge of the C++ API and design of [Coherent UI](#) may be advantageous. To familiarize yourself with [Coherent UI](#), please read the main documentation file or visit [Coherent UI](#) website.

1.1 Brief overview of Coherent UI

[Coherent UI](#) is a modern user interface middleware solution that allows you to integrate HTML pages built with CSS and JavaScript in your game. The communication between your game and the HTML engine is done through the UI System component. Each HTML page is called a *View*. The *View* component allows you to perform operations on the page, such as resizing, navigating to a different URL, sending input events, executing custom JavaScript code and so on. You can create a view through the `CreateView` method of the UI System component. It requires you to supply some initialization parameters, such as width, height, initial URL, etc. It also requires an instance of a *View Listener*. [Coherent UI](#) is highly asynchronous by design, meaning that when you change the URL of a *View*, for example, the function will return immediately and you will receive a notification when the URL has actually changed. The `ViewListener` is the class that receives such notifications for a specific view - when the URL was changed, the page you're trying to open requires authentication details, etc.

1.2 Differences between Desktop and Mobile version

[Coherent UI](#) can be divided conceptually in two libraries - [Coherent UI Desktop](#) (for Windows & MacOSX) and [Coherent UI Mobile](#) (for iOS and Android). Due to platform limitations the two have a different subset of features. Namely the Mobile version has some limitations while the Desktop version is fully featured.

Warning

The current version of [Coherent UI](#) for Android has known issues when using the software keyboard alongside with Unity's one. Keyboards other than the default may not work as expected (e.g. Swype).

Mobile limitations on [Coherent UI Mobile](#) include:

- You are only able to create 2D views on-top of your game for HUDs or in-game browsers. Views splatted on 3D surfaces in the game world are not supported due to platform limitations on iOS and Android.
- Input management must be implemented through minor changes in the HTML & JS and is not pixel perfect but HTML element-based.
- Bound objects are currently missing from the binding
- No on-demand views and frame-rate control

- When writing scripts, the IDE's autocompletion will use the API for the Desktop version. There are a few methods that are available only for Desktop and others only for Mobile, so you won't see the mobile ones in your code editor. The classes for the mobile version are named the same as the desktop version but they're in a different namespace, *Coherent.UI.Mobile*. You can inspect the objects in that namespace to check the availability of the method you're looking for. In MonoDevelop you can inspect an object by using the "Go to declaration (F12)" feature.

Other than that the API has been kept 100% compatible between the Desktop & Mobile versions. The Core binding, Resource management and View management are the same. *Coherent UI Mobile* supports both device builds and simulator ones.

Chapter 2

Installation

[Coherent UI](#) for Unity3D is distributed in a **unitypackage** file. You can import this package in your project by either double-clicking on it, or by importing it through Unity in the *Project* window.

Note

Versions 1.5.3 and prior: After importing the package, you have to **install** the assets provided. This is done by the *Assets* → [Coherent UI](#) → *Install Coherent UI* menu entry.

Versions 1.5.4 and later: The install step required for previous versions was removed in [Coherent UI](#) 1.5.4. The new structure places the UI Resources inside the `WebPlayerTemplates` folder since it's the only one that Unity ignores when compiling scripts. The files placed there are not actual web player templates but a collection of HTML/CSS/JS files that are used by the samples. These files won't interfere with actual Web Player Templates as long as there is no file named *index.html*. The default UI Resources path is no longer set (the installation step in previous versions did that) and the default file handler will try to find the assets in the `WebPlayerTemplates` folder when ran in the **Editor**. For built games you **must** set the UI Resources path using the *Edit* → *Project Settings* → [Coherent UI](#) → *Select UI Folder* entry.

2.1 Prerequisites

- Unity3D 3.5.7 or later is required
- Only Pro version of Unity is supported
- [Coherent UI Mobile](#) supports iOS 5.1 and above.
- [Coherent UI Mobile](#) supports Android 3.0 and above (API level 11).
- Mobile versions of [Coherent UI](#) SDK for Unity3D work with the free version, but the *Preview* feature will not work.

Note

[Coherent UI](#) SDK has different requirements than the [requirements for Unity3D](#). Unity supports older hardware via fallbacks, which may prevent [Coherent UI](#) SDK from running on older graphics cards. Please make sure that the requirements of [Coherent UI](#) SDK match your client requirements for the project.

2.2 Package contents and structure

The package has the following structure:

- *CoherentUI* - contains the UI debugger, samples, and documentation.

- *CoherentUI/Editor* - contains editor classes for displaying the properties of [Coherent UI](#) components plus a post-build step class. These classes provide utility functionality.
- *Plugins* - contains the [Coherent UI](#) libraries. These are automatically copied when building.
- *Standard Assets/Scripts/CoherentUI* - contains the [Coherent UI](#) integration classes. You'll find a Detail folder inside which contains classes that are internal for the implementation and are used by the "public" classes. The interface you should be using is outside the Detail folder.
- *StreamingAssets* - contains assets that need to be copied as-is in the build directory. These include the [Coherent UI](#) host process executable, the libraries it needs, locales and UI resources.

2.3 Usage of the package

After importing the *CoherentUI.unitypackage* in your project, the two main scripts you'll be using are *Standard Assets/Scripts/CoherentUI/CoherentUISystem* and *Standard Assets/Scripts/CoherentUI/CoherentUIView*. The easiest way to use [Coherent UI](#) is to drag the *CoherentUIView* component onto an object and hitting Play - that's it! Everything will be up and running. Actually, you can do the same for most of the usage scenarios - just drag the component and then configure it in the inspector. Here's a bit more detail about the two scripts.

The first script, *CoherentUISystem*, defines initialization parameters of the [Coherent UI](#) System and should be placed no more than once in your project. The UI system is meant to be initialized in the first scene and live throughout the game's lifetime. You need to add this component to your scene only if you need custom initialization of the [Coherent UI](#) System. For the most cases, using only *CoherentUIView*s is enough - they will automatically create an instance of the [Coherent UI](#) System for you with reasonable default parameters. Check [CoherentUISystem Lifetime](#) for details.




Figure 2.1: CoherentUISystem properties

The second script, *CoherentUIView*, will represent a single HTML page. This is the component that renders

your CSS and JavaScript animations and makes your game alive. This component can be placed on any object that is renderable and serves as its material. When placing it on an object all the needed components are automatically created, hidden from you, and the rendered output is bound to the mainTexture of a new material that is created at runtime. This material is set as the gameObject's renderer material so that you see the page rendered on your object.




Figure 2.2: CoherentUIView properties

You can also place views on cameras. When doing so, you get your page rendered on the whole viewport of the camera. This way you can easily add a heads-up display for your game. Don't forget to mark your HUD as transparent and make your HTML page transparent! There's even an option for drawing the HUD after the post-effects if you like (The option is available for non-HUDs, too, but it results in a no-op because it doesn't make sense).

2.4 Switching between build targets

Coherent UI Mobile has different properties and a restricted subset of features compared to the desktop versions. To switch between the desktop features and the mobile ones you must switch the current active target in Unity. This is done by clicking on File->Build Settings selecting the target platform and clicking "Switch Platform". After doing so the properties of the Views will change to reflect their capabilities specific to the selected platform. Even if the current target is iOS or Android and hence you'll build with *Coherent UI Mobile* you can still preview your game in the Editor. The preview will use the desktop version of *Coherent UI*. Keep in mind that in this case you might see some differences compared to the the mobile device after the build as the desktop version has more features. You should check often how your UI behaves and looks on the device itself (or the simulator).

2.5 Trial version registration

The trial version of [Coherent UI](#) for Unity3D requires a simple registration. The registration requires:

- the email you used for downloading [Coherent UI](#)
- internet connection
- outgoing connections to port 3000 to be allowed in your firewall

The registration is started automatically when you run the game. It shows a simple form that asks for your email.

You can register [Coherent UI](#) on multiple machines, provided that they run different operating systems.

Games exported with the trial version of [Coherent UI](#) also require registration. This means if you want to run your built game on a different computer, you'll have to register [Coherent UI](#) on that computer, too. When building a game using the trial version of [Coherent UI](#) the activator is packaged as well and ran when the game is started. For manual activation, copy the *CoherentUI/Activator* folder from your Unity3D project to the machine and run:

```
Activator.exe --unity3d --host \  
    "<FULL PATH TO GAME DATA FOLDER>/StreamingAssets/CoherentUI_Host/windows"
```

on Windows and:

```
Activator.app/Contents/MacOS/Activator --unity3d --host \  
    "<FULL PATH TO GAME APP>/Contents/Data/StreamingAssets/CoherentUI_Host/macosx"
```

on Mac OS X.

Chapter 3

Samples

Note

Some samples show Desktop-specific features while others focus on Mobile targets

The samples provide a starting point for you. They are located in `Assets/CoherentUI/Samples` and the required scripts are already configured.

The samples are based on a simple scene we've set up for you. The scene consists of a light, a floor, a cube, and a FPS controller so you can move around. There are a few key points in the base sample you should be aware of.

- The FPS controller's `MouseLook` script has been modified a bit - you can toggle if it's active using the **Alt** key. This was done for convenience so you can navigate over the page, projected on the cube easily, without looking around. The `CharacterMotor` script has also been modified for the same reason.
- The cube's faces all have `MeshCollider` components. They are needed by Unity to produce texture coordinates in the raycast hit info. The texture coordinates, in turn, are needed to calculate the position of the hit point on the [Coherent UI View](#).
- The scenes that have interactive [Coherent UI](#) surfaces placed on objects use the *Click-to-focus* feature of the [Coherent UI View](#). It allows the user to forward input to the view when she clicks on it and stop forwarding it when she clicks outside.

Note

In the case where the mesh collider does not coincide with the actual geometry of the object, the raycast and coordinate calculation must take place in the user code. In the samples we're only using simple geometry that is the same as the mesh collider so no further work is needed.

3.1 Hello, Coherent UI

Just hit play - and you'll see google. To stop looking around when you move the mouse, press the **Alt** key. You can toggle that any time. Now feel free to search for anything you like :). You can change the dimensions of the View or the Page URL while playing - try changing it to something interesting, for example <http://hexgl.bkcore.com/> (also change the resolution to 1280x720 to be more natural).

You can also add a `CoherentUIView` component to one of the other sides of the cube. To do so, locate the `CoherentUIView` script under **Standard Assets/Scripts/Coherent UI/CoherentUIView** in the *Project* window. In the Hierarchy window, expand the cube-textures object and drag the `CoherentUIView` script on the back-face sub-object in cube-textures.




Figure 3.1: CoherentUIView on a texture

You can also try pages that show dialog boxes, such as

- http://www.w3schools.com/js/tryit.asp?filename=tryjs_alert
- http://www.w3schools.com/js/tryit.asp?filename=tryjs_confirm
- http://www.w3schools.com/js/tryit.asp?filename=tryjs_prompt
- <http://www.httpwatch.com/httpgallery/authentication/> (scroll down and click Display Image)




Figure 3.2: CoherentUIView showing a prompt

3.2 Facebook integration

This sample uses a facebook application that shows some of your photos in a rotating circle. You'll see how to customize the `View` and `ViewListener` behaviour to suit your needs.

Note

If you're having trouble displaying the local resources, make sure you have selected the `UIResources` folder located in the root of the project using the `Edit` → `Project Settings` → `Coherent UI` → `Select UI folder` menu in the editor. This folder will be used for resources addressed with `coui://` links.




Figure 3.3: CoherentUIView Facebook integration sample

You will find a new script - `FacebookSampleScript`. We need to modify the default behaviour of `UnityViewListener` for this sample. The key points are:

- In its `Start` method the `FacebookSampleScript` obtains the `CoherentUIView` component in the game object.
- In the `Start` method the script also attaches to the `CoherentUIView.OnViewCreated` event to enable intercepting URL requests and to the `UnityViewListener.URLRequest` event to redirect the Facebook login URL to the local HTML page.

This is the easiest way to handle events provided by the `UnityViewListener`. Another option is to derive the `UnityViewListener` and `CoherentUIView` but that is unnecessary.

The `FacebookSampleScript.OnURLRequestHandler` checks if the requested URL is the one that was registered in the *Facebook Application settings* (this might be any made up URL). If that's the case, we redirect it to the local page that uses our Facebook application. You will find the page we're redirecting to in the sample project folder under `FacebookSample/facebook.html`.

Now that we've explained what the class does, the only thing left is to hit play. You can press **Alt** to stop moving/looking so you can browse in the Facebook application.

3.3 Menu And HUD

This sample shows a game menu and HUD built with [Coherent UI](#).

Note

If you're having trouble displaying the local resources, make sure you have selected the *UIResources* folder located in the root of the project using the *Edit → Project Settings → Coherent UI → Select UI folder* menu in the editor. This folder will be used for resources addressed with `coui : //` links.

Double-click the *Menu* scene in the Project window (located in *Scenes*) to make it active, if it isn't already. In the *Menu* scene we have a *MenuScript* component attached to the camera. *MenuScript* does three things:

- sends the mouse position to the view every `Update()`
- registers the handlers for clicking on a menu button
- loads the game when the "New Game" button is clicked

Note

You have to add the *game* scene to the build settings of your project so Unity3D can load it.

In the game, we have another component for controlling the view - HUD, this time implemented in *UnityScript*. Each frame the component updates the compass orientation, based on its transformation.

In addition to updating the compass, the HUD component takes care of disabling the *CharacterMotor* component when the focus is on a *Click-to-focus* view. The HUD script attaches to *CoherentUISystem::On-ViewFocused* event and changes the `canControl` property of the selected *CharacterMotor* whenever a *Click-to-focus* view gains or loses focus. This allows typing in the focused view without moving the character. Here is the HUD component in code:

```
#pragma strict
#if UNITY_STANDALONE || UNITY_STANDALONE_WIN || UNITY_STANDALONE_OSX || UNITY_EDITOR
import Coherent.UI.Binding; // to use View.TriggerEvent with extra arguments

private var View : Coherent.UI.View;
private var CurrentDirection : float;

// CharacterMotor component to be disabled when a Click-To-Focus view has gained focus
public var characterMotor : CharacterMotor;

function Start () {
    var viewComponent = GetComponent(typeof(CoherentUIView)) as CoherentUIView;

    viewComponent.OnViewCreated += this.ViewCreated;
    viewComponent.OnViewDestroyed += this.ViewDestroyed;

    CurrentDirection = 0;

    var uiSystem = Component.FindObjectOfType(typeof(CoherentUISystem)) as CoherentUISystem;
    // get notified when a Click-to-focus view gains or loses focus
    uiSystem.OnViewFocused += this.ViewFocused;
}

function ViewCreated(view : Coherent.UI.View) {
    View = view;
    var viewComponent = GetComponent(typeof(CoherentUIView)) as CoherentUIView;
    Debug.LogWarning(String.Format("View {0} created", viewComponent.Page));
}

function ViewDestroyed() {
    View = null;
}

function ViewFocused(focused : boolean) {
    if (characterMotor) {
        // enable or disable the character movements
        characterMotor.canControl = !focused;
    }
}

function Update () {
    if (View != null)
    {
        var direction = this.transform.rotation.eulerAngles.y;
        if (Mathf.Abs(direction - CurrentDirection) > 2)
        {

```

```

        View.TriggerEvent("SetAbsoluteCompassRotation", direction);
        CurrentDirection = direction;
    }
}
#endif

```

In the game scene we have one more component - `ObjectPicker`, that takes care of directing the input to the correct `CoherentUIView`. First it checks whether the mouse is on a HUD element and if it is not, then raycasts and checks whether the mouse is over the browser window. Make sure the "Support Click Through" checkbox is ticked on the HUD `CoherentUIView` - this allows you to detect whether the mouse is over a transparent area in the View. If the property is left unchecked the input will never reach any objects in the world, because the system will think that the mouse is always over the HUD.




Figure 3.4: CoherentUIView HUD sample in action

3.4 Binding Demo

This sample will demonstrate communication between Unity3D and JavaScript used by the HTML page loaded in a [Coherent UI View](#).

Note

If you're having trouble displaying the local resources, make sure you have selected the `UIResources` folder located in the root of the project using the `Edit → Project Settings → Coherent UI → Select UI folder` menu in the editor. This folder will be used for resources addressed with `coui://` links.

The sample shows a simple options dialog. The options are passed from JavaScript to Unity3D and back to exercise the binding. This walkthrough will give you a brief overview of the [Coherent UI Binding](#) fundamentals but be sure

to check out the [Binding](#) section in this guide, as well as the **Binding for .NET** section in the general reference document.

Note

This sample guide is written for C# Unity3D scripts

First, when passing custom object types between Unity3D and JavaScript, you must first inform [Coherent UI](#) about the data in the type. You can do that using the `CoherentType` attribute:

```
using Coherent.UI.Binding;

// all properties / fields for Options will be visible to Coherent UI
[CoherentType(PropertyBindingFlags.All)]
public struct GameOptions
{
    public string Backend;
    public uint Width;
    public uint Height;

    public string Username
    {
        get {
            return System.Security.Principal.WindowsIdentity.GetCurrent().Name.ToString();
        }
    }

    // rename the NetPort property to NetworkPort
    [CoherentProperty("NetworkPort")]
    public uint NetPort { get; set; }
}
```

Now the `GameOptions` structure will correspond to a JavaScript object having the same properties. Note that you can rename a property using the `CoherentProperty` attribute. In this case, the "NetPort" property will correspond to "NetworkPork" in JavaScript.

After exposing the properties, we need to register some event handlers. This can be done in two ways. The first way to bind event handlers is to add a handler for the `ReadyForBindings` event of the `UnityViewListener` (manual binding). The second way (.NET only) is to add a `CoherentMethod` attribute to the method you want to bind (automatic binding). See the [CoherentMethod](#) section in this guide for more details.

Note

The sample provides two scripts for binding - `ManualBinding.cs` and `AutomaticBinding.cs`. Make sure that only one of those scripts is active when exploring the sample.

We'll explore the manual binding first. Start by registering a handler for `ReadyForBindings`:

```
m_View = GetComponent<CoherentUIView>();
m_View.Listener.ReadyForBindings += HandleReadyForBindings;
```

The handler would look like this:

```
void HandleReadyForBindings (int frameId, string path, bool isMainFrame)
{
    if (isMainFrame)
    {
        // bind ApplyOptions to "ApplyOptions" in JavaScript
        m_View.View.BindCall("ApplyOptions", (Action<GameOptions>)this.ApplyOptions);
        m_View.View.BindCall("GetLatency", (Func<int>)this.GetNetworkLatency);
        m_View.View.BindCall("GetGameTime", (Func<int>)this.GetGameTime);

        m_View.View.BindCall("GetMath", (Func<BoundObject>)(() => {
            return BoundObject.BindMethods(new MyMath());
        }));

        // triggered by the view when it has loaded
        m_View.View.RegisterForEvent("ViewReady", (Action)this.ViewReady);
    }
}
```

Now, when JavaScript calls `engine.call("ApplyOptions", options)`, Unity3D will execute its handler - namely the `(Action<GameOptions>)this.ApplyOptions` method registered above.

The `options` structure passed as a parameter looks like this:

```
function onApplyButton() {
    var options = {};
    options.__Type = "GameOptions";
    options.Backend = $("#backend").text();
    options.Width = Number($("#gameWidth").val());
    options.Height = Number($("#gameHeight").val());
    options.Username = $("#user").text();
    options.NetworkPort = Number($("#netPort").val());

    // This will call the C++ engine code with the just created structure. It'll be correctly populated
    engine.call("ApplyOptions", options);
}
```

Note that there is one "internal" property - `__Type`. This property defines the mapped type and is essential for correct behavior of the binding provided by [Coherent UI](#).

The "ApplyOptions" handler just bounces the options back to JavaScript:

```
public void ApplyOptions(GameOptions options)
{
    m_View.View.TriggerEvent("gameConsole:Trace", options);
}
```

`gameConsole:Trace` will dump the `options` object in the console.




Figure 3.5: Binding sample in action

The automatic binding saves us the first two steps - instead of registering a handler in the `UnityEventListener` callback you can decorate a method with the `CoherentMethod` attribute:

```
[Coherent.UI.CoherentMethod("ApplyOptions", false)]
public void ApplyOptions(GameOptions options)
{
    m_View.View.TriggerEvent("gameConsole:Trace", options);
}
```

The first argument of the attribute is the JavaScript function that we're binding. The second defines whether the function is an *event* (opposed to a *call* - *calls* are single-cast only).

Returning a value to JavaScript

Calls can also return a value. Let's inspect the "GetLatency" binding:

```
// By default, the second argument of CoherentMethod is false
[Coherent.UI.CoherentMethod("GetLatency")]
public int GetNetworkLatency()
{
    // not actual latency :)
    return (int)UnityEngine.Random.Range(0, 1000);
}
```

Since the execution of JavaScript is **not** synchronous you will receive the result in a callback. [Coherent UI](#) provides a promise/future pattern for convenience. This is the "GetLatency" JavaScript call in all its glory:

```
function getLatency() {
    engine.call("GetLatency").then(function() {
        $("#latency").text(arguments[0]);
    });
}
```

As you can see from the script, the value returned by Unity3D will be passed to the callback as an argument.

Method Binding

This sample also shows how to use binding of .Net methods. For detailed explanation see "Exposing Methods" in the "Binding for .Net" chapter in the API documentation.

The sample exposes an instance of `MyMath` to JavaScript.

```
class MyMath
{
    public double Sum(double[] numbers)
    {
        return numbers.Sum();
    }

    public double Average(double[] numbers)
    {
        return numbers.Average();
    }
}
```

When the game is up and running, we request the `MyMath` instance, store it as a global object and register two console commands that use it.

```
engine.on('Ready', function () {
    //get the exposed MyMath object
    engine.call('GetMath').then(function (math) {

        // store reference to the object
        window.MyMath = math;

        // register commands for the console
        engine.trigger('gameConsole:AddCommand', 'sum', 'computes the sum of its arguments', function (line) {
            var numbers = line.split(/\s+/).map(Number);
            numbers.splice(0, 1);
            window.MyMath.Sum(numbers).then(function (sum) {
                engine.trigger('gameConsole:Trace', 'The sum of', numbers, 'is', sum);
            });
        });

        engine.trigger('gameConsole:AddCommand', 'avg', 'computes the average of its arguments', function (line) {
            var numbers = line.split(/\s+/).map(Number);
            numbers.splice(0, 1);
            window.MyMath.Average(numbers).then(function (avg) {
```

```

        engine.trigger('gameConsole:Trace', 'The average of', numbers, 'is', avg);
    });
    });
});
});

```

To try out the commands press `~` to open the game console and type `sum 40 2`.

Events

When you need multiple handlers for a JavaScript function you need to register an *event*. This can be done by the `Coherent.UI.View.RegisterForEvent` method for manual binding

```
m_View.View.RegisterForEvent("ViewReady", (Action)this.ViewReady);
```

and passing `true` as a second parameter of the `CoherentMethod` attribute for automatic binding.

```

[Coherent.UI.CoherentMethod("ViewReady", true)]
public void ViewReady()
{
    // show the options
    m_View.View.TriggerEvent("OpenOptions", m_GameOptions);
}

```

Bear in mind that *events* **cannot** return a value.

If you want to handle an event in JavaScript, you need to register a handler using the `engine.on` call.

```

engine.on('OpenOptions', function (options) {
    // Open an options dialog
});

```

An event can be triggered by JavaScript by using

```
engine.trigger("EventName", eventArgs);
```

or by Unity3D using

```
m_View.View.TriggerEvent("EventName", eventArgs);
```

where `m_View` is `CoherentUIView`.

This concludes the binding demo walkthrough.

3.5 Archive resource

This sample demonstrates reading resources from an archive through a custom file handler.

The scene is just a simple camera that has an attached `CoherentUIView` component and another one that forwards input to the view. The important component for this sample is *CustomFileHandlerScript*. It sets the `CoherentUISystem` factory function object in its `Awake` method so the system is initialized with the custom handler.

```

void Awake()
{
    CoherentUISystem.FileHandlerFactoryFunc = () => { return new CustomFileHandler("UIResources", "
        ArchiveResource.tar"); };
}

```

In fact, that's all the component has to do - set the `CoherentUISystem.FileHandlerFactoryFunc` prior to any `Start` method being called. The returned `CustomFileHandler` is the class that does the actual reading/writing. The methods the user needs to implement are:

```
public override void ReadFile (string url, Coherent.UI.ResourceResponse response)
{
    ...
}

public override void WriteFile (string url, Coherent.UI.ResourceData resource)
{
    ...
}
```

They will be called for all *coui://* links and for the cookies (if enabled).

Note

When reading/writing cookies, you may receive a URL that has a *file://* scheme.

The input URL can be interpreted in any way you see fit for your handler. In the example we try to open the link *coui://UIResources/mainmenu/menu.html*. The *mainmenu/menu.html* is actually compressed in an archive. First we verify that the host part of the URL (*UIResources*) is what we expect for compressed resources and then proceed to search the archive for the resource.

Since **Coherent UI** supports asynchronous reading/writing of resources, when done with the I/O operations, you must use the *ResourceResponse* or *ResourceData* object to signal the outcome. You can do that by using the *SignalSuccess* and *SignalFailure* methods.

Note

At the moment the data you read/write must be converted to a native buffer before usage. This is done with the *System.Runtime.InteropServices.Marshal* class. Here's a short snippet that reads a file and then copies the managed buffer in an unmanaged buffer provided by the *ResourceResponse* object:

```
public override void ReadFile (string url, Coherent.UI.ResourceResponse response)
{
    byte[] bytes = File.ReadAllBytes(url);

    IntPtr buffer = response.GetBuffer((uint)bytes.Length);
    if (buffer == IntPtr.Zero)
    {
        response.SignalFailure();
        return;
    }

    Marshal.Copy(bytes, 0, buffer, bytes.Length);

    response.SignalSuccess();
}
```

Make sure you check out the code in *CustomFileHandlerScript* for a complete example.

3.6 Mobile Demo

Warning

Unity3D 3.5 doesn't support native plugins for iOS simulator builds. There are a couple of articles explaining how to workaround this limitation, but the most helpful is <http://tech.enekochan.com/2012/05/28/using-the-xcode-simulator-with-a-unity-3-native-ios-plugin/>. We have added a script with a post-process step that tries to fix the project, so it can be used with the iOS simulator. The script is in *Editor/iOSSimulatorProjectFixer.cs*.

This sample demonstrates how you can control what part of the input is forwarded to Unity3D by using JavaScript. The sample starts with an overlay that has 3 buttons on the left side, area for testing input forwarding on the right, and a red box in the world. The buttons enable/disable the input forwarding for touches on the right side of the overlay and the third one bumps the box upwards. When you touch the box a little force is applied and it should move forward as if you pushed it. If you touch the box in the right area of the overlay the force is applied only if input forwarding is enabled.

There are also buttons for toggling the overlay and mouse look controller in the top left corner for convenience.

Warning

The HTML code for the sample is not designed for small displays so it may look out of proportion on a phone or a phone simulator. You can try lowering the font size in the accompanying `css` file.

Note

The [Coherent](#) UI View used has its input state set to "Transparent". If you set it to "Take all" input is consumed before reaching Unity3D and if you set it to "Take none" it is sent directly to Unity3D.

Warning

Unfortunately, at the moment you can't see the actual behavior of the sample in the Unity3D Editor. Input is handled differently for the standalone and mobile versions so it is recommended that you test your project either on a mobile device or an emulator.

Code-wise speaking, when you make a touch on a "Transparent" [Coherent](#) UI View, the `engine.checkClickThrough` function is called. You can check its code in `coherent.js`. Basically it obtains the DOM element from the touch coordinates and begins a series of checks. First, if the element is the *document body* or has the **`coui-noinput`** class, input is directly sent to the client (Unity3D). Otherwise, the element is checked for having a **`coui-inputcallback`** class. If it does, the element's `couiInputCallback` is invoked which determines whether the input is forwarded or consumed; if it doesn't have such class, input is consumed.

The sample enables/disables the input forwarding on the right area by removing/adding the **`coui-noinput`** class to the corresponding DOM element. In this sample, only the DOM element for the right area has the class **`coui-inputcallback`** and its `couiInputCallback` function is set when the engine has signaled it's ready. The function itself doesn't do anything special, it just always returns `true`, meaning that the input is consumed in JavaScript and never sent to the client (Unity3D).

You can also bump the box upwards which is a demonstration for the binding for [Coherent](#) UI Mobile. It's very much the same as binding for .NET/Unity3D standalone so we'll not go in detail here.

Summing up:

- if you want the input forwarded to the client when touching an element, simply add the **`coui-noinput`** class to the element.
- if you want an element to consume input, ensure that it does **not** have the **`coui-noinput`**.
- if you want to have custom processing over an element, ensure that it does **not** have the **`coui-noinput`**, add a **`coui-inputcallback`**, and add a function `couiInputCallback` which ultimately returns `true` if you want to consume the input or `false` if you want to forward it to the client.

Note that for obtaining the element below the touch point we're currently using `document.elementFromPoint`. In the sample, the right area is represented by a `<div>` and there's some text inside it as a child element. Only the `<div>` has the `coui-inputcallback` class. If you touch the text its element will be checked for the `coui-inputcallback` class and since it doesn't have one input will be consumed. Since we want to apply the logic for all touches inside the area this presents a problem. One solution is to add the `coui-inputcallback` class to all child elements and set their `couiInputCallback` functions to the same variable. Another solution is to use the **`pointer-events`** CSS property on the children elements, e.g.:

```
#menu-right > *
{
  pointer-events: none;
}
```

This is how the sample solves the problem. Note that this is an experimental CSS property and prevents elements from being the target of pointer events. This is fine in the sample but may have adverse effects in your code so use it with caution.

3.7 Oculus

Note

It is not possible to create a sample scene for Oculus Rift for Unity3D 3.5 using the official Oculus SDK. So our Oculus Rift sample scene is created with Unity3D 4 and can not be packaged in our asset store packages. You can download a package with the scene from: https://s3.amazonaws.com/CoherentLabs/-Public/Coherent_UI_Oculus_Sample.unitypackage

This sample demonstrates how you can create UI elements in your games for the Oculus Rift, using the CoherentUI and OculusVR integrations in Unity. The focus of the sample is on creating a HUD element that can be used with the Oculus headset.

Note

You should include the Oculus integration package for Unity in order to use Oculus in Unity3D (you need a Unity Pro 4.01 or higher version). For more information about the Oculus SDK and its integration with Unity, please visit <http://www.oculusvr.com/>.

You can get Oculus ready for use in Unity by following these steps:

- go to the official website of Oculus Rift - <http://www.oculusvr.com/> ;
- download OculusUnityIntegration.unitypackage from there;
- open an Unity3D instance and go to Assets -> Import Package -> Custom Package. When the dialog box for choosing packages opens, go to the place with the downloaded package and select it. A new dialog box with a list of the files for import will open. Choose 'Import All'. After completing this step you should be able to see a new menu - 'Oculus'.

Now we are ready to proceed with the sample. As you can see, there is an OVRPlayerController in the *Scene* menu (it can be added from Oculus -> Prefabs -> OVRPlayerController). The controller is comprised of two things: a simple character controller and another OVR prefab - OVRCameraController. The latter is used as an interface between Unity and the two cameras. Double-click it to reveal its children objects. Double-clicking the OVRCameraController will show the cameras and a plane object attached to the right camera. This plane is used as a surface for drawing the HUD. There is an CoherentUIView component attached to it, which uses `coui://UIResources/Menu-AndHUD/hud/hud.html` as a page. It is suggested that for drawing HUD elements you attach the surface to the right camera for optimal results.

Note

To render a view on top of everything, we put an check mark in 'IsIndependentOfZBuffer'.

Warning

: Whenever using a plane as a surface for views, choose a material for the plane and use a 'Transparent/-Diffuse' shader for it.

This is basically all you need to draw the HUD. Hit play to see the result

Chapter 4

Programmer's API

The Unity API is an extension of the normal .Net API, and it is contained in the main API Reference documentation.

4.1 CoherentUISystem properties for Desktop

- **Main Camera** - The main camera in the scene. This property is used only for [Click to focus Views](#).
- **Host Directory** - Path to the directory where the [Coherent](#) UI executable resides. This path can be relative to the resource path of the game (i.e. the *Assets* folder of the Unity3D project or the <YourGameName>_Data folder of the built game). By default it is *StreamingAssets/CoherentUI*.
- **Proxy** - Enables proxy support by autodetecting the system settings. This detection is usually very slow and this setting should be enabled only when the user is behind a proxy and you're accessing the Internet.
- **Cookies** - Enables support for cookies.
- **Cookies file** - A file that will be used for reading and writing cookies when they are enabled.
- **Cache path** - Path for saving cached data. Leave null for in-memory caching only.
- **Local storage path** - Path for saving HTML5 page local storage data. Leave null to forbid local storage.
- **Disable fullscreen plugins** - Disables fullscreen mode for all plugins (e.g. Flash, Silverlight, etc.)
- **Disable web security** - Disable same origin policy. Use with caution.
- **Debugger port** - The port that will be opened for the debugger to connect and debug your interface. A value of -1 means disabled.
- **Support for Alt Tab** - Enables support for Alt and Tab in fullscreen DirectX9 applications for Windows. Due to restrictions in Dx9, it is necessary to reset Unity's graphics device in windowed mode before initializing UI System and after the system has been initialized and is ready, set reset it to fullscreen mode. If you uncheck this, the resets won't happen in fullscreen mode, but Alt+Tab functionality will not be supported.

The `CoherentUISystem` component also provides a static factory function object (`FileHandlerFactory-Func`) that the user can customize in order to make use of her own `FileHandler`. See the [Custom file handler](#) section for a detailed explanation.

4.2 CoherentUISystem properties for Mobile

- **URL cache** - Decides if the device URL cache will be used.
- **Memory cache size** - The maximum size of the in-memory cache.
- **Disk cache size** - The maximum size of the disk cache.

4.3 CoherentUIView properties for Desktop

- **URL** - Indicates the URL that will be initially loaded.
- **Width** - The width of the [Coherent](#) UI View.
- **Height** - The height of the [Coherent](#) UI View.
- **Transparent** - Defines if the View supports transparency.
- **Pre-load script** - The script will be executed before any other code in the UI View
- **Smart input** - *Available for transparent Views.* Enables support for queries whether the cursor is over a transparent pixel. A transparent pixel is considered one that has an alpha value below or equal to the *click-through alpha threshold*.
- **Smart input alpha** - A value in the range [0-1] inclusive that determines whether a pixel is transparent; A pixel is transparent if its alpha value is below or equal to the threshold.
- **Lockable focus** - When enabled, the View takes the input focus when clicked and releases it when you click outside the View. See [Click to focus Views](#)
- **On Demand ([Coherent UI Pro](#) only)** - Provides perfect synchronization of the game frames and [Coherent](#) UI frames. Use this when you need to synchronize the game and the interface, e.g. when displaying name tags over the players. Using standard views may introduce a delay of a few frames.
- **Timer override** - The UI uses the in-game timer (requires On-demand)
- **Max. frame-rate ([Coherent UI Pro](#) only)** - Sets the maximum framerate for the View. The view will never exceed this framerate.
- **Draw order** - Defines whether the View is drawn before or after the post-effects. Available for Views attached to cameras.
- **Flip Y** - Flips the drawn image vertically.
- **Auto UI messages** - When enabled, any event triggered in *JavaScript* on the `engine` object is forwarded to the game object containing the View.
- **Enable [[CoherentMethodAttribute](#)]** - Enables the usage of the [Coherent Method attribute](#)
- **Compensate gamme** - The View will have gamma corrected when linear color space is used. Takes effect only if DirectX9 is used. Whether you should use this property or not depends on the scene you are making - are there any additional cameras, what kind of rendering path they use, etc. Generally, this property comes handy when you use linear color space and the view is attached to a camera with deferred lighting or if your main camera uses deferred lighting and the camera with the view does not.
- **Always on top** - Indicates whether this value is z-buffer independent. If it is set to true, the view is rendered on top of everything.
- **Show JS dialogs** - Automatically handle JavaScript messages and authentication requests. If enabled, a visual dialog will be shown; otherwise it's up to the programmer to make the appropriate response. If you do not respond to the message, the page will block until you do. Examine `ViewListener.cs` and `CoherentDialog.cs` for a sample reply logic.
- **Software only rendering** - The View will be rendered without hardware acceleration.
- **Match camera size** - The View will be automatically resized to always match the size of the camera

4.4 CoherentUIView properties for Mobile

- **URL** - Indicates the URL that will be initially loaded.
- **Width** - The width of the [Coherent](#) UI View in pixels.
- **Height** - The height of the [Coherent](#) UI View in pixels.
- **X Position** - The X of the [Coherent](#) UI View position relative to the upper-left corner of the device screen.
- **Y Position** - The Y of the [Coherent](#) UI View position relative to the upper-left corner of the device screen.
- **Retina rescale** - If set the content will be scaled to fit the View.
- **Enable WebGL Support** - If set to true, the view will be created with WebGL support.
- ****Input behavior** - Controls how the view handles user input (touches and gestures). The behavior only influences events that happen in the bounds of the View. If the user touches outside a view the event goes normally to the game.
 - **Transparent** - the user controls which input events to be taken by the UI and which to pass to the game. This is explained in the Mobile input management section ([Input forwarding - Mobile](#))
 - **Take all** - the View takes all the input - nothing is passed to the game
 - **Take none** - the View takes no input - everything goes to the game
- **Transparent** - Defines if the View supports transparency.
- **Smart input** - *Available for transparent Views.* Enables transparent input.
- **Auto UI messages** - When enabled, any event triggered in *JavaScript* on the `engine` object is forwarded to the game object containing the View.
- **Enable [CoherentMethodAttribute]** - Enables the usage of the [Coherent Method attribute](#)

Chapter 5

Important points

5.1 Binding

Binding *C#*, *UnityScript* and *Boo* handlers to JavaScript callbacks is the same as binding for the .Net platform. You have to register handlers when the `UnityViewListener`'s `ReadyForBindings` event is fired. You can do that by using either `Coherent.UI.View.BindCall` (for single-cast delegates) and `Coherent.UI.View.RegisterForEvent` (when you have multiple subscribers for the event). For more details see the general reference documentation, chapter **Binding for .Net**.

```
private void RegisterBindings(int frame, string url, bool isMain)
{
    if (isMain)
    {
        var view = ViewComponent.View;
        if (view != null)
        {
            // When engine.call('NewGame') is executed in JavaScript,
            // the this.NewGame method will be called as well
            view.BindCall("NewGame", (System.Action)this.NewGame);
        }
    }
}
```

The `Coherent.UI.View` can be obtained using the `View` property of the `CoherentUIView` component.

To take advantage of the *Unity3D* component and message system each `CoherentUIView` has the `Intercept-AllEvents` property. If intercepting of all events is enabled, any event triggered in *JavaScript* on the engine object is forwarded to the game object containing the view. This is done by using `SendMessage` with `Coherent.UI.Binding.Value[]` containing all the event arguments.

```
engine.trigger('Event', 42);
// will execute SendMessage('Event', [42])
```

Note

Using this method of handling triggered events has some additional overhead over the direct `.Net Coherent.UI.View.RegisterForEvent` method.

5.2 CoherentMethod attribute for .NET scripts

Instead of handling the `ReadyForBindings` event and doing `BindCall` or `RegisterForEvent` by yourself, you can use the `CoherentMethod` attribute to decorate methods in components.

Warning

This attribute only works if the `CoherentUIView`'s `Enable Binding Attribute` is set to `true`. By default it is **false**.

The decorated methods will be automatically bound to the `View` owned by the `CoherentUIView` component in the Game Object. If the Game Object has no `CoherentUIView` component, the attribute has no effect. The `CoherentMethod` attribute has a string property for the JavaScript event name, and an optional boolean parameter that specifies whether the method is a *call* or *event* handler (*calls* can have only a single handler, while *events* may have many). Here's an example component using the attribute:

```
public class BindingComponent : MonoBehaviour {

    [Coherent.UI.CoherentMethod("NewGame")]
    void MyCallHandler()
    {
        Debug.Log("MyCallHandler called in response to engine.call('NewGame')");
    }

    [Coherent.UI.CoherentMethod("EnemySpotted", true)]
    void MyEventHandler()
    {
        Debug.Log("MyEventHandler called in response to engine.trigger('EnemySpotted')");
    }
}
```

See the [Binding Sample](#) for a complete example.

Warning

* Binding methods using the `CoherentMethod` attribute is easier than doing it manually in `ReadyForBindings`, but presents possible performance penalties during game startup. When the `CoherentUIView` component is created, it searches all the other components in the host Game Object for methods marked with `CoherentMethod` using reflection. This can be a costly operation and to prevent undesirable slowdowns during startup the `Enable Binding Attribute` property for each `CoherentUIView` is set to **false** by default.

* The `CoherentMethod` attribute currently does **NOT** support dynamically added components. Methods decorated with the attribute are only bound when the `CoherentUIView` component is created, which is usually when the Game Object it is part of is created.

JavaScript and Unity3D

Consult the *Binding for .NET* chapter in the general reference document. Check the [Binding Sample](#) and its walk-through in this guide for an example.

Briefly, Unity3D can call JavaScript using *events*; JavaScript can call Unity3D using *events* or *calls*.

- Events

Events can be called by JavaScript

```
engine.trigger("MyEvent", args);
```

or Unity3D

```
coherentUIView.View.TriggerEvent("MyEvent", args);
```

The "MyEvent" will be handled by any registered method in JavaScript

```
engine.on("MyEvent", function() {...});
```

or Unity3D


```
coherentUIView.View.RegisterForEvent("MyEvent", handlerMethod);
```

- Calls

Calls, unlike events, can have only one handler. They can also return values. To execute a *call* from JavaScript use

```
engine.call("MyCall", args);
```

It will be handled by a method registered using

```
coherentUIView.View.BindCall("MyCall", handlerMethod);
```

5.3 Namespaces

[Coherent](#) UI classes are placed in the [Coherent.UI](#) namespace for Desktop and [Coherent.UI.Mobile](#) for the Mobile version. You can check the [Coherent](#) UI files - for instance [CoherentUIView](#) and take a look at the beginning of the file at how the namespaces are imported depending on the Unity platform targeted. Exceptions to that rule are classes that cannot be in a namespace because Unity doesn't allow it, such as components that derive from [MonoBehaviour](#).

5.4 Subclassing CoherentUIView and UnityViewListener

The default [CoherentUIView](#) component and the [UnityViewListener](#) provide the most common functionality and are usually enough for normal usage of [Coherent UI](#). If you need custom behavior, you need to subclass them.

The class you derive from [UnityViewListener](#) would usually subscribe to various events that aren't handled by default. It is recommended not to override the [OnViewCreated](#) callbacks since the [UnityViewListener](#) class contains important logic that you would have to implement yourself otherwise.

The class you derive from [CoherentUIView](#) would only need to create an instance of your custom View Listener. This can be done by copying the [Update](#) method of [CoherentUIView](#) and editing it appropriately.

Note that when subclassing [CoherentUIView](#) you will no longer be able to view or edit the properties in the Inspector. That's because we're using C# properties in our component instead of fields and they are not automatically shown. To show the properties of a given C# script we need to make a new Editor script (inside the [Editor](#) folder of your Assets) that shows the properties for a specific type. We've already done that for [CoherentUIView](#), but you'll have to do it yourself for derived classes. The script contents should be the following:

```
using UnityEngine;
using System.Collections;
using UnityEditor;

[CustomEditor(typeof(<YourType>))]
public class <YourType>ViewEditor : Editor {

    private <YourType> m_Target;
    private CoherentPropertyField[] m_Fields;

    public void OnEnable() {
        m_Target = target as <YourType>;
        m_Fields = CoherentExposeProperties.GetProperties(m_Target);
    }

    public override void OnInspectorGUI() {
        if(m_Target == null)
            return;
        this.DrawDefaultInspector();
        CoherentExposeProperties.Expose(m_Fields);
    }
}
```

Just replace [<YourType>](#) with the actual name of your class.

Note

In most cases, subclassing is unnecessary. See [Facebook Sample](#) for an example how to subscribe for `UnityViewListener` events.

5.5 Coherent UI system lifetime

Since initialization of the `CoherentUISystem` component is a costly operation, it is designed to be done once in the first scene of your game. The component itself has the same lifetime as the application. Since Unity tears down the state of the game when you load a new scene, the component is marked not be destroyed using the `DontDestroyOnLoad()` function. This makes it persist through scenes and is available using the `Object.FindObjectOfType` function. Getting the system can be done with the following line of code:

```
var uiSystem = Object.FindObjectOfType(typeof(CoherentUISystem)) as CoherentUISystem;
```

5.6 Customizing initialization of the Coherent UI System

When using only `CoherentUI` components, the [Coherent UI](#) System will be automatically initialized using the default parameters. These parameters define global system settings such as whether cookies are enabled, local storage and cache paths, debugger port and others. Check the `CoherentUISystem` component for a full list.

The [Coherent UI](#) System can be initialized with parameters other than the defaults in the following ways. Either drag the `CoherentUISystem` component to any object and edit the properties in the Inspector window, or edit the `CoherentUISystem.cs` script located in *Standard Assets/Scripts/CoherentUI* to fit your needs.




Figure 5.1: Custom CoherentUISystem component

The `CoherentUISystem` component is designed to be only one in the whole game. Adding more than one `CoherentUISystems` to your level will result in undefined behavior.

5.7 Update cycle

In a standard C++ or .NET application you need to poll [Coherent UI](#) for surfaces each frame using the `Update` and `FetchSurfaces` API calls. In our Unity integration, this is all hidden from you and you don't have to worry about it. The `CoherentUIViewRenderer` component issues rendering events which are handled by our library. All that's left for you is to drag a `CoherentUIView` component on an object!

5.8 Input forwarding - Desktop

A `CoherentUIView` requires focus to receive user input. Usually you'd want to forward input to a single view, but for flexibility [Coherent UI](#) supports multiple focused views. A `CoherentUIView`'s focus is controlled by the `ReceivesInput` property. To avoid confusion with multiple views, the property is set to **false** by default, meaning no input will be forwarded to [Coherent UI](#) unless you explicitly set it in your Game Object. It is **NOT** exposed in the Inspector, as it designed to be modified in code only.

Note

The forwarding happens in the `CoherentUISystem`'s `LateUpdate` method, allowing you to do all your logic for input focus management in the `Update` methods of your components.

5.9 Input forwarding - Mobile

Due to differences in the input management for iOS/Android, [Coherent UI](#) provides a helper class for getting the list of touches for the current frame. The [Coherent](#) touch structure is `InputManager.CoherentTouch` - very much the same as Unity3D's `Touch` structure. The equivalent methods for `Input.touchCount` and `Input.GetTouch(index)` are `InputManager.TouchesCount` and `InputManger.GetTouch(index)`, respectively.

For **iOS** there's practically no difference between the [Coherent](#) and Unity3D touches. For **Android**, however, [Coherent](#) touches contain only touches that reached the game (i.e. the touch wasn't filtered using the techniques described in the next paragraph). The Unity3D supplied touches on Android aren't filtered and you get all of them when using the `Input.touches` array, regardless of whether they are on the UI or not. When using [Coherent UI](#) for mobile, it is recommended to use [Coherent](#) touches instead of Unity3D touches to avoid platform differences between iOS and Android.

On iOS/Android all [Coherent UI](#) Views are composited in 2D on-top of your Unity3D application content. When the user start a touch event or performs a gesture there is a mechanism that decides if that event should be handled by the UI or the application. It works like this: in the properties of the View the user can select one of three input modes for a every View - "Take All", "Take None", "Transparent". Keep in mind that all those modifiers are in effect only for events that happend are in the bounds of the View. If the user touches outside a particular View the event is always handled by the game.

- "Take All" specifies that all events are handled by the View and nothing goes to the game. It is usable if you want to have for instance an in-game browser. All touches on it should be handled by itself and not influence the game.
- "Take None" specifies that the View passes all input to the game. This is usable if you need to just show some non-interactive views or disable their input completely in some situation.
- "Transparent" specifies that the input is either handled by the View or the game - usable for HUDs, Menus etc. For Views with "Transparent" input mode the user is the one in charge of deciding if an element on the page is interactive - hence should receive input or is 'input transparent'.

Note

iOS: Input "Transparent" views work correctly **ONLY** if you have included *coherent.js* in your HTML page.

Android: Input on any view works correctly **ONLY** if you have included *coherent.js* in your HTML page.

Upon touch within a View, *Coherent UI Mobile* inspects the touched element:

- if the element has the CSS class *coui-noinput* it passes input to the game. The element does not accept input.
- if the element has the CSS class *coui-inputcallback*, a method called *couiInputCallback(x, y)* is called on the element with the coordinates of the event. It should return "true" if the user wants the element to handle the input and "false" if the game should handle it. This allows for custom fine-grained control in JavaScript on which elements are interactive.
- if the class *coui-noinput* and *coui-inputcallback* are missing from the element, it is assumed that it is interactive and takes the input.

To summarize: If a View has an Input State set to "Transparent" all elements are by default interactive and take input. You can mark elements with the CSS class *coui-noinput* to make them transparent to input. If you need more advanced logic when deciding if an element is interactive or not you can decorate it with *coui-inputcallback* and implement a method *couiInputCallback(x, y)* on it.

5.10 Custom file handler

The *CoherentUISystem* component makes use of a static factory function object (*FileHandlerFactoryFunc*) to create the *FileHandler* object that is used reading URLs with the *coui* scheme. The default function returns a handler that reads resources from the path set by *Edit* → *Project Settings* → *Coherent UI* → *Select UI folder* for the Editor and in the Data folder for built games.

The factory function object is public and can be customized. The *FileHandler* it returns is passed to the UI initialization routine in the *Start* method of the *CoherentUISystem* component. That means the user should set the factory function prior to the invocation of the *Start* method of the components - e.g. in the *Awake* method.

Note

You can check the execution order of event function in Unity3D [on this page](#)

This is an example usage of a custom file handler:

```
public class CustomFileHandlerScript : MonoBehaviour {
    class CustomFileHandler : Coherent.UI.FileHandler
    {
        public override void ReadFile (string url, Coherent.UI.ResourceResponse response)
        {
            // Implementation here
        }

        public override void WriteFile (string url, Coherent.UI.ResourceData resource)
        {
            // Implementation here
        }
    }

    //-----

    void Awake()
    {
        CoherentUISystem.FileHandlerFactoryFunc = () => { return new CustomFileHandler(); };
    }
}
```

See [Archive resource demo](#) for an example.

5.11 UI Resources

Files for [Coherent UI](#) are by default selected from the folder set by *Edit* → *Project Settings* → [Coherent UI](#) → *Select UI folder*. Resources found there will be used by the editor and will automatically be copied in your game upon build.

The selected UI resources folder is per-user so that different developers working on the game can have their UI folders wherever they want on their machine. You can also set a per-project folder for the UI resources. This is done by extending the `CoherentPostProcessor` class by setting a static const setting named `ProjectUIResources`:

```
public partial class CoherentPostProcessor {  
    public static string ProjectUIResources = "relative/path/to/ui/resources";  
}
```

The per-project path must be relative to the folder of the project and the extension class should live under the 'Editor' folder in Unity. This feature is very handy also if you build your game on machines that can't start Unity and you use the command line. The per-user setting overrides the per-project one so that developers can still put their resources wherever they want.

Warning

When using the "Build & run" option for Android, the required resources will **NOT** be packaged because this is done as a post-build step. Unity3D pushes the non-repacked APK first, and then executes the post-build step which results in an APK without UI resources and including unneeded files. To work around that, you should either use the "Build" option, which produces an APK on your computer that can be installed on a device using the ADB tool in the Android SDK, or generate an Eclipse project and run it from the IDE.

5.12 Click-to-focus Views - Desktop only

When the `ClickToFocus` property is enabled on a View, it will automatically take **all** the input focus when you click on it and lose it when you click somewhere else. When focused, all mouse and keyboard input will be forwarded to the View. "Click-to-focus" views have their `ReceivesInput` property managed by the `CoherentUISystem` and you should **NOT** set it manually. If you do so, you'll receive a warning message in Unity3D and the input forwarding behavior will be unexpected.

Warning

There is no way to prevent the standard Unity character controller scripts from moving the character, even when the input event is *used*. You have to manually disable your character controller when you want the user to type in in a view and stands still. For an explanation see the [Menu And HUD](#) sample.

Note

"Click-to-focus" views perform raycasts to obtain the object in the 3D world below the cursor. For a raycast to report the correct texture coordinates of the hitpoint, you need to set up a *Mesh Collider* on the objects with [Coherent UI](#) Views placed.

"Click-to-focus" Views are useful in cases when you want keyboard input forwarded to a View regardless of the mouse position, e.g. input fields.

Note

To function properly, "Click-to-focus" views need to know which camera is the main camera in the scene. For simple scenes, this can be obtained from the `Camera.main` property in Unity3D. This is what [Coherent UI](#) assumes is the main camera, and obtains it in the `MonoBehaviour.OnEnable` callback, which is executed when a scene is loaded. This is done only if there is no currently set camera for the `m_MainCamera` field so it does not interfere with custom user code. For complex scenes with multiple cameras, however, it is up to you to set the public `m_MainCamera` field to the appropriate camera (also visible in the Inspector window).

Which `CoherentUIViews` receive input is up to your gameplay needs. Here we'll walk you through a simple script that you'll see used in the samples - it forwards input to the closest view under the cursor. First, it sets the `ReceivesInput` property to *all* views to **false**. Then it queries the `CoherentUIView` attached to the main camera (if any) whether the mouse is over a solid or transparent pixel (make sure to set the `SupportClickThrough` property of the HUD view to **true** to support this operation). If the mouse is over a solid pixel, then the HUD is focused and receives input. Otherwise, a raycast is generated that finds the object under the cursor. If that object has a `CoherentUIView` component, that's what gets the focus.

Here's the script itself:

To summarize, you can apply any logic you like for input forwarding - e.g. forward input to objects in the view frustum, HUD only, etc. [Coherent UI](#) supports multiple focused views. View focus can be modified using the `ReceivesInput` property of `CoherentUIView` which is controlled only by the script code.

You can also mark views as "Click to focus" which makes them take all the focus when clicking them (and lose focus when clicking somewhere else). You should take care not to set the `ReceivesInput` property on "Click to focus"-enabled Views as it is automatically managed. Setting the `ReceivesInput` property on such views manually will result in unexpected behavior and will produce a warning message.

5.13 Hit testing - Desktop only

Note

For and explanation about input forwarding for Mobile check [Input Forwarding Mobile](#)

Forwarding input to Views attached to the camera is straight-forward - you only have to mark your view as an input receiver using the `ReceivesInput` property of `CoherentUIView`. The mouse position will be obtained from the `Input.mousePosition` property.

If you want to forward an input event to a View that's attached on an object in the 3D world, you'll have to do a bit more work. You'll have to use a raycast to find the object below the cursor and then transform the texture coordinates of the hit point into the space of the [Coherent UI](#) View. Note that Unity provides texture coordinates only when the object has a `Mesh Collider` component attached. The coordinates must be transformed from `[0, 1]` to `[view.Width, view.Height]`. This can usually be done simply by multiplying the coordinates by the dimensions of the View (which are available as properties). Then, you have to set the resulting coordinates to the `CoherentUIView` component using the `SetMousePosition` method. Check [Input Forwarding](#) for an example script that forwards input to the view on the object that is currently below the cursor. Note that in the samples the `MeshCollider` component has the same geometry as the renderable mesh. This may not always be true and in such cases you would have to make a transformation of the coordinates that works for you.

For a sample how hit testing works see the [Menu and HUD](#) sample.

5.14 Logging

[Coherent UI](#) logs are automatically redirected to the Unity console (or game log for built games) using the `Debug.Log` method. You can control the minimum severity of the [Coherent UI](#) logs when initializing the [Coherent UI](#) System.

Chapter 6

Requirements

To use [Coherent](#) UI SDK in your project, please make sure that the following minimum system requirements are met by your development environment and are compatible with your project requirements for the end-users.

Software Requirements

Windows

- Windows XP (required Service Pack 3)
- Windows Vista (required Service Pack 2)
- Windows 7 (required Service Pack 1)
- Windows 8
- Windows 8.1

Visual Studio 2010, 2012, 2013 is required to build [Coherent](#) UI SDK. DirectX SDK is required for older versions of Visual Studio to build some of the samples.

Note

- All Windows systems must have the latest Service Pack provided by Microsoft installed.
- DirectX shared textures require Windows Vista or later.
- Latest drivers provided by the hardware vendor are required.
- For Windows 8 and 8.1 only desktop mode applications are supported
- WinRT is not supported
- [Microsoft DirectX End-User Runtime \(June 2010\)](#) has to be distributed with your application (or at least d3dx9_43.dll and D3DCompiler_43.dll should be included with your application).

Linux

Generally any distribution similar to Ubuntu 12.04 LTS.

- glibc 2.14 or later
- libstdc++6 or later
- GTK 2.24.10 or later
- GCC 4.6.3 or later

Note

Only the latest video card drivers are supported. OpenGL 3.0 support is required.

Mac OS X

- 10.7 or later
- XCode 4.4 or later

Note

Limited support for Mac OS 10.6.8 is available, but extensive testing should be performed, and some features might not work.

Hardware Requirements

- Intel or AMD CPU architectures are supported (no ARM support)
- Dual-core CPU is recommended
- 512 MB RAM
- 350 MB HDD space for development
- 40-80 MB HDD space for runtime libraries

Video adapter:

- Support for shader model 3.0 is required
- DirectX 9.0c or later support
- OpenGL 3.0* or later support
- Full non-power-of-two textures support
- Dedicated video card recommended
- Certain features of [Coherent](#) UI may be available on earlier versions of OpenGL but we don't test that configuration and results may be unpredictable.
- On configurations with multiple video cards - SLI, Optimus, etc., the faster card should be enabled, and your users should make sure that the same adapter runs both your application and the [Coherent](#) UI rendering processes.

Chapter 7

Namespace Documentation

7.1 Package Coherent

Namespaces

- package [UI](#)

7.2 Package Coherent.UI

Namespaces

- package [Binding](#)

Classes

- class [HTTPHeader](#)
Encapsulates a HTTP header field with it's content.
- class [BrowserView](#)
Class that encapsulates a browser [Coherent::UI::View](#)
- class [BrowserViewListener](#)
Interface that allows clients to listen to [Coherent::UI::ViewListener](#)
- class [BrowserViewListenerBase](#)
Interface all browser view listeners inherit. For an easier to use interface inherit instead -. [Coherent::UI::BrowserViewListener](#)
- class [Certificate](#)
Represents an SSL certificate.
- class [CertificatePrincipal](#)
Represents certificate principal.
- class [Download](#)
Encapsulates a download task.
- class [EventListener](#)
Abstract interface to listen to System-related events.
- class [EventModifiersState](#)
The state of the key modifiers when an event happens.
- class [EventMouseModifiersState](#)
The state of the mouse modifiers when an event happens.
- class [FileHandler](#)

- Abstract interface that allows clients to provide their own file-handling functionality.*

 - class [ILogHandler](#)

Interface to allow custom logging.
 - class [KeyEventData](#)

A keyboard event.
 - class [MediaStreamDevice](#)

Represents a media stream device.
 - class [MediaStreamRequest](#)

Represents a request for media stream.
 - class [MouseEventData](#)

A mouse event.
 - class [ResourceData](#)

Abstract interface providing data for storing resources.
 - class [ResourceResponse](#)

Abstract interface for responding to read resource requests.
 - class [SurfaceResponse](#)

Interface that signals for creation of rendering surfaces.
 - class [SystemError](#)

Encapsulates a system-related error.
 - class [SystemSettings](#)

Encapsulates the settings of the
 - class [SystemSettingsBase](#)

Encapsulates the settings of the
 - class [TouchEventData](#)

A touch event.
 - class [UISystem](#)

Encapsulates basic [UI](#) system functionality.
 - class [View](#)

Class that encapsulates a [UI](#)
 - class [ViewError](#)

Encapsulates a view-related error.
 - class [ViewInfo](#)

Encapsulates the options of a
 - class [ViewListener](#)

Interface that allows clients to listen to
 - class [ViewListenerBase](#)

Interface all view listeners inherit. For an easier to use interface inherit instead -. [Coherent::UI::ViewListener](#)
 - struct [BoundEventHandle](#)

Handle for registered delegates

Enumerations

- enum [CertificateStatus](#)

Enum containing the possible certificate validation errors.
- enum [CursorTypes](#)

Enum containing all the cursor types that a view can signal.
- enum [Direct3DInterfaceType](#)

Types of interface used for DirectX.
- enum [DownloadErrorType](#) { [DownloadErrorType.DET_Success](#), [DownloadErrorType.DET_Download-OperationFailed](#) }
- enum [JavaScriptMessageType](#)

- Enum containing the possible types of a javascript message.*

 - enum [MediaStreamType](#)

Enumeration of media stream types.
 - enum [RenderingDeviceType](#)

Types of rendering backend.
 - enum [ScriptCallErrorType](#) { [ScriptCallErrorType.SCE_Success](#), [ScriptCallErrorType.SCE_ArgumentType](#), [ScriptCallErrorType.SCE_NoSuchMethod](#), [ScriptCallErrorType.SCE_NoResult](#) }
 - enum [SystemErrorType](#) { [SystemErrorType.SE_Success](#), [SystemErrorType.SE_InternalError](#), [SystemErrorType.SE_InvalidKey](#), [SystemErrorType.SE_MissingComponent](#) }
 - System-related error-codes.*
 - enum [TextInputControlType](#)

Enum containing the text input types reported for IME.
 - enum [ViewErrorType](#) { [ViewErrorType.VE_Success](#), [ViewErrorType.VE_FailedCreation](#), [ViewErrorType.VE_FailedRenderingCreation](#), [ViewErrorType.VE_ClickThroughFailed](#), [ViewErrorType.VE_InvalidPath](#), [ViewErrorType.VE_ChildCompositionFailed](#), [ViewErrorType.VE_InvalidCall](#), [ViewErrorType.VE_FrameAlreadyInFlight](#), [ViewErrorType.VE_FrameNotReady](#), [ViewErrorType.VE_FrameNotRequested](#), [ViewErrorType.VE_AbnormalTermination](#) }
 - View-related error codes.*
 - enum [ViewType](#)

Enum containing the possible view types.

7.2.1 Enumeration Type Documentation

7.2.1.1 enum Coherent.UI.CertificateStatus

Enum containing the possible certificate validation errors.

7.2.1.2 enum Coherent.UI.CursorTypes

Enum containing all the cursor types that a view can signal.

7.2.1.3 enum Coherent.UI.Direct3DInterfaceType

Types of interface used for DirectX.

7.2.1.4 enum Coherent.UI.DownloadErrorType

Enumerator

DET_Success Indicates everything went fine.

DET_DownloadOperationFailed Indicates the download operation failed.

7.2.1.5 enum Coherent.UI.JavaScriptMessageType

Enum containing the possible types of a javascript message.

7.2.1.6 enum Coherent.UI.MediaStreamType

Enumeration of media stream types.

7.2.1.7 enum Coherent.UI.RenderingDeviceType

Types of rendering backend.

7.2.1.8 enum Coherent.UI.ScriptCallErrorType

Enumerator

SCE_Success Indicates that the call was successful.

SCE_ArgumentType Indicates that a script provided argument has different type than the one expected.

SCE_NoSuchMethod Indicates that there is no such method.

SCE_NoResult Indicates that there is no result for this call.

7.2.1.9 enum Coherent.UI.SystemErrorType

System-related error-codes.

Enumerator

SE_Success Indicates no error.

SE_InternalError Indicates a serious system internal error.

SE_InvalidKey Indicates that the user supplied an invalid activation key for this version of the product.

SE_MissingComponent Indicates that a component required by [Coherent UI](#) is missing.

7.2.1.10 enum Coherent.UI.TextInputControlType

Enum containing the text input types reported for IME.

7.2.1.11 enum Coherent.UI.ViewErrorType

View-related error codes.

Enumerator

VE_Success Indicates no error.

VE_FailedCreation Indicates failure to create a view.

VE_FailedRenderingCreation Indicates failure to create the rendering resources associated with a view.

VE_ClickThroughFailed Indicates an error during click-through a query.

VE_InvalidPath Indicates that the view was redirected to an invalid path.

VE_ChildCompositionFailed Indicates that the composition of a child widget failed.

VE_InvalidCall Indicates a call on a type of view that is not called.

VE_FrameAlreadyInFlight Indicates that a frame is already in-flight.

VE_FrameNotReady Indicates that a frame is still being rendered.

VE_FrameNotRequested Indicates that a new frame was not requested.

VE_AbnormalTermination Indicates an abnormal termination of the view.

7.2.1.12 enum Coherent.UI.ViewType

Enum containing the possible view types.

7.3 Package Coherent.UI.Binding

Classes

- class [CallbackArguments](#)
Holds the arguments for the generic callback not handled by a registered delegate
- struct [BoundObject](#)
Wrapper class for .Net objects exposed to [Coherent UI](#)
- class [CoherentProperty](#)
Specify a property / field or method visible to [Coherent UI](#)
- class [CoherentType](#)
Specify which properties and fields of a type are visible to [Coherent UI](#)
- class [UnsupportedPrimitiveTypeException](#)
Thrown when trying to bind a value of unsupported primitive type such as long
- class [InvalidValueCastException](#)
Thrown when casting a [Value](#) to an incompatible type
- class [Value](#)
Type for representing generic JavaScript values
- class [ValueObject](#)
Class for compound JavaScript objects, behaves like a Dictionary<string, Value>

Enumerations

- enum [PropertyBindingFlags](#) { [PropertyBindingFlags.Explicit](#) = 0, [PropertyBindingFlags.Instance](#) = 1, [PropertyBindingFlags.Static](#) = 2, [PropertyBindingFlags.All](#) = 3 }
Determines the set of the bound properties for this type
- enum [ValueType](#) { [ValueType.Null](#), [ValueType.Boolean](#), [ValueType.Integer](#), [ValueType.UInteger](#), [ValueType.Number](#), [ValueType.String](#), [ValueType.Array](#), [ValueType.Object](#), [ValueType.SByte](#) = 10, [ValueType.Byte](#) }
Specifies the type of [Coherent.UI.Binding.Value](#)

7.3.1 Enumeration Type Documentation

7.3.1.1 enum Coherent.UI.Binding.PropertyBindingFlags

Determines the set of the bound properties for this type

Enumerator

- Explicit** Bind only properties and fields with [CoherentProperty](#) attribute
- Instance** Bind only instance properties and fields
- Static** Bind only static properties and fields
- All** Bind all instance and static properties and fields

7.3.1.2 enum Coherent.UI.Binding.ValueType

Specifies the type of [Coherent.UI.Binding.Value](#)

Enumerator

- Null** empty value

Boolean boolean value

Integer integer value

UInteger unsigned integer value

Number double value

String string value

Array array value

Object object value

SByte signed byte value

Byte unsigned byte value

Chapter 8

Class Documentation

8.1 Coherent.UI.BoundEventHandle Struct Reference

Handle for registered delegates

8.1.1 Detailed Description

Handle for registered delegates

8.2 Coherent.UI.Binding.BoundObject Struct Reference

Wrapper class for .Net objects exposed to [Coherent UI](#)

Static Public Member Functions

- static [BoundObject BindMethods](#) (object target)
expose object's methods to [Coherent UI](#)

8.2.1 Detailed Description

Wrapper class for .Net objects exposed to [Coherent UI](#)

8.2.2 Member Function Documentation

8.2.2.1 static **BoundObject** Coherent.UI.Binding.BoundObject.BindMethods (object *target*) [inline],[static]

expose object's methods to [Coherent UI](#)

Parameters


<i>target</i>	instance
---------------	----------

Returns

8.3 Coherent.UI.BrowserView Class Reference

Class that encapsulates a browser [Coherent::UI::View](#)

Inheritance diagram for Coherent.UI.BrowserView:



Public Member Functions

- override [ViewType](#) [GetViewType](#) ()
Get The type of this view.
- virtual void [GoBack](#) ()
Navigates back to the previous URL, if any.
- virtual void [GoForward](#) ()
Navigates to the next URL, if any (i.e. available after navigating back)
- virtual void [GetHistory](#) ()
Issues a request for obtaining the navigation history for the view. [BrowserViewListener::OnHistoryObtained](#)

8.3.1 Detailed Description

Class that encapsulates a browser [Coherent::UI::View](#)

8.3.2 Member Function Documentation

8.3.2.1 virtual void [Coherent.UI.BrowserView.GetHistory](#) () `[inline], [virtual]`

Issues a request for obtaining the navigation history for the view. [BrowserViewListener::OnHistoryObtained](#)

8.3.2.2 override [ViewType](#) [Coherent.UI.BrowserView.GetViewType](#) () `[inline], [virtual]`

Get The type of this view.

Returns

the type of the view

Reimplemented from [Coherent.UI.View](#).

8.3.2.3 virtual void [Coherent.UI.BrowserView.GoBack](#) () `[inline], [virtual]`

Navigates back to the previous URL, if any.


8.3.2.4 virtual void [Coherent.UI.BrowserView.GoForward](#) () `[inline], [virtual]`

Navigates to the next URL, if any (i.e. available after navigating back)

8.4 Coherent.UI.BrowserViewListener Class Reference

Interface that allows clients to listen to [Coherent::UI::ViewListener](#)

Inheritance diagram for Coherent.UI.BrowserViewListener:



Public Member Functions

- override void [Release](#) ()
Called when the listener is no longer needed by the [UI](#) system.
- override void [OnViewCreated](#) ([View](#) view)
Called when the requested
- override void [OnDraw](#) ([CoherentHandle](#) handle, bool usesSharedMemory, int width, int height)
Called when a new surface has been drawn and is ready to use by the client.
- override void [OnFinishLoad](#) (int frameId, string validatedPath, bool isMainFrame, int statusCode, [HTTPHeader\[\]](#) headers)
Called when a frame has been successfully loaded.
- override void [OnFailLoad](#) (int frameId, string validatedPath, bool isMainFrame, string error)
Called when a frame has been failed loading.
- override void [OnURLRequest](#) (string url, [URLResponse](#) response)
Called before an URL request is made. The default implementation allows all requests.
- override void [OnReadyForBindings](#) (int frameId, string path, bool isMainFrame)
Called when a frame is ready for bindings.
- override void [OnBindingsReleased](#) (int frameId, string path, bool isMainFrame)
Called when the bindings for frame are released.
- override void [OnStartLoading](#) ()
Called when a new path has started loading.
- override void [OnStopLoading](#) ()
Called when all load operations have completed.
- override void [OnNavigateTo](#) (string path)
Called when the view starts navigation to a new path.
- override void [OnError](#) ([ViewError](#) error)
Called when an error occurs for this specific
- override void [OnScriptMessage](#) ([ViewListenerBase.MessageLevel](#) level, string message, string sourceId, int line)
Called when a message is sent from a script running in this specific
- override void [OnCursorChanged](#) ([CursorTypes](#) cursor)
Called when the cursor has changed internally in the
- override void [OnCallback](#) (string eventName, [Binding.CallbackArguments](#) arguments)
Called by the [UI](#) when there is no registered handler for this event.
- override void [OnJavaScriptMessage](#) (string message, string defaultPrompt, string frameUrl, int messageType)
Called when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.
- override void [OnGetAuthCredentials](#) (bool isProxy, string host, uint port, string realm, string scheme)

Called when a view requires authentication credentials.

- override void [CreateSurface](#) (bool sharedMemory, uint width, uint height, [SurfaceResponse](#) response)
Called when the The format for DirectX9 must be D3DFMT_A8R8G8B8 The format for DirectX10 and DirectX11 must be B8G8R8A8_UNORM
- override void [DestroySurface](#) (CoherentHandle surface, bool usesSharedMemory)
Called when a surface is unneeded anymore and should be destroyed This function can be called from a thread different than the main UI system thread in order to support client applications with multi-threaded rendering.
- override void [OnCertificateError](#) (string url, [CertificateStatus](#) status, [Certificate](#) certificate, [CertificateError-Response](#) response)
Called when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call
- override void [OnRequestMediaStream](#) ([MediaStreamRequest](#) request)
Called when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.
- override void [OnTextInputTypeChanged](#) ([TextInputControlType](#) type, bool canComposeInline)
Called when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)
- override void [OnCaretRectChanged](#) (uint x, uint y, uint width, uint height)
Called when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.
- override void [OnIMEShouldCancelComposition](#) ()
Called when the user must cancel the IME composition due to an event in the

Events

- CoherentUI_OnViewCreated [ViewCreated](#)
Fired when the requested
- CoherentUI_OnDraw [Draw](#)
Fired when a new surface has been drawn and is ready to use by the client.
- CoherentUI_OnFinishLoad [FinishLoad](#)
Fired when a frame has been successfully loaded.
- CoherentUI_OnFailLoad [FailLoad](#)
Fired when a frame has been failed loading.
- CoherentUI_OnURLRequest [URLRequest](#)
Fired before an URL request is made. The default implementation allows all requests.
- CoherentUI_OnReadyForBindings [ReadyForBindings](#)
Fired when a frame is ready for bindings.
- CoherentUI_OnBindingsReleased [BindingsReleased](#)
Fired when the bindings for frame are released.
- CoherentUI_OnStartLoading [StartLoading](#)
Fired when a new path has started loading.
- CoherentUI_OnStopLoading [StopLoading](#)
Fired when all load operations have completed.
- CoherentUI_OnNavigateTo [NavigateTo](#)
Fired when the view starts navigation to a new path.
- CoherentUI_OnError [Error](#)
Fired when an error occurs for this specific
- CoherentUI_OnScriptMessage [ScriptMessage](#)
Fired when a message is sent from a script running in this specific
- CoherentUI_OnCursorChanged [CursorChanged](#)
Fired when the cursor has changed internally in the
- CoherentUI_OnCallback [Callback](#)

Fired by the [UI](#) when there is no registered handler for this event.

- CoherentUI_OnJavaScriptMessage [JavaScriptMessage](#)

Fired when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.

- CoherentUI_OnGetAuthCredentials [GetAuthCredentials](#)

Fired when a view requires authentication credentials.

- CoherentUI_OnCertificateError [CertificateError](#)

Fired when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call

- CoherentUI_OnRequestMediaStream [RequestMediaStream](#)

Fired when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.

- CoherentUI_OnTextInputTypeChanged [TextInputTypeChanged](#)

Fired when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)

- CoherentUI_OnCaretRectChanged [CaretRectChanged](#)

Fired when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.

- CoherentUI_OnIMEShouldCancelComposition [IMEShouldCancelComposition](#)

Fired when the user must cancel the IME composition due to an event in the

Additional Inherited Members

8.4.1 Detailed Description

Interface that allows clients to listen to [Coherent::UI::ViewListener](#)

8.4.2 Member Function Documentation

8.4.2.1 `override void Coherent.UI.BrowserViewListener.CreateSurface (bool sharedMemory, uint width, uint height, SurfaceResponse response) [inline],[virtual]`

Called when the The format for DirectX9 must be D3DFMT_A8R8G8B8 The format for DirectX10 and DirectX11 must be B8G8R8A8_UNORM

Parameters

<i>sharedMemory</i>	true if the surface should be created in shared memory (4 * width * height bytes); false if a shared texture must be created.
<i>width</i>	the width of the surface in pixels
<i>height</i>	the height of the surface in pixels
<i>response</i>	<ul style="list-style-type: none"> • object to hold the response when the surface is created or fails it's creation - must be signaled

Returns

a handle to the created surface

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.2 `override void Coherent.UI.BrowserViewListener.DestroySurface (CoherentHandle surface, bool usesSharedMemory)`
`[inline], [virtual]`

Called when a surface is unneeded anymore and should be destroyed This function can be called from a thread different than the main [UI](#) system thread in order to support client applications with multi-threaded rendering.

Parameters

<i>surface</i>	handle to the surface
<i>usesShared-Memory</i>	determines whether the surface parameter is a handle to shared memory or shared texture

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.3 `override void Coherent.UI.BrowserViewListener.OnBindingsReleased (int frameId, string path, bool isMainFrame) [inline],[virtual]`

Called when the bindings for frame are released.

Parameters

<i>frameId</i>	the id of the frame
<i>path</i>	the path in the frame
<i>isMainFrame</i>	true if this is the main frame of the view

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.4 `override void Coherent.UI.BrowserViewListener.OnCallback (string eventName, Binding.CallbackArguments arguments) [inline],[virtual]`

Called by the [UI](#) when there is no registered handler for this event.

Parameters

<i>eventName</i>	name of the event
<i>arguments</i>	arguments of the event invocation

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.5 `override void Coherent.UI.BrowserViewListener.OnCaretRectChanged (uint x, uint y, uint width, uint height) [inline],[virtual]`

Called when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.

Parameters

<i>the</i>	x position of the selection caret
<i>the</i>	y position of the selection caret
<i>the</i>	width of the selection caret
<i>the</i>	height of the selection caret

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.6 `override void Coherent.UI.BrowserViewListener.OnCertificateError (string url, CertificateStatus status, Certificate certificate, CertificateErrorResponse response) [inline],[virtual]`

Called when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call

Parameters

<i>url</i>	the url of the request
<i>status</i>	the error status of the certificate
<i>certificate</i>	the certificate details. This pointer will be valid only for this call
<i>response</i>	object to signal whether to continue loading the URL. This pointer will be valid only for this call

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.7 `override void Coherent.UI.BrowserViewListener.OnCursorChanged (CursorTypes cursor) [inline], [virtual]`

Called when the cursor has changed internally in the

Parameters

<i>cursor</i>	the new cursor
---------------	----------------

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.8 `override void Coherent.UI.BrowserViewListener.OnDraw (CoherentHandle handle, bool usesSharedMemory, int width, int height) [inline], [virtual]`

Called when a new surface has been drawn and is ready to use by the client.

Parameters

<i>handle</i>	a handle to one of the buffers created by CreateSurface. May be a shared memory buffer or a shared texture depending on the way the View was created. The handle is valid only during this call
<i>usesSharedMemory</i>	determines whether the handle parameter is a handle to shared memory or shared texture
<i>width</i>	the width of the surface
<i>height</i>	the height of the surface

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.9 `override void Coherent.UI.BrowserViewListener.OnError (ViewError error) [inline], [virtual]`

Called when an error occurs for this specific

Parameters

<i>error</i>	error description
--------------	-------------------

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.10 `override void Coherent.UI.BrowserViewListener.OnFailLoad (int frameId, string validatedPath, bool isMainFrame, string error) [inline], [virtual]`

Called when a frame has been failed loading.

Parameters

<i>frameId</i>	the id of the frame
<i>validatedPath</i>	the path in the frame

<i>isMainFrame</i>	true if this is the main frame of the View
<i>error</i>	error message for the failure

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.11 `override void Coherent.UI.BrowserViewListener.OnFinishLoad (int frameId, string validatedPath, bool isMainFrame, int statusCode, HTTPHeader[] headers) [inline],[virtual]`

Called when a frame has been successfully loaded.

Parameters

<i>frameId</i>	the id of the loaded frame
<i>validatedPath</i>	the path loaded in the frame
<i>isMainFrame</i>	true if this is the main frame of the View
<i>statusCode</i>	the status code of the response
<i>headers</i>	an array of header fields
<i>headersCount</i>	the count of items in the headers array

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.12 `override void Coherent.UI.BrowserViewListener.OnGetAuthCredentials (bool isProxy, string host, uint port, string realm, string scheme) [inline],[virtual]`

Called when a view requires authentication credentials.

Parameters

<i>isProxy</i>	whether the request came from a server or a proxy
<i>host</i>	the host which triggered the request
<i>port</i>	the port at which the request was triggered
<i>realm</i>	realm of the authentication challenge. Encoded in UTF-8
<i>scheme</i>	the authentication scheme used, e.g. "basic" or "digest". Encoded in ASCII

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.13 `override void Coherent.UI.BrowserViewListener.OnIMEShouldCancelComposition () [inline],[virtual]`

Called when the user must cancel the IME composition due to an event in the

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.14 `override void Coherent.UI.BrowserViewListener.OnJavaScriptMessage (string message, string defaultPrompt, string frameUrl, int messageType) [inline],[virtual]`

Called when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.

Parameters

<i>message</i>	the JavaScript message
<i>defaultPrompt</i>	the default value of the prompt text box, in case the message type is prompt
<i>frameUrl</i>	the URL which created the message
<i>messageType</i>	the type of the message (alert/confirm/prompt)

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.15 `override void Coherent.UI.BrowserViewListener.OnNavigateTo (string path) [inline],[virtual]`

Called when the view starts navigation to a new path.

Parameters

<i>path</i>	URL that the view is navigating to
-------------	------------------------------------

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.16 `override void Coherent.UI.BrowserViewListener.OnReadyForBindings (int frameId, string path, bool isMainFrame)`
`[inline],[virtual]`

Called when a frame is ready for bindings.

Parameters

<i>frameId</i>	the id of the frame
<i>path</i>	the path in the frame
<i>isMainFrame</i>	true if this is the main frame of the view

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.17 `override void Coherent.UI.BrowserViewListener.OnRequestMediaStream (MediaStreamRequest request)`
`[inline],[virtual]`

Called when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.

Parameters

<i>request</i>	contains the available media streams for the request
----------------	--

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.18 `override void Coherent.UI.BrowserViewListener.OnScriptMessage (ViewListenerBase.MessageLevel level, string message, string sourceId, int line)`
`[inline],[virtual]`

Called when a message is sent from a script running in this specific

Parameters

<i>level</i>	message level
<i>message</i>	the text of the message
<i>sourceId</i>	id of the script (usually file name)
<i>line</i>	the number of the line in which the message was sent

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.19 `override void Coherent.UI.BrowserViewListener.OnStartLoading ()` `[inline],[virtual]`

Called when a new path has started loading.

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.20 `override void Coherent.UI.BrowserViewListener.OnStopLoading ()` `[inline],[virtual]`

Called when all load operations have completed.

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.21 `override void Coherent.UI.BrowserViewListener.OnTextInputTypeChanged (TextInputControlType type, bool canComposeInline) [inline], [virtual]`

Called when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)

Parameters

<i>type</i>	the type of the currently focused text input control by the user
<i>canCompose-Inline</i>	if the IME composition could be performed in-line in the control

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.22 `override void Coherent.UI.BrowserViewListener.OnURLRequest (string url, URLResponse response) [inline], [virtual]`

Called before an URL request is made. The default implementation allows all requests.

Parameters

<i>url</i>	the request URL
<i>response</i>	response whether to allow the request and may be redirect it. This pointer will be valid only for this call

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.23 `override void Coherent.UI.BrowserViewListener.OnViewCreated (View view) [inline], [virtual]`

Called when the requested

Parameters

<i>view</i>	the instance of the view containing all manipulation methods
-------------	--

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.2.24 `override void Coherent.UI.BrowserViewListener.Release () [inline], [virtual]`

Called when the listener is no longer needed by the [UI](#) system.

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.4.3 Event Documentation

8.4.3.1 `CoherentUI_OnBindingsReleased Coherent.UI.BrowserViewListener.BindingsReleased`

Fired when the bindings for frame are released.

8.4.3.2 `CoherentUI_OnCallback Coherent.UI.BrowserViewListener.Callback`

Fired by the [UI](#) when there is no registered handler for this event.

8.4.3.3 `CoherentUI_OnCaretRectChanged Coherent.UI.BrowserViewListener.CaretRectChanged`

Fired when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.

8.4.3.4 `CoherentUI_OnCertificateError Coherent.UI.BrowserViewListener.CertificateError`

Fired when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call

8.4.3.5 CoherentUI_OnCursorChanged Coherent.UI.BrowserViewListener.CursorChanged

Fired when the cursor has changed internally in the

8.4.3.6 CoherentUI_OnDraw Coherent.UI.BrowserViewListener.Draw

Fired when a new surface has been drawn and is ready to use by the client.

8.4.3.7 CoherentUI_OnError Coherent.UI.BrowserViewListener.Error

Fired when an error occurs for this specific

8.4.3.8 CoherentUI_OnFailLoad Coherent.UI.BrowserViewListener.FailLoad

Fired when a frame has been failed loading.

8.4.3.9 CoherentUI_OnFinishLoad Coherent.UI.BrowserViewListener.FinishLoad

Fired when a frame has been successfully loaded.

8.4.3.10 CoherentUI_OnGetAuthCredentials Coherent.UI.BrowserViewListener.GetAuthCredentials

Fired when a view requires authentication credentials.

8.4.3.11 CoherentUI_OnIMEShouldCancelComposition Coherent.UI.BrowserViewListener.IMEShouldCancelComposition

Fired when the user must cancel the IME composition due to an event in the

8.4.3.12 CoherentUI_OnJavaScriptMessage Coherent.UI.BrowserViewListener.JavaScriptMessage

Fired when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.

8.4.3.13 CoherentUI_OnNavigateTo Coherent.UI.BrowserViewListener.NavigateTo

Fired when the view starts navigation to a new path.

8.4.3.14 CoherentUI_OnReadyForBindings Coherent.UI.BrowserViewListener.ReadyForBindings

Fired when a frame is ready for bindings.

8.4.3.15 CoherentUI_OnRequestMediaStream Coherent.UI.BrowserViewListener.RequestMediaStream

Fired when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.

8.4.3.16 CoherentUI_OnScriptMessage Coherent.UI.BrowserViewListener.ScriptMessage

Fired when a message is sent from a script running in this specific

8.4.3.17 CoherentUI_OnStartLoading Coherent.UI.BrowserViewListener.StartLoading

Fired when a new path has started loading.

8.4.3.18 CoherentUI_OnStopLoading Coherent.UI.BrowserViewListener.StopLoading

Fired when all load operations have completed.

8.4.3.19 CoherentUI_OnTextInputTypeChanged Coherent.UI.BrowserViewListener.TextInputTypeChanged

Fired when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)

8.4.3.20 CoherentUI_OnURLRequest Coherent.UI.BrowserViewListener.URLRequest

Fired before an URL request is made. The default implementation allows all requests.


8.4.3.21 CoherentUI_OnViewCreated Coherent.UI.BrowserViewListener.ViewCreated

Fired when the requested

8.5 Coherent.UI.BrowserViewListenerBase Class Reference

Interface all browser view listeners inherit. For an easier to use interface inherit instead -. [Coherent::UI::BrowserViewListener](#)

Inheritance diagram for Coherent.UI.BrowserViewListenerBase:

**Additional Inherited Members****8.5.1 Detailed Description**

Interface all browser view listeners inherit. For an easier to use interface inherit instead -. [Coherent::UI::BrowserViewListener](#)

8.6 Coherent.UI.Binding.CallbackArguments Class Reference

Holds the arguments for the generic callback not handled by a registered delegate

Public Attributes

- [Value\[\] Arguments](#)

Arguments provided by JavaScript

8.6.1 Detailed Description

Holds the arguments for the generic callback not handled by a registered delegate

8.6.2 Member Data Documentation

8.6.2.1 [Value \[\] Coherent.UI.Binding.CallbackArguments.Arguments](#)

Arguments provided by JavaScript

8.7 Coherent.UI.Certificate Class Reference

Represents an SSL certificate.

Inherits [IDisposable](#).

Properties

- [byte\[\] SerialNumber](#) [\[get\]](#)
Serial number of the certificate in DER encoding.
- [byte\[\] Fingerprint](#) [\[get\]](#)
the fingerprint of the certificate
- [byte\[\] FingerprintCA](#) [\[get\]](#)
the fingerprint of the certificate authority
- [CertificatePrincipal Subject](#) [\[get\]](#)
Subject of the certificate.
- [CertificatePrincipal Issuer](#) [\[get\]](#)
Issuer of the certificate.
- [uint ValidStart](#) [\[get\]](#)
The starting date from which the certificate becomes valid in seconds since the UNIX epoch 01.01.1970.
- [uint ValidEnd](#) [\[get\]](#)
The date after which the certificate is no longer valid in seconds since the UNIX epoch 01.01.1970.

8.7.1 Detailed Description

Represents an SSL certificate.

8.7.2 Property Documentation

8.7.2.1 [byte \[\] Coherent.UI.Certificate.Fingerprint](#) [\[get\]](#)

the fingerprint of the certificate

the fingerprint in binary as 20 bytes

8.7.2.2 `byte [] Coherent.UI.Certificate.FingerprintCA` `[get]`

the fingerprint of the certificate authority

the fingerprint in binary as 20 bytes

8.7.2.3 `CertificatePrincipal Coherent.UI.Certificate.Issuer` `[get]`

Issuer of the certificate.

8.7.2.4 `byte [] Coherent.UI.Certificate.SerialNumber` `[get]`

Serial number of the certificate in DER encoding.

8.7.2.5 `CertificatePrincipal Coherent.UI.Certificate.Subject` `[get]`

Subject of the certificate.

8.7.2.6 `uint Coherent.UI.Certificate.ValidEnd` `[get]`

The date after which the certificate is no longer valid in seconds since the UNIX epoch 01.01.1970.

8.7.2.7 `uint Coherent.UI.Certificate.ValidStart` `[get]`

The starting date from which the certificate becomes valid in seconds since the UNIX epoch 01.01.1970.

8.8 Coherent.UI.CertificatePrincipal Class Reference

Represents certificate principal.

Inherits `IDisposable`.

Properties

- `string[] StreetAddresses` `[get]`
The list of street addresses of the principal
- `string[] OrganizationNames` `[get]`
The list of organization names of the principal
- `string[] OrganizationUnitNames` `[get]`
The list of organization unit names of the principal
- `string[] DomainComponents` `[get]`
The list of domain components storage of the principal
- `string CommonName` `[get]`
Null terminated string with the common name of the subject.
- `string LocalityName` `[get]`
Null terminated string with the locality name of the subject.
- `string StateOrProvinceName` `[get]`
Null terminated string with the state or province name of the subject.
- `string CountryName` `[get]`
Null terminated string with the country name of the subject.

8.8.1 Detailed Description

Represents certificate principal.

8.8.2 Property Documentation

8.8.2.1 `string Coherent.UI.CertificatePrincipal.CommonName` [get]

Null terminated string with the common name of the subject.

8.8.2.2 `string Coherent.UI.CertificatePrincipal.CountryName` [get]

Null terminated string with the country name of the subject.

8.8.2.3 `string [] Coherent.UI.CertificatePrincipal.DomainComponents` [get]

The list of domain components storage of the principal

8.8.2.4 `string Coherent.UI.CertificatePrincipal.LocalityName` [get]

Null terminated string with the locality name of the subject.

8.8.2.5 `string [] Coherent.UI.CertificatePrincipal.OrganizationNames` [get]

The list of organization names of the principal

8.8.2.6 `string [] Coherent.UI.CertificatePrincipal.OrganizationUnitNames` [get]

The list of organization unit names of the principal

8.8.2.7 `string Coherent.UI.CertificatePrincipal.StateOrProvinceName` [get]

Null terminated string with the state or province name of the subject.

8.8.2.8 `string [] Coherent.UI.CertificatePrincipal.StreetAddresses` [get]

The list of street addresses of the principal

8.9 Coherent.UI.Binding.CoherentProperty Class Reference

Specify a property / field or method visible to [Coherent UI](#)

Inherits Attribute.

Public Member Functions

- [CoherentProperty](#) ()
Make a property / field or method visible to [Coherent UI](#)
- [CoherentProperty](#) (string name)
Make a property / field or method visible to [Coherent UI](#)

8.9.1 Detailed Description

Specify a property / field or method visible to [Coherent UI](#)

8.9.2 Constructor & Destructor Documentation

8.9.2.1 Coherent.UI.Binding.CoherentProperty.CoherentProperty () [inline]

Make a property / field or method visible to [Coherent UI](#)

8.9.2.2 Coherent.UI.Binding.CoherentProperty.CoherentProperty (string *name*) [inline]

Make a property / field or method visible to [Coherent UI](#)

Parameters

<i>name</i>	name of the property / field / method
-------------	---------------------------------------

8.10 Coherent.UI.Binding.CoherentType Class Reference

Specify which properties and fields of a type are visible to [Coherent UI](#)

Inherits Attribute.

8.10.1 Detailed Description

Specify which properties and fields of a type are visible to [Coherent UI](#)

8.11 Coherent.UI.Download Class Reference

Encapsulates a download task.

Inherits IDisposable.

Public Member Functions

- virtual void [Destroy](#) ()
Must be called when the client is ready with the download to free the resources associated with it If the download is not yet complete this implies a Cancel operation Calling any method after Finish is undefined.
- virtual uint [GetId](#) ()
An opaque id of the download. Ids are unique per-system per-session and can be used to distinguish downloads pointing to the same resource.
- virtual bool [Cancel](#) ()
Cancels a download task.
- virtual string [GetURL](#) ()
The download url.
- virtual string [GetFilename](#) ()
The name of the downloaded file.
- virtual string [GetReferrer](#) ()
The referrer of the download.
- virtual uint [GetTotalBytes](#) ()

The estimated size of the download.

- virtual uint [GetDownloadedBytesSoFar](#) ()

The bytes downloaded so far. NB. Downloads are completed asynchronously, this is an estimation and might not be up-to-date.

- virtual bool [IsComplete](#) ()

Tells if the download is complete.

- virtual bool [IsCancelled](#) ()

Tells if the download has been cancelled.

- virtual bool [HasFailed](#) ()

Tells if the download has failed.

8.11.1 Detailed Description

Encapsulates a download task.

8.11.2 Member Function Documentation

8.11.2.1 virtual bool [Coherent.UI.Download.Cancel](#) () `[inline], [virtual]`

Cancels a download task.

Returns

true if the task has been cancelled. Calling Cancel on an already finished or stopped task will return false

8.11.2.2 virtual void [Coherent.UI.Download.Destroy](#) () `[inline], [virtual]`

Must be called when the client is ready with the download to free the resources associated with it If the download is not yet complete this implies a Cancel operation Calling any method after Finish is undefined.

8.11.2.3 virtual uint [Coherent.UI.Download.GetDownloadedBytesSoFar](#) () `[inline], [virtual]`

The bytes downloaded so far. NB. Downloads are completed asynchronously, this is an estimation and might not be up-to-date.

Returns

the bytes downloaded so far

8.11.2.4 virtual string [Coherent.UI.Download.GetFilename](#) () `[inline], [virtual]`

The name of the downloaded file.

Returns

the name of the file being downloaded

8.11.2.5 virtual uint Coherent.UI.Download.GetId () [inline],[virtual]

An opaque id of the download. Ids are unique per-system per-session and can be used to distinguish downloads pointing to the same resource.

Returns

a unique id of the download

8.11.2.6 virtual string Coherent.UI.Download.GetReferrer () [inline],[virtual]

The referrer of the download.

Returns

the referrer

8.11.2.7 virtual uint Coherent.UI.Download.GetTotalBytes () [inline],[virtual]

The estimated size of the download.

Returns

the estimated size in bytes

8.11.2.8 virtual string Coherent.UI.Download.GetURL () [inline],[virtual]

The download url.

Returns

the url to download

8.11.2.9 virtual bool Coherent.UI.Download.HasFailed () [inline],[virtual]

Tells if the download has failed.

Returns

if the download has failed

8.11.2.10 virtual bool Coherent.UI.Download.IsCancelled () [inline],[virtual]

Tells if the download has been cancelled.

Returns

if the download has been cancelled

8.11.2.11 virtual bool Coherent.UI.Download.IsComplete () [inline],[virtual]

Tells if the download is complete.

Returns

if the download is complete

8.12 Coherent.UI.EventListener Class Reference

Abstract interface to listen to System-related events.

Inherits IDisposable.

Public Member Functions

- virtual void [SystemReady](#) ()
Called when the system is fully initialized. Creating Views is now permitted.
- virtual void [OnError](#) ([SystemError](#) arg0)
Called when an error in the system occurs.
- virtual bool [OnDownloadStarted](#) ([Download](#) downloadItem)
Called when the system tries to start a new download. Return true to allow for the download to begin or false to cancel it.
- virtual void [OnDownloadComplete](#) ([Download](#) downloadItem, System.IntPtr data, uint size)
Called when a download is complete.
- virtual void [OnDownloadFailed](#) ([Download](#) downloadItem, [DownloadErrorType](#) error)
Called when a download has failed.

8.12.1 Detailed Description

Abstract interface to listen to System-related events.

8.12.2 Member Function Documentation

8.12.2.1 virtual void Coherent.UI.EventListener.OnDownloadComplete ([Download](#) downloadItem, System.IntPtr data, uint size) [inline],[virtual]

Called when a download is complete.

8.12.2.2 virtual void Coherent.UI.EventListener.OnDownloadFailed ([Download](#) downloadItem, [DownloadErrorType](#) error) [inline],[virtual]

Called when a download has failed.

8.12.2.3 virtual bool Coherent.UI.EventListener.OnDownloadStarted ([Download](#) downloadItem) [inline],[virtual]

Called when the system tries to start a new download. Return true to allow for the download to begin or false to cancel it.

8.12.2.4 virtual void Coherent.UI.EventListener.OnError ([SystemError](#) arg0) [inline],[virtual]

Called when an error in the system occurs.

8.12.2.5 virtual void Coherent.UI.EventListener.SystemReady () [inline],[virtual]

Called when the system is fully initialized. Creating Views is now permitted.

8.13 Coherent.UI.EventModifiersState Class Reference

The state of the key modifiers when an event happens.

Inherits IDisposable.

8.13.1 Detailed Description

The state of the key modifiers when an event happens.

8.14 Coherent.UI.EventMouseModifiersState Class Reference

The state of the mouse modifiers when an event happens.

Inherits IDisposable.

8.14.1 Detailed Description

The state of the mouse modifiers when an event happens.

8.15 Coherent.UI.FileHandler Class Reference

Abstract interface that allows clients to provide their own file-handling functionality.

Inherits IDisposable.

Public Member Functions

- virtual void [ReadFile](#) (string url, [ResourceResponse](#) response)
Requests to read a resource.
- virtual void [WriteFile](#) (string url, [ResourceData](#) resource)
Request to write to a resource.

8.15.1 Detailed Description

Abstract interface that allows clients to provide their own file-handling functionality.

8.15.2 Member Function Documentation

8.15.2.1 virtual void Coherent.UI.FileHandler.ReadFile (string url, ResourceResponse response) [inline],
[virtual]

Requests to read a resource.

Parameters

<i>url</i>	the coui url of the resource.
------------	-------------------------------

<i>response</i>	the response to be filled with the resource data or notified for failure
-----------------	--

8.15.2.2 `virtual void Coherent.UI.FileHandler.WriteFile (string url, ResourceData resource) [inline],[virtual]`

Request to write to a resource.

Parameters

<i>url</i>	the coui url of the resource.
<i>resource</i>	the resource data that has to be written

8.16 Coherent.UI.HTTPHeader Class Reference

Encapsulates a HTTP header field with it's content.

Inherits IDisposable.

Properties

- string [Field](#) [get, set]
The name (key) of the HTTP header field.
- string [Content](#) [get, set]
The value of the HTTP header field.

8.16.1 Detailed Description

Encapsulates a HTTP header field with it's content.

8.16.2 Property Documentation

8.16.2.1 `string Coherent.UI.HTTPHeader.Content [get],[set]`

The value of the HTTP header field.

8.16.2.2 `string Coherent.UI.HTTPHeader.Field [get],[set]`

The name (key) of the HTTP header field.

8.17 Coherent.UI.ILogHandler Class Reference

Interface to allow custom logging.

Inherits IDisposable.

Public Member Functions

- virtual void [WriteLog](#) (Severity severity, string message, uint length)
Called when a log message has to be written.

- virtual void [Assert](#) (string message)
Called when an assert is triggered.

8.17.1 Detailed Description

Interface to allow custom logging.

8.17.2 Member Function Documentation

8.17.2.1 virtual void Coherent.UI.ILogHandler.Assert (string *message*) [inline], [virtual]

Called when an assert is triggered.

Parameters

<i>message</i>	a message that describes the reason for the assertion
----------------	---

8.17.2.2 virtual void Coherent.UI.ILogHandler.WriteLog (Severity *severity*, string *message*, uint *length*) [inline], [virtual]

Called when a log message has to be written.

Parameters

<i>severity</i>	the severity of the message
<i>message</i>	the log message itself
<i>length</i>	the length of the message

8.18 Coherent.UI.Binding.InvalidValueCastException Class Reference

Thrown when casting a [Value](#) to an incompatible type

Inherits InvalidCastException.

8.18.1 Detailed Description

Thrown when casting a [Value](#) to an incompatible type

8.19 Coherent.UI.KeyEventData Class Reference

A keyboard event.

Inherits IDisposable.

Properties

- int [KeyCode](#) [get, set]
The key code.
- KeyEventData.EventType [Type](#) [get, set]
The type of the event.
- [EventModifiersState Modifiers](#) [get, set]

The current key modifiers.

- bool [IsAutoRepeat](#) [get, set]

Is it an auto-repeat event (the user is holding the key down). This value isn't crucial and you can set it to false if you don't have the information, however you might experience incorrect repeat behavior in such case.

- bool [IsNumPad](#) [get, set]

Is it a key from the num-pad.

8.19.1 Detailed Description

A keyboard event.

8.19.2 Property Documentation

8.19.2.1 bool Coherent.UI.KeyEventData.IsAutoRepeat [get], [set]

Is it an auto-repeat event (the user is holding the key down). This value isn't crucial and you can set it to false if you don't have the information, however you might experience incorrect repeat behavior in such case.

8.19.2.2 bool Coherent.UI.KeyEventData.IsNumPad [get], [set]

Is it a key from the num-pad.

8.19.2.3 int Coherent.UI.KeyEventData.KeyCode [get], [set]

The key code.

8.19.2.4 EventModifiersState Coherent.UI.KeyEventData.Modifiers [get], [set]

The current key modifiers.

8.19.2.5 KeyEventData.EventType Coherent.UI.KeyEventData.Type [get], [set]

The type of the event.

8.20 Coherent.UI.MediaStreamDevice Class Reference

Represents a media stream device.

Inherits IDisposable.

Properties

- [MediaStreamType Type](#) [get]

type of the device

- string [Deviceld](#) [get]

Null terminated string with the unique id of the device.

- string [Name](#) [get]

Null terminated string with the device name. It may not be unique.

8.20.1 Detailed Description

Represents a media stream device.

8.20.2 Property Documentation

8.20.2.1 `string Coherent.UI.MediaStreamDevice.DeviceId` `[get]`

Null terminated string with the unique id of the device.

8.20.2.2 `string Coherent.UI.MediaStreamDevice.Name` `[get]`

Null terminated string with the device name. It may not be unique.

8.20.2.3 `MediaStreamType Coherent.UI.MediaStreamDevice.Type` `[get]`

type of the device

8.21 Coherent.UI.MediaStreamRequest Class Reference

Represents a request for media stream.

Inherits `IDisposable`.

Public Member Functions

- `void Respond (uint[] devices)`
Respond to the media stream request.

Properties

- `MediaStreamDevice[] Devices` `[get]`
Get the list of available devices for the request. The list contains only devices of the requested types.

8.21.1 Detailed Description

Represents a request for media stream.

8.21.2 Member Function Documentation

8.21.2.1 `void Coherent.UI.MediaStreamRequest.Respond (uint[] devices)` `[inline]`

Respond to the media stream request.

Parameters

<i>devices</i>	array of indices of the media stream devices to use for the request
----------------	---

Only a single device per stream type must be allowed. After a call to `Respond` calling any method on the instance results in undefined behavior. Must be called on the thread that owns the `Coherent::UI::UISystem` instance.

8.21.3 Property Documentation

8.21.3.1 `MediaStreamDevice [] Coherent.UI.MediaStreamRequest.Devices` [get]

Get the list of available devices for the request. The list contains only devices of the requested types.

8.22 `Coherent.UI.MouseEventData` Class Reference

A mouse event.

Inherits `IDisposable`.

Properties

- `MouseEventData.EventType` [Type](#) [get, set]
The type of the event.
- `MouseEventData.MouseButton` [Button](#) [get, set]
The mouse button that triggered the event.
- `int X` [get, set]
The X position of the mouse in pixels in the space of the view.
- `int Y` [get, set]
The Y position of the mouse in pixels in the space of the view.
- `float WheelX` [get, set]
Scroll Delta X in wheel ticks. Positive numbers mean scrolling left.
- `float WheelY` [get, set]
Scroll Delta Y in wheel ticks. Positive numbers mean scrolling up.
- `EventModifiersState Modifiers` [get, set]
Key modifiers.
- `EventMouseModifiersState MouseModifiers` [get, set]
Mouse modifiers.

8.22.1 Detailed Description

A mouse event.

8.22.2 Property Documentation

8.22.2.1 `MouseEventData.MouseButton` `Coherent.UI.MouseEventData.Button` [get], [set]

The mouse button that triggered the event.

8.22.2.2 `EventModifiersState` `Coherent.UI.MouseEventData.Modifiers` [get], [set]

Key modifiers.

8.22.2.3 `EventMouseModifiersState` `Coherent.UI.MouseEventData.MouseModifiers` [get], [set]

Mouse modifiers.

8.22.2.4 MouseEventData.EventType Coherent.UI.MouseEventData.Type [get], [set]

The type of the event.

8.22.2.5 float Coherent.UI.MouseEventData.WheelX [get], [set]

Scroll Delta X in wheel ticks. Positive numbers mean scrolling left.

8.22.2.6 float Coherent.UI.MouseEventData.WheelY [get], [set]

Scroll Delta Y in wheel ticks. Positive numbers mean scrolling up.

8.22.2.7 int Coherent.UI.MouseEventData.X [get], [set]

The X position of the mouse in pixels in the space of the view.

8.22.2.8 int Coherent.UI.MouseEventData.Y [get], [set]

The Y position of the mouse in pixels in the space of the view.

8.23 Coherent.UI.ResourceData Class Reference

Abstract interface providing data for storing resources.

Inherits IDisposable.

Public Member Functions

- virtual IntPtr [GetBuffer](#) ()
Get the buffer with the resource data.
- virtual uint [GetSize](#) ()
Get the size of the data.
- virtual void [SignalSuccess](#) ()
Report that writing to resource was successful. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.
- virtual void [SignalFailure](#) ()
Report that resource writing has failed. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.

8.23.1 Detailed Description

Abstract interface providing data for storing resources.

8.23.2 Member Function Documentation

8.23.2.1 virtual IntPtr Coherent.UI.ResourceData.GetBuffer () [inline], [virtual]

Get the buffer with the resource data.

Returns

pointer to the beginning of the data. May return nullptr when acquiring the buffer has failed

8.23.2.2 `virtual uint Coherent.UI.ResourceData.GetSize () [inline],[virtual]`

Get the size of the data.

Returns

the size of the data

8.23.2.3 `virtual void Coherent.UI.ResourceData.SignalFailure () [inline],[virtual]`

Report that resource writing has failed. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.

8.23.2.4 `virtual void Coherent.UI.ResourceData.SignalSuccess () [inline],[virtual]`

Report that writing to resource was successful. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.

8.24 Coherent.UI.ResourceResponse Class Reference

Abstract interface for responding to read resource requests.

Inherits IDisposable.

Public Member Functions

- virtual IntPtr [GetBuffer](#) (uint size)
Request buffer for resource data. GetBuffer must be called only once. GetBuffer may be called in any thread.
- virtual void [SignalSuccess](#) ()
Report that the resource is read successfully. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.
- virtual void [SignalFailure](#) ()
Report that resource reading has failed. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.

8.24.1 Detailed Description

Abstract interface for responding to read resource requests.

8.24.2 Member Function Documentation

8.24.2.1 `virtual IntPtr Coherent.UI.ResourceResponse.GetBuffer (uint size) [inline],[virtual]`

Request buffer for resource data. GetBuffer must be called only once. GetBuffer may be called in any thread.

Parameters

<i>size</i>	the size of the resource
-------------	--------------------------

Returns

pointer to the beginning of the buffer. It may return nullptr when allocating the buffer has failed

8.24.2.2 virtual void Coherent.UI.ResourceResponse.SignalFailure () [inline],[virtual]

Report that resource reading has failed. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.

8.24.2.3 virtual void Coherent.UI.ResourceResponse.SignalSuccess () [inline],[virtual]

Report that the resource is read successfully. This should be executed in the thread that all [Coherent UI](#) methods are executed. After this method is called, any calls to any method of the instance are undefined behavior.

8.25 Coherent.UI.SurfaceResponse Class Reference

Interface that signals for creation of rendering surfaces.

Inherits IDisposable.

Public Member Functions

- virtual void [Signal](#) (CoherentHandle handle)

Signals that the operation was completed. You should call this function in the same thread that updates the [UI](#) system.

8.25.1 Detailed Description

Interface that signals for creation of rendering surfaces.

8.25.2 Member Function Documentation

8.25.2.1 virtual void Coherent.UI.SurfaceResponse.Signal (CoherentHandle *handle*) [inline],[virtual]

Signals that the operation was completed. You should call this function in the same thread that updates the [UI](#) system.

Parameters

<i>handle</i>	the created surface handle or a NULL handle if the operation fails
---------------	--

8.26 Coherent.UI.SystemError Class Reference

Encapsulates a system-related error.

Inherits IDisposable.

Properties

- **SystemErrorType ErrorCode** [get, set]
Indicates an error code.
- string **Error** [get, set]
Error description.

8.26.1 Detailed Description

Encapsulates a system-related error.

8.26.2 Property Documentation

8.26.2.1 string Coherent.UI.SystemError.Error [get], [set]

Error description.


8.26.2.2 SystemErrorType Coherent.UI.SystemError.ErrorCode [get], [set]

Indicates an error code.

8.27 Coherent.UI.SystemSettings Class Reference

Encapsulates the settings of the

Inheritance diagram for Coherent.UI.SystemSettings:



Properties

- new string **HostDirectory** [get, set]
Points to the folder where the host application and it's libraries reside (relative to the application's directory)
- new string **CookiesResource** [get, set]
Resource name to be used for storing and loading cookies. Leave nullptr to disable persistence of cookies.
- new string **CachePath** [get, set]
Path (relative to the host executable) where to save cached data. Leave nullptr for in-memory only caching.
- new string **HTML5LocalStoragePath** [get, set]
Path (relative to the host executable) where to allow pages to save their HTML5 local data. Leave nullptr to forbid local storage.
- new string **MinidumpFolder** [get, set]
The folder where eventual minidumps will be saved (Windows only)
- System.IntPtr **FocusWindow** [set]
The focus window that the client has passed when creating her device. This, along with D3DInterfaceType and D3D-Object, is needed for fullscreen apps that use DirectX9 or DirectX9Ex so as to support Alt+Tab functionality. Otherwise might be omitted. (Windows only)
- System.IntPtr **D3DObject** [set]

The D3DObject used by client to create her device. This, along with D3DInterfaceType and FocusWindow, is needed for fullscreen apps that use DirectX9 or DirectX9Ex so as to support Alt+Tab functionality. Otherwise might be omitted. (Windows only)

8.27.1 Detailed Description

Encapsulates the settings of the

8.27.2 Property Documentation

8.27.2.1 `new string Coherent.UI.SystemSettings.CachePath` `[get], [set]`

Path (relative to the host executable) where to save cached data. Leave nullptr for in-memory only caching.

8.27.2.2 `new string Coherent.UI.SystemSettings.CookiesResource` `[get], [set]`

Resource name to be used for storing and loading cookies. Leave nullptr to disable persistence of cookies.

8.27.2.3 `System.IntPtr Coherent.UI.SystemSettings.D3DObject` `[set]`

The D3DObject used by client to create her device. This, along with D3DInterfaceType and FocusWindow, is needed for fullscreen apps that use DirectX9 or DirectX9Ex so as to support Alt+Tab functionality. Otherwise might be omitted. (Windows only)

8.27.2.4 `System.IntPtr Coherent.UI.SystemSettings.FocusWindow` `[set]`

The focus window that the client has passed when creating her device. This, along with D3DInterfaceType and D3DObject, is needed for fullscreen apps that use DirectX9 or DirectX9Ex so as to support Alt+Tab functionality. Otherwise might be omitted. (Windows only)

8.27.2.5 `new string Coherent.UI.SystemSettings.HostDirectory` `[get], [set]`

Points to the folder where the host application and it's libraries reside (relative to the application's directory)

8.27.2.6 `new string Coherent.UI.SystemSettings.HTML5LocalStoragePath` `[get], [set]`

Path (relative to the host executable) where to allow pages to save their HTML5 local data. Leave nullptr to forbid local storage.


8.27.2.7 `new string Coherent.UI.SystemSettings.MinidumpFolder` `[get], [set]`

The folder where eventual minidumps will be saved (Windows only)

8.28 Coherent.UI.SystemSettingsBase Class Reference

Encapsulates the settings of the

Inheritance diagram for Coherent.UI.SystemSettingsBase:



Properties

- bool [EnableProxy](#) [get, set]
Enables/disables proxy support. Proxy settings are auto-detected when proxy support is enabled. Enable proxy support only when the user really has a proxy, because otherwise the auto-detection is very slow.
- bool [AllowCookies](#) [get, set]
Enables/disables cookies when accessing the web.
- bool [ForceDisablePluginFullscreen](#) [get, set]
Disables 'Fullscreen mode' on all Plugins(Flash etc.)
- bool [DisableWebSecurity](#) [get, set]
Disable Same-Origin Policy. Use with caution.
- int [DebuggerPort](#) [get, set]
Port to use for remote debugging. Use -1 to disable debugging.
- bool [WriteMinidumps](#) [get, set]
If a
- bool [EnableSupportForProprietaryCodecs](#) [get, set]
Enable support for proprietary codecs. Playing proprietary codecs requires ffmpegsumo library that is capable of playing them as well. Note that distributing such ffmpegsumo library requires license from the respective rights holder.
- [Direct3DInterfaceType](#) [D3DInterfaceType](#) [get, set]
The type of D3DObject supplied. This, along with D3DObject and FocusWindow, is needed for fullscreen apps that use DirectX9 or DirectX9Ex so as to support Alt+Tab functionality. Otherwise might be omitted. (Windows only)

8.28.1 Detailed Description

Encapsulates the settings of the

8.28.2 Property Documentation

8.28.2.1 bool Coherent.UI.SystemSettingsBase.AllowCookies [get], [set]

Enables/disables cookies when accessing the web.

8.28.2.2 Direct3DInterfaceType Coherent.UI.SystemSettingsBase.D3DInterfaceType [get], [set]

The type of D3DObject supplied. This, along with D3DObject and FocusWindow, is needed for fullscreen apps that use DirectX9 or DirectX9Ex so as to support Alt+Tab functionality. Otherwise might be omitted. (Windows only)

8.28.2.3 int Coherent.UI.SystemSettingsBase.DebuggerPort [get], [set]

Port to use for remote debugging. Use -1 to disable debugging.

8.28.2.4 bool Coherent.UI.SystemSettingsBase.DisableWebSecurity [get], [set]

Disable Same-Origin Policy. Use with caution.

8.28.2.5 `bool Coherent.UI.SystemSettingsBase.EnableProxy` `[get], [set]`

Enables/disables proxy support. Proxy settings are auto-detected when proxy support is enabled. Enable proxy support only when the user really has a proxy, because otherwise the auto-detection is very slow.

8.28.2.6 `bool Coherent.UI.SystemSettingsBase.EnableSupportForProprietaryCodecs` `[get], [set]`

Enable support for proprietary codecs. Playing proprietary codecs requires ffmpegsumo library that is capable of playing them as well. Note that distributing such ffmpegsumo library requires license from the respective rights holder.

8.28.2.7 `bool Coherent.UI.SystemSettingsBase.ForceDisablePluginFullscreen` `[get], [set]`

Disables 'Fullscreen mode' on all Plugins(Flash etc.)

8.28.2.8 `bool Coherent.UI.SystemSettingsBase.WriteMinidumps` `[get], [set]`

If a

8.29 Coherent.UI.TouchEventData Class Reference

A touch event.

Inherits IDisposable.

Properties

- `int X` `[get, set]`
The X position where the touch happened in pixels in the space of the view.
- `int Y` `[get, set]`
The Y position where the touch happened in pixels in the space of the view.
- `uint Id` `[get, set]`
Identifies a particular touch input. This value must stay consistent in a touch contact sequence.
- `TouchEventData.EventType Type` `[get, set]`
The type of the touch event.
- `bool HasRadiusInformation` `[get, set]`
Flags if there is contact radius information for this event.
- `uint RadiusX` `[get, set]`
The X radius of the contact (must be set only if HasRadiusInformation == true)
- `uint RadiusY` `[get, set]`
The Y radius of the contact (must be set only if HasRadiusInformation == true)

8.29.1 Detailed Description

A touch event.

8.29.2 Property Documentation

8.29.2.1 `bool Coherent.UI.TouchEventData.HasRadiusInformation` `[get], [set]`

Flags if there is contact radius information for this event.

8.29.2.2 uint Coherent.UI.TouchEventData.Id [get], [set]

Identifies a particular touch input. This value must stay consistent in a touch contact sequence.

8.29.2.3 uint Coherent.UI.TouchEventData.RadiusX [get], [set]

The X radius of the contact (must be set only if HasRadiusInformation == true)

8.29.2.4 uint Coherent.UI.TouchEventData.RadiusY [get], [set]

The Y radius of the contact (must be set only if HasRadiusInformation == true)

8.29.2.5 TouchEventData.EventType Coherent.UI.TouchEventData.Type [get], [set]

The type of the touch event.

8.29.2.6 int Coherent.UI.TouchEventData.X [get], [set]

The X position where the touch happened in pixels in the space of the view.

8.29.2.7 int Coherent.UI.TouchEventData.Y [get], [set]

The Y position where the touch happened in pixels in the space of the view.

8.30 Coherent.UI.UISystem Class Reference

Encapsulates basic [UI](#) system functionality.

Inherits [IDisposable](#).

Public Member Functions

- virtual bool [Uninitialize](#) ()
Frees all resources used by the event system. the [UISystem](#) object is unusable after this call
- virtual void [Update](#) ()
Communicates with the [UI](#) system process and performs all updates. Must be called in the thread that owns the system. All registered callbacks will be called in here
- virtual void [FetchSurfaces](#) ()
Check if new surfaces have been drawn and are available. This function can be called from a thread different than the main [UI](#) system thread in order to support client applications with multi-threaded rendering. Fetches only the surfaces of buffered views; on-demand views must be fetched manually per-view
- virtual void [CreateView](#) ([ViewInfo](#) info, string path, [ViewListenerBase](#) listener)
Creates a new [UI](#) Must be called after the system has signaled that it is ready via [Coherent::UI::EventListener::SystemReady](#)
- virtual void [CreateView](#) ([ViewInfo](#) info, string path, [ViewListenerBase](#) listener, string scriptToExecute)
Creates a new [UI](#) Must be called after the system has signaled that it is ready via [Coherent::UI::EventListener::SystemReady](#)

8.30.1 Detailed Description

Encapsulates basic [UI](#) system functionality.

8.30.2 Member Function Documentation

8.30.2.1 `virtual void Coherent.UI.UISystem.CreateView (ViewInfo info, string path, ViewListenerBase listener) [inline],[virtual]`

Creates a new [UI](#) Must be called after the system has signaled that it is ready via [Coherent::UI::EventListener::SystemReady](#)

Parameters

<i>info</i>	an instance of the ViewInfo struct that describes all the parameters of the view
<i>path</i>	the page to load when the view is created
<i>listener</i>	an instance of the ViewListenerBase interface to allow listening to all the events raised for this view

8.30.2.2 `virtual void Coherent.UI.UISystem.CreateView (ViewInfo info, string path, ViewListenerBase listener, string scriptToExecute) [inline],[virtual]`

Creates a new [UI](#) Must be called after the system has signaled that it is ready via [Coherent::UI::EventListener::SystemReady](#)

Parameters

<i>info</i>	an instance of the ViewInfo struct that describes all the parameters of the view
<i>path</i>	the page to load when the view is created
<i>listener</i>	an instance of the ViewListenerBase interface to allow listening to all the events raised for this view

8.30.2.3 `virtual void Coherent.UI.UISystem.FetchSurfaces () [inline],[virtual]`

Check if new surfaces have been drawn and are available. This function can be called from a thread different than the main [UI](#) system thread in order to support client applications with multi-threaded rendering. Fetches only the surfaces of buffered views; on-demand views must be fetched manually per-view

8.30.2.4 `virtual bool Coherent.UI.UISystem.Uninitialize () [inline],[virtual]`

Frees all resources used by the event system. the [UISystem](#) object is unusable after this call

Returns

true if the system has been properly uninitialized

8.30.2.5 `virtual void Coherent.UI.UISystem.Update () [inline],[virtual]`

Communicates with the [UI](#) system process and performs all updates. Must be called in the thread that owns the system. All registered callbacks will be called in here

8.31 Coherent.UI.Binding.UnsupportedPrimitiveTypeException Class Reference

Thrown when trying to bind a value of unsupported primitive type such as long

Inherits [Exception](#).

8.31.1 Detailed Description

Thrown when trying to bind a value of unsupported primitive type such as long

8.32 Coherent.UI.Binding.Value Class Reference

Type for representing generic JavaScript values

Public Member Functions

- [Value](#) ()
Create a null value
- [Value](#) (bool value)
Create a boolean value
- [Value](#) (int value)
Create an integer value
- [Value](#) (uint value)
Create an unsigned integer value
- [Value](#) (sbyte value)
Create a signed byte value
- [Value](#) (byte value)
Create a byte value
- [Value](#) (float value)
Create a float value
- [Value](#) (double value)
Create a double value
- [Value](#) (string value)
Create a string value
- [Value](#) ([Value](#)[] value)
Create an array value
- [Value](#) (Dictionary< string, [Value](#) > value)
Create an object value
- [Value](#) ([ValueObject](#) value)
Create an object value
- override bool [Equals](#) (object obj)
Compare to another object
- override int [GetHashCode](#) ()
Hash code for [Value](#)

Static Public Member Functions

- static implicit [operator bool](#) ([Value](#) value)
cast a value to a boolean
- static implicit [operator int](#) ([Value](#) value)
cast a value to an int
- static implicit [operator uint](#) ([Value](#) value)
cast a value to an uint
- static implicit [operator sbyte](#) ([Value](#) value)
cast a value to a signed byte

- static implicit [operator byte](#) ([Value](#) value)
cast a value to a byte
- static implicit [operator float](#) ([Value](#) value)
cast a value to a float
- static implicit [operator double](#) ([Value](#) value)
cast a value to a double
- static implicit [operator string](#) ([Value](#) value)
cast a value to a string
- static implicit [operator Value\[\]](#) ([Value](#) value)
cast a value to an array
- static implicit [operator Dictionary< string, Value >](#) ([Value](#) value)
cast a value to a dictionary of properties
- static bool [operator==](#) ([Value](#) lhs, [Value](#) rhs)
Compares two [Value](#) objects
- static bool [operator!=](#) ([Value](#) lhs, [Value](#) rhs)
Compares two [Value](#) objects

Public Attributes

- [ValueType](#) Type
The type of the data stored in this [Value](#) instance

8.32.1 Detailed Description

Type for representing generic JavaScript values

8.32.2 Constructor & Destructor Documentation

8.32.2.1 Coherent.UI.Binding.Value.Value () [inline]

Create a null value

8.32.2.2 Coherent.UI.Binding.Value.Value (bool value) [inline]

Create a boolean value

Parameters

<i>value</i>	the integer value of the Value object
--------------	---

8.32.2.3 Coherent.UI.Binding.Value.Value (int value) [inline]

Create an integer value

Parameters

<i>value</i>	the integer value of the Value object
--------------	---

8.32.2.4 Coherent.UI.Binding.Value.Value (uint value) [inline]

Create an unsigned integer value

Parameters

<i>value</i>	the unsigned integer value of the Value object
--------------	--

8.32.2.5 `Coherent.UI.Binding.Value.Value (sbyte value) [inline]`

Create a signed byte value

Parameters

<i>value</i>	the signed byte value of the Value object
--------------	---

8.32.2.6 `Coherent.UI.Binding.Value.Value (byte value) [inline]`

Create a byte value

Parameters

<i>value</i>	the byte value of the Value object
--------------	--

8.32.2.7 `Coherent.UI.Binding.Value.Value (float value) [inline]`

Create a float value

Parameters

<i>value</i>	the float value of the Value object
--------------	---

8.32.2.8 `Coherent.UI.Binding.Value.Value (double value) [inline]`

Create a double value

Parameters

<i>value</i>	the double value of the Value object
--------------	--

8.32.2.9 `Coherent.UI.Binding.Value.Value (string value) [inline]`

Create a string value

Parameters

<i>value</i>	the string value of the Value object
--------------	--

8.32.2.10 `Coherent.UI.Binding.Value.Value (Value[] value) [inline]`

Create an array value

Parameters

<i>value</i>	the array value of the Value object
--------------	---

8.32.2.11 Coherent.UI.Binding.Value.Value (Dictionary< string, Value > *value*) [inline]

Create an object value

Parameters

<i>value</i>	dictionary of properties of the Value object
--------------	--

8.32.2.12 `Coherent.UI.Binding.Value.Value (ValueObject value) [inline]`

Create an object value

Parameters

<i>value</i>	dictionary of properties of the Value object
--------------	--

8.32.3 Member Function Documentation**8.32.3.1** `override bool Coherent.UI.Binding.Value.Equals (object obj) [inline]`

Compare to another object

Parameters

<i>obj</i>	
------------	--

Returns

true if obj is a [Value](#) instance equal to this one

8.32.3.2 `override int Coherent.UI.Binding.Value.GetHashCode () [inline]`

Hash code for [Value](#)

Returns

hash code for the current instance

8.32.3.3 `static implicit Coherent.UI.Binding.Value.operator bool (Value value) [inline],[static]`

cast a value to a boolean

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the boolean stored in the value

8.32.3.4 `static implicit Coherent.UI.Binding.Value.operator byte (Value value) [inline],[static]`

cast a value to a byte

Parameters

<i>value</i>	value to be cast
--------------	------------------

Returns

the byte stored in the value

8.32.3.5 static implicit Coherent.UI.Binding.Value.operator Dictionary< string, Value > (Value *value*) [inline], [static]

cast a value to a dictionary of properties

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the dictionary of properties of the value

8.32.3.6 static implicit Coherent.UI.Binding.Value.operator double (Value *value*) [inline], [static]

cast a value to a double

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the double stored in the value

8.32.3.7 static implicit Coherent.UI.Binding.Value.operator float (Value *value*) [inline], [static]

cast a value to a float

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the float stored in the value

8.32.3.8 static implicit Coherent.UI.Binding.Value.operator int (Value *value*) [inline], [static]

cast a value to an int

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the int stored in the value

8.32.3.9 static implicit Coherent.UI.Binding.Value.operator sbyte (Value *value*) [inline], [static]

cast a value to a signed byte

Parameters

<i>value</i>	value to be cast
--------------	------------------

Returns

the signed byte stored in the value

8.32.3.10 `static implicit Coherent.UI.Binding.Value.operator string (Value value) [inline],[static]`

cast a value to a string

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the string stored in the value

8.32.3.11 `static implicit Coherent.UI.Binding.Value.operator uint (Value value) [inline],[static]`

cast a value to an uint

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the unsigned int stored in the value

8.32.3.12 `static implicit Coherent.UI.Binding.Value.operator Value[] (Value value) [inline],[static]`

cast a value to an array

Parameters

<i>value</i>	value to be casted
--------------	--------------------

Returns

the array of [Value](#) objects stored in the value

8.32.3.13 `static bool Coherent.UI.Binding.Value.operator!= (Value lhs, Value rhs) [inline],[static]`

Compares two [Value](#) objects

Parameters

<i>lhs</i>	object to be compared
<i>rhs</i>	object to be compared

Returns

false if the objects are from the same type and have the same values

8.32.3.14 `static bool Coherent.UI.Binding.Value.operator==(Value lhs, Value rhs) [inline],[static]`

Compares two [Value](#) objects

Parameters

<i>lhs</i>	object to be compared
<i>rhs</i>	object to be compared

Returns

true if the objects are from the same type and have the same values

8.32.4 Member Data Documentation

8.32.4.1 ValueType Coherent.UI.Binding.Value.Type

The type of the data stored in this [Value](#) instance

8.33 Coherent.UI.Binding.ValueObject Class Reference

Class for compound JavaScript objects, behaves like a Dictionary<string, Value>

Inherits IDictionary< string, Value >, and IDictionary.


8.33.1 Detailed Description

Class for compound JavaScript objects, behaves like a Dictionary<string, Value>

8.34 Coherent.UI.View Class Reference

Class that encapsulates a [UI](#)

Inheritance diagram for Coherent.UI.View:



Public Member Functions

- [BoundEventHandle BindCall](#) (string name, System.Delegate handler)
Expose C++ handler to be called from [UI](#).
- [BoundEventHandle RegisterForEvent](#) (string name, System.Delegate handler)
Expose C++ handler to be called when a specific event occurs.
- void [UnregisterFromEvent](#) ([BoundEventHandle](#) handle)
Remove a registered C++ handler.
- void [UnbindCall](#) ([BoundEventHandle](#) handle)
Remove a bound C++ handler.
- void [UnbindObject](#) (object target)
Remove all handlers bound to a specific object.
- virtual [ViewType GetViewType](#) ()
Get the type of the view.

- virtual void [Destroy](#) ()
Destroys this view. After a call to Destroy calling any other method except the destructor results in undefined behavior
- virtual void [SetFocus](#) ()
Sets this view on focus.
- virtual void [KillFocus](#) ()
Removes the focus from this view.
- virtual void [MouseEvent](#) ([MouseEventData](#) arg0)
Sends a mouse event to the [UI](#) renderer.
- virtual void [KeyEvent](#) ([KeyEventData](#) arg0)
Sends a key event to the [UI](#) renderer.
- virtual void [TouchEvent](#) ([TouchEventData](#) events, uint count)
Sends a touch event to the [UI](#) renderer.
- virtual void [MouseActivate](#) ()
Sends a mouse event to the [UI](#) renderer.
- virtual int [GetWidth](#) ()
Gets the width of the
- virtual int [GetHeight](#) ()
Gets the height of the
- virtual void [Resize](#) (uint width, uint height)
Send a resize event to the [UI](#) renderer. Resize will result in multiple calls to CreateBuffers and DestroyBuffers in the listener
- virtual void [IssueMouseOnUIQuery](#) (float normX, float normY)
Issues a query on the [Calling IsMouseOnView](#) while a query is in-flight is an error and will be logged - the result returned by IsMouseOnView in that case is undefined.
- virtual void [FetchMouseOnUIQuery](#) ()
Ends a mouse-on-UI query. Waits for the result. Should be called as far apart from IssueMouseOnUIQuery in order to maximize the chances that the query has finished at the time of this call and no waiting will be performed
- virtual bool [IsMouseOnView](#) ()
Checks if the mouse is currently on the logical view (a part of the view that has elements on it) or not (click-through). Uses the coordinates last set in IssueMouseOnUIQuery. Calling the method while a query is in-flight (between a call to IssueMouseOnUIQuery and FetchMouseOnUIQuery) results in a warning and the return result is undefined
- virtual void [SetClickThroughAlphaThreshold](#) (float threshold)
The alpha value of the pixels is used to determine if the mouse is on an element or on the background (click-through). All pixels below or equal to the alpha threshold (default = 0) are marked as not-belonging to the
- virtual float [GetClickThroughAlphaThreshold](#) ()
Get the currently set alpha threshold for click-through queries.
- virtual void [SetTargetFramerate](#) (int target)
Sets the target frame-rate for the
- virtual int [GetTargetFramerate](#) ()
Get the currently set target frame-rate for the
- virtual bool [IsOnDemand](#) ()
Tells if this is an on-demand view. Frames must be explicitly requested for on-demand views (available only in Full versions of '[Coherent::UI::View::RequestFrame](#)'
- virtual [ViewErrorType](#) [RequestFrame](#) ()
Requests a new frame for rendering. All triggered events before this call will be accounted for in the rendered view. Only one frame per-view could be requested simultaneously (available only in Full versions of
- virtual [ViewErrorType](#) [RequestFrame](#) (double timeSinceArbitraryMoment)
Requests a new frame for rendering. All triggered events before this call will be accounted for in the rendered view. Only one frame per-view could be requested simultaneously (available only in Full versions of
- virtual [ViewErrorType](#) [PeekFrameReady](#) ()
Tells if the last requested frame is ready or not. Does not block. This call must always be made between calls to RequestFrame and FetchSurface. (available only in Full versions of '[Coherent::UI::View::RequestFrame](#)' '[Coherent::UI::View::FetchSurface](#)'

- virtual [ViewErrorType FetchSurface](#) ()
Returns the requested surface. Works only for on-demand views. All buffered view should use the system's Fetch-Surfaces method. This call will block until the surface is ready. (available only in Full versions of
- virtual [ViewErrorType DrawSurface](#) ()
[EXPERIMENTAL - DO NOT USE]
- virtual bool [UsesSharedMemory](#) ()
Tells if this view uses shared memory for image transport.
- virtual bool [IsTransparent](#) ()
Tells if this view is transparent or not.
- virtual bool [SupportsClickThrough](#) ()
Tells if this view supports click-through queries or not.
- virtual void [Redraw](#) ()
Request a redraw of the current view.
- virtual void [DownloadUrl](#) (string path)
Initiates a download request on the specified path.
- virtual void [Load](#) (string path)
Loads a new path in the
- virtual void [Reload](#) (bool ignoreCache)
Reloads the last requested or navigated-to path.
- virtual string [GetCurentViewPath](#) ()
Get the last requested or navigated-to path.
- virtual string [GetLastRequestedPath](#) ()
Get the last requested path to load for the
- virtual string [GetLastLoadedPath](#) ()
Get the last successfully loaded path for the
- virtual string [GetLastFailedPath](#) ()
Get the last failed path for the
- virtual void [ExecuteScript](#) (string script)
Execute arbitrary JavaScript code.
- virtual void [TriggerEvent](#) (string eventName)
Triggers a UI event.
- virtual void [ReplyToJavaScriptMessage](#) (bool success, string userInput)
Sends a reply to a javascript message triggered for the view.
- virtual void [AuthCredentialsResponse](#) (string username, string password, bool success)
Sends credentials for a pending authentication request for the view.
- virtual void [SetScriptError](#) ([ScriptCallErrorType](#) error, string message)
Sets an error for the currently executing handler.
- virtual void [InterceptURLRequests](#) (bool intercept)
Controls intercepting URL requests. For each request
- virtual void [IMEActivate](#) (bool active)
Sets if the
- virtual bool [IMEIsActive](#) ()
Tells if IME events are currently active for this view.
- virtual bool [IMESetComposition](#) (string composition, uint cursorPos, uint targetStart, uint targetEnd)
Updates the internal state of the IME composition in the
- virtual bool [IMEConfirmComposition](#) (string composition)
Confirms the current IME composition.
- virtual bool [IMECancelComposition](#) ()
Cancels the current IME composition.

8.34.1 Detailed Description

Class that encapsulates a [UI](#)

8.34.2 Member Function Documentation

8.34.2.1 `virtual void Coherent.UI.View.AuthCredentialsResponse (string username, string password, bool success)` `[inline], [virtual]`

Sends credentials for a pending authentication request for the view.

Parameters

<i>username</i>	the username
<i>password</i>	the password
<i>success</i>	defines whether the response is valid, i.e. if the request should be answered or canceled

8.34.2.2 `BoundEventHandle Coherent.UI.View.BindCall (string name, System.Delegate handler)` `[inline]`

Expose C++ handler to be called from [UI](#).

Parameters

<i>name</i>	name for the handler in the UI
<i>handler</i>	handler to be executed

Returns

bound handle so the handler can be unbound later

8.34.2.3 `virtual void Coherent.UI.View.Destroy ()` `[inline], [virtual]`

Destroys this view. After a call to Destroy calling any other method except the destructor results in undefined behavior

8.34.2.4 `virtual void Coherent.UI.View.DownloadUrl (string path)` `[inline], [virtual]`

Initiates a download request on the specified path.

8.34.2.5 `virtual ViewErrorType Coherent.UI.View.DrawSurface ()` `[inline], [virtual]`

[EXPERIMENTAL - DO NOT USE]

8.34.2.6 `virtual void Coherent.UI.View.ExecuteScript (string script)` `[inline], [virtual]`

Execute arbitrary JavaScript code.

Parameters

<i>script</i>	code to be evaluated in the context of the main frame of the view
---------------	---

8.34.2.7 `virtual void Coherent.UI.View.FetchMouseOnUIQuery () [inline],[virtual]`

Ends a mouse-on-UI query. Waits for the result. Should be called as far apart from `IssueMouseOnUIQuery` in order to maximize the chances that the query has finished at the time of this call and no waiting will be performed

8.34.2.8 `virtual ViewErrorType Coherent.UI.View.FetchSurface () [inline],[virtual]`

Returns the requested surface. Works only for on-demand views. All buffered view should use the system's `FetchSurfaces` method. This call will block until the surface is ready. (available only in Full versions of

Returns

the outcome of the operation

8.34.2.9 `virtual float Coherent.UI.View.GetClickThroughAlphaThreshold () [inline],[virtual]`

Get the currently set alpha threshold for click-through queries.

Returns

the currently set alpha threshold

8.34.2.10 `virtual string Coherent.UI.View.GetCurentViewPath () [inline],[virtual]`

Get the last requested or navigated-to path.

Returns

the path as null-terminated string

8.34.2.11 `virtual int Coherent.UI.View.GetHeight () [inline],[virtual]`

Gets the height of the

Returns

the height of the [View](#)

8.34.2.12 `virtual string Coherent.UI.View.GetLastFailedPath () [inline],[virtual]`

Get the last failed path for the

Returns

the path as null-terminated string

8.34.2.13 `virtual string Coherent.UI.View.GetLastLoadedPath () [inline],[virtual]`

Get the last successfully loaded path for the

Returns

the path as null-terminated string

8.34.2.14 `virtual string Coherent.UI.View.GetLastRequestedPath () [inline],[virtual]`

Get the last requested path to load for the

Returns

the path as null-terminated string

8.34.2.15 `virtual int Coherent.UI.View.GetTargetFramerate () [inline],[virtual]`

Get the currently set target frame-rate for the

Returns

the current target frame-rate (available only in Full versions of [Coherent UI](#))

8.34.2.16 `virtual ViewType Coherent.UI.View.GetViewType () [inline],[virtual]`

Get the type of the view.

Returns

the type of the view

Reimplemented in [Coherent.UI.BrowserView](#).

8.34.2.17 `virtual int Coherent.UI.View.GetWidth () [inline],[virtual]`

Gets the width of the

Returns

the width of the [View](#)

8.34.2.18 `virtual void Coherent.UI.View.IMEActivate (bool active) [inline],[virtual]`

Sets if the

Parameters

<i>active</i>	whether to activate IME handling for this view
---------------	--

8.34.2.19 `virtual bool Coherent.UI.View.IMECancelComposition () [inline],[virtual]`

Cancels the current IME composition.

Returns

the outcome of the operation (will fail if IME is inactive for this view)

8.34.2.20 `virtual bool Coherent.UI.View.IMEConfirmComposition (string composition) [inline],[virtual]`

Confirms the current IME composition.

Parameters

<i>composition</i>	the string to confirm
--------------------	-----------------------

Returns

the outcome of the operation (will fail if IME is inactive for this view)

8.34.2.21 `virtual bool Coherent.UI.View.IMEIsActive () [inline],[virtual]`

Tells if IME events are currently active for this view.

Returns

if the view has IME active

8.34.2.22 `virtual bool Coherent.UI.View.IMESetComposition (string composition, uint cursorPos, uint targetStart, uint targetEnd) [inline],[virtual]`

Updates the internal state of the IME composition in the

Parameters

<i>composition</i>	the composition string so far
<i>the</i>	cursor position in the composition
<i>targetStart</i>	the index at the start of the selection
<i>targetEnd</i>	the index at the end of the selection

Returns

the outcome of the operation (will fail if IME is inactive for this view)

8.34.2.23 `virtual void Coherent.UI.View.InterceptURLRequests (bool intercept) [inline],[virtual]`

Controls intercepting URL requests. For each request

Parameters

<i>intercept</i>	whether to intercept all URL requests
------------------	---------------------------------------

8.34.2.24 `virtual bool Coherent.UI.View.IsMouseOnView () [inline],[virtual]`

Checks if the mouse is currently on the logical view (a part of the view that has elements on it) or not (click-through). Uses the coordinates last set in `IssueMouseOnUIQuery`. Calling the method while a query is in-flight (between a call to `IssueMouseOnUIQuery` and `FetchMouseOnUIQuery`) results in a warning and the return result is undefined

Returns

true if the mouse is on the view

8.34.2.25 `virtual bool Coherent.UI.View.IsOnDemand () [inline],[virtual]`

Tells if this is an on-demand view. Frames must be explicitly requested for on-demand views (available only in Full versions of '[Coherent::UI::View::RequestFrame](#)')

Returns

true if this is an on-demand view

8.34.2.26 `virtual void Coherent.UI.View.IssueMouseOnUIQuery (float normX, float normY) [inline],[virtual]`

Issues a query on the Calling IsMouseOnView while a query is in-flight is an error and will be logged - the result returned by IsMouseOnView in that case is undefined.

Put as much processing as possible between IssueMouseOnUIQuery and the corresponding FetchMouseOnUIQuery, this allows leveraging the cost of the query and to reduce it to ~0. The best way to do this is call IssueMouseOnUIQuery early in the frame, perform all game rendering and the call FetchMouseOnUIQuery followed by IsMouseOnView to update the needed data.

Parameters

<i>normX</i>	the x coordinate of the mouse in the normalized space of the view [0..1]
<i>normY</i>	the y coordinate of the mouse in the normalized space of the view [0..1]

8.34.2.27 `virtual bool Coherent.UI.View.IsTransparent () [inline],[virtual]`

Tells if this view is transparent or not.

Returns

true if the view is transparent

8.34.2.28 `virtual void Coherent.UI.View.KeyEvent (KeyEventData arg0) [inline],[virtual]`

Sends a key event to the [UI](#) renderer.

Parameters

<i>event</i>	the key event
--------------	---------------

8.34.2.29 `virtual void Coherent.UI.View.KillFocus () [inline],[virtual]`

Removes the focus from this view.

8.34.2.30 `virtual void Coherent.UI.View.Load (string path) [inline],[virtual]`

Loads a new path in the

Parameters

<i>path</i>	the path to load
-------------	------------------

8.34.2.31 `virtual void Coherent.UI.View.MouseActivate () [inline],[virtual]`

Sends a mouse event to the [UI](#) renderer.

8.34.2.32 `virtual void Coherent.UI.View.MouseEvent (MouseEventData arg0) [inline],[virtual]`

Sends a mouse event to the [UI](#) renderer.

Parameters

<i>event</i>	the mouse event
--------------	-----------------

8.34.2.33 `virtual ViewErrorType Coherent.UI.View.PeekFrameReady () [inline],[virtual]`

Tells if the last requested frame is ready or not. Does not block. This call must always be made between calls to RequestFrame and FetchSurface. (available only in Full versions of '[Coherent::UI::View::RequestFrame](#)' '[Coherent::UI::View::FetchSurface](#)'

Returns

VE_Success; VE_FrameNotReady; VE_FrameNotRequested; VE_InvalidCall

8.34.2.34 `virtual void Coherent.UI.View.Redraw () [inline],[virtual]`

Request a redraw of the current view.

8.34.2.35 `BoundEventHandle Coherent.UI.View.RegisterForEvent (string name, System.Delegate handler) [inline]`

Expose C++ handler to be called when a specific event occurs.

Parameters

<i>name</i>	name of the event
<i>handler</i>	handler to be executed

Returns

bound handle so the handler can be unregistered

8.34.2.36 `virtual void Coherent.UI.View.Reload (bool ignoreCache) [inline],[virtual]`

Reloads the last requested or navigated-to path.

Parameters

<i>ignoreCache</i>	whether to ignore the cache for the reload
--------------------	--

8.34.2.37 `virtual void Coherent.UI.View.ReplyToJavaScriptMessage (bool success, string userInput) [inline],[virtual]`

Sends a reply to a javascript message triggered for the view.

Parameters

<i>success</i>	defines whether the user replies positively to the message (i.e. clicks the OK button)
<i>userInput</i>	the user reply message (only used in prompt messages)

8.34.2.38 `virtual ViewErrorType Coherent.UI.View.RequestFrame () [inline],[virtual]`

Requests a new frame for rendering. All triggered events before this call will be accounted for in the rendered view. Only one frame per-view could be requested simultaneously (available only in Full versions of

Returns

the outcome of the operation

8.34.2.39 `virtual ViewErrorType Coherent.UI.View.RequestFrame (double timeSinceArbitraryMoment)` `[inline]`,
`[virtual]`

Requests a new frame for rendering. All triggered events before this call will be accounted for in the rendered view. Only one frame per-view could be requested simultaneously (available only in Full versions of

Returns

the outcome of the operation

8.34.2.40 `virtual void Coherent.UI.View.Resize (uint width, uint height)` `[inline]`,`[virtual]`

Send a resize event to the [UI](#) renderer. Resize will result in multiple calls to CreateBuffers and DestroyBuffers in the listener

Parameters

<i>width</i>	the new width of the View
<i>height</i>	the new height of the View

8.34.2.41 `virtual void Coherent.UI.View.SetClickThroughAlphaThreshold (float threshold)` `[inline]`,`[virtual]`

The alpha value of the pixels is used to determine if the mouse is on an element or on the background (click-through). All pixels below or equal to the alpha threshold (default = 0) are marked as not-belonging to the

Parameters

<i>threshold</i>	sets the new alpha threshold
------------------	------------------------------

8.34.2.42 `virtual void Coherent.UI.View.SetFocus ()` `[inline]`,`[virtual]`

Sets this view on focus.

8.34.2.43 `virtual void Coherent.UI.View.SetScriptError (ScriptCallErrorType error, string message)` `[inline]`,
`[virtual]`

Sets an error for the currently executing handler.

Parameters

<i>error</i>	the type of the error
<i>message</i>	the error message

8.34.2.44 `virtual void Coherent.UI.View.SetTargetFramerate (int target)` `[inline]`,`[virtual]`

Sets the target frame-rate for the

Parameters

<i>target</i>	the new target frame-rate
---------------	---------------------------

8.34.2.45 `virtual bool Coherent.UI.View.SupportsClickThrough () [inline],[virtual]`

Tells if this view supports click-through queries or not.

Returns

true if click-through is supported

8.34.2.46 `virtual void Coherent.UI.View.TouchEvent (TouchEventData events, uint count) [inline],[virtual]`

Sends a touch event to the [UI](#) renderer.

Parameters

<i>events</i>	array of touch events
<i>count</i>	the count of the passed touch events in the array

8.34.2.47 `virtual void Coherent.UI.View.TriggerEvent (string eventName) [inline],[virtual]`

Triggers a [UI](#) event.

8.34.2.48 `void Coherent.UI.View.UnbindCall (BoundEventHandle handle) [inline]`

Remove a bound C++ handler.

Parameters

<i>handle</i>	the handle of the handler to be unbound
---------------	---

8.34.2.49 `void Coherent.UI.View.UnbindObject (object target) [inline]`

Remove all handlers bound to a specific object.

Parameters

<i>object</i>	the object whose handlers will be removed
---------------	---

8.34.2.50 `void Coherent.UI.View.UnregisterFromEvent (BoundEventHandle handle) [inline]`

Remove a registered C++ handler.

Parameters

<i>handle</i>	the handle of the event handler to be unregistered
---------------	--

8.34.2.51 `virtual bool Coherent.UI.View.UsesSharedMemory () [inline],[virtual]`

Tells if this view uses shared memory for image transport.

Returns

true if the view uses shared memory, false if shared textures

8.35 Coherent.UI.ViewError Class Reference

Encapsulates a view-related error.

Inherits IDisposable.

Properties

- [ViewErrorType ErrorCode](#) [get, set]
Indicates an error code.
- string [Error](#) [get, set]
Error description.

8.35.1 Detailed Description

Encapsulates a view-related error.

8.35.2 Property Documentation

8.35.2.1 string [Coherent.UI.ViewError.Error](#) [get], [set]

Error description.

8.35.2.2 [ViewErrorType Coherent.UI.ViewError.ErrorCode](#) [get], [set]

Indicates an error code.

8.36 Coherent.UI.ViewInfo Class Reference

Encapsulates the options of a

Inherits IDisposable.

Properties

- int [Width](#) [get, set]
The Width of a
- int [Height](#) [get, set]
The Height of a
- bool [UsesSharedMemory](#) [get, set]
Flags if a
- bool [SupportClickThrough](#) [get, set]
Defines if the view should support click-through queries. Not supporting click-through increases performance slightly.
- float [ClickThroughAlphaThreshold](#) [get, set]
The alpha threshold for click-through queries.
- bool [IsTransparent](#) [get, set]

Defines if a view is transparent or not. A transparent view can be have transparent parts that will be correctly blended with the client's surfaces. Non-transparent views are always implicitly composited as if on a white background. Don't use transparent views unless you have transparent parts in the page because non-transparent view are slightly faster. Do not blend non-transparent views.

- `int TargetFrameRate` [get, set]

The frame-rate of the view will never exceed the target set here. It will also never exceed the rate at which the System Update is called. (available only in Full versions of

- `bool IsOnDemand` [get, set]

Defines if a view is an on-demand view. On-demand views require explicit frame requests. (available only in Full versions of

- `bool ControlTimeOnDemand` [get, set]

Defines if the client controls the time of on-demand views himself. If not

- `bool InProcessGPURendering` [get, set]

[EXPERIMENTAL - DO NOT USE] Defines if the view should be rendered in-process with a rendering context provided by the client

- `bool ForceSoftwareRendering` [get, set]

Forces the view to use software rendering. If the application is GPU-bound pure software Views might be a good choice. CSS 3D transforms, WebGL and accelerated Canvas don't work with software Views. Software Views are incompatible with the OnDemand option and work only with shared memory surfaces.

8.36.1 Detailed Description

Encapsulates the options of a

8.36.2 Property Documentation

8.36.2.1 `float Coherent.UI.ViewInfo.ClickThroughAlphaThreshold` [get], [set]

The alpha threshold for click-through queries.

8.36.2.2 `bool Coherent.UI.ViewInfo.ControlTimeOnDemand` [get], [set]

Defines if the client controls the time of on-demand views himself. If not

8.36.2.3 `bool Coherent.UI.ViewInfo.ForceSoftwareRendering` [get], [set]

Forces the view to use software rendering. If the application is GPU-bound pure software Views might be a good choice. CSS 3D transforms, WebGL and accelerated Canvas don't work with software Views. Software Views are incompatible with the OnDemand option and work only with shared memory surfaces.

8.36.2.4 `int Coherent.UI.ViewInfo.Height` [get], [set]

The Height of a

8.36.2.5 `bool Coherent.UI.ViewInfo.InProcessGPURendering` [get], [set]

[EXPERIMENTAL - DO NOT USE] Defines if the view should be rendered in-process with a rendering context provided by the client

8.36.2.6 `bool Coherent.UI.ViewInfo.IsOnDemand` [get], [set]

Defines if a view is an on-demand view. On-demand views require explicit frame requests. (available only in Full versions of

8.36.2.7 bool Coherent.UI.ViewInfo.IsTransparent [get], [set]

Defines if a view is transparent or not. A transparent view can have transparent parts that will be correctly blended with the client's surfaces. Non-transparent views are always implicitly composited as if on a white background. Don't use transparent views unless you have transparent parts in the page because non-transparent views are slightly faster. Do not blend non-transparent views.

8.36.2.8 bool Coherent.UI.ViewInfo.SupportClickThrough [get], [set]

Defines if the view should support click-through queries. Not supporting click-through increases performance slightly.

8.36.2.9 int Coherent.UI.ViewInfo.TargetFrameRate [get], [set]

The frame-rate of the view will never exceed the target set here. It will also never exceed the rate at which the System Update is called. (available only in Full versions of

8.36.2.10 bool Coherent.UI.ViewInfo.UsesSharedMemory [get], [set]

Flags if a


8.36.2.11 int Coherent.UI.ViewInfo.Width [get], [set]

The Width of a

8.37 Coherent.UI.ViewListener Class Reference

Interface that allows clients to listen to

Inheritance diagram for Coherent.UI.ViewListener:



Public Member Functions

- override void [Release](#) ()
Called when the listener is no longer needed by the [UI](#) system.
- override void [OnViewCreated](#) ([View](#) view)
Called when the requested
- override void [OnDraw](#) (CoherentHandle handle, bool usesSharedMemory, int width, int height)
Called when a new surface has been drawn and is ready to use by the client.
- override void [OnFinishLoad](#) (int frameId, string validatedPath, bool isMainFrame, int statusCode, [HTTP-Header\[\]](#) headers)
Called when a frame has been successfully loaded.
- override void [OnFailLoad](#) (int frameId, string validatedPath, bool isMainFrame, string error)
Called when a frame has been failed loading.
- override void [OnURLRequest](#) (string url, URLResponse response)

Called before an URL request is made. The default implementation allows all requests.

- override void [OnReadyForBindings](#) (int frameId, string path, bool isMainFrame)

Called when a frame is ready for bindings.

- override void [OnBindingsReleased](#) (int frameId, string path, bool isMainFrame)

Called when the bindings for frame are released.

- override void [OnStartLoading](#) ()

Called when a new path has started loading.

- override void [OnStopLoading](#) ()

Called when all load operations have completed.

- override void [OnNavigateTo](#) (string path)

Called when the view starts navigation to a new path.

- override void [OnError](#) ([ViewError](#) error)

Called when an error occurs for this specific

- override void [OnScriptMessage](#) ([ViewListenerBase.MessageLevel](#) level, string message, string sourceId, int line)

Called when a message is sent from a script running in this specific

- override void [OnCursorChanged](#) ([CursorTypes](#) cursor)

Called when the cursor has changed internally in the

- override void [OnCallback](#) (string eventName, [Binding.CallbackArguments](#) arguments)

Called by the [UI](#) when there is no registered handler for this event.

- override void [OnJavaScriptMessage](#) (string message, string defaultPrompt, string frameUrl, int messageType)

Called when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.

- override void [OnGetAuthCredentials](#) (bool isProxy, string host, uint port, string realm, string scheme)

Called when a view requires authentication credentials.

- override void [CreateSurface](#) (bool sharedMemory, uint width, uint height, [SurfaceResponse](#) response)

Called when the The format for DirectX9 must be D3DFMT_A8R8G8B8 The format for DirectX10 and DirectX11 must be B8G8R8A8_UNORM

- override void [DestroySurface](#) ([CoherentHandle](#) surface, bool usesSharedMemory)

Called when a surface is unneeded anymore and should be destroyed This function can be called from a thread different than the main [UI](#) system thread in order to support client applications with multi-threaded rendering.

- override void [OnCertificateError](#) (string url, [CertificateStatus](#) status, [Certificate](#) certificate, [CertificateError-Response](#) response)

Called when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call

- override void [OnRequestMediaStream](#) ([MediaStreamRequest](#) request)

Called when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.

- override void [OnTextInputTypeChanged](#) ([TextInputControlType](#) type, bool canComposeInline)

Called when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)

- override void [OnCaretRectChanged](#) (uint x, uint y, uint width, uint height)

Called when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.

- override void [OnIMEShouldCancelComposition](#) ()

Called when the user must cancel the IME composition due to an event in the

Events

- CoherentUI_OnViewCreated [ViewCreated](#)
Fired when the requested
- CoherentUI_OnDraw [Draw](#)
Fired when a new surface has been drawn and is ready to use by the client.
- CoherentUI_OnFinishLoad [FinishLoad](#)
Fired when a frame has been successfully loaded.
- CoherentUI_OnFailLoad [FailLoad](#)
Fired when a frame has been failed loading.
- CoherentUI_OnURLRequest [URLRequest](#)
Fired before an URL request is made. The default implementation allows all requests.
- CoherentUI_OnReadyForBindings [ReadyForBindings](#)
Fired when a frame is ready for bindings.
- CoherentUI_OnBindingsReleased [BindingsReleased](#)
Fired when the bindings for frame are released.
- CoherentUI_OnStartLoading [StartLoading](#)
Fired when a new path has started loading.
- CoherentUI_OnStopLoading [StopLoading](#)
Fired when all load operations have completed.
- CoherentUI_OnNavigateTo [NavigateTo](#)
Fired when the view starts navigation to a new path.
- CoherentUI_OnError [Error](#)
Fired when an error occurs for this specific
- CoherentUI_OnScriptMessage [ScriptMessage](#)
Fired when a message is sent from a script running in this specific
- CoherentUI_OnCursorChanged [CursorChanged](#)
Fired when the cursor has changed internally in the
- CoherentUI_OnCallback [Callback](#)
Fired by the [UI](#) when there is no registered handler for this event.
- CoherentUI_OnJavaScriptMessage [JavaScriptMessage](#)
Fired when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.
- CoherentUI_OnGetAuthCredentials [GetAuthCredentials](#)
Fired when a view requires authentication credentials.
- CoherentUI_OnCertificateError [CertificateError](#)
Fired when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call
- CoherentUI_OnRequestMediaStream [RequestMediaStream](#)
Fired when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.
- CoherentUI_OnTextInputTypeChanged [TextInputTypeChanged](#)
Fired when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)
- CoherentUI_OnCaretRectChanged [CaretRectChanged](#)
Fired when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.
- CoherentUI_OnIMEShouldCancelComposition [IMEShouldCancelComposition](#)
Fired when the user must cancel the IME composition due to an event in the

Additional Inherited Members

8.37.1 Detailed Description

Interface that allows clients to listen to

8.37.2 Member Function Documentation

8.37.2.1 `override void Coherent.UI.ViewListener.CreateSurface (bool sharedMemory, uint width, uint height, SurfaceResponse response) [inline],[virtual]`

Called when the The format for DirectX9 must be D3DFMT_A8R8G8B8 The format for DirectX10 and DirectX11 must be B8G8R8A8_UNORM

Parameters

<i>sharedMemory</i>	true if the surface should be created in shared memory (4 * width * height bytes); false if a shared texture must be created.
<i>width</i>	the width of the surface in pixels
<i>height</i>	the height of the surface in pixels
<i>response</i>	<ul style="list-style-type: none"> object to hold the response when the surface is created or fails it's creation - must be signaled

Returns

a handle to the created surface

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.2 `override void Coherent.UI.ViewListener.DestroySurface (CoherentHandle surface, bool usesSharedMemory) [inline],[virtual]`

Called when a surface is unneeded anymore and should be destroyed This function can be called from a thread different than the main UI system thread in order to support client applications with multi-threaded rendering.

Parameters

<i>surface</i>	handle to the surface
<i>usesSharedMemory</i>	determines whether the surface parameter is a handle to shared memory or shared texture

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.3 `override void Coherent.UI.ViewListener.OnBindingsReleased (int frameId, string path, bool isMainFrame) [inline],[virtual]`

Called when the bindings for frame are released.

Parameters

<i>frameId</i>	the id of the frame
----------------	---------------------

<i>path</i>	the path in the frame
<i>isMainFrame</i>	true if this is the main frame of the view

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.4 `override void Coherent.UI.ViewListener.OnCallback (string eventName, Binding.CallbackArguments arguments) [inline],[virtual]`

Called by the [UI](#) when there is no registered handler for this event.

Parameters

<i>eventName</i>	name of the event
<i>arguments</i>	arguments of the event invocation

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.5 `override void Coherent.UI.ViewListener.OnCaretRectChanged (uint x, uint y, uint width, uint height) [inline],[virtual]`

Called when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.

Parameters

<i>the</i>	x position of the selection caret
<i>the</i>	y position of the selection caret
<i>the</i>	width of the selection caret
<i>the</i>	height of the selection caret

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.6 `override void Coherent.UI.ViewListener.OnCertificateError (string url, CertificateStatus status, Certificate certificate, CertificateErrorResponse response) [inline],[virtual]`

Called when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call

Parameters

<i>url</i>	the url of the request
<i>status</i>	the error status of the certificate
<i>certificate</i>	the certificate details. This pointer will be valid only for this call
<i>response</i>	object to signal whether to continue loading the URL. This pointer will be valid only for this call

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.7 `override void Coherent.UI.ViewListener.OnCursorChanged (CursorTypes cursor) [inline],[virtual]`

Called when the cursor has changed internally in the

Parameters

<i>cursor</i>	the new cursor
---------------	----------------

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.8 `override void Coherent.UI.ViewListener.OnDraw (CoherentHandle handle, bool usesSharedMemory, int width, int height) [inline],[virtual]`

Called when a new surface has been drawn and is ready to use by the client.

Parameters

<i>handle</i>	a handle to one of the buffers created by CreateSurface. May be a shared memory buffer or a shared texture depending on the way the View was created. The handle is valid only during this call
<i>usesSharedMemory</i>	determines whether the handle parameter is a handle to shared memory or shared texture
<i>width</i>	the width of the surface
<i>height</i>	the height of the surface

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.9 override void Coherent.UI.ViewListener.OnError ([ViewError](#) *error*) [inline],[virtual]

Called when an error occurs for this specific

Parameters

<i>error</i>	error description
--------------	-------------------

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.10 override void Coherent.UI.ViewListener.OnFailLoad (int *frameId*, string *validatedPath*, bool *isMainFrame*, string *error*) [inline],[virtual]

Called when a frame has been failed loading.

Parameters

<i>frameId</i>	the id of the frame
<i>validatedPath</i>	the path in the frame
<i>isMainFrame</i>	true if this is the main frame of the View
<i>error</i>	error message for the failure

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.11 override void Coherent.UI.ViewListener.OnFinishLoad (int *frameId*, string *validatedPath*, bool *isMainFrame*, int *statusCode*, [HTTPHeader](#)[] *headers*) [inline],[virtual]

Called when a frame has been successfully loaded.

Parameters

<i>frameId</i>	the id of the loaded frame
<i>validatedPath</i>	the path loaded in the frame
<i>isMainFrame</i>	true if this is the main frame of the View
<i>statusCode</i>	the status code of the response
<i>headers</i>	an array of header fields
<i>headersCount</i>	the count of items in the headers array

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.12 override void Coherent.UI.ViewListener.OnGetAuthCredentials (bool *isProxy*, string *host*, uint *port*, string *realm*, string *scheme*) [inline],[virtual]

Called when a view requires authentication credentials.

Parameters

<i>isProxy</i>	whether the request came from a server or a proxy
<i>host</i>	the host which triggered the request
<i>port</i>	the port at which the request was triggered
<i>realm</i>	realm of the authentication challenge. Encoded in UTF-8
<i>scheme</i>	the authentication scheme used, e.g. "basic" or "digest". Encoded in ASCII

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.13 `override void Coherent.UI.ViewListener.OnIMEShouldCancelComposition () [inline],[virtual]`

Called when the user must cancel the IME composition due to an event in the

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.14 `override void Coherent.UI.ViewListener.OnJavaScriptMessage (string message, string defaultPrompt, string frameUrl, int messageType) [inline],[virtual]`

Called when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.

Parameters

<i>message</i>	the JavaScript message
<i>defaultPrompt</i>	the default value of the prompt text box, in case the message type is prompt
<i>frameUrl</i>	the URL which created the message
<i>messageType</i>	the type of the message (alert/confirm/prompt)

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.15 `override void Coherent.UI.ViewListener.OnNavigateTo (string path) [inline],[virtual]`

Called when the view starts navigation to a new path.

Parameters

<i>path</i>	URL that the view is navigating to
-------------	------------------------------------

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.16 `override void Coherent.UI.ViewListener.OnReadyForBindings (int frameId, string path, bool isMainFrame) [inline],[virtual]`

Called when a frame is ready for bindings.

Parameters

<i>frameId</i>	the id of the frame
<i>path</i>	the path in the frame
<i>isMainFrame</i>	true if this is the main frame of the view

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.17 `override void Coherent.UI.ViewListener.OnRequestMediaStream (MediaStreamRequest request) [inline],[virtual]`

Called when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.

Parameters

<i>request</i>	contains the available media streams for the request
----------------	--

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.18 `override void Coherent.UI.ViewListener.OnScriptMessage (ViewListenerBase.MessageLevel level, string message, string sourceId, int line) [inline],[virtual]`

Called when a message is sent from a script running in this specific

Parameters

<i>level</i>	message level
<i>message</i>	the text of the message
<i>sourceId</i>	id of the script (usually file name)
<i>line</i>	the number of the line in which the message was sent

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.19 `override void Coherent.UI.ViewListener.OnStartLoading () [inline],[virtual]`

Called when a new path has started loading.

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.20 `override void Coherent.UI.ViewListener.OnStopLoading () [inline],[virtual]`

Called when all load operations have completed.

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.21 `override void Coherent.UI.ViewListener.OnTextInputTypeChanged (TextInputType type, bool canComposeInline) [inline],[virtual]`

Called when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)

Parameters

<i>type</i>	the type of the currently focused text input control by the user
<i>canComposeInline</i>	if the IME composition could be performed in-line in the control

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.22 `override void Coherent.UI.ViewListener.OnURLRequest (string url, URLResponse response) [inline],[virtual]`

Called before an URL request is made. The default implementation allows all requests.

Parameters

<i>url</i>	the request URL
<i>response</i>	response whether to allow the request and may be redirect it. This pointer will be valid only for this call

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.23 `override void Coherent.UI.ViewListener.OnViewCreated (View view) [inline],[virtual]`

Called when the requested

Parameters

<i>view</i>	the instance of the view containing all manipulation methods
-------------	--

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.2.24 `override void Coherent.UI.ViewListener.Release () [inline],[virtual]`

Called when the listener is no longer needed by the [UI](#) system.

Reimplemented from [Coherent.UI.ViewListenerBase](#).

8.37.3 Event Documentation

8.37.3.1 `CoherentUI_OnBindingsReleased Coherent.UI.ViewListener.BindingsReleased`

Fired when the bindings for frame are released.

8.37.3.2 `CoherentUI_OnCallback Coherent.UI.ViewListener.Callback`

Fired by the [UI](#) when there is no registered handler for this event.

8.37.3.3 `CoherentUI_OnCaretRectChanged Coherent.UI.ViewListener.CaretRectChanged`

Fired when the caret changes during IME composition. You can use this method to correctly position a custom IME control & candidate list.

8.37.3.4 `CoherentUI_OnCertificateError Coherent.UI.ViewListener.CertificateError`

Fired when there is an error with the certificate of a particular URL. the certificate and response pointers are valid only for the duration of this call

8.37.3.5 `CoherentUI_OnCursorChanged Coherent.UI.ViewListener.CursorChanged`

Fired when the cursor has changed internally in the

8.37.3.6 `CoherentUI_OnDraw Coherent.UI.ViewListener.Draw`

Fired when a new surface has been drawn and is ready to use by the client.

8.37.3.7 `CoherentUI_OnError Coherent.UI.ViewListener.Error`

Fired when an error occurs for this specific

8.37.3.8 `CoherentUI_OnFailLoad Coherent.UI.ViewListener.FailLoad`

Fired when a frame has been failed loading.

8.37.3.9 `CoherentUI_OnFinishLoad Coherent.UI.ViewListener.FinishLoad`

Fired when a frame has been successfully loaded.

8.37.3.10 CoherentUI_OnGetAuthCredentials Coherent.UI.ViewListener.GetAuthCredentials

Fired when a view requires authentication credentials.

8.37.3.11 CoherentUI_OnIMEShouldCancelComposition Coherent.UI.ViewListener.IMEShouldCancelComposition

Fired when the user must cancel the IME composition due to an event in the

8.37.3.12 CoherentUI_OnJavaScriptMessage Coherent.UI.ViewListener.JavaScriptMessage

Fired when the view triggered a javascript message box, i.e. an alert, confirmation dialog or a prompt dialog.

8.37.3.13 CoherentUI_OnNavigateTo Coherent.UI.ViewListener.NavigateTo

Fired when the view starts navigation to a new path.

8.37.3.14 CoherentUI_OnReadyForBindings Coherent.UI.ViewListener.ReadyForBindings

Fired when a frame is ready for bindings.

8.37.3.15 CoherentUI_OnRequestMediaStream Coherent.UI.ViewListener.RequestMediaStream

Fired when the view requests access to a media stream. Media streams are the audio capture (microphone) and video capture (camera) devices on the system.

8.37.3.16 CoherentUI_OnScriptMessage Coherent.UI.ViewListener.ScriptMessage

Fired when a message is sent from a script running in this specific

8.37.3.17 CoherentUI_OnStartLoading Coherent.UI.ViewListener.StartLoading

Fired when a new path has started loading.

8.37.3.18 CoherentUI_OnStopLoading Coherent.UI.ViewListener.StopLoading

Fired when all load operations have completed.

8.37.3.19 CoherentUI_OnTextInputTypeChanged Coherent.UI.ViewListener.TextInputTypeChanged

Fired when the current text input control changes (i.e. the user click an edit-box). Use this method to decide when to allow for IME input. the method will be called ONLY if IME is activated on this [View](#). [View::IMEActivate](#)

8.37.3.20 CoherentUI_OnURLRequest Coherent.UI.ViewListener.URLRequest

Fired before an URL request is made. The default implementation allows all requests.


8.37.3.21 CoherentUI_OnViewCreated Coherent.UI.ViewListener.ViewCreated

Fired when the requested

8.38 Coherent.UI.ViewListenerBase Class Reference

Interface all view listeners inherit. For an easier to use interface inherit instead - [Coherent::UI::ViewListener](#)

Inheritance diagram for Coherent.UI.ViewListenerBase:



Public Types

- enum [MessageLevel](#)
Levels of script messages.

8.38.1 Detailed Description

Interface all view listeners inherit. For an easier to use interface inherit instead - [Coherent::UI::ViewListener](#)

8.38.2 Member Enumeration Documentation

8.38.2.1 enum Coherent.UI.ViewListenerBase.MessageLevel

Levels of script messages.

Index

- All
 - Coherent::UI::Binding, [39](#)
- AllowCookies
 - Coherent::UI::SystemSettingsBase, [74](#)
- Arguments
 - Coherent::UI::Binding::CallbackArguments, [56](#)
- Array
 - Coherent::UI::Binding, [40](#)
- Assert
 - Coherent::UI::ILogHandler, [65](#)
- AuthCredentialsResponse
 - Coherent::UI::View, [89](#)
- BindCall
 - Coherent::UI::View, [89](#)
- BindMethods
 - Coherent::UI::Binding::BoundObject, [41](#)
- BindingsReleased
 - Coherent::UI::BrowserViewListener, [53](#)
 - Coherent::UI::ViewListener, [109](#)
- Boolean
 - Coherent::UI::Binding, [39](#)
- Button
 - Coherent::UI::MouseEventData, [68](#)
- Byte
 - Coherent::UI::Binding, [40](#)
- CachePath
 - Coherent::UI::SystemSettings, [73](#)
- Callback
 - Coherent::UI::BrowserViewListener, [53](#)
 - Coherent::UI::ViewListener, [109](#)
- Cancel
 - Coherent::UI::Download, [60](#)
- CaretRectChanged
 - Coherent::UI::BrowserViewListener, [53](#)
 - Coherent::UI::ViewListener, [109](#)
- CertificateError
 - Coherent::UI::BrowserViewListener, [53](#)
 - Coherent::UI::ViewListener, [109](#)
- CertificateStatus
 - Coherent::UI, [37](#)
- ClickThroughAlphaThreshold
 - Coherent::UI::ViewInfo, [98](#)
- Coherent, [35](#)
- Coherent.UI, [35](#)
- Coherent.UI.Binding, [39](#)
- Coherent.UI.Binding.BoundObject, [41](#)
- Coherent.UI.Binding.CallbackArguments, [55](#)
- Coherent.UI.Binding.CoherentProperty, [58](#)
- Coherent.UI.Binding.CoherentType, [59](#)
- Coherent.UI.Binding.InvalidValueCastException, [65](#)
- Coherent.UI.Binding.UnsupportedPrimitiveTypeException, [77](#)
- Coherent.UI.Binding.Value, [78](#)
- Coherent.UI.Binding.ValueObject, [86](#)
- Coherent.UI.BoundEventHandle, [41](#)
- Coherent.UI.BrowserView, [42](#)
- Coherent.UI.BrowserViewListener, [43](#)
- Coherent.UI.BrowserViewListenerBase, [55](#)
- Coherent.UI.Certificate, [56](#)
- Coherent.UI.CertificatePrincipal, [57](#)
- Coherent.UI.Download, [59](#)
- Coherent.UI.EventListener, [62](#)
- Coherent.UI.EventModifiersState, [63](#)
- Coherent.UI.EventMouseModifiersState, [63](#)
- Coherent.UI.FileHandler, [63](#)
- Coherent.UI.HTTPHeader, [64](#)
- Coherent.UI.ILogHandler, [64](#)
- Coherent.UI.KeyEventData, [65](#)
- Coherent.UI.MediaStreamDevice, [66](#)
- Coherent.UI.MediaStreamRequest, [67](#)
- Coherent.UI.MouseEventData, [68](#)
- Coherent.UI.ResourceData, [69](#)
- Coherent.UI.ResourceResponse, [70](#)
- Coherent.UI.SurfaceResponse, [71](#)
- Coherent.UI.SystemError, [71](#)
- Coherent.UI.SystemSettings, [72](#)
- Coherent.UI.SystemSettingsBase, [73](#)
- Coherent.UI.TouchEventData, [75](#)
- Coherent.UI.UISystem, [76](#)
- Coherent.UI.View, [86](#)
- Coherent.UI.ViewError, [97](#)
- Coherent.UI.ViewInfo, [97](#)
- Coherent.UI.ViewListener, [99](#)
- Coherent.UI.ViewListenerBase, [111](#)
- Coherent::UI
 - DET_DownloadOperationFailed, [37](#)
 - DET_Success, [37](#)
 - SCE_ArgumentType, [38](#)
 - SCE_NoResult, [38](#)
 - SCE_NoSuchMethod, [38](#)
 - SCE_Success, [38](#)
 - SE_InternalError, [38](#)
 - SE_InvalidKey, [38](#)
 - SE_MissingComponent, [38](#)
 - SE_Success, [38](#)
 - VE_AbnormalTermination, [38](#)
 - VE_ChildCompositionFailed, [38](#)

- VE_ClickThroughFailed, [38](#)
- VE_FailedCreation, [38](#)
- VE_FailedRenderingCreation, [38](#)
- VE_FrameAlreadyInFlight, [38](#)
- VE_FrameNotReady, [38](#)
- VE_FrameNotRequested, [38](#)
- VE_InvalidCall, [38](#)
- VE_InvalidPath, [38](#)
- VE_Success, [38](#)
- Coherent::UI::Binding
 - All, [39](#)
 - Array, [40](#)
 - Boolean, [39](#)
 - Byte, [40](#)
 - Explicit, [39](#)
 - Instance, [39](#)
 - Integer, [40](#)
 - Null, [39](#)
 - Number, [40](#)
 - Object, [40](#)
 - SByte, [40](#)
 - Static, [39](#)
 - String, [40](#)
 - UInteger, [40](#)
- Coherent::UI
 - CertificateStatus, [37](#)
 - CursorTypes, [37](#)
 - Direct3DInterfaceType, [37](#)
 - DownloadErrorType, [37](#)
 - JavaScriptMessageType, [37](#)
 - MediaStreamType, [37](#)
 - RenderingDeviceType, [37](#)
 - ScriptCallErrorType, [38](#)
 - SystemErrorType, [38](#)
 - TextInputControlType, [38](#)
 - ViewErrorType, [38](#)
 - ViewType, [38](#)
- Coherent::UI::Binding
 - PropertyBindingFlags, [39](#)
 - ValueType, [39](#)
- Coherent::UI::Binding::BoundObject
 - BindMethods, [41](#)
- Coherent::UI::Binding::CallbackArguments
 - Arguments, [56](#)
- Coherent::UI::Binding::CoherentProperty
 - CoherentProperty, [59](#)
- Coherent::UI::Binding::Value
 - Equals, [82](#)
 - GetHashCode, [82](#)
 - operator bool, [82](#)
 - operator byte, [82](#)
 - operator Dictionary< string, Value >, [83](#)
 - operator double, [83](#)
 - operator float, [83](#)
 - operator int, [83](#)
 - operator sbyte, [83](#)
 - operator string, [84](#)
 - operator uint, [84](#)
 - operator ==, [84](#)
 - Type, [86](#)
 - Value, [79](#), [80](#), [82](#)
- Coherent::UI::BrowserView
 - GetHistory, [42](#)
 - GetViewType, [42](#)
 - GoBack, [42](#)
 - GoForward, [42](#)
- Coherent::UI::BrowserViewListener
 - BindingsReleased, [53](#)
 - Callback, [53](#)
 - CaretRectChanged, [53](#)
 - CertificateError, [53](#)
 - CreateSurface, [45](#)
 - CursorChanged, [53](#)
 - DestroySurface, [45](#)
 - Draw, [54](#)
 - Error, [54](#)
 - FailLoad, [54](#)
 - FinishLoad, [54](#)
 - GetAuthCredentials, [54](#)
 - IMEShouldCancelComposition, [54](#)
 - JavaScriptMessage, [54](#)
 - NavigateTo, [54](#)
 - OnBindingsReleased, [47](#)
 - OnCallback, [47](#)
 - OnCaretRectChanged, [47](#)
 - OnCertificateError, [47](#)
 - OnCursorChanged, [48](#)
 - OnDraw, [48](#)
 - OnError, [48](#)
 - OnFailLoad, [48](#)
 - OnFinishLoad, [49](#)
 - OnGetAuthCredentials, [49](#)
 - OnIMEShouldCancelComposition, [49](#)
 - OnJavaScriptMessage, [49](#)
 - OnNavigateTo, [49](#)
 - OnReadyForBindings, [51](#)
 - OnRequestMediaStream, [51](#)
 - OnScriptMessage, [51](#)
 - OnStartLoading, [51](#)
 - OnStopLoading, [51](#)
 - OnTextInputTypeChanged, [51](#)
 - OnURLRequest, [53](#)
 - OnViewCreated, [53](#)
 - ReadyForBindings, [54](#)
 - Release, [53](#)
 - RequestMediaStream, [54](#)
 - ScriptMessage, [54](#)
 - StartLoading, [54](#)
 - StopLoading, [55](#)
 - TextInputTypeChanged, [55](#)
 - URLRequest, [55](#)
 - ViewCreated, [55](#)
- Coherent::UI::Certificate
 - Fingerprint, [56](#)
 - FingerprintCA, [56](#)
 - Issuer, [57](#)

- SerialNumber, [57](#)
- Subject, [57](#)
- ValidEnd, [57](#)
- ValidStart, [57](#)
- Coherent::UI::CertificatePrincipal
 - CommonName, [58](#)
 - CountryName, [58](#)
 - DomainComponents, [58](#)
 - LocalityName, [58](#)
 - OrganizationNames, [58](#)
 - OrganizationUnitNames, [58](#)
 - StateOrProvinceName, [58](#)
 - StreetAddresses, [58](#)
- Coherent::UI::Download
 - Cancel, [60](#)
 - Destroy, [60](#)
 - GetDownloadedBytesSoFar, [60](#)
 - GetFilename, [60](#)
 - GetId, [60](#)
 - GetReferrer, [61](#)
 - GetTotalBytes, [61](#)
 - GetURL, [61](#)
 - HasFailed, [61](#)
 - IsCancelled, [61](#)
 - IsComplete, [61](#)
- Coherent::UI::EventListener
 - OnDownloadComplete, [62](#)
 - OnDownloadFailed, [62](#)
 - OnDownloadStarted, [62](#)
 - OnError, [62](#)
 - SystemReady, [62](#)
- Coherent::UI::FileHandler
 - ReadFile, [63](#)
 - WriteFile, [64](#)
- Coherent::UI::HTTPHeader
 - Content, [64](#)
 - Field, [64](#)
- Coherent::UI::ILogHandler
 - Assert, [65](#)
 - WriteLog, [65](#)
- Coherent::UI::KeyEventData
 - IsAutoRepeat, [66](#)
 - IsNumPad, [66](#)
 - KeyCode, [66](#)
 - Modifiers, [66](#)
 - Type, [66](#)
- Coherent::UI::MediaStreamDevice
 - Deviceld, [67](#)
 - Name, [67](#)
 - Type, [67](#)
- Coherent::UI::MediaStreamRequest
 - Devices, [68](#)
 - Respond, [67](#)
- Coherent::UI::MouseEventData
 - Button, [68](#)
 - Modifiers, [68](#)
 - MouseModifiers, [68](#)
 - Type, [68](#)
- WheelX, [69](#)
- WheelY, [69](#)
- X, [69](#)
- Y, [69](#)
- Coherent::UI::ResourceData
 - GetBuffer, [69](#)
 - GetSize, [70](#)
 - SignalFailure, [70](#)
 - SignalSuccess, [70](#)
- Coherent::UI::ResourceResponse
 - GetBuffer, [70](#)
 - SignalFailure, [71](#)
 - SignalSuccess, [71](#)
- Coherent::UI::SurfaceResponse
 - Signal, [71](#)
- Coherent::UI::SystemError
 - Error, [72](#)
 - ErrorCode, [72](#)
- Coherent::UI::SystemSettings
 - CachePath, [73](#)
 - CookiesResource, [73](#)
 - D3DObject, [73](#)
 - FocusWindow, [73](#)
 - HTML5LocalStoragePath, [73](#)
 - HostDirectory, [73](#)
 - MinidumpFolder, [73](#)
- Coherent::UI::SystemSettingsBase
 - AllowCookies, [74](#)
 - D3DInterfaceType, [74](#)
 - DebuggerPort, [74](#)
 - DisableWebSecurity, [74](#)
 - EnableProxy, [74](#)
 - EnableSupportForProprietaryCodecs, [75](#)
 - ForceDisablePluginFullscreen, [75](#)
 - WriteMinidumps, [75](#)
- Coherent::UI::TouchEventData
 - HasRadiusInformation, [75](#)
 - Id, [75](#)
 - RadiusX, [76](#)
 - RadiusY, [76](#)
 - Type, [76](#)
 - X, [76](#)
 - Y, [76](#)
- Coherent::UI::UISystem
 - CreateView, [77](#)
 - FetchSurfaces, [77](#)
 - Uninitialize, [77](#)
 - Update, [77](#)
- Coherent::UI::View
 - AuthCredentialsResponse, [89](#)
 - BindCall, [89](#)
 - Destroy, [89](#)
 - DownloadUrl, [89](#)
 - DrawSurface, [89](#)
 - ExecuteScript, [89](#)
 - FetchMouseOnUIQuery, [89](#)
 - FetchSurface, [90](#)
 - GetClickThroughAlphaThreshold, [90](#)

- GetCurentViewPath, [90](#)
- GetHeight, [90](#)
- GetLastFailedPath, [90](#)
- GetLastLoadedPath, [90](#)
- GetLastRequestedPath, [90](#)
- GetTargetFramerate, [91](#)
- GetViewType, [91](#)
- GetWidth, [91](#)
- IMEActivate, [91](#)
- IMECancelComposition, [91](#)
- IMEConfirmComposition, [91](#)
- IMEIsActive, [92](#)
- IMESetComposition, [92](#)
- InterceptURLRequests, [92](#)
- IsMouseOnView, [92](#)
- IsOnDemand, [92](#)
- IsTransparent, [93](#)
- IssueMouseOnUIQuery, [93](#)
- KeyEvent, [93](#)
- KillFocus, [93](#)
- Load, [93](#)
- MouseActivate, [93](#)
- MouseEvent, [93](#)
- PeekFrameReady, [94](#)
- Redraw, [94](#)
- RegisterForEvent, [94](#)
- Reload, [94](#)
- ReplyToJavaScriptMessage, [94](#)
- RequestFrame, [94](#), [95](#)
- Resize, [95](#)
- SetClickThroughAlphaThreshold, [95](#)
- SetFocus, [95](#)
- SetScriptError, [95](#)
- SetTargetFramerate, [95](#)
- SupportsClickThrough, [96](#)
- TouchEvent, [96](#)
- TriggerEvent, [96](#)
- UnbindCall, [96](#)
- UnbindObject, [96](#)
- UnregisterFromEvent, [96](#)
- UsesSharedMemory, [96](#)
- Coherent::UI::ViewError
 - Error, [97](#)
 - ErrorCode, [97](#)
- Coherent::UI::ViewInfo
 - ClickThroughAlphaThreshold, [98](#)
 - ControlTimeOnDemand, [98](#)
 - ForceSoftwareRendering, [98](#)
 - Height, [98](#)
 - InProcessGPURendering, [98](#)
 - IsOnDemand, [98](#)
 - IsTransparent, [98](#)
 - SupportClickThrough, [99](#)
 - TargetFrameRate, [99](#)
 - UsesSharedMemory, [99](#)
 - Width, [99](#)
- Coherent::UI::ViewListener
 - BindingsReleased, [109](#)
- Callback, [109](#)
- CaretRectChanged, [109](#)
- CertificateError, [109](#)
- CreateSurface, [102](#)
- CursorChanged, [109](#)
- DestroySurface, [102](#)
- Draw, [109](#)
- Error, [109](#)
- FailLoad, [109](#)
- FinishLoad, [109](#)
- GetAuthCredentials, [109](#)
- IMEShouldCancelComposition, [110](#)
- JavaScriptMessage, [110](#)
- NavigateTo, [110](#)
- OnBindingsReleased, [102](#)
- OnCallback, [103](#)
- OnCaretRectChanged, [103](#)
- OnCertificateError, [103](#)
- OnCursorChanged, [103](#)
- OnDraw, [103](#)
- OnError, [105](#)
- OnFailLoad, [105](#)
- OnFinishLoad, [105](#)
- OnGetAuthCredentials, [105](#)
- OnIMEShouldCancelComposition, [106](#)
- OnJavaScriptMessage, [106](#)
- OnNavigateTo, [106](#)
- OnReadyForBindings, [106](#)
- OnRequestMediaStream, [106](#)
- OnScriptMessage, [107](#)
- OnStartLoading, [107](#)
- OnStopLoading, [107](#)
- OnTextInputTypeChanged, [107](#)
- OnURLRequest, [107](#)
- OnViewCreated, [107](#)
- ReadyForBindings, [110](#)
- Release, [109](#)
- RequestMediaStream, [110](#)
- ScriptMessage, [110](#)
- StartLoading, [110](#)
- StopLoading, [110](#)
- TextInputTypeChanged, [110](#)
- URLRequest, [110](#)
- ViewCreated, [110](#)
- Coherent::UI::ViewListenerBase
 - MessageLevel, [111](#)
- CoherentProperty
 - Coherent::UI::Binding::CoherentProperty, [59](#)
- CommonName
 - Coherent::UI::CertificatePrincipal, [58](#)
- Content
 - Coherent::UI::HTTPHeader, [64](#)
- ControlTimeOnDemand
 - Coherent::UI::ViewInfo, [98](#)
- CookiesResource
 - Coherent::UI::SystemSettings, [73](#)
- CountryName
 - Coherent::UI::CertificatePrincipal, [58](#)

- CreateSurface
 - Coherent::UI::BrowserViewListener, [45](#)
 - Coherent::UI::ViewListener, [102](#)
- CreateView
 - Coherent::UI::UISystem, [77](#)
- CursorChanged
 - Coherent::UI::BrowserViewListener, [53](#)
 - Coherent::UI::ViewListener, [109](#)
- CursorTypes
 - Coherent::UI, [37](#)
- D3DInterfaceType
 - Coherent::UI::SystemSettingsBase, [74](#)
- D3DObject
 - Coherent::UI::SystemSettings, [73](#)
- DET_DownloadOperationFailed
 - Coherent::UI, [37](#)
- DET_Success
 - Coherent::UI, [37](#)
- DebuggerPort
 - Coherent::UI::SystemSettingsBase, [74](#)
- Destroy
 - Coherent::UI::Download, [60](#)
 - Coherent::UI::View, [89](#)
- DestroySurface
 - Coherent::UI::BrowserViewListener, [45](#)
 - Coherent::UI::ViewListener, [102](#)
- DeviceId
 - Coherent::UI::MediaStreamDevice, [67](#)
- Devices
 - Coherent::UI::MediaStreamRequest, [68](#)
- Direct3DInterfaceType
 - Coherent::UI, [37](#)
- DisableWebSecurity
 - Coherent::UI::SystemSettingsBase, [74](#)
- DomainComponents
 - Coherent::UI::CertificatePrincipal, [58](#)
- DownloadErrorType
 - Coherent::UI, [37](#)
- DownloadUrl
 - Coherent::UI::View, [89](#)
- Draw
 - Coherent::UI::BrowserViewListener, [54](#)
 - Coherent::UI::ViewListener, [109](#)
- DrawSurface
 - Coherent::UI::View, [89](#)
- EnableProxy
 - Coherent::UI::SystemSettingsBase, [74](#)
- EnableSupportForProprietaryCodecs
 - Coherent::UI::SystemSettingsBase, [75](#)
- Equals
 - Coherent::UI::Binding::Value, [82](#)
- Error
 - Coherent::UI::BrowserViewListener, [54](#)
 - Coherent::UI::SystemError, [72](#)
 - Coherent::UI::ViewError, [97](#)
 - Coherent::UI::ViewListener, [109](#)
- ErrorCode
 - Coherent::UI::SystemError, [72](#)
 - Coherent::UI::ViewError, [97](#)
- ExecuteScript
 - Coherent::UI::View, [89](#)
- Explicit
 - Coherent::UI::Binding, [39](#)
- FailLoad
 - Coherent::UI::BrowserViewListener, [54](#)
 - Coherent::UI::ViewListener, [109](#)
- FetchMouseOnUIQuery
 - Coherent::UI::View, [89](#)
- FetchSurface
 - Coherent::UI::View, [90](#)
- FetchSurfaces
 - Coherent::UI::UISystem, [77](#)
- Field
 - Coherent::UI::HTTPHeader, [64](#)
- Fingerprint
 - Coherent::UI::Certificate, [56](#)
- FingerprintCA
 - Coherent::UI::Certificate, [56](#)
- FinishLoad
 - Coherent::UI::BrowserViewListener, [54](#)
 - Coherent::UI::ViewListener, [109](#)
- FocusWindow
 - Coherent::UI::SystemSettings, [73](#)
- ForceDisablePluginFullscreen
 - Coherent::UI::SystemSettingsBase, [75](#)
- ForceSoftwareRendering
 - Coherent::UI::ViewInfo, [98](#)
- GetAuthCredentials
 - Coherent::UI::BrowserViewListener, [54](#)
 - Coherent::UI::ViewListener, [109](#)
- GetBuffer
 - Coherent::UI::ResourceData, [69](#)
 - Coherent::UI::ResourceResponse, [70](#)
- GetClickThroughAlphaThreshold
 - Coherent::UI::View, [90](#)
- GetCurrentViewPath
 - Coherent::UI::View, [90](#)
- GetDownloadedBytesSoFar
 - Coherent::UI::Download, [60](#)
- GetFilename
 - Coherent::UI::Download, [60](#)
- GetHashCode
 - Coherent::UI::Binding::Value, [82](#)
- GetHeight
 - Coherent::UI::View, [90](#)
- GetHistory
 - Coherent::UI::BrowserView, [42](#)
- GetId
 - Coherent::UI::Download, [60](#)
- GetLastFailedPath
 - Coherent::UI::View, [90](#)
- GetLastLoadedPath
 - Coherent::UI::View, [90](#)
- GetLastRequestedPath

- Coherent::UI::View, 90
- GetReferrer
 - Coherent::UI::Download, 61
- GetSize
 - Coherent::UI::ResourceData, 70
- GetTargetFramerate
 - Coherent::UI::View, 91
- GetTotalBytes
 - Coherent::UI::Download, 61
- GetURL
 - Coherent::UI::Download, 61
- GetViewType
 - Coherent::UI::BrowserView, 42
 - Coherent::UI::View, 91
- GetWidth
 - Coherent::UI::View, 91
- GoBack
 - Coherent::UI::BrowserView, 42
- GoForward
 - Coherent::UI::BrowserView, 42
- HTML5LocalStoragePath
 - Coherent::UI::SystemSettings, 73
- HasFailed
 - Coherent::UI::Download, 61
- HasRadiusInformation
 - Coherent::UI::TouchEventData, 75
- Height
 - Coherent::UI::ViewInfo, 98
- HostDirectory
 - Coherent::UI::SystemSettings, 73
- IMEActivate
 - Coherent::UI::View, 91
- IMECancelComposition
 - Coherent::UI::View, 91
- IMEConfirmComposition
 - Coherent::UI::View, 91
- IMEIsActive
 - Coherent::UI::View, 92
- IMESetComposition
 - Coherent::UI::View, 92
- IMEShouldCancelComposition
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- Id
 - Coherent::UI::TouchEventData, 75
- InProcessGPURendering
 - Coherent::UI::ViewInfo, 98
- Instance
 - Coherent::UI::Binding, 39
- Integer
 - Coherent::UI::Binding, 40
- InterceptURLRequests
 - Coherent::UI::View, 92
- IsAutoRepeat
 - Coherent::UI::KeyEventData, 66
- IsCancelled
 - Coherent::UI::Download, 61
- IsComplete
 - Coherent::UI::Download, 61
- IsMouseOnView
 - Coherent::UI::View, 92
- IsNumPad
 - Coherent::UI::KeyEventData, 66
- IsOnDemand
 - Coherent::UI::View, 92
 - Coherent::UI::ViewInfo, 98
- IsTransparent
 - Coherent::UI::View, 93
 - Coherent::UI::ViewInfo, 98
- IssueMouseOnUIQuery
 - Coherent::UI::View, 93
- Issuer
 - Coherent::UI::Certificate, 57
- JavaScriptMessage
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- JavaScriptMessageType
 - Coherent::UI, 37
- KeyCode
 - Coherent::UI::KeyEventData, 66
- KeyEvent
 - Coherent::UI::View, 93
- KillFocus
 - Coherent::UI::View, 93
- Load
 - Coherent::UI::View, 93
- LocalityName
 - Coherent::UI::CertificatePrincipal, 58
- MediaStreamType
 - Coherent::UI, 37
- MessageLevel
 - Coherent::UI::ViewListenerBase, 111
- MinidumpFolder
 - Coherent::UI::SystemSettings, 73
- Modifiers
 - Coherent::UI::KeyEventData, 66
 - Coherent::UI::MouseEventData, 68
- MouseActivate
 - Coherent::UI::View, 93
- MouseEvent
 - Coherent::UI::View, 93
- MouseModifiers
 - Coherent::UI::MouseEventData, 68
- Name
 - Coherent::UI::MediaStreamDevice, 67
- NavigateTo
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- Null
 - Coherent::UI::Binding, 39
- Number

- Coherent::UI::Binding, 40
- Object
 - Coherent::UI::Binding, 40
- OnBindingsReleased
 - Coherent::UI::BrowserViewListener, 47
 - Coherent::UI::ViewListener, 102
- OnCallback
 - Coherent::UI::BrowserViewListener, 47
 - Coherent::UI::ViewListener, 103
- OnCaretRectChanged
 - Coherent::UI::BrowserViewListener, 47
 - Coherent::UI::ViewListener, 103
- OnCertificateError
 - Coherent::UI::BrowserViewListener, 47
 - Coherent::UI::ViewListener, 103
- OnCursorChanged
 - Coherent::UI::BrowserViewListener, 48
 - Coherent::UI::ViewListener, 103
- OnDownloadComplete
 - Coherent::UI::EventListener, 62
- OnDownloadFailed
 - Coherent::UI::EventListener, 62
- OnDownloadStarted
 - Coherent::UI::EventListener, 62
- OnDraw
 - Coherent::UI::BrowserViewListener, 48
 - Coherent::UI::ViewListener, 103
- OnError
 - Coherent::UI::BrowserViewListener, 48
 - Coherent::UI::EventListener, 62
 - Coherent::UI::ViewListener, 105
- OnFailLoad
 - Coherent::UI::BrowserViewListener, 48
 - Coherent::UI::ViewListener, 105
- OnFinishLoad
 - Coherent::UI::BrowserViewListener, 49
 - Coherent::UI::ViewListener, 105
- OnGetAuthCredentials
 - Coherent::UI::BrowserViewListener, 49
 - Coherent::UI::ViewListener, 105
- OnIMEShouldCancelComposition
 - Coherent::UI::BrowserViewListener, 49
 - Coherent::UI::ViewListener, 106
- OnJavaScriptMessage
 - Coherent::UI::BrowserViewListener, 49
 - Coherent::UI::ViewListener, 106
- OnNavigateTo
 - Coherent::UI::BrowserViewListener, 49
 - Coherent::UI::ViewListener, 106
- OnReadyForBindings
 - Coherent::UI::BrowserViewListener, 51
 - Coherent::UI::ViewListener, 106
- OnRequestMediaStream
 - Coherent::UI::BrowserViewListener, 51
 - Coherent::UI::ViewListener, 106
- OnScriptMessage
 - Coherent::UI::BrowserViewListener, 51
 - Coherent::UI::ViewListener, 107
- OnStartLoading
 - Coherent::UI::BrowserViewListener, 51
 - Coherent::UI::ViewListener, 107
- OnStopLoading
 - Coherent::UI::BrowserViewListener, 51
 - Coherent::UI::ViewListener, 107
- OnTextInputTypeChanged
 - Coherent::UI::BrowserViewListener, 51
 - Coherent::UI::ViewListener, 107
- OnURLRequest
 - Coherent::UI::BrowserViewListener, 53
 - Coherent::UI::ViewListener, 107
- OnViewCreated
 - Coherent::UI::BrowserViewListener, 53
 - Coherent::UI::ViewListener, 107
- operator bool
 - Coherent::UI::Binding::Value, 82
- operator byte
 - Coherent::UI::Binding::Value, 82
- operator Dictionary< string, Value >
 - Coherent::UI::Binding::Value, 83
- operator double
 - Coherent::UI::Binding::Value, 83
- operator float
 - Coherent::UI::Binding::Value, 83
- operator int
 - Coherent::UI::Binding::Value, 83
- operator sbyte
 - Coherent::UI::Binding::Value, 83
- operator string
 - Coherent::UI::Binding::Value, 84
- operator uint
 - Coherent::UI::Binding::Value, 84
- operator==
 - Coherent::UI::Binding::Value, 84
- OrganizationNames
 - Coherent::UI::CertificatePrincipal, 58
- OrganizationUnitNames
 - Coherent::UI::CertificatePrincipal, 58
- PeekFrameReady
 - Coherent::UI::View, 94
- PropertyBindingFlags
 - Coherent::UI::Binding, 39
- RadiusX
 - Coherent::UI::TouchEventData, 76
- RadiusY
 - Coherent::UI::TouchEventData, 76
- ReadFile
 - Coherent::UI::FileHandler, 63
- ReadyForBindings
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- Redraw
 - Coherent::UI::View, 94
- RegisterForEvent
 - Coherent::UI::View, 94
- Release

- Coherent::UI::BrowserViewListener, 53
- Coherent::UI::ViewListener, 109
- Reload
 - Coherent::UI::View, 94
- RenderingDeviceType
 - Coherent::UI, 37
- ReplyToJavaScriptMessage
 - Coherent::UI::View, 94
- RequestFrame
 - Coherent::UI::View, 94, 95
- RequestMediaStream
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- Resize
 - Coherent::UI::View, 95
- Respond
 - Coherent::UI::MediaStreamRequest, 67
- SByte
 - Coherent::UI::Binding, 40
- SCE_ArgumentType
 - Coherent::UI, 38
- SCE_NoResult
 - Coherent::UI, 38
- SCE_NoSuchMethod
 - Coherent::UI, 38
- SCE_Success
 - Coherent::UI, 38
- SE_InternalError
 - Coherent::UI, 38
- SE_InvalidKey
 - Coherent::UI, 38
- SE_MissingComponent
 - Coherent::UI, 38
- SE_Success
 - Coherent::UI, 38
- ScriptCallErrorType
 - Coherent::UI, 38
- ScriptMessage
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- SerialNumber
 - Coherent::UI::Certificate, 57
- SetClickThroughAlphaThreshold
 - Coherent::UI::View, 95
- SetFocus
 - Coherent::UI::View, 95
- SetScriptError
 - Coherent::UI::View, 95
- SetTargetFramerate
 - Coherent::UI::View, 95
- Signal
 - Coherent::UI::SurfaceResponse, 71
- SignalFailure
 - Coherent::UI::ResourceData, 70
 - Coherent::UI::ResourceResponse, 71
- SignalSuccess
 - Coherent::UI::ResourceData, 70
 - Coherent::UI::ResourceResponse, 71
- StartLoading
 - Coherent::UI::BrowserViewListener, 54
 - Coherent::UI::ViewListener, 110
- StateOrProvinceName
 - Coherent::UI::CertificatePrincipal, 58
- Static
 - Coherent::UI::Binding, 39
- StopLoading
 - Coherent::UI::BrowserViewListener, 55
 - Coherent::UI::ViewListener, 110
- StreetAddresses
 - Coherent::UI::CertificatePrincipal, 58
- String
 - Coherent::UI::Binding, 40
- Subject
 - Coherent::UI::Certificate, 57
- SupportClickThrough
 - Coherent::UI::ViewInfo, 99
- SupportsClickThrough
 - Coherent::UI::View, 96
- SystemErrorType
 - Coherent::UI, 38
- SystemReady
 - Coherent::UI::EventListener, 62
- TargetFrameRate
 - Coherent::UI::ViewInfo, 99
- TextInputControlType
 - Coherent::UI, 38
- TextInputTypeChanged
 - Coherent::UI::BrowserViewListener, 55
 - Coherent::UI::ViewListener, 110
- TouchEvent
 - Coherent::UI::View, 96
- TriggerEvent
 - Coherent::UI::View, 96
- Type
 - Coherent::UI::Binding::Value, 86
 - Coherent::UI::KeyEventData, 66
 - Coherent::UI::MediaStreamDevice, 67
 - Coherent::UI::MouseEventData, 68
 - Coherent::UI::TouchEventData, 76
- UInteger
 - Coherent::UI::Binding, 40
- URLRequest
 - Coherent::UI::BrowserViewListener, 55
 - Coherent::UI::ViewListener, 110
- UnbindCall
 - Coherent::UI::View, 96
- UnbindObject
 - Coherent::UI::View, 96
- Uninitialize
 - Coherent::UI::UISystem, 77
- UnregisterFromEvent
 - Coherent::UI::View, 96
- Update
 - Coherent::UI::UISystem, 77
- UsesSharedMemory

- Coherent::UI::View, [96](#)
- Coherent::UI::ViewInfo, [99](#)
- VE_AbnormalTermination
 - Coherent::UI, [38](#)
- VE_ChildCompositionFailed
 - Coherent::UI, [38](#)
- VE_ClickThroughFailed
 - Coherent::UI, [38](#)
- VE_FailedCreation
 - Coherent::UI, [38](#)
- VE_FailedRenderingCreation
 - Coherent::UI, [38](#)
- VE_FrameAlreadyInFlight
 - Coherent::UI, [38](#)
- VE_FrameNotReady
 - Coherent::UI, [38](#)
- VE_FrameNotRequested
 - Coherent::UI, [38](#)
- VE_InvalidCall
 - Coherent::UI, [38](#)
- VE_InvalidPath
 - Coherent::UI, [38](#)
- VE_Success
 - Coherent::UI, [38](#)
- ValidEnd
 - Coherent::UI::Certificate, [57](#)
- ValidStart
 - Coherent::UI::Certificate, [57](#)
- Value
 - Coherent::UI::Binding::Value, [79](#), [80](#), [82](#)
- ValueType
 - Coherent::UI::Binding, [39](#)
- ViewCreated
 - Coherent::UI::BrowserViewListener, [55](#)
 - Coherent::UI::ViewListener, [110](#)
- ViewErrorType
 - Coherent::UI, [38](#)
- ViewType
 - Coherent::UI, [38](#)
- WheelX
 - Coherent::UI::MouseEventData, [69](#)
- WheelY
 - Coherent::UI::MouseEventData, [69](#)
- Width
 - Coherent::UI::ViewInfo, [99](#)
- WriteFile
 - Coherent::UI::FileHandler, [64](#)
- WriteLog
 - Coherent::UI::ILogHandler, [65](#)
- WriteMinidumps
 - Coherent::UI::SystemSettingsBase, [75](#)
- X
 - Coherent::UI::MouseEventData, [69](#)
 - Coherent::UI::TouchEventData, [76](#)
- Y