

## 1 Overture SYNTAX AND SEMANTICS

$v \in \mathbb{F}_p$ ,  $w \in \text{String}$ ,  $\iota \in \text{Clients} \subset \mathbb{N}$

$\varepsilon ::= r[w] \mid s[w] \mid m[w] \mid p[w] \mid v \mid \varepsilon - \varepsilon \mid \varepsilon + \varepsilon \mid \varepsilon * \varepsilon$  expressions

$x ::= r[w]@_\iota \mid s[w]@_\iota \mid m[w]@_\iota \mid p[w] \mid \text{out}_\iota$  variables

$\pi ::= m[w]@_\iota := \varepsilon@_\iota \mid p[w] := e@_\iota \mid \text{out}_\iota := \varepsilon@_\iota \mid \pi; \pi$  protocols

$$\begin{aligned} \llbracket \sigma, v \rrbracket_\iota &= v \\ \llbracket \sigma, \varepsilon_1 + \varepsilon_2 \rrbracket_\iota &= \llbracket \llbracket \sigma, \varepsilon_1 \rrbracket_\iota + \llbracket \sigma, \varepsilon_2 \rrbracket_\iota \\ \llbracket \sigma, \varepsilon_1 - \varepsilon_2 \rrbracket_\iota &= \llbracket \llbracket \sigma, \varepsilon_1 \rrbracket_\iota - \llbracket \sigma, \varepsilon_2 \rrbracket_\iota \\ \llbracket \sigma, \varepsilon_1 * \varepsilon_2 \rrbracket_\iota &= \llbracket \llbracket \sigma, \varepsilon_1 \rrbracket_\iota * \llbracket \sigma, \varepsilon_2 \rrbracket_\iota \\ \llbracket \sigma, r[w] \rrbracket_\iota &= \sigma(r[w]@_\iota) \\ \llbracket \sigma, s[w] \rrbracket_\iota &= \sigma(s[w]@_\iota) \\ \llbracket \sigma, m[w] \rrbracket_\iota &= \sigma(m[w]@_\iota) \\ \llbracket \sigma, p[w] \rrbracket_\iota &= \sigma(p[w]) \end{aligned}$$

$$\begin{array}{c} (\sigma, x := \varepsilon@_\iota) \Rightarrow \sigma\{x \mapsto \llbracket \sigma, \varepsilon \rrbracket_\iota\} \\ \hline (\sigma_1, \pi_1) \Rightarrow \sigma_2 \quad (\sigma_2, \pi_2) \Rightarrow \sigma_3 \\ \hline (\sigma_1, \pi_1; \pi_2) \Rightarrow \sigma_3 \end{array}$$

## 2 Overture ADVERSARIAL SEMANTICS

$$\begin{aligned} (\sigma, x := \varepsilon@_\iota) &\Rightarrow_{\mathcal{A}} \sigma\{x \mapsto \llbracket \sigma, \varepsilon \rrbracket_\iota\} & \iota \in H \\ (\sigma, x := \varepsilon@_\iota) &\Rightarrow_{\mathcal{A}} \sigma\{x \mapsto \llbracket \text{rewrite}_{\mathcal{A}}(\sigma_C, \varepsilon) \rrbracket_\iota\} & \iota \in C \end{aligned}$$

$$\begin{aligned} (\sigma, \text{assert}(\varepsilon_1 = \varepsilon_2)@_\iota) &\Rightarrow_{\mathcal{A}} \sigma & \text{if } \llbracket \sigma, \varepsilon_1 \rrbracket_\iota = \llbracket \sigma, \varepsilon_2 \rrbracket_\iota \text{ or } \iota \in C \\ (\sigma, \text{assert}(\phi(\varepsilon))@_\iota) &\Rightarrow_{\mathcal{A}} \perp & \text{if } \neg\phi(\sigma, \llbracket \sigma, \varepsilon \rrbracket_\iota) \end{aligned}$$

$$\begin{array}{c} (\sigma_1, \pi_1) \Rightarrow_{\mathcal{A}} \sigma_2 \quad (\sigma_2, \pi_2) \Rightarrow_{\mathcal{A}} \sigma_3 \\ \hline (\sigma_1, \pi_1; \pi_2) \Rightarrow_{\mathcal{A}} \sigma_3 \end{array} \quad \begin{array}{c} (\sigma_1, \pi_1) \Rightarrow_{\mathcal{A}} \perp \\ \hline (\sigma_1, \pi_1; \pi_2) \Rightarrow_{\mathcal{A}} \perp \end{array}$$

$$\begin{array}{c} (\sigma_1, \pi_1) \Rightarrow_{\mathcal{A}} \sigma_2 \quad (\sigma_2, \pi_2) \Rightarrow_{\mathcal{A}} \perp \\ \hline (\sigma_1, \pi_1; \pi_2) \Rightarrow_{\mathcal{A}} \perp \end{array}$$

## 3 Overture CONSTRAINT TYPING

$$\begin{aligned} \phi &::= x \mid \phi + \phi \mid \phi - \phi \mid \phi * \phi \\ E &::= \phi \equiv \phi \mid E \wedge E \end{aligned}$$

We write  $E_1 \models E_2$  iff every model of  $E_1$  is a model of  $E_2$ . Note that this relation is reflexive and transitive.

### 3.1 Confidentiality Types

$$\begin{array}{c} \text{DEPTy} \\ \emptyset, E \vdash \phi : \text{vars}(\phi) \end{array} \quad \begin{array}{c} \text{ENCODE} \\ E \models \phi \equiv \phi' \oplus r[w]@_\iota \quad \oplus \in \{+, -\} \quad R, E \vdash \phi' : T \\ \hline R; \{r[w]@_\iota\}, E \vdash \phi : \{c(r[w]@_\iota, T)\} \end{array}$$

$$\begin{array}{c} \text{SEND} \\ R, E \vdash \llbracket \varepsilon@_\iota \rrbracket : T \\ \hline R, E \vdash x := \varepsilon@_\iota : x : T \end{array} \quad \begin{array}{c} \text{SEQ} \\ R_1, E \vdash \pi_1 : \Gamma_1 \quad R_2, E \vdash \pi_2 : \Gamma_2 \\ \hline R_1; R_2, E \vdash \pi_1; \pi_2 : \Gamma_1; \Gamma_2 \end{array}$$

*Definition 3.1.*  $R, E \vdash \pi : \Gamma$  is valid iff it is derivable and  $\lfloor \pi \rfloor \models E$ .

$$\frac{\iota \in C}{\Gamma, C \vdash \Gamma(m[w]@_l)} \quad \frac{\Gamma, C \vdash T_1 \cup T_2}{\Gamma, C \vdash T_1} \quad \frac{\Gamma, C \vdash \{m[w]@_l\}}{\Gamma, C \vdash \Gamma(m[w]@_l)}$$

$$\frac{\Gamma, C \vdash \{r[w]@_l\} \quad \Gamma, C \vdash \{c(r[w]@_l, T)\}}{\Gamma, C \vdash T}$$

**THEOREM 3.2.** *If  $R, E \vdash \pi : \Gamma$  is valid and for all  $H, C$  it is not the case that  $\Gamma, C \vdash \{s[w]@_l\}$  for  $\iota \in H$ , then  $\pi$  satisfies gradual release.*

### 3.2 Integrity Types

<p><b>VALUE</b></p> $\Gamma, \emptyset, E \vdash_l v : \emptyset \cdot \text{High}$	<p><b>SECRET</b></p> $\Gamma, \emptyset, E \vdash_l s[w] : \{s[w]@_l\} \cdot \mathcal{L}(\iota)$	<p><b>RANDO</b></p> $\Gamma, \emptyset, E \vdash_l r[w] : \{r[w]@_l\} \cdot \mathcal{L}(\iota)$
<p><b>MESG</b></p> $\Gamma, \emptyset, E \vdash_l m[w] : \Gamma(m[w]@_l)$	<p><b>PUBM</b></p> $\Gamma, \emptyset, E \vdash_l p[w] : \Gamma(p[w])$	<p><b>INTEGRITYWEAKEN</b></p> $\frac{\Gamma, R, E \vdash_l \varepsilon : T \cdot \zeta_1 \quad \zeta_1 \leq \zeta_2}{\Gamma, R, E \vdash_l \varepsilon : T \cdot \zeta_2}$
<p><b>ENCODE</b></p> $\frac{\Gamma, \emptyset, E \vdash_l \varepsilon : T \cdot \zeta \quad E \models \lfloor \varepsilon@_l \rfloor = \phi \oplus r[w]@_l' \quad \oplus \in \{+, -\}}{\Gamma, r[w]@_l, E \vdash_l \varepsilon : \{c(r[w]@_l', \Gamma(\phi))\} \cdot \zeta}$		
<p><b>BINOP</b></p> $\frac{\Gamma, R_1, E \vdash_l \varepsilon_1 : T_1 \cdot \zeta \quad \Gamma, R_2, E \vdash_l \varepsilon_2 : T_2 \cdot \zeta \quad \oplus \in \{+, -, *\}}{\Gamma, R_1; R_2, E \vdash_l \varepsilon_1 \oplus \varepsilon_2 : T_1 \cup T_2 \cdot \zeta}$		
<p><b>SEND</b></p> $\frac{\Gamma, R, E \vdash_l \varepsilon : T \cdot \mathcal{L}(\iota) \quad E' \models E \wedge x = \lfloor \varepsilon@_l \rfloor}{\Gamma, R, E \vdash x := \varepsilon@_l : \Gamma; x : T \cdot \mathcal{L}(\iota), E'}$		<p><b>ASSERT</b></p> $\frac{E \models \lfloor \varepsilon_1@_l \rfloor = \lfloor \varepsilon_2@_l \rfloor}{\Gamma, R, E \vdash \text{assert}(\varepsilon_1 = \varepsilon_2)@_l : \Gamma, E}$
<p><b>SEQ</b></p> $\frac{\Gamma_1, R_1, E_1 \vdash \pi_1 : \Gamma_2, E_2 \quad \Gamma_2, R_2, E_2 \vdash \pi_2 : \Gamma_3, E_3}{\Gamma_1, R_1; R_2, E_1 \vdash \pi_1; \pi_2 : \Gamma_3, E_3}$		<p><b>CONSTRAINT</b></p> $\frac{\Gamma_1, R, E_1 \vdash \pi : \Gamma_2, E_2 \quad E'_1 \models E'_1 \quad E_2 \models E'_2}{\Gamma_1, R, E'_1 \vdash \pi : \Gamma_2, E'_2}$
<p><b>MAC</b></p> $\frac{E \models m[w]@_l = m[wk]@_l + (m[\text{delta}]@_l * m[ws]@_l) \quad \Gamma(m[ws]@_l) = T \cdot \zeta}{\Gamma, R, E \vdash \text{assert}(m[w]@_l = m[wk]@_l + (m[\text{delta}]@_l * m[ws]@_l))@_l : \Gamma; m[ws]@_l : T \cdot \text{High}, E}$		

## 4 Prelude SYNTAX AND SEMANTICS

 $\ell \in \text{Field}, y \in \text{EVar}, f \in \text{FName}$ 

$$\begin{aligned} e &::= v \mid r[e] \mid s[e] \mid m[e] \mid p[e] \mid e \text{ binop } e \mid \text{let } y = e \text{ in } e \mid \\ &\quad f(e, \dots, e) \mid \{\ell = e; \dots; \ell = e\} \mid e.\ell \\ c &::= m[e]@e := e@e \mid p[e] := e@e \mid \text{out}@e := e@e \mid \text{assert}(e = e)@e \mid \\ &\quad f(e, \dots, e) \mid c; c \mid \text{pre}(E) \mid \text{post}(E) \\ \text{binop} &::= + \mid - \mid * \mid ++ \\ v &::= w \mid \iota \mid \varepsilon \mid \{\ell = v; \dots; \ell = v\} \\ fn &::= f(y, \dots, y)\{e\} \mid f(y, \dots, y)\{c\} \\ \phi &::= r[e]@e \mid s[e]@e \mid m[e]@e \mid p[e] \mid \text{out}@e \mid \phi + \phi \mid \phi - \phi \mid \phi * \phi \\ E &::= \phi \equiv \phi \mid E \wedge E \end{aligned}$$

$$\frac{e[v/y] \Rightarrow v'}{\text{let } y = v \text{ in } e \Rightarrow v'}$$

$$\frac{C(f) = y_1, \dots, y_n, e \quad e_1 \Rightarrow v_1 \dots e_n \Rightarrow v_n \quad e[v_1/y_1] \dots [v_n/y_n] \Rightarrow v}{f(e_1, \dots, e_n) \Rightarrow v}$$

$$\frac{e_1 \Rightarrow v_1 \dots e_n \Rightarrow v_n}{\{\ell_1 = e_1; \dots; \ell_n = e_n\} \Rightarrow \{\ell_1 = v_1; \dots; \ell_n = v_n\}} \quad \frac{e \Rightarrow \{\dots; \ell = v; \dots\}}{e.\ell \Rightarrow v} \quad \frac{e_1 \Rightarrow w_1 \quad e_2 \Rightarrow w_2}{e_1 ++ e_2 \Rightarrow w_1 w_2}$$

$$\frac{e_1 \Rightarrow \varepsilon_1 \quad e_2 \Rightarrow \varepsilon_2 \quad e \Rightarrow \iota}{(\pi, (E_1, E_2), \text{on}, \text{assert}(e_1 = e_2)@e) \Rightarrow (\pi; \text{assert}(\varepsilon_1 = \varepsilon_2)@_{\iota}, (E_1, E_2 \wedge \lfloor \varepsilon_1 @_{\iota} \rfloor = \lfloor \varepsilon_2 @_{\iota} \rfloor), \text{on})}$$

$$\frac{e_1 \Rightarrow \varepsilon_1 \quad e_2 \Rightarrow \varepsilon_2 \quad e \Rightarrow \iota}{(\pi, (E_1, E_2), \text{off}, \text{assert}(e_1 = e_2)@e) \Rightarrow (\pi; \text{assert}(\varepsilon_1 = \varepsilon_2)@_{\iota}, (E_1, E_2, \text{off}))}$$

$$\frac{e_1 \Rightarrow w \quad e_2 \Rightarrow \iota_1 \quad e_3 \Rightarrow \varepsilon \quad e_4 \Rightarrow \iota_2}{(\pi, (E_1, E_2), \text{on}, m[e_1]@e_2 := e_3@e_4) \Rightarrow (\pi; m[w]@_{\iota_1} := \varepsilon@_{\iota_2}, (E_1 \wedge m[w]@_{\iota_1} = \lfloor \varepsilon@_{\iota_2} \rfloor, E_2), \text{on})}$$

$$\frac{e_1 \Rightarrow w \quad e_2 \Rightarrow \iota_1 \quad e_3 \Rightarrow \varepsilon \quad e_4 \Rightarrow \iota_2}{(\pi, (E_1, E_2), \text{off}, m[e_1]@e_2 := e_3@e_4) \Rightarrow (\pi; m[w]@_{\iota_1} := \varepsilon@_{\iota_2}, (E_1, E_1), \text{off})}$$

$$(\pi, (E_1, E_2), \text{on}, \text{pre}(E)) \Rightarrow (\pi, E_1, E_2 \wedge E, \text{off})$$

$$(\pi, (E_1, E_2), \text{off}, \text{post}(E)) \Rightarrow (\pi, (E_1 \wedge E, E_2), \text{on})$$

$$\frac{(\pi_1, (E_{11}, E_{12}), \text{sw}_1, c_1) \Rightarrow (\pi_2, (E_{21}, E_{22}), \text{sw}_2) \quad (\pi_2, (E_{21}, E_{22}), \text{sw}_2, c_2) \Rightarrow (\pi_3, (E_{31}, E_{32}), \text{sw}_3)}{(\pi_1, (E_{11}, E_{12}), \text{sw}_1, c_1; c_2) \Rightarrow (\pi_3, (E_{31}, E_{32}), \text{sw}_3)}$$

$$\frac{C(f) = y_1, \dots, y_n, c \quad e_1 \Rightarrow v_1 \dots e_n \Rightarrow v_n \quad (\pi_1, (E_{11}, E_{12}), \text{sw}_1, c[v_1/y_1] \dots [v_n/y_n]) \Rightarrow (\pi_2, (E_{21}, E_{22}), \text{sw}_2)}{(\pi_1, (E_{11}, E_{12}), \text{sw}_1, f(e_1, \dots, e_n)) \Rightarrow (\pi_2, (E_{21}, E_{22}), \text{sw}_2)}$$

## 5 EXAMPLES

```

99
100 encodegmw(in, i1, i2) {
101     m[in]@i2 := (s[in] xor r[in])@i2;
102     m[in]@i1 := r[in]@i2
103 }
104
105 andtablegmw(b1, b2, r) {
106     let r11 = r xor (b1 xor true) and (b2 xor true) in
107     let r10 = r xor (b1 xor true) and (b2 xor false) in
108     let r01 = r xor (b1 xor false) and (b2 xor true) in
109     let r00 = r xor (b1 xor false) and (b2 xor false) in
110     { row1 = r11; row2 = r10; row3 = r01; row4 = r00 }
111 }
112
113 andgmw(z, x, y) {
114     pre();
115     let r = r[z] in
116     let table = andtablegmw(m[x],m[y],r) in
117     m[z]@2 := OT4(m[x],m[y],table,2,1);
118     m[z]@1 := r@1;
119     post(m[z]@1 xor m[z]@2 == (m[x]@1 xor m[x]@2) and (m[y]@1 xor m[y]@2))
120 }
121
122 xorgmw(z, x, y) {
123     m[z]@1 := (m[x] xor m[y])@1; m[z]@2 := (m[x] xor m[y])@2;
124 }
125
126 decodegmw(z) {
127     p["1"] := m[z]@1; p["2"] := m[z]@2;
128     out@1 := (p["1"] xor p["2"])@1;
129     out@2 := (p["1"] xor p["2"])@2
130 }
131
132 encodegmw("x",2,1);
133 encodegmw("y",2,1);
134 encodegmw("z",1,2);
135 andgmw("g1","x","z");
136 xorgmw("g2","g1","y");
137 decodegmw("g2")
138 pre();
139 post(out@1 == (s["x"]@1 and s["z"]@2) xor s["y"]@1)
140
141
142 secopen(w1,w2,w3,i1,i2) {
143     pre(m[w1++"m"]@i2 == m[w1++"k"]@i1 + (m["delta"]@i1 * m[w1++"s"]@i2 /\
144         m[w1++"m"]@i2 == m[w1++"k"]@i1 + (m["delta"]@i1 * m[w1++"s"]@i2));
145     let locsum = macsum(macshare(w1), macshare(w2)) in
146     m[w3++"s"]@i1 := (locsum.share)@i2;
147

```

```

148     m[w3++"m"]@i1 := (locsum.mac)@i2;
149     auth(m[w3++"s"],m[w3++"m"],mack(w1) + mack(w2),i1);
150     m[w3]@i1 := (m[w3++"s"] + (locsum.share))@i1
151 }
152
153
154 _open(x,i1,i2){
155     m[x++"exts"]@i1 := m[x++"s"]@i2;
156     m[x++"extm"]@i1 := m[x++"m"]@i2;
157     assert(m[x++"extm"] == m[x++"k"] + (m["delta"] * m[x++"exts"]));
158     m[x]@i1 := (m[x++"exts"] + m[x++"s"]@i2
159 }~
160
161 _sum(z, x, y,i1,i2) {
162     pre(m[x++"m"]@i2 == m[x++"k"]@i1 + (m["delta"]@i1 * m[x++"s"]@i2 /\
163         m[y++"m"]@i2 == m[y++"k"]@i1 + (m["delta"]@i1 * m[y++"s"]@i2));
164     m[z++"s"]@i2 := (m[x++"s"] + m[y++"s"]@i2);
165     m[z++"m"]@i2 := (m[x++"m"] + m[y++"m"]@i2);
166     m[z++"k"]@i1 := (m[x++"k"] + m[y++"k"]@i1);
167     post(m[z++"m"]@i2 == m[z++"k"]@i1 + (m["delta"]@i1 * m[z++"s"]@i2)
168 }
169
170 sum(z,x,y) { _sum(z,x,y,1,2);_sum(z,x,y,2,1) }
171
172 open(x) { _open(x,1,2); _open(x,2,1) }
173
174
175 sum("a","x","d");
176 open("d");
177 sum("b","y","e");
178 open("e");
179 let xys =
180     macsum(macctimes(macshare("b"), m["d"]),
181         macsum(macctimes(macshare("a"), m["e"]),
182             macshare("c")))
183 let xyk = mack("b") * m["d"] + mack("a") * m["e"] + mack("c")
184
185 secopen("a","x","d",1,2);
186 secopen("a","x","d",2,1);
187 secopen("b","y","e",1,2);
188 secopen("b","y","e",2,1);
189 let xys =
190     macsum(macctimes(macshare("b"), m["d"]),
191         macsum(macctimes(macshare("a"), m["e"]),
192             macshare("c")))
193 in
194 let xyk = mack("b") * m["d"] + mack("d") * m["d"] + mack("c")
195 in
196

```

```
197     secreveal(xys,xyk,"1",1,2);
198     secreveal(maccsum(xys,m["d"] * m["e"]),
199               xyk - m["d"] * m["e"],
200               "2",2,1);
201     out@1 := (p[1] + p[2])@1;
202     out@2 := (p[1] + p[2])@2;
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
```