



TRYKER

The first special tire for tricycle recumbents. Tire construction and profile contours are co-ordinated with the special requirements of a multi-track vehicle in mind. Tricycle recumbents exert completely different loads on tires than do (normal) bicycles. Nevertheless the tires must be light and fast, because drive is still achieved through muscle power and should therefore be as effective as possible. Massive motor vehicle tires are out of the question. The Tryker takes on the challenge of minimal rolling friction and high durability for the recumbent tricyclist. It has ECE-R75 certification for faster E-Bikes.



ENERGIZER SOLAR

For the World Solar challenge. Together with the University of Bochum we developed these tires for the World Solar challenge in Australia. In addition to the low rolling resistance, high durability and reliability is also very important. Special Solar-Compound. Tubeless. Designed for speeds of 100 or 120 km/h (ECE certified!).

TRYKER HS 433, Performance Line, Folding tire

	ETRTO	Size	!	ECE			Skin	Bar	Psi			EPI	Load	Art.-No.
20"	40-406	20x1.50	RaceGuard	•	Endurance	Black-Reflex	Lite	4.0-6.0	55-85	320	11	67	73 kg	11600303

ENERGIZER SOLAR HS 437, Evolution Line, Wired tire

20"	2.40-16	20x2.40	Tubeless, 42J	•	Solar	Black	Twin	max. 8	max. 115	1200	42	50	150 kg	10300437
	90/80-16		Tubeless, 42L	•	Solar	Black	Twin	max. 5	max. 70	1500	53	50	150 kg	10310437

HS 140	12"	47-203	12 1/2x1.75	K-Guard		SBC	White Line	Twin	2.0-3.0	30-45	285	10	50	45 kg	11102050.01
	14"	37-288	14x1 3/8, 350x35A	K-Guard		SBC	White Line	Twin	2.0-3.0	30-45	365	13	50	40 kg	11104050.01
HS 158	12"	62-203	12 1/2x2 1/4	K-Guard, Reinforced		GRC	Grey	Twin	1.5-2.5	20-35	650	23	50	70 kg	10213622.01
HS 159	18"	47-355	18x1.75	K-Guard		SBC	White Line	Twin	2.5-3.0	35-45	450	16	50	65 kg	11110053.01
	20"	54-428	20x2.00	K-Guard		SBC	Black	Twin	2.0-3.0	30-45	610	21	50	85 kg	11119100.01
	26"	37-584	26x1 3/8, 650STD	K-Guard		SBC	Gumwall	Twin	2.5-4.5	35-65	580	20	50	75 kg	11136073.01
				K-Guard		SBC	Whitewall	Twin	2.5-4.5	35-65	580	20	50	75 kg	11136063.01
	27"	44-584	26x1 5/8, 650 1/2B	K-Guard		SBC	Gumwall	Twin	2.5-4.5	35-65	645	23	50	95 kg	11138073.01
				K-Guard		SBC	Gumwall	Twin	3.5-6.0	50-85	550	19	50	70 kg	11157073.01
HS 166	22"	37-490	22x1 3/8, 550x35A	K-Guard		SBC	Gumwall	Twin	2.5-4.0	35-55	450	16	50	65 kg	11123070.01
				K-Guard		SBC	Gumwall	Twin	3.5-6.0	50-85	500	18	50	65 kg	11139170.01
HS 180	26"	28/32-590	26x11/8x1 1/4, 650x28/32A	K-Guard		SBC	Gumwall	Twin	3.5-6.0	50-85	500	18	50	65 kg	11139170.01
HS 228	22"	25-489	22x1.00	K-Guard		GRC	Grey	Twin	6.0-7.5	85-110	270	9	50	55 kg	10275671.01
	24"	25-540	24x1.00	K-Guard		GRC	Grey	Twin	6.0-10.0	85-145	280	10	50	60 kg	10282675.01
		37-540	24x1 3/8	K-Guard		GRC	Grey	Twin	2.5-5.0	35-70	445	16	50	75 kg	10282691.01