Battery Input (6s1p)

Ideal Diode Controller



Title Power Distribution Board Rev2 - Power		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li	
Date: 2020-11-06	Sheet 1 of 12	
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH1 - POWER.SchDoc		

LED Matrix



5V Output



URM04 Ultrasonic Sensors



Title Power Distribution Board Rev2 - Connectors		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086	UW ROBOTICS TEAM
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 2 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH2 - CONNECTORS.SchDoc			

24V Buck-Boost Converter @ 3A Max

Input voltage range: 18-25.8V



Inductor: SDR1307-2R2ML
20%, 6mΩ DCR
9A (rms), 18A (sat), 7mm tall



24V Output

Title PDB Rev2 - 24V Buck-Boost Converter		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li	
Date: 2020-11-06	Sheet 3 of 12	
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH3 - 24V BUCK-BOOST CONVERTER.SchD		

UW ROBOTICS TEAM

17V Regulator @ 4A Max

Input voltage range: 18-24V



Estimated max current draw: 1.65A
Peak efficiency: 94.8%
Output voltage ripple: 19.45mVpp

LED forward drop = 2.2V

LED current = (17-2.2)/3300 = 4.5mA

On/Off Switch



Internally pulled up
Pull below 1.2V to disable.
Float or connect to VIN to enable.
Debounce time: 100k * 0.1µ = 10ms

Title Power Distribution Board Rev2 - 17V Buck Converter			Altium Limited 13, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 4 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH4 - 17V BUCK CONVERTER.SchDoc			

5V Regulator @ 16A Max

Input voltage range: 9-50V



Inductor: 744309033
20%, 0.165mΩ DCR
47.5A (rms), 62.5A (sat), 9mm tall

Estimated max current draw: 8A
Maximum expected output power: 40W
Peak efficiency: 88% @ 16A
Output voltage ripple: 277mVpp

LED forward drop = 2.2V

LED current = (5-2.2)/1000 = 2.8mA

On/Off Switch



Internally pulled up to VCC
Debounce time: 100k * 0.1µ = 10ms

Fault Indicator



LED forward drop = 2.0V
FT voltage = 3.3V (from internally generated VCC)

LED current = (3.3-2)/1000 = 1.3mA

Title Power Distribution Board Rev2 - 5V Vicor DCDC			Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 5 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH5 - 5V VICOR DCDC.SchDoc			

5V to 3.3V LDO (Max 1A)



Current Calculations

Green LED voltage drop: 2.2V
- I = (3.3-2.2V)/220 = 5mA

Title Power Distribution Board Rev2 - 3.3V Linear Regulator			Altium Limited 13, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 6 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH6 - 3.3V LINEAR REGULATOR.SchDoc			

5V Loads Smart Switches

Output pull-up added
for open-load detection



Smart Switch Current Limited to 5A

- I_out = 5A, V_CL(th) = 0.8V, K_CL = 2500 (values from datasheet)
- R_CL = V_CL(th) * K_CL / I_out = 0.8 * 2500 / 5 = 400Ω → use R_CL = 402Ω

Current Limit Configurations - Refer to DELAY Pin
- Holding mode: depopulate pull-up and populate pull-down with a 0Ω resistor
- Latch-off mode: depopulate pull-up and populate pull-down with a capacit o r (calculated based on required delay time)
- Auto-retry mode: populate pull-up with a pull-up resistor and depopulate pull-down

Title Power Distribution Board Rev2 - Load Monitoring 1		Altium Limited 13, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li	
Date: 2020-11-06	Sheet 7 of 12	
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH7 - LOAD MONITORING 1.SchDoc		

17V Load Smart Switch



17V Output



Power Rail Voltage Monitoring



Divides 5V to 3.3V



Divides 17V to 3.3V



Divides 24V to 3.3V



Divides 24V to 3.3V

Title: Power Distribution Board Rev2 - Load Monitoring 2			Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 8 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH8 - LOAD MONITORING 2.SchDoc			

Status LED



Current Calculations

RGB LED voltage drops:
- Red: 2.1V: I = (3.3-2.1V)/120 = 10mA
- Blue: 3.1V: I = (3.3-3.1V)/20 = 10mA
- Green: 3.1V: I = (3.3-3.1V)/20 = 10mA

Debounce Calculation:

T=RC -> C= T/R
C= 10ms/10kOhm= 1uF

Decoupling Caps



STM32F446RET6



Debug/Programming





Title Power Distribution Board Rev2 - MCU		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086	UW ROBOTICS TEAM
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 9 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH9 - MICROCONTROLLER.SchDoc			



Title Power Distribution Board Rev2 - USB		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086	UW ROBOTICS TEAM
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 10 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH10 - USB.SchDoc			

CAN BUS A





CAN BUS B





CAN Transceivers





Title Power Distribution Board Rev2 - CAN Transceivers		Altium Limited 13, 12a Rodborough Rd Frenchs Forest NSW Australia 2086	UW ROBOTICS TEAM
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 11 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH11 - CAN.SchDoc			

RS-485 Transceiver

Voltage divider on RS-485_RX line divides 5V to 3.3V
MAX485 logic high input voltage is 2V



Title Power Distribution Board Rev2 - RS-485			Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li		
Date: 2020-11-06	Sheet 12 of 12		
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH12 - RS-485.SchDoc