

A

A

B

B


C

C

D

D


24V Input



Rated Current = 16A

TODO:
- What is the actual rated current?

Reverse Polarity Protection





LED forward drop = 2.0V
Max VBAT = 24V
Min VBAT = 18V



Max LED current = $(24-2)/4700 = 4.7\text{mA}$
Min LED current = $(18-2)/4700 = 3.4\text{mA}$

Title Power Distribution Board Rev2 - Power		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li	
Date: 2020-11-02	Sheet 1 of 12	
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH1 - POWER.SchDoc		UW ROBOTICS TEAM



CAN BUS A




LED Matrix




CAN BUS B



5V Output



17V Output








TODO:
- check if using correct connectors






Can use 12-26AWG

Input voltage range: 18-25.8V


24V Buck-Boost Converter @ 3A Max




24V



△ TODO:
- add appropriate test points
- add appropriate comments






A

A

B

B

5V to 3.3V LDO



C


C

D

D

Title Power Distribution Board Rev2 - 3.3V Linear		Altium Limited 23/728 Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li	
Date: 2020-11-02	Sheet 6 of 12	
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH6 - 3.3V LINEAR REGULATOR.SchDoc		UW ROBOTICS TEAM

5V Loads Smart Switches



Smart Switch Current Limited to 5A

- $I_{out} = 5A$, $V_{CL(th)} = 0.8V$, $K_{CL} = 2500$ (values from datasheet)
- $R_{CL} = V_{CL(th)} * K_{CL} / I_{out} = 0.8 * 2500 / 5 = 400\Omega \rightarrow$ use $R_{CL} = 402\Omega$

Current Limit Configurations - Refer to DELAY Pin

- Holding mode: depopulate pull-up and populate pull-down with a 0Ω resistor
- Latch-off mode: depopulate pull-up and populate pull-down with a capacitor (calculated based on required delay time)
- Auto-retry mode: populate pull-up with a pull-up resistor and depopulate pull-down

A

A

B

B


C

C


D

D


Jetson Smart Switch




Power Rail Voltage Monitoring




Status/Debug LEDs




Decoupling Caps




STM32F446RET6



B




C



D

Debug/Programming



A

B

C

D

Title Power Distribution Board Rev2 - MCU


Size: Letter Drawn By: Cindy Li

Date: 2020-11-02 Sheet 9 of 12

File: C:\UWRT\火星探测器\Hardware\Projects\Power Distribution Board\Rev2\SH9 - MICROCONTROLLER.schDoc

Altium Limited
L3, 12a Rodborough Rd
Frenchs Forest
NSW Australia 2086


UW
ROBOTICS
TEAM



A


A

CAN Transceivers



B

B



C

C

D

D

Title Power Distribution Board Rev2 - CAN Transcei

Altium Limited
L3, 12a Rodborough Rd
Frenchs Forest
NSW
Australia 2086

Size: Letter Drawn By: Cindy Li

Date: 2020-11-02 Sheet 1 of 12

File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH11 - CAN.SchDoc



A

A

B

B


C

C

D

D

RS-485 Transceiver



Title Power Distribution Board Rev2 - RS-485		Altium Limited L3, 12a Rodborough Rd Frenchs Forest NSW Australia 2086
Size: Letter	Drawn By: Cindy Li	
Date: 2020-11-02	Sheet 12 of 12	
File: C:\UWRT\MarsRover2021-hardware\Projects\Power Distribution Board\Rev2\SH12 - RS-485.SchDoc		UW ROBOTICS TEAM

