

FASTENING COMPONENTS

CAR REDUCTION			
THREAD SIZE	TYPE	THREAD LENGTH	QTY.
5/16" - 18	PERNO CABEZA HEXAGONAL	2"	6
5/16" - 18	TUERCA HEXAGONAL	17/64"	6
5/16"	GOLILLA PLANA	-	12
5/16" - 18	SEPARADOR ROSCADO HEMBRA	1 1/8"	6

SIDE REDUCTION			
THREAD SIZE	TYPE	THREAD LENGTH	QTY.
5/16" - 18	PERNO CABEZA HEXAGONAL	2"	6
5/16" - 18	TUERCA HEXAGONAL	17/64"	6
5/16"	GOLILLA PLANA	-	12
5/16" - 18	SEPARADOR ROSCADO HEMBRA	1 1/8"	6
3/8" - 16	PERNO CABEZA HEXAGONAL	7/8"	7
3/8"	GOLILLA PLANA	-	8
3/8" - 16	TUERCA HEXAGONAL	7/32"	4
NO. 10 - 32	PERNO ALLEN	5/8"	4
NO. 10	GOLILLA PLANA	-	4
NO. 10 - 32	TUERCA HEXAGONAL	-	4

GANTRY SUPPORT			
THREAD SIZE	TYPE	THREAD LENGTH	QTY.
M12	TUERCA HEXAGONAL	6 mm	4
M12	PERNO CABEZA HEXAGONAL	1 1/8" - 1 1/4"	4
M12	GOLILLA PLANA	-	4
M12	TUERCA HEXAGONAL C/FLANGE	-	2
M12	TUERCA HEXAGONAL	10 mm	2
5/16" - 18	PERNO CABEZA HEXAGONAL	1"	4
5/16"	GOLILLA PLANA	-	4
5/16" - 18	TUERCA HEXAGONAL	3/16" O MENOR	4

NOTE 1:

EL "THREAD LENGTH" SÓLO ES PARA LOS PERNOS, EN LAS TUERCAS HACE REFERENCIA A LA ALTURA DE ÉSTE.

NOTE 2:

PARA LAS FIJACIONES CON HILO MÉTRICO, COMPRAR LA LONGITUD DEL HILO QUE MÁS SE APROXIME A LA MEDIDA EN PULGADAS.

BEARINGS

GANTRY SUPPORT			
TYPE	SUPPLIER	MODEL	QTY.
RODAMIENTO RÍGIDO DE BOLA	SKF	6001 - Z	8
DIMENSIONS	D_INT	D_EXT	WIDTH
	28 mm	12 mm	8 mm