In [1]:
```python
import numpy as np
import pandas as pd
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier
```

In [2]:
```python
df=pd.read_csv(r"C:\Users\pucha\Downloads\loan1.csv")
df
```

Out[2]:

	Home Owner	Marital Status	Annual Income	Defaulted Borrower
0	Yes	Single	125	No
1	No	Married	100	No
2	No	Single	70	No
3	Yes	Married	120	No
4	No	Divorced	95	Yes
5	No	Married	60	No
6	Yes	Divorced	220	No
7	No	Single	85	Yes
8	No	Married	75	No
9	No	Single	90	Yes

In [3]:
```python
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 10 entries, 0 to 9
Data columns (total 4 columns):
 #   Column             Non-Null Count  Dtype
---  ------             --------------  -----
 0   Home Owner         10 non-null     object
 1   Marital Status     10 non-null     object
 2   Annual Income      10 non-null     int64
 3   Defaulted Borrower 10 non-null     object
dtypes: int64(1), object(3)
memory usage: 448.0+ bytes
```

In [6]:
```python
df['Marital Status'].value_counts()
df['Annual Income'].value_counts()
```

Out[6]:
```
Annual Income
125    1
100    1
70     1
120    1
95     1
60     1
220    1
85     1
75     1
90     1
Name: count, dtype: int64
```

```
In [7]: convert={"Home Owner":{"Yes":1,"No":0}}
        df=df.replace(convert)
        df
```

Out[7]:

	Home Owner	Marital Status	Annual Income	Defaulted Borrower
0	1	Single	125	No
1	0	Married	100	No
2	0	Single	70	No
3	1	Married	120	No
4	0	Divorced	95	Yes
5	0	Married	60	No
6	1	Divorced	220	No
7	0	Single	85	Yes
8	0	Married	75	No
9	0	Single	90	Yes

In [8]:
```python
convert={"Marital Status":{"Single":1,"Married":2,"Divorced":3}}
df=df.replace(convert)
df
```

Out[8]:

	Home Owner	Marital Status	Annual Income	Defaulted Borrower
0	1	1	125	No
1	0	2	100	No
2	0	1	70	No
3	1	2	120	No
4	0	3	95	Yes
5	0	2	60	No
6	1	3	220	No
7	0	1	85	Yes
8	0	2	75	No
9	0	1	90	Yes

In [9]:
```python
x=["Home Owner","Marital Status","Annual Income"]
y=["Yes","No"]
all_inputs=df[x]
all_classes=df["Defaulted Borrower"]
```

In [10]:
```python
(x_train,x_test,y_train,y_test)=train_test_split(all_inputs,all_classes,test_size=0.3)
```

In [11]:
```python
df=DecisionTreeClassifier(random_state=0)
```

In [13]:
```python
df.fit(x_train,y_train)
```

Out[13]:
```
▾          DecisionTreeClassifier
DecisionTreeClassifier(random_state=0)
```

In [15]:
```python
score=df.score(x_test,y_test)
print(score)
```

0.3333333333333333

In [ ]: