Page 1: Authentication

The Aster Events API is served from the base URL https://api.aster-events.example/v2. Every request must be authenticated with an API key sent in the Authorization header as a Bearer token.

Aster issues two kinds of keys. Live keys start with the prefix ast_live_ and act on production data. Test keys start with ast_test_ and only touch the sandbox. A workspace may hold at most 5 active keys at the same time.

Each key expires 90 days after creation unless it is rotated. To rotate a key, send a POST request to /v2/keys/rotate; the old key keeps working for a 24 hour grace period after rotation. Keys carry scopes. The available scopes are events:read, events:write and tickets:write. A request that needs a scope the key does not have is rejected.

Never embed a live key in browser code or a mobile app. Store keys in a secrets manager and rotate them immediately if they are exposed.

Page 2: Rate Limits

The Standard plan allows 600 requests per minute per workspace, and the Enterprise plan allows 3000 requests per minute. Sandbox keys are limited to 60 requests per minute regardless of plan. Short bursts of up to 50 requests per second are tolerated as long as the per-minute total is respected.

Bulk endpoints, whose paths end in /bulk, count as 5 requests each against the limit. Every response carries two headers: X-RateLimit-Remaining shows how many requests are left in the current window, and X-RateLimit-Reset shows the Unix timestamp at which the window resets.

When the limit is exceeded the API answers with HTTP status 429 and a Retry-After header giving the number of seconds to wait. Clients should use exponential backoff, starting at 500 milliseconds and doubling after each failed attempt, with a ceiling of 30 seconds. Workspaces that are throttled for more than 1 hour in a row are flagged for review by Aster support.

Page 3: Pagination

List endpoints such as GET /v2/events use cursor-based pagination. Pass the limit parameter to choose the page size. The default page size is 25 items and the maximum is 100 items. Requests above the maximum are silently reduced to 100.

Each response contains a next_cursor field. To fetch the following page, send that value back in the cursor parameter. When next_cursor is null there are no more results. A cursor expires 15 minutes after it was issued, and an expired cursor produces an error, so long running jobs should restart from the first page.

Filters such as status and starts_after can be combined with pagination. The same filters must be repeated on every page request, otherwise the API returns an invalid_request error.

Results are sorted by created_at in descending order by default. Use sort=created_at to reverse the order. The API does not return a total count by default. Add include_total=true to receive a total field; a request with this flag counts as 2 requests against the rate limit.

Page 4: Webhooks

Webhooks notify your server when something changes. The supported event types are event.created, event.updated and ticket.sold. Register an endpoint with POST /v2/webhooks. A workspace may register at most 20 endpoints, and each delivery payload is capped at 256 KB.

Every delivery includes an X-Aster-Signature header. It contains an HMAC-SHA256 digest of the raw request body, computed with your webhook signing secret. Reject any delivery whose signature does not match, and reject deliveries whose timestamp differs from your server clock by more than 5 minutes.

Your endpoint must answer with a 2xx status within 10 seconds. Otherwise Aster retries the delivery up to 6 times, with delays that grow exponentially over a period of 24 hours. After the last failed attempt the delivery is marked as failed and can be replayed manually from the dashboard for 7 days.

Use the test-delivery button in the dashboard to send a sample payload to a new endpoint before going live. Test deliveries are signed in the same way as real ones.

Page 5: Errors

Error responses use a JSON body with three fields: code, message and request_id. Always log the request_id, because Aster support needs it to trace a failed call.

The main status codes are: 400 invalid_request for malformed input; 401 invalid_key when the key is missing or unknown; 403 scope_missing when the key lacks a required scope; 404 not_found for unknown resources; 409 conflict when an idempotency key is reused with a different payload; 422 validation_failed for fields that break a rule; 429 rate_limited when the limit is exceeded; and 500 or 503 for server-side problems.

To make retries safe, send an Idempotency-Key header on every POST request. Aster remembers each key for 24 hours and returns the original response if the same key is sent again with the same payload. Server errors with status 500 or 503 are safe to retry with backoff. The current service status is published at status.aster-events.example.